

**Oracle® Data Provider for .NET**

Developer's Guide

11g Release 2 (11.2)

**E12249-01**

January 2010

Oracle Data Provider for .NET Developer's Guide 11g Release 2 (11.2)

E12249-01

Copyright © 2002, 2010, Oracle and/or its affiliates. All rights reserved.

Primary Author: Sumit Jeloka

Contributing Authors: Janis Greenberg, Riaz Ahmed, Kiminari Akiyama, Shailendra Jain, Ashish Shah, Lakshminarayanan Suriamoorthy, Steven Caminez, Naveen Doraiswamy, Neeraj Gupta, Sinclair Hsu, Alex Keh, Chithra Ramamurthy, Martha Woo, Arun Singh, Sujith Somanathan, Nishant Singh

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

---

---

# Contents

<b>Preface</b> .....	xvii
Audience .....	xvii
Documentation Accessibility .....	xvii
Related Documents .....	xviii
Passwords in Code Examples .....	xix
Conventions .....	xix
<b>What's New in Oracle Data Provider for .NET?</b> .....	xxi
New Features in Oracle Data Provider for .NET Release 11.2 .....	xxi
New Features in Oracle Data Provider for .NET Release 11.1.0.7.20 .....	xxii
New Features in Oracle Data Provider for .NET Release 11.1.0.6.20 .....	xxiii
New Features in Oracle Data Provider for .NET Release 11.1 .....	xxv
New Features in Oracle Data Provider for .NET Release 10.2.0.4.....	xxv
New Features in Oracle Data Provider for .NET Release 10.2.0.3.....	xxv
New Features in Oracle Data Provider for .NET Release 10.2.0.2.....	xxvi
New Features in Oracle Data Provider for .NET Release 10.2.....	xxvi
New Features in Oracle Data Provider for .NET Release 10.1.0.3 .....	xxviii
New Features in Oracle Data Provider for .NET Release 10.1 .....	xxix
New Features in Oracle Data Provider for .NET Release 9.2.0.4 .....	xxix
<b>1 Introducing Oracle Data Provider for .NET</b>	
<b>.NET Data Access in Oracle: Products and Documentation</b> .....	1-1
Oracle Data Provider for .NET (ODP.NET) .....	1-1
Oracle Developer Tools for Visual Studio .....	1-1
Oracle Database Extensions for .NET .....	1-2
Oracle Providers for ASP.NET .....	1-2
<b>Overview of Oracle Data Provider for .NET (ODP.NET)</b> .....	1-3
<b>Oracle Data Provider for .NET Assembly</b> .....	1-3
Oracle.DataAccess.Client Namespace .....	1-4
Oracle.DataAccess.Types Namespace .....	1-9
<b>Using ODP.NET Client Provider in a Simple Application</b> .....	1-11
<b>2 Installing and Configuring Oracle Data Provider for .NET</b>	
System Requirements.....	2-1

<b>Installing Oracle Data Provider for .NET</b> .....	2-2
File Locations After Installation .....	2-2
Windows Registry .....	2-3
Configuration File Support .....	2-3
Search Order for Unmanaged DLLs .....	2-4
ODP.NET and Dependent Unmanaged DLL Mismatch .....	2-4
<b>Performance Counters</b> .....	2-4
<b>Configuring a Port to Listen for Database Notifications</b> .....	2-5
<b>General .NET Programming Recommendations and Tips for ODP.NET</b> .....	2-5

### **3 Features of Oracle Data Provider for .NET**

<b>Connecting to Oracle Database</b> .....	3-1
Connection String Attributes .....	3-2
Specifying the Data Source Attribute .....	3-4
Connection Pooling .....	3-5
Connection Pool Management .....	3-7
Connection Pool Performance Counters .....	3-7
Connecting to an Oracle Real Application Clusters (RAC) Database .....	3-9
Operating System Authentication .....	3-11
Privileged Connections .....	3-12
Password Expiration .....	3-12
Proxy Authentication .....	3-14
Dynamic Distributed Transaction Enlistment .....	3-15
Client Identifier and End-to-End Tracing .....	3-16
Transparent Application Failover (TAF) Callback Support .....	3-16
<b>ADO.NET 2.0 Features</b> .....	3-18
About ADO.NET 2.0 .....	3-19
Base Classes and Provider Factory Classes .....	3-19
Connection String Builder .....	3-20
Data Source Enumerator .....	3-20
Support for Code Access Security .....	3-20
Support for Schema Discovery .....	3-21
System.Transactions and Promotable Transactions .....	3-22
Batch Processing Support .....	3-27
ADO.NET 2.0 Only Classes and Class Members .....	3-27
Bulk Copy Support .....	3-28
<b>OracleCommand Object</b> .....	3-30
Transactions .....	3-30
Parameter Binding .....	3-31
Statement Caching .....	3-42
Self-Tuning .....	3-44
<b>ODP.NET Types Overview</b> .....	3-46
<b>Obtaining Data from an OracleDataReader Object</b> .....	3-47
Typed OracleDataReader Accessors .....	3-48
Obtaining LONG and LONG RAW Data .....	3-51
Obtaining LOB Data .....	3-52
Controlling the Number of Rows Fetched in One Database Round-Trip .....	3-56



<b>PL/SQL REF CURSOR and OracleRefCursor</b> .....	3-58
Obtaining an OracleRefCursor Object .....	3-58
Obtaining a REF CURSOR Data Type.....	3-58
Populating an OracleDataReader from a REF CURSOR.....	3-58
Populating the DataSet from a REF CURSOR .....	3-59
Populating an OracleRefCursor from a REF CURSOR .....	3-59
Updating a DataSet Obtained from a REF CURSOR.....	3-59
Behavior of ExecuteScalar Method for REF CURSOR.....	3-59
Passing a REF CURSOR to a Stored Procedure .....	3-60
<b>LOB Support</b> .....	3-61
Large Character and Large Binary Data Types .....	3-61
Oracle Data Provider for .NET LOB Objects.....	3-62
Updating LOBs Using a DataSet.....	3-63
Updating LOBs Using OracleCommand and OracleParameter .....	3-63
Updating LOBs Using ODP.NET LOB Objects.....	3-63
Temporary LOBs .....	3-64
<b>ODP.NET XML Support</b> .....	3-64
Supported XML Features .....	3-64
XQuery Support .....	3-65
OracleXmlType and Connection Dependency .....	3-66
Updating XMLType Data in the Database .....	3-66
Updating XML Data in OracleXmlType .....	3-68
Characters with Special Meaning in XML.....	3-68
Retrieving Query Result Set as XML.....	3-68
Data Manipulation Using XML.....	3-73
<b>Oracle User-Defined Types (UDTs) and .NET Custom Types</b> .....	3-77
Oracle User-Defined Types (UDTs).....	3-78
Custom Types .....	3-78
Specifying Custom Type Mappings .....	3-81
Converting Between Custom Types and Oracle UDTs.....	3-83
Oracle UDT Attribute Mappings .....	3-84
Oracle UDT Retrieval from OracleDataReader .....	3-86
Oracle UDT Metadata Retrieval from OracleDataReader.....	3-87
Oracle UDT Parameter Binding with OracleParameter .....	3-88
Populating the DataSet with Oracle UDTs.....	3-90
UDT Method Invocation .....	3-91
Configuration Settings for Oracle UDTs.....	3-91
<b>Oracle Streams Advanced Queuing Support</b> .....	3-92
Using ODP.NET for Advanced Queuing .....	3-94
<b>Database Change Notification Support</b> .....	3-97
Database Change Notification Classes .....	3-99
Supported Operations .....	3-100
Requirements of Notification Registration.....	3-101
Using Database Change Notification .....	3-101
Best Practice Guidelines and Performance Considerations.....	3-104
<b>OracleDataAdapter Safe Type Mapping</b> .....	3-104
Comparison Between Oracle Data Types and .NET Types .....	3-104

SafeMapping Property .....	3-106
<b>OracleDataAdapter Requery Property</b> .....	3-108
<b>Guaranteeing Uniqueness in Updating DataSet to Database</b> .....	3-108
What Constitutes Uniqueness in DataRow Objects? .....	3-109
Configuring PrimaryKey and Constraints Properties .....	3-109
Updating Without PrimaryKey and Constraints Configuration .....	3-110
<b>Globalization Support</b> .....	3-110
Globalization Settings.....	3-110
Globalization-Sensitive Operations.....	3-113
<b>Debug Tracing</b> .....	3-114
<b>ODP.NET Configuration</b> .....	3-114
Supported Configuration Settings.....	3-115
Sample Configuration Files .....	3-122

## 4 Oracle Data Provider for .NET Server-Side Features

<b>Introducing .NET Stored Procedure Execution Using ODP.NET</b> .....	4-1
<b>Limitations and Restrictions on ODP.NET Within .NET Stored Procedure</b> .....	4-2
Implicit Database Connection .....	4-2
Transaction Support .....	4-3
Unsupported SQL Commands.....	4-6
Oracle User-Defined Type (UDT) Support .....	4-6
<b>Porting Client Application to .NET Stored Procedure</b> .....	4-6

## 5 Oracle Data Provider for .NET Classes

<b>OracleCommand Class</b> .....	5-2
OracleCommand Members.....	5-4
OracleCommand Constructors .....	5-7
OracleCommand Static Methods .....	5-9
OracleCommand Properties .....	5-10
OracleCommand Public Methods .....	5-27
<b>OracleCommandBuilder Class</b> .....	5-41
OracleCommandBuilder Members .....	5-44
OracleCommandBuilder Constructors .....	5-47
OracleCommandBuilder Static Methods.....	5-49
OracleCommandBuilder Properties .....	5-53
OracleCommandBuilder Public Methods .....	5-58
OracleCommandBuilder Events .....	5-63
<b>OracleConnection Class</b> .....	5-64
OracleConnection Members .....	5-66
OracleConnection Constructors .....	5-69
OracleConnection Static Properties .....	5-71
OracleConnection Static Methods .....	5-73
OracleConnection Properties.....	5-76
OracleConnection Public Methods.....	5-89
OracleConnection Events.....	5-111
<b>OracleDataAdapter Class</b> .....	5-115

OracleDataAdapter Members .....	5-117
OracleDataAdapter Constructors .....	5-120
OracleDataAdapter Static Methods.....	5-123
OracleDataAdapter Properties.....	5-124
OracleDataAdapter Public Methods.....	5-130
OracleDataAdapter Events .....	5-135
<b>OracleDatabase Class</b> .....	5-139
OracleDatabase Members .....	5-141
OracleDatabase Constructor.....	5-142
OracleDatabase Properties.....	5-143
OracleDatabase Public Methods .....	5-144
<b>OracleDataReader Class</b> .....	5-151
OracleDataReader Members.....	5-154
OracleDataReader Static Methods.....	5-158
OracleDataReader Properties .....	5-159
OracleDataReader Public Methods .....	5-170
<b>OracleError Class</b> .....	5-215
OracleError Members .....	5-217
OracleError Static Methods .....	5-218
OracleError Properties.....	5-219
OracleError Methods .....	5-222
<b>OracleErrorCollection Class</b> .....	5-223
OracleErrorCollection Members .....	5-225
OracleErrorCollection Static Methods .....	5-226
OracleErrorCollection Properties.....	5-227
OracleErrorCollection Public Methods.....	5-228
<b>OracleException Class</b> .....	5-229
OracleException Members.....	5-231
OracleException Static Methods .....	5-233
OracleException Properties .....	5-234
OracleException Methods.....	5-237
<b>OracleInfoMessageEventArgs Class</b> .....	5-239
OracleInfoMessageEventArgs Members .....	5-241
OracleInfoMessageEventArgs Static Methods .....	5-242
OracleInfoMessageEventArgs Properties.....	5-243
OracleInfoMessageEventArgs Public Methods.....	5-245
<b>OracleInfoMessageEventHandler Delegate</b> .....	5-246
<b>OracleParameter Class</b> .....	5-247
OracleParameter Members .....	5-249
OracleParameter Constructors.....	5-251
OracleParameter Static Methods.....	5-262
OracleParameter Properties.....	5-263
OracleParameter Public Methods.....	5-279
<b>OracleParameterCollection Class</b> .....	5-282
OracleParameterCollection Members .....	5-284
OracleParameterCollection Static Methods.....	5-286
OracleParameterCollection Properties.....	5-287

OracleParameterCollection Public Methods .....	5-290
<b>OraclePermission Class</b> .....	5-308
OraclePermission Members .....	5-309
OraclePermission Constructor .....	5-311
OraclePermission Static Methods .....	5-312
OraclePermission Public Properties .....	5-313
OraclePermission Public Methods .....	5-314
<b>OraclePermissionAttribute Class</b> .....	5-317
OraclePermissionAttribute Members .....	5-318
OraclePermissionAttribute Constructor .....	5-320
OraclePermissionAttribute Static Methods .....	5-321
OraclePermissionAttribute Public Properties .....	5-322
OraclePermissionAttribute Public Methods .....	5-323
<b>OracleRowUpdatedEventArgs Class</b> .....	5-324
OracleRowUpdatedEventArgs Members .....	5-325
OracleRowUpdatedEventArgs Constructor .....	5-327
OracleRowUpdatedEventArgs Static Methods .....	5-328
OracleRowUpdatedEventArgs Properties .....	5-329
OracleRowUpdatedEventArgs Public Methods .....	5-330
<b>OracleRowUpdatedEventHandler Delegate</b> .....	5-331
<b>OracleRowUpdatingEventArgs Class</b> .....	5-332
OracleRowUpdatingEventArgs Members .....	5-333
OracleRowUpdatingEventArgs Constructor .....	5-335
OracleRowUpdatingEventArgs Static Methods .....	5-336
OracleRowUpdatingEventArgs Properties .....	5-337
OracleRowUpdatingEventArgs Public Methods .....	5-338
<b>OracleRowUpdatingEventHandler Delegate</b> .....	5-339
<b>OracleTransaction Class</b> .....	5-340
OracleTransaction Members .....	5-343
OracleTransaction Static Methods .....	5-344
OracleTransaction Properties .....	5-345
OracleTransaction Public Methods .....	5-347
<b>OracleCollectionType Enumeration</b> .....	5-355
<b>OracleDBShutdownMode Enumeration</b> .....	5-356
<b>OracleDBStartupMode Enumeration</b> .....	5-357
<b>OracleDbType Enumeration</b> .....	5-358
<b>OracleParameterStatus Enumeration</b> .....	5-360

## 6 Oracle Data Provider for .NET

### XML-Related Classes

<b>OracleXmlCommandType Enumeration</b> .....	6-2
<b>OracleXmlQueryProperties Class</b> .....	6-3
OracleXmlQueryProperties Members .....	6-7
OracleXmlQueryProperties Constructor .....	6-8
OracleXmlQueryProperties Properties .....	6-9
OracleXmlQueryProperties Public Methods .....	6-12
<b>OracleXmlSaveProperties Class</b> .....	6-13

OracleXmlSaveProperties Members.....	6-16
OracleXmlSaveProperties Constructor .....	6-17
OracleXmlSaveProperties Properties .....	6-18
OracleXmlSaveProperties Public Methods .....	6-22
<b>OracleXmlStream Class</b> .....	6-23
OracleXmlStream Members.....	6-24
OracleXmlStream Constructor .....	6-26
OracleXmlStream Static Methods.....	6-27
OracleXmlStream Instance Properties .....	6-28
OracleXmlStream Instance Methods.....	6-32
<b>OracleXmlType Class</b> .....	6-37
OracleXmlType Members .....	6-38
OracleXmlType Constructors.....	6-40
OracleXmlType Static Methods .....	6-43
OracleXmlType Instance Properties.....	6-44
OracleXmlType Instance Methods .....	6-49
<b>7 ADO.NET 2.0 Classes</b>	
<b>OracleClientFactory Class</b> .....	7-2
OracleClientFactory Members .....	7-4
OracleClientFactory Public Properties.....	7-5
OracleClientFactory Public Methods .....	7-6
<b>OracleConnectionStringBuilder Class</b> .....	7-10
OracleConnectionStringBuilder Members .....	7-13
OracleConnectionStringBuilder Constructors .....	7-16
OracleConnectionStringBuilder Public Properties.....	7-18
OracleConnectionStringBuilder Public Methods .....	7-33
<b>OracleDataSourceEnumerator Class</b> .....	7-36
OracleDataSourceEnumerator Members.....	7-38
OracleDataSourceEnumerator Public Methods.....	7-39
<b>8 Oracle Data Provider for .NET HA Event Classes</b>	
<b>OracleHAEventArgs Class</b> .....	8-2
OracleHAEventArgs Members .....	8-3
OracleHAEventArgs Properties.....	8-4
<b>OracleHAEventHandler Delegate</b> .....	8-8
<b>OracleHAEventSource Enumeration</b> .....	8-9
<b>OracleHAEventStatus Enumeration</b> .....	8-10
<b>9 Database Change Notification</b>	
<b>OracleDependency Class</b> .....	9-2
OracleDependency Members .....	9-3
OracleDependency Constructors.....	9-5
OracleDependency Static Fields .....	9-9
OracleDependency Static Methods .....	9-11
OracleDependency Properties.....	9-12

OracleDependency Methods .....	9-18
OracleDependency Events.....	9-21
<b>OracleNotificationRequest Class</b> .....	9-22
OracleNotificationRequest Members .....	9-23
OracleNotificationRequest Static Methods .....	9-24
OracleNotificationRequest Properties.....	9-25
OracleNotificationRequest Methods .....	9-29
<b>OracleNotificationEventArgs Class</b> .....	9-30
OracleNotificationEventArgs Members .....	9-31
OracleNotificationEventArgs Static Fields.....	9-32
OracleNotificationEventArgs Static Methods.....	9-33
OracleNotificationEventArgs Properties.....	9-34
OracleNotificationEventArgs Methods .....	9-39
<b>OnChangeEventHandler Delegate</b> .....	9-40
<b>OracleRowidInfo Enumeration</b> .....	9-41
<b>OracleNotificationType Enumeration</b> .....	9-42
<b>OracleNotificationSource Enumeration</b> .....	9-43
<b>OracleNotificationInfo Enumeration</b> .....	9-44

## 10 Oracle Data Provider for .NET Globalization Classes

<b>OracleGlobalization Class</b> .....	10-2
OracleGlobalization Members.....	10-4
OracleGlobalization Static Methods .....	10-6
OracleGlobalization Properties .....	10-12
OracleGlobalization Public Methods .....	10-22

## 11 Oracle Data Provider for .NET Failover Classes

<b>OracleFailoverEventArgs Class</b> .....	11-2
OracleFailoverEventArgs Members .....	11-5
OracleFailoverEventArgs Static Methods .....	11-6
OracleFailoverEventArgs Properties.....	11-7
OracleFailoverEventArgs Public Methods.....	11-8
<b>OracleFailoverEventHandler Delegate</b> .....	11-9
<b>FailoverEvent Enumeration</b> .....	11-10
<b>FailoverReturnCode Enumeration</b> .....	11-11
<b>FailoverType Enumeration</b> .....	11-12

## 12 Advanced Queuing Support

<b>OracleAQAgent Class</b> .....	12-2
OracleAQAgent Members .....	12-3
OracleAQAgent Constructors .....	12-4
OracleAQAgent Properties.....	12-6
<b>OracleAQDequeueOptions Class</b> .....	12-8
OracleAQDequeueOptions Members .....	12-9

OracleAQDequeueOptions Constructor.....	12-11
OracleAQDequeueOptions Properties.....	12-12
OracleAQDequeueOptions Public Methods.....	12-18
<b>OracleAQEnqueueOptions Class.....</b>	<b>12-19</b>
OracleAQEnqueueOptions Members .....	12-20
OracleAQEnqueueOptions Constructor.....	12-21
OracleAQEnqueueOptions Properties.....	12-22
OracleAQEnqueueOptions Public Methods .....	12-24
<b>OracleAQMessage Class .....</b>	<b>12-25</b>
OracleAQMessage Members .....	12-26
OracleAQMessage Constructors.....	12-28
OracleAQMessage Properties .....	12-30
<b>OracleAQMessageAvailableEventArgs Class .....</b>	<b>12-38</b>
OracleAQMessageAvailableEventArgs Members .....	12-39
OracleAQMessageAvailableEventArgs Properties.....	12-40
<b>OracleAQMessageAvailableEventHandler Delegate .....</b>	<b>12-47</b>
<b>OracleAQQueue Class .....</b>	<b>12-48</b>
OracleAQQueue Members .....	12-49
OracleAQQueue Constructors .....	12-51
OracleAQQueue Static Methods.....	12-55
OracleAQQueue Properties.....	12-58
OracleAQQueue Public Methods .....	12-64
OracleAQQueue Events .....	12-79
<b>OracleAQDequeueMode Enumeration .....</b>	<b>12-84</b>
<b>OracleAQMessageDeliveryMode Enumeration .....</b>	<b>12-85</b>
<b>OracleAQMessageState Enumeration.....</b>	<b>12-87</b>
<b>OracleAQMessageType Enumeration.....</b>	<b>12-88</b>
<b>OracleAQNavigationMode Enumeration.....</b>	<b>12-89</b>
<b>OracleAQNotificationGroupingType Enumeration .....</b>	<b>12-90</b>
<b>OracleAQNotificationType Enumeration .....</b>	<b>12-91</b>
<b>OracleAQVisibilityMode Enumeration.....</b>	<b>12-92</b>

## 13 Oracle Data Provider for .NET Types Classes

<b>OracleBFile Class.....</b>	<b>13-2</b>
OracleBFile Members.....	13-4
OracleBFile Constructors .....	13-7
OracleBFile Static Fields.....	13-9
OracleBFile Static Methods.....	13-11
OracleBFile Instance Properties .....	13-12
OracleBFile Instance Methods.....	13-19
<b>OracleBlob Class .....</b>	<b>13-38</b>
OracleBlob Members .....	13-40
OracleBlob Constructors .....	13-43
OracleBlob Static Fields.....	13-45
OracleBlob Static Methods.....	13-46
OracleBlob Instance Properties .....	13-47
OracleBlob Instance Methods.....	13-53

<b>OracleClob Class</b> .....	13-73
OracleClob Members .....	13-75
OracleClob Constructors .....	13-78
OracleClob Static Fields .....	13-80
OracleClob Static Methods .....	13-81
OracleClob Instance Properties .....	13-82
OracleClob Instance Methods .....	13-88
<b>OracleRefCursor Class</b> .....	13-113
OracleRefCursor Members .....	13-116
OracleRefCursor Static Methods .....	13-117
OracleRefCursor Properties .....	13-118
OracleRefCursor Instance Methods .....	13-121

## 14 Oracle Data Provider for .NET Types Structures

<b>OracleBinary Structure</b> .....	14-2
OracleBinary Members .....	14-4
OracleBinary Constructor .....	14-7
OracleBinary Static Fields .....	14-8
OracleBinary Static Methods .....	14-9
OracleBinary Static Operators .....	14-15
OracleBinary Static Type Conversion Operators .....	14-21
OracleBinary Properties .....	14-23
OracleBinary Instance Methods .....	14-26
<b>OracleDate Structure</b> .....	14-29
OracleDate Members .....	14-31
OracleDate Constructors .....	14-34
OracleDate Static Fields .....	14-39
OracleDate Static Methods .....	14-41
OracleDate Static Operators .....	14-47
OracleDate Static Type Conversions .....	14-52
OracleDate Properties .....	14-56
OracleDate Methods .....	14-60
<b>OracleDecimal Structure</b> .....	14-65
OracleDecimal Members .....	14-67
OracleDecimal Constructors .....	14-72
OracleDecimal Static Fields .....	14-78
OracleDecimal Static (Comparison) Methods .....	14-82
OracleDecimal Static (Manipulation) Methods .....	14-87
OracleDecimal Static (Logarithmic) Methods .....	14-101
OracleDecimal Static (Trigonometric) Methods .....	14-106
OracleDecimal Static (Comparison) Operators .....	14-112
OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal) .....	14-120
OracleDecimal Static Operators (Conversion from OracleDecimal to .NET) .....	14-124
OracleDecimal Properties .....	14-129
OracleDecimal Instance Methods .....	14-133
<b>OracleIntervalDS Structure</b> .....	14-139



OracleIntervalDS Members .....	14-141
OracleIntervalDS Constructors .....	14-144
OracleIntervalDS Static Fields.....	14-149
OracleIntervalDS Static Methods.....	14-151
OracleIntervalDS Static Operators.....	14-158
OracleIntervalDS Type Conversions.....	14-166
OracleIntervalDS Properties.....	14-169
OracleIntervalDS Methods .....	14-174
<b>OracleIntervalYM Structure</b> .....	14-177
OracleIntervalYM Members .....	14-179
OracleIntervalYM Constructors.....	14-182
OracleIntervalYM Static Fields .....	14-186
OracleIntervalYM Static Methods .....	14-188
OracleIntervalYM Static Operators .....	14-194
OracleIntervalYM Type Conversions.....	14-201
OracleIntervalYM Properties.....	14-204
OracleIntervalYM Methods .....	14-207
<b>OracleString Structure</b> .....	14-210
OracleString Members.....	14-212
OracleString Constructors.....	14-215
OracleString Static Fields .....	14-220
OracleString Static Methods .....	14-221
OracleString Static Operators.....	14-226
OracleString Type Conversions .....	14-231
OracleString Properties .....	14-233
OracleString Methods.....	14-236
<b>OracleTimeStamp Structure</b> .....	14-241
OracleTimeStamp Members .....	14-243
OracleTimeStamp Constructors.....	14-247
OracleTimeStamp Static Fields .....	14-254
OracleTimeStamp Static Methods .....	14-256
OracleTimeStamp Static Operators .....	14-263
OracleTimeStamp Static Type Conversions.....	14-272
OracleTimeStamp Properties.....	14-278
OracleTimeStamp Methods .....	14-283
<b>OracleTimeStampLTZ Structure</b> .....	14-294
OracleTimeStampLTZ Members .....	14-296
OracleTimeStampLTZ Constructors .....	14-300
OracleTimeStampLTZ Static Fields.....	14-307
OracleTimeStampLTZ Static Methods.....	14-309
OracleTimeStampLTZ Static Operators.....	14-317
OracleTimeStampLTZ Static Type Conversions .....	14-326
OracleTimeStampLTZ Properties.....	14-332
OracleTimeStampLTZ Methods .....	14-337
<b>OracleTimeStampTZ Structure</b> .....	14-349
OracleTimeStampTZ Members .....	14-351
OracleTimeStampTZ Constructors.....	14-355

OracleTimeStampTZ Static Fields .....	14-367
OracleTimeStampTZ Static Methods .....	14-369
OracleTimeStampTZ Static Operators .....	14-376
OracleTimeStampTZ Static Type Conversions.....	14-385
OracleTimeStampTZ Properties .....	14-391
OracleTimeStampTZ Methods.....	14-397
<b>INullable Interface</b> .....	14-409
INullable Interface Members.....	14-410
INullable Interface Properties .....	14-411

## 15 Oracle Data Provider for .NET Types Exceptions

<b>OracleTypeException Class</b> .....	15-2
OracleTypeException Members.....	15-3
OracleTypeException Constructors.....	15-5
OracleTypeException Static Methods .....	15-7
OracleTypeException Properties .....	15-8
OracleTypeException Methods.....	15-10
<b>OracleNullValueException Class</b> .....	15-11
OracleNullValueException Members .....	15-12
OracleNullValueException Constructors .....	15-14
OracleNullValueException Static Methods.....	15-16
OracleNullValueException Properties.....	15-17
OracleNullValueException Methods .....	15-18
<b>OracleTruncateException Class</b> .....	15-19
OracleTruncateException Members .....	15-20
OracleTruncateException Constructors.....	15-22
OracleTruncateException Static Methods .....	15-24
OracleTruncateException Properties.....	15-25
OracleTruncateException Methods .....	15-26

## 16 Oracle Data Provider for .NET UDT-Related Classes

<b>OracleCustomTypeMappingAttribute Class</b> .....	16-2
OracleCustomTypeMappingAttribute Members.....	16-4
OracleCustomTypeMappingAttribute Constructors.....	16-6
OracleCustomTypeMappingAttribute Static Methods .....	16-7
OracleCustomTypeMappingAttribute Properties .....	16-8
OracleCustomTypeMappingAttribute Methods.....	16-9
<b>OracleObjectMappingAttribute Class</b> .....	16-10
OracleObjectMappingAttribute Members.....	16-11
OracleObjectMappingAttribute Constructors .....	16-13
OracleObjectMappingAttribute Static Methods.....	16-15
OracleObjectMappingAttribute Properties .....	16-16
OracleObjectMappingAttribute Methods.....	16-18
<b>OracleArrayMappingAttribute Class</b> .....	16-19
OracleArrayMappingAttribute Members .....	16-20
OracleArrayMappingAttribute Constructors .....	16-22
OracleArrayMappingAttribute Static Methods.....	16-23

OracleArrayMappingAttribute Properties .....	16-24
OracleArrayMappingAttribute Methods .....	16-25
<b>IOracleCustomType Interface</b> .....	16-26
IOracleCustomType Members .....	16-27
IOracleCustomType Interface Methods.....	16-28
<b>IOracleCustomTypeFactory Interface</b> .....	16-30
IOracleCustomTypeFactory Members.....	16-31
IOracleCustomTypeFactory Interface Methods .....	16-32
<b>IOracleArrayTypeFactory Interface</b> .....	16-33
IOracleArrayTypeFactory Members .....	16-34
IOracleArrayTypeFactory Interface Methods.....	16-35
<b>OracleUdt Class</b> .....	16-37
OracleUdt Members.....	16-38
OracleUDT Static Methods .....	16-39
<b>OracleRef Class</b> .....	16-51
OracleRef Members.....	16-52
OracleRef Constructors .....	16-54
OracleRef Static Fields.....	16-56
OracleRef Static Methods.....	16-57
OracleRef Instance Properties .....	16-58
Oracle Ref Instance Methods.....	16-62
<b>OracleUdtFetchOption Enumeration</b> .....	16-73
<b>OracleUdtStatus Enumeration</b> .....	16-74

## 17 Oracle Data Provider for .NET

### Bulk Copy Classes

<b>OracleBulkCopy Class</b> .....	17-2
OracleBulkCopy Members.....	17-3
OracleBulkCopy Constructors .....	17-5
OracleBulkCopy Properties .....	17-9
OracleBulkCopy Public Methods .....	17-14
OracleBulkCopy Events .....	17-20
<b>OracleBulkCopyColumnMapping Class</b> .....	17-21
OracleBulkCopyColumnMapping Members.....	17-22
OracleBulkCopyColumnMapping Constructors.....	17-23
OracleBulkCopyColumnMapping Properties .....	17-26
<b>OracleBulkCopyColumnMappingCollection Class</b> .....	17-29
OracleBulkCopyColumnMappingCollection Members.....	17-31
OracleBulkCopyColumnMappingCollection Properties .....	17-32
OracleBulkCopyColumnMappingCollection Public Methods.....	17-33
<b>OracleBulkCopyOptions Enumeration</b> .....	17-42
<b>OracleRowsCopiedEventHandler Delegate</b> .....	17-43
<b>OracleRowsCopiedEventArgs Class</b> .....	17-44
OracleRowsCopiedEventArgs Members.....	17-45
OracleRowsCopiedEventArgs Constructors.....	17-46
OracleRowsCopiedEventArgs Properties .....	17-47

## A Oracle Schema Collections

<b>Common Schema Collections</b> .....	A-1
MetadataCollections.....	A-1
DataSourceInformation .....	A-2
DataTypes .....	A-3
Restrictions .....	A-4
ReservedWords .....	A-5
<b>ODP.NET-Specific Schema Collection</b> .....	A-5
Tables .....	A-5
Columns .....	A-6
Views .....	A-6
XMLSchema .....	A-7
Users .....	A-7
Synonyms .....	A-7
Sequences .....	A-8
Functions .....	A-8
Procedures .....	A-9
ProcedureParameters .....	A-10
Arguments .....	A-11
Packages .....	A-11
PackageBodies .....	A-12
JavaClasses .....	A-13
Indexes .....	A-13
IndexColumns .....	A-16
PrimaryKeys .....	A-16
ForeignKeys .....	A-17
ForeignKeyColumns .....	A-18
UniqueKeys .....	A-18

## Glossary

## Index

---

---

# Preface

This document is your primary source of introductory, installation, postinstallation configuration, and usage information for Oracle Data Provider for .NET.

Oracle Data Provider for .NET is an implementation of the Microsoft ADO.NET interface.

This Preface contains these topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Passwords in Code Examples](#)
- [Conventions](#)

## Audience

*Oracle Data Provider for .NET Developer's Guide* is intended for programmers who are developing applications to access an Oracle database using Oracle Data Provider for .NET. This documentation is also valuable to systems analysts, project managers, and others interested in the development of database applications.

To use this document, you must be familiar with Microsoft .NET Framework classes and ADO.NET and have a working knowledge of application programming using Microsoft C#, Visual Basic .NET, or another .NET language.

Although the examples in the documentation and the samples in the sample directory are written in C#, developers can use these examples as models for writing code in other .NET languages.

Users should also be familiar with the use of Structured Query Language (SQL) to access information in relational database systems.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be

accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

### **Accessibility of Code Examples in Documentation**

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### **Accessibility of Links to External Web Sites in Documentation**

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

### **Deaf/Hard of Hearing Access to Oracle Support Services**

To reach Oracle Support Services, use a telecommunications relay service (TRS) to call Oracle Support at 1.800.223.1711. An Oracle Support Services engineer will handle technical issues and provide customer support according to the Oracle service request process. Information about TRS is available at <http://www.fcc.gov/cgb/consumerfacts/trs.html>, and a list of phone numbers is available at <http://www.fcc.gov/cgb/dro/trsphonebk.html>.

## **Related Documents**

For more information, see these Oracle resources:

- *Oracle Database Installation Guide for Windows*
- *Oracle Database Release Notes for Windows*
- *Oracle Database Platform Guide for Windows*
- *Oracle Database Administrator's Guide*
- *Oracle Database Advanced Application Developer's Guide*
- *Oracle Database Application Developer's Guide - Large Objects*
- *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database New Features*
- *Oracle Database Concepts*
- *Oracle Database Reference*
- *Oracle Database Extensions for .NET Developer's Guide*
- *Oracle Database Application Developer's Guide - Object-Relational Features*
- *Oracle Database SQL Reference*
- *Oracle Net Services Administrator's Guide*
- *Oracle Net Services Reference Guide*
- *Oracle Call Interface Programmer's Guide*
- *Oracle Services for Microsoft Transaction Server Developer's Guide*
- *Oracle Database Globalization Support Guide*

- *Oracle XML DB Developer's Guide*
- *Oracle XML Developer's Kit Programmer's Guide*
- *Oracle Database Security Guide*
- *Oracle Spatial User's Guide and Reference*
- Oracle Data Guard Concepts and Administration

Many of the examples in this book use the sample schemas, which are installed by default when you select the Basic Installation option with an Oracle Database installation. Refer to *Oracle Database Sample Schemas* for information on how these schemas were created and how you can use them yourself.

Printed documentation is available for sale in the Oracle Store at

<http://oraclestore.oracle.com/>

To download free release notes, installation documentation, white papers, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technology/contact/welcome.html>

If you already have a username and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://www.oracle.com/technology/documentation/index.html>

For additional information, see:

<http://msdn.microsoft.com/netframework>

and

<http://msdn.microsoft.com/library>

## Passwords in Code Examples

For simplicity in demonstrating this product, code examples do not perform the password management techniques that a deployed system normally uses. In a production environment, follow the Oracle Database password management guidelines, and disable any sample accounts. See *Oracle Database Security Guide* for password management guidelines and other security recommendations.

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.





---

---

# What's New in Oracle Data Provider for .NET?

This section describes new features in Oracle Data Provider for .NET and provides references to additional information. New features information from previous releases is also retained to help those users migrating to the current release.

The following sections describe the new features in Oracle Data Provider for .NET:

- [New Features in Oracle Data Provider for .NET Release 11.2](#)
- [New Features in Oracle Data Provider for .NET Release 11.1.0.7.20](#)
- [New Features in Oracle Data Provider for .NET Release 11.1.0.6.20](#)
- [New Features in Oracle Data Provider for .NET Release 11.1](#)
- [New Features in Oracle Data Provider for .NET Release 10.2.0.4](#)
- [New Features in Oracle Data Provider for .NET Release 10.2.0.3](#)
- [New Features in Oracle Data Provider for .NET Release 10.2.0.2](#)
- [New Features in Oracle Data Provider for .NET Release 10.2](#)
- [New Features in Oracle Data Provider for .NET Release 10.1.0.3](#)
- [New Features in Oracle Data Provider for .NET Release 10.1](#)
- [New Features in Oracle Data Provider for .NET Release 9.2.0.4](#)

## New Features in Oracle Data Provider for .NET Release 11.2

Oracle Data Provider for .NET release 11.2 includes the following:

- End-to-End Tracing: `ClientInfo` Property

ODP.NET now supports the `ClientInfo` write-only property, in addition to the `ActionName`, `ClientId`, and `ModuleName` properties, on the `OracleConnection` object. This property specifies the client information for the connection.

The `ClientInfo` property is an end-to-end tracing attribute that can be set on the client or middle tier. This attribute is propagated to the database server whenever the next server round-trip happens. This reduces the added overhead associated with an independent database round trip. Using the `ClientInfo` property is helpful in tracking database user activities and debugging applications.

**See Also:**

- ["Client Identifier and End-to-End Tracing"](#) on page 3-16
- ["ClientInfo"](#) on page 5-77

## New Features in Oracle Data Provider for .NET Release 11.1.0.7.20

Oracle Data Provider for .NET release 11.1.0.7.20 includes the following:

- Self-Tuning for Applications

Based on run-time sampling, ODP.NET dynamically adjusts statement cache size to provide better application performance. Self-tuning also takes into account memory usage on the client machine in order to prevent excessive memory usage. Self-tuning improves ODP.NET performance, reduces network usage, and decreases server CPU and client CPU activity.

**See Also:** ["Self-Tuning"](#) on page 3-44

- Faster Data Retrieval and Less Memory Usage

Retrieving data using `OracleDataReader` or populating a `DataSet` from an `OracleDataAdapter` is now faster.

ODP.NET reuses the same fetch array buffer for statements executed non-concurrently, saving on memory usage. The fetch array buffer stores data retrieved from the database.

No code changes are necessary to use these features. These features provide better performance and scalability for ODP.NET applications.

- Oracle Streams Advanced Queuing Support

ODP.NET supports access to Oracle Streams Advanced Queuing (AQ). AQ provides database-integrated message queuing functionality to store messages persistently, propagate messages between queues on different machines and databases, and transmit messages using Oracle NET services, HTTP, HTTPS and SMTP.

ODP.NET can access all the operational features of AQ, such as enqueue, dequeue, listen and notification. Oracle Developer Tools for Visual Studio can administer and manage AQ resources.

**See Also:** ["Oracle Streams Advanced Queuing Support"](#) on page 3-92

- Promotable Local Transaction Support

Distributed transactions require the orchestration of application, transaction coordinator, and multiple databases. Local transactions only require an application and a single resource manager, or database. Local transactions have less of an overhead when compared to distributed transactions.

It may be difficult to determine whether a transaction will be local or distributed at design time. Developers are forced to design applications for distributed transactions, even if local transactions are used most of the time. This situation leads to more resource usage than necessary at run time.

Promotable local transactions allow all transactions to remain local until more than one database is brought into the transaction. At this point, the transaction is

promoted to a distributed transaction so that it can be managed by the transaction coordinator. This provides a better utilization of system resources. This feature is supported with Oracle Database 11g release 1 (11.1.0.7) and higher.

**See Also:** ["System.Transactions and Promotable Transactions"](#) on page 3-22

- ODP.NET Security Enhancements

ODP.NET makes use of the `OraclePermission` class to enforce imperative security. This helps ensure that a user or application has a security level adequate for accessing data.

**See Also:**

- ["Support for Code Access Security"](#) on page 3-20
- ["OraclePermission Class"](#) on page 5-308
- ["OraclePermissionAttribute Class"](#) on page 5-317

- Callbacks for HA Event Notifications

ODP.NET can register for Oracle High Availability (HA) events when `"ha events=true"` is specified in the connection string. ODP.NET is then able to receive notifications on which database, service, host, or instance has gone down or come up. .NET developers can register a callback with ODP.NET to notify the application when one of these events occurs and subsequently execute an event handler, as needed.

**See Also:**

- [Chapter 8, "Oracle Data Provider for .NET HA Event Classes"](#) on page 8-1
- ["HAEvent"](#) on page 5-112
- ["OracleConnection Properties"](#) on page 5-76

- Database Startup and Shutdown Operations

Users with database administrator privileges can use the `OracleDatabase` class to startup or shutdown a database instance.

**See Also:**

- ["OracleDatabase Class"](#) on page 5-139
- ["Shutdown"](#) on page 5-144
- ["Startup"](#) on page 5-148

## New Features in Oracle Data Provider for .NET Release 11.1.0.6.20

Oracle Data Provider for .NET release 11.1.0.6.20 includes the following:

- Oracle XCopy

Oracle XCopy provides system administrators with an ODP.NET client that is smaller in disk size than the standard ODP.NET client and is easily configurable. Oracle XCopy makes embedding ODP.NET in customized deployment packages much simpler.

**See Also:** ["XCopy"](#) on page 2-2

- Support for Oracle User-Defined Types

ODP.NET has the ability to represent Oracle UDTs defined in the database as custom types in .NET applications.

**See Also:**

- ["Oracle User-Defined Types \(UDTs\) and .NET Custom Types"](#) on page 3-77
- [Chapter 16, "Oracle Data Provider for .NET UDT-Related Classes"](#) on page 16-1

- Bulk Copy Operations

ODP.NET supports the Bulk Copy operations to load a large amount of data efficiently.

**See Also:**

- ["Bulk Copy Support"](#) on page 3-28
- [Chapter 17, "Oracle Data Provider for .NET Bulk Copy Classes"](#) on page 17-1

- Additional Connection Pool Optimizations for Real Application Clusters (RAC) and Oracle Data Guard

ODP.NET now cleans up the connection pool when the database down event is received from Oracle RAC or Oracle Data Guard. This is in addition to the events that ODP.NET already cleaned up the connection pool for: node down, service member down, and service down events.

**See Also:** ["Connection Optimization for Oracle RAC and Oracle Data Guard"](#) on page 3-9

- Windows-Authenticated User Connection Pooling

Operating system-authenticated connections can now be managed as part of ODP.NET connection pools

**See Also:** ["Operating System Authentication"](#) on page 3-11

- Connection Pool Performance Counters

ODP.NET publishes performance counters for connection pooling, which can be viewed using the Windows Performance Monitor.

**See Also:**

- ["Performance Counters"](#) on page 2-4
- ["Connection Pool Performance Counters"](#) on page 3-7

- End-to-End Tracing Attribute Support

ODP.NET supports the `ActionName`, `ClientId`, `ClientInfo`, and `ModuleName` write-only properties on the `OracleConnection` object. These properties correspond to end-to-end tracing attributes that can be set on the client

or middle-tier, and propagated to the database server whenever the next server round-trip happens. This reduces the added overhead associated with an independent database round trip. Using these attributes is helpful in tracking database user activities and debugging applications.

**See Also:** ["Client Identifier and End-to-End Tracing"](#) on page 3-16

## New Features in Oracle Data Provider for .NET Release 11.1

Oracle Data Provider for .NET release 11.1 includes the following:

- Performance Enhancements

The following performance enhancements have been made:

- Improved Parameter Context Caching

This release enhances the existing caching infrastructure to cache ODP.NET parameter contexts. This enhancement is independent of database version and it is available for all the supported database versions. This feature provides significant performance improvement for the applications that execute the same statement repeatedly.

This enhancement is transparent to the developer. No code changes are needed to use this feature.

- Efficient LOB Retrieval with LOBS or SecureFiles

When using LOBS or SecureFiles, this release improves the performance of small-sized LOB retrieval by reducing the number of round-trips to the database. SecureFiles is available with Oracle 11g release 1 or later database versions.

This enhancement is transparent to the developer. No code changes are needed to use this feature.

## New Features in Oracle Data Provider for .NET Release 10.2.0.4

Oracle Data Provider for .NET release 10.2.0.4 includes the following:

- ODP.NET Configuration

Developers can now configure ODP.NET using configuration files, including application config, `web.config`, or `machine.config`.

Settings in the `machine.config` override the registry settings. The settings in the application config or the `web.config` override the values in the `machine.config`.

**See Also:** ["ODP.NET Configuration"](#) on page 3-114

## New Features in Oracle Data Provider for .NET Release 10.2.0.3

Oracle Data Provider for .NET release 10.2.0.3 includes the following:

- 64-bit ODP.NET for Windows x64 and Windows Itanium

ODP.NET natively supports the 64-bit .NET Framework for both 64-bit Windows platforms:

- Windows x64 for AMD64 and Intel EM64T processors

- 64-bit Windows for Intel Itanium

64-bit systems allow for more scalable and better performing ODP.NET applications.

- Configuring `FetchSize` Through the Windows Registry

This feature enables applications to specify the default result set fetch size through the registry.

- Local Transaction Support for `System.Transactions`

This feature enables `System.Transactions` to use local transactions rather than distributed transactions. This can be specified either through the registry or through a connection string attribute.

**See Also:** ["Local Transaction Support for Older Databases"](#) on page 3-26

## New Features in Oracle Data Provider for .NET Release 10.2.0.2

Oracle Data Provider for .NET release 10.2.0.2 includes the following:

- Support for Microsoft ADO.NET 2.0, including.
  - Provider Factory Classes and Base Classes  
Simplifies data access code to access multiple data sources with a provider generic API.
  - Connection String Builder  
Makes creating connections strings less error-prone and easier to manage.
  - Data Source Enumerator  
Enables the application to generically obtain a collection of the Oracle data sources that the application can connect to.
  - Support for Schema Discovery  
Permits application developers to find and return database schema information, such as tables, columns, and stored procedures.
  - System.Transactions Support  
ODP.NET supports implicit and explicit transactions using the `System.Transactions` namespace models.
  - Batch Processing Support  
Enables batch processing when the `OracleDataAdapter.Update` method is called.

**See Also:** ["ADO.NET 2.0 Features"](#) on page 3-18

## New Features in Oracle Data Provider for .NET Release 10.2

Oracle Data Provider for .NET release 10.2 includes the following:

- Server-Side Features  
Server-side features for Oracle Data Provider for .NET provide data access from .NET stored procedures. Such procedures are enabled by Oracle Database Extensions for .NET, a new feature included with Oracle database on Windows.

**See Also:**

- [Chapter 4, "Oracle Data Provider for .NET Server-Side Features"](#)
- *Oracle Database Extensions for .NET Developer's Guide*

- Support for Client Identifier

Oracle Data Provider for .NET exposes the `OracleConnection.ClientId` property, thus providing support for Oracle Virtual Private Database (VPD) and application context. Client identifier makes configuring VPD simpler for the developer.

**See Also:** ["Client Identifier and End-to-End Tracing"](#) on page 3-16

- Connection Pool Optimizations for Real Application Clusters (RAC)

Oracle Data Provider for .NET optimizes connection pooling for Oracle RAC databases by balancing work requests across Oracle RAC instances, based on the load balancing advisory and service goal. Furthermore, the ODP.NET connection pool can be enabled to proactively free resources associated with connections that have been severed due to a down Oracle RAC service, instance, or node.

**See Also:** ["Connecting to an Oracle Real Application Clusters \(RAC\) Database"](#) on page 3-9

- Database Change Notification Support

Oracle Data Provider for .NET provides a notification framework that supports Continuous Query Notification. This enables applications to receive notifications when there is a change in a query result set or a change in the state of the database.

**See Also:**

- ["Database Change Notification Support"](#) on page 3-97
- [Chapter 9, "Database Change Notification"](#)

- Connection Pooling Management

Oracle Data Provider for .NET connection pool management provides explicit connection pool control to ODP.NET applications. Applications can explicitly clear connections in a connection pool or all the connection pools.

**See Also:** ["Connection Pool Management"](#) on page 3-7

- Better LOB performance and functionality with Oracle Database 10g release 2 (10.2) and later

**See Also:** ["InitialLOBFetchSize"](#) on page 5-18

- Support for IN and IN/OUT REF CURSOR Objects

This feature enables applications to retrieve `REF CURSOR`s from a PL/SQL procedure or function and pass them to another stored procedure or function.

**See Also:** ["Passing a REF CURSOR to a Stored Procedure"](#) on page 3-60

## New Features in Oracle Data Provider for .NET Release 10.1.0.3

Oracle Data Provider for .NET release 10.1.0.3 includes the following:

- Statement Caching

This feature provides and manages a cache of statements for each session. The developer can control which statements are cached and how many. This improves performance and scalability.

**See Also:** ["Statement Caching"](#) on page 3-42

- .NET Framework 1.1 Enhancements

These enhancements expose new ADO.NET functionality that was introduced in Microsoft .NET Framework 1.1.

**See Also:**

- ["EnlistDistributedTransaction"](#) on page 5-95
- ["HasRows"](#) on page 5-161

- Support for Command Cancellation and Timeout

These two new features relate to command cancellation. The `CommandTimeout` feature cancels the execution of a command when a specified amount of time elapses after the execution, while the `Cancel` method can be called explicitly by the application to terminate the execution of a command.

**See Also:**

- ["CommandTimeout"](#) on page 5-15
- ["Cancel"](#) on page 5-27

- `DeriveParameters` Method

This method populates the parameter collection for the `OracleCommand` that represents a stored procedure or function by querying the database for the parameter information.

**See Also:** ["DeriveParameters"](#) on page 5-49

- LOB Retrieval Enhancement

Entire LOB column data can be retrieved even if the select list does not contain a primary key, ROWID, or unique key. This enhancement is available by setting the `InitialLOBFetchSize` property value to -1 for CLOB and BLOB objects.

**See Also:** ["Setting InitialLOBFetchSize to -1"](#) on page 3-54

- LONG Retrieval Enhancement

Entire LONG column data can be retrieved even if the select list does not contain a primary key, ROWID, or unique key. This enhancement is available by setting the `InitialLONGFetchSize` property value to -1.



**See Also:** ["Setting InitialLONGFetchSize to -1"](#) on page 3-52

## New Features in Oracle Data Provider for .NET Release 10.1

Oracle Data Provider for .NET release 10.1 includes the following:

- Support for Oracle Grids  
ODP.NET is grid-enabled, allowing developers to take advantage of Oracle Database Grid support without having to make changes to their application code.
- Support for BINARY\_FLOAT and BINARY\_DOUBLE data types in the database  
ODP.NET supports the new database native types BINARY\_FLOAT and BINARY\_DOUBLE

**See Also:** ["Data Types BINARY\\_FLOAT and BINARY\\_DOUBLE"](#) on page 3-31

- Support for Multiple Homes  
ODP.NET can be installed in Multiple Oracle Homes.  
In order to make multiple homes available, some of the ODP.NET files include a version number, and the use of a HOMEID is required.
- Support for Schema-Based XMLType in the Database  
ODP.NET supports the native schema-based XMLType.

## New Features in Oracle Data Provider for .NET Release 9.2.0.4

Oracle Data Provider for .NET release 9.2.0.4, which was released on Oracle Technology Network (OTN), included the following:

- XML Support in ODP.NET  
With XML support, ODP.NET can now:
  - Store XML data natively in the database as Oracle Database native type, XMLType.
  - Access relational and object-relational data as XML data from an Oracle Database instance into a Microsoft .NET environment, process the XML using the Microsoft .NET Framework.
  - Save changes to the database using XML data.

**See Also:** ["ODP.NET XML Support"](#) on page 3-64

- Support for PL/SQL Associative Array Binding  
ODP.NET supports PL/SQL Associative Array (formerly known as PL/SQL Index-By Tables) binding.  
An application can bind an OracleParameter, as a PL/SQL Associative Array, to a PL/SQL stored procedure using OracleParameter properties.

**See Also:** ["PL/SQL Associative Array Binding"](#) on page 3-36

- Support for InitialLOBFetchSize property on OracleCommand and OracleDataReader objects

**See Also:** ["Obtaining LOB Data"](#) on page 3-52

---

---

# Introducing Oracle Data Provider for .NET

This chapter introduces Oracle Data Provider for .NET (ODP.NET), an implementation of a .NET data provider for Oracle Database.

This chapter contains these topics:

- [.NET Data Access in Oracle: Products and Documentation](#)
- [Overview of Oracle Data Provider for .NET \(ODP.NET\)](#)
- [Oracle Data Provider for .NET Assembly](#)
- [Using ODP.NET Client Provider in a Simple Application](#)

## .NET Data Access in Oracle: Products and Documentation

This section discusses Oracle components and products that work together to provide .NET data access to Oracle Database, how they relate to each other, and what documentation is provided.

These Oracle products provide .NET integration on the Windows operating system:

### Oracle Data Provider for .NET (ODP.NET)

Oracle Data Provider for .NET provides fast data access from .NET clients to Oracle databases. ODP.NET enables .NET applications to take advantage of Oracle advanced features, such as Real Application Clusters (RAC) and XML DB. It is accessible through any .NET language, including C#, Visual Basic .NET, and C++ .NET.

*Oracle Data Provider for .NET Developer's Guide* describes Oracle Data Provider for .NET features, their use, installation, requirements, and classes. The guide distinguishes which classes are supported in .NET stored procedures and which classes are supported for .NET clients.

Additionally, Oracle Data Provider for .NET Dynamic Help, which is context-sensitive online help, contains the same reference sections available in *Oracle Data Provider for .NET Developer's Guide*, this guide.

Oracle Data Provider for .NET Dynamic Help is integrated with Visual Studio Dynamic Help. With Dynamic Help, you can access Oracle Data Provider for .NET documentation within Visual Studio by placing the cursor on an Oracle Data Provider for .NET keyword and pressing the F1 function key.

### Oracle Developer Tools for Visual Studio

Oracle Developer Tools is an add-in to Visual Studio that provides graphical user interface (GUI) access to Oracle functionality. It provides improved developer

productivity and ease of use. Oracle Developer Tools provide the ability to build .NET stored procedures using Visual Basic .NET, C#, and other .NET languages.

Oracle Developer Tools for Visual Studio Help describes Oracle Developer Tools. This help is in the form of dynamic help, which installs as part of the product.

Additionally, the Oracle Developer Tools for Visual Studio Help includes the following documentation:

- *Oracle Database PL/SQL User's Guide and Reference*
- *Oracle Database SQL Reference*
- *Oracle Database Extensions for .NET Developer's Guide*
- *Oracle Database Error Messages*
- Access to Oracle Data Provider for .NET Dynamic Help
- Access to Oracle Providers for ASP.NET Dynamic Help

## Oracle Database Extensions for .NET

Oracle Database Extensions for .NET provides the following:

- Hosting of Microsoft Common Language Runtime (CLR) in an external process on the server side, to execute .NET stored procedures.
- ODP.NET data access on the server side, from within the .NET stored procedure.

Oracle Database Extensions for .NET features, their use, installation, and requirements are described in *Oracle Database Extensions for .NET Developer's Guide*.

*Oracle Data Provider for .NET Developer's Guide* describes all ODP.NET classes. Classes that are not supported by Oracle Database Extensions for .NET are described as *Not Supported in a .NET Stored Procedure*.

### See Also:

- Oracle Developer Tools for Visual Studio Help
- *Oracle Database Extensions for .NET Developer's Guide* for more information about .NET stored procedures and functions
- ["Oracle Data Provider for .NET Assembly"](#) on page 1-3 for class listings
- [Chapter 4, "Oracle Data Provider for .NET Server-Side Features"](#)

## Oracle Providers for ASP.NET

Oracle Providers for ASP.NET offer ASP.NET developers an easy to use method to store state common to web applications within an Oracle database. These providers are modeled on existing Microsoft ASP.NET providers, sharing similar schema and programming interfaces to provide .NET developers a familiar interface. Oracle supports the following providers:

- Cache Dependency Provider
- Membership Provider
- Profile Provider
- Role Provider
- Session State Provider

- Site Map Provider
- Web Events Provider
- Web Parts Personalization Provider

Oracle Providers for ASP.NET classes, their use, installation, and requirements are described in *Oracle Providers for ASP.NET Developer's Guide*, which is also provided as dynamic help.

## Overview of Oracle Data Provider for .NET (ODP.NET)

Oracle Data Provider for .NET (ODP.NET) is an implementation of a .NET data provider for Oracle Database, using and inheriting from classes and interfaces available in the [Microsoft .NET Framework Class Library](#).

Following the .NET Framework, ODP.NET uses the ADO.NET model, which allows native providers to expose provider-specific features and data types. This is similar to Oracle Provider for OLE DB, where ADO (ActiveX Data Objects) provides an automation layer that exposes an easy programming model. ADO.NET provides a similar programming model, but without the automation layer, for better performance.

Oracle Data Provider for .NET uses Oracle native APIs to offer fast and reliable access to Oracle data and features from any .NET application.

The ODP.NET classes described in this guide are contained in the `Oracle.DataAccess.dll` assembly.

- Client Applications: All ODP.NET classes are available for use in client applications.
- .NET Stored Procedures: Most ODP.NET classes can be used from within .NET stored procedures and functions. Those classes which cannot, are labeled *Not Supported in a .NET Stored Procedure*. Additionally, some classes contain members which may not be supported, and this is so indicated in the member tables that follow the class descriptions, and listed in Chapter 4 of this guide.

### See Also:

- [Table 4–1, "API Support Comparison Between Client Application and .NET Stored Procedure"](#)
- ["Oracle Data Provider for .NET Assembly"](#) on page 1-3 for class lists
- [Chapter 4, "Oracle Data Provider for .NET Server-Side Features"](#)
- *Oracle Database Extensions for .NET Developer's Guide* for more information about .NET stored procedures and functions

## Oracle Data Provider for .NET Assembly

The `Oracle.DataAccess.dll` [assembly](#) provides two namespaces:

- The `Oracle.DataAccess.Client` namespace contains ODP.NET classes and enumerations for the client-side provider.
- The `Oracle.DataAccess.Types` namespace contains the Oracle Data Provider for .NET data types (ODP.NET Types).

## Oracle.DataAccess.Client Namespace

The `Oracle.DataAccess.Client` namespace contains implementations of core ADO.NET classes and enumerations for ODP.NET, as well as ODP.NET specific classes.

The following tables list ODP.NET classes, enumerations, and types that are supported by the `Oracle.DataAccess.Client` namespace. The tables also indicated which classes are not supported in .NET stored procedures.

### Oracle.DataAccess.Client

Table 1–1 lists the client classes.

**Table 1–1 Oracle.DataAccess.Client**

Class	Description
<a href="#">OnChangeEventHandler Delegate</a>	The <code>OnChangedEventHandler</code> event delegate represents the signature of the method that handles the notification. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleAQAgent Class</a>	The <code>OracleAQAgent</code> class represents agents that may be senders or recipients of a message.
<a href="#">OracleAQDequeueOptions Class</a>	An <code>OracleAQDequeueOptions</code> object represents the options available when dequeuing a message from an <code>OracleAQQueue</code> object.
<a href="#">OracleAQEnqueueOptions Class</a>	The <code>OracleAQEnqueueOptions</code> class represents the options available when enqueueing a message to an <code>OracleAQQueue</code> .
<a href="#">OracleAQMessage Class</a>	An <code>OracleAQMessage</code> object represents a message to be enqueued and dequeued.
<a href="#">OracleAQMessageAvailableEventArgs Class</a>	The <code>OracleAQMessageAvailableEventArgs</code> class provides event data for the <code>OracleAQQueue.MessageAvailable</code> event.
<a href="#">OracleAQMessageAvailableEventHandler Delegate</a>	The <code>OracleAQMessageAvailableEventHandler</code> delegate represents the signature of the method that handles the <code>OracleAQQueue.MessageAvailable</code> event.
<a href="#">OracleAQQueue Class</a>	An <code>OracleAQQueue</code> object represents a queue.
<a href="#">OracleBulkCopy Class</a>	An <code>OracleBulkCopy</code> object efficiently bulk loads or copies data into an Oracle table from another data source.
<a href="#">OracleBulkCopyColumnMapping Class</a>	The <code>OracleBulkCopyColumnMapping</code> class defines the mapping between a column in the data source and a column in the destination database table.
<a href="#">OracleBulkCopyColumnMappingCollection Class</a>	The <code>OracleBulkCopyColumnMappingCollection</code> class represents a collection of <code>OracleBulkCopyColumnMapping</code> objects that are used to map columns in the data source to columns in a destination table.

**Table 1–1 (Cont.) Oracle.DataAccess.Client**

<b>Class</b>	<b>Description</b>
<a href="#">OracleClientFactory Class</a>	An <code>OracleClientFactory</code> object allows applications to instantiate ODP.NET classes in a generic way.
<a href="#">OracleCommand Class</a>	An <code>OracleCommand</code> object represents a SQL command, a stored procedure or function, or a table name.
<a href="#">OracleCommandBuilder Class</a>	An <code>OracleCommandBuilder</code> object provides automatic SQL generation for the <code>OracleDataAdapter</code> when the database is updated.
<a href="#">OracleConnection Class</a>	An <code>OracleConnection</code> object represents a connection to Oracle Database.
<a href="#">OracleConnectionStringBuilder Class</a>	An <code>OracleConnectionStringBuilder</code> object allows applications to create or modify connection strings.
<a href="#">OracleDataAdapter Class</a>	An <code>OracleDataAdapter</code> object represents a data provider object that communicates with the <code>DataSet</code> .
<a href="#">OracleDataReader Class</a>	An <code>OracleDataReader</code> object represents a forward-only, read-only, in-memory result set.
<a href="#">OracleDataSourceEnumerator Class</a>	An <code>OracleDataSourceEnumerator</code> object allows applications to generically obtain a collection of data sources to connect to.
<a href="#">OracleDependency Class</a>	An <code>OracleDependency</code> class represents a dependency between an application and an Oracle database. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleError Class</a>	The <code>OracleError</code> object represents an error reported by an Oracle database.
<a href="#">OracleErrorCollection Class</a>	An <code>OracleErrorCollection</code> object represents a collection of <code>OracleErrors</code> .
<a href="#">OracleException Class</a>	The <code>OracleException</code> object represents an exception that is thrown when Oracle Data Provider for .NET encounters an error.
<a href="#">OracleFailoverEventArgs Class</a>	The <code>OracleFailoverEventArgs</code> class provides event data for the <code>OracleConnection.Failover</code> event. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleFailoverEventHandler Delegate</a>	The <code>OracleFailoverEventHandler</code> represents the signature of the method that handles the <code>OracleConnection.Failover</code> event. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleGlobalization Class</a>	The <code>OracleGlobalization</code> class is used to obtain and set the Oracle globalization settings of the session, thread, and local computer (read-only).
<a href="#">OracleHAEEventArgs Class</a>	The <code>OracleHAEEventArgs</code> class provides event data for the <code>OracleConnection.HAEvent</code> event.

**Table 1–1 (Cont.) Oracle.DataAccess.Client**

<b>Class</b>	<b>Description</b>
<a href="#">OracleHAEventHandler Delegate</a>	The <code>OracleHAEventHandler</code> delegate represents the signature of the method that handles the <code>OracleConnection.HAEvent</code> event.
<a href="#">OracleInfoMessageEventArgs Class</a>	The <code>OracleInfoMessageEventArgs</code> object provides event data for the <code>OracleConnection.InfoMessage</code> event.
<a href="#">OracleInfoMessageEventHandler Delegate</a>	The <code>OracleInfoMessageEventHandler</code> delegate represents the signature of the method that handles the <code>OracleConnection.InfoMessage</code> event.
<a href="#">OracleNotificationEventArgs Class</a>	The <code>OracleNotificationEventArgs</code> class provides event data for a notification.
<a href="#">OracleNotificationRequest Class</a>	An <code>OracleNotificationRequest</code> class represents a notification request to be subscribed in the database. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleParameter Class</a>	An <code>OracleParameter</code> object represents a parameter for an <code>OracleCommand</code> .
<a href="#">OracleParameterCollection Class</a>	An <code>OracleParameterCollection</code> object represents a collection of <code>OracleParameters</code> .
<a href="#">OraclePermission Class</a>	An <code>OraclePermission</code> object enables ODP.NET to enforce imperative security and helps ensure that a user has a security level adequate for accessing data.
<a href="#">OraclePermissionAttribute Class</a>	An <code>OraclePermissionAttribute</code> object enables ODP.NET to enforce declarative security and helps ensure that a user has a security level adequate for accessing data.
<a href="#">OracleRowsCopiedEventHandler Delegate</a>	The <code>OracleRowsCopiedEventHandler</code> delegate represents the method that handles the <code>OracleRowsCopied</code> event of an <code>OracleBulkCopy</code> object.
<a href="#">OracleRowsCopiedEventArgs Class</a>	The <code>OracleRowsCopiedEventArgs</code> class represents the set of arguments passed as part of event data for the <code>OracleRowsCopied</code> event.
<a href="#">OracleRowUpdatedEventArgs Class</a>	The <code>OracleRowUpdatedEventArgs</code> object provides event data for the <code>OracleDataAdapter.RowUpdated</code> event.
<a href="#">OracleRowUpdatedEventHandler Delegate</a>	The <code>OracleRowUpdatedEventHandler</code> delegate represents the signature of the method that handles the <code>OracleDataAdapter.RowUpdated</code> event.
<a href="#">OracleRowUpdatingEventArgs Class</a>	The <code>OracleRowUpdatingEventArgs</code> object provides event data for the <code>OracleDataAdapter.RowUpdating</code> event.
<a href="#">OracleRowUpdatingEventHandler Delegate</a>	The <code>OracleRowUpdatingEventHandler</code> delegate represents the signature of the method that handles the <code>OracleDataAdapter.RowUpdating</code> event.



**Table 1–1 (Cont.) Oracle.DataAccess.Client**

<b>Class</b>	<b>Description</b>
OracleTransaction Class	An OracleTransaction object represents a local transaction. <i>Not Supported in a .NET Stored Procedure</i>
OracleXmlQueryProperties Class	An OracleXmlQueryProperties object represents the XML properties used by the OracleCommand class when the XmlCommandType property is Query.
OracleXmlSaveProperties Class	An OracleXmlSaveProperties object represents the XML properties used by the OracleCommand class when the XmlCommandType property is Insert, Update, or Delete.

**Oracle.DataAccess.Client Enumerations**

Table 1–2 lists the client enumerations.

**Table 1–2 Oracle.DataAccess.Client Enumerations**

<b>Enumeration</b>	<b>Description</b>
FailoverEvent Enumeration	FailoverEvent enumerated values are used to specify the state of the failover. <i>Not Supported in a .NET Stored Procedure</i>
FailoverReturnCode Enumeration	FailoverReturnCode enumerated values are passed back by the application to the ODP.NET provider to request a retry in case of a failover error, or to continue in case of a successful failover. <i>Not Supported in a .NET Stored Procedure</i>
FailoverType Enumeration	FailoverType enumerated values are used to indicate the type of failover event that was raised. <i>Not Supported in a .NET Stored Procedure</i>
OracleAQDequeueMode Enumeration	The OracleAQDequeueMode enumeration type specifies the dequeue mode.
OracleAQMessageDeliveryMode Enumeration	The OracleAQMessageDeliveryMode enumeration type specifies the delivery mode of the message.
OracleAQMessageState Enumeration	The OracleAQMessageState enumeration type identifies the state of the message at the time of dequeue.
OracleAQMessageType Enumeration	The OracleAQMessageType enumeration type specifies the message payload type.
OracleAQNavigationMode Enumeration	The OracleAQNavigationMode enumeration type specifies the navigation mode.
OracleAQNotificationGroupingType Enumeration	The OracleAQNotificationGroupingType enumeration type specifies the notification grouping type.

**Table 1–2 (Cont.) Oracle.DataAccess.Client Enumerations**

<b>Enumeration</b>	<b>Description</b>
<a href="#">OracleAQNotificationType Enumeration</a>	The <code>OracleAQNotificationType</code> enumeration type specifies the notification type of the received notification.
<a href="#">OracleAQVisibilityMode Enumeration</a>	The <code>OracleAQVisibilityMode</code> enumeration type specifies whether the enqueue or dequeue operation is part of the current transaction.
<a href="#">OracleBulkCopyOptions Enumeration</a>	The <code>OracleBulkCopyOptions</code> enumeration specifies the values that can be combined with an instance of the <code>OracleBulkCopy</code> class and used as options to determine its behavior and the behavior of the <code>WriteToServer</code> methods for that instance.
<a href="#">OracleCollectionType Enumeration</a>	<code>OracleCollectionType</code> enumerated values specify whether or not the <code>OracleParameter</code> object represents a collection, and if so, specifies the collection type. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleDBShutdownMode Enumeration</a>	<code>OracleDBShutdownMode</code> enumerated values specify the database shutdown options.
<a href="#">OracleDBStartupMode Enumeration</a>	<code>OracleDBStartupMode</code> enumerated values specify the database startup options.
<a href="#">OracleDbType Enumeration</a>	<code>OracleDbType</code> enumerated values are used to explicitly specify the <code>OracleDbType</code> of an <code>OracleParameter</code> .
<a href="#">OracleHAEventSource Enumeration</a>	The <code>OracleHAEventSource</code> enumeration indicates the source of the HA event.
<a href="#">OracleHAEventStatus Enumeration</a>	The <code>OracleHAEventStatus</code> enumeration indicates the status of the HA event source.
<a href="#">OracleNotificationInfo Enumeration</a>	<code>OracleNotificationInfo</code> enumerated values specify the database event that causes the notification. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleNotificationSource Enumeration</a>	<code>OracleNotificationSource</code> enumerated values specify the different sources that cause notification. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleNotificationType Enumeration</a>	<code>OracleNotificationType</code> enumerated values specify the different types that cause the notification. <i>Not Supported in a .NET Stored Procedure</i>
<a href="#">OracleParameterStatus Enumeration</a>	The <code>OracleParameterStatus</code> enumeration type indicates whether a NULL value is fetched from a column, or truncation has occurred during the fetch, or a NULL value is to be inserted into a database column.
<a href="#">OracleRowidInfo Enumeration</a>	The <code>OracleRowidInfo</code> enumeration values specify whether ROWID information is included as part of the <code>ChangeNotificationEventArgs</code> or not

**Table 1–2 (Cont.) Oracle.DataAccess.Client Enumerations**

Enumeration	Description
<a href="#">OracleXmlCommandType Enumeration</a>	The <code>OracleXmlCommandType</code> enumeration specifies the values that are allowed for the <code>OracleXmlCommandType</code> property of the <code>OracleCommand</code> class.

## Oracle.DataAccess.Types Namespace

The `Oracle.DataAccess.Types` namespace provides classes, structures, and exceptions for Oracle native types that can be used with Oracle Data Provider for .NET.

### Oracle.DataAccess.Types Structures

Table 1–3 lists the type structures.

**Table 1–3 Oracle.DataAccess.Types Structures**

Structure	Description
<a href="#">OracleBinary Structure</a>	The <code>OracleBinary</code> structure represents a variable-length stream of binary data.
<a href="#">OracleDate Structure</a>	The <code>OracleDate</code> structure represents the Oracle <code>DATE</code> data type.
<a href="#">OracleDecimal Structure</a>	The <code>OracleDecimal</code> structure represents an Oracle <code>NUMBER</code> in the database or any Oracle numeric value.
<a href="#">OracleIntervalDS Structure</a>	The <code>OracleIntervalDS</code> structure represents the Oracle <code>INTERVAL DAY TO SECOND</code> data type.
<a href="#">OracleIntervalYM Structure</a>	The <code>OracleIntervalYM</code> structure represents the Oracle <code>INTERVAL YEAR TO MONTH</code> data type.
<a href="#">OracleString Structure</a>	The <code>OracleString</code> structure represents a variable-length stream of characters.
<a href="#">OracleTimeStamp Structure</a>	The <code>OracleTimeStamp</code> structure represents the Oracle <code>TimeStamp</code> data type.
<a href="#">OracleTimeStampLTZ Structure</a>	The <code>OracleTimeStampLTZ</code> structure represents the Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> data type.
<a href="#">OracleTimeStampTZ Structure</a>	The <code>OracleTimeStampTZ</code> structure represents the Oracle <code>TIMESTAMP WITH TIME ZONE</code> data type.

### Oracle.DataAccess.Types Exceptions

Type Exceptions are thrown only by ODP.NET type structures. Table 1–4 lists the type exceptions.

**Table 1–4 Oracle.DataAccess.Types Exceptions**

Exception	Description
<a href="#">OracleTypeException Class</a>	The <code>OracleTypeException</code> object is the base exception class for handling exceptions that occur in the ODP.NET Types classes.
<a href="#">OracleNullValueException Class</a>	The <code>OracleNullValueException</code> represents an exception that is thrown when trying to access an ODP.NET Types structure that is null.

**Table 1–4 (Cont.) Oracle.DataAccess.Types Exceptions**

Exception	Description
<a href="#">OracleTruncateException Class</a>	The <code>OracleTruncateException</code> class represents an exception that is thrown when truncation in an ODP.NET Types class occurs.

## Oracle.DataAccess.Types Classes

Table 1–5 lists the type classes.

**Table 1–5 Oracle.DataAccess.Types Classes**

Class	Description
<a href="#">OracleArrayMappingAttribute Class</a>	The <code>OracleArrayMappingAttribute</code> class is required to mark a custom class field or property with information that ODP.NET uses when a custom type represents an Oracle Collection type.
<a href="#">OracleBFile Class</a>	An <code>OracleBFile</code> is an object that has a reference to BFILE data. It provides methods for performing operations on BFILE objects.
<a href="#">OracleBlob Class</a>	An <code>OracleBlob</code> object is an object that has a reference to BLOB data. It provides methods for performing operations on BLOB objects.
<a href="#">OracleClob Class</a>	An <code>OracleClob</code> is an object that has a reference to CLOB data. It provides methods for performing operations on CLOB objects.
<a href="#">OracleCustomTypeMappingAttribute Class</a>	The <code>OracleCustomTypeMappingAttribute</code> class is used to mark a custom type factory class or struct with information that is used by ODP.NET when a custom type is used to represent an Oracle UDT.
<a href="#">OracleObjectMappingAttribute Class</a>	The <code>OracleObjectMappingAttribute</code> class marks custom class fields or properties with information that ODP.NET uses when a custom type represents an Oracle Object type.
<a href="#">OracleRef Class</a>	An <code>OracleRef</code> instance represents an Oracle REF, which references a persistent, standalone, referenceable object that resides in the database. The <code>OracleRef</code> object provides methods to insert, update, and delete the Oracle REF.
<a href="#">OracleRefCursor Class</a>	An <code>OracleRefCursor</code> object represents an Oracle REF CURSOR.
<a href="#">OracleUdt Class</a>	The <code>OracleUdt</code> class defines static methods that are used when converting between Custom Types and Oracle UDTs and vice-versa.
<a href="#">OracleXmlStream Class</a>	An <code>OracleXmlStream</code> object represents a sequential read-only stream of XML data stored in an <code>OracleXmlType</code> object.
<a href="#">OracleXmlType Class</a>	An <code>OracleXmlType</code> object represents an Oracle <code>XmlType</code> instance.

## Oracle.DataAccess.Types Interfaces

Table 1–6 lists the type interfaces.

**Table 1–6 Oracle.DataAccess.Types Interfaces**

Interface	Description
<a href="#">IOracleArrayTypeFactory Interface</a>	The IOracleArrayTypeFactory interface is used by ODP.NET to create arrays that represent Oracle Collections.
<a href="#">IOracleCustomType Interface</a>	IOracleCustomType is an interface for converting between a Custom Type and an Oracle Object or Collection Type.
<a href="#">IOracleCustomTypeFactory Interface</a>	The IOracleCustomTypeFactory interface is used by ODP.NET to create custom objects that represent Oracle Objects or Collections.
<a href="#">INullable Interface</a>	The INullable interface is used to determine whether or not an ODP.NET type has a NULL value.

### Oracle.DataAccess.Types Enumerations

Table 1–7 lists the type enumerations.

**Table 1–7 Oracle.DataAccess.Types Enumerations**

Enumeration	Description
<a href="#">OracleUdtFetchOption Enumeration</a>	OracleUdtFetchOption enumeration values specify how to retrieve a copy of the referenceable object.
<a href="#">OracleUdtStatus Enumeration</a>	OracleUdtStatus enumeration values specify the status of an object attribute or collection element. An object attribute or a collection element can be a valid value or a null value.

## Using ODP.NET Client Provider in a Simple Application

The following is a simple C# application that connects to Oracle Database and displays its version number before disconnecting:

```
// C#

using System;
using Oracle.DataAccess.Client;

class Sample
{
    static void Main()
    {
        // Connect to Oracle
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Display Version Number
        Console.WriteLine("Connected to Oracle " + con.ServerVersion);

        // Close and Dispose OracleConnection
        con.Close();
        con.Dispose();
    }
}
```

---

---

**Note:** Additional samples are provided in the *ORACLE\_*  
*BASE\ORACLE\_HOME\ODP.NET\Samples* directory.

---

---

---

---

# Installing and Configuring Oracle Data Provider for .NET

This chapter describes installation and configuration requirements for Oracle Data Provider for .NET.

This chapter contains these topics:

- [System Requirements](#)
- [Installing Oracle Data Provider for .NET](#)
- [Performance Counters](#)
- [Configuring a Port to Listen for Database Notifications](#)
- [General .NET Programming Recommendations and Tips for ODP.NET](#)

## System Requirements

Oracle Data Provider for .NET requires the following:

- Windows operating system
  - 32-bit: Windows 7 (Professional, Enterprise, and Ultimate Editions), Windows Vista (Business, Enterprise, and Ultimate Editions), Windows Server 2008 (Standard, Enterprise, Datacenter, Web, and Foundation Editions), Windows Server 2003 R2 (all editions), Windows Server 2003 (all editions), or Windows XP Professional Edition.

Oracle supports 32-bit ODP.NET on x86, AMD64, and Intel EM64T processors on these operating systems.

- 64-bit: Windows 7 x64 (Professional, Enterprise, and Ultimate Editions), Windows Vista x64 (Business, Enterprise, and Ultimate Editions), Windows Server 2008 R2 x64 (Standard, Enterprise, Datacenter, Web, and Foundation Editions), Windows Server 2008 x64 (Standard, Enterprise, Datacenter, Web, and Foundation Editions), Windows Server 2003 x64 (all editions), Windows Server 2003 R2 x64 (all editions), or Windows XP x64.

Oracle supports 32-bit ODP.NET and 64-bit ODP.NET for Windows x64 on these operating systems.

---

---

**Note:** ODP.NET does not support Itanium systems.

---

---

- Microsoft .NET Framework 2.0 or later

- Access to Oracle9i Database Release 2 or later
- Oracle Client release 11.2 and later

Additional requirements are the following:

- Applications using distributed transactions require Oracle Services for Microsoft Transaction Server release 11.2.
- Applications using `OracleXmlStream` and `OracleXmlType` classes with schema-based `XMLType` require access to Oracle Database 10g release 1 (10.1) or later.

**See Also:**

- <http://msdn.microsoft.com/netframework>
- <http://otn.oracle.com/tech/xml/xdkhome.html> to download the Oracle XML Developer's Kit (XDK)

## Installing Oracle Data Provider for .NET

Oracle Data Provider for .NET is part of Oracle Data Access Components (ODAC), which can be downloaded from OTN. Beginning with ODAC 11.1.0.6.20, Oracle Data Provider for .NET can be installed through XCopy or Oracle Universal Installer.

- XCopy

Administrators use XCopy to deploy Oracle Data Provider for .NET to large numbers of computers for production deployments. The XCopy has a smaller installation size and fine grain control during installation and configuration than Oracle Universal Installer.

- Oracle Universal Installer (OUI)

Developers and administrators use Oracle Universal Installer for automated ODP.NET installations. It includes documentation and code samples that are not part of the XCopy.

---

---

**Note:** This section describes installation using the Oracle Universal Installer. For installation and configuration using the XCopy install, refer to the README.TXT file that is part of the XCopy installation.

---

---

Additionally, Oracle Data Provider for .NET Dynamic Help is registered with Visual Studio, providing context-sensitive online help that is seamlessly integrated with Visual Studio Dynamic Help. With Dynamic Help, the user can access ODP.NET documentation within the Visual Studio IDE by placing the cursor on an ODP.NET keyword and pressing the F1 function key.

Oracle Data Provider for .NET creates an entry in the `machine.config` file of the computer on which it is installed, for applications using ADO.NET 2.0 and `OracleClientFactory` class. This enables the `DbProviderFactories` class to recognize ODP.NET.

**See Also:** *Oracle Database Installation Guide for Windows* for installation instructions

## File Locations After Installation

The `Oracle.DataAccess.dll` assembly is installed as follows:



.NET Framework 2.0 and higher:

`ORACLE_BASE\ORACLE_HOME\odp.net\bin\2.x` directory

Documentation and the `readme.txt` file are installed in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\doc` directory.

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples` directory.

## Windows Registry

Upon installation, ODP.NET creates entries for configuration and tracing within the Windows Registry. Configuration and tracing registry values apply across all ODP.NET applications running in that Oracle client installation. Individual ODP.NET applications can override some of these values by configuring them within the ODP.NET application itself (for example, `FetchSize`). Applications can also use the .NET configuration files to override some of the ODP.NET Windows Registry values.

The ODP.NET registry values are located under `HKEY_LOCAL_MACHINE\Software\Oracle\ODP.NET\version\`.

---

**Note:** 32-bit applications running on an x64-based version of Windows use the registry subkey, `HKEY_LOCAL_MACHINE\Software\WOW6432node` in place of `HKEY_LOCAL_MACHINE\Software`. If such applications use Oracle Data Provider for .NET (32-bit), then the ODP.NET registry values are located under `HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Oracle\ODP.NET\version\`.

---

## Configuration File Support

For customers who have numerous applications on a computer that depends on a single version of ODP.NET, the Windows Registry settings for a given version of ODP.NET may not necessarily be applicable for all applications that use that version of ODP.NET. To provide more granular control, ODP.NET Configuration File Support allows developers to specify ODP.NET configuration settings in an application `config`, `web.config`, or a `machine.config` file.

If a computer does not require granular control beyond configuration settings at the ODP.NET version level, there is no need to specify ODP.NET configuration settings through configuration files.

The following is an example of a `web.config` file for .NET Framework 2.0 and higher:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DllPath" value="C:\oracle\bin"/>
      <add name="FetchSize" value="131072"/>
      <add name="PromotableTransaction" value="promotable"/>
      <add name="StatementCacheSize" value="10"/>
      <add name="TraceFileName" value="C:\odpnet2.trc"/>
      <add name="TraceLevel" value="63"/>
      <add name="TraceOption" value="1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

```
</oracle.dataaccess.client>  
</configuration>
```

## Search Order for Unmanaged DLLs

ODP.NET consists of managed and unmanaged binaries. Through the use of the `DllPath` configuration parameter, each application can specify the `ORACLE_BASE\ORACLE_HOME\bin` location that the dependent unmanaged Oracle Client binaries are loaded from. However, the `ORACLE_BASE\ORACLE_HOME` must have the same ODP.NET version installed as the version that the application uses. Otherwise, a version mismatch exception is thrown.

The `Oracle.DataAccess.dll` searches for dependent unmanaged DLLs (such as Oracle Client) based on the following order:

1. Directory of the application or executable.
2. `DllPath` setting specified by application config or `web.config`.
3. `DllPath` setting specified by `machine.config`.
4. `DllPath` setting specified by the Windows Registry.

```
HKEY_LOCAL_MACHINE\Software\Oracle\ODP.NET\version\DllPath
```

5. Directories specified by the Windows `PATH` environment variable.

Upon installation of ODP.NET, Oracle Universal Installer sets the `DllPath` Windows Registry value to the `ORACLE_BASE\ORACLE_HOME\bin` directory where the corresponding dependent DLLs are installed. Developers must provide this configuration information on an application-by-application basis.

When a new ODP.NET version is installed, default values are set in the Windows Registry for the new version. Because the policy DLLs redirect all ODP.NET references to this new ODP.NET version, applications use the default values. Developers can provide a config or `web.config` file specific to the application to prevent this redirection. The configuration file settings always apply to the application, regardless of whether or not patches or new versions are installed later.

ODP.NET Configuration File Support is only available for version 10.2.0.4 and later.

## ODP.NET and Dependent Unmanaged DLL Mismatch

To enforce the usage of `Oracle.DataAccess.dll` assembly with the correct version of its unmanaged DLLs, an exception is raised if `Oracle.DataAccess.dll` notices it has loaded a mismatched version of a dependent unmanaged DLL.

## Performance Counters

Installing Oracle Data Provider for .NET creates a set of performance counters on the target system. These performance counters are published by ODP.NET for each ODP.NET client application. These performance counters can be viewed using Windows Performance Monitor (Perfmon).

ODP.NET performance counters are published under the following Category Name: Oracle Data Provider for .NET.

**See Also:** ["Connection Pool Performance Counters"](#) on page 3-7

## Configuring a Port to Listen for Database Notifications

Oracle Data Provider for .NET opens a port to listen for database notifications when the following features are used:

- HA Events
- Load Balancing
- Database change notification
- AQ Notifications

All these features share the same port, which can be configured centrally by setting the `db notifications` port in an application or web configuration file.

If the configuration file does not exist or the `db notification` port is not specified, ODP.NET uses a valid, random port number. The configuration file may also request for a random port by specifying a `db notification` port value of `-1`. To specify a particular port, for example, `1200`, an application or web configuration file can be used as shown below.

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="1200"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

The port number should be unique for each process running on a computer. Thus, the port number should be set uniquely for each application either programmatically or through an application config file. Note that if the specified port number is already in use, ODP.NET does not provide any errors. For details on configuring ODP.NET, see "[ODP.NET Configuration](#)" on page 3-114.

When the process using ODP.NET starts, the application reads the `db notification` port number and listens on that port. Once the port is opened, the port number cannot be changed during the lifetime of the process.

### See Also:

- "[HA Events](#)" on page 3-10
- "[Runtime Connection Load Balancing](#)" on page 3-9
- "[Database Change Notification Support](#)" on page 3-97
- "[Oracle Streams Advanced Queuing Support](#)" on page 3-92

## General .NET Programming Recommendations and Tips for ODP.NET

- `Thread.Abort()` should not be used, as unmanaged resources may remain unreleased, which can potentially cause memory leaks and hangs.
- To optimize resource usage, ODP.NET objects, such as `OracleConnection` and `OracleCommand`, should be explicitly closed or disposed, or both, when they are no longer needed. This should be done rather than relying on the .NET Framework garbage collector to reclaim resources. Many users have found that under stress conditions, explicit `Close` or `Dispose` calls result in much lower resource usage.



---

---

## Features of Oracle Data Provider for .NET

This chapter describes Oracle Data Provider for .NET provider-specific features and how to use them to develop .NET applications.

This chapter contains these topics:

- [Connecting to Oracle Database](#)
- [ADO.NET 2.0 Features](#)
- [OracleCommand Object](#)
- [ODP.NET Types Overview](#)
- [Obtaining Data from an OracleDataReader Object](#)
- [PL/SQL REF CURSOR and OracleRefCursor](#)
- [LOB Support](#)
- [ODP.NET XML Support](#)
- [Oracle User-Defined Types \(UDTs\) and .NET Custom Types](#)
- [Oracle Streams Advanced Queuing Support](#)
- [Database Change Notification Support](#)
- [OracleDataAdapter Safe Type Mapping](#)
- [OracleDataAdapter Requery Property](#)
- [Guaranteeing Uniqueness in Updating DataSet to Database](#)
- [Globalization Support](#)
- [Debug Tracing](#)
- [ODP.NET Configuration](#)

### Connecting to Oracle Database

This section describes `OracleConnection` provider-specific features, including:

- [Connection String Attributes](#)
- [Connection Pooling](#)
- [Connection Pool Management](#)
- [Connection Pool Performance Counters](#)
- [Connecting to an Oracle Real Application Clusters \(RAC\) Database](#)

- [Operating System Authentication](#)
- [Privileged Connections](#)
- [Password Expiration](#)
- [Proxy Authentication](#)
- [Dynamic Distributed Transaction Enlistment](#)
- [Client Identifier and End-to-End Tracing](#)
- [Transparent Application Failover \(TAF\) Callback Support](#)

## Connection String Attributes

Table 3–1 lists the supported connection string attributes.

**Table 3–1 Supported Connection String Attributes**

Connection String Attribute	Description	Default Value
Connection Lifetime	Maximum life time (in seconds) of the connection.	0
Connection Timeout	Maximum time (in seconds) to wait for a free connection from the pool.	15
Context Connection	Returns an implicit database connection if set to true. <i>Supported in a .NET stored procedure only</i>	false
Data Source	Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.	empty string
DBA Privilege	Administrative privileges: SYSDBA or SYSOPER.	empty string
Decr Pool Size	Number of connections that are closed when an excessive amount of established connections are unused.	1
Enlist	Controls the enlistment behavior and capabilities of a connection in context of COM+ transactions or System.Transactions.	true
HA Events	Enables ODP.NET connection pool to proactively remove connections from the pool when an Oracle RAC service, service member, database, or node goes down. Works with RAC, Data Guard, or a single database instance.	false
Load Balancing	Enables ODP.NET connection pool to balance work requests across Oracle RAC instances based on the load balancing advisory and service goal.	false
Incr Pool Size	Number of new connections to be created when all connections in the pool are in use.	5
Max Pool Size	Maximum number of connections in a pool.	100

**Table 3–1 (Cont.) Supported Connection String Attributes**

Connection String Attribute	Description	Default Value
Metadata Pooling	Caches metadata information.	True
Min Pool Size	Minimum number of connections in a pool.	1
Password	Password for the user specified by User Id.	empty string
Persist Security Info	Retrieval of the password in the connection string.	false
Pooling	Connection pooling.	true
Promotable Transaction	Indicates whether or not a transaction is local or distributed throughout its lifetime.	promotable
Proxy User Id	User name of the proxy user.	empty string
Proxy Password	Password of the proxy user.	empty string
Self Tuning	Enables or disables self-tuning for a connection.	true
Statement Cache Purge	Statement cache purged when the connection goes back to the pool.	false
Statement Cache Size	Statement cache enabled and cache size, that is, the maximum number of statements that can be cached.	0
User Id	Oracle user name.	empty string
Validate Connection	Validation of connections coming from the pool.	false

The following example uses connection string attributes to connect to Oracle Database:

```
// C#

using System;
using Oracle.DataAccess.Client;

class ConnectionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //using connection string attributes to connect to Oracle Database
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```

**See Also:**

- ["OracleConnection Properties"](#) on page 5-76 for detailed information on connection attributes
- ["OracleCommand Object"](#) on page 3-30 for detailed information on statement caching

## Specifying the Data Source Attribute

This section describes different ways of specifying the data source attribute.

The following example shows a connect descriptor mapped to a TNS alias called `sales` in the `tnsnames.ora` file:

```
sales=
  (DESCRIPTION=
    (ADDRESS= (PROTOCOL=tcp) (HOST=sales-server) (PORT=1521))
    (CONNECT_DATA=
      (SERVICE_NAME=sales.us.acme.com)))
```

### Using the TNS Alias

To connect as `scott/tiger` using the TNS Alias, a valid connection appears as follows:

```
"user id=scott;password=tiger;data source=sales";
```

### Using the Connect Descriptor

ODP.NET also allows applications to connect without the use of the `tnsnames.ora` file. To do so, the entire connect descriptor can be used as the "data source".

The connection string appears as follows:

```
"user id=scott;password=tiger;data source=" +
  "(DESCRIPTION=(ADDRESS=(PROTOCOL=tcp) " +
  "(HOST=sales-server) (PORT=1521)) (CONNECT_DATA="+
  "(SERVICE_NAME=sales.us.acme.com)))"
```

### Using Easy Connect Naming Method

The easy connect naming method enables clients to connect to a database without any configuration.

Prior to using the easy connect naming method, make sure that `EZCONNECT` is specified by the `NAMES.DIRECTORY_PATH` parameter in the `sqlnet.ora` file as follows:

```
NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT)
```

With this enabled, ODP.NET allows applications to specify the "Data Source" attribute in the form of:

```
//host:[port]/[service_name]
```

Using the same example, some valid connection strings follow:

```
"user id=scott;password=tiger;data source=//sales-server:1521/sales.us.acme.com"
"user id=scott;password=tiger;data source=//sales-server/sales.us.acme.com"
"user id=scott;password=tiger;data source=sales-server/sales.us.acme.com"
```



If the port number is not specified, 1521 is used by default.

**See Also:** *Oracle Net Services Administrator's Guide* for details and requirements in the section Using Easy Connect Naming Method

## Connection Pooling

ODP.NET connection pooling is enabled and disabled using the `Pooling` connection string attribute. By default, connection pooling is enabled. The following are `ConnectionString` attributes that control the behavior of the connection pooling service:

- `Connection Lifetime`
- `Connection Timeout`
- `Decr Pool Size`
- `HA Events`
- `Incr Pool Size`
- `Load Balancing`
- `Max Pool Size`
- `Min Pool Size`
- `Pooling`
- `Validate Connection`

### Connection Pooling Example

The following example opens a connection using `ConnectionString` attributes related to connection pooling.

```
// C#

using System;
using Oracle.DataAccess.Client;

class ConnectionPoolingSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Open a connection using ConnectionString attributes
        //related to connection pooling.
        con.ConnectionString =
            "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min Pool Size=10;Connection Lifetime=120;Connection Timeout=60;" +
            "Incr Pool Size=5; Decr Pool Size=2";
        con.Open();
        Console.WriteLine("Connection pool successfully created");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Connection is placed back into the pool.");
    }
}
```

}

## Using Connection Pooling

When connection pooling is enabled (the default), the `Open` and `Close` methods of the `OracleConnection` object implicitly use the connection pooling service, which is responsible for pooling and returning connections to the application.

The connection pooling service creates connection pools by using the `ConnectionString` property as a signature, to uniquely identify a pool.

If there is no existing pool with the exact attribute values as the `ConnectionString` property, the connection pooling service creates a new connection pool. If a pool already exists with the requested signature, a connection is returned to the application from that pool.

When a connection pool is created, the connection pooling service initially creates the number of connections defined by the `Min Pool Size` attribute of the `ConnectionString` property. This number of connections is always maintained by the connection pooling service for the connection pool.

At any given time, these connections are in use by the application or are available in the pool.

The `Incr Pool Size` attribute of the `ConnectionString` property defines the number of new connections to be created by the connection pooling service when more connections are needed in the connection pool.

When the application closes a connection, the connection pooling service determines whether or not the connection lifetime has exceeded the value of the `Connection Lifetime` attribute. If so, the connection pooling service closes the connection; otherwise, the connection goes back to the connection pool. The connection pooling service enforces the `Connection Lifetime` only when a connection is going back to the connection pool.

The `Max Pool Size` attribute of the `ConnectionString` property sets the maximum number of connections for a connection pool. If a new connection is requested, but no connections are available and the limit for `Max Pool Size` has been reached, then the connection pooling service waits for the time defined by the `Connection Timeout` attribute. If the `Connection Timeout` time has been reached, and there are still no connections available in the pool, the connection pooling service raises an exception indicating that the connection pool request has timed-out.

The `Validate Connection` attribute validates connections coming out of the pool. This attribute should be used only when absolutely necessary, because it causes a round-trip to the database to validate each connection immediately before it is provided to the application. If invalid connections are uncommon, developers can create their own event handler to retrieve and validate a new connection, rather than using the `Validate Connection` attribute. This generally provides better performance.

The connection pooling service closes connections when they are not used; connections are closed every 3 minutes. The `Decr Pool Size` attribute of the `ConnectionString` property provides connection pooling service for the maximum number of connections that can be closed every 3 minutes.

Beginning with Oracle Data Provider for .NET release 11.1.0.6.20, enabling connection pooling by setting "`pooling=true`" in the connection string (which is the case by default) will also pool operating system authenticated connections.

## Connection Pool Management

ODP.NET connection pool management provides explicit connection pool control to ODP.NET applications. Applications can explicitly clear connections in a connection pool.

Using connection pool management, applications can do the following:

---



---

**Note:** These APIs are not supported in a .NET stored procedure.

---



---

- Clear connections from connection pools using the `ClearPool` method.
- Clear connections in all the connection pools in an application domain, using the `ClearAllPools` method.

When connections are cleared from a pool, ODP.NET repopulates the pool with new connections that have at least the number of connections set by `Min Pool Size` in the connection string. New connections do not necessarily mean the pool will have valid connections. For example, if the database server is down when `ClearPool` or `ClearAllPools` is called, ODP.NET creates new connections, but these connections are still invalid because they cannot connect to the database, even if the database comes up a later time.

It is recommended that `ClearPool` and `ClearAllPools` not be called until the application can create valid connections back to the database. .NET developers can develop code that continuously checks whether or not a valid database connection can be created and calls `ClearPool` or `ClearAllPools` once this is true.

**See Also:**

- ["ClearPool"](#) on page 5-73
- ["ClearAllPools"](#) on page 5-74

## Connection Pool Performance Counters

Oracle Data Provider for .NET enables or disables publishing performance counters for connection pooling, using registry entries.

[Table 3–2](#) lists the performance counters used for connection pooling with their valid registry values.

**Table 3–2 Performance Counters for Connection Pooling**

Performance Counter	Valid Values	Description
None	0	Not enabled (Default)
HardConnectsPerSecond	1	Number of sessions being established with the Oracle Database every second.
HardDisconnectsPerSecond	2	Number of sessions being severed from the Oracle Database every second.
SoftConnectsPerSecond	4	Number of active connections originating from connection pools every second.
SoftDisconnectsPerSecond	8	Number of active connections going back to the connection pool every second.

**Table 3–2 (Cont.) Performance Counters for Connection Pooling**

Performance Counter	Valid Values	Description
NumberOfActiveConnectionPools	16	Total number of active connection pools.
NumberOfInactiveConnectionPools	32	Number of inactive connection pools.
NumberOfActiveConnections	64	Total number of connections in use.
NumberOfFreeConnections	128	Total number of connections available for use in all the connection pools.
NumberOfPooledConnections	256	Number of pooled active connections.
NumberOfNonPooledConnections	512	Number of non-pooled active connections.
NumberOfReclaimedConnections	1024	Number of connections which were garbage-collected implicitly.
NumberOfStasisConnections	2048	Number of connections that will be soon available in the pool. User has closed these connections, but they are currently awaiting actions such transaction completion before they can be placed back into the pool as free connections.

### Publishing Performance Counters

Publication of individual performance counters is enabled or disabled using the registry value `PerformanceCounters` of type `REG_SZ`. This registry value is under:

```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version
```

where `Assembly_Version` is the full assembly version number of `Oracle.DataAccess.dll`.

Multiple performance counters can be obtained by adding the valid values. For example, if `PerformanceCounters` is set to 3, both `HardConnectsPerSecond` and `HardDisconnectsPerSecond` are enabled.

### Setting Performance Counters Using app.config Entry

Performance counters can be set using an `app.config` entry. Since `app.config` entries take precedence over the registry value setting, they can be used for a specific application.

An `app.config` entry uses name/value pairs as in the following example:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="PerformanceCounters"
        value="3"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

### Instance Names of Performance Counters

Performance counters are published instance-wise, that is, for each process, different values of the performance counters are published. The instance name is based on `AppDomain` name, `AppDomain Id` and `Process Id` and displayed in the following form:

`AppDomain_Name[Process Id, AppDomain Id]`

For example, if a process named `App1.exe` uses ODP.NET 2.x in default `appdomain` and the process id is 234 then the instance name would be `App1.exe [234, 1]`.

**See Also:** ["Performance Counters"](#) on page 2-4

## Connecting to an Oracle Real Application Clusters (RAC) Database

This section discusses optimization and other aspects of connection and connection pooling for a Real Application Clusters (RAC) database. Oracle RAC is the technology that makes grids possible for Oracle database by providing the ability to access the database from multiple instances, each running on nodes in a cluster.

### Connecting in Real Application Clusters (RAC) and Data Guard Database

This section discusses optimization and other aspects of connection and connection pooling for a Real Application Clusters (RAC) and Data Guard databases. Oracle RAC is the technology that makes grids possible for Oracle database by providing the ability to access the database from multiple instances, each running on nodes in a cluster. Oracle Data Guard is a technology that enables high availability and disaster recovery by maintaining a secondary standby database in case the primary database fails.

**See Also:** [Oracle Data Guard Concepts and Administration](#)

### Connection Optimization for Oracle RAC and Oracle Data Guard

Oracle Data Provider for .NET supports Oracle RAC and Data Guard transparently. Additionally, the Oracle Data Provider for .NET connection pooling features work with RAC or Data Guard version 10.2 or higher.

Oracle Data Provider for .NET optimizes connection and connection pooling for Oracle RAC database by balancing work requests across Oracle RAC instances, based on the load balancing advisory and service goal. Furthermore, the ODP.NET connection pool can be enabled to proactively free resources associated with connections that have been severed due to a down Oracle RAC service, service member, node, or database in the case of Data Guard.

Oracle Data Provider for .NET uses the following features to optimize connection and connection pooling for Oracle RAC:

- Runtime Connection Load Balancing

When Runtime Connection Load Balancing is enabled:

- The ODP.NET connection pool dispenses connections based on the load balancing advisory and service goal.
- The ODP.NET connection pool also balances the number of connections to each service member providing the service, based on the load balancing advisory and service goal.

By default, this feature is disabled. To enable runtime connection load balancing, include `"Load Balancing=true"` in the connection string.

This feature can only be used with an Oracle RAC database and only if `"pooling=true"`. If `"Load Balancing=true"` is set and the connection attempts to connect to a non-RAC database, an `OracleException` is thrown with an error of `"ORA-1031: insufficient privileges."`

In order to use Runtime Connection Load Balancing, specific RAC configurations must be set. For further information, see *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*. Oracle Net Services should also be configured for load balancing. See *Oracle Net Services Administrator's Guide* for further details.

The following connection string example enables Runtime Connection Load Balancing:

```
"user id=scott;password=tiger;data source=erp;load balancing=true;"
```

**See Also:**

- ["Supported Connection String Attributes"](#) on page 5-79
- ["Configuring a Port to Listen for Database Notifications"](#) on page 2-5
- *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*

- HA Events

When HA (High Availability) events is enabled, Oracle RAC, Data Guard, and single database instances exhibit the following behavior:

- ODP.NET connection pool proactively removes connections from the pool when an Oracle RAC service, service member, node, or database goes down.
- ODP.NET establishes connections to existing Oracle instances if the removal of severed connections bring the total number of connections below the "min pool size".

By default this feature is disabled. To enable HA events, include "HA Events=true" and "pooling=true" in the connection string.

---

---

**Note:**

The database service being connected to must be configured for AQ\_HA\_NOTIFICATIONS. For more details, see *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*

---

---

The following connection string example enables HA Events:

```
"user id=scott;password=tiger;data source=erp;HA events=true;"
```

**See Also:**

- ["Supported Connection String Attributes"](#) on page 5-79
- ["Configuring a Port to Listen for Database Notifications"](#) on page 2-5
- *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*
- Oracle Data Guard Concepts and Administration

## Pool Size Attributes in an Oracle RAC Database

When connection pools are created for a non-RAC database, pool size attributes are applied to the single service. Similarly, when connection pools are created for an Oracle RAC database, the pool size attributes are applied to a service and not to service members. For example, if "Min Pool Size" is set to  $N$ , ODP.NET does not create  $N$  connections for each service member. Instead, it creates, at minimum,  $N$  connections for the entire service, where  $N$  connections are distributed among the service members.

The following pool size connection string attributes are applied to a service.

- Min Pool Size
- Max Pool Size
- Incr Pool Size
- Decr Pool Size

## Operating System Authentication

Oracle Database can use Windows user login credentials to authenticate database users. To open a connection using Windows user login credentials, the `User Id` connection string attribute must be set to a slash (/). If the `Password` attribute is provided, it is ignored.

---



---

**Note:** Operating System Authentication is not supported in a .NET stored procedure.

---



---

Beginning with Oracle Data Provider for .NET release 11.1.0.6.20, all connections, including those using operating system authentication, can be pooled. Connections are pooled by default, and no configuration is required, as long as pooling is enabled.

The following example shows the use of operating system authentication:

```

/* Create an OS-authenticated user in the database
   Assume init.ora has OS_AUTHENT_PREFIX set to "" and <OS_USER>
   is any valid OS or DOMAIN user.

   create user <OS_USER> identified externally;
   grant connect, resource to <OS_USER>;

   Login through OS Authentication and execute the sample. See Oracle
   documentation for details on how to configure an OS-Authenticated user
*/

// C#

using System;
using Oracle.DataAccess.Client;

class OSAuthenticationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Establish connection using OS Authentication
        con.ConnectionString = "User Id=;/;Data Source=oracle;";
    }
}

```

```
con.Open();
Console.WriteLine("Connected to Oracle" + con.ServerVersion);

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
Console.WriteLine("Disconnected");
}
}
```

**See Also:** *Oracle Database Platform Guide for Windows* for information on how to set up Oracle Database to authenticate database users using Windows user login credentials

## Privileged Connections

Oracle allows database administrators to connect to Oracle Database with either SYSDBA or SYSOPER privileges. This is done through the DBA Privilege attribute of the ConnectionString property.

The following example connects scott/tiger as SYSDBA:

```
// C#

using System;
using Oracle.DataAccess.Client;

class PrivilegedConnectionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Connect scott/tiger as SYSDBA
        con.ConnectionString = "User Id=scott;Password=tiger;" +
            "DBA Privilege=SYSDBA;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```

**See Also:** DBA Privilege "[Supported Connection String Attributes](#)" on page 5-79 for further information on privileged connections in the database

## Password Expiration

Oracle allows users passwords to expire. ODP.NET lets applications handle the password expiration by providing a new method, `OpenWithNewPassword`, that opens the connection with a new password.

The following example uses the OracleConnection `OpenWithNewPassword` method to connect with a new password of panther:

```
/* Database Setup
```



```
connect / as sysdba;
drop user testexpire cascade;
-- create user "testexpire" with password "testexpire"
grant connect , resource to testexpire identified by testexpire;
alter user testexpire password expire;
*/

// C#

using System;
using Oracle.DataAccess.Client;

class PasswordExpirationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        try
        {
            con.ConnectionString =
                "User Id=testexpire;Password=testexpire;Data Source=oracle";
            con.Open();
            Console.WriteLine("Connected to Oracle" + con.ServerVersion);
        }
        catch (OracleException ex)
        {
            Console.WriteLine(ex.Message);

            //check the error number
            //ORA-28001 : the password has expired
            if (ex.Number == 28001)
            {
                Console.WriteLine("\nChanging password to panther");
                con.OpenWithNewPassword("panther");
                Console.WriteLine("Connected with new password.");
            }
        }
        finally
        {
            // Close and Dispose OracleConnection object
            con.Close();
            con.Dispose();
            Console.WriteLine("Disconnected");
        }
    }
}
```

---

**Note:**

- The `OpenWithNewPassword` method should be used only when the user password has expired, not for changing the password.
  - If connection pooling is enabled, then invoking the `OpenWithNewPassword` method also clears the connection pool. This closes all idle connections created with the old password.
- 

**See Also:** ["OpenWithNewPassword"](#) on page 5-107

## Proxy Authentication

With proper setup in the database, proxy authentication enables middle-tier applications to control the security by preserving database user identities and privileges, and auditing actions taken on behalf of these users. This is accomplished by creating and using a proxy database user that connects and authenticates against the database on behalf of a database user (that is, the *real* user) or database users.

Proxy authentication can then be used to provide better scalability with connection pooling. When connection pooling is used in conjunction with proxy authentication, the proxy authenticated connections can be shared among different real users. This is because only the connection and session established for the proxy is cached. An additional session is created for the real user when a proxy authenticated connection is requested, but it will be destroyed appropriately when the proxy authenticated connection is placed back into the pool. This design enables the application to scale well without sacrificing security.

ODP.NET applications can use proxy authentication by setting the "Proxy User Id" and "Proxy Password" attributes in the connection string. The real user is specified by the "User Id" attribute. Optionally, to enforce greater security, the real user's password can be provided through the "Password" connection string attribute.

The following example illustrates the use of ODP.NET proxy authentication:

```
/* Log on as DBA (SYS or SYSTEM) that has CREATE USER privilege.
   Create a proxy user and modified scott to allow proxy connection.

   create user appserver identified by eagle;
   grant connect, resource to appserver;
   alter user scott grant connect through appserver;
*/

// C#

using System;
using Oracle.DataAccess.Client;

class ProxyAuthenticationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        // Connecting using proxy authentication
        con.ConnectionString = "User Id=scott;Password=tiger;" +
```

```

        "Data Source=oracle;Proxy User Id=appserver;Proxy Password=eagle; ";
con.Open();
Console.WriteLine("Connected to Oracle" + con.ServerVersion);

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
Console.WriteLine("Disconnected");
    }
}

```

**See Also:**

- *Oracle Database Advanced Application Developer's Guide* for details on designing a middle-tier server using proxy users
- *Oracle Database SQL Reference* for the description and syntax of the proxy clause for the ALTER USER statement
- *Oracle Database Security Guide* section "Standard Auditing in a Multitier Environment"

## Dynamic Distributed Transaction Enlistment

For those applications that dynamically enlist in distributed transactions through the `EnlistDistributedTransaction` of the `OracleConnection` object, the "enlist" connection string attribute must be set to a value of either "dynamic" or "true". If "enlist=true", the connection enlists in a transaction when the `Open` method is called on the `OracleConnection` object, if it is within the context of a COM+ transaction or a `System.Transactions`. If not, the `OracleConnection` object does not enlist in a distributed transaction, but it can later enlist explicitly using the `EnlistDistributedTransaction` or the `EnlistTransaction` method. If "enlist=false", the connection cannot enlist in the transaction.

For applications that cannot be rebuilt using "Enlist=dynamic", a registry string value, named `DynamicEnlistment`, of type `REG_SZ`, should be created and set to 1 under `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version` where `Assembly_Version` is the full assembly version number of `Oracle.DataAccess.dll`.

If ODP.NET is properly installed, there should already be registry string values such as `StatementCacheSize`, `TraceFileName`, and so forth, under the same ODP.NET key. Dynamic Enlistment can also be configured through an XML configuration file. For details, see "[ODP.NET Configuration](#)" on page 3-114.

If the `DynamicEnlistment` registry key is set to 0 (or if the registry entry does not exist), it does not affect the application in any way. However, if `DynamicEnlistment` is set to 1, "Enlist=false" is treated the same as "Enlist=dynamic", enabling applications to enlist successfully through the `EnlistDistributedTransaction` method without any code change. Having `DynamicEnlistment` set to 1 does not affect `OracleConnection` objects that have "Enlist=true" or "Enlist=dynamic" in the connection string.

**See Also:**

- "[Connection String Attributes](#)" on page 3-2
- "[EnlistDistributedTransaction](#)" on page 5-95

## Client Identifier and End-to-End Tracing

The client identifier is a predefined attribute from the Oracle application context namespace `USERENV`. It is similar to proxy authentication because it can enable tracking of user identities. However, client identifier does not require the creation of two sessions (one for the proxy user and another for the end user) as proxy authentication does. In addition, the client identifier does not have to be a database user. It can be set to any string. But most importantly, by using client identifier, ODP.NET developers can use application context and Oracle Label Security, and configure Oracle Virtual Private Database (VPD) more easily. To set the client identifier, ODP.NET applications can set the `ClientId` property on the `OracleConnection` object after opening a connection. If connection pooling is enabled, the `ClientId` is reset to null whenever a connection is placed back into the pool.

The client identifier can also be used for end-to-end application tracing. End-to-end tracing simplifies the process of diagnosing performance problems in multitier environments. In multitier environments, a request from an end client is routed to different database sessions by the middle tier making it difficult to track a client across different database sessions. End-to-end tracing uses the client identifier to uniquely trace a specific end-client through all tiers to the database server.

ODP.NET exposes the `ActionName`, `ClientId`, `ClientInfo`, and `ModuleName` write-only properties on the `OracleConnection` object. These properties correspond to the following end-to-end tracing attributes:

- `Action` - Specifies an action, such as an `INSERT` or `UPDATE` operation, in a module
- `ClientId` - Specifies an end user based on the logon ID, such as `HR.HR`
- `Client info` - Specifies user session information
- `Module` - Specifies a functional block, such as Accounts Receivable or General Ledger, of an application

### See Also:

- ["OracleConnection Properties"](#) on page 5-76
- "End-to-End Application Tracing" in the *Oracle Database Performance Tuning Guide*
- *Oracle Database Security Guide*

## Transparent Application Failover (TAF) Callback Support

**Transparent Application Failover (TAF)** is a feature in Oracle Database that provides high availability.

---

---

**Note:** TAF is not supported in a .NET stored procedure.

---

---

TAF enables an application connection to automatically reconnect to another database instance if the connection gets severed. Active transactions roll back, but the new database connection, made by way of a different node, is identical to the original. This is true regardless of how the connection fails.

With TAF, a client notices no loss of connection as long as there is one instance left serving the application. The database administrator controls which applications run on which instances, and also creates a failover order for each application.

When a session fails over to another database, the NLS settings that were initially set on the original session are not carried over to the new session. Therefore, it is the responsibility of the application to set these NLS settings on the new session.

### TAF Notification

Given the delays that failovers can cause, applications may wish to be notified by a TAF callback. ODP.NET supports the TAF callback function through the `Failover` event of the `OracleConnection` object, which allows applications to be notified whenever a failover occurs. To receive TAF callbacks, an event handler function must be registered with the `Failover` event.

### When Failover Occurs

When a failover occurs, the `Failover` event is raised and the registered event handler is invoked several times during the course of reestablishing the connection to another Oracle instance.

The first call to the event handler occurs when Oracle Database first detects an instance connection loss. This allows the application to act accordingly for the upcoming delay for the failover.

If the failover is successful, the `Failover` event is raised again when the connection is reestablished and usable. At this time, the application can resynchronize the `OracleGlobalization` session setting and inform the application user that a failover has occurred.

If failover is unsuccessful, the `Failover` event is raised to inform the application that a failover did not take place.

The application can determine whether or not the failover is successful by checking the `OracleFailoverEventArgs` object that is passed to the event handler.

### Registering an Event Handler for Failover

The following example registers an event handler method called `OnFailover`:

```
// C#
using System;
using Oracle.DataAccess.Client;

class TAFCallBackSample
{
    public static FailoverReturnCode OnFailover(object sender,
                                                OracleFailoverEventArgs eventArgs)
    {
        switch (eventArgs.FailoverEvent)
        {
            case FailoverEvent.Begin :
                Console.WriteLine(
                    " \nFailover Begin - Failing Over ... Please standby \n");
                Console.WriteLine(
                    " Failover type was found to be " + eventArgs.FailoverType);
                break;

            case FailoverEvent.Abort :
                Console.WriteLine(" Failover aborted. Failover will not take place.\n");
                break;
        }
    }
}
```

```
        case FailoverEvent.End :
            Console.WriteLine(" Failover ended ...resuming services\n");
            break;

        case FailoverEvent.Reauth :
            Console.WriteLine(" Failed over user. Resuming services\n");
            break;

        case FailoverEvent.Error :
            Console.WriteLine(" Failover error gotten. Sleeping...\n");
            return FailoverReturnCode.Retry;

        default :
            Console.WriteLine("Bad Failover Event: %d.\n", eventArgs.FailoverEvent);
            break;
    }
    return FailoverReturnCode.Success;
} /* OnFailover */

static void Main()
{
    OracleConnection con = new OracleConnection();

    con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
    con.Open();
    con.Failover += new OracleFailoverEventHandler(OnFailover);
    Console.WriteLine("Event Handler is successfully registered");

    // Close and Dispose OracleConnection object
    con.Close();
    con.Dispose();
}
}
```

The `Failover` event invokes only one event handler. If multiple `Failover` event handlers are registered with the `Failover` event, only the event handler registered last is invoked.

---

---

**Note:** Distributed transactions are not supported in an environment where failover is enabled.

---

---

**See Also:**

- *Oracle Net Services Administrator's Guide*
- ["OracleFailoverEventHandler Delegate"](#) on page 11-9
- ["OracleFailoverEventArgs Class"](#) on page 11-2

## ADO.NET 2.0 Features

Oracle Data Provider for .NET 10.2.0.2 or later supports Microsoft ADO.NET 2.0 APIs.

This section contains the following topics:

- [About ADO.NET 2.0](#)
- [Base Classes and Provider Factory Classes](#)

- [Connection String Builder](#)
- [Data Source Enumerator](#)
- [Support for Code Access Security](#)
- [Support for Schema Discovery](#)
- [System.Transactions and Promotable Transactions](#)
- [Batch Processing Support](#)
- [ADO.NET 2.0 Only Classes and Class Members](#)
- [Bulk Copy Support](#)

## About ADO.NET 2.0

ADO.NET 2.0 is a Microsoft specification that provides data access features designed to work together for provider independence, increased component reuse, and application convertibility. Additional features make it easier for an application to dynamically discover information about the data source, schema, and provider.

---



---

**Note:** Using ODP.NET with Microsoft ADO.NET 2.0 requires ADO.NET 2.0- compliant ODP.NET.

---



---

### See Also:

ADO.NET in the MSDN Library

## Base Classes and Provider Factory Classes

With ADO.NET 2.0, data classes derive from the base classes defined in the `System.Data.Common` namespace. Developers can create provider-specific instances of these base classes using provider factory classes.

Provider factory classes allow generic data access code to access multiple data sources with a minimum of data source-specific code. This reduces much of the conditional logic currently used by applications accessing multiple data sources.

Using Oracle Data Provider for .NET, the `OracleClientFactory` class can be returned and instantiated, enabling an application to create instances of the following ODP.NET classes that inherit from the base classes:

**Table 3–3 ODP.NET Classes that Inherit from ADO.NET 2.0 Base Classes**

ODP.NET Classes	Inherited from ADO.NET 2.0 Base Class
<code>OracleClientFactory</code>	<code>DbProviderFactory</code>
<code>OracleCommand</code>	<code>DbCommand</code>
<code>OracleCommandBuilder</code>	<code>DbCommandBuilder</code>
<code>OracleConnection</code>	<code>DbConnection</code>
<code>OracleConnectionStringBuilder</code>	<code>DbConnectionStringBuilder</code>
<code>OracleDataAdapter</code>	<code>DbDataAdapter</code>
<code>OracleDataReader</code>	<code>DbDataReader</code>
<code>OracleDataSourceEnumerator</code>	<code>DbDataSourceEnumerator</code>
<code>OracleException</code>	<code>DbException</code>

**Table 3–3 (Cont.) ODP.NET Classes that Inherit from ADO.NET 2.0 Base Classes**

ODP.NET Classes	Inherited from ADO.NET 2.0 Base Class
OracleParameter	DbParameter
OracleParameterCollection	DbParameterCollection
OracleTransaction	DbTransaction

In general, applications still require Oracle-specific connection strings, SQL or stored procedure calls, and declare that a factory from `Oracle.DataAccess.Client` is used.

**See Also:** ["OracleClientFactory Class"](#) on page 7-10

## Connection String Builder

The `OracleConnectionStringBuilder` class makes creating connection strings less error-prone and easier to manage.

Using this class, developers can employ a configuration file to provide the connection string and/or dynamically set the values through the key/value pairs. One example of a configuration file entry follows:

```
<configuration>
  <connectionStrings>
    <add name="Publications" providerName="Oracle.DataAccess.Client"
          connectionString="User Id=scott;Password=tiger;Data Source=inst1" />
  </connectionStrings>
</configuration>
```

Connection string information can be retrieved by specifying the connection string name, in this example, `Publications`. Then, based on the `providerName`, the appropriate factory for that provider can be obtained. This makes managing and modifying the connection string easier. In addition, this provides better security against string injection into a connection string.

**See Also:** ["OracleConnectionStringBuilder Class"](#) on page 7-10

## Data Source Enumerator

The data source enumerator enables the application to generically obtain a collection of the Oracle data sources that the application can connect to.

**See Also:** ["OracleDataSourceEnumerator Class"](#) on page 7-36

## Support for Code Access Security

ODP.NET implements code access security through the `OraclePermission` class. This ensures that application code trying to access the database has the requisite permission to do so.

When a .NET assembly tries to access Oracle Database through ODP.NET, ODP.NET demands `OraclePermission`. The .NET runtime security system checks to see whether the calling assembly, and all other assemblies in the call stack, have `OraclePermission` granted to them. If all assemblies in the call stack have `OraclePermission` granted to them, then the calling assembly can access the database. If any one of the assemblies in the call stack does not have `OraclePermission` granted to it, then a security exception is thrown.



## Configuring OraclePermission

The `DemandOraclePermission` configuration attribute is used to enable or disable `OraclePermission` demand for an ODP.NET API. The `DemandOraclePermission` value can be specified in the Windows registry or an individual application configuration file.

The following Windows registry key is used to configure the `DemandOraclePermission` configuration attribute:

```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version\DemandOraclePermission
```

Here `Assembly_Version` is the full assembly version number of `Oracle.DataAccess.dll`. The `DemandOraclePermission` key is of type `REG_SZ`. It can be set to either 1 (enabled) or 0 (disabled).

You can also enable `OraclePermission` demand for an individual application using its application configuration file. The following example enables the `DemandOraclePermission` property in an application configuration file:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DemandOraclePermission" value="1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

An application or assembly can successfully access the database if `OraclePermission` has been added to the permission set associated with the assembly's code group. A system administrator can modify the appropriate permission set manually or by using the Microsoft .NET configuration tool (`Mscorcfg.msc`).

Administrators may also use an appropriate .NET Framework Tool, such as the Code Access Security Policy Tool (`Caspol.exe`), to modify security policy at the machine, user, and enterprise levels for including `OraclePermission`.

`OracleConnection` makes security demands using the `OraclePermission` object when `OraclePermission` demand has been enabled using `DemandOraclePermission` configuration attribute. Application developers should make sure that their code has sufficient permission before using `OracleConnection`.

### See Also:

- ["OraclePermission Class"](#) on page 5-308
- ["OraclePermissionAttribute Class"](#) on page 5-317

## Support for Schema Discovery

ADO.NET 2.0 exposes five different types of metadata collections through the `OracleConnection.GetSchema` API. This permits application developers to customize metadata retrieval on an individual-application basis, for any Oracle data source. Thus, developers can build a generic set of code to manage metadata from multiple data sources.

The following types of metadata are exposed:

- `MetaDataCollections`

A list of metadata collections that is available from the data source, such as tables, columns, indexes, and stored procedures.

- **Restrictions**  
The restrictions that apply to each metadata collection, restricting the scope of the requested schema information.
- **DataSourceInformation**  
Information about the instance of the database that is currently being used, such as product name and version.
- **DataTypes**  
A set of information about each data type that the database supports.
- **ReservedWords**  
Reserved words for the Oracle query language.

**See Also:** [Appendix A, "Oracle Schema Collections"](#)

### User Customization of Metadata

ODP.NET provides a comprehensive set of database schema information. Developers can extend or customize the metadata that is returned by the `GetSchema` method on an individual application basis.

To do this, developers must create a customized metadata file and provide the file name to the application as follows:

1. Create a customized metadata file and put it in the `CONFIG` subdirectory where the .NET framework is installed. This is the directory that contains `machine.config` and the security configuration settings.

This file must contain the entire set of schema configuration information, not just the changes. Developers provide changes that modify the behavior of the schema retrieval to user-specific requirements. For instance, a developer can filter out internal database tables and just retrieve user-specific tables

2. Add an entry in the `app.config` file of the application, similar to the following, to provide the name of the metadata file, in name-value pair format.

```
<oracle.dataaccess.client>
  <settings>
    <add name="MetaDataXml" value="CustomMetaData.xml" />
  </settings>
</oracle.dataaccess.client>
```

When the `GetSchema` method is called, ODP.NET checks the `app.config` file for the name of the customized metadata XML file. First, the `GetSchema` method searches for an entry in the file with a element named after the provider, in this example, `oracle.dataaccess.client`. In this XML element, the value that corresponds to the name `MetaDataXml` is the name of the customized XML file, in this example, `CustomMetaData.xml`.

If the metadata file is not in the correct directory, then the application loads the default metadata XML file, which is part of ODP.NET.

**See Also:** ["GetSchema"](#) on page 5-99

## System.Transactions and Promotable Transactions

ODP.NET for .NET Framework 2.0 supports `System.Transactions`. A local transaction is created for the first connection opened in the `System.Transactions`

scope to Oracle Database 11g release 1 (11.1), or higher. When a second connection is opened, this transaction is automatically promoted to a distributed transaction. This functionality provides enhanced performance and scalability.

Connections created within a transaction context, such as `TransactionScope` or `ServicedComponent`, can be established to different versions of Oracle Database. However, in order to enable the local transaction to be promotable, the following must be true:

- The first connection in the transaction context must be established to an Oracle Database 11g release 1(11.1) instance or higher.
- All connections opened within the transaction context must have the "Promotable Transaction" setting set to "promotable". If you try to open a subsequent connection in the same transaction context with the "Promotable Transaction" setting set to "local", an exception is thrown.
- Promoting local transactions requires Oracle Services for Microsoft Transaction Server 11.1.0.7.20, or higher. If this requirement is not met, then a second connection request in the same transaction context throws an exception.

Setting "local" as the value of "PromotableTransaction" in the registry, configuration file (machine/Web/application), or the "Promotable Transaction" connection string attribute allows only one connection to be opened in the transaction context, which is associated with a local transaction. Such local transactions cannot be promoted.

For applications connecting to a pre-Oracle Database 11g release 1 (11.1) instance, refer to "[Local Transaction Support for Older Databases](#)" on page 3-26. This section describes how ODP.NET behavior can be controlled using the "Promotable Transaction" setting.

If applications use `System.Transactions`, it is required that the "enlist" connection string attribute is set to either "true" (default) or "dynamic".

ODP.NET supports the following `System.Transactions` programming models for applications using distributed transactions.

- [Implicit Transaction Enlistment Using TransactionScope](#)
- [Explicit Transaction Enlistment Using CommittableTransaction](#).
- [Local Transaction Support for Older Databases](#)

### **Implicit Transaction Enlistment Using TransactionScope**

The `TransactionScope` class provides a mechanism to write transactional applications where the applications do not need to explicitly enlist in transactions.

To accomplish this, the application uses the `TransactionScope` object to define the transactional code. Connections created within this transactional scope will enlist in a local transaction that can be promoted to a distributed transaction.

---

**Note:**

If the first connection is opened to a pre-Oracle Database 11g release 1 (11.1) instance, then the connection enlists as a distributed transaction, by default.

You can optionally create the transaction as a local transaction by using the procedure described in "[Local Transaction Support for Older Databases](#)" on page 26. However, these transactions cannot be promoted to distributed transactions.

---

Note that the application must call the `Complete` method on the `TransactionScope` object to commit the changes. Otherwise, the transaction is aborted by default.

```
// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;
using System.Data.Common;
using System.Transactions;

class psfTxnScope
{
    static void Main()
    {
        int retVal = 0;
        string providerName = "Oracle.DataAccess.Client";
        string constr =
            @"User Id=scott;Password=tiger;Data Source=oracle;enlist=true";

        // Get the provider factory.
        DbProviderFactory factory = DbProviderFactories.GetFactory(providerName);

        try
        {
            // Create a TransactionScope object, (It will start an ambient
            // transaction automatically).
            using (TransactionScope scope = new TransactionScope())
            {
                // Create first connection object.
                using (DbConnection conn1 = factory.CreateConnection())
                {
                    // Set connection string and open the connection. this connection
                    // will be automatically enlisted in a promotable local transaction.
                    conn1.ConnectionString = constr;
                    conn1.Open();

                    // Create a command to execute the sql statement.
                    DbCommand cmd1 = factory.CreateCommand();
                    cmd1.Connection = conn1;
                    cmd1.CommandText = @"insert into emp (empno, ename, job) values
                                        (1234, 'emp1', 'dev1)";

                    // Execute the SQL statement to insert one row in DB.
                    retVal = cmd1.ExecuteNonQuery();
                    Console.WriteLine("Rows to be affected by cmd1: {0}", retVal);
                }
            }
        }
    }
}
```

```

        // Close the connection and dispose the command object.
        conn1.Close();
        conn1.Dispose();
        cmd1.Dispose();
    }

    // The Complete method commits the transaction. If an exception has
    // been thrown or Complete is not called then the transaction is
    // rolled back.
    scope.Complete();
}
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
}

```

### Explicit Transaction Enlistment Using `CommittableTransaction`

The instantiation of the `CommittableTransaction` object and the `EnlistTransaction` method provides an explicit way to create and enlist in a transaction.

Note that the application must call `Commit` or `Rollback` on the `CommittableTransaction` object.

```

// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;
using System.Data.Common;
using System.Transactions;

class psfEnlistTransaction
{
    static void Main()
    {
        int retVal = 0;
        string providerName = "Oracle.DataAccess.Client";
        string constr =
            @"User Id=scott;Password=tiger;Data Source=oracle;enlist=dynamic";

        // Get the provider factory.
        DbProviderFactory factory = DbProviderFactories.GetFactory(providerName);

        try
        {
            // Create a committable transaction object.
            CommittableTransaction cmtTx = new CommittableTransaction();

            // Open a connection to the DB.
            DbConnection conn1 = factory.CreateConnection();
            conn1.ConnectionString = constr;
            conn1.Open();

            // enlist the connection with the committable transaction.
            conn1.EnlistTransaction(cmtTx);

```

```
// Create a command to execute the sql statement.
DbCommand cmd1 = factory.CreateCommand();
cmd1.Connection = conn1;
cmd1.CommandText = @"insert into emp (empno, ename, job) values
                    (1234, 'emp1', 'dev1')";

// Execute the SQL statement to insert one row in DB.
retVal = cmd1.ExecuteNonQuery();
Console.WriteLine("Rows to be affected by cmd1: {0}", retVal);

// commit/rollback the transaction.
cmtTx.Commit(); // commits the txn.
//cmtTx.Rollback(); // rolls back the txn.

// close and dispose the connection
conn1.Close();
conn1.Dispose();
cmd1.Dispose();
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
```

**See Also:** ["EnlistTransaction"](#) on page 5-97

### Local Transaction Support for Older Databases

If the first connection in a `TransactionScope` is opened to a pre-Oracle Database 11g release 1 (11.1) instance, then the connection creates a distributed transaction, by default. You can optionally have the first connection create a local transaction by using the procedure described in this section.

To create local transactions in a `System.Transactions` scope, either the `PromotableTransaction` setting in the registry, machine/Web/application configuration file, or the "Promotable Transaction" connection string attribute must be set to "local".

If "local" is specified, the first connection opened in the `TransactionScope` uses a local transaction. If any subsequent connections are opened within the same `TransactionScope`, an exception is thrown. If there are connections already opened in the `TransactionScope`, and an `OracleConnection` with "Promotable Transaction=local" attempts to open within the same `TransactionScope`, an exception is thrown.

If "promotable" is specified, the first and all subsequent connections opened in the same `TransactionScope` enlist in the same distributed transaction.

If both the registry and the connection string attribute are used and set to different values, the connection string attribute overrides the registry entry value. If neither are set, "promotable" is used. This is the default value and is equivalent to previous versions of ODP.NET which only supported distributed transactions.

The registry entry for a particular version of ODP.NET applies for all applications using that version of ODP.NET.

## Batch Processing Support

The `OracleDataAdapter.UpdateBatchSize` property enables batch processing when the `OracleDataAdapter.Update` method is called. `UpdateBatchSize` is a numeric property that indicates how many `DataSet` rows to update the Oracle database for each round-trip.

This enables the developer to reduce the number of round-trips to the database.

---



---

### Note: Microsoft Hotfix Needed

There is a known issue in Microsoft ADO.NET 2.0 that affects the `BatchUpdate` functionality.

To resolve this issue, both ODP.NET release 11.1 and a specific Microsoft hotfix must be installed on the same computer. The Microsoft hotfix is available for free download from the following site: <http://support.microsoft.com/?id=916002>

Without this fix, the `BatchUpdate` feature does not provide the correct error description for the failed rows in the `DataSet`. All errors in a batch are either appended to the exception message, if `DbDataAdapter.ContinueUpdateOnError` is false, or appended to the `RowError` property of the last updated row of the `DataSet`.

ODP.NET has been enhanced to use this hotfix and to populate the correct error description to the `RowError` property of the individual failed rows in a batch.

---



---

**See Also:** "[UpdateBatchSize](#)" on page 5-128

## ADO.NET 2.0 Only Classes and Class Members

In addition to classes which are ADO.NET 2.0 only, other ODP.NET classes that inherit from the `System.Data.Common` namespace include methods and properties which require ADO.NET 2.0.

The following classes are ADO.NET 2.0 only:

- [OracleClientFactory Class](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleDataSourceEnumerator Class](#)

The following class members are ADO.NET 2.0 only:

- `OracleCommandBuilder` Class Members
  - [CatalogLocation](#) Property (*Not Supported*)
  - [CatalogSeparator](#) Property (*Not Supported*)
  - [ConflictOption](#) Property (*Not Supported*)
  - [QuotePrefix](#) Property
  - [QuoteSuffix](#) Property
  - [SchemaSeparator](#) Property
  - [QuoteIdentifier](#) Method

- [UnquoteIdentifier](#) Method
- OracleConnection Class Members
  - [GetSchema](#) Methods
- OracleDataAdapter Class Members
  - [UpdateBatchSize](#) Property
  - [ReturnProviderSpecificTypes](#) Property
- OracleDataReader Class Members
  - [HiddenFieldCount](#) Property
  - [VisibleFieldCount](#) Property
  - [GetProviderSpecificFieldType](#) Method
  - [GetProviderSpecificValue](#) Method
  - [GetProviderSpecificValues](#) Method
- OracleParameter Class Members
  - [SourceColumnNullMapping](#) Property
  - [ResetDbType](#) Method
  - [ResetOracleDbType](#) Method
- OracleParameterCollection Class Members
  - [AddRange](#) Method

## Bulk Copy Support

ODP.NET provides a Bulk Copy feature which enables applications to efficiently load large amounts of data from a table in one database to another table in the same or a different database.

The ODP.NET Bulk Copy feature uses a direct path load approach, which is similar to, but not the same as Oracle SQL\*Loader. Using direct path load is faster than conventional loading (using conventional SQL INSERT statements). Conventional loading formats Oracle data blocks and writes the data blocks directly to the data files. Bulk Copy eliminates considerable processing overhead.

The ODP.NET Bulk Copy feature can load data into older Oracle databases.

**See Also:** ["System Requirements"](#) on page 2-1 to learn which versions of the Oracle Database ODP.NET interoperates with

The ODP.NET Bulk Copy feature is subject to the same basic restrictions and integrity constraints for direct path loads, as discussed in the next few sections.

### Data Types Supported by Bulk Copy

The data types supported by Bulk Copy are:

- ORA\_SB4
- ORA\_VARNUM
- ORA\_FLOAT
- ORA\_CHARN



- ORA\_RAW
- ORA\_BFLOAT
- ORA\_BDOUBLE
- ORA\_IBDOUBLE
- ORA\_IBFLOAT
- ORA\_DATE
- ORA\_TIMESTAMP
- ORA\_TIMESTAMP\_TZ
- ORA\_TIMESTAMP\_LTZ
- ORA\_INTERVAL\_DS
- ORA\_INTERVAL\_YM

Bulk copy does not support overwrites.

### Restrictions on Oracle Bulk Copy of a Single Partition

- The table that contains the partition cannot have any global indexes defined on it.
- The tables that the partition is a member of cannot have referential and check constraints enabled.
- Enabled triggers are not allowed.

### Integrity Constraints Affecting Oracle Bulk Copy

During a Oracle bulk copy, some integrity constraints are automatically enabled or disabled, as follows:

#### Enabled Constraints

During an Oracle bulk copy, the following constraints are automatically enabled by default:

- NOT NULL
- UNIQUE
- PRIMARY KEY (unique-constraints on not-null columns)

NOT NULL constraints are checked at column array build time. Any row that violates the NOT NULL constraint is rejected.

UNIQUE constraints are verified when indexes are rebuilt at the end of the load. The index is left in an Index Unusable state if it violates a UNIQUE constraint.

#### Disabled Constraints

During an Oracle bulk copy, the following constraints are automatically disabled by default:

- CHECK constraints
- Referential constraints (FOREIGN KEY)

If the EVALUATE CHECK\_CONSTRAINTS clause is specified, then CHECK constraints are not automatically disabled. The CHECK constraints are evaluated during a direct path load and any row that violates the CHECK constraint is rejected.

### Database Insert Triggers

Table insert triggers are disabled when a direct path load begins. After the rows are loaded and indexes rebuilt, any triggers that were disabled are automatically reenabled. The log file lists all triggers that were disabled for the load. There should be no errors reenabling triggers.

Unlike integrity constraints, insert triggers are not reapplied to the whole table when they are enabled. As a result, insert triggers do not fire for any rows loaded on the direct path. When using the direct path, the application must ensure that any behavior associated with insert triggers is carried out for the new rows.

### Field Defaults

Default column specifications defined in the database are not available with direct path loading. Fields for which default values are desired must be specified with the `DEFAULTIF` clause. If a `DEFAULTIF` clause is not specified and the field is `NULL`, then a null value is inserted into the database.

**See Also:** [Chapter 17, "Oracle Data Provider for .NET Bulk Copy Classes"](#)

## OracleCommand Object

The `OracleCommand` object represents SQL statements or stored procedures executed on Oracle Database.

---

---

**Note:** Optimizer hint syntax in the form `--+ . . .` is not supported. ODP.NET supports this syntax: `/*+ . . . */`.

---

---

This section includes the following topics:

- [Transactions](#)
- [Parameter Binding](#)
- [Statement Caching](#)
- [Self-Tuning](#)

## Transactions

Oracle Database starts a transaction only in the context of a connection. Once a transaction starts, all the successive command execution on that connection run in the context of that transaction. Transactions can be started only on an `OracleConnection` object, and the read-only `Transaction` property on the `OracleCommand` object is implicitly set by the `OracleConnection` object. Therefore, the application cannot set the `Transaction` property, nor does it need to.

---

---

**Note:** Transactions are not supported in a .NET stored procedure.

---

---

Explicit transactions are required with SQL statements containing `"FOR UPDATE"` and `"RETURNING"` clauses. This is not necessary if global transactions are used.

## Parameter Binding

When the `DbType` property of an `OracleParameter` object is set, the `OracleDbType` property of the `OracleParameter` object changes accordingly, or vice versa. The parameter set last prevails.

An application can bind the data and have ODP.NET infer both the `DbType` and `OracleDbType` properties from the .NET type of the parameter value.

ODP.NET allows applications to obtain an output parameter as either a .NET Framework type or an ODP.NET type. The application can specify which type to return for an output parameter by setting the `DbType` property of the output parameter (.NET type) or the `OracleDbType` property (ODP.NET type) of the `OracleParameter` object. For example, if the output parameter is set as a `DbType.String` type by setting the `DbType` property, the output data is returned as a .NET String type. On the other hand, if the parameter is set as an `OracleDbType.Char` type by setting the `OracleDbType` property, the output data is returned as an `OracleString` type. If both `DbType` and `OracleDbType` properties are set before the command execution, the last setting takes affect.

ODP.NET populates `InputOutput`, `Output`, and `ReturnValue` parameters with the Oracle data, through the execution of the following `OracleCommand` methods:

- `ExecuteReader`
- `ExecuteNonQuery`
- `ExecuteScalar`

An application should not bind a value for output parameters; it is the responsibility of ODP.NET to create the value object and populate the `OracleParameter.Value` property with the object.

When binding by position (default) to a function, ODP.NET expects the return value to be bound first, before any other parameters.

This section describes the following:

- [Data Types `BINARY\_FLOAT` and `BINARY\_DOUBLE`](#)
- [OracleDbType Enumeration Type](#)
- [Inference of DbType, OracleDbType, and .NET Types](#)
- [PL/SQL Associative Array Binding](#)
- [Array Binding](#)

**See Also:** ["OracleDbType Enumeration"](#) on page 5-358

### Data Types `BINARY_FLOAT` and `BINARY_DOUBLE`

Starting from Oracle Database 10g, the database supports two new native data types, `BINARY_FLOAT` and `BINARY_DOUBLE`.

The `BINARY_FLOAT` and `BINARY_DOUBLE` data types represent single-precision and double-precision, floating-point values respectively.

In `OracleParameter` binding, an application should use the enumerations `OracleDbType.BinaryFloat` and `OracleDbType.BinaryDouble` for `BINARY_FLOAT` and `BINARY_DOUBLE` data types.

**See Also:**

- ["GetDouble"](#) on page 5-178
- ["GetFloat"](#) on page 5-180

**OracleDbType Enumeration Type**

OracleDbType enumerated values are used to explicitly specify the OracleDbType value of an OracleParameter object.

[Table 3-4](#) lists all the OracleDbType enumeration values with a description of each enumerated value.

**Table 3-4 OracleDbType Enumeration Values**

Member Name	Description
Array	Oracle Collection type
BFile	Oracle BFILE type
BinaryFloat	Oracle BINARY_FLOAT type
BinaryDouble	Oracle BINARY_DOUBLE type
Blob	Oracle BLOB type
Byte	byte type
Char	Oracle CHAR type
Clob	Oracle CLOB type
Date	Oracle DATE type
Decimal	Oracle NUMBER type
Double	8-byte FLOAT type
Int16	2-byte INTEGER type
Int32	4-byte INTEGER type
Int64	8-byte INTEGER type
IntervalDS	Oracle INTERVAL DAY TO SECOND type
IntervalYM	Oracle INTERVAL YEAR TO MONTH type
Long	Oracle LONG type
LongRaw	Oracle LONG RAW type
NChar	Oracle NCHAR type
Object	Oracle Object type
NClob	Oracle NCLOB type
NVarChar2	Oracle NVARCHAR2 type
Raw	Oracle RAW type
Ref	Oracle REF type
RefCursor	Oracle REF CURSOR type
Single	4-byte FLOAT type
TimeStamp	Oracle TIMESTAMP type
TimeStampLTZ	Oracle TIMESTAMP WITH LOCAL TIME ZONE type

**Table 3–4 (Cont.) OracleDbType Enumeration Values**

Member Name	Description
TimeStampTZ	Oracle TIMESTAMP WITH TIME ZONE type
Varchar2	Oracle VARCHAR2 type
XmlType	Oracle XMLType type

### Inference of DbType, OracleDbType, and .NET Types

This section explains the inference from the `System.Data.DbType`, `OracleDbType`, and `Value` properties in the `OracleParameter` class.

In the `OracleParameter` class, `DbType`, `OracleDbType`, and `Value` properties are linked. Specifying the value of any of these properties infers the value of one or more of the other properties.

**Inference of DbType from OracleDbType** In the `OracleParameter` class, specifying the value of `OracleDbType` infers the value of `DbType` as shown in [Table 3–5](#).

**Table 3–5 Inference of System.Data.DbType from OracleDbType**

OracleDbType	System.Data.DbType
Array	Object
BFile	Object
Blob	Object
BinaryFloat	Single
BinaryDouble	Double
Byte	Byte
Char	StringFixedLength
Clob	Object
Date	Date
Decimal	Decimal
Double	Double
Int16	Int16
Int32	Int32
Int64	Int64
IntervalDS	Object
IntervalYM	Int64
Long	String
LongRaw	Binary
NChar	StringFixedLength
NClob	Object
NVarchar2	String
Object	Object
Raw	Binary
Ref	Object

**Table 3–5 (Cont.) Inference of System.Data.DbType from OracleDbType**

<b>OracleDbType</b>	<b>System.Data.DbType</b>
RefCursor	Object
Single	Single
TimeStamp	DateTime
TimeStampLTZ	DateTime
TimeStampTZ	DateTime
Varchar2	String
XmlType	String

**Inference of OracleDbType from DbType** In the `OracleParameter` class, specifying the value of `DbType` infers the value of `OracleDbType` as shown in [Table 3–6](#).

**Table 3–6 Inference of OracleDbType from DbType**

<b>System.Data.DbType</b>	<b>OracleDbType</b>
Binary	Raw
Boolean	<i>Not Supported</i>
Byte	Byte
Currency	<i>Not Supported</i>
Date	Date
DateTime	TimeStamp
Decimal	Decimal
Double	Double
Guid	<i>Not Supported</i>
Int16	Int16
Int32	Int32
Int64	Int64
Object	Object
Sbyte	<i>Not Supported</i>
Single	Single
String	Varchar2
StringFixedLength	Char
Time	TimeStamp
UInt16	<i>Not Supported</i>
UInt32	<i>Not Supported</i>
UInt64	<i>Not Supported</i>
VarNumeric	<i>Not Supported</i>

**Inference of DbType and OracleDbType from Value** In the `OracleParameter` class, `Value` is an object type that can be of any .NET Framework data type or ODP.NET type. If the `OracleDbType` and `DbType` properties of the `OracleParameter` class are not

specified, the `OracleDbType` property is inferred from the type of the `Value` property.

[Table 3–7](#) shows the inference of `DbType` and `OracleDbType` properties from the `Value` property when the type of `Value` is one of the .NET Framework data types.

**Table 3–7 Inference of DbType and OracleDbType from Value (.NET Datatypes)**

Value (.NET Datatypes)	System.Data.DbType	OracleDbType
Byte	Byte	Byte
Byte[]	Binary	Raw
Char / Char []	String	Varchar2
DateTime	DateTime	TimeStamp
Decimal	Decimal	Decimal
Double	Double	Double
Float	Single	Single
Int16	Int16	Int16
Int32	Int32	Int32
Int64	Int64	Int64
IOracleCustomType	Object	Object
Single	Single	Single
String	String	Varchar2
TimeSpan	Object	IntervalDS

---

**Note:** Using other .NET Framework data types as values for the `OracleParameter` class without specifying either the `DbType` or the `OracleDbType` properties raises an exception because inferring `DbType` and `OracleDbType` properties from other .NET Framework data types is not supported.

---

[Table 3–8](#) shows the inference of `DbType` and `OracleDbType` properties from the `Value` property when type of `Value` is one of `Oracle.DataAccess.Types`.

**Table 3–8 Inference of DbType and OracleDbType from Value (ODP.NET Types)**

Value (Oracle.DataAccess.Types)	System.Data.DbType	OracleDbType
OracleBFile	Object	BFile
OracleBinary	Binary	Raw
OracleBlob	Object	Blob
OracleClob	Object	Clob
OracleDate	Date	Date
OracleDecimal	Decimal	Decimal
OracleIntervalDS	Object	IntervalDS
OracleIntervalYM	Int64	IntervalYM

**Table 3–8 (Cont.) Inference of DbType and OracleDbType from Value (ODP.NET Types)**

<b>Value (Oracle.DataAccess.Types)</b>	<b>System.Data.DbType</b>	<b>OracleDbType</b>
OracleRef	Object	Ref
OracleRefCursor	Object	RefCursor
OracleString	String	Varchar2
OracleTimeStamp	DateTime	TimeStamp
OracleTimeStampLTZ	DateTime	TimeStampLTZ
OracleTimeStampTZ	DateTime	TimeStampTZ
OracleXmlType	String	XmlType

### PL/SQL Associative Array Binding

ODP.NET supports PL/SQL Associative Arrays (formerly known as PL/SQL Index-By Tables) binding.

An application can bind an `OracleParameter` object, as a PL/SQL Associative Array, to a PL/SQL stored procedure. The following `OracleParameter` properties are used for this feature:

- `CollectionType`  
This property must be set to `OracleCollectionType.PLSQLAssociativeArray` to bind a PL/SQL Associative Array.
- `ArrayBindSize`  
This property is ignored for the fixed-length element types (such as `Int32`).  
For variable-length element types (such as `Varchar2`), each element in the `ArrayBindSize` property specifies the size of the corresponding element in the `Value` property.  
For Output parameters, InputOutput parameters, and return values, this property must be set for variable-length variables.
- `ArrayBindStatus`  
This property specifies the execution status of each element in the `OracleParameter.Value` property.
- `Size`  
This property specifies the maximum number of elements to be bound in the PL/SQL Associative Array.
- `Value`  
This property must be set to an array of values, `null`, or the `DBNull.Value` property.

ODP.NET supports binding parameters of PL/SQL Associative Arrays which contain the following data types.

- `BINARY_FLOAT`
- `CHAR`
- `DATE`



- NCHAR
- NUMBER
- NVARCHAR2
- RAW
- ROWID
- UROWID
- VARCHAR2

Using unsupported data types with associative arrays can cause an ORA-600 error.

### Example of PL/SQL Associative Arrays

This example binds three OracleParameter objects as PL/SQL Associative Arrays: Param1 as an In parameter, Param2 as an InputOutput parameter, and Param3 as an Output parameter.

PL/SQL Package: MYPACK

/\* Setup the tables and required PL/SQL:

```

connect scott/tiger@oracle
CREATE TABLE T1(COL1 number, COL2 varchar2(20));

CREATE or replace PACKAGE MYPACK AS
  TYPE AssocArrayVarchar2_t is table of VARCHAR(20) index by BINARY_INTEGER;
  PROCEDURE TestVarchar2(
    Param1 IN      AssocArrayVarchar2_t,
    Param2 IN OUT AssocArrayVarchar2_t,
    Param3  OUT AssocArrayVarchar2_t);
END MYPACK;
/

CREATE or REPLACE package body MYPACK as
  PROCEDURE TestVarchar2(
    Param1 IN      AssocArrayVarchar2_t,
    Param2 IN OUT AssocArrayVarchar2_t,
    Param3  OUT AssocArrayVarchar2_t)
  IS
    i integer;
  BEGIN
    -- copy a few elements from Param2 to Param1\n
    Param3(1) := Param2(1);
    Param3(2) := NULL;
    Param3(3) := Param2(3);
    -- copy all elements from Param1 to Param2\n
    Param2(1) := Param1(1);
    Param2(2) := Param1(2);
    Param2(3) := Param1(3);
    -- insert some values to db\n
    FOR i IN 1..3 LOOP
      insert into T1 values(i,Param2(i));
    END LOOP;
  END TestVarchar2;
END MYPACK;
/
*/

// C#
```

```
using System;
using System.Data;
using Oracle.DataAccess.Client;

class AssociativeArraySample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        OracleCommand cmd = new OracleCommand(
            "begin MyPack.TestVarchar2(:1, :2, :3); end;", con);

        OracleParameter Param1 = cmd.Parameters.Add("1", OracleDbType.Varchar2);
        OracleParameter Param2 = cmd.Parameters.Add("2", OracleDbType.Varchar2);
        OracleParameter Param3 = cmd.Parameters.Add("3", OracleDbType.Varchar2);

        Param1.Direction = ParameterDirection.Input;
        Param2.Direction = ParameterDirection.InputOutput;
        Param3.Direction = ParameterDirection.Output;

        // Specify that we are binding PL/SQL Associative Array
        Param1.CollectionType = OracleCollectionType.PLSQLAssociativeArray;
        Param2.CollectionType = OracleCollectionType.PLSQLAssociativeArray;
        Param3.CollectionType = OracleCollectionType.PLSQLAssociativeArray;

        // Setup the values for PL/SQL Associative Array
        Param1.Value = new string[3] {
            "First Element", "Second Element ", "Third Element "
        };
        Param2.Value = new string[3] {
            "First Element", "Second Element ", "Third Element "
        };
        Param3.Value = null;

        // Specify the maximum number of elements in the PL/SQL Associative Array
        Param1.Size = 3;
        Param2.Size = 3;
        Param3.Size = 3;

        // Setup the ArrayBindSize for Param1
        Param1.ArrayBindSize = new int[3] { 13, 14, 13 };

        // Setup the ArrayBindStatus for Param1
        Param1.ArrayBindStatus = new OracleParameterStatus[3] {
            OracleParameterStatus.Success, OracleParameterStatus.Success,
            OracleParameterStatus.Success};

        // Setup the ArrayBindSize for Param2
        Param2.ArrayBindSize = new int[3] { 20, 20, 20 };

        // Setup the ArrayBindSize for Param3
        Param3.ArrayBindSize = new int[3] { 20, 20, 20 };

        // execute the cmd
    }
}
```

```

cmd.ExecuteNonQuery();

//print out the parameter's values
Console.WriteLine("parameter values after executing the PL/SQL block");
for (int i = 0; i < 3; i++)
    Console.WriteLine("Param2[{0}] = {1} ", i,
        (cmd.Parameters[1].Value as Array).GetValue(i));

for (int i = 0; i < 3; i++)
    Console.WriteLine("Param3[{0}] = {1} ", i,
        (cmd.Parameters[2].Value as Array).GetValue(i));

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
Console.WriteLine("Disconnected");
}
}

```

## Array Binding

The array bind feature enables applications to bind arrays of a type using the `OracleParameter` class. Using the array bind feature, an application can insert multiple rows into a table in a single database round-trip.

The following example inserts three rows into the `Dept` table with a single database round-trip. The `OracleCommand` `ArrayBindCount` property defines the number of elements of the array to use when executing the statement.

```

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected successfully");

        int[] myArrayDeptNo = new int[3] { 10, 20, 30 };
        OracleCommand cmd = new OracleCommand();

        // Set the command text on an OracleCommand object
        cmd.CommandText = "insert into dept(deptno) values (:deptno)";
        cmd.Connection = con;

        // Set the ArrayBindCount to indicate the number of values
        cmd.ArrayBindCount = 3;

        // Create a parameter for the array operations
        OracleParameter prm = new OracleParameter("deptno", OracleDbType.Int32);

        prm.Direction = ParameterDirection.Input;
        prm.Value = myArrayDeptNo;
    }
}

```

```
// Add the parameter to the parameter collection
cmd.Parameters.Add(prm);

// Execute the command
cmd.ExecuteNonQuery();
Console.WriteLine("Insert Completed Successfully");

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
}
}
```

**See Also:** ["Value"](#) on page 5-276 for more information

**OracleParameter Array Bind Properties** The `OracleParameter` class provides two properties for granular control when using the array bind feature:

- `ArrayBindSize`

The `ArrayBindSize` property is an array of integers specifying the maximum size for each corresponding value in an array. The `ArrayBindSize` property is similar to the `Size` property of an `OracleParameter` object, except the `ArrayBindSize` property specifies the size for each value in an array.

Before the execution, the application must populate the `ArrayBindSize` property; after the execution, ODP.NET populates it.

The `ArrayBindSize` property is used only for parameter types that have variable length such as `Clob`, `Blob`, and `Varchar2`. The size is represented in bytes for binary data types, and characters for the Unicode string types. The count for string types does not include the terminating character. The size is inferred from the actual size of the value, if it is not explicitly set. For an output parameter, the size of each value is set by ODP.NET. The `ArrayBindSize` property is ignored for fixed-length data types.

- `ArrayBindStatus`

The `ArrayBindStatus` property is an array of `OracleParameterStatus` values that specify the status of each corresponding value in an array for a parameter. This property is similar to the `Status` property of the `OracleParameter` object, except that the `ArrayBindStatus` property specifies the status for each array value.

Before the execution, the application must populate the `ArrayBindStatus` property. After the execution, ODP.NET populates the property. Before the execution, an application using the `ArrayBindStatus` property can specify a `NULL` value for the corresponding element in the array for a parameter. After the execution, ODP.NET populates the `ArrayBindStatus` property, indicating whether the corresponding element in the array has a null value, or if data truncation occurred when the value was fetched.

**Error Handling for Array Binding** If an error occurs during an array bind execution, it can be difficult to determine which element in the `Value` property caused the error. ODP.NET provides a way to determine the row where the error occurred, making it easier to find the element in the row that caused the error.

When an `OracleException` object is thrown during an array bind execution, the `OracleErrorCollection` object contains one or more `OracleError` objects. Each

of these `OracleError` objects represents an individual error that occurred during the execution, and contains a provider-specific property, `ArrayBindIndex`, which indicates the row number at which the error occurred.

The following example demonstrates error handling for array binding:

```

/* Database Setup
connect scott/tiger@oracle
drop table depttest;
create table depttest(deptno number(2));
*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindExceptionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        OracleCommand cmd = new OracleCommand();

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(IsolationLevel.ReadCommitted);

        try
        {
            int[] myArrayDeptNo = new int[3] { 10, 20000, 30 };
            // int[] myArrayDeptNo = new int[3]{ 10,20,30};

            // Set the command text on an OracleCommand object
            cmd.CommandText = "insert into depttest(deptno) values (:deptno)";
            cmd.Connection = con;

            // Set the ArrayBindCount to indicate the number of values
            cmd.ArrayBindCount = 3;

            // Create a parameter for the array operations
            OracleParameter prm = new OracleParameter("deptno", OracleDbType.Int32);

            prm.Direction = ParameterDirection.Input;
            prm.Value = myArrayDeptNo;

            // Add the parameter to the parameter collection
            cmd.Parameters.Add(prm);

            // Execute the command
            cmd.ExecuteNonQuery();
        }
        catch (OracleException e)
        {
            Console.WriteLine("OracleException {0} occured", e.Message);
            if (e.Number == 24381)
                for (int i = 0; i < e.Errors.Count; i++)
                    Console.WriteLine("Array Bind Error {0} occured at Row Number {1}",

```

```

        e.Errors[i].Message, e.Errors[i].ArrayBindIndex);

        txn.Commit();
    }
    cmd.Parameters.Clear();
    cmd.CommandText = "select count(*) from depttest";

    decimal rows = (decimal)cmd.ExecuteScalar();

    Console.WriteLine("{0} row have been inserted", rows);
    con.Close();
    con.Dispose();
}
}

```

**See Also:** ["ArrayBindIndex"](#) on page 5-219 for more information

**OracleParameterStatus Enumeration Types** Table 3–9 lists OracleParameterStatus enumeration values.

**Table 3–9 OracleParameterStatus Members**

Member Names	Description
Success	For input parameters, indicates that the input value has been assigned to the column.  For output parameters, indicates that the provider assigned an intact value to the parameter.
NullFetched	Indicates that a NULL value has been fetched from a column or an OUT parameter.
NullInsert	Indicates that a NULL value is to be inserted into a column.
Truncation	Indicates that truncation has occurred when fetching the data from the column.

## Statement Caching

Statement caching eliminates the need to parse each SQL or PL/SQL statement before execution by caching server cursors created during the initial statement execution. Subsequent executions of the same statement can reuse the parsed information from the cursor, and then execute the statement without reparsing, for better performance.

In order to see performance gains from statement caching, Oracle recommends caching only those statements that will be repeatedly executed. Furthermore, SQL or PL/SQL statements should use parameters rather than literal values. Doing so takes full advantage of statement caching, because parsed information from parameterized statements can be reused even if the parameter values change in subsequent executions. However, if the literal values in the statements are different, the parsed information cannot be reused unless the subsequent statements also have the same literal values.

### Statement Caching Connection String Attributes

The following connection string attributes control the behavior of the ODP.NET statement caching feature:

- Statement Cache Size

This attribute enables or disables ODP.NET statement caching. By default, this attribute is set to 0 (disabled). If it is set to a value greater than 0, ODP.NET statement caching is enabled and the value specifies the maximum number of statements that can be cached for a connection. Once a connection has cached up to the specified maximum cache size, the least recently used cursor is freed to make room to cache the newly created cursor.

If self tuning is enabled, then statement caching is enabled as well. The `Statement Cache Size` is configured automatically in such cases.

- `Statement Cache Purge`

This attribute provides a way for connections to purge all statements that are cached when a connection is closed or placed back into the connection pool. By default, this attribute is set to `false`, which means that cursors are not freed when connections are placed back into the pool.

### Enabling Statement Caching through the Registry

To enable statement caching by default for all ODP.NET applications running in a system, without changing the application, set the registry key of `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version\StatementCacheSize` to a value greater than 0. This value specifies the number of cursors that are to be cached on the server.

The default value for the system can be overridden at the connection pool level. The `Statement Cache Size` attribute can be set to a different size than the registry value or it can be turned off. The `Statement Cache Size` can also be configured through an XML configuration file. For details, see "[ODP.NET Configuration](#)" on page 3-114.

### Statement Caching Methods and Properties

The following property and method are relevant only when statement caching is enabled:

- `OracleCommand.AddToStatementCache` property

If statement caching is enabled, having this property set to `true` (default) adds statements to the cache when they are executed. If statement caching is disabled or if this property is set to `false`, the executed statement is not cached.

- `OracleConnection.PurgeStatementCache` method

This method purges all the cached statements by closing all open cursors on the database that are associated with the particular connection. Note that statement caching remains enabled after this call.

### Connections and Statement Caching

Statement caching is managed separately for each connection. Therefore, executing the same statement on different connections requires parsing once for each connection and caching a separate cursor for each connection.

### Pooling and Statement Caching

Pooling and statement caching can be used in conjunction. If connection pooling is enabled and the `Statement Cache Purge` attribute is set to `false`, statements executed on each separate connection are cached throughout the lifetime of the pooled connection.

If the `Statement Cache Purge` attribute is set to `true`, all the cached cursors are freed when the connection is placed back into the pool. When connection pooling is

disabled, cursors are cached during the lifetime of the connection, but the cursors are closed when the `OracleConnection` object is closed or disposed of.

## Self-Tuning

ODP.NET applications can be self-tuned for performance optimization. ODP.NET dynamically monitors application queries during runtime.

---

---

**Note:** Self-tuning for applications does not take place if the `Pooling` connection string attribute is set to `false`. Self-tuning is also not supported inside .NET stored procedures.

---

---

The statement cache size (`StatementCacheSize`) is tuned automatically by monitoring the statements that are executed by the application. The following sections discuss self-tuning in applications:

- [Self-Tuning Statement Caching](#)
- [Enabling or Disabling Self-Tuning for Applications](#)
- [Tracing Optimization Changes](#)

### Self-Tuning Statement Caching

Statement caching helps improve performance by eliminating the need to re-parse each SQL or PL/SQL statement before execution.

If self-tuning is enabled for an application, then ODP.NET continuously monitors application behavior in order to determine the optimum value for the statement cache size. Any statement cache size value specified in the connection string, configuration file, or registry is ignored.

When the application first initializes, it uses the default value of statement cache size. As the application executes statements, ODP.NET collects statistics that are used to self-tune the value of statement cache size. Self-tuning of statement cache size results in increased performance.

---

---

**Note:** To take full advantage of statement caching, you should not dynamically generate statements, with different inline values, for every statement execution. Instead, use parameterized commands to minimize the number of unique statements that need to be executed and cached. This is because only one statement needs to be cached for every unique command text, regardless of the parameter values and the number of times that the statement is executed.

---

---

The maximum number of statements that can be cached per connection is determined by the `MaxStatementCacheSize` configuration attribute. The `MaxStatementCacheSize` value can be specified in the Windows registry or XML configuration file.

The `MaxStatementCacheSize` setting is useful in limiting the number of cached statements, as well as the number of open cursors. This is because a cached statement equates to a cursor being opened on the server. For this reason, you should not set `MaxStatementCacheSize` to a value that is greater than the database `MAX_OPEN_CURSORS` setting.



The following Windows registry key is used to configure the `MaxStatementCacheSize` configuration attribute:

```
HKLM\Software\Oracle\ODP.NET\version\MaxStatementCacheSize
```

The `MaxStatementCacheSize` key is of type `REG_SZ`. It can be set to an integer value between 0 and `System.Int32.MaxValue`.

The following example sets the `MaxStatementCacheSize` property in an ADO.NET 2.0, or above, configuration file:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="MaxStatementCacheSize" value="300" />
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

If self-tuning is disabled for an application, then the value of statement cache size is determined by the settings in the connection string, configuration file, or the registry. If statement cache size is not specified in any of these sources, then the default value of statement cache size is set to 0. To have ODP.NET configured with the same default settings as previous releases of ODP.NET, disable self-tuning and set the `StatementCacheSize` value to 10.

**See Also:** ["Statement Caching"](#) on page 3-42

### Enabling or Disabling Self-Tuning for Applications

Self-tuning for ODP.NET applications is enabled by default. An application can enable or disable self-tuning using one of the following methods:

- Self-Tuning Connection String Attribute

An application can modify the `Self Tuning` connection string attribute to enable or disable self-tuning for a particular connection pool. The default value for `Self Tuning` is `true`.

- Windows Registry

An application can enable or disable self-tuning for a particular version of ODP.NET by modifying the following registry entry:

```
HKLM\Software\Oracle\ODP.NET\version\SelfTuning
```

The `SelfTuning` key is of type `REG_SZ`. It can be set to either 1 (enabled) or 0 (disabled).

- Configuration File

An ODP.NET application can modify the application configuration file (`app.config`) or Web configuration file (`web.config`) to enable or disable self-tuning.

The following example shows how to enable self-tuning in an ADO.NET 2.0 application configuration file:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
```

```

        <add name="SelfTuning" value="1" />
    </settings>
</oracle.dataaccess.client>
</configuration>

```

---

**Note:** If the optimal statement cache size is known for an application, then you can disable self-tuning and set `StatementCacheSize` to its optimum value in the registry, configuration file, or the application. If self-tuning is disabled and `StatementCacheSize` is not set at all, then the default value of 0 is used for `StatementCacheSize`.

---

### Tracing Optimization Changes

Applications can trace optimization changes made by self-tuning. All changes to `StatementCacheSize` are traced. Errors, if any, are also traced.

The `TraceLevel` used for tracing self-tuning is 64.

**See Also:** [Table 3–30, "Configuration Attributes"](#) for details on `TraceLevel` values

## ODP.NET Types Overview

ODP.NET types represent Oracle native data types and PL/SQL data types as a structure or as a class. ODP.NET type structures follow **value semantics**, while ODP.NET type classes follow **reference semantics**. ODP.NET types provide safer and more efficient ways of obtaining Oracle native data and PL/SQL data types in a .NET application than .NET types. For example, an `OracleDecimal` structure holds up to 38 digits of precision, while a .NET `Decimal` only holds up to 28.

[Table 3–10](#) lists data types supported by ODP.NET and their corresponding ODP.NET types: data types in the first column refer to both Oracle native data types and PL/SQL data types of that name. Those data types that exist only in PL/SQL are indicated by (PL/SQL only) after the data type name. The entries for the PL/SQL data types also represent the subtypes of the data types, if any. The third column lists the .NET Framework data type that corresponds to the `Value` property of each ODP.NET type.

**Table 3–10 Value Property Type of ODP.NET Type**

Oracle Native Data Type or PL/SQL Data Type	ODP.NET Type	.NET Framework Data Types
BFILE	<code>OracleBFile</code> class	<code>System.Byte[]</code>
BINARY_DOUBLE	<code>OracleDecimal</code> structure	<code>System.Decimal</code>
BINARY_FLOAT	<code>OracleDecimal</code> structure	<code>System.Decimal</code>
BINARY_INTEGER (PL/SQL only)	<code>OracleDecimal</code> structure	<code>System.Decimal</code>
BLOB	<code>OracleBlob</code> class	<code>System.Byte[]</code>
CHAR	<code>OracleString</code> structure	<code>System.String</code>
CLOB	<code>OracleClob</code> class	<code>System.String</code>

**Table 3–10 (Cont.) Value Property Type of ODP.NET Type**

Oracle Native Data Type or PL/SQL Data Type	ODP.NET Type	.NET Framework Data Types
DATE	OracleDate structure	System.DateTime
INTERVAL DAY TO SECOND	OracleIntervalDS structure	System.TimeSpan
INTERVAL YEAR TO MONTH	OracleIntervalYM structure	System.Int64
LONG	OracleString structure	System.String
LONG RAW	OracleBinary structure	System.Byte[]
NCHAR	OracleString structure	System.String
NCLOB	OracleClob class	System.String
NUMBER	OracleDecimal structure	System.Decimal
NVARCHAR2	OracleString structure	System.String
PLS_INTEGER (PL/SQL only)	OracleDecimal Structure	System.Decimal
RAW	OracleBinary structure	System.Byte[]
REF	OracleRef class	System.String
REF CURSOR (PL/SQL only)	OracleRefCursor class	Not Applicable
ROWID	OracleString structure	System.String
TIMESTAMP	OracleTimeStamp structure	System.DateTime
TIMESTAMP WITH LOCAL TIME ZONE	OracleTimeStampLTZ structure	System.DateTime
TIMESTAMP WITH TIME ZONE	OracleTimeStampTZ structure	System.DateTime
UROWID	OracleString structure	System.String
VARCHAR2	OracleString structure	System.String
XMLType	OracleXmlType class	System.String

## Obtaining Data from an OracleDataReader Object

The `ExecuteReader` method of the `OracleCommand` object returns an `OracleDataReader` object, which is a read-only, forward-only result set.

This section provides the following information about the `OracleDataReader` object:

- [Typed OracleDataReader Accessors](#)
- [Obtaining LONG and LONG RAW Data](#)

- [Obtaining LOB Data](#)
- [Controlling the Number of Rows Fetched in One Database Round-Trip](#)

## Typed OracleDataReader Accessors

The `OracleDataReader` class provides two types of typed accessors:

- [.NET Type Accessors](#)
- [ODP.NET Type Accessors](#)

### .NET Type Accessors

[Table 3–11](#) lists all the Oracle native database types that ODP.NET supports, and the corresponding .NET types that can represent the Oracle native type. If more than one .NET type can be used to represent an Oracle native type, the first entry is the .NET type that best represents the Oracle native type. The third column indicates the valid typed accessor that can be invoked for an Oracle native type to be obtained as a .NET type. If an invalid typed accessor is used for a column, an `InvalidCastException` is thrown. Oracle native data types depend on the version of the database; therefore, some data types are not available in earlier versions of Oracle Database.

#### See Also:

- ["OracleDataAdapter Class"](#) on page 5-115
- ["OracleDataReader Class"](#) on page 5-151

**Table 3–11 .NET Type Accessors**

Oracle Native Data Type	.NET Type	Typed Accessor
BFILE	<code>System.Byte[]</code>	<code>GetBytes</code>
BINARY_DOUBLE	<code>System.Double</code>	<code>GetDouble</code>
BINARY_FLOAT	<code>System.Single</code>	<code>GetFloat</code>
BLOB	<code>System.Byte[]</code>	<code>GetBytes</code>
CHAR	<code>System.String</code>	<code>GetString</code>
	<code>System.Char[]</code>	<code>GetChars</code>
CLOB	<code>System.String</code>	<code>GetString</code>
	<code>System.Char[]</code>	<code>GetChars</code>
DATE	<code>System.DateTime</code>	<code>GetDateTime</code>
INTERVAL DAY TO SECOND	<code>System.Timespan</code>	<code>GetTimeSpan</code>
INTERVAL YEAR TO MONTH	<code>System.Int64</code>	<code>GetInt64</code>
LONG	<code>System.String</code>	<code>GetString</code>
	<code>System.Char[]</code>	<code>GetChars</code>
LONG RAW	<code>System.Byte[]</code>	<code>GetBytes</code>
NCHAR	<code>System.String</code>	<code>GetString</code>
	<code>System.Char[]</code>	<code>GetChars</code>
NCLOB	<code>System.String</code>	<code>GetString</code>
	<code>System.Char[]</code>	<code>GetChars</code>

**Table 3–11 (Cont.) .NET Type Accessors**

Oracle Native Data Type	.NET Type	Typed Accessor
NUMBER	System.Decimal	GetDecimal
	System.Byte	GetByte
	System.Int16	GetInt16
	System.Int32	GetInt32
	System.Int64	GetInt64
	System.Single	GetFloat
NVARCHAR2	System.Double	GetDouble
	System.String	GetString
RAW	System.Char[]	GetChars
	System.Byte[]	GetBytes
REF	System.String	GetString
ROWID	System.String	GetString
	System.Char[]	GetChars
TIMESTAMP	System.DateTime	GetDateTime
TIMESTAMP WITH LOCAL TIME ZONE	System.DateTime	GetDateTime
TIMESTAMP WITH TIME ZONE	System.DateTime	GetDateTime
UROWID	System.String	GetString
	System.Char[]	GetChars
VARCHAR2	System.String	GetString
	System.Char[]	GetChars
XMLType	System.String	GetString
	System.Xml.XmlReader	GetXmlReader

Certain methods and properties of the `OracleDataReader` object require ODP.NET to map a `NUMBER` column to a .NET type based on the precision and scale of the column. These members are:

- `Item` property
- `GetFieldType` method
- `GetValue` method
- `GetValues` method

ODP.NET determines the appropriate .NET type by considering the following .NET types in order, and selecting the first .NET type from the list that can represent the entire range of values of the column:

- `System.Byte`
- `System.Int16`
- `System.Int32`
- `System.Int64`
- `System.Single`
- `System.Double`

- `System.Decimal`

If no .NET type exists that can represent the entire range of values of the column, then an attempt is made to represent the column values as a `System.Decimal` type. If the value in the column cannot be represented as `System.Decimal`, then an exception is raised.

For example, consider two columns defined as `NUMBER(4, 0)` and `NUMBER(10, 2)`. The first .NET types from the previous list that can represent the entire range of values of the columns are `System.Int16` and `System.Double`, respectively. However, consider a column defined as `NUMBER(20, 10)`. In this case, there is no .NET type that can represent the entire range of values on the column, so an attempt is made to return values in the column as a `System.Decimal` type. If a value in the column cannot be represented as a `System.Decimal` type, then an exception is raised.

The `Fill` method of the `OracleDataAdapter` class uses the `OracleDataReader` object to populate or refresh a `DataTable` or `DataSet` with .NET types. As a result, the .NET type used to represent a `NUMBER` column in the `DataTable` or `DataSet` also depends on the precision and scale of the column.

**See Also:**

- ["OracleDataReader Class"](#) on page 5-151
- ["OracleDataAdapter Class"](#) on page 5-115
- ["Item"](#) on page 5-163
- ["GetFieldType"](#) on page 5-179
- ["GetValues"](#) on page 5-211
- ["GetValue"](#) on page 5-210

### ODP.NET Type Accessors

ODP.NET exposes provider-specific types that natively represent the data types in the database. In some cases, these ODP.NET types provide better performance and functioning than the corresponding .NET types. The ODP.NET types can be obtained from the `OracleDataReader` object by calling their respective typed accessor.

**See Also:** ["ODP.NET Types Overview"](#) on page 3-46 for a list of all ODP.NET types

[Table 3–12](#) lists the valid type accessors that ODP.NET uses to obtain ODP.NET types for an Oracle native type.

**Table 3–12 ODP.NET Type Accessors**

Oracle Native Data Type	ODP.NET Type	Typed Accessor
BFILE	OracleBFile	GetOracleBFile
BINARY_DOUBLE	OracleDecimal	GetOracleDecimal
BINARY_FLOAT	OracleDecimal	GetOracleDecimal
BLOB	OracleBlob	GetOracleBlob
	OracleBlob	GetOracleBlobForUpdate
	OracleBinary	GetOracleBinary
CHAR	OracleString	GetOracleString

**Table 3–12 (Cont.) ODP.NET Type Accessors**

Oracle Native Data Type	ODP.NET Type	Typed Accessor
CLOB	OracleClob	GetOracleClob
	OracleClob	GetOracleClobForUpdate
	OracleString	GetOracleString
DATE	OracleDate	GetOracleDate
INTERVAL DAY TO SECOND	OracleIntervalDS	GetOracleIntervalDS
INTERVAL YEAR TO MONTH	OracleIntervalYM	GetOracleIntervalYM
LONG	OracleString	GetOracleString
LONG RAW	OracleBinary	GetOracleBinary
NCHAR	OracleString	GetOracleString
NCLOB	OracleString	GetOracleString
NUMBER	OracleDecimal	GetOracleDecimal
NVARCHAR2	OracleString	GetOracleString
RAW	OracleBinary	GetOracleBinary
REF	OracleRef	GetOracleRef
ROWID	OracleString	GetOracleString
TIMESTAMP	OracleTimeStamp	GetOracleTimeStamp
TIMESTAMP WITH LOCAL TIME ZONE	OracleTimeStampLTZ	GetOracleTimeStampLTZ
TIMESTAMP WITH TIME ZONE	OracleTimeStampTZ	GetOracleTimeStampTZ
UROWID	OracleString	GetOracleString
VARCHAR2	OracleString	GetOracleString
XMLType	OracleString	GetOracleString
	OracleXmlType	GetOracleXmlType

## Obtaining LONG and LONG RAW Data

ODP.NET fetches and caches rows from the database during the Read method invocations on the OracleDataReader object. The amount of LONG and LONG RAW column data that is retrieved from this operation is determined by InitialLONGFetchSize. The different behaviors observed when InitialLONGFetchSize is set to 0, greater than 0, and -1 are explained in the following sections.

---

**Note:** ODP.NET does not support the CommandBehavior.SequentialAccess enumeration value. Therefore, LONG and LONG RAW data can be fetched randomly.

---

### Setting InitialLONGFetchSize to Zero or a Value Greater than Zero

The specified amount of InitialLONGFetchSize characters or bytes for LONG or LONG RAW column data is retrieved into the cache during the Read method invocations on the OracleDataReader object.

By default, `InitialLONGFetchSize` is set to 0. In this case, ODP.NET does not fetch any LONG or LONG RAW column data during the `Read` method invocations on the `OracleDataReader` object. The LONG or LONG RAW data is fetched when the typed accessor method is explicitly invoked for the LONG or LONG RAW column, which incurs a database round-trip because no data is cached.

If `InitialLONGFetchSize` is set to a value greater than 0, that amount of specified data is cached by ODP.NET during the `Read` method invocations on the `OracleDataReader` object. If the application requests an amount of data less than or equal to the `InitialLONGFetchSize` through the typed accessor methods, no database round-trip is incurred. However, an additional database round-trip is required to fetch data beyond `InitialLONGFetchSize`.

To obtain data beyond the `InitialLONGFetchSize` characters or bytes, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

To be able to fetch the entire LONG or LONG RAW data without having a primary key column, a ROWID, or unique columns in the select list, set the size of the `InitialLONGFetchSize` property on the `OracleCommand` object to equal or greater than the number of characters or bytes needed to be retrieved.

The LONG or LONG RAW data is returned when the appropriate typed accessor method (`GetChars`, `GetOracleString`, or `GetString` for LONG or `GetOracleBinary` or `GetBytes` for LONG RAW) is called on the `OracleDataReader` object.

### Setting InitialLONGFetchSize to -1

By setting `InitialLONGFetchSize` to -1, it is possible to fetch the entire LONG or LONG RAW data from the database for a select query, without requiring a primary key, ROWID, or unique column in the select list.

When `InitialLONGFetchSize` is set to -1, the entire LONG or LONG RAW data is retrieved and cached during `Read` method invocations on the `OracleDataReader` object. Calls to `GetString`, `GetOracleString`, `GetChars`, `GetBytes`, or `GetOracleBinary` in the `OracleDataReader` return the entire column data.

## Obtaining LOB Data

ODP.NET fetches and caches rows from the database during the `Read` method invocations on the `OracleDataReader` object. The amount of LOB column data that is retrieved from this operation is determined by `InitialLOBFetchSize`.

The following sections explain the different behaviors observed when `InitialLOBFetchSize` is set to 0, greater than 0, and -1.

### Setting InitialLOBFetchSize to Zero

By default, when the `InitialLOBFetchSize` property is 0, the `GetOracleBlob` and `GetOracleClob` methods can be invoked on the `OracleDataReader` object to obtain `OracleBlob` and `OracleClob` objects.

The following is a complete list of typed accessor methods that an application can call for the CLOB and BLOB columns, if `InitialLOBFetchSize` is set to 0:



- Methods callable for BLOB column
  - GetBytes
  - GetValue
  - GetValues
  - GetOracleBinary
  - GetOracleBlob
  - GetOracleBlobForUpdate
  - GetOracleValue
  - GetOracleValues
- Methods callable for CLOB column
  - GetChars
  - GetString
  - GetValue
  - GetValues
  - GetOracleString
  - GetOracleClob
  - GetOracleClobForUpdate
  - GetOracleValue
  - GetOracleValues

### Setting InitialLOBFetchSize to a Value Greater than Zero

If `InitialLOBFetchSize` is set to a value greater than 0, ODP.NET caches LOB data up to `InitialLOBFetchSize` characters or bytes for each LOB selected during the `Read` method invocations on the `OracleDataReader` object.

This section discusses the ways to fetch beyond the `InitialLOBFetchSize` characters or bytes that are cached. The functionality has changed from Oracle Database 10g release 2 (10.2) and later.

**Obtaining Additional Data Prior to Oracle Database 10g Release 2 (10.2)** With releases prior to Oracle Database 10g release 2 (10.2), obtaining data beyond `InitialLOBFetchSize` characters or bytes requires one of the following in the query select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

The requested LOB data is fetched from the database when the appropriate typed accessor method is called on the `OracleDataReader` object.

To be able to fetch the entire LOB data without having a primary key column, a ROWID, or unique columns in the select list, set the size of the `InitialLOBFetchSize` property on the `OracleCommand` object to equal or greater than the number of characters or bytes needed to be retrieved.

When the `InitialLOBFetchSize` property is set to a nonzero value, the `GetOracleBlob`, `GetOracleClob`, `GetOracleBlobForUpdate`, and `GetOracleClobForUpdate` typed accessor methods are disabled.

**Obtaining Additional Data From Oracle Database 10g Release 2 (10.2) and Later** Starting with Oracle Database 10g release 2 (10.2), the entire LOB data is returned when a typed accessor is invoked, regardless of the value set to the `InitialLOBFetchSize` property. Primary key, ROWID, or unique columns are not required to be in the query select list to obtain data beyond the specified `InitialLOBFetchSize`.

The `GetOracleBlob`, `GetOracleClob`, `GetOracleBlobForUpdate`, and `GetOracleClobForUpdate` methods can now be invoked even if `InitialLOBFetchSize` is greater than 0, starting with Oracle Database 10g release 2.

The following is a complete list of typed accessor methods that an application can call for the CLOB and BLOB columns if `InitialLOBFetchSize` is set to a value greater than 0:

- Methods callable for BLOB column
  - `GetBytes`
  - `GetValue`
  - `GetValues`
  - `GetOracleBinary`
  - `GetOracleBlob`
  - `GetOracleBlobForUpdate`
  - `GetOracleValue`
  - `GetOracleValues`
- Methods callable for CLOB column
  - `GetChars`
  - `GetString`
  - `GetValue`
  - `GetValues`
  - `GetOracleString`
  - `GetOracleClob`
  - `GetOracleClobForUpdate`
  - `GetOracleValue`
  - `GetOracleValues`

### Setting InitialLOBFetchSize to -1

By setting `InitialLOBFetchSize` to -1, it is possible to fetch the entire LOB data from the database for a select query, without requiring a primary key, ROWID, or unique column in the select list. When `InitialLOBFetchSize` is set to -1, the entire LOB column data is fetched and cached during the `Read` method invocations on the `OracleDataReader` object. Calls to `GetString`, `GetOracleString`, `GetChars`, `GetBytes`, or `GetOracleBinary` in the `OracleDataReader` allow retrieving all data.

**Methods Supported for InitialLOBFetchSize of -1** This section lists supported and not supported methods for the CLOB and BLOB data types when the `InitialLOBFetchSize` property is set to -1.

[Table 3–13](#) lists supported and not supported methods for the CLOB data types.

**Table 3–13 OracleDataReader CLOB Methods**

Supported	Not Supported
<code>GetChars</code>	<code>GetOracleClob</code>
<code>GetString</code>	<code>GetOracleClobForUpdate</code>
<code>GetValue</code>	
<code>GetValues</code>	
<code>GetOracleString</code>	
<code>GetOracleValue</code>	
<code>GetOracleValues</code>	

[Table 3–14](#) lists supported and not supported methods for the BLOB data types.

**Table 3–14 OracleDataReader BLOB Methods**

Supported	Not Supported
<code>GetBytes</code>	<code>GetOracleBlob</code>
<code>GetValue</code>	<code>GetOracleBlobForUpdate</code>
<code>GetValues</code>	
<code>GetOracleBinary</code>	
<code>GetOracleValue</code>	
<code>GetOracleValues</code>	

### Performance Considerations Related to the InitialLOBFetchSize Property

This section discusses the advantages and disadvantages of the various `InitialLOBFetchSize` property settings in different situations. It also discusses ways to enhance performance, depending on which database release you are using.

**Prior to Oracle Database 10g Release 2 (10.2)** Setting the `InitialLOBFetchSize` property to a nonzero value can improve performance in certain cases. Using the `InitialLOBFetchSize` property can provide better performance than retrieving the underlying LOB data using `OracleBlob` or `OracleClob` objects. This is true if an application does not need to obtain `OracleBlob` and `OracleClob` objects from the `OracleDataReader` object and the size of the LOB column data is not very large. The `InitialLOBFetchSize` property is particularly useful in cases where the size of the LOB column data returned by the query is approximately the same for all the rows.

It is generally recommended that the `InitialLOBFetchSize` property be set to a value larger than the size of the LOB data for more than 80% of the rows returned by the query. For example, if the size of the LOB data is less than 1 KB in 80% of the rows, and more than 1 MB for 20% of the rows, set the `InitialLOBFetchSize` property to 1 KB.

**See Also:**

- ["LOB Support"](#) on page 3-61
- ["InitialLOBFetchSize"](#) on page 5-18
- ["InitialLONGFetchSize"](#) on page 5-20

**Oracle Database 10g Release 2 (10.2) and Later** An application does not have to choose between performance and `OracleBlob` and `OracleClob` functionality. Setting the `InitialLOBFetchSize` property results in a performance boost and still gives the flexibility to use the `OracleBlob` and `OracleClob` objects.

If the size of the LOB data is unknown or if the LOB data size varies irregularly, then it is better to leave the `InitialLOBFetchSize` property to its default value of 0. This still gives better performance in most cases.

Setting the `InitialLOBFetchSize` property to a size equal to or greater than the LOB data size for most rows improves performance. It is generally recommended that the `InitialLOBFetchSize` property be set to a value larger than the size of the LOB data for more than 80% of the rows returned by the query. For example, if the size of the LOB data is less than 1 KB in 80% of the rows, and more than 1 MB for 20% of the rows, set the `InitialLOBFetchSize` property to 1 KB.

**See Also:**

- ["LOB Support"](#) on page 3-61
- ["InitialLOBFetchSize"](#) on page 5-18
- ["InitialLONGFetchSize"](#) on page 5-20

## Controlling the Number of Rows Fetched in One Database Round-Trip

Application performance depends on the number of rows the application needs to fetch, and the number of database round-trips that are needed to retrieve them.

### Use of FetchSize

The `FetchSize` property represents the total memory size in bytes that ODP.NET allocates to cache the data fetched from a database round-trip.

The `FetchSize` property can be set either on the `OracleCommand` or the `OracleDataReader` object, depending on the situation. Additionally, the `FetchSize` property of the `OracleCommand` object is inherited by the `OracleDataReader` object and can be modified.

If the `FetchSize` property is set on the `OracleCommand` object, then the newly created `OracleDataReader` object inherits the `FetchSize` property of the `OracleCommand` object. This inherited `FetchSize` value can be left as is, or modified to override the inherited value. The `FetchSize` property of the `OracleDataReader` object can be changed before the first `Read` method invocation, which allocates memory specified by the `FetchSize` property. All subsequent fetches from the database use the same cache allocated for that `OracleDataReader` object. Therefore, changing the `FetchSize` value after the first `Read` method invocation has no effect.

### Fine-Tuning FetchSize

By fine-tuning the `FetchSize` property, applications can control memory usage and the number of rows fetched in one database round-trip for better performance. For example, if a query returns 100 rows and each row takes 1024 bytes, then setting the

`FetchSize` property to 102400 takes just one database round-trip to fetch 100 rows. For the same query, if the `FetchSize` property is set to 10240, it takes 10 database round-trips to retrieve 100 rows. If the application requires all the rows to be fetched from the result set, the first scenario is faster than the second. However, if the application requires just the first 10 rows from the result set, the second scenario can perform better because it fetches only 10 rows, not 100 rows.

### Using the RowSize Property

The `RowSize` property of the `OracleCommand` object is populated with the row size (in bytes) after an execution of a `SELECT` statement. The `FetchSize` property can then be set to a value relative to the `RowSize` property by setting it to the result of multiplying the `RowSize` value times the number of rows to fetch for each database round-trip.

For example, setting the `FetchSize` to `RowSize * 10` forces the `OracleDataReader` object to fetch exactly 10 rows for each database round-trip. Note that the `RowSize` value does not change due to the data length in each individual column. Instead, the `RowSize` value is determined strictly from the metadata information of the database table(s) that the `SELECT` statement is executed against.

The `RowSize` property can be used to set the `FetchSize` property at design time or at run time, as described in the following sections.

**Setting FetchSize Value in the Registry** The `HKLM\Software\Oracle\ODP.NET\version\FetchSize` registry entry can be set to specify the default result set fetch size (in bytes) for all applications that use that particular version of ODP.NET or the `FetchSize` attribute in the application configuration or `web.config` file can specify the default value for a given application. By default, the fetch size is 131072 bytes. This value can be overridden programmatically by having the applications set the `FetchSize` property on either the `OracleCommand` or the `OracleDataReader` at run time.

**Setting FetchSize Value at Design Time** If the row size for a particular `SELECT` statement is already known from a previous execution, the `FetchSize` value of the `OracleCommand` object can be set at design time to the result of multiplying that row size times the number of rows the application wishes to fetch for each database round-trip. The `FetchSize` value set on the `OracleCommand` object is inherited by the `OracleDataReader` object that is created by the `ExecuteReader` method invocation on the `OracleCommand` object. Rather than setting the `FetchSize` value on the `OracleCommand` object, the `FetchSize` value can also be set on the `OracleDataReader` object directly. In either case, the `FetchSize` value is set at design time, without accessing the `RowSize` property value at run time.

**Setting FetchSize Value at Run Time** Applications that do not know the row size at design time can use the `RowSize` property of the `OracleCommand` object to set the `FetchSize` property of the `OracleDataReader` object. The `RowSize` property provides a dynamic way of setting the `FetchSize` property based on the size of a row.

After an `OracleDataReader` object is obtained by invoking the `ExecuteReader` method on the `OracleCommand` object, the `RowSize` property is populated with the size of the row (in bytes). By using the `RowSize` property, the application can dynamically set the `FetchSize` property of the `OracleDataReader` object to the product of the `RowSize` property value multiplied by the number of rows the application wishes to fetch for each database round-trip. In this scenario, the `FetchSize` property is set by accessing the `RowSize` property at run time.

## PL/SQL REF CURSOR and OracleRefCursor

The `REF CURSOR` is a data type in the Oracle PL/SQL language. It represents a cursor or a result set in Oracle Database. The `OracleRefCursor` object is a corresponding ODP.NET type for the `REF CURSOR` type.

This section discusses the following aspects of using the `REF CURSOR` data type and `OracleRefCursor` objects:

- [Obtaining an OracleRefCursor Object](#)
- [Obtaining a REF CURSOR Data Type](#)
- [Populating an OracleDataReader from a REF CURSOR](#)
- [Populating the DataSet from a REF CURSOR](#)
- [Populating an OracleRefCursor from a REF CURSOR](#)
- [Updating a DataSet Obtained from a REF CURSOR](#)
- [Behavior of ExecuteScalar Method for REF CURSOR](#)
- [Passing a REF CURSOR to a Stored Procedure](#)

### Obtaining an OracleRefCursor Object

There are no constructors for `OracleRefCursor` objects. They can be acquired only as parameter values from PL/SQL stored procedures, stored functions, or anonymous blocks.

An `OracleRefCursor` object is a connected object. The connection used to execute the command returning an `OracleRefCursor` object is required for its lifetime. Once the connection associated with an `OracleRefCursor` object is closed, the `OracleRefCursor` object cannot be used.

### Obtaining a REF CURSOR Data Type

A `REF CURSOR` data type can be obtained as an `OracleDataReader`, `DataSet`, or `OracleRefCursor` object. If the `REF CURSOR` data type is obtained as an `OracleRefCursor` object, it can be used to create an `OracleDataReader` object or populate a `DataSet` from it. When accessing a `REF CURSOR` data type, always bind it as an `OracleDbType.RefCursor` parameter.

### Populating an OracleDataReader from a REF CURSOR

A `REF CURSOR` data type can be obtained as an `OracleDataReader` object by calling the `ExecuteReader` method of the `OracleCommand` object. The output parameter with the `OracleDbType` property set is bound to `OracleDbType.RefCursor`. None of the output parameters of type `OracleDbType.RefCursor` is populated after the `ExecuteReader` method is invoked.

If there are multiple output `REF CURSOR` parameters, use the `NextResult` method of the `OracleDataReader` object to access the next `REF CURSOR` data type. The `OracleDataReader.NextResult` method provides sequential access to the `REF CURSOR` data types; only one `REF CURSOR` data type can be accessed at a given time.

The order in which `OracleDataReader` objects are created for the corresponding `REF CURSOR` data types depends on the order in which the parameters are bound. If a PL/SQL stored function returns a `REF CURSOR` data type, then it becomes the first `OracleDataReader` object and all the output `REF CURSOR` data types follow the order in which the parameters are bound.

## Populating the DataSet from a REF CURSOR

For the `Fill` method to populate the `DataSet` properly, the `SelectCommand` property of the `OracleDataAdapter` class must be bound with an output parameter of type `OracleDbType.RefCursor`. If the `Fill` method is successful, the `DataSet` is populated with a `DataTable` that represents a REF CURSOR data type.

If the command execution returns multiple REF CURSOR data types, the `DataSet` is populated with multiple `DataTable` objects.

With Oracle Data Provider for .NET release 11.1.0.6.20, the extended property, `RefCursorName`, has been introduced on the `DataTable`, to identify the REF CURSOR that populates the `DataTable`.

This property is particularly useful when a `DataSet` is being populated with more than one REF CURSOR, one or more of which is `NULL`. For example, if a `DataSet` is populated by executing a stored procedure that returns three REF CURSORS and the second REF CURSOR is `NULL`, the `RefCursorName` property value for the first `DataTable` is `RefCursor` and for the second `DataTable`, `RefCursor2`. No `DataTable` is populated for the `NULL` REF CURSOR.

## Populating an OracleRefCursor from a REF CURSOR

When the `ExecuteNonQuery` method is invoked on a command that returns one or more REF CURSOR data types, each of the `OracleCommand` parameters that are bound as an `OracleDbType.RefCursor` gets a reference to an `OracleRefCursor` object.

To create an `OracleDataReader` object from an `OracleRefCursor` object, invoke the `GetDataReader` method from the `OracleRefCursor` object. Subsequent calls to the `GetDataReader` method return a reference to the same `OracleDataReader` object.

To populate a `DataSet` with an `OracleRefCursor` object, the application can invoke a `Fill` method of the `OracleDataAdapter` class that takes an `OracleRefCursor` object. Similar to the `OracleDataReader` object, an `OracleRefCursor` object is forward-only. Therefore, once a row is read from an `OracleRefCursor` object, that same row cannot be obtained again from it unless it is populated again from a query.

When multiple REF CURSOR data types are returned from a command execution as `OracleRefCursor` objects, the application can choose to create an `OracleDataReader` object or populate a `DataSet` with a particular `OracleRefCursor` object. All the `OracleDataReader` objects or `DataSet` objects created from the `OracleRefCursor` objects are active at the same time, and can be accessed in any order.

## Updating a DataSet Obtained from a REF CURSOR

REF CURSOR types cannot be updated. However, data that is retrieved into a `DataSet` can be updated. Therefore, the `OracleDataAdapter` class requires a custom SQL statement to flush any REF CURSOR data updates to the database.

The `OracleCommandBuilder` object cannot be used to generate SQL statements for REF CURSOR updates.

## Behavior of ExecuteScalar Method for REF CURSOR

The `ExecuteScalar` method returns the value of the first column of the first row of the REF CURSOR if it is one of the following:

- A return value of a stored function execution

- The first bind parameter of a stored procedure execution

**See Also:** *Oracle Database Application Developer's Guide - Large Objects* for more information

## Passing a REF CURSOR to a Stored Procedure

An application can retrieve a REF CURSOR type from a PL/SQL stored procedure or function and pass it to another stored procedure or function. This feature is useful in scenarios where a stored procedure or a function returns a REF CURSOR type to the .NET application, and based on the application logic, the application passes this REF CURSOR to another stored procedure for processing. Note that if you retrieve the data from a REF CURSOR type in the .NET application, you cannot pass it back to another stored procedure.

The following example demonstrate passing a REF CURSOR:

```
/*
connect scott/tiger@oracle
create table test (col1 number);
insert into test(col1) values (1);
commit;

create or replace package testPkg as type empCur is REF Cursor;
end testPkg;
/

create or replace procedure testSP(param1 IN testPkg.empCur, param2 OUT NUMBER)
as
begin
FETCH param1 into param2;
end;
/
*/

// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;

class InRefCursorParameterSample
{
    static void Main()
    {
        OracleConnection conn = new OracleConnection
            ("User Id=scott; Password=tiger; Data Source=oracle");

        conn.Open(); // Open the connection to the database

        // Command text for getting the REF Cursor as OUT parameter
        String cmdTxt1 = "begin open :1 for select col1 from test; end;";

        // Command text to pass the REF Cursor as IN parameter
        String cmdTxt2 = "begin testSP (:1, :2); end;";

        // Create the command object for executing cmdTxt1 and cmdTxt2
        OracleCommand cmd = new OracleCommand(cmdTxt1, conn);
```



```

// Bind the Ref cursor to the PL/SQL stored procedure
OracleParameter outRefPrm = cmd.Parameters.Add("outRefPrm",
    OracleDbType.RefCursor, DBNull.Value, ParameterDirection.Output);

cmd.ExecuteNonQuery(); // Execute the anonymous PL/SQL block

// Reset the command object to execute another anonymous PL/SQL block
cmd.Parameters.Clear();
cmd.CommandText = cmdTxt2;

// REF Cursor obtained from previous execution is passed to this
// procedure as IN parameter
OracleParameter inRefPrm = cmd.Parameters.Add("inRefPrm",
    OracleDbType.RefCursor, outRefPrm.Value, ParameterDirection.Input);

// Bind another Number parameter to get the REF Cursor column value
OracleParameter outNumPrm = cmd.Parameters.Add("outNumPrm",
    OracleDbType.Int32, DBNull.Value, ParameterDirection.Output);

cmd.ExecuteNonQuery(); //Execute the stored procedure

// Display the out parameter value
Console.WriteLine("out parameter is: " + outNumPrm.Value.ToString());
}
}

```

## LOB Support

ODP.NET provides an easy and optimal way to access and manipulate large object (LOB) data types.

---



---

**Note:** SecureFiles can be used with existing ODP.NET LOB classes.

---



---

This section includes the following topics:

- [Large Character and Large Binary Data Types](#)
- [Oracle Data Provider for .NET LOB Objects](#)
- [Updating LOBs Using a DataSet](#)
- [Updating LOBs Using OracleCommand and OracleParameter](#)
- [Updating LOBs Using ODP.NET LOB Objects](#)
- [Temporary LOBs](#)

### Large Character and Large Binary Data Types

Oracle Database supports large character and large binary data types.

#### Large Character Data Types

- CLOB - Character data can store up to 4 gigabytes.
- NCHAR - Unicode National character set data can store up to 4 gigabytes.

#### Large Binary Data Types

- BLOB - Unstructured binary data can store up to 4 gigabytes.

- BFILE - Binary data stored in external file can store up to 4 gigabytes.

---

**Note:** LONG and LONG RAW data types are made available for backward compatibility in Oracle9i, but should not be used in new applications.

---

## Oracle Data Provider for .NET LOB Objects

ODP.NET provides three objects for manipulating LOB data: `OracleBFile`, `OracleBlob`, and `OracleClob`.

Table 3–15 shows the proper ODP.NET object to use for a particular Oracle LOB type.

**Table 3–15 ODP.NET LOB Objects**

Oracle LOB Type	ODP.NET LOB Object
BFILE	<code>OracleBFile</code>
BLOB	<code>OracleBlob</code>
CLOB	<code>OracleClob</code>
NCLOB	<code>OracleClob</code>

The ODP.NET LOB objects can be obtained by calling the proper typed accessor on the `OracleDataReader` object, or by calling the proper typed accessor as an output parameter on a command execution with the proper bind type.

All ODP.NET LOB objects inherit from the .NET `Stream` class to provide generic `Stream` operations. The LOB data (except for BFILE types) can be updated using the ODP.NET LOB objects by using methods such as `Write`. Data is not cached in the LOB objects when read and write operations are carried out. Therefore, each read or write request incurs a database round-trip. The `OracleClob` object overloads the `Read` method, providing two ways to read data from a CLOB. The `Read` method that takes a `byte[]` as the buffer populates it with CLOB data as Unicode byte array. The `Read` method that takes a `char[]` as the buffer populates it with Unicode characters.

Additional methods can also be found on the `OracleBFile` object. An `OracleBFile` object must be explicitly opened using the `OpenFile` method before any data can be read from it. To close a previously opened BFILE, use the `CloseFile` method.

Every ODP.NET LOB object is a connected object and requires a connection during its lifetime. If the connection associated with a LOB object is closed, then the LOB object is not usable and should be disposed of.

If an ODP.NET LOB object is obtained from an `OracleDataReader` object through a typed accessor, then its `Connection` property is set with a reference to the same `OracleConnection` object used by the `OracleDataReader` object. If a LOB object is obtained as an output parameter, then its `Connection` property is set with a reference to the same `OracleConnection` property used by the `OracleCommand` object. If a LOB object is obtained by invoking an ODP.NET LOB object constructor to create a temporary LOB, the `Connection` property is set with a reference to the `OracleConnection` object provided in the constructor.

The ODP.NET LOB object `Connection` property is read-only and cannot be changed during its lifetime. In addition, the ODP.NET LOB types object can be used only within the context of the same `OracleConnection` referenced by the ODP.NET LOB object. For example, the ODP.NET LOB `Connection` property must reference the same connection as the `OracleCommand` object if the ODP.NET LOB object is a parameter of

the `OracleCommand`. If that is not the case, ODP.NET raises an exception when the command is executed.

**See Also:** *Oracle Database Application Developer's Guide - Large Objects* for complete information about Oracle Database 10g LOBs and how to use them

## Updating LOBs Using a DataSet

BFILE and BLOB data are stored in the `DataSet` as byte arrays while CLOB and NCLOB data are stored as strings. In a similar manner to other types, an `OracleDataAdapter` object can be used to fill and update LOB data changes along with the use of the `OracleCommandBuilder` object for automatically generating SQL.

Note that an Oracle LOB column can store up to 4 GB of data. When the LOB data is fetched into the `DataSet`, the actual amount of LOB data the `DataSet` can hold for a LOB column is limited to the maximum size of a .NET string type, which is 2 GB. Therefore, when fetching LOB data that is greater than 2 GB, ODP.NET LOB objects must be used to avoid any data loss.

## Updating LOBs Using OracleCommand and OracleParameter

To update LOB columns, LOB data can be bound as a parameter for SQL statements, anonymous PL/SQL blocks, or stored procedures. The parameter value can be set as a .NET Framework type, ODP.NET type, or as an ODP.NET LOB object type. For example, when inserting .NET string data into a LOB column in an Oracle9i database or later, that parameter can be bound as `OracleDbType.Varchar2`. For a parameter whose value is set to an `OracleClob` object, the parameter should be bound as `OracleDbType.Clob`.

## Updating LOBs Using ODP.NET LOB Objects

Oracle BFILES cannot be updated; therefore, `OracleBFile` objects do not allow updates to BFILE columns.

Two requirements must be met to update LOB data using ODP.NET LOB objects:

1. A transaction must be started before a LOB column is selected.

The transaction must be started using the `BeginTransaction` method on the `OracleConnection` object before the command execution, so that the lock can be released when the `OracleTransaction.Commit` or `Rollback` method is invoked.

2. The row in which the LOB column resides must be locked; as part of an entire result set, or on a row-by-row basis.

- a. Locking the entire result set

Add the `FOR UPDATE` clause to the end of the `SELECT` statement. After execution of the command, the entire result set is locked.

- b. Locking the row - there are two options:

- Invoke one of the `OracleDataReader` typed accessors (`GetOracleClobForUpdate` or `GetOracleBlobForUpdate`) on the `OracleDataReader` object to obtain an ODP.NET LOB object, while also locking the current row.

This approach requires a primary key, unique column(s), or a ROWID in the result set because the `OracleDataReader` object must uniquely identify the row to re-select it for locking.

- Execute an `INSERT` or an `UPDATE` statement that returns a LOB in the `RETURNING` clause.

## Temporary LOBs

Temporary LOBs can be instantiated for `BLOB`, `CLOB`, and `NCLOB` objects. To instantiate an ODP.NET LOB object that represents a temporary LOB, the `OracleClob` or the `OracleBlob` constructor can be used.

Temporary ODP.NET LOB objects can be used for the following purposes:

- To initialize and populate a LOB column with empty or non-empty LOB data.
- To pass a LOB type as an input parameter to a SQL statement, an anonymous PL/SQL block, or a stored procedure.
- To act as the source or the destination of data transfer between two LOB objects as in the `CopyTo` operation.

---

---

**Note:** Temporary LOBs are not transaction aware. Commit and rollback operations do not affect the data referenced by a temporary LOB.

---

---

## ODP.NET XML Support

ODP.NET allows the extraction of data from relational and object-relational tables and views as XML documents. The use of XML documents for insert, update, and delete operations to the database is also allowed. Oracle Database supports XML natively in the database, through Oracle XML DB, a distinct group of technologies related to high-performance XML storage and retrieval. Oracle XML DB is an evolution of the database that encompasses both SQL and XML data models in a highly interoperable manner, providing native XML support.

For samples related to ODP.NET XML support, see the following directory:

`ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples`

This section includes these topics:

- [Supported XML Features](#)
- [OracleXmlType and Connection Dependency](#)
- [Updating XMLType Data in the Database](#)
- [Updating XML Data in OracleXmlType](#)
- [Characters with Special Meaning in XML](#)
- [Retrieving Query Result Set as XML](#)
- [Data Manipulation Using XML](#)

## Supported XML Features

XML support in ODP.NET provides the ability to do the following:

- Store XML data natively in the database as the Oracle database native type, `XMLType`.
- Access relational and object-relational data as XML data from an Oracle Database instance into the Microsoft .NET environment, and process the XML using the Microsoft .NET Framework.
- Save changes to the database using XML data.
- Execute XQuery statements.

**See Also:** ["XQuery Support"](#) on page 3-65

For the .NET application developer, these features include the following:

- Enhancements to the `OracleCommand`, `OracleConnection`, and `OracleDataReader` classes.
- The following XML-specific classes:
  - `OracleXmlType`  
`OracleXmlType` objects are used to retrieve Oracle native `XMLType` data.
  - `OracleXmlStream`  
`OracleXmlStream` objects are used to retrieve XML data from `OracleXmlType` objects as a read-only .NET Stream object.
  - `OracleXmlQueryProperties`  
`OracleXmlQueryProperties` objects represent the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Query`.
  - `OracleXmlSaveProperties`  
`OracleXmlSaveProperties` objects represent the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.

**See Also:**

- ["OracleCommand Class"](#) on page 5-2
- ["OracleXmlType Class"](#) on page 6-37
- ["OracleXmlStream Class"](#) on page 6-23
- ["OracleXmlQueryProperties Class"](#) on page 6-3
- ["OracleXmlSaveProperties Class"](#) on page 6-13
- *Oracle XML DB Developer's Guide*

## XQuery Support

Beginning with Oracle Database 10g release 2(10.2), ODP.NET supports the XQuery language through a native implementation of SQL/XML functions, `XMLQuery` and `XMLTable`. When executing XQuery statements, Oracle XML DB generally evaluates XQuery expressions by compiling them into the same underlying structures as relational queries. Queries are optimized, leveraging both relational-database and XQuery-specific optimization technologies, so that Oracle XML DB serves as a native XQuery engine.

The treatment of all XQuery expressions, whether natively compiled or evaluated functionally, is transparent: programmers do not need to change their code to take advantage of XQuery optimizations.

**See Also:** *Oracle XML DB Developer's Guide* to learn more about Oracle's XQuery support

## OracleXmlType and Connection Dependency

The read-only `Connection` property of the `OracleXmlType` class holds a reference to the `OracleConnection` object used to instantiate the `OracleXmlType` class.

How the `OracleXmlType` object obtains a reference to an `OracleConnection` object depends on how the `OracleXmlType` class is instantiated:

- Instantiated from an `OracleDataReader` class using the `GetOracleXmlType`, `GetOracleValue`, or `GetOracleValues` method:

The `Connection` property is set with a reference to the same `OracleConnection` object used by the `OracleDataReader` object.

- Instantiated by invoking an `OracleXmlType` constructor with one of the parameters of type `OracleConnection`:

The `Connection` property is set with a reference to the same `OracleConnection` object provided in the constructor.

- Instantiated by invoking an `OracleXmlType(OracleClob)` constructor:

The `Connection` property is set with a reference to the `OracleConnection` object used by the `OracleClob` object.

An `OracleXmlType` object that is associated with one connection cannot be used with a different connection. For example, if an `OracleXmlType` object is obtained using `OracleConnection A`, that `OracleXmlType` object cannot be used as an input parameter of a command that uses `OracleConnection B`. By checking the `Connection` property of the `OracleXmlType` objects, the application can ensure that `OracleXmlType` objects are used only within the context of the `OracleConnection` referenced by its connection property. Otherwise, ODP.NET raises an exception.

## Updating XMLType Data in the Database

Updating `XMLType` columns does not require a transaction. However, encapsulating the entire database update process within a transaction is highly recommended. This allows the updates to be rolled back if there are any errors.

`XMLType` columns in the database can be updated using Oracle Data Provider for .NET in a few ways:

- [Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder](#)
- [Updating with OracleCommand and OracleParameter](#)

### Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder

If the `XMLType` column is fetched into the `DataSet`, the `XMLType` data is represented as a .NET `String`.

Modifying `XMLType` data in the `DataSet` does not require special treatment. `XMLType` data can be modified in the same way as any data that is stored in the `DataSet`. When a change is made and the `OracleDataAdapter.Update` method is invoked, the `OracleDataAdapter` object ensures that the `XMLType` data is handled

properly. The `OracleDataAdapter` object uses any custom SQL `INSERT`, `UPDATE`, or `DELETE` statements that are provided. Otherwise, valid SQL statements are generated by the `OracleCommandBuilder` object as needed to **flush** the changes to the database.

### Updating with `OracleCommand` and `OracleParameter`

The `OracleCommand` class provides a powerful way of updating `XMLType` data, especially with the use of an `OracleParameter` object. To update columns in a database table, the new value for the column can be passed as an input parameter of a command.

**Input Binding** To update an `XMLType` column in the database, a SQL statement can be executed using static values. In addition, input parameters can be bound to SQL statements, anonymous PL/SQL blocks, or stored procedures to update `XMLType` columns. The parameter value can be set as .NET Framework Types, ODP.NET Types, or `OracleXmlType` objects.

While `XMLType` columns can be updated using an `OracleXmlType` object, having an instance of an `OracleXmlType` class does not guarantee that the `XMLType` column in the database can be updated.

**Setting `XMLType` Column to NULL Value** Applications can set an `XMLType` column in the database to a `NULL` value, with or without input binding, as follows:

- Setting `NULL` values in an `XMLType` column with input binding

To set the `XMLType` column to `NULL`, the application can bind an input parameter whose value is `DBNull.Value`. This indicates to the `OracleCommand` object that a `NULL` value is to be inserted.

Passing in a null `OracleXmlType` object as an input parameter does not insert a `NULL` value into the `XMLType` column. In this case, the `OracleCommand` object raises an exception.

- Setting `NULL` Values in an `XMLType` Column without input binding

The following example demonstrates setting `NULL` values in an `XMLType` column without input binding:

```
// Create a table with an XMLType column in the database
CREATE TABLE XML_TABLE(NUM_COL number, XMLTYPE_COL xmltype);
```

An application can set a `NULL` value in the `XMLType` column by explicitly inserting a `NULL` value or by not inserting anything into that column as in the following examples:

```
insert into xml_table(xmltype_col) values (NULL);
```

```
update xml_table t set t.xmltype_col=NULL;
```

**Setting `XMLType` Column to Empty XML Data** The `XMLType` column can be initialized with empty XML data, using a SQL statement:

```
// Create a table with an XMLType column in the database
CREATE TABLE XML_TABLE(NUM_COL number, XMLTYPE_COL xmltype);
```

```
INSERT INTO XML_TABLE (NUM_COL, XMLTYPE_COL) VALUES (4,
XMLType.createxml('<DOC/>'));
```

## Updating XML Data in OracleXmlType

The following are ways that XML data can be updated in an `OracleXmlType` object.

- The XML data can be updated by passing an XPATH expression and the new value to the `Update` method on the `OracleXmlType` object.
- The XML data can be retrieved on the client side as the .NET Framework `XmlDocument` object using the `GetXmlDocument` method on the `OracleXmlType` object. This XML data can then be manipulated using suitable .NET Framework classes. A new `OracleXmlType` can be created with the updated XML data from the .NET Framework classes. This new `OracleXmlType` is bound as an input parameter to an update or insert statement.

## Characters with Special Meaning in XML

The following characters in [Table 3–16](#) have special meaning in XML. For more information, refer to the XML 1.0 specifications

**Table 3–16 Characters with Special Meaning in XML**

Character	Meaning in XML	Entity Encoding
<	Begins an XML tag	&lt;
>	Ends an XML tag	&gt;
"	Quotation mark	&quot;
'	Apostrophe or single quotation mark	&apos;
&	Ampersand	&amp;

When these characters appear as data in an XML element, they are replaced with their equivalent entity encoding.

Also certain characters are not valid in XML element names. When SQL identifiers (such as column names) are mapped to XML element names, these characters are converted to a sequence of hexadecimal digits, derived from the Unicode encoding of the character, bracketed by an introductory underscore, a lowercase `x` and a trailing underscore. A blank space is not a valid character in an XML element name. If a SQL identifier contains a space character, then in the corresponding XML element name, the space character is replaced by `_x0020_`, which is based on Unicode encoding of the space character.

## Retrieving Query Result Set as XML

This section discusses retrieving the result set from a SQL query as XML data.

### Handling Date and Time Format

[Table 3–17](#) lists the date and time format handling when retrieving data, for different database releases.



**Table 3–17 Date and Time Format Handling When Retrieving Data**

Database Release	Date and Time Format Supported
Oracle9i release 2 (9.2.x) and Oracle Database 10g	<p>Oracle <code>DATE</code> type data is retrieved in the format specified using the <code>NLS_DATE_FORMAT</code> in the session.</p> <p><code>TIMESTAMP</code> and <code>TIMESTAMP WITH TIME ZONE</code> type data is retrieved in the format specified using the <code>NLS_TIMESTAMP_FORMAT</code> and the <code>NLS_TIMESTAMP_TZ_FORMAT</code> in the session.</p> <p>If the result XML document is used to save changes back to the database, then all <code>DATE</code> and <code>TIMESTAMP</code> data must be retrieved in the XML document as the following ISO Date and Time Format: <code>YYYY-MM-DDThh:mm:ss.sss</code> (ISO Format notation).</p> <p>To do this, before the query is executed, the application must explicitly perform an <code>ALTER SESSION</code> statement on the session for the following NLS session parameters:</p> <ul style="list-style-type: none"> <li>■ <code>NLS_DATE_FORMAT</code> - Must be set to the following Oracle Date and Time Format: <code>YYYY-MM-DD" T" HH24 : MI : SS</code></li> <li>■ <code>NLS_TIMESTAMP_FORMAT</code> - Must be set to the following Oracle Date and Time Format: <code>YYYY-MM-DD" T" HH24 : MI : SS . FF3</code></li> <li>■ <code>NLS_TIMESTAMP_TZ_FORMAT</code> - Must be set to the following Oracle Date and Time Format: <code>YYYY-MM-DD" T" HH24 : MI : SS . FF3</code></li> </ul>
Oracle Database 10g release 2 (10.2) or later	<p>The generated XML <code>DATE</code> and <code>TIMESTAMP</code> formats are based on the standard XML Schema formats.</p> <p>For more information on the XML Schema specification, see <a href="http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats">http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats</a></p>

### Characters with Special Meaning in Column Data

If the data in any of the select list columns in the query contains any characters with special meaning in XML (see Table 3–16), these characters are replaced with their corresponding entity encoding in the result XML document.

The following examples demonstrate how ODP.NET handles the angle bracket characters in the column data:

```

/* Database Setup
connect scott/tiger@oracle
drop table specialchars;
create table specialchars ("id" number, name varchar2(255));
insert into specialchars values (1, '<Jones>');
commit;
*/

// C#

using System;
using System.Data;
using System.Xml;
using Oracle.DataAccess.Client;

class QueryResultAsXMLSample
{
    static void Main()
    {

```

```
OracleConnection con = new OracleConnection();

con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
con.Open();

// Create the command
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to query.
cmd.XmlCommandType = OracleXmlCommandType.Query;

// Set the SQL query
cmd.CommandText = "select * from specialchars";

// Set command properties that affect XML query behavior.
cmd.BindByName = true;

// Set the XML query properties
cmd.XmlQueryProperties.MaxRows = -1;

// Get the XML document as an XmlReader.
XmlReader xmlReader = cmd.ExecuteXmlReader();
XmlDocument xmlDocument = new XmlDocument();

xmlDocument.PreserveWhitespace = true;
xmlDocument.Load(xmlReader);
Console.WriteLine(xmlDocument.OuterXml);

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
}
}
```

The following XML document is generated for that table: The XML entity encoding that represents the angle brackets appears in bold.

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <id>1</id >
    <NAME>&lt;Jones&gt;</NAME>
  </ROW>
</ROWSET>
```

### Characters in Table or View Name

If a table or view name has any non-alphanumeric characters other than an underscore (`_`), the table or view name must be enclosed in quotation marks.

For example, to select all entries from a table with the name `test'ing`, the `CommandText` property of the `OracleCommand` object must be set to the following string:

```
"select * from \"test'ing\"";
```

### Case-Sensitivity in Column Name to XML Element Name Mapping

The mapping of SQL identifiers (column names) to XML element names is case-sensitive, and the element names are in exactly the same case as the column names of the table or view.

However, the root tag and row tag names are case-insensitive. The following example demonstrates case-sensitivity in this situation:

```
//Create the following table
create table casesensitive_table ("Id" number, NAME varchar2(255));

//insert name and id
insert into casesensitive_table values(1, 'Smith');
```

The following XML document is generated:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <Id>1</Id>
      <NAME>Smith</NAME>
    </ROW>
  </ROWSET>
```

Note that the element name for the Id column matches the case of the column name.

### Column Name to XML Element Name Mapping

For each row generated by the SQL query, the SQL identifier (column name) maps to an XML element in the generated XML document, as shown in the following example:

```
// Create the following table
create table emp_table (EMPLOYEE_ID NUMBER(4), LAST_NAME varchar2(25));
// Insert some data
insert into emp_table values(205, 'Higgins');
```

The SQL query, `SELECT * FROM EMP_TABLE`, generates the following XML document:

```
<?XML version="1.0"?>
  <ROWSET>
    <ROW>
      <EMPLOYEE_ID>205</EMPLOYEE_ID>
      <LAST_NAME>Higgins</LAST_NAME>
    </ROW>
  </ROWSET>
```

The `EMPLOYEE_ID` and `LAST_NAME` database columns of the `employees` table map to the `EMPLOYEE_ID` and `LAST_NAME` elements of the generated XML document.

This section demonstrates how Oracle database handles the mapping of SQL identifiers to XML element names, when retrieving query results as XML from the database. The demonstration uses the `specialchars` table involving the `some id` column.

```
// Create the specialchars table
create table specialchars ("some id" number, name varchar2(255));
```

Note that the `specialchars` table has a column named `some id` that contains a blank space character. The space character is not allowed in an XML element name.

When retrieving the query results as XML, the SQL identifiers in the query select list can contain characters that are not valid in XML element names. When these SQL

identifiers (such as column names) are mapped to XML element names, each of these characters is converted to a sequence of hexadecimal digits, derived from the Unicode encoding of the characters, bracketed by an introductory underscore, a lowercase x, and a trailing underscore.

Thus, the SQL query in the following example can be used to get a result as an XML document from the `specialchars` table:

```
select "some id", name from specialchars;
```

**See Also:** ["Characters with Special Meaning in XML"](#) on page 3-68

**Improving Default Mapping** You can improve the default mapping of SQL identifiers to XML element names by using the following techniques:

- Modify the source. Create an object-relational view over the source schema, and make that view the new source.
- Use cursor subqueries and cast-multiset constructs in the SQL query.
- Create an alias for the column or attribute names in the SQL query. Prefix the aliases with an at sign (@) to map them to XML attributes instead of XML elements.
- Modify the XML document. Use [Extensible Stylesheet Language Transformation \(XSLT\)](#) to transform the XML document. Specify the XSL document and parameters. The transformation is done automatically after the XML document is generated from the relational data. Note that this may have an impact on performance.
- Specify the name of the root tag and row tag used in the XML document.

### Object-Relational Data

ODP.NET can generate an XML document for data stored in object-relational columns, tables, and views, as shown in the following example:

```
// Create the following tables and types
CREATE TYPE "EmployeeType" AS OBJECT (EMPNO NUMBER, ENAME VARCHAR2(20));
/
CREATE TYPE EmployeeListType AS TABLE OF "EmployeeType";
/
CREATE TABLE mydept (DEPTNO NUMBER, DEPTNAME VARCHAR2(20),
                    EMPLIST EmployeeListType)
                    NESTED TABLE EMPLIST STORE AS EMPLIST_TABLE;
INSERT INTO mydept VALUES (1, 'depta',
                          EmployeeListType("EmployeeType"(1, 'empa')));
```

The following XML document is generated for the table:

```
<?xml version = "1.0"?>
<ROWSET>
  <ROW>
    <DEPTNO>1</DEPTNO>
    <DEPTNAME>depta</DEPTNAME>
    <EMPLIST>
      <EmployeeType>
        <EMPNO>1</EMPNO>
        <ENAME>empa</ENAME>
      </EmployeeType>
```

```

    </EMPLIST>
  </ROW>
</ROWSET>

```

ODP.NET encloses each item in a collection element, with the database type name of the element in the collection. The `mydept` table has a collection in the `EMPLIST` database column and each item in the collection is of type `EmployeeType`. Therefore, in the XML document, each item in the collection is enclosed in the type name `EmployeeType`, which appears in bold in the example.

### NULL Values

If any database row has a column with a NULL value, then that column does not appear for that row in the generated XML document.

## Data Manipulation Using XML

This section discusses making changes to the database data using XML.

### Handling Date and Time Format

Table 3–18 lists the date and time format handling when saving data, for different database releases.

**Table 3–18** *Date and Time Format Handling When Saving Data*

Database Release	Date and Time Format Supported
Oracle9i release 2 (9.2.x) and Oracle Database 10g	<p>All DATE, TIMESTAMP, and TIMESTAMP WITH TIME ZONE type data must be specified in the XML document in the ISO Date and Time Format <code>YYYY-MM-DDThh:mm:ss.SSS</code> (ISO Format notation).</p> <p>The following string is the ISO Date and Time Format notation represented in the Oracle Date and Time Format notation:  <code>YYYY-MM-DD"T"HH24:MI:SS.FF3</code>.</p> <p>In addition to using the ISO Format notation in the XML document, before the save is executed, the application must explicitly perform an <code>ALTER SESSION</code> command on the session for the following NLS session parameters:</p> <ul style="list-style-type: none"> <li>■ <code>NLS_DATE_FORMAT</code> - Must be set to the following Oracle Date and Time Format: <code>YYYY-MM-DD"T"HH24:MI:SS</code></li> <li>■ <code>NLS_TIMESTAMP_FORMAT</code> - Must be set to the following Oracle Date and Time Format:  <code>YYYY-MM-DD"T"HH24:MI:SS.FF3</code></li> <li>■ <code>NLS_TIMESTAMP_TZ_FORMAT</code> - Must be set to the following Oracle Date and Time Format:  <code>YYYY-MM-DD"T"HH24:MI:SS.FF3</code></li> </ul>
Oracle Database 10g release 2 (10.2) or later	<p>The generated XML DATE and TIMESTAMP formats are based on the standard XML Schema formats.</p> <p>For more information on the XML Schema specification, see <a href="http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats">http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats</a></p>

### Saving Changes Using XML

Changes can be saved to database tables and views using XML data. However, insert, update, and delete operations cannot be combined in a single XML document.

ODP.NET cannot accept a single XML document and determine which are insert, update, or delete changes.

The insert change must be in an XML document containing only rows to be inserted, the update changes only with rows to be updated, and the delete changes only with rows to be deleted.

For example, using the `employees` table that comes with the HR sample schema, you can specify the following query:

```
select employee_id, last_name from employees where employee_id = 205;
```

The following XML document is generated:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Higgins</LAST_NAME>
  </ROW>
</ROWSET>
```

To change the name of employee 205 from **Higgins** to **Smith**, specify the `employees` table and the XML data containing the changes as follows:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Smith</LAST_NAME>
  </ROW>
</ROWSET>
```

### Characters with Special Meaning in Column Data

If the data in any of the elements in the XML document contains characters that have a special meaning in XML (see [Table 3-16](#)), these characters must be replaced with appropriate entity encoding, or be preceded by an escape character in the XML document, so that the data is stored correctly in the database table column. Otherwise, ODP.NET throws an exception.

The following example demonstrates how ODP.NET handles the angle bracket special characters in the column data, using entity encoding:

```
// Create the following table
create table specialchars ("id" number, name varchar2(255));
```

The following XML document can be used to insert values (1, '<Jones>') into the `specialchars` table. The XML entity encoding that represents the angle brackets appears in bold.

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <id>1</id >
    <NAME>&lt;Jones&gt;</NAME>
  </ROW>
</ROWSET>
```

## Characters with Special Meaning in Table or View Name

If a table or view name has any non-alphanumeric characters other than an underscore (`_`), the table or view name must be enclosed in quotation marks.

For example, to save changes to a table with the name `test'ing`, the `OracleCommand.XmlSaveProperties.TableName` property must be set to `"\"test'ing\""`.

## Case-Sensitivity in XML Element Name to Column Name Mapping

For each XML element that represents a row of data in the XML document, the child XML elements map to database column names. The mapping of the child element name to the column name is always case-sensitive, but the root tag and row tag names are case-insensitive. The following example demonstrates this case-sensitivity:

```
//Create the following table
create table casesensitive_table ("Id" number, NAME varchar2(255));
```

The following XML document can be used to insert values (1, Smith) into the `casesensitive_table`:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <Id>1</Id>
      <NAME>Smith</NAME>
    </ROW>
  </ROWSET>
```

Note that the element name for the `Id` column matches the case of the column name.

## XML Element Name to Column Name Mapping

This section describes how Oracle database handles the mapping of XML element names to column names when using XML for data manipulation in the database. The following `specialchars` table involving the `some id` column demonstrates this handling.

```
// Create the specialchars table
create table specialchars ("some id" number, name varchar2(255));
```

Note that the `specialchars` table has a column named `some id` that contains a blank space character. The space character is not allowed in an XML element name.

## Saving Changes to a Table Using an XML Document

When an XML document is used to save changes to a table or view, the `OracleCommand.XmlSaveProperties.UpdateColumnsList` property is used to specify the list of columns to update or insert.

When an XML document is used to save changes to a column in a table or view, and the corresponding column name contains any of the characters that are not valid in an XML element name, the escaped column name must be specified in the `UpdateColumnsList` property as in the following example.

The following XML document can be used to insert values (2, `<Jones>`) into the `specialchars` table:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
```

```
        <some_x0020_id>2</some_x0020_id>
        <NAME>&lt;Jones&gt;</NAME>
    </ROW>
</ROWSET>
```

The following example specifies the list of columns to update or insert:

```
/* Database Setup
connect scott/tiger@oracle
drop table specialchars;
create table specialchars ("some id" number, name varchar2(255));
insert into specialchars values (1, '<Jones>');
commit;
*/

// C#

using System;
using System.Data;
using System.Xml;
using Oracle.DataAccess.Client;

class InsertUsingXmlDocSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected Successfully");

        // Create the command
        OracleCommand cmd = new OracleCommand("", con);

        // Set the XML command type to query.
        cmd.XmlCommandType = OracleXmlCommandType.Insert;

        // Set the XML document
        cmd.CommandText = "<?xml version = '1.0'?>\n" + "<ROWSET>\n" + "<ROW>\n" +
            "<some_x0020_id>2</some_x0020_id>\n" + "<NAME>&lt;Jones&gt;</NAME>\n" +
            "</ROW>\n" + "</ROWSET>\n";
        cmd.XmlSaveProperties.Table = "specialchars";

        string[] ucols = new string[2];

        ucols[0] = "some_x0020_id";
        ucols[1] = "NAME";
        cmd.XmlSaveProperties.UpdateColumnsList = ucols;

        // Insert rows
        int rows = cmd.ExecuteNonQuery();

        Console.WriteLine("Number of rows inserted successfully : {0} ", rows);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}
```



**Improving Default Mapping** You can improve the default mapping by using the following techniques:

- Modify the target. Create an object-relational view over the target schema, and make the view the new target.
- Modify the XML document. Use XSLT to transform the XML document. Specify the XSL document and parameters. The transformation is done before the changes are saved. Note that this may have an impact on performance.
- Specify the name of the row tag used in the XML document.

### Object-Relational Data

Changes in an XML document can also be saved to object-relational data. Each item in a collection can be specified in one of the following ways in the XML document:

- By enclosing the database type name of the item as the XML element name.
- By enclosing the name of the database column holding the collection with `_ITEM` appended as the XML element name.

### Multiple Tables

Oracle Database does not save changes to multiple relational tables that have been joined together. Oracle recommends that you create a view on those relational tables, and then update that view. If the view cannot be updated, triggers can be used instead.

**See Also:** *Oracle Database SQL Reference* for the description and syntax of the `CREATE VIEW` statement

### Commit Transactions

When the changes in an XML document are made, either all the changes are committed, or if an error occurs, all changes are rolled back.

## Oracle User-Defined Types (UDTs) and .NET Custom Types

ODP.NET has the ability to represent Oracle UDTs found in the database as custom types in .NET applications. UDTs are useful in representing complex entities as a single object that can be shared among applications. Oracle products, such as Oracle Spatial and Oracle XML DB, use their own complex types frequently.

To represent Oracle UDTs as .NET custom types, applications must apply .NET attributes to custom classes and structs, and to their public fields and properties

To convert between UDTs and custom types, ODP.NET uses custom interfaces.

This section discusses the following topics:

- [Oracle User-Defined Types \(UDTs\)](#)
- [Custom Types](#)
- [Specifying Custom Type Mappings](#)
- [Converting Between Custom Types and Oracle UDTs](#)
- [Oracle UDT Attribute Mappings](#)
- [Oracle UDT Retrieval from OracleDataReader](#)
- [Oracle UDT Metadata Retrieval from OracleDataReader](#)

- [Oracle UDT Parameter Binding with OracleParameter](#)
- [Populating the DataSet with Oracle UDTs](#)
- [UDT Method Invocation](#)
- [Configuration Settings for Oracle UDTs](#)

## Oracle User-Defined Types (UDTs)

Oracle Data Provider for .NET supports Oracle object types or user-defined types (UDTs), which are defined in the Oracle database.

There are two kinds of UDTs:

- Object types (Oracle Object)
- Collection types (which can be `VARRAY` types or nested table types)

Additionally, ODP.NET supports references (`REF`) to object types.

**See Also:** ["OracleRef Class"](#) on page 16-51

The term UDT is used interchangeably with Oracle object types and abstract data types (ADTs).

**See Also:** *Oracle Database Application Developer's Guide - Object-Relational Features* for complete descriptions of object types

The name of the Oracle UDT is case-sensitive and must be in the form `schema_name.type_name`.

UDT samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples\UDT` directory.

## Custom Types

Oracle Data Provider for .NET supports UDTs by representing Oracle UDTs defined in the database as .NET types, that is, custom types. For every Oracle UDT that the application wishes to fetch and manipulate, one custom type factory and one custom type are needed. The custom factory class is solely responsible for instantiating the custom type. ODP.NET uses the interfaces implemented on the custom factory classes to instantiate custom types at run time. Custom types define the mapping between the Oracle UDT attributes or elements to the .NET members. ODP.NET uses the interfaces implemented on the custom type instances to transfer values between the Oracle UDT and the custom type at run time.

Custom types can be .NET classes or structures. They can represent either Oracle Objects or Oracle Collections. Custom types can be implemented manually by the application developer or generated through an ODP.NET code generation tool.

Once the factory class and the custom type are defined and meet the implementation requirements, the application may set ODP.NET to automatically discover the mapping between the Oracle UDT and the custom type. This discovery process is based on the attribute that is applied on the custom factory class. Alternatively, the application can provide an explicit mapping through a configuration file.

Oracle Collections can be represented as an array of .NET Types. For example, an Oracle Collection type of `NUMBER` can be mapped to an `int []`. Moreover, an Oracle Collection type of an Oracle UDT can be mapped to an array of the custom type.

Custom types must adhere to certain requirements in order for ODP.NET to represent Oracle UDTs as custom types. These requirements are as follows:

### Required Custom Type Implementations

This section lists the required implementations for a custom .NET class or structure.

- `Oracle.DataAccess.Types.IOracleCustomType` interface implementation

This interface is used for conversions between custom types and Oracle UDTs.

The interface methods are implemented using the static methods of the `OracleUdt` class.

- Custom Type Factories

A custom type factory is used to create an instance of a custom type. A custom type factory is an implementation of either the `IOracleCustomTypeFactory` interface, the `IOracleArrayTypeFactory` interface, or both interfaces, as follows:

- To create a custom type that represents an Oracle Object, the custom type or a separate custom type factory class must implement the `Oracle.DataAccess.Types.IOracleCustomTypeFactory` interface.
- To create a custom type that represents an Oracle Collection, the custom type or a separate custom type factory class must implement the `Oracle.DataAccess.Types.IOracleCustomTypeFactory` interface and the `Oracle.DataAccess.Types.IOracleArrayTypeFactory` interface.
- To create an array type that represents an Oracle Collection, a custom type factory class must implement the `Oracle.DataAccess.Types.IOracleArrayTypeFactory` interface.

- Custom Type Member Mapping Attributes

The custom type member mapping attributes specify the mapping between custom type members and either Oracle object attributes or Oracle collection elements.

There are two types of custom type member mapping attributes:

- `OracleObjectMappingAttribute`

This attribute specifies the mapping between custom type members and Oracle object attributes for custom types that represent Oracle objects.

This attribute must be applied to each custom type member (either field or property) that represents an Oracle Object attribute.

---

**Note:** Not all Oracle object attributes need to be mapped to custom type members. If there is no `OracleObjectMappingAttribute` for a particular object attribute, ODP.NET ignores that object attribute when converting between Oracle objects and custom types.

---

- `OracleArrayMappingAttribute`

This attribute specifies the custom type member that stores the elements of an Oracle collection for custom types representing Oracle collections.

The attribute must be specified on only one of the custom type members.

- `Oracle.DataAccess.Types.INullable` interface implementation  
This interface is used to determine if an instance of a custom type represents a null UDT.  
The `IsNull` property of the interface enables applications and ODP.NET to determine whether or not the UDT is null.
- Static Null field  
The public static `Null` property is used to return a null UDT.  
This property returns a custom type with an `IsNull` property that returns true.

### Optional Custom Type Implementations

The following are optional:

- `IXMLSerializable`  
The `IXMLSerializable` interface is used in the .NET 2.0 framework to enable conversion between the custom type and its XML representation.  
This interface is only used if the serialization and deserialization of a custom type is needed in the `DataSet`.
- Static `Parse` and Public `ToString` methods  
These methods enable conversion between the custom type and its string representation.  
These methods are invoked when a `DataGrid` control is used to accept changes and display instance values.
- Type Inheritance  
Type Inheritance refers to the process of deriving an Oracle UDT in the database from a super type.  
If the custom type represents an Oracle UDT that is derived from a super type, the custom class should follow the same type hierarchy, that is, the custom class should be derived from another custom class that represents the super type defined in the database.
- `OracleCustomTypeMappingAttribute`  
The `OracleCustomTypeMappingAttribute` object specifies the mapping between a custom type (or an array type) and an Oracle UDT.  
There must be a unique custom type factory for each Oracle UDT used by the application as follows:
  - Oracle Object Types:  
The custom type factory must return a custom type that only represents the specified Oracle Object Type.
  - Oracle Collection Types:  
The custom type factory may return a custom type that can be used by other Oracle Collection Types. This is common when an array type is used to represent an Oracle Collection, for example, when an `int []` is used to represent a collection of `NUMBERS`.  
If the `OracleCustomTypeMappingAttribute` is not specified, then custom type mappings must be specified through XML configuration files, that is,

`machine.config`, and either `app.config` for Windows applications or `web.config` for web applications.

**See Also:**

- ["IOracleCustomType Interface"](#) on page 16-26
- ["OracleRef Class"](#) on page 16-51
- ["IOracleCustomTypeFactory Interface"](#) on page 16-30

## Specifying Custom Type Mappings

After creating a custom type, the application must specify a custom type mapping that maps the custom type to an Oracle UDT in the database. This can be done using a custom type factory or XML in configuration files.

Using XML to specify custom type mappings has priority, if both techniques have been implemented. At run time, if ODP.NET finds custom type mappings specified in configuration files, it ignores any custom type mappings specified through the `OracleCustomTypeMappingAttribute` object.

Custom type mappings cannot be specified using synonyms, regardless of whether or not the mapping is provided through the `OracleCustomTypeMappingAttribute` object or the XML configuration file.

**See Also:** *Oracle Developer Tools for Visual Studio help* sections on User-Defined Types Node, under Server Explorer for Visual Studio 2005 and Oracle Explorer for Visual Studio 2003, for further information on UDT mapping

This section contains these topics:

- ["Using a Custom Type Factory to Specify Custom Type Mappings"](#)
- ["Using XML in Configuration Files to Specify Custom Type Mappings"](#)

### Using a Custom Type Factory to Specify Custom Type Mappings

The application can specify a custom type mapping using a custom type factory. The application supplies the name of the Oracle UDT, in the format `schema_name.type_name`, to an `OracleCustomTypeMappingAttribute` object and applies the name to the corresponding custom type factory. A custom type factory is a class or struct that implements either or both the `IOracleCustomTypeFactory` and `IOracleArrayTypeFactory` interfaces.

Note that for each Oracle UDT used by the application, there must be a unique custom type factory. Additionally, for Oracle Object Types, the custom type factory must return a custom type that uniquely represents the specified Oracle Object Type. For Oracle Collection Types, the custom type factory returns a custom type that can be used by other Oracle Collection Types. This is common when a custom type that is an array type represents an Oracle Collection, that is, when an `int []` is used to represent a collection of `NUMBERS`.

At run time, using reflection programming, ODP.NET discovers all the custom type mappings specified by the application through the `OracleCustomTypeMappingAttribute` object.

---

---

**Note:** The UDT name that is specified in the `OracleCustomTypeMappingAttribute` may not contain a period.

---

---

### Using XML in Configuration Files to Specify Custom Type Mappings

The application can specify a custom type mapping with XML in configuration files, for example: using `machine.config`, and either `app.config` for Windows applications or `web.config` for web applications.

The custom type mappings must be specified in the `oracle.dataaccess.client` configuration section group. Each custom type mapping must be added to the collection of custom type mappings using the XML element `<add>`.

Each custom type mapping consists of a name attribute and a value attribute. The name attribute may be any user-specified name that represents the custom type mapping. The value attribute must begin with `udtMapping` and be followed by the required and optional attributes listed below.

#### Required Attributes

- `factoryName`

The case-sensitive assembly qualified name of the custom type factory class or struct.

If the assembly that defines the custom type factory does not have a strong name, then a partial assembly name consisting of just the assembly name is sufficient. In the case of strongly named assemblies, a complete assembly name is required. It must include the assembly name, the `Version`, `Culture`, `PublicKeyToken`.

- `typeName`

The case-sensitive name of the UDT defined in the database. By default all UDTs are created in the database with upper case names

- `schemaName`

The case-sensitive schema in which the UDT is defined in the database. By default all schemas are created in the database with upper case names

#### Optional Attributes

- `dataSource`

If specified, indicates that the custom type mapping applies only to Oracle UDTs defined in the database that the application connects to, as specified by the TNS name alias.

The Data Source is case-insensitive.

The following is an example of the format of the XML that can be specified in the configuration file for .NET 2.0:

```
<oracle.dataaccess.client>
  <settings>
    <add name="Person" value="udtMapping factoryName='Sample.PersonFactory,
      Sample, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null'
      typeName='PERSON' schemaName='SCOTT' dataSource='oracle'"/>
    <add name="Student" value="udtMapping factoryName='Sample.StudentFactory,
      Sample, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null'
      typeName='STUDENT' schemaName='SCOTT'"/>
  </settings>
```

```
</oracle.dataaccess.client>
```

## Using Custom Type Mappings

During data retrieval, the application uses the custom type mappings to convert an Oracle UDT to a custom type. When data is provided back to the database through an input or input/output parameter, or by an update through an Oracle REF, the application uses the mappings to convert the custom type to an Oracle UDT.

In the case of input and input/output parameters, the application must also set the `OracleParameter.UdtTypeName` property to the user-defined type name of the parameter.

In certain cases, where Oracle UDTs are part of a type hierarchy, the custom type must be instantiated as a specific type in the type hierarchy. The Oracle UDT provided by the custom type mapping must be a subtype of the Oracle UDT specified by the `OracleParameter.UdtTypeName` property.

For example, the parameter for a stored procedure is of type, `SCOTT.PERSON` and has a subtype, `SCOTT.STUDENT`. The application has a custom class instance that represents `SCOTT.STUDENT`. The `UdtTypeName` is set to `SCOTT.PERSON`, but the custom type mapping indicates that the custom class is mapped to `SCOTT.STUDENT` and overrides the `UdtTypeName` when it instantiates the Oracle UDT. Thus, ODP.NET instantiates and binds Oracle UDTs appropriately when the custom object represents an Oracle UDT that is a subtype of the parameter type.

## Converting Between Custom Types and Oracle UDTs

ODP.NET can convert between Oracle UDTs and custom types, if the proper attribute mappings are specified and the custom types are defined properly.

ODP.NET performs a conversion whenever an Oracle UDT is fetched as:

- In, out, in/out parameters bound for SQL or PL/SQL execution

The `DbType` property of `OracleParameter` must be set to `DbType.Object` or the `OracleDbType` property must be set to `OracleDbType.Object` or `OracleDbType.Array`.

For parameters that are user-defined types, the `UdtTypeName` property of the `OracleParameter` object must be always set to the parameter type.

Note: The `UdtTypeName` may differ from the Oracle UDT specified in the custom type mapping. This is the case when the parameter type is a super type of the Oracle UDT that the custom type represents.

- Column value retrieved from an `OracleDataReader` object

If the application requests for the value either through the `GetValue`, `GetValues`, `GetOracleValue`, `GetOracleValues`, `GetProviderSpecificValue`, or `GetProviderSpecificValues` methods or the `Item[]` property for a UDT column, ODP.NET finds the corresponding custom type that represents the Oracle UDT and carries out the proper conversion.

- Part of a Resultset that populates the `DataSet`

If the application populates the `DataSet` with a result that contains UDTs using the `Fill` method on the `OracleDataAdapter`, the `DataSet` is populated with custom types that represent Oracle UDTs. With ADO.NET 2.0, the `DataSet` is populated with custom types for UDT columns regardless of whether the

`ReturnProviderSpecificTypes` on the `OracleDataAdapter` is set to `true` or `false`.

- A Object referenced through a REF

When an Object referenced by a REF is retrieved, the custom type that represents the Oracle UDT is returned.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned as follows:

- If the `OracleUdtFetchOption.Cache` option is specified and a cached copy of the object exists, the cached copy is immediately returned. If no cached copy exists, the latest object copy from the database is cached and returned.
- If the `OracleUdtFetchOption.Server` option is specified, the latest object copy from the database is cached and returned. If the object is already cached, the latest object copy overwrites the existing one.
- If the `OracleUdtFetchOption.TransactionCache` option is specified, there are two possibilities within the same transaction:
  - If the object copy was previously retrieved using the `Server` or `TransactionCache` option, the `TransactionCache` option behavior becomes equivalent to the `Cache` option behavior.
  - If the object copy was not previously retrieved using the `Server` or `TransactionCache` option, the `TransactionCache` option behavior becomes equivalent to the `Server` option behavior.

## Oracle UDT Attribute Mappings

Table 3–19 lists valid mappings of attributes (for objects) and elements (for collections), between Oracle UDT types and custom object types which can be either .NET types or Oracle provider-specific types (ODP.NET types).

Oracle collections do not have to map to a custom class. They can map to arrays of a specific type. Table 3–19 indicates those collections with elements of a specified Oracle type that can map to arrays of a .NET Type or a provider-specific type. For example, if an Oracle Collection is a `VARRAY` of `NUMBER(8)`, it can map to a `typeof(int[])`. This eliminates the need to construct a class that only holds an `int[]`.

For .NET 2.0, Oracle Collections can be mapped to Nullable types. This allows .NET 2.0 applications to obtain a nullable `int[]` which can hold null values in the `int[]`.

Note that Oracle UDT attributes and elements cannot be mapped to `object` or `object[]`.

**Table 3–19 Attribute Mappings Between UDTs and Custom Object Types**

Type of UDT Attribute or Element	.NET Type	ODP.NET Type
BFILE #1	<code>System.Byte[]</code>	<code>OracleBFile</code>
BINARY FLOAT	<code>System.Byte</code> , <code>System.Int16</code> , <code>System.Int32</code> , <code>System.Int64</code> , <code>System.Single</code> , <code>System.Double</code> , <code>System.Decimal</code>	<code>OracleDecimal</code>



**Table 3–19 (Cont.) Attribute Mappings Between UDTs and Custom Object Types**

Type of UDT Attribute or Element	.NET Type	ODP.NET Type
BINARY DOUBLE	System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal	OracleDecimal
BLOB	System.Byte[]	OracleBlob
CHAR	System.Char[], System.String	OracleString
CLOB	System.Char[], System.String	OracleClob
DATE	System.DateTime	OracleDate
INTERVAL DAY TO SECOND	System.TimeSpan	OracleIntervalDS
INTERVAL YEAR TO MONTH	System.Int64	OracleIntervalYM
LONG RAW	System.Byte[]	OracleBinary
NCHAR	System.Char[], System.String	OracleString
NCLOB	System.Char[], System.String	OracleClob
Nested Table	<i>custom type, .NET type[], or custom type[]</i>	<i>ODP Type[]</i>
NUMBER	System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal	OracleDecimal
NVARCHAR2	System.Char[], System.String	OracleString
Object Type	<i>custom type</i>	N/A
RAW	System.Byte[]	OracleBinary
REF	System.String	OracleRef
TIMESTAMP	System.DateTime	OracleTimeStamp
TIMESTAMP WITH LOCAL TIME ZONE	System.DateTime	OracleTimeStampL TZ
TIMESTAMP WITH TIME ZONE	System.DateTime	OracleTimeStampT Z
VARCHAR2	System.Char[], System.String	OracleString
VARRAY	<i>custom type, .NET type[], or custom type[]</i>	<i>ODP Type[]</i>
XMLTYPE	System.Char[], System.String	OracleXmlType

**Notes:**

1. Conversion from a `System.Byte[]` to a `BFILE` is not supported, and therefore, `System.Byte[]` only represents a `BFILE` in read-only scenarios.

**Oracle UDT Retrieval from OracleDataReader**

In order to retrieve Oracle UDTs from the `OracleDataReader`, an application must specify a custom type mapping that determines the type that will represent the Oracle UDT. Once a custom type mapping has been specified and any necessary custom types have been created, the application can retrieve Oracle UDTs.

Table 3–20 shows the type and value returned from an `OracleDataReader` object based on the method invoked, the column type, and whether or not there is a valid Custom type mapping.

---



---

**Note:** *PS Object* refers to a provider-specific object.

---



---

**Table 3–20 Type and Value Returned from OracleDataReader Object**

<b>OracleDataReader method/property invocation</b>	<b>Column Data Type</b>	<b>Custom Type Mapping</b>	<b>Value Returned for Oracle UDT</b>	<b>NULL Value Returned for Oracle UDT</b>
<code>Item[index]</code> , <code>Item[name]</code> , <code>GetValue()</code> , <code>GetValues()</code>	Object, Collection	none	Exception thrown	Exception thrown
<code>Item[index]</code> , <code>Item[name]</code> , <code>GetValue()</code> , <code>GetValues()</code>	Object	<i>schema.type</i>	<i>custom object</i>	<code>DBNull.Value</code>
<code>Item[index]</code> , <code>Item[name]</code> , <code>GetValue()</code> , <code>GetValues()</code>	Collection	<i>schema.type</i>	<i>custom object</i>   <i>custom object[]</i>   <i>.NET Type[]</i>   <i>PS object[]</i>	<code>DBNull.Value</code>
<code>Item[index]</code> , <code>Item[name]</code> , <code>GetValue()</code> , <code>GetValues()</code>	REF	none   <i>schema.type</i>	<i>string</i> (HEX)	<code>DBNull.Value</code>
<code>GetString()</code>	REF	none   <i>schema.type</i>	<i>string</i> (HEX)	Exception thrown
<code>GetProviderSpecificValue()</code> , <code>GetProviderSpecificValues()</code> , <code>GetOracleValue()</code> , <code>GetOracleValues()</code>	Object, Collection	<i>schema.type</i>	<i>custom object</i>	<i>custom type.Null</i>

**Table 3–20 (Cont.) Type and Value Returned from OracleDataReader Object**

OracleDataReader method/property invocation	Column Data Type	Custom Type Mapping	Value Returned for Oracle UDT	NULL Value Returned for Oracle UDT
GetProviderSpecificValue(), GetProviderSpecificValues(), GetOracleValue(), GetOracleValues()	Collection	<i>schema.type</i>	<i>custom object[]</i>   <i>.NET Type[]</i>   <i>PS object[]</i>	null
GetProviderSpecificValue(), GetProviderSpecificValues(), GetOracleValue(), GetOracleValues(), GetOracleRef()	REF	none   <i>schema.type</i>	OracleRef	OracleRef.Null
GetOracleString()	REF	none   <i>schema.type</i>	OracleString (HEX)	OracleString.Null

**See Also:** ["Obtaining Data from an OracleDataReader Object"](#) on page 3-47

## Oracle UDT Metadata Retrieval from OracleDataReader

An `OracleDataReader` object can return metadata used to determine the custom type that represents an Oracle UDT when a .NET Type or Provider-Specific Type accessor is invoked. The same custom type is used when populating the `DataSet` using the `OracleDataAdapter.Fill` method.

[Table 3–21](#) shows the values returned from the `OracleDataReader` `GetFieldType` and `GetProviderSpecificFieldType` methods that specify the .NET type of the column.

**Table 3–21 Values Returned from OracleDataReader Methods**

OracleDataReader Method/Property invocation	Column Data Type	Custom Type Mapping	Return Value
<code>GetFieldType(index)</code>	Object, Collection	none	Exception thrown
<code>GetFieldType(index)</code>	Object	<i>schema.type</i>	<code>typeof(custom type)</code>
<code>GetFieldType(index)</code>	Collection	<i>schema.type</i>	<code>typeof(custom type)</code>   <code>typeof(custom type[])</code>   <code>typeof(.NET type[])</code>   <code>typeof(PS type[])</code>
<code>GetFieldType(index)</code>	REF	none   <i>schema.type</i>	<code>typeof(string)</code>
<code>GetProviderSpecificFieldType(index)</code>	Object, Collection	none	Exception thrown
<code>GetProviderSpecificFieldType(index)</code>	Object,	<i>schema.type</i>	<code>typeof(custom type)</code>

**Table 3–21 (Cont.) Values Returned from OracleDataReader Methods**

OracleDataReader Method/Property invocation	Column Data Type	Custom Type Mapping	Return Value
GetProviderSpecificField(index)	Collection	<i>schema.type</i>	typeof( <i>custom type</i> )   typeof( <i>custom type</i> [])   typeof(.NET type[])   typeof( <i>PS type</i> [])
GetProviderSpecificField(index)	REF	none   <i>schema.type</i>	typeof(OracleRef)

## Oracle UDT Parameter Binding with OracleParameter

This section discusses using UDT output and input parameter bindings with an `OracleParameter` object.

**See Also:** ["Parameter Binding"](#) on page 3-31

This section contains these topics:

- [Guidelines for Binding UDT Input and Output Parameters](#)
- [UDT Input Parameter Binding with OracleParameters](#)
- [UDT Output Parameter Binding with OracleParameters](#)

### Guidelines for Binding UDT Input and Output Parameters

Developers must consider the following when using UDT parameter bindings with an `OracleParameter` object.

- The `UdtTypeName` property must be set. Binding is based on the `UdtTypeName` property regardless of the parameter direction.

---

**Note:** The `UdtTypeName` may differ from the Oracle UDT specified in the custom type mapping. This occurs when the parameter type is a super type of the Oracle UDT that the custom type represents.

---

- In case of Input/Output binding, the behavior is the same as Input and Output parameters.
- For Input parameter values, the bind value is converted to the UDT specified by the custom type mapping.
- For Output parameters:
  - If the value being returned is an Oracle Object or Collection, it is converted to a custom type or array type as specified by the custom type mapping. The value returned is always a custom type or an array type, regardless of whether the property most recently set was `DbType` or `OracleDbType`.
  - If the value being returned is a REF, then no custom type mapping is required.

### UDT Input Parameter Binding with OracleParameters

Only certain combinations of these `OracleParameter` property values, `DbType`, `OracleDbType`, and `UdtTypeName`, can exist on the `OracleParameter` object. `OracleParameter` objects cannot be set to combinations that are not listed.

Table 3–22 describes the valid ways of binding input parameters for Oracle UDTs.

The last column indicates the Oracle type that ODP.NET converts the `OracleParameter` value to before binding.

**Table 3–22 Valid Ways to Bind Input Parameters for Oracle UDTs**

OracleParameter.Value	OracleParameter.DbType or OracleDbType	OracleParameter.UdtTypeName	Custom Type Mappings	Oracle Type converted to before Binding
<code>custom object</code>   <code>custom object[]</code>   <code>.NET object[]</code>   <code>PS object[]</code>   <code>String(HEX)</code>   <code>OracleString(HEX)</code>   <code>OracleRef</code>	<code>DbType.Object</code>   <code>OracleDbType.Object</code>   <code>OracleDbType.Array</code>   <code>OracleDbType.Ref</code>	not set	none   <code>schema.type</code>	Exception thrown
<code>custom object[]</code>   <code>.NET object[]</code>   <code>PS object[]</code>   <code>object[]</code>	<code>DbType.Object</code>   <code>OracleDbType.Object</code>   <code>OracleDbType.Array</code>	<code>schema.type</code>	none	Exception thrown
<code>custom object</code>	<code>DbType.Object</code>	<code>schema.type</code>	<code>schema.type</code>	Specified UDT is instantiated. Value is bound as <code>Object</code> or <code>Collection</code> , based on the <code>UdtTypeName</code> property
<code>custom object</code>	<code>OracleDbType.Object</code>	<code>schema.type</code>	<code>schema.type</code>	Specified UDT is instantiated. <code>schema.type</code> must represent an object.
<code>custom object</code>	<code>OracleDbType.Array</code>	<code>schema.type</code>	<code>schema.type</code>	Specified UDT is instantiated. <code>schema.type</code> must represent a collection.
<code>.NET object[]</code>   <code>PS object[]</code>   <code>custom object[]</code>	<code>DbType.Object</code>   <code>OracleDbType.Array</code>	<code>schema.type</code>	<code>schema.type</code>	UDT specified by <code>OracleParameter.UdtTypeName</code> is instantiated.
<code>.NET object[]</code>   <code>PS object[]</code>   <code>custom object[]</code>	<code>OracleDbType.Object</code>	<code>schema.type</code>	none   <code>schema.type</code>	Exception thrown
<code>custom object</code>   <code>.NET object[]</code>   <code>PS object[]</code>   <code>custom object[]</code>	<code>OracleDbType.Ref</code>	<code>schema.type</code>	none   <code>schema.type</code>	Exception thrown
<code>String(HEX)</code>   <code>OracleString(HEX)</code>   <code>OracleRef</code>	<code>DbType.Object</code>   <code>OracleDbType.Object</code>   <code>OracleDbType.Array</code>	<code>schema.type</code>	none   <code>schema.type</code>	Exception thrown
<code>Char[](HEX)</code>   <code>String(HEX)</code>   <code>OracleString(HEX)</code>   <code>OracleRef</code>	<code>OracleDbType.Ref</code>	<code>schema.type</code>	none   <code>schema.type</code>	A REF

## UDT Output Parameter Binding with OracleParameters

Only certain combinations of these `OracleParameter` property values, `DbType`, `OracleDbType`, and `UdtTypeName`, can exist on the `OracleParameter` object. `OracleParameter` objects cannot be set to combinations that are not listed.

[Table 3–23](#) shows the supported ODP.NET output parameter bindings of Oracle database objects.

The last column indicates the type that ODP.NET converts the `OracleParameter` value to before binding.

**Table 3–23** Valid Ways to Bind Output Parameters for Oracle UDTs

Type returned from Oracle	<code>OracleParameter.DbType</code>	OracleParameter. <code>UdtTypeName</code>	Custom Type Mappings	Type converted to
Object/Collection/REF	<code>DbType.Object</code>   <code>OracleDbType.Object</code>   <code>OracleDbType.Array</code>   <code>OracleDbType.Ref</code>	not set	none   <code>schema.type</code>	Exception thrown
Object/Collection	<code>DbType.Object</code>   <code>OracleDbType.Object</code>   <code>OracleDbType.Array</code>	<code>schema.type</code>	none	Exception thrown
Object	<code>DbType.Object</code>   <code>OracleDbType.Object</code>	<code>schema.type</code>	<code>schema.type</code>	custom object
Object	<code>OracleDbType.Array</code>   <code>OracleDbType.Ref</code>	<code>schema.type</code>	none   <code>schema.type</code>	Exception thrown
Collection	<code>OracleDbType.Array</code>   <code>DbType.Object</code>	<code>schema.type</code>	<code>schema.type</code>	custom object   custom object[]   .NET object[]   PS object[]
Collection	<code>OracleDbType.Ref</code>   <code>OracleDbType.Object</code>	<code>schema.type</code>	none   <code>schema.type</code>	Exception thrown
REF	<code>DbType.Object</code>   <code>OracleDbType.Object</code>   <code>OracleDbType.Array</code>	<code>schema.type</code>	none   <code>schema.type</code>	Exception thrown
REF	<code>OracleDbType.Ref</code>	<code>schema.type</code>	none   <code>schema.type</code>	OracleRef

### See Also:

- ["Parameter Binding"](#) on page 3-31
- ["Typed OracleDataReader Accessors"](#) on page 3-48

## Populating the DataSet with Oracle UDTs

The `DataSet` is a disconnected result set. With ADO.NET 2.0, both .NET types and provider-specific types can be used to populate the `DataSet`. This section describes the types used to populate the `DataSet` when the column is an Oracle UDT.

[Table 3–24](#) lists the types that populate the `DataSet` column, based on the Oracle column type, the `ReturnProviderSpecificTypes` property of the `DataAdapter`, the existence of a custom type mapping, the `DataSet` column type, the `DataSet` column value, and the `DataSet` column null value.

**Table 3–24 Types that Populate the DataSet with ADO.NET 2.0**

Oracle Column Type	ReturnProvider-SpecificTypes Property	Custom Type Mappings	DataSet Column Type	DataSet Column Value	DataSet Column Null Value
Object / Collection	False/True	none	Exception thrown	Exception thrown	Exception thrown
Object / Collection	False	schema.type	<code>typeof(custom type)</code>	<i>custom object</i>	<code>DBNull.Value</code>
Object / Collection	True	schema.type	<code>typeof(custom type)</code>	<i>custom object</i>	<code>custom object.Null</code>
Collection	False	schema.type	<code>typeof(custom type[])   typeof(.NET type[])   typeof(PS type[])</code>	<i>.NET type[]   PS object[]   custom object[]</i>	<code>DBNull.Value</code>
Collection	True	schema.type	<code>typeof(custom type[])   typeof(.NET type[])   typeof(PS type[])</code>	<i>.NET type[]   PS object[]   custom object[]</i>	null
REF	False	none   schema.type	<code>typeof(string)</code>	string/HEX	<code>DBNull.Value</code>
REF	True	none   schema.type	<code>typeof(OracleRef)</code>	OracleRef	<code>OracleRef.Null</code>

## UDT Method Invocation

ODP.NET supports invocation of methods defined for a UDT on the database. This can be accomplished by doing the following:

1. Set the `CommandType` as `CommandType.StoredProcedure`.
2. Set the `CommandText` as "*type\_name.procedure\_name*"
3. Execute the command using any of the `Execute` methods on the `OracleCommand` object.

For instance functions, the parameters are as follows:

- The first parameter must be the return value.
- The second parameter must be the UDT instance on which the instance method is invoked, which is the instance of the .NET custom object.
- Subsequent parameters are for the function.

For instance procedures, the first parameter must be the UDT instance.

For static methods, the UDT instance is not needed.

## Configuration Settings for Oracle UDTs

ODP.NET exposes two configuration settings to determine how ODP.NET handles Oracle UDTs.

- [StatementCacheWithUdts](#)
- [UdtCacheSize](#)

These configuration settings can be specified as machine-wide settings for a particular version of ODP.NET, using the registry key with the name that exists under `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version`. The configuration settings specified in the registry can be overridden if an entry is created in the `machine.config` for .NET framework-wide settings, or in the `app.config` or `web.config` for application-specific settings. For details on configuring ODP.NET, see "[ODP.NET Configuration](#)" on page 3-114.

### **StatementCacheWithUdts**

`StatementCacheWithUdts` specifies whether or not ODP.NET caches Oracle UDTs retrieved by a `SELECT` statement along with the statement when it is returned to the statement cache. Possible values are 1 - Yes (the default) or 0 - No.

For the value of 1, the Oracle UDTs are cached along with the statements. Therefore, the memory that contained the UDTs can be re-used; subsequent executions of the same statement do not require additional memory. This may result in an overall higher performance.

For the value of 0, ODP.NET frees the memory for the retrieved Oracle UDTs before the statement is returned to the statement cache. This may result in poorer performance because subsequent executions will require new memory allocations.

### **UdtCacheSize**

`UdtCacheSize` specifies the size of the object cache for each connection that ODP.NET uses when retrieving and manipulating Oracle UDTs. The value for this setting must be specified in kilobytes (KB) with the default 4096KB, equivalent to 4 MB.

This configuration setting is used to determine how frequently the objects in the object cache will be purged (using an LRU approach) as the limit of the object cache size approaches.

## **Oracle Streams Advanced Queuing Support**

Oracle Streams Advanced Queuing (AQ) provides database-integrated message queuing functionality. Oracle Streams AQ is built on top of Oracle Streams and leverages the functions of Oracle Database so that messages can be stored persistently, propagated between queues on different computers and databases, and transmitted using Oracle Net Services and HTTP(S).

**See Also:** *Oracle Streams Advanced Queuing User's Guide and Reference*

As Oracle Streams AQ is implemented in database tables, all operational benefits of high availability, scalability, and reliability are also applicable to queue data. Oracle Streams AQ supports standard database features such as recovery, restart, and security.

The following items discuss Oracle Streams AQ concepts:

- **Queues and Queue Tables**

Messages enqueued in a queue are stored in a queue table. A queue table must be created before creating a queue based on it. Use the `DBMS_AQADM` PL/SQL package or Oracle Developer Tools for Visual Studio to create and administer queue tables and queues.

Queues are represented by `OracleAQQueue` objects.



**See Also:** ["OracleAQQueue Class"](#) on page 12-48

- Single-Consumer and Multiple-Consumer Queues

A single-consumer queue is created based on a single consumer queue table. Messages enqueued in a single-consumer queue can be dequeued by only a single consumer.

A multiple-consumer queue is based on a multiple-consumer queue table. This queue supports queue subscribers and message recipients.

- Message Recipients

A message producer can submit a list of recipients when enqueueing a message. This allows for a unique set of recipients for each message in the queue. The recipient list associated with the message overrides the subscriber list, if any, associated with the queue. The recipients need not be in the subscriber list. However, recipients can be selected from among the subscribers.

The `Recipients` property of an `OracleAQMessage` can be used to specify the recipients to a specific message in terms of `OracleAQAgent` objects.

**See Also:**

- ["Recipients"](#) on page 12-35
- ["OracleAQAgent Class"](#) on page 12-2

- Enqueue

Messages are enqueued when producer applications push the messages into a queue. This is accomplished by calling the `Enqueue` method on an `OracleAQQueue` object. Multiple messages can be enqueued using the `EnqueueArray` method.

**See Also:**

- ["Enqueue"](#) on page 12-68
- ["EnqueueArray"](#) on page 12-70

- Dequeue

Messages are dequeued when consumer applications pull the messages from a queue. This is accomplished by calling the `Dequeue` method on an `OracleAQQueue` object. Multiple messages can be dequeued using the `DequeueArray` method.

**See Also:**

- ["Dequeue"](#) on page 12-64
- ["DequeueArray"](#) on page 12-66

- Listen

Subscriber applications can use a `Listen` call to monitor multiple queues for subscriptions on different queues. This is a more scalable solution for cases where a subscriber application has subscribed to many queues and wishes to receive messages that arrive in any of the queues.

This is accomplished by calling the `Listen` method of the `OracleAQQueue` class, passing the list of subscriptions in form of an array.

**See Also:** ["Listen"](#) on page 12-72

- Notification

Subscriber applications can utilize the notification mechanism to get notifications about message availability in a queue. The applications can decide to skip or dequeue the message from the queue based on the information received.

A subscriber application must register for event notification on the queues from which it wants to receive notifications. This is represented by the `MessageAvailable` event on `OracleAQQueue`. The event is triggered when messages matching the subscriptions arrive.

Notifications can be registered as regular or grouping notifications. A time out value for these notifications can also be specified. Various notification options can be set using the `OracleAQQueue.Notification` property. Notifications set on an `OracleAQQueue` object gets cancelled automatically when the object gets disposed.

**See Also:**

- ["MessageAvailable Event"](#) on page 12-79
- ["Notification"](#) on page 12-61

- Buffered Messaging

Buffered messaging was introduced in Oracle Streams AQ 10g Release 2 (10.2). In buffered messaging, messages reside in a shared memory area. This makes it faster than persistent messaging. The messages are written to disk only when the total memory consumption of buffered messages approaches the available shared memory limit. Buffered messaging is ideal for applications that do not require the reliability and transaction support of Oracle Streams AQ persistent messaging.

Buffered and persistent messages use the same single-consumer or multi-consumer queues, and the same administrative and operational interfaces. They are distinguished from each other by a delivery mode parameter. When an application enqueues a message to an Oracle Streams AQ queue, it sets the delivery mode parameter as well.

The delivery mode parameter can be set on `OracleAQMessage` by modifying the `DeliveryMode` property. Buffered messaging is supported in all queue tables created with compatibility 8.1 or higher.

**See Also:** ["DeliveryMode"](#) on page 12-31

## Using ODP.NET for Advanced Queuing

.NET applications can use ODP.NET to access all the operational features of AQ such as Enqueuing, Dequeuing, Listen, and Notification.

[Table 3–25](#) maps the AQ features to their corresponding ODP.NET implementation.

**Table 3–25 Mapping AQ Features with their ODP.NET Implementation**

Functionality	ODP.NET Implementation
Create a Message	Create an <code>OracleAQMessage</code> object
Enqueue a single message	Specify the message as <code>OracleAQMessage</code> , queue as <code>OracleAQQueue</code> and enqueue options on <code>OracleAQQueue</code> , call <code>OracleAQQueue.Enqueue</code>
Enqueue multiple messages	Specify the messages as an <code>OracleAQMessage</code> array in <code>OracleAQQueue.EnqueueArray</code>
Dequeue a single message	Specify dequeue options on <code>OracleAQQueue</code> and call <code>OracleAQQueue.Dequeue</code>
Dequeue multiple messages	Call <code>OracleAQQueue.DequeueArray</code>
Listen for messages on Queue(s)	Call <code>OracleAQQueue.Listen</code> . To listen on multiple queues use static <code>Listen</code> method of <code>OracleAQQueue</code>
Message Notifications	Use <code>OracleAQQueue.MessageAvailableEvent</code> along with the <code>NotificationConsumers</code> property

---

**Note:** AQ samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples` directory.

---

### Enqueuing and Dequeuing Example

The following example demonstrates enqueueing and dequeuing messages using a single consumer queue. The first part of the example performs the requisite database setup for the database user, SCOTT. The second part of the example demonstrates enqueueing and dequeuing messages.

```
-- Part I: Database setup required for this demo

-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
SQL> GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PL/SQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PL/SQL to stop queue and drop queue & queue-table from SCOTT
```

```
-----  
BEGIN  
  DBMS_AQADM.STOP_QUEUE('scott.test_q');  
  
  DBMS_AQADM.DROP_QUEUE(  
    queue_name => 'scott.test_q',  
    auto_commit => TRUE);  
  
  DBMS_AQADM.DROP_QUEUE_TABLE(  
    queue_table => 'scott.test_q_tab',  
    force => FALSE,  
    auto_commit => TRUE);  
END;  
/  
-- End of Part I, database setup.  
  
//Part II: Enqueuing and dequeuing messages  
//C#  
using System;  
using System.Text;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
namespace ODPSample  
{  
  /// <summary>  
  /// Demonstrates Enqueuing and Dequeuing raw message  
  /// using a single consumer queue  
  /// </summary>  
  class EnqueueDequeue  
  {  
    static void Main(string[] args)  
    {  
      // Create connection  
      string constr = "user id=scott;password=Pwd4Sct;data source=oracle";  
      OracleConnection con = new OracleConnection(constr);  
  
      // Create queue  
      OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);  
  
      try  
      {  
        // Open connection  
        con.Open();  
  
        // Begin txn for enqueue  
        OracleTransaction txn = con.BeginTransaction();  
  
        // Set message type for the queue  
        queue.MessageType = OracleAQMessageType.Raw;  
  
        // Prepare message and RAW payload  
        OracleAQMessage enqMsg = new OracleAQMessage();  
        byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };  
        enqMsg.Payload = bytePayload;  
  
        // Prepare to Enqueue  
        queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;  
  
        // Enqueue message
```

```

queue.Enqueue(enqMsg);

Console.WriteLine("Enqueued Message Payload      : "
    + ByteArrayToString(enqMsg.Payload as byte[]));
Console.WriteLine("MessageId of Enqueued Message : "
    + ByteArrayToString(enqMsg.MessageId));

// Enqueue txn commit
txn.Commit();

// Begin txn for Dequeue
txn = con.BeginTransaction();

// Prepare to Dequeue
queue.DequeueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
queue.DequeueOptions.Wait = 10;

// Dequeue message
OracleAQMessage deqMsg = queue.Dequeue();

Console.WriteLine("Dequeued Message Payload      : "
    + ByteArrayToString(deqMsg.Payload as byte[]));
Console.WriteLine("MessageId of Dequeued Message : "
    + ByteArrayToString(deqMsg.MessageId));

// Dequeue txn commit
txn.Commit();
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString()).ToString("X"));
    }
    return sb.ToString();
}
}
}

```

## Database Change Notification Support

Oracle Data Provider for .NET provides a notification framework that supports Continuous Query Notification, enabling applications to receive notifications when there is a change in a query result set, schema objects, or the state of the database.

Using Continuous Query Notification, an application can maintain the validity of the client-side cache (for example, the ADO.NET `DataSet`) easily.

---

---

**Note:** The ODP.NET Database Change Notification feature uses the Continuous Query Notification feature in the Oracle database.

---

---

---

---

**Note:** Database change notification is not supported in a .NET stored procedure.

---

---

Using the notification framework, applications can specify a query result set as a registered query for notification request on the database, and create this notification registration to maintain the validity of the query result set. When there is a change on the database that could affect the client-side cache's query results, the notification framework notifies the application.

---

---

**Note:** The content of a change notification is referred to as an *invalidation message*. It indicates that the query result set is now invalid and provides information about the changes.

---

---

Based on the information provided by the invalidation message, the application can then act accordingly. For example, the application might need to refresh its own copy of the data for the registered query that is stored locally in the application.

---

---

**Note:** If a registered object is dropped from the database and a new one is created with the same name in the same schema, re-registration is required to receive notifications for the newly created object.

---

---

**See Also:** *Oracle Database Advanced Application Developer's Guide* for further information on Continuous Query Notification

By default, Windows Vista and Windows XP Service Pack 2 and later enable the Windows Firewall to block virtually all TCP network ports to incoming connections. Therefore, for Continuous Query Notification to work properly on these operating systems, the Windows Firewall must be configured properly to allow specific executables to open specific ports.

**See Also:** *Oracle Database Platform Guide for Windows* for details on configuring the Windows Firewall

Beginning with Oracle Database 11g and ODP.NET 11g (11.1), Database Change Notification queries can be query-based (default) or object-based. The query-based registrations allow ODP.NET to notify applications when the selected rows have changed in the database. The object-based registrations allow ODP.NET to notify applications for any changes that occur in the table(s) containing the selected rows.

Query-based notifications are supported only when all the following are true:

1. The Oracle database version is at least 11.1.
2. The select list contains no other column data types other than `VARCHAR2` and `NUMBER`.

3. The `COMPATIBLE` initialization parameter of the database is set to at least 11.0.0 and Automatic Undo Management (AUM) is enabled (the default).

If 1) is not met, the notification is registered as object-based for backward compatibility.

If 2) and other documented restrictions are not met, the notification is registered as object-based since ODP.NET uses the best-effort mode.

If 3) is not met, an error is returned upon registration.

**See Also:**

- ["Configuring a Port to Listen for Database Notifications"](#) on page 2-5
- *Oracle Database Advanced Application Developer's Guide* for further details on the requirements for Continuous Query Notification

This section contains the following topics:

- [Database Change Notification Classes](#)
- [Supported Operations](#)
- [Requirements of Notification Registration](#)
- [Using Database Change Notification](#)
- [Best Practice Guidelines and Performance Considerations](#)

## Database Change Notification Classes

The following classes are associated with Continuous Query Notification Support:

- `OracleDependency`

Represents a dependency between an application and an Oracle database based on the database events which the application is interested in. It contains information about the dependency and provides the mechanism to notify the application when specified database events occurs. The `OracleDependency` class is also responsible for creating the notification listener to listen for database notifications. There is only one database notification listener for each application domain. This notification listener terminates when the application process terminates.

The dependency between the application and the database is not established when the `OracleDependency` object is created. The dependency is established when the command that is associated with this `OracleDependency` object is executed. That command execution creates a database change notification registration in the database.

When a change has occurred in the database, the `HasChanges` property of the `OracleDependency` object is set to `true`. Furthermore, if an event handler was registered with the `OnChange` event of the `OracleDependency` object, the registered event handler function will be invoked.

- `OracleNotificationRequest`

Represents a notification request to be registered in the database. It contains information about the request and the properties of the notification.

- `OracleNotificationEventArgs`

Represents the **invalidation message** generated for a notification when a specified database event occurs and contains details about that database event.

**See Also:**

- ["OracleDependency Class"](#) on page 9-2
- ["OracleNotificationRequest Class"](#) on page 9-22
- ["OracleNotificationEventArgs Class"](#) on page 9-30

## Supported Operations

The ODP.NET notification framework in conjunction with Continuous Query Notification supports the following activities:

- Creating a notification registration by:
  - Creating an `OracleDependency` instance and binding it to an `OracleCommand` instance.
- Grouping multiple notification requests into one registration by:
  - Using the `OracleDependency.AddCommandDependency` method.
  - Setting the `OracleCommand.Notification` request using the same `OracleNotificationRequest` instance.
- Registering for Database Change Notification by:
  - Executing the `OracleCommand`. If either the notification property is null or `NotificationAutoEnlist` is false, the notification will not be made.
- Removing notification registration by:
  - Using the `OracleDependency.RemoveRegistration` method.
  - Setting the `Timeout` property in the `OracleNotificationRequest` instance before the registration is created.
  - Setting the `IsNotifiedOnce` property to true in the `OracleNotificationRequest` instance before the registration is created. The registration is removed once a database notification is sent.
- Ensuring Change Notification Persistence by:
  - Specifying whether or not the invalidation message is queued persistently in the database before delivery. If an invalidation message is to be stored persistently in the database, then the change notification is guaranteed to be sent. If an invalidation message is stored in an in-memory queue, the change notification can be received faster, however, it could be lost upon database shutdown or crashes.
- Retrieving notification information including:
  - The changed object name.
  - The schema name of the changed object.
  - Database events that cause the notification, such as insert, delete, and so on.
  - The `RowID` of the modified object row.

In Oracle SQL, the `ROWIDTOCHAR (ROWID)` and `ROWIDTONCHAR (ROWID)` functions convert a `ROWID` value to `VARCHAR2` and `NVARCHAR` data types, respectively.



If these functions are used within a SQL statement, ROWIDs are not returned in the `OracleNotificationEventArgs` object that is passed to the database change notification callback.

- Defining the listener port number.

By default, the static `OracleDependency.Port` property is set to `-1`. This indicates that the ODP.NET listens on a port that is randomly picked when ODP.NET registers a database change notification request for the first time during the execution of an application.

ODP.NET creates only one listener that listens on one port within an application domain. Once ODP.NET starts the listener, the port number cannot be changed; Changes to the static `OracleDependency.Port` property will generate an error if a listener has already been created.

**See Also:**

- ["OracleCommand Class"](#) on page 5-2
- ["Notification"](#) on page 5-21
- ["NotificationAutoEnlist"](#) on page 5-22
- ["OracleDependency Class"](#) on page 9-2
- ["OracleNotificationEventArgs Class"](#) on page 9-30

## Requirements of Notification Registration

The connected user must have the `CHANGE NOTIFICATION` privilege to create a notification registration.

This SQL statement grants the `CHANGE NOTIFICATION` privilege:

```
grant change notification to user name
```

This SQL statement revokes the `CHANGE NOTIFICATION` privilege:

```
revoke change notification from user name
```

## Using Database Change Notification

This section describes what the application should do, and the flow of the process, when an application uses Continuous Query Notification to receive notifications for any changes in the registered query result set.

### Application Steps

The application should do the following:

1. Create an `OracleDependency` instance.
2. Assign an event handler to the `OracleDependency.OnChange` event property if the application wishes to have an event handler invoked when database changes are detected. Otherwise, the application can choose to poll on the `HasChanges` property of the `OracleDependency` object. This event handler is invoked when the change notification is received.
3. Set the port number for the listener to listen on. The application can specify the port number for one notification listener to listen on. If the application does not specify a port number, a random one is used by the listener.

4. Bind the `OracleDependency` instance to an `OracleCommand` instance that contains the actual query to be executed. Internally, the Continuous Query Notification request (an `OracleNotificationRequest` instance) is created and assigned to the `OracleCommand.Notification` property.

### Flow of Notification Process

1. When the command associated with the notification request is executed, the notification registration is created in the database. The command execution must return a result set, or contain one or more REF cursors for a PL/SQL stored procedure.
2. ODP.NET starts the application listener on the first successful notification registration.
3. When a change related to the registration occurs in the database, the application is notified through the event delegate assigned to the `OracleDependency.OnChange` event property, or the application can poll the `OracleDependency.HasChanges` property.

The following example demonstrates the database change notification feature.

```
// Database Setup
// NOTE: unless the following SQL command is executed,
// ORA-29972 will be obtained from running this sample
/*
grant change notification to scott;
*/
using System;
using System.Threading;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

//This sample shows the database change notification feature in ODP.NET.
//Application specifies to get a notification when emp table is updated.
//When emp table is updated, the application will get a notification
//through an event handler.
namespace NotificationSample
{
    public class MyNotificationSample
    {
        public static bool IsNotified = false;

        public static void Main(string[] args)
        {
            //To Run this sample, make sure that the change notification privilege
            //is granted to scott.
            string constr = "User Id=scott;Password=tiger;Data Source=oracle";
            OracleConnection con = null;
            OracleDependency dep = null;

            try
            {
                con = new OracleConnection(constr);
                OracleCommand cmd = new OracleCommand("select * from emp", con);
                con.Open();

                // Set the port number for the listener to listen for the notification
                // request
                OracleDependency.Port = 1005;
```

```

// Create an OracleDependency instance and bind it to an OracleCommand
// instance.
// When an OracleDependency instance is bound to an OracleCommand
// instance, an OracleNotificationRequest is created and is set in the
// OracleCommand's Notification property. This indicates subsequent
// execution of command will register the notification.
// By default, the notification request is using the Database Change
// Notification.
dep = new OracleDependency(cmd);

// Add the event handler to handle the notification. The
// OnMyNotification method will be invoked when a notification message
// is received from the database
dep.OnChange +=
    new OnChangeEventHandler(MyNotificationSample.OnMyNotificaton);

// The notification registration is created and the query result sets
// associated with the command can be invalidated when there is a
// change. When the first notification registration occurs, the
// notification listener is started and the listener port number
// will be 1005.
cmd.ExecuteNonQuery();

// Updating emp table so that a notification can be received when
// the emp table is updated.
// Start a transaction to update emp table
OracleTransaction txn = con.BeginTransaction();
// Create a new command which will update emp table
string updateCmdText =
    "update emp set sal = sal + 10 where empno = 7782";
OracleCommand updateCmd = new OracleCommand(updateCmdText, con);
// Update the emp table
updateCmd.ExecuteNonQuery();
//When the transaction is committed, a notification will be sent from
//the database
txn.Commit();
}
catch (Exception e)
{
    Console.WriteLine(e.Message);
}

con.Close();
// Loop while waiting for notification
while(MyNotificationSample.IsNotified == false)
{
    Thread.Sleep(100);
}
}

public static void OnMyNotificaton(object src,
OracleNotificationEventArgs arg)
{
    Console.WriteLine("Notification Received");
    DataTable changeDetails = arg.Details;
    Console.WriteLine("Data has changed in {0}",
        changeDetails.Rows[0]["ResourceName"]);
    MyNotificationSample.IsNotified = true;
}
}

```

```
}  
}
```

## Best Practice Guidelines and Performance Considerations

This section provides guidelines for working with Continuous Query Notification and the ODP.NET notification framework, and discusses the performance impacts.

Every change notification registration consumes database memory, storage or network resources, or some combination thereof. The resource consumption further depends on the volume and size of the **invalidation message**. In order to scale well with a large number of mid-tier clients, Oracle recommends that the client implement these best practices:

- Few and mostly read-only tables  
There should be few registered objects, and these should be mostly read-only, with very infrequent invalidations. If an object is extremely volatile, then a large number of invalidation notifications are sent, potentially requiring a lot of space (in memory or on disk) in the invalidation queue. This is also true if a large number of objects are registered.
- Few rows updated for each table  
Transactions should update (or insert or delete) only a small number of rows within the registered tables. Depending on database resources, a whole table could be invalidated if too many rows are updated within a single transaction, for a given table.  
This policy helps to contain the size of a single invalidation message, and reduces disk storage for the invalidation queue.

**See Also:** *Oracle Database Advanced Application Developer's Guide* for further information on Continuous Query Notification

## OracleDataAdapter Safe Type Mapping

The ODP.NET `OracleDataAdapter` class provides the Safe Type Mapping feature to ensure that the following Oracle data types do not lose data when converted to their closely related .NET types in the `DataSet`:

- NUMBER
- DATE
- TimeStamp (refers to all TimeStamp objects)
- INTERVAL DAY TO SECOND

This section includes the following topics:

- [Comparison Between Oracle Data Types and .NET Types](#)
- [SafeMapping Property](#)

## Comparison Between Oracle Data Types and .NET Types

The following sections provide more details about the differences between the Oracle data types and the corresponding .NET types. In general, the Oracle data types allow a greater degree of precision than the .NET types do.



precision. The Oracle `INTERVAL DAY TO SECOND` type can represent values in units of  $e^{-9}$ , and the `.NET TimeSpan` type can represent only values in units of  $e^{-7}$ .

[Table 3–29](#) lists the maximum and minimum values for Oracle `INTERVAL DAY TO SECOND` and `.NET DateTime` types.

**Table 3–29 Oracle `INTERVAL DAY TO SECOND` to `.NET TimeSpan` Comparisons**

Value Limits	Oracle <code>INTERVAL DAY TO SECOND</code>	<code>.NET TimeSpan</code>
Maximum	+999999999 23:59:59.999999999	+10675199 02:48:05.4775807
Minimum	-999999999 23:59:59.999999999	-10675199 02:48:05.4775808

## SafeMapping Property

The `OracleDataAdapter Safe Type Mapping` feature prevents data loss when populating Oracle data for any of these types into a `.NET DataSet`. By setting the `SafeMapping` property appropriately, these types can be safely represented in the `DataSet`, as either of the following:

- `.NET byte[]` in Oracle format
- `.NET String`

By default, `Safe Type Mapping` is disabled.

### Using Safe Type Mapping

To use the `Safe Type Mapping` feature, the `OracleDataAdapter.SafeMapping` property must be set with a hash table of key-value pairs. The key-value pairs must map database table column names (of type `string`) to a `.NET` type (of type `Type`). `ODP.NET` supports `Safe Type Mapping` to `byte[]` and `String` types. Any other type mapping causes an exception.

In situations where the column names are not known at design time, an asterisk ("`*`") can be used to map all occurrences of database types to a safe `.NET` type. If both the valid column name and the asterisk are present, the column name is used.

---



---

#### Note:

- Database table column names are case-sensitive.
  - Column names in the hash table that correspond to invalid column names are ignored.
- 
- 

`Safe Type Mapping` as a string is more readable without further conversion. Converting certain Oracle data types to a string requires extra conversion, which can be slower than converting it to a `byte[]`. Conversion of `.NET` strings back to `ODP.NET` types relies on the formatting information of the session.

### SafeTyping Example

```
// C#
using System;
using System.Data;
using Oracle.DataAccess.Client;
```

```

class SafeMappingSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";

        // In this SELECT statement, EMPNO, HIREDATE and SALARY must be
        // preserved using safe type mapping.
        string cmdstr = "SELECT EMPNO, ENAME, HIREDATE, SAL FROM EMP";

        // Create the adapter with the selectCommand txt and the connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Get the connection from the adapter
        OracleConnection connection = adapter.SelectCommand.Connection;

        // Create the safe type mapping for the adapter
        // which can safely map column data to byte arrays, where
        // applicable. By executing the following statement, EMPNO, HIREDATE AND
        // SALARY columns will be mapped to byte[]
        adapter.SafeMapping.Add("*", typeof(byte[]));

        // Map HIREDATE to a string
        // If the column name in the EMP table is case-sensitive,
        // the safe type mapping column name must be case-sensitive.
        adapter.SafeMapping.Add("HIREDATE", typeof(string));

        // Map EMPNO to a string
        // If the column name in the EMP table is case-sensitive,
        // the safe type mapping column name must also be case-sensitive.
        adapter.SafeMapping.Add("EMPNO", typeof(string));
        adapter.SafeMapping.Add("SAL", typeof(string));

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];

        // Get the first row from the EMP table
        DataRow row = table.Rows[0];

        // Print out the row info
        Console.WriteLine("EMPNO Column: type = " + row["EMPNO"].GetType() +
            "; value = " + row["EMPNO"]);
        Console.WriteLine("ENAME Column: type = " + row["ENAME"].GetType() +
            "; value = " + row["ENAME"]);
        Console.WriteLine("HIREDATE Column: type = " + row["HIREDATE"].GetType()+
            "; value = " + row["HIREDATE"]);
        Console.WriteLine("SAL Column: type = " + row["SAL"].GetType() +
            "; value = " + row["SAL"]);
    }
}

```

**See Also:** ["SafeMapping"](#) on page 5-126

## OracleDataAdapter Requery Property

The `OracleDataAdapter.Requery` property controls whether or not queries are reexecuted for `OracleDataAdapter.Fill` calls after the initial `Fill` call.

The `OracleDataAdapter.Fill` method allows appending or refreshing data in the `DataSet`. When appending the `DataSet` using the same query with subsequent `Fill` calls, reexecuting the query may not be desirable.

When the `Requery` property is set to `true`, each subsequent `Fill` call reexecutes the query and fills the `DataSet`. This is an expensive operation, and if the reexecution is not required, set `Requery` to `false`. If any of the `SelectCommand` properties or associated parameters must be changed, `Requery` must be set to `true`.

When the `Requery` property is set to `false`, the `DataSet` has all the data as a snapshot at a particular time. The query is executed only for the first `Fill` call; subsequent `Fill` calls fetch the data from a cursor opened with the first execution of the query. This feature is supported only for forward-only fetches. `Fill` calls that try to fetch rows before the last fetched row raise an exception. The connection used for the first `Fill` call must be available for subsequent `Fill` calls.

When filling a `DataSet` with an `OracleRefCursor` object, the `Requery` property can be used in a similar manner. When the `Requery` property is set to `false`, both the connection used for the first `Fill` call and the `OracleRefCursor` object must be available for the subsequent `Fill` calls.

### See Also:

- ["Requery"](#) on page 5-126
- ["SelectCommand"](#) on page 5-127

## Guaranteeing Uniqueness in Updating DataSet to Database

This section describes how the `OracleDataAdapter` object configures the `PrimaryKey` and `Constraints` properties of the `DataTable` object which guarantee uniqueness when the `OracleCommandBuilder` object is updating `DataSet` changes to the database.

Using the `OracleCommandBuilder` object to dynamically generate DML statements to be executed against the database is one of the ways to reconcile changes made in a single `DataTable` object with the database.

In this process, the `OracleCommandBuilder` object must not be allowed to generate DML statements that may affect (update or delete) more than a single row in the database when reconciling a single `DataRow` change. Otherwise the `OracleCommandBuilder` could corrupt data in the database.

To guarantee that each `DataRow` object change affects only a single row, there must be a set of `DataColumn` objects in the `DataTable` for which all rows in the `DataTable` have a unique set of values. The set of `DataColumn` objects indicated by the properties `DataTable.PrimaryKey` and `DataTable.Constraints` meets this requirement. The `OracleCommandBuilder` object determines uniqueness in the `DataTable` by checking if the `DataTable.PrimaryKey` is not a null value or if there exists a `UniqueConstraint` object in the `DataTable.Constraints` collection.

This discussion first explains what constitutes uniqueness in `DataRow` objects and then explains how to maintain that uniqueness while updating, through the `DataTable` property configuration.

This section includes the following topics:



- [What Constitutes Uniqueness in DataRow Objects?](#)
- [Configuring PrimaryKey and Constraints Properties](#)
- [Updating Without PrimaryKey and Constraints Configuration](#)

## What Constitutes Uniqueness in DataRow Objects?

This section describes the minimal conditions that must be met to guarantee uniqueness of DataRow objects. The condition of uniqueness must be guaranteed before the DataTable.PrimaryKey and DataTable.Constraints properties can be configured, as described in the next section.

Uniqueness is guaranteed in a DataTable object if any one of the following is true:

- All the columns of the primary key are in the select list of the OracleDataAdapter.SelectCommand property.
- All the columns of a unique constraint are in the select list of the OracleDataAdapter.SelectCommand property, with at least one involved column having a NOT NULL constraint defined on it.
- All the columns of a unique index are in the select list of the OracleDataAdapter.SelectCommand property, with at least one of the involved columns having a NOT NULL constraint defined on it.
- A ROWID is present in the select list of the OracleDataAdapter.SelectCommand property.

---

---

**Note:** A set of columns, on which a unique constraint has been defined or a unique index has been created, requires at least one column that cannot be null for the following reason: if all the columns of the column set can be null, then multiple rows could exist that have a NULL value for each column in the column set. This would violate the uniqueness condition that each row has a unique set of values for the column set.

---

---

## Configuring PrimaryKey and Constraints Properties

If the minimal conditions described in "[What Constitutes Uniqueness in DataRow Objects?](#)" on page 3-109 are met, then the DataTable.PrimaryKey or DataTable.Constraints properties can be set.

After these properties are set, the OracleCommandBuilder object can determine uniqueness in the DataTable by checking the DataTable.PrimaryKey property or the presence of a UniqueConstraint object in the DataTable.Constraints collection. Once uniqueness is determined, the OracleCommandBuilder object can safely generate DML statements to update the database.

The OracleDataAdapter.FillSchema method attempts to set these properties according to this order of priority:

1. If the primary key is returned in the select list, it is set as the DataTable.PrimaryKey property.
2. If a set of columns that meets the following criteria is returned in the select list, it is set as the DataTable.PrimaryKey property.

Criteria: The set of columns has a unique constraint defined on it or a unique index created on it, with each column having a NOT NULL constraint defined on it.

3. If a set of columns that meets the following criteria is returned in the select list, a `UniqueConstraint` object is added to the `DataTable.Constraints` collection, but the `DataTable.PrimaryKey` property is not set.  
  
Criteria: The set of columns has a unique constraint defined on it or a unique index created on it, with at least one column having a `NOT NULL` constraint defined on it.
4. If a `ROWID` is part of the select list, it is set as the `DataTable.PrimaryKey` property.

Additionally, the `OracleDataAdapter.FillSchema` method performs as follows:

- Setting the `DataTable.PrimaryKey` property implicitly creates a `UniqueConstraint` object.
- If a column is part of the `DataTable.PrimaryKey` property or the `UniqueConstraint` object, or both, it will be repeated for each occurrence of the column in the select list.

## Updating Without PrimaryKey and Constraints Configuration

If the `DataTable.PrimaryKey` or `Constraints` properties have not been configured, for example, if the application has not called the `OracleDataAdapter.FillSchema` method, the `OracleCommandBuilder` object directly checks the select list of the `OracleDataAdapter.SelectCommand` property to determine if it guarantees uniqueness in the `DataTable`. However this check results in a database round-trip to retrieve the metadata for the `SELECT` statement of the `OracleDataAdapter.SelectCommand`.

Note that `OracleCommandBuilder` object cannot update a `DataTable` created from PL/SQL statements because they do not return any key information in their metadata.

## Globalization Support

ODP.NET globalization support enables applications to manipulate culture-sensitive data appropriately. This feature ensures proper string format, date, time, monetary, numeric, sort order, and calendar conventions depending on the Oracle globalization settings.

**See Also:** ["OracleGlobalization Class"](#) on page 10-2

This section includes the following:

- [Globalization Settings](#)
- [Globalization-Sensitive Operations](#)

## Globalization Settings

An `OracleGlobalization` object can be used to represent the following:

- [Client Globalization Settings](#)
- [Session Globalization Settings](#)
- [Thread-Based Globalization Settings](#)

## Client Globalization Settings

Client globalization settings are derived from the Oracle globalization setting (NLS\_LANG) in the Windows registry of the local computer. The client globalization parameter settings are read-only and remain constant throughout the lifetime of the application. These settings can be obtained by calling the `OracleGlobalization.GetClientInfo` static method.

The following example retrieves the client globalization settings:

```
// C#

using System;
using Oracle.DataAccess.Client;

class ClientGlobalizationSample
{
    static void Main()
    {
        OracleGlobalization ClientGlob = OracleGlobalization.GetClientInfo();

        Console.WriteLine("Client machine language: " + ClientGlob.Language);
        Console.WriteLine("Client character set: " + ClientGlob.ClientCharacterSet);
    }
}
```

The properties of the `OracleGlobalization` object provide the Oracle globalization value settings.

## Session Globalization Settings

Session globalization parameters are initially identical to client globalization settings. Unlike client settings, session globalization settings can be updated. However, they can be obtained only after establishing a connection against the database. The session globalization settings can be obtained by calling the `GetSessionInfo` method on the `OracleConnection` object. Invoking this method returns an instance of an `OracleGlobalization` class whose properties represent the globalization settings of the session.

When the `OracleConnection` object establishes a connection, it implicitly opens a session whose globalization parameters are initialized with those values specified by the client computer's Oracle globalization (or (NLS)) registry settings. The session settings can be updated and can change during its lifetime.

The following example changes the date format setting on the session:

```
// C#

using System;
using Oracle.DataAccess.Client;

class SessionGlobalizationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        OracleGlobalization SessionGlob = con.GetSessionInfo();
    }
}
```

```
// SetSessionInfo updates the Session with the new value
SessionGlob.DateFormat = "YYYY/MM/DD";
con.SetSessionInfo(SessionGlob);
Console.WriteLine("Date Format successfully changed for the session");

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
}
}
```

### Thread-Based Globalization Settings

Thread-based globalization parameter settings are specific to each thread. Initially, these settings are identical to the client globalization parameters, but they can be changed as specified by the application. When ODP.NET Types are converted to and from strings, the thread-based globalization parameters are used, if applicable.

Thread-based globalization parameter settings are obtained by invoking the `GetThreadInfo` static method of the `OracleGlobalization` class. The `SetThreadInfo` static method of the `OracleGlobalization` class can be called to set the thread's globalization settings.

ODP.NET classes and structures rely solely on the `OracleGlobalization` settings when manipulating culture-sensitive data. They do not use .NET thread culture information. If the application uses only .NET types, `OracleGlobalization` settings have no effect. However, when conversions are made between ODP.NET types and .NET types, `OracleGlobalization` settings are used where applicable.

---

---

**Note:** Changes to the `System.Threading.Thread.CurrentThread.CurrentCulture` property do not impact the `OracleGlobalization` settings of the thread or the session, or the reverse.

---

---

The following example shows how the thread's globalization settings are used by the ODP.NET Types:

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ThreadBasedGlobalizationSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleDate from a string using the DateFormat specified.
        OracleDate date = new OracleDate("1999-DEC-01");

        // Set a different DateFormat for the thread
        info.DateFormat = "MM/DD/YYYY";
        OracleGlobalization.SetThreadInfo(info);
    }
}
```

```

    // Print "12/01/1999"
    Console.WriteLine(date.ToString());
}
}

```

The `OracleGlobalization` object validates property changes made to it. If an invalid value is used to set a property, an exception is thrown. Note that changes made to the `Territory` and `Language` properties change other properties of the `OracleGlobalization` object implicitly.

**See Also:** *Oracle Database Globalization Support Guide* for more information on the properties affected by `Territory` and `Language` globalization settings

## Globalization-Sensitive Operations

This section lists ODP.NET types and operations that are dependent on or sensitive to globalization settings.

### Operations Dependent on Client Computer's Globalization Settings

The `OracleString` structure depends on the `OracleGlobalization` settings of the client computer. The client character set of the local computer is used when it converts a Unicode string to a `byte[]` in the `GetNonUnicode` method and when it converts a `byte[]` of ANSI characters to Unicode in the `OracleString` constructor that accepts a `byte[]`.

### Operations Dependent on Thread Globalization Settings

The thread globalization settings are used by ODP.NET types whenever they are converted to and from .NET string types, where applicable. Specific thread globalization settings are used in most cases, depending on the ODP.NET type, by the following:

- The `ToString` method
- The `Parse` static method
- Constructors that accept .NET string data
- Conversion operators to and from .NET strings

For example, the `OracleDate` type uses the `DateFormat` property of the thread globalization settings when the `ToString` method is invoked on it. This returns a `DATE` as a string in the format specified by the thread's settings.

For more details on the ODP.NET type methods that convert between ODP.NET types and .NET string types, and to identify which thread globalization settings are used for that particular method, read the remarks in [Chapter 10](#).

The thread globalization settings also affect data that is retrieved into the `DataSet` as a string using Safe Type Mapping. If the type is format-sensitive, the strings are always in the format specified by the thread globalization settings.

For example, `INTERVAL DAY TO SECOND` data is not affected by thread settings because no format is applicable for this type. However, the `DateFormat` and `NumericCharacters` properties can impact the string representation of `DATE` and `NUMBER` types, respectively, when they are retrieved as strings into the `DataSet` through Safe Type Mapping.

**See Also:**

- ["OracleDataAdapter Safe Type Mapping"](#) on page 3-104
- [Chapter 10, "Oracle Data Provider for .NET Globalization Classes"](#)
- [Chapter 14, "Oracle Data Provider for .NET Types Structures"](#)

**Operations Sensitive to Session Globalization Parameters**

Session globalization settings affect any data that is retrieved from or sent to the database as a string.

For example, if a `DATE` column is selected with the `TO_CHAR` function applied on it, the `DATE` column data will be a string in the date format specified by the `DateFormat` property of the session globalization settings. Transmitting data in the other direction, the string data that is to be inserted into the `DATE` column, must be in the format specified by the `DateFormat` property of the session globalization settings.

## Debug Tracing

ODP.NET provides debug tracing support, which allows logging of all the ODP.NET activities into a trace file. Different levels of tracing are available.

The provider can record the following information:

- Entry and exit information for the ODP.NET public methods
- User-provided SQL statements as well as SQL statements modified by the provider
- Connection pooling statistics such as enlistment and delistment
- Thread ID (entry and exit)
- HA Events and Load Balancing information
- Distributed Transactions
- Self-tuning information
- User-mode dumps upon unmanaged exceptions

To enable ODP.NET for tracing, `TraceFileName`, `TraceLevel`, and `TraceOption` must be set appropriately either in the Windows Registry or in an XML configuration file.

**See Also:** ["ODP.NET Configuration"](#) on page 3-114 for further details

## ODP.NET Configuration

The settings for specific versions of ODP.NET can be configured several ways for specific effects on precedence:

- The Windows registry entries are machine-wide settings for a particular version of ODP.NET.
- The `machine.config` settings are .NET framework-wide settings that override the Windows registry values.
- The application or web config file settings are application-specific settings that override the `machine.config` settings and the Windows registry settings.

- Any attribute settings that are equivalent to the connection string override everything.

The application or web config file can be useful and sometimes essential in scenarios where more than one application on a computer use the same version of ODP.NET, but each application needs a different ODP.NET configuration. The Windows registry value settings for a given version of ODP.NET affect all the applications that use that version of ODP.NET. However, having ODP.NET configuration values in the application or web config file assure that these settings are applied only for that application, thus providing more granularity.

For example, if the application or web.config file has a `StatementCacheSize` configuration setting of 100, this application-specific setting forces the version of ODP.NET that is loaded by that application to use 100 for the `StatementCacheSize` and overrides any setting in the `machine.config` and in the registry. Note that for any setting that does not exist in a config file (`machine.config` or application/web config), the value in the registry for a loaded version of ODP.NET is used, as in previous releases.

Note that ODP.NET reads the `machine.config` files from the version of the .NET Framework on which ODP.NET runs, not from the version of ODP.NET.

ODP.NET only reads the Windows Registry and the XML configuration file when it is loaded into memory, thus any configuration changes made after that are not read or used until the application is re-started.

## Supported Configuration Settings

ODP.NET supports the configuration of an attribute as follows:

- In the Windows registry.
- In an XML file.
- Through a different mechanism such as a connection string or programmatically through an ODP.NET class, if applicable.

[Table 3–30](#) describes each configurable attribute that is supported by ODP.NET. In the table, the term Configuration Support is followed by the types of configuration support (Windows registry, XML file, and so on) that are available for that attribute.

The table describes valid values as well as the default for each attribute.

---



---

**Note:** The default values shown are the values used for an attribute if the registry key does not exist or if it is not configured anywhere.

---



---

**Table 3–30 Configuration Attributes**

Attribute/Setting Name	Description
CheckConStatus	<p>Specifies whether the status of the connection is checked or not before putting the connection back into the connection pool. This registry entry is not created by the installation of ODP.NET. However, the default value 1 is used.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 1: Check the status of the connection. 0: Do not check the status of the connection.</p> <p>Default: 1</p>
DbNotificationPort	<p>Specifies the port number which ODP.NET listens to, for all notifications sent by the database for change notification, HA, or RLB features. ODP.NET does not throw any errors if an invalid or used port number is specified. The port can also be set to override the Windows registry and XML configuration file by setting the <code>OracleDependency.Port</code> static field.</p> <p>Configuration Support: XML file, and ODP.NET class</p> <p>Valid Values: -1: Open a random unused port to listen to. <math>n &gt; = 0</math>: Listen on port <math>n</math>.</p> <p>Default: -1</p>
DemandOraclePermission	<p>Specifies whether ODP.NET demands <code>OraclePermission</code> from the .NET application that is trying to access the database using ODP.NET.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0: Disables demands for <code>OraclePermission</code>. 1: Enables demands for <code>OraclePermission</code></p> <p>Default: 0</p>
DllPath	<p>Specifies the location where dependent unmanaged Oracle Client binaries load from.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: The path where dependent unmanaged Oracle Client binaries reside.</p> <p>Default: <code>ORACLE_BASE\ORACLE_HOME\bin</code></p>



**Table 3–30 (Cont.) Configuration Attributes**

Attribute/Setting Name	Description
DynamicEnlistment	<p>Specifies whether the application enlists in distributed transactions explicitly <i>after</i> an <code>OracleConnection.Open</code> method invocation through <code>EnlistTransaction()</code> or <code>EnlistDistributedTransaction()</code>. To configure ODP.NET to enable dynamic enlistment programmatically, the connection string must contain "enlist=dynamic".</p> <p>Configuration Support: Windows Registry, XML file, and "enlist" connection string attribute</p> <p>Valid Values: 0: Disables ability to explicitly enlist in distributed transactions. 1: Enables ability to explicitly enlist in distributed transactions. Default: 0</p>
FetchSize	<p>Specifies the total memory size, in bytes, that ODP.NET allocates to cache the data fetched from a database round-trip. This value can be set on the <code>OracleCommand</code> and the <code>OracleDataReader.FetchSize</code> property as well.</p> <p>Configuration Support: Windows Registry, XML file, and ODP.NET class</p> <p>Valid Values: 0 &lt;= n &lt;= <code>int.MaxValue</code>: n is the size of the cache in bytes. Default: 131072</p>
MaxStatementCacheSize	<p>Specifies the maximum number of statements that can be cached when self-tuning is enabled.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0 to <code>System.Int32.MaxValue</code>. Default: 100</p>
MetaDataXml	<p>Specifies the name of the XML file that customizes the queries to obtain the metadata the ADO.NET 2.0 <code>GetSchema</code> method returns. <code>MetaDataXml</code> can only be set in a configuration file.</p> <p>Configuration Support: XML file only</p> <p>Valid Values: A complete file name for the XML file. Default: <i>none</i></p>

**Table 3–30 (Cont.) Configuration Attributes**

Attribute/Setting Name	Description
PerformanceCounters	<p>Enables or disables publishing performance counters for connection pooling. Multiple performance counters can be obtained by adding the valid values.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Not Enabled</p> <p>1: Number of sessions being established with Oracle Database every second.</p> <p>2: Number of sessions being severed from Oracle Database every second.</p> <p>4: Number of active connections originating from connection pools every second.</p> <p>8: Number of active connections going back to the connection pool every second.</p> <p>16: Total number of active connections.</p> <p>32: Number of inactive connection pools.</p> <p>64: Total number of connections in use.</p> <p>128: Total number of connections available for use in all the connection pools.</p> <p>256: Number of pooled active connections.</p> <p>1024: Number of non-pooled active connections.</p> <p>2048: Number of connections that will be soon available in the pool. User has closed these connections, but they are currently awaiting actions, such transaction completion, before they can be placed back into the pool as free connections.</p> <p>4095: All the above</p> <p>Default: 0</p>
PromotableTransaction	<p>Specifies the type of transaction to use when the first connection participates in the <code>TransactionScope</code> object.</p> <p>Configuration Support: Windows Registry, XML file, and <i>promotable transaction</i> connection string attribute</p> <p>Valid Values:</p> <p><code>local</code>: The first connection opened in the <code>TransactionScope</code> object uses a local transaction.</p> <p><code>promotable</code>: The first connection and all subsequent connections opened in the same <code>TransactionScope</code> object enlist in the same distributed transaction.</p> <p>Default: <code>promotable</code></p>

**Table 3–30 (Cont.) Configuration Attributes**

Attribute/Setting Name	Description
SelfTuning	<p>Specifies whether self-tuning is enabled for an ODP.NET application.</p> <p>Configuration Support: Windows Registry, XML file, and Self Tuning connection string attribute</p> <p>Valid Values:</p> <p>0: Self Tuning is disabled. Used in the registry or XML file.</p> <p>false: Self Tuning is disabled. Used for the Self Tuning connection string attribute.</p> <p>1: Self Tuning is enabled. Used in the registry or XML file.</p> <p>true: Self Tuning is enabled. Used for the Self Tuning connection string attribute.</p> <p>Default: 1</p>
StatementCacheSize	<p>Specifies the number of cursors or statements to be cached on the database for each connection. This setting corresponds to <i>Statement Cache Size</i> attribute in the connection string. A value greater than zero also enables statement caching.</p> <p>Configuration Support: Windows Registry, XML file, and <i>Statement Cache Size</i> connection string attribute</p> <p>Valid Values:</p> <p>0 &lt;= <i>n</i> &lt;= the value of OPEN_CURSORS parameter set in <i>init.ora</i> database config file.</p> <p><i>n</i> is the number to set.</p> <p>Default: 0</p>
StatementCacheWithUdts	<p>Specifies whether or not Oracle UDTs retrieved by executing a <i>SELECT</i> statement are cached along with the statement in the statement cache. This setting affects the memory usage and performance of the application.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Oracle UDTs are not cached with statements.</p> <p>1: Oracle UDTs are cached along with statements.</p> <p>Default: 1</p>

**Table 3–30 (Cont.) Configuration Attributes**

Attribute/Setting Name	Description
ThreadPoolMaxSize	<p>Specifies the default maximum size of worker threads for each available processor in a process. This value may affect the performance of ODP.NET connection creation, command execution timeout, and external procedures (<code>extproc</code>) that use the thread pool. However, unnecessarily increasing thread pool maximum size can also cause performance problems.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p><code>0 &lt;= n &lt;= int.MaxValue</code>: Allows ODP.NET to reset thread pool maximum size with the value <i>n</i>. The ODP.NET reset operation may be ignored if the value is invalid. For example, if <i>n</i> is less than the number of available processors of the system. In this case, the result is the same as the value <code>-1</code>.</p> <p><code>-1</code>: Leave the thread pool max size as is.</p> <p>Default: <code>-1</code> (this registry entry is not created by default)</p> <p>Note that prior to ODAC 2007 or version 11.1.0.6.20, ODP.NET resets the thread pool maximum size to <code>int.MaxValue</code> when the <code>OracleCommand.CommandTimeout</code> property is set to a value greater than 0. This erroneous behavior has been corrected. <code>OracleCommand.CommandTimeout</code> does not change thread pool maximum size.</p>
TraceFileName	<p>Specifies the file name to be used for logging trace information.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>Any valid directory location and file name.</p> <p>Default: <code>c:\odpnet2.trc</code> (for .NET Framework 2.0)</p>

**Table 3–30 (Cont.) Configuration Attributes**

Attribute/Setting Name	Description
TraceLevel	<p>Specifies the level of tracing in ODP.NET. Because tracing all the entry and exit calls for all the objects can be excessive, TraceLevel is provided to limit tracing to certain areas of the provider. Each valid value indicates a possible tracing level. Compounded tracing levels can be obtained by adding the valid values.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <ul style="list-style-type: none"> <li>0: None</li> <li>1: Entry, exit, and SQL statement information</li> <li>2: Connection pooling statistics</li> <li>4: Distributed transactions (enlistment and delistment)</li> <li>8: User-mode dump creation upon unmanaged exception</li> <li>16: HA Event Information</li> <li>32: Load Balancing Information</li> <li>64: Self Tuning Information</li> <li>127: All the above</li> </ul> <p>Default: 0</p> <p><b>Note:</b> ODP.NET does bit-wise checking on the value. When tracing is enabled, logging to the trace file can affect ODP.NET performance.</p> <p><b>Note:</b> The user-mode dump creation requires <code>dbghelp.dll</code> version 5.1.2600.0 or later.</p>
TraceOption	<p>Specifies whether to log trace information in single or multiple files for different threads. If a single trace file is specified, the file name specified in <code>TraceFileName</code> is used. If the multiple trace files option is requested, a Thread ID is appended to the file name provided to create a trace file for each thread.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <ul style="list-style-type: none"> <li>0: Single trace file</li> <li>1: Multiple trace files</li> </ul> <p>Default: 0</p>
UdtCacheSize	<p>Specifies the size of the object cache for each connection in kilobytes (KB) that ODP.NET uses to retrieve and manipulate Oracle UDTs.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p><math>0 \leq n \leq 4194303</math>, <math>n</math> is the number to set.</p> <p>Default: 4096</p>

**Table 3–30 (Cont.) Configuration Attributes**

Attribute/Setting Name	Description
<i>UDT Mapping</i>	<p>Specifies a mapping between a custom type and an Oracle UDT in the database. The mappings can be specified in configuration files and custom type factories. However, if the mapping is specified in both places, mappings specified in the configuration files takes precedence over mappings specified using custom type factories.</p> <p>Configuration Support: XML file and Custom Type Factory Classes</p> <p>Valid Values: Any valid mapping.</p> <p>Default: <i>none</i></p>

## Sample Configuration Files

The following is an example of `app.config` for ODP.NET using .NET Framework 2.0, which sets some additional attributes as well as two UDT type mappings:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="-1"/>
      <add name="DllPath" value="C:\app\user\product\11.1.0\client_1\bin"/>
      <add name="DynamicEnlistment" value="0"/>
      <add name="FetchSize" value="131072"/>
      <add name="MetaDataXml" value="CustomMetaData.xml"/>
      <add name="PerformanceCounters" value="4095"/>
      <add name="PromotableTransaction" value="promotable"/>
      <add name="StatementCacheSize" value="50"/>
      <add name="ThreadPoolMaxSize" value="30"/>
      <add name="TraceFileName" value="c:\odpnet2.trc"/>
      <add name="TraceLevel" value="0"/>
      <add name="TraceOption" value="0"/>
      <add name="Person" value="udtMapping factoryName='PersonFactory, Sample,
        Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='PERSON'
        schemaName='SCOTT' dataSource='oracle'"/>
      <add name="Student" value="udtMapping factoryName='StudentFactory, Sample,
        Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='STUDENT'
        schemaName='SCOTT'"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

---

---

## Oracle Data Provider for .NET Server-Side Features

This chapter discusses server-side features provided by Oracle Data Provider for .NET. With the support for .NET stored procedures in Oracle Databases for Windows that Oracle Database Extensions for .NET provides, ODP.NET can be used to access Oracle data through the [implicit database connection](#) that is available from the context of the .NET stored procedure execution. Explicit user connections can also be created to establish connections to the database that hosts the .NET stored procedure or to other Oracle Databases.

**See Also:** *Oracle Database Extensions for .NET Developer's Guide*

This chapter contains these topics:

- [Introducing .NET Stored Procedure Execution Using ODP.NET](#)
- [Limitations and Restrictions on ODP.NET Within .NET Stored Procedure](#)
- [Porting Client Application to .NET Stored Procedure](#)

### Introducing .NET Stored Procedure Execution Using ODP.NET

Oracle Data Provider for .NET classes and APIs provide data access to the Oracle Database from a .NET client application and from .NET stored procedures and functions.

However, some limitations and restrictions exist when Oracle Data Provider for .NET is used within a .NET stored procedure. These are discussed in the next section.

The following is a simple .NET stored procedure example.

```
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

public class CLRLibrary1
{
    // .NET Stored Function returning the DEPTNO of the employee whose
    // EMPNO is 'empno'
    public static uint GetDeptNo(uint empno)
    {
        uint deptno = 0;

        // Create and open a context connection
```

```
OracleConnection conn = new OracleConnection();
if( OracleConnection.IsAvailable == true )
{
    conn.ConnectionString = "context connection=true";
}
else
{
    //set connection string for a normal client connection
    conn.ConnectionString = "user id=scott;password=tiger;" +
        "data source=oracle";
}
conn.Open();

// Create and execute a command
OracleCommand cmd = conn.CreateCommand();
cmd.CommandText = "SELECT DEPTNO FROM EMP WHERE EMPNO = :1";
cmd.Parameters.Add(":1", OracleDbType.Int32, empno,
    System.Data.ParameterDirection.Input);
OracleDataReader rdr = cmd.ExecuteReader();
if (rdr.Read())
    deptno = (uint)rdr.GetInt32(0);
rdr.Close();
cmd.Dispose();
conn.Close();
return deptno;
} // GetDeptNo
} // CLRLibrary1
```

**See Also:**

- *Oracle Database Extensions for .NET Developer's Guide* for more information about how to create .NET Stored procedures
- [Table 4–1, "API Support Comparison Between Client Application and .NET Stored Procedure"](#) on page 4-6

## Limitations and Restrictions on ODP.NET Within .NET Stored Procedure

This section covers important concepts that apply when Oracle Data Provider for .NET is used within a .NET stored procedure.

### Implicit Database Connection

Within a .NET stored procedure, an implicit database connection is available for use to access Oracle data. This implicit database connection should be used rather than establishing a user connection because the **implicit database connection** is already established by the caller of the .NET stored procedure, thereby minimizing resource usage.

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to "context connection=true" and invoke the `Open` method. No connection string attributes can be used with "context connection=true", except the `Statement Cache Size` attribute.

The availability of the implicit database connection can be checked at run time through the static `OracleConnection.IsAvailable` property. This property always returns `true` when Oracle Data Provider for .NET is used within a .NET stored procedure. Otherwise, `false` is returned.



---



---

**Note:** DBLinks are not supported in .NET stored procedures.

---



---

Only one implicit database connection is available within a .NET stored procedure invocation. To establish more connections in addition to the implicit database connection, an explicit connection must be created. When the `Close` method is invoked on the `OracleConnection` that represents the implicit database connection, the connection is not actually closed. Therefore, the `Open` method of the same or another `OracleConnection` object can be invoked to obtain the connection that represents the implicit database connection.

The implicit database connection can only be acquired by the `Open` method invocation by a native Oracle thread that initially invokes the .NET stored procedure. However, threads spawned from the native Oracle thread can use implicit database connections that are obtained by the native Oracle thread.

**See Also:** ["IsAvailable"](#) on page 5-71

## Transaction Support

The .NET stored procedure execution automatically inherits the current transaction on the implicit database connection. No explicit transaction can be started, committed, or rolled back inside a .NET stored procedure on a `Context` connection. However, explicit transaction can be started, committed, or rolled back inside a .NET stored procedure on a `Client` connection.

For example, `OracleConnection.BeginTransaction` is not allowed inside a .NET stored procedure for a context connection, but is allowed for a client connection. .NET stored procedures do not support distributed transactions. If you have enlisted a client connection in a distributed transaction and call a .NET stored procedure or function, an error occurs.

If a .NET stored procedure or function performs operations on the database that are required to be part of a transaction, the transaction must be started prior to calling the .NET stored procedure. Any desired commit or rollback must be performed after returning from the .NET stored procedure or function.

The following example consists of a client application and a .NET stored procedure, `InsertRecordSP`, that inserts an employee record into an `EMP` table.

### Example (.NET Stored Procedure)

```
using System;
using System.Data;
using Oracle.DataAccess.Client;
// This class represents an Oracle .NET stored procedure that inserts
// an employee record into an EMP table of SCOTT schema.
public class InsertRecordSP
{
    // This procedure will insert a row into the emp database
    // For simplicity we are using only two parameters, the rest are hard coded
    public static void InsertRecord( int EmpNo, string EmpName )
    {
        if(OracleConnection.IsAvailable == true )
        {
            OracleConnection conn = new OracleConnection(
                "context connection=true");
            conn.Open();
            // Create new command object from connection context
```

```

        OracleCommand Cmd = conn.CreateCommand();
        Cmd.CommandText = "INSERT INTO EMP( EMPNO, ENAME, JOB, " +
            "MGR, HIREDATE, SAL, COMM, DEPTNO ) " +
            "VALUES ( :1, :2, 'ANALYST', 7566, " +
            "'06-DEC-04', 5000, 0, 20 )";
        Cmd.Parameters.Add( ":1", OracleDbType.Int32,
            EmpNo, ParameterDirection.Input );
        Cmd.Parameters.Add( ":2", OracleDbType.Varchar2,
            EmpName, ParameterDirection.Input );
        Cmd.ExecuteNonQuery();
    }
}

```

### Example (Client Application)

The example enters new employee, Bernstein, employee number 7950, into the EMP table.

```

// C#
// This sample demonstrates how to start the transaction with ODP.NET client
// application and execute an Oracle .NET stored procedure that performs
// a DML operation. Since .NET stored procedure inherits the current
// transaction from the implicit database connection, DML operation
// in .NET stored procedure will not be in auto-committed mode.
// Therefore, it is up to the client application to do a COMMIT or ROLLBACK
// after returning from .NET stored procedure
using System;
using System.Data;
using Oracle.DataAccess.Client;
// In this class we are starting a transaction on the client side and
// executing a .NET stored procedure, which inserts a record into EMP
// table and then verifies record count before and after COMMIT statement
class TransactionSample
{
    static void Main(string[] args)
    {
        OracleConnection Conn = null;
        OracleTransaction Txn = null;
        OracleCommand Cmd = null;
        try
        {
            Console.WriteLine( "Sample: Open DB connection in non auto-committed "
                + "mode," +
                "DML operation performed by .NET stored " +
                "procedure doesn't have an effect before COMMIT " +
                "is called." );
            // Create and Open oracle connection
            Conn = new OracleConnection();
            Conn.ConnectionString = "User Id=scott;Password=tiger;" +
                "Data Source=oracle;";
            Conn.Open();
            // Start transaction
            Txn = Conn.BeginTransaction( IsolationLevel.ReadCommitted );
            // Create command object
            Cmd = new OracleCommand();
            Cmd.Connection = Conn;
            Cmd.CommandType = CommandType.StoredProcedure;
            Cmd.CommandText = "InsertRecord"; // .NET Stored procedure
            // Parameter settings
            OracleParameter EmpNoPrm = Cmd.Parameters.Add(

```

```

        "empno", OracleDbType.Int32 );
    EmpNoPrm.Direction = ParameterDirection.Input;
    EmpNoPrm.Value = 7950;
    OracleParameter EmpNamePrm = Cmd.Parameters.Add(
        "ename", OracleDbType.Varchar2, 10 );
    EmpNamePrm.Direction = ParameterDirection.Input;
    EmpNamePrm.Value = "Bernstein";
    // Execute .NET stored procedure
    Cmd.ExecuteNonQuery();
    Console.WriteLine( "Number of record(s) before COMMIT {0}",
        RecordCount() );
    Txn.Commit();
    Console.WriteLine( "Number of record(s) after COMMIT {0}",
        RecordCount() );
}
catch( OracleException OE )
{
    Console.WriteLine( OE.Message );
}
finally
{
    // Cleanup objects
    if( null != Txn )
        Txn.Dispose();
    if( null != Cmd )
        Cmd.Dispose();
    if( null != Conn && Conn.State == ConnectionState.Open )
        Conn.Close();
}
}
static int RecordCount()
{
    int EmpCount = 0;
    OracleConnection Conn = null;
    OracleCommand Cmd = null;
    try
    {
        Conn = new OracleConnection( "User Id=scott;Password=tiger;" +
            "Data Source=oracle;" );
        Conn.Open();
        Cmd = new OracleCommand( "SELECT COUNT(*) FROM EMP", Conn );
        Object o = Cmd.ExecuteScalar();
        EmpCount = Convert.ToInt32(o.ToString());
    }
    catch( OracleException OE )
    {
        Console.WriteLine( OE.Message );
    }
    finally
    {
        if( null != Cmd )
            Cmd.Dispose();
    }
    return EmpCount;
}
}

```

## Unsupported SQL Commands

Transaction controls commands such as `COMMIT`, `ROLLBACK`, and `SAVEPOINT` are not supported in a .NET stored procedure.

Data definition commands such as `CREATE` and `ALTER` are not supported with an implicit database connection, but they are supported with an explicit user connection in a .NET stored procedure.

## Oracle User-Defined Type (UDT) Support

UDTs are not supported within a context connection but they are supported with a client connection. UDTs are not supported as parameters to .NET stored procedures.

## Porting Client Application to .NET Stored Procedure

All classes and class members provide the same functionality for both client applications and .NET stored procedures, unless it is otherwise stated.

Table 4–1 lists those classes or class members that have different behavior depending on whether or not they are used in a client application or in a .NET stored procedure.

### Column Headings

The column heading for this table are:

Client application: The client application.

Implicit connection: The implicit database connections in a .NET stored procedure.

Explicit connection: The explicit user connections in a .NET stored procedure.

**Table 4–1 API Support Comparison Between Client Application and .NET Stored Procedure**

Class or Class Members	Client Application	Implicit Connection/ Explicit Connection
<a href="#">OnChangeEventHandler Delegate</a> -all members	Yes	No/No
<a href="#">OracleDependency Class</a> -all members	Yes	No/No
<a href="#">OracleNotificationEventArgs Class</a> -all members	Yes	No/No
<a href="#">OracleNotificationRequest Class</a> -all members	Yes	No/No
<a href="#">OracleFailoverEventArgs Class</a> -all members	Yes	No/No
<a href="#">OracleFailoverEventHandler Delegate</a> -all members	Yes	No/No
<a href="#">OracleTransaction Class</a> -all members	Yes	No/No
<a href="#">OracleCommand Class</a> -Transaction Property	Yes	No #1/No #1

**Table 4–1 (Cont.) API Support Comparison Between Client Application and .NET Stored Procedure**

<b>Class or Class Members</b>	<b>Client Application</b>	<b>Implicit Connection/ Explicit Connection</b>
<b>OracleConnection Class</b>		
-ConnectionTimeout Property	Yes	Yes #3/Yes
-DataSource Property	Yes	Yes #2/Yes
-BeginTransaction Method	Yes	No/Yes
-ChangeDatabase Method	No	No/No
-Clone Method	Yes	No/Yes
-EnlistDistributedTransaction Method	Yes	No/No
-OpenWithNewPassword Method	Yes	No/Yes
-Failover Event	Yes	No/No
-OracleFailoverEventHandler Delegate	Yes	No/No
<b>ODP.NET Enumerations</b>		
-FailoverEvent Enumeration	Yes	No/No
-FailoverReturnCode Enumeration	Yes	No/No
-FailoverType Enumeration	Yes	No/No
-OracleNotificationInfo Enumeration	Yes	No/No
-OracleNotificationSource Enumeration	Yes	No/No
-OracleNotificationType Enumeration	Yes	No/No

**Comments on Items in Table 4–1**

1. Always returns null.
2. Implicit database connection always returns an empty string.
3. Implicit database connection always returns 0.



---

## Oracle Data Provider for .NET Classes

This chapter describes the following Oracle Data Provider for .NET classes.

- OracleCommand Class
- OracleCommandBuilder Class
- OracleConnection Class
- OracleDataAdapter Class
- OracleDatabase Class
- OracleDataReader Class
- OracleError Class
- OracleErrorCollection Class
- OracleException Class
- OracleInfoMessageEventArgs Class
- OracleInfoMessageEventHandler Delegate
- OracleParameter Class
- OracleParameterCollection Class
- OraclePermission Class
- OraclePermissionAttribute Class
- OracleRowUpdatedEventArgs Class
- OracleRowUpdatedEventHandler Delegate
- OracleRowUpdatingEventArgs Class
- OracleRowUpdatingEventHandler Delegate
- OracleTransaction Class
- OracleCollectionType Enumeration
- OracleDBShutdownMode Enumeration
- OracleDBStartupMode Enumeration
- OracleDbType Enumeration
- OracleParameterStatus Enumeration

## OracleCommand Class

An `OracleCommand` object represents a SQL command, a stored procedure, or a table name. The `OracleCommand` object is responsible for formulating the request and passing it to the database. If results are returned, `OracleCommand` is responsible for returning results as an `OracleDataReader`, a `.NET XmlReader`, a `.NET Stream`, a scalar value, or as output parameters.

### Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.ComponentModel.Component`

`System.Data.Common.DbCommand (ADO.NET 2.0 only)`

`Oracle.DataAccess.Client.OracleCommand`

### Declaration

```
// ADO.NET 2.0: C#  
public sealed class OracleCommand : DbCommand, ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

The execution of any transaction-related statements from an `OracleCommand` is not recommended because it is not reflected in the state of the `OracleTransaction` object represents the current local transaction, if one exists.

`ExecuteXmlReader`, `ExecuteStream`, and `ExecuteToStream` methods are only supported for XML operations.

`ExecuteReader` and `ExecuteScalar` methods are not supported for XML operations.

To minimize the number of open server cursors, `OracleCommand` objects should be explicitly disposed.

### Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class OracleCommandSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        string cmdQuery = "select ename, empno from emp";
```



```
// Create the OracleCommand
OracleCommand cmd = new OracleCommand(cmdQuery);

cmd.Connection = con;
cmd.CommandType = CommandType.Text;

// Execute command, create OracleDataReader object
OracleDataReader reader = cmd.ExecuteReader();

while (reader.Read())
{
    // output Employee Name and Number
    Console.WriteLine("Employee Name : " + reader.GetString(0) + " , " +
        "Employee Number : " + reader.GetDecimal(1));
}

// Clean up
reader.Dispose();
cmd.Dispose();
con.Dispose();
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Members](#)
- [OracleCommand Constructors](#)
- [OracleCommand Static Methods](#)
- [OracleCommand Properties](#)
- [OracleCommand Public Methods](#)

## OracleCommand Members

OracleCommand members are listed in the following tables.

### OracleCommand Constructors

OracleCommand constructors are listed in [Table 5-1](#).

**Table 5-1 OracleCommand Constructors**

Constructor	Description
<a href="#">OracleCommand Constructors</a>	Instantiates a new instance of OracleCommand class (Overloaded)

### OracleCommand Static Methods

The OracleCommand static method is listed in [Table 5-2](#).

**Table 5-2 OracleCommand Static Method**

Method	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleCommand Properties

OracleCommand properties are listed in [Table 5-3](#).

**Table 5-3 OracleCommand Properties**

Property	Description
<a href="#">AddRowid</a>	Adds the ROWID as part of the select list
<a href="#">AddToStatementCache</a>	Causes executed statements to be cached, when the property is set to true and statement caching is enabled
<a href="#">ArrayBindCount</a>	Specifies if the array binding feature is to be used and also specifies the maximum number of array elements to be bound in the Value property
<a href="#">BindByName</a>	Specifies the binding method in the collection
<a href="#">CommandText</a>	Specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database
<a href="#">CommandTimeout</a>	Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception
<a href="#">CommandType</a>	Specifies the command type that indicates how the CommandText property is to be interpreted
<a href="#">Connection</a>	Specifies the OracleConnection object that is used to identify the connection to execute a command
<a href="#">Container</a>	Inherited from System.ComponentModel.Component
<a href="#">DesignTimeVisible</a>	Specifies whether or not the OracleCommand object is visible on designer controls.
<a href="#">FetchSize</a>	Specifies the size of OracleDataReader's internal cache to store result set data

**Table 5–3 (Cont.) OracleCommand Properties**

Property	Description
<a href="#">InitialLOBFetchSize</a>	Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LOB columns
<a href="#">InitialLONGFetchSize</a>	Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LONG and LONG RAW columns
<a href="#">Notification</a>	Indicates that there is a notification request for the command
<a href="#">NotificationAutoEnlist</a>	Indicates whether or not to register for a database change notification with the database automatically when the command is executed
<a href="#">Parameters</a>	Specifies the parameters for the SQL statement or stored procedure
<a href="#">RowSize</a>	Specifies the amount of memory needed by the <code>OracleDataReader</code> internal cache to store one row of data
<a href="#">Site</a>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Transaction</a>	Specifies the <code>OracleTransaction</code> object in which the <code>OracleCommand</code> executes <i>Not supported in a .NET stored procedure</i>
<a href="#">UpdatedRowSource</a>	Specifies how query command results are applied to the row being updated <i>Not supported in a .NET stored procedure</i>
<a href="#">XmlCommandType</a>	Specifies the type of XML operation on the <code>OracleCommand</code>
<a href="#">XmlQueryProperties</a>	Specifies the properties that are used when an XML document is created from the result set of a SQL query statement
<a href="#">XmlSaveProperties</a>	Specifies the properties that are used when an XML document is used to save changes to the database

### OracleCommand Public Methods

`OracleCommand` public methods are listed in [Table 5–4](#).

**Table 5–4 OracleCommand Public Methods**

Public Method	Description
<a href="#">Cancel</a>	Attempts to cancel a command that is currently executing on a particular connection
<a href="#">Clone</a>	Creates a copy of <code>OracleCommand</code> object
<a href="#">CreateObjRef</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">CreateParameter</a>	Creates a new instance of <code>OracleParameter</code> class
<a href="#">Dispose</a>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)

**Table 5–4 (Cont.) OracleCommand Public Methods**

Public Method	Description
<a href="#">ExecuteNonQuery</a>	Executes a SQL statement or a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the number of rows affected
<a href="#">ExecuteReader</a>	Executes a command (Overloaded)
<a href="#">ExecuteScalar</a>	Returns the first column of the first row in the result set returned by the query
<a href="#">ExecuteStream</a>	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the results in a new <code>Stream</code> object
<a href="#">ExecuteToStream</a>	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and appends the results as an XML document to the existing <code>Stream</code>
<a href="#">ExecuteXmlReader</a>	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the result as an XML document in a .NET <code>XmlTextReader</code> object
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>Prepare</code>	<i>This method is a no-op</i>
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)

## OracleCommand Constructors

OracleCommand constructors instantiate new instances of OracleCommand class.

### Overload List:

- [OracleCommand\(\)](#)

This constructor instantiates a new instance of OracleCommand class.

- [OracleCommand\(string\)](#)

This constructor instantiates a new instance of OracleCommand class using the supplied SQL command or stored procedure, and connection to the Oracle database.

- [OracleCommand\(string, OracleConnection\)](#)

This constructor instantiates a new instance of OracleCommand class using the supplied SQL command or stored procedure, and connection to the Oracle database.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

### OracleCommand()

This constructor instantiates a new instance of OracleCommand class.

### Declaration

```
// C#  
public OracleCommand();
```

### Remarks

Default constructor.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

### OracleCommand(string)

This constructor instantiates a new instance of OracleCommand class using the supplied SQL command or stored procedure, and connection to the Oracle database.

### Declaration

```
// C#  
public OracleCommand(string cmdText);
```

### Parameters

- *cmdText*

The SQL command or stored procedure to be executed.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

### OracleCommand(string, OracleConnection)

This constructor instantiates a new instance of `OracleCommand` class using the supplied SQL command or stored procedure, and connection to the Oracle database.

**Declaration**

```
// C#  
public OracleCommand(string cmdText, OracleConnection OracleConnection);
```

**Parameters**

- *cmdText*  
The SQL command or stored procedure to be executed.
- *OracleConnection*  
The connection to the Oracle database.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## OracleCommand Static Methods

The `OracleCommand` static method is listed in [Table 5-5](#).

**Table 5-5** *OracleCommand Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## OracleCommand Properties

OracleCommand properties are listed in [Table 5-6](#).

**Table 5-6 OracleCommand Properties**

Property	Description
<a href="#">AddRowid</a>	Adds the ROWID as part of the select list
<a href="#">AddToStatementCache</a>	Causes executed statements to be cached, when the property is set to <code>true</code> and statement caching is enabled
<a href="#">ArrayBindCount</a>	Specifies if the array binding feature is to be used and also specifies the maximum number of array elements to be bound in the <code>Value</code> property
<a href="#">BindByName</a>	Specifies the binding method in the collection
<a href="#">CommandText</a>	Specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database
<a href="#">CommandTimeout</a>	Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception
<a href="#">CommandType</a>	Specifies the command type that indicates how the <code>CommandText</code> property is to be interpreted
<a href="#">Connection</a>	Specifies the <code>OracleConnection</code> object that is used to identify the connection to execute a command
<code>Container</code>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">DesignTimeVisible</a>	Specifies whether or not the <code>OracleCommand</code> object is visible on designer controls.
<a href="#">FetchSize</a>	Specifies the size of <code>OracleDataReader</code> 's internal cache to store result set data
<a href="#">InitialLOBFetchSize</a>	Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LOB columns
<a href="#">InitialLONGFetchSize</a>	Specifies the amount that of data the <code>OracleDataReader</code> initially fetches for LONG and LONG RAW columns
<a href="#">Notification</a>	Indicates that there is a notification request for the command
<a href="#">NotificationAutoEnlist</a>	Indicates whether or not to register for a database change notification with the database automatically when the command is executed
<a href="#">Parameters</a>	Specifies the parameters for the SQL statement or stored procedure
<a href="#">RowSize</a>	Specifies the amount of memory needed by the <code>OracleDataReader</code> internal cache to store one row of data
<code>Site</code>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Transaction</a>	Specifies the <code>OracleTransaction</code> object in which the <code>OracleCommand</code> executes <i>Not supported in a .NET stored procedure</i>



**Table 5–6 (Cont.) OracleCommand Properties**

Property	Description
<a href="#">UpdatedRowSource</a>	Specifies how query command results are applied to the row being updated <i>Not supported in a .NET stored procedure</i>
<a href="#">XmlCommandType</a>	Specifies the type of XML operation on the OracleCommand
<a href="#">XmlQueryProperties</a>	Specifies the properties that are used when an XML document is created from the result set of a SQL query statement
<a href="#">XmlSaveProperties</a>	Specifies the properties that are used when an XML document is used to save changes to the database

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**AddRowid**

This property adds the ROWID as part of the select list.

**Declaration**

```
// C#
public bool AddRowid {get; set;}
```

**Property Value**

bool

**Remarks**

Default is false.

This ROWID column is hidden and is not accessible by the application. To gain access to the ROWIDs of a table, the ROWID must explicitly be added to the select list without the use of this property.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["LOB Support"](#) on page 3-61 for further information on how this property used with LOBs

**AddToStatementCache**

This property causes executed statements to be cached when the property is set to true and statement caching is enabled. If statement caching is disabled or if this property is set to false, the executed statement is not cached.

**Declaration**

```
// C#  
public bool AddToStatementCache{get; set;}
```

**Return Value**

Returns `bool` value. A value of `true` indicates that statements are being added to the cache, `false` indicates otherwise.

**Property Value**

A `bool` value that indicates that the statements will be cached when they are executed, if statement caching is enabled.

**Remarks**

Default is `true`.

`AddToStatementCache` is ignored if statement caching is disabled. Statement caching is enabled by setting the `Statement Cache Size` connection string attribute to a value greater than 0.

When statement caching is enabled, however, this property provides a way to selectively add statements to the cache.

**Example**

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class AddToStatementCacheSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle;" +  
            "statement cache size=10";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand("select * from emp", con);  
  
        if (cmd.AddToStatementCache)  
            Console.WriteLine("Added to the statement cache:" + cmd.CommandText);  
        else  
            Console.WriteLine("Not added to the statement cache:" + cmd.CommandText);  
  
        // The execution of "select * from emp" will be added to the statement cache  
        // because statement cache size is greater than 0 and OracleCommand's  
        // AddToStatementCache is true by default.  
        OracleDataReader readerEmp = cmd.ExecuteReader();  
  
        // Do not add "select * from dept" to the statement cache  
        cmd.CommandText = "select * from dept";  
        cmd.AddToStatementCache = false;  
  
        if (cmd.AddToStatementCache)  
            Console.WriteLine("Added to the statement cache:" + cmd.CommandText);  
        else
```

```

        Console.WriteLine("Not added to the statement cache:" + cmd.CommandText);

        // The execution of "select * from dept" will not be added to the
        // statement cache because AddToStatementCache is set to false.
        OracleDataReader readerDept = cmd.ExecuteReader();

        // Clean up
        con.Dispose();
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Statement Caching"](#) on page 3-42
- [ConnectionString](#) on page 5-78

**ArrayBindCount**

This property specifies if the array binding feature is to be used and also specifies the number of array elements to be bound in the `OracleParameter Value` property.

**Declaration**

```

// C#
public int ArrayBindCount {get; set;}

```

**Property Value**

An `int` value that specifies number of array elements to be bound in the `OracleParameter Value` property.

**Exceptions**

`ArgumentException` - The `ArrayBindCount` value specified is invalid.

**Remarks**

Default = 0.

If `ArrayBindCount` is equal to 0, array binding is not used; otherwise, array binding is used and `OracleParameter Value` property is interpreted as an array of values. The value of `ArrayBindCount` must be specified to use the array binding feature.

If neither `DbType` nor `OracleDbType` is set, it is strongly recommended that you set `ArrayBindCount` before setting the `OracleParameter Value` property so that inference of `DbType` and `OracleDbType` from `Value` can be correctly done.

Array binding is not used by default.

If the `XmlCommandType` property is set to any value other than `None`, this property is ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#) on page 3-39
- ["Value"](#) on page 5-276

**BindByName**

This property specifies the binding method in the collection.

**Declaration**

```
// C#  
public bool BindByName {get; set;}
```

**Property Value**

Returns `true` if the parameters are bound by name; returns `false` if the parameters are bound by position.

**Remarks**

Default = `false`.

`BindByName` is ignored under the following conditions:

- The value of the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.
- The value of the `XmlCommandType` property is `Query`, but there are no parameters set on the `OracleCommand`.

If the `XmlCommandType` property is `OracleXmlCommandType.Query` and any parameters are set on the `OracleCommand`, the `BindByName` property must be set to `true`. Otherwise, the following `OracleCommand` methods throw an `InvalidOperationException`.

- `ExecuteNonQuery`
- `ExecuteXmlReader`
- `ExecuteStream`
- `ExecuteToStream`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#) on page 3-39
- ["Value"](#) on page 5-276

**CommandText**

This property specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string CommandText {get; set;}
```

**Property Value**

A string.

**Implements**

IDbCommand

**Remarks**

The default is an empty string.

When the `CommandType` property is set to `StoredProcedure`, the `CommandText` property is set to the name of the stored procedure. The command calls this stored procedure when an `Execute` method is called.

The effects of `XmlCommandType` values on `CommandText` are:

- `XmlCommandType = None`.  
`CommandType` property determines the contents of `CommandText`.
- `XmlCommandType = Query`.  
`CommandText` must be a SQL query. The SQL query should be a select statement.  
`CommandType` property is ignored.
- `XmlCommandType` property is `Insert`, `Update`, or `Delete`.  
`CommandText` must be an XML document. `CommandType` property is ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**CommandTimeout**

This property specifies the number of seconds that the command is allowed to execute before terminating with an exception.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int CommandTimeout {get; set;}
```

**Property Value**

int

**Implements**

IDbCommand.CommandTimeout

**Exceptions**

`InvalidArgument` - The specified value is less than 0.

**Remarks**

Default is 0 seconds, which enforces no time limit.

When the specified timeout value expires before a command execution finishes, the command attempts to cancel. If cancellation is successful, an exception is thrown with the message of `ORA-01013: user requested cancel of current operation`. If the command executed in time without any errors, no exceptions are thrown.

In a situation where multiple `OracleCommand` objects use the same connection, the timeout expiration on one of the `OracleCommand` objects may terminate any of the executions on the single connection. To make the timeout expiration of a `OracleCommand` cancel only its own command execution, simply use one `OracleCommand` for each connection if that `OracleCommand` sets the `CommandTimeout` property to a value greater than 0.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

**CommandType**

This property specifies the command type that indicates how the `CommandText` property is to be interpreted.

**Declaration**

```
// ADO.NET 2.0: C#  
public override CommandType CommandType {get; set;}
```

**Property Value**

A `CommandType`.

**Exceptions**

`ArgumentException` - The value is not a valid `CommandType` such as: `CommandType.Text`, `CommandType.StoredProcedure`, `CommandType.TableDirect`.

**Remarks**

Default = `CommandType.Text`

If the value of the `XmlCommandType` property is not `None`, then the `CommandType` property is ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## Connection

This property specifies the `OracleConnection` object that is used to identify the connection to execute a command.

### Declaration

```
// C#  
public OracleConnection Connection {get; set;}
```

### Property Value

An `OracleConnection` object.

### Implements

`IDbCommand`

### Remarks

Default = null

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## DesignTimeVisible

This property specifies whether or not the `OracleCommand` object is visible on designer controls.

### Declaration

```
// C#  
public override bool DesignTimeVisible { get; set; }
```

### Property Value

A value that indicate whether or not `OracleCommand` object is visible in a control. The default is `true`.

### Remarks

This property is used by developers to indicate whether or not `OracleCommand` object is visible in a control.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## FetchSize

This property specifies the size of `OracleDataReader`'s internal cache to store result set data.

**Declaration**

```
// C#  
public long FetchSize {get; set;}
```

**Property Value**

A long that specifies the size (in bytes) of the `OracleDataReader`'s internal cache.

**Exceptions**

`ArgumentException` - The `FetchSize` value specified is invalid.

**Remarks**

Default = 131072.

The `FetchSize` property is inherited by the `OracleDataReader` that is created by a command execution returning a result set. The `FetchSize` property on the `OracleDataReader` object determines the amount of data the `OracleDataReader` fetches into its internal cache for each database round-trip.

If the `XmlCommandType` property is set to any value other than `None`, this property is ignored.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and `XMLType` data. Thus, applications can inadvertently fetch a large number of UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data do not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- `OracleDataReader` ["FetchSize"](#) on page 5-160

**InitialLOBFetchSize**

This property specifies the amount of data that the `OracleDataReader` initially fetches for LOB columns.

**Declaration**

```
// C#  
public int InitialLOBFetchSize {get; set;}
```



**Property Value**

An `int` specifying the number of characters or bytes to fetch initially.

**Exceptions**

`ArgumentException` - The `InitialLOBFetchSize` value specified is invalid.

**Remarks**

The value of `InitialLOBFetchSize` specifies the initial amount of LOB data that is immediately fetched by the `OracleDataReader`. The property value specifies the number of characters for CLOB and NCLOB data, and the number of bytes for BLOB data.

The `InitialLOBFetchSize` value is used to determine the length of the LOB column data to fetch, if the LOB column is in the select list. If the select list does not contain a LOB column, the `InitialLOBFetchSize` value is ignored.

When `InitialLOBFetchSize` is set to `-1`, the entire LOB data is prefetched and stored in the fetch array. Calls to `GetString`, `GetChars` or `GetBytes` in `OracleDataReader` allow retrieving the entire data. In this case, the following methods are disabled.

- `GetOracleBlob`
- `GetOracleClob`
- `GetOracleClobForUpdate`
- `GetOracleBlobForUpdate`

This feature works for retrieving data from Oracle Database 9i release 2 (9.2) and later  
Default = 0.

**For Oracle Database 10g release 2 (10.2) and later:**

The maximum value supported for `InitialLOBFetchSize` is 2 GB.

Prior to Oracle Database 10g release 2 (10.2), if the `InitialLOBFetchSize` is set to a nonzero value, `GetOracleBlob` and `GetOracleClob` methods were disabled. BLOB and CLOB data was fetched by using `GetBytes` and `GetChars` methods, respectively. In Oracle Database 10g release 2 (10.2), this restriction no longer exists. `GetOracleBlob` and `GetOracleClob` methods can be used for any `InitialLOBFetchSize` value zero or greater.

**For releases prior to Oracle Database 10g release 2 (10.2):**

The maximum value supported for `InitialLOBFetchSize` is 32 K.

To fetch more than the specified `InitialLOBFetchSize` value, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

If this property is set to 0, none of the preceding is required

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Obtaining LOB Data"](#) on page 3-52

**InitialLONGFetchSize**

This property specifies the amount of data that the `OracleDataReader` initially fetches for `LONG` and `LONG RAW` columns.

**Declaration**

```
// C#  
public int InitialLONGFetchSize {get; set;}
```

**Property Value**

An `int` specifying the amount.

**Exceptions**

`ArgumentException` - The `InitialLONGFetchSize` value specified is invalid.

**Remarks**

The maximum value supported for `InitialLONGFetchSize` is 32767. If this property is set to a higher value, the provider resets it to 32767.

The value of `InitialLONGFetchSize` specifies the initial amount of `LONG` or `LONG RAW` data that is immediately fetched by the `OracleDataReader`. The property value specifies the number of characters for `LONG` data and the number of bytes for `LONG RAW`. To fetch more than the specified `InitialLONGFetchSize` amount, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a `NOT NULL` constraint defined on it)

The `InitialLONGFetchSize` value is used to determine the length of the `LONG` and `LONG RAW` column data to fetch if one of the two is in the select list. If the select list does not contain a `LONG` or a `LONG RAW` column, the `InitialLONGFetchSize` value is ignored.

When `InitialLONGFetchSize` is set to `-1`, the entire `LONG` or `LONG RAW` data is prefetched and stored in the fetch array. Calls to `GetString`, `GetChars`, or `GetBytes` in `OracleDataReader` allow retrieving the entire data.

Default = 0.

Setting this property to 0 defers the `LONG` and `LONG RAW` data retrieval entirely until the application specifically requests it.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Obtaining LONG and LONG RAW Data"](#) on page 3-51 for further information

**Notification**

This instance property indicates that there is a notification request for the command.

**Declaration**

```
// C#
public OracleNotificationRequest Notification {set; get;}
```

**Property Value**

A notification request for the command.

**Remarks**

When a changed notification is first registered, the client listener is started in order to receive any database notification. The listener uses the port number defined in the `OracleDependency.Port` static field. Subsequent change notification registrations use the same listener in the same client process and do not start another listener.

When `Notification` is set to an `OracleNotificationRequest` instance, a notification registration is created (if it has not already been created) when the command is executed. Once the registration is created, the properties of the `OracleNotificationRequest` instance cannot be modified. If the notification registration has already been created, the result set that is associated with the command is added to the existing registration.

When `Notification` is set to `null`, subsequent command executions do not require a notification request. If a notification request is not required, set the `Notification` property to `null`, or set the `NotificationAutoEnlist` property to `false`.

For Continuous Query Notification, a notification request can be used for multiple command executions. In that case, any query result set associated with different commands can be invalidated within the same registration.

When the `OracleDependency.OnChange` event is fired, if the `ROWID` column is explicitly included in the query (or `AddRowid` property is set to `true`), then the `Rowid` column contains `ROWID` values in the `DataTable` referenced by the `OracleNotificationEventArgs.Details` property. This behavior can be overridden by explicitly requesting for an inclusion and exclusion of `ROWID` values in the `OracleNotificationEventArgs` by setting the `OracleDependency.RowidInfo` to `OracleRowidInfo.Include` or `OracleRowidInfo.Exclude`, respectively.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Database Change Notification Support"](#) on page 3-97
- [Chapter 9, "Database Change Notification"](#) on page 9-1

**NotificationAutoEnlist**

This instance property indicates whether or not to register for a database change notification with the database automatically when the command is executed.

**Declaration**

```
// C#  
public bool NotificationAutoEnlist {set; get;}
```

**Property Value**

A `bool` value indicating whether or not to make a database change notification request automatically, when the command is executed. If `NotificationAutoEnlist` is set to `true`, and the `Notification` property is set appropriately, a database change notification request is registered automatically; otherwise, no database change notification registration is made.

Default value: `true`

**Remarks**

A notification request can be used for multiple command executions using the same `OracleCommand` instance. In that case, set the `NotificationAutoEnlist` property to `true`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Database Change Notification Support"](#) on page 3-97
- [Chapter 9, "Database Change Notification"](#) on page 9-1

**Parameters**

This property specifies the parameters for the SQL statement or stored procedure.

**Declaration**

```
// C#  
public OracleParameterCollection Parameters {get;}
```

**Property Value**

`OracleParameterCollection`

**Implements**

IDbCommand

**Remarks**

Default value = an empty collection

The number of the parameters in the collection must be equal to the number of parameter placeholders within the command text, or an error is raised.

If the command text does not contain any parameter tokens (such as, :1, :2), the values in the `Parameters` property are ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**RowSize**

This property specifies the amount of memory needed by the `OracleDataReader` internal cache to store one row of data.

**Declaration**

```
// C#
public long RowSize {get;}
```

**Property Value**

A `long` that indicates the amount of memory (in bytes) that an `OracleDataReader` needs to store one row of data for the executed query.

**Remarks**

Default value = 0

The `RowSize` property is set to a nonzero value after the execution of a command that returns a result set. This property can be used at design time or dynamically during run time, to set the `FetchSize`, based on number of rows. For example, to enable the `OracleDataReader` to fetch `N` rows for each database round-trip, the `OracleDataReader FetchSize` property can be set dynamically to `RowSize * N`. Note that for the `FetchSize` to take effect appropriately, it must be set after `OracleCommand.ExecuteReader()` but before `OracleDataReader.Read()`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- `OracleDataReader FetchSize` on page 5-17

**Transaction**

This property specifies the `OracleTransaction` object in which the `OracleCommand` executes.

**Declaration**

```
// C#  
public OracleTransaction Transaction {get;}
```

**Property Value**

OracleTransaction

**Implements**

IDbCommand

**Remarks**

Default value = null

Transaction returns a reference to the transaction object associated with the OracleCommand connection object. Thus the command is executed in whatever transaction context its connection is currently in.

---

---

**Note:** When this property is accessed through an IDbCommand reference, its set accessor method is not operational.

---

---

**Remarks (.NET Stored Procedure)**

Always returns null.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**UpdatedRowSource**

This property specifies how query command results are applied to the row to be updated.

**Declaration**

```
// ADO.NET 2.0: C#  
public override UpdateRowSource UpdatedRowSource {get; set;}
```

**Property Value**

An UpdateRowSource.

**Implements**

IDbCommand

**Exceptions**

ArgumentException - The UpdateRowSource value specified is invalid.

**Remarks**

Always returns UpdateRowSource,

Set accessor throws an ArgumentException if the value is other than UpdateRowSource.None.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## XmlCommandType

This property specifies the type of XML operation on the `OracleCommand`.

**Declaration**

```
// C#  
public OracleXmlCommandType XmlCommandType {get; set;}
```

**Property Value**

An `OracleXmlCommandType`.

**Remarks**

Default value is `None`.

`XmlCommandType` values and usage:

- `None` - The `CommandType` property specifies the type of operation.
- `Query` - `CommandText` property must be set to a SQL select statement. The query is executed, and the results are returned as an XML document. The SQL select statement in the `CommandText` and the properties specified by the `XmlQueryProperties` property are used to perform the operation. The `CommandType` property is ignored.
- `Insert, Update, or Delete` - `CommandText` property is an XML document containing the changes to be made. The XML document in the `CommandText` and the properties specified by the `XmlSaveProperties` property are used to perform the operation. The `CommandType` property is ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## XmlQueryProperties

This property specifies the properties that are used when an XML document is created from the result set of a SQL query statement.

**Declaration**

```
// C#  
public OracleXmlQueryProperties XmlQueryProperties {get; set;}
```

**Property Value**

`OracleXmlQueryProperties`.

**Remarks**

When a new instance of `OracleCommand` is created, an instance of `OracleXmlQueryProperties` is automatically available on the `OracleCommand` instance through the `OracleCommand.XmlQueryProperties` property.

A new instance of `OracleXmlQueryProperties` can be assigned to an `OracleCommand` instance. Assigning an instance of `OracleXmlQueryProperties` to the `XmlQueryProperties` of an `OracleCommand` instance creates a new instance of the given `OracleXmlQueryProperties` instance for the `OracleCommand`. This way each `OracleCommand` instance has its own `OracleXmlQueryProperties` instance.

Use the default constructor to get a new instance of `OracleXmlQueryProperties`.

Use the `OracleXmlQueryProperties.Clone()` method to get a copy of an `OracleXmlQueryProperties` instance.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**XmlSaveProperties**

This property specifies the properties that are used when an XML document is used to save changes to the database.

**Declaration**

```
// C#  
public OracleXmlSaveProperties XmlSaveProperties {get; set;}
```

**Property Value**

`OracleXmlSaveProperties`.

**Remarks**

When a new instance of `OracleCommand` is created, an instance of `OracleXmlSaveProperties` is automatically available on the `OracleCommand` instance through the `OracleCommand.XmlSaveProperties` property.

A new instance of `OracleXmlSaveProperties` can be assigned to an `OracleCommand` instance. Assigning an instance of `OracleXmlSaveProperties` to the `XmlSaveProperties` of an `OracleCommand` instance creates a new instance of the given `OracleXmlSaveProperties` instance for the `OracleCommand`. This way each `OracleCommand` instance has its own `OracleXmlSaveProperties` instance.

Use the default constructor to get a new instance of `OracleXmlSaveProperties`.

Use the `OracleXmlSaveProperties.Clone()` method to get a copy of an `OracleXmlSaveProperties` instance.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)



## OracleCommand Public Methods

OracleCommand public methods are listed in [Table 5-7](#).

**Table 5-7 OracleCommand Public Methods**

Public Method	Description
<a href="#">Cancel</a>	Attempts to cancel a command that is currently executing on a particular connection
<a href="#">Clone</a>	Creates a copy of OracleCommand object
<a href="#">CreateObjRef</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">CreateParameter</a>	Creates a new instance of OracleParameter class
<a href="#">Dispose</a>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">ExecuteNonQuery</a>	Executes a SQL statement or a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the number of rows affected
<a href="#">ExecuteReader</a>	Executes a command (Overloaded)
<a href="#">ExecuteScalar</a>	Returns the first column of the first row in the result set returned by the query
<a href="#">ExecuteStream</a>	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the results in a new <code>Stream</code> object
<a href="#">ExecuteToStream</a>	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and appends the results as an XML document to the existing <code>Stream</code>
<a href="#">ExecuteXmlReader</a>	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the result as an XML document in a .NET <code>XmlTextReader</code> object
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">InitializeLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Prepare</a>	<i>This method is a no-op</i>
<a href="#">ToString</a>	Inherited from <code>System.Object</code>

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

### Cancel

This method attempts to cancel a command that is currently executing on a particular connection.

## Declaration

```
// ADO.NET 2.0: C#  
public override void Cancel();
```

## Implements

```
IDbCommand.Cancel
```

## Remarks

If cancellation of the command succeeds, an exception is thrown. If cancellation is not successful, no exception is thrown. If there is no command being executed at the time of the `Cancel` invocation, `Cancel` does nothing. Invoking the `Cancel` method does not guarantee that the command executing at the time will always be cancelled. The execution may complete before it can be terminated. In such cases, no exception is thrown.

When multiple `OracleCommand` objects share the same connection, only one command can be executed on that connection at any one time. When it is invoked, the `Cancel` method attempts to cancel the statement currently running on the connection that the `OracleCommand` object is using to execute the command. However, when multiple `OracleCommand` objects execute statements on the same connection simultaneously, issuing a `Cancel` method invocation may cancel any of the issued commands. This is because the command designated for cancellation may complete before the `Cancel` invocation is effective. If this happens, a command executed by a different `OracleCommand` could be cancelled instead.

There are several ways to avoid this non-deterministic situation that the `Cancel` method can cause:

- The application can create just one `OracleCommand` object for each connection. Doing so assures that the `Cancel` invocation only cancels commands executed by the `OracleCommand` object using a particular connection.
- Command executions in the application are synchronized between `OracleCommand` objects that use the same connection.

These suggestions do not apply if `Cancel` is not used in the application.

Because the termination on the currently running execution is non-deterministic, it is recommended that any *non-atomic* SQL or PL/SQL execution be started within a transaction. When the command execution successfully terminates with an exception of `ORA-01013: user requested cancel of current operation`, the transaction can be rolled back for data integrity. Examples of non-atomic execution are collections of DML command executions that are executed one-by-one and multiple DML commands that are part of a PL/SQL stored procedure or function.

## Example

```
// C#  
  
// This example shows how command executions can be cancelled in a  
// deterministic way even if multiple commands are executed on a single  
// connection. This is accomplished by synchronizing threads through events.  
// Since the Cancel method terminates the currently running operation on the  
// connection, threads must be serialized if multiple threads are using the  
// same connection to execute server round-trip incurring operations.  
// Furthermore, the example shows how the execution and cancel threads should  
// be synchronized so that nth iteration of the command execution does not  
// inappropriately cancel the (n+1)th command executed by the same thread.
```

```

using System;
using System.Data;
using Oracle.DataAccess.Client;
using System.Threading;

class CancelSample
{
    private OracleCommand cmd;
    Thread t1, t2;
    // threads signal following events when assigned operations are completed

    private AutoResetEvent ExecuteEvent = new AutoResetEvent(false);
    private AutoResetEvent CancelEvent = new AutoResetEvent(false);
    private AutoResetEvent FinishedEvent = new AutoResetEvent(false);
    AutoResetEvent[] ExecuteAndCancel = new AutoResetEvent[2];

    // Default constructor
    CancelSample()
    {
        cmd = new OracleCommand("select * from all_objects",
            new OracleConnection("user id=scott;password=tiger;data source=oracle"));
        ExecuteAndCancel[0] = ExecuteEvent;
        ExecuteAndCancel[1] = CancelEvent;
    }

    // Constructor that takes a particular command and connection
    CancelSample(string command, OracleConnection con)
    {
        cmd = new OracleCommand(command, con);
        ExecuteAndCancel[0] = ExecuteEvent;
        ExecuteAndCancel[1] = CancelEvent;
    }

    // Execution of the command
    public void Execute()
    {
        OracleDataReader reader = null;
        try
        {
            Console.WriteLine("Execute.");
            reader = cmd.ExecuteReader();
            Console.WriteLine("Execute Done.");
            reader.Close();
        }
        catch(Exception e)
        {
            Console.WriteLine("The command has been cancelled.", e.Message);
        }
        Console.WriteLine("ExecuteEvent.Set()");
        ExecuteEvent.Set();
    }

    // Canceling of the command
    public void Cancel()
    {
        try
        {
            // cancel query if it takes longer than 100 ms to finish execution
            System.Threading.Thread.Sleep(100);
            Console.WriteLine("Cancel.");
        }
    }
}

```

```
        cmd.Cancel();
    }
    catch (Exception e)
    {
        Console.WriteLine(e.ToString());
    }
    Console.WriteLine("Cancel done.");
    Console.WriteLine("CancelEvent.Set()");
    CancelEvent.Set();
}

// Execution of the command with a potential of cancelling
public void ExecuteWithinLimitedTime()
{
    for (int i = 0; i < 5; i++)
    {
        Monitor.Enter(typeof(CancelSample));
        try
        {
            Console.WriteLine("Executing " + this.cmd.CommandText);
            ExecuteEvent.Reset();
            CancelEvent.Reset();
            t1 = new Thread(new ThreadStart(this.Execute));
            t2 = new Thread(new ThreadStart(this.Cancel));
            t1.Start();
            t2.Start();
        }
        finally
        {
            WaitHandle.WaitAll(ExecuteAndCancel);
            Monitor.Exit(typeof(CancelSample));
        }
    }
    FinishedEvent.Set();
}

[MTAThread]
static void Main()
{
    try
    {
        AutoResetEvent[] ExecutionCompleteEvents = new AutoResetEvent[3];

        // Create the connection that is to be used by three commands
        OracleConnection con = new OracleConnection("user id=scott;" +
            "password=tiger;data source=oracle");
        con.Open();

        // Create instances of CancelSample class
        CancelSample test1 = new CancelSample("select * from all_objects", con);
        CancelSample test2 = new CancelSample("select * from all_objects, emp",
            con);
        CancelSample test3 = new CancelSample("select * from all_objects, dept",
            con);

        // Create threads for each CancelSample object instance
        Thread t1 = new Thread(new ThreadStart(test1.ExecuteWithinLimitedTime));
        Thread t2 = new Thread(new ThreadStart(test2.ExecuteWithinLimitedTime));
        Thread t3 = new Thread(new ThreadStart(test3.ExecuteWithinLimitedTime));

        // Obtain a handle to an event from each object
```

```

ExecutionCompleteEvents[0] = test1.FinishedEvent;
ExecutionCompleteEvents[1] = test2.FinishedEvent;
ExecutionCompleteEvents[2] = test3.FinishedEvent;

// Start all threads to execute three commands using a single connection
t1.Start();
t2.Start();
t3.Start();

// Wait for all three commands to finish executing/canceling before
//closing the connection
WaitHandle.WaitAll(ExecutionCompleteEvents);
con.Close();
}
catch (Exception e)
{
    Console.WriteLine(e.ToString());
}
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

**Clone**

This method creates a copy of an `OracleCommand` object.

**Declaration**

```
// C#
public object Clone();
```

**Return Value**

An `OracleCommand` object.

**Implements**

`ICloneable`

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**CreateParameter**

This method creates a new instance of `OracleParameter` class.

**Declaration**

```
// C#  
public OracleParameter CreateParameter();
```

**Return Value**

A new `OracleParameter` with default values.

**Implements**

`IDbCommand`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**ExecuteNonQuery**

This method executes a SQL statement or a command using the `XmlCommandType` and `CommandText` properties and returns the number of rows affected.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int ExecuteNonQuery();
```

**Return Value**

The number of rows affected.

**Implements**

`IDbCommand`

**Exceptions**

`InvalidOperationException` - The command cannot be executed.

**Remarks**

`ExecuteNonQuery` returns the number of rows affected, for the following:

- If the command is `UPDATE`, `INSERT`, or `DELETE` and the `XmlCommandType` property is set to `OracleXmlCommandType.None`.
- If the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`.

For all other types of statements, the return value is `-1`.

`ExecuteNonQuery` is used for either of the following:

- Catalog operations (for example, querying the structure of a database or creating database objects such as tables).
- Changing the data in a database without using a `DataSet`, by executing `UPDATE`, `INSERT`, or `DELETE` statements.
- Changing the data in a database using an XML document.

Although `ExecuteNonQuery` does not return any rows, it populates any output parameters or return values mapped to parameters with data.

If the `XmlCommandType` property is set to `OracleXmlCommandType.Query` then `ExecuteNonQuery` executes the select statement in the `CommandText` property, and if successful, returns -1. The XML document that is generated is discarded. This is useful for determining if the operation completes successfully without getting the XML document back as a result.

If the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`, then the value of the `CommandText` property is an XML document. `ExecuteNonQuery` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. The return value is the number of rows that are processed in the XML document. Also, each row in the XML document could affect multiple rows in the database, but the return value is still the number of rows in the XML document.

### Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteNonQuerySample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand(
            "select sal from emp where empno=7934", con);

        object sal = cmd.ExecuteScalar();
        Console.WriteLine("Employee sal before update: " + sal);

        cmd.CommandText = "update emp set sal = sal + .01 where empno=7934";

        // Auto-commit changes
        int rowsUpdated = cmd.ExecuteNonQuery();

        if (rowsUpdated > 0)
        {
            cmd.CommandText = "select sal from emp where empno=7934";
            sal = cmd.ExecuteScalar();
            Console.WriteLine("Employee sal after update: " + sal);
        }

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

### Requirements

For XML support, this method requires Oracle9i XML Developer's Kits (Oracle XDK) or later, to be installed in the database. Oracle XDK can be downloaded from Oracle Technology Network (OTN).

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://otn.oracle.com/>

## ExecuteReader

**Overload List:**

ExecuteReader executes a command specified in the `CommandText`.

- [ExecuteReader\(\)](#)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object.

- [ExecuteReader\(CommandBehavior\)](#)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object, using the specified `CommandBehavior` value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

## ExecuteReader()

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object.

**Declaration**

```
// C#  
public OracleDataReader ExecuteReader();
```

**Return Value**

An `OracleDataReader`.

**Implements**

`IDbCommand`

**Exceptions**

`InvalidOperationException` - The command cannot be executed.

**Remarks**

When the `CommandType` property is set to `CommandType.StoredProcedure`, the `CommandText` property should be set to the name of the stored procedure.

The specified command executes this stored procedure when `ExecuteReader` is called. If parameters for the stored procedure consist of `REF CURSOR` objects, behavior differs depending on whether `ExecuteReader()` or `ExecuteNonQuery()` is called.



If `ExecuteReader()` is invoked, REF CURSOR objects can be accessed through the `OracleDataReader` that is returned.

If more than one REF CURSOR is returned from a single execution, subsequent REF CURSOR objects can be accessed sequentially by the `NextResult` method on the `OracleDataReader`. If the `ExecuteNonQuery` method is invoked, the output parameter value can be cast to a `OracleRefCursor` type and the `OracleRefCursor` object then can be used to either populate a `DataSet` or create an `OracleDataReader` object from it. This approach provides random access to all the REF CURSOR objects returned as output parameters.

The value of 100 is used for the `FetchSize`. If 0 is specified, no rows are fetched. For further information, see ["Obtaining LONG and LONG RAW Data"](#) on page 3-51.

If the value of the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`, or `OracleXmlCommandType.Query` then the `ExecuteReader` method throws an `InvalidOperationException`.

### Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteReaderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand("select ename from emp", con);

        OracleDataReader reader = cmd.ExecuteReader();

        while (reader.Read())
        {
            Console.WriteLine("Employee Name : " + reader.GetString(0));
        }

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}
```

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["OracleRefCursor Class"](#) on page 13-113

## ExecuteReader(CommandBehavior)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object, using the specified behavior.

### Declaration

```
// C#  
public OracleDataReader ExecuteReader(CommandBehavior behavior);
```

### Parameters

- *behavior*  
The expected behavior.

### Return Value

An `OracleDataReader`.

### Implements

`IDbCommand`

### Exceptions

`InvalidOperationException` - The command cannot be executed.

### Remarks

A description of the results and the effect on the database of the query command is indicated by the supplied *behavior* that specifies command behavior.

For valid `CommandBehavior` values and for the command behavior of each `CommandBehavior` enumerated type, read the .NET Framework documentation.

When the `CommandType` property is set to `CommandType.StoredProcedure`, the `CommandText` property should be set to the name of the stored procedure. The command executes this stored procedure when `ExecuteReader()` is called.

If the stored procedure returns stored `REF CURSORS`, read the section on `OracleRefCursors` for more details. See "[OracleRefCursor Class](#)" on page 13-113.

The value of 100 is used for the `FetchSize`. If 0 is specified, no rows are fetched. For more information, see "[Obtaining LONG and LONG RAW Data](#)" on page 3-51.

If the value of the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`, or `OracleXmlCommandType.Query` then the `ExecuteReader` method throws an `InvalidOperationException`.

#### See Also:

- "[Oracle.DataAccess.Client Namespace](#)" on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- "[OracleRefCursor Class](#)" on page 13-113

## ExecuteScalar

This method executes the query using the connection, and returns the first column of the first row in the result set returned by the query.

## Declaration

```
// ADO.NET 2.0: C#  
public override object ExecuteScalar();
```

## Return Value

An object which represents the value of the first row, first column.

## Implements

IDbCommand

## Exceptions

`InvalidOperationException` - The command cannot be executed.

## Remarks

Extra columns or rows are ignored. `ExecuteScalar` retrieves a single value (for example, an aggregate value) from a database. This requires less code than using the `ExecuteReader()` method, and then performing the operations necessary to generate the single value using the data returned by an `OracleDataReader`.

If the query does not return any row, it returns `null`.

The `ExecuteScalar` method throws an `InvalidOperationException`, if the value of the `XmlCommandType` property is set to one of the following `OracleXmlCommandType` values: `Insert`, `Update`, `Delete`, `Query`.

## Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class ExecuteScalarSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand("select count(*) from emp", con);  
  
        object count = cmd.ExecuteScalar();  
  
        Console.WriteLine("There are {0} rows in table emp", count);  
  
        // Clean up  
        cmd.Dispose();  
        con.Dispose();  
    }  
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)

**ExecuteStream**

This method executes a command using the `XmlCommandType` and `CommandText` properties and returns the result as an XML document in a new `Stream` object.

**Declaration**

```
// C#  
public Stream ExecuteStream();
```

**Return Value**

A `Stream`.

**Remarks**

The behavior of `ExecuteStream` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`  
`ExecuteStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`  
`ExecuteStream` executes the select statement in the `CommandText` property, and if successful, returns an `OracleClob` object containing the XML document that was generated. `OracleClob` contains Unicode characters.  
  
If the SQL query does not return any rows, then `ExecuteStream` returns an `OracleClob` object containing an empty XML document.
- `XmlCommandType = OracleXmlCommandType.Insert`,  
`OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`.  
  
The value of the `CommandText` property is an XML document. `ExecuteStream` saves the data in that XML document to the table or view that is specified in the `XmlSaveProperties` property and an empty `OracleClob` is returned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- *Oracle XML DB Developer's Guide*
- <http://otn.oracle.com/>

**ExecuteToStream**

This method executes a command using the `XmlCommandType` and `CommandText` properties and appends the result as an XML document to the existing `Stream` provided by the application.

### Declaration

```
// C#  
public void ExecuteToStream(Stream outputStream);
```

### Parameters

- *outputStream*  
A Stream.

### Remarks

The behavior of `ExecuteToStream` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`  
`ExecuteToStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`  
`ExecuteToStream` executes the select statement in the `CommandText` property, and if successful, appends the XML document that was generated to the given Stream.

If the SQL query does not return any rows, then nothing is appended to the given Stream. The character set of the appended data is Unicode.

- `XmlCommandType = OracleXmlCommandType.Insert`,  
`OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`

The value of the `CommandText` property is an XML document.

`ExecuteToStream` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. Nothing is appended to the given Stream.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- *Oracle XML DB Developer's Guide*
- <http://otn.oracle.com/>

## ExecuteXmlReader

This method executes the command using the `XmlCommandType` and `CommandText` properties and returns the result as an XML document in a .NET `XmlTextReader` object.

### Declaration

```
// C#  
public XmlReader ExecuteXmlReader();
```

### Return Value

An `XmlReader`.

**Remarks**

The behavior of `ExecuteXmlReader` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`  
`ExecuteStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`  
`ExecuteXmlReader` executes the select statement in the `CommandText` property, and if successful, returns a .NET `XmlTextReader` object containing the XML document that was generated.

If the XML document is empty, which can happen if the SQL query does not return any rows, then an empty .NET `XmlTextReader` object is returned.

- `XmlCommandType = OracleXmlCommandType.Insert`,  
`OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`.

The value of the `CommandText` property is an XML document, and `ExecuteXmlReader` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. An empty .NET `XmlTextReader` object is returned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- *Oracle XML DB Developer's Guide*
- <http://otn.oracle.com/>

---

## OracleCommandBuilder Class

An `OracleCommandBuilder` object provides automatic SQL generation for the `OracleDataAdapter` when updates are made to the database.

### Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.ComponentModel.Component
            System.Data.Common.DbCommandBuilder (ADO.NET 2.0 only)
                Oracle.DataAccess.Client.OracleCommandBuilder
```

### Declaration

```
// ADO.NET 2.0: C#
public sealed class OracleCommandBuilder : DbCommandBuilder
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

`OracleCommandBuilder` automatically generates SQL statements for single-table updates when the `SelectCommand` property of the `OracleDataAdapter` is set. An exception is thrown if the `DataSet` contains multiple tables. The `OracleCommandBuilder` registers itself as a listener for `RowUpdating` events whenever its `DataAdapter` property is set. Only one `OracleDataAdapter` object and one `OracleCommandBuilder` object can be associated with each other at one time.

To generate `INSERT`, `UPDATE`, or `DELETE` statements, the `OracleCommandBuilder` uses `ExtendedProperties` within the `DataSet` to retrieve a required set of metadata. If the `SelectCommand` is changed after the metadata is retrieved (for example, after the first update), the `RefreshSchema` method should be called to update the metadata.

`OracleCommandBuilder` first looks for the metadata from the `ExtendedProperties` of the `DataSet`; if the metadata is not available, `OracleCommandBuilder` uses the `SelectCommand` property of the `OracleDataAdapter` to retrieve the metadata.

### Example

The following example performs an update on the `EMP` table. It uses the `OracleCommandBuilder` object to create the `UpdateCommand` for the `OracleDataAdapter` object when `OracleDataAdapter.Update()` is called.

```
// C#
using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleCommandBuilderSample
```

```
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT empno, sal from emp";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
        // the Command when needed
        OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];

        // Indicate DataColumn EMPNO is unique
        // This is required by the OracleCommandBuilder to update the EMP table
        table.Columns["EMPNO"].Unique = true;

        // Get the first row from the EMP table
        DataRow row = table.Rows[0];

        // Update the salary
        double sal = double.Parse(row["SAL"].ToString());
        row["SAL"] = sal + .01;

        // Now update the EMP using the adapter
        // The OracleCommandBuilder will create the UpdateCommand for the
        // adapter to update the EMP table
        adapter.Update(dataset, "EMP");

        Console.WriteLine("Row updated successfully");
    }
}
```

### Requirements

Namespace: Oracle.DataAccess.Client

Assembly: Oracle.DataAccess.dll

Microsoft .NET Framework Version: 2.0 or later



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Members](#)
- [OracleCommandBuilder Constructors](#)
- [OracleCommandBuilder Static Methods](#)
- [OracleCommandBuilder Properties](#)
- [OracleCommandBuilder Public Methods](#)
- [OracleCommandBuilder Events](#)

## OracleCommandBuilder Members

OracleCommandBuilder members are listed in the following tables.

### OracleCommandBuilder Constructors

OracleCommandBuilder constructors are listed in [Table 5-8](#).

**Table 5-8 OracleCommandBuilder Constructors**

Constructor	Description
<a href="#">OracleCommandBuilder Constructors</a>	Instantiates a new instance of OracleCommandBuilder class (Overloaded)

### OracleCommandBuilder Static Methods

OracleCommandBuilder static methods are listed in [Table 5-9](#).

**Table 5-9 OracleCommandBuilder Static Methods**

Method	Description
<a href="#">DeriveParameters</a>	Queries for the parameters of a stored procedure or function, represented by a specified OracleCommand, and populates the OracleParameterCollection of the command with the return values
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleCommandBuilder Properties

OracleCommandBuilder properties are listed in [Table 5-10](#).

**Table 5-10 OracleCommandBuilder Properties**

Property	Description
<a href="#">Container</a>	Inherited from System.ComponentModel.Component
<a href="#">CaseSensitive</a>	Indicates whether or not double quotes are used around Oracle object names when generating SQL statements
<a href="#">CatalogLocation</a>	<i>Not Supported</i>
<a href="#">CatalogSeparator</a>	<i>Not Supported</i>
<a href="#">ConflictOption</a>	<i>Not Supported</i>
<a href="#">DataAdapter</a>	Indicates the OracleDataAdapter for which the SQL statements are generated
<a href="#">QuotePrefix</a>	Specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">QuoteSuffix</a>	Specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">SchemaSeparator</a>	Specifies the character to be used for the separator between the schema identifier and other identifiers <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>

**Table 5–10 (Cont.) OracleCommandBuilder Properties**

Property	Description
Site	Inherited from <code>System.ComponentModel.Component</code>

## OracleCommandBuilder Public Methods

OracleCommandBuilder public methods are listed in [Table 5–11](#).

**Table 5–11 OracleCommandBuilder Public Methods**

Public Method	Description
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Inherited from <code>System.ComponentModel.Component</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">GetDeleteCommand</a>	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database
GetHashCode	Inherited from <code>System.Object</code>
<a href="#">GetInsertCommand</a>	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
<a href="#">GetUpdateCommand</a>	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform updates on the database
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">QuoteIdentifier</a>	Returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">RefreshSchema</a>	Refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements
<a href="#">UnquoteIdentifier</a>	Returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
ToString	Inherited from <code>System.Object</code>

## OracleCommandBuilder Events

The OracleCommandBuilder event is listed in [Table 5–12](#).

**Table 5–12 OracleCommandBuilder Events**

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)

## OracleCommandBuilder Constructors

OracleCommandBuilder constructors create new instances of the OracleCommandBuilder class.

### Overload List:

- [OracleCommandBuilder\(\)](#)

This constructor creates an instance of the OracleCommandBuilder class.

- [OracleCommandBuilder\(OracleDataAdapter\)](#)

This constructor creates an instance of the OracleCommandBuilder class and sets the DataAdapter property to the provided OracleDataAdapter object.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

### OracleCommandBuilder()

This constructor creates an instance of the OracleCommandBuilder class.

### Declaration

```
// C#  
public OracleCommandBuilder();
```

### Remarks

Default constructor.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

### OracleCommandBuilder(OracleDataAdapter)

This constructor creates an instance of the OracleCommandBuilder class and sets the DataAdapter property to the provided OracleDataAdapter object.

### Declaration

```
// C#  
public OracleCommandBuilder(OracleDataAdapter da);
```

### Parameters

- *da*

The OracleDataAdapter object provided.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## OracleCommandBuilder Static Methods

OracleCommandBuilder static methods are listed in [Table 5–13](#).

**Table 5–13 OracleCommandBuilder Static Methods**

Method	Description
<a href="#">DeriveParameters</a>	Queries for the parameters of a stored procedure or function, represented by a specified <code>OracleCommand</code> , and populates the <code>OracleParameterCollection</code> of the command with the return values
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## DeriveParameters

This method queries for the parameters of a stored procedure or function, represented by a specified `OracleCommand`, and populates the `OracleParameterCollection` of the command with the return values.

### Declaration

```
// C#
public static void DeriveParameters(OracleCommand command);
```

### Parameters

- *command*  
The command that represents the stored procedure or function for which parameters are to be derived.

### Exceptions

`InvalidOperationException` - The `CommandText` is not a valid stored procedure or function name, the `CommandType` is not `CommandType.StoredProcedure`, or the `Connection.State` is not `ConnectionState.Open`.

### Remarks

When `DeriveParameters` is used to populate the `Parameter` collection of an `OracleCommand` Object that represents a stored function, the return value of the function is bound as the first parameter (at position 0 of the `OracleParameterCollection`).

`DeriveParameters` can only be used for stored procedures or functions, not for anonymous PL/SQL blocks.

Invoking `DeriveParameters` deletes all existing parameters in the parameter collection of the command.

`DeriveParameters` incurs a database round-trip and should only be used during design time. To avoid unnecessary database round-trips in a production environment,

the `DeriveParameters` method itself should be replaced with the explicit parameter settings that were returned by the `DeriveParameters` method at design time.

`DeriveParameters` can only preserve the case of the stored procedure or function name if it is encapsulated by double-quotes. For example, if the stored procedure in the database is named `GetEmployees` with mixed-case, the `CommandText` property on the `OracleCommand` object must be set appropriately as in the following example:

```
cmd.CommandText = "\"GetEmployees\"";
```

Stored procedures and functions in a package must be provided in the following format:

```
<package name>.<procedure or function name>
```

For example, to obtain parameters for a stored procedure named `GetEmployees` (mixed-case) in a package named `EmpProcedures` (mixed-case), the name provided to the `OracleCommand` is:

```
"\"EmpProcedures\".\"GetEmployees\""
```

`DeriveParameters` cannot be used for object type methods.

The derived parameters contain all the metadata information that is needed for the stored procedure to execute properly. The application must provide the value of the parameters before execution, if required. The application may also modify the metadata information of the parameters before execution. For example, the `Size` property of the `OracleParameter` may be modified for PL/SQL character and string types to optimize the execution of the stored procedure.

The output values of derived parameters return as .NET Types by default. To obtain output parameters as provider types, the `OracleDbType` property of the parameter must be set explicitly by the application to override this default behavior. One quick way to do this is to set the `OracleDbType` to itself for all output parameters that should be returned as provider types.

The `BindByName` property of the supplied `OracleCommand` is left as is, but the application can change its value.

If the specified stored procedure or function is overloaded, the first overload is used to populate the parameters collection.

```
// Database Setup
/*
connect scott/tiger@oracle
CREATE OR REPLACE PROCEDURE MyOracleStoredProc (arg_in IN VARCHAR2,
  arg_out OUT VARCHAR2) IS
BEGIN
  arg_out := arg_in;
END;
/
*/

// C#
using System;
using System.Data;
using Oracle.DataAccess.Client;

class DeriveParametersSample
{
  static void Main()
  {
```



```
// Create the PL/SQL Stored Procedure MyOracleStoredProc as indicated in
// the preceding Database Setup

string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Create an OracleCommand
OracleCommand cmd = new OracleCommand("MyOracleStoredProc", con);
cmd.CommandType = CommandType.StoredProcedure;

// Derive Parameters
OracleCommandBuilder.DeriveParameters(cmd);
Console.WriteLine("Parameters Derived");

// Prints "Number of Parameters for MyOracleStoredProc = 2"
Console.WriteLine("Number of Parameters for MyOracleStoredProc = {0}",
    cmd.Parameters.Count);

// The PL/SQL stored procedure MyOracleStoredProc has one IN and
// one OUT parameter. Set the Value for the IN parameter.
cmd.Parameters[0].Value = "MyText";

// The application may modify the other OracleParameter properties also
// This sample uses the default Size for the IN parameter and modifies
// the Size for the OUT parameter

// The default size for OUT VARCHAR2 is 4000
// Prints "cmd.Parameters[1].Size = 4000"
Console.WriteLine("cmd.Parameters[1].Size = " + cmd.Parameters[1].Size);

// Set the Size for the OUT parameter
cmd.Parameters[1].Size = 6;

// Execute the command
cmd.ExecuteNonQuery();

// Prints "cmd.Parameters[1].Value = MyText"
Console.WriteLine("cmd.Parameters[1].Value = " + cmd.Parameters[1].Value);

con.Close();
con.Dispose();
}
}
```

## Example

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)
- [OracleCommand Class](#)
- [OracleParameter Class](#)
- [OracleParameterCollection Class](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

## OracleCommandBuilder Properties

OracleCommandBuilder properties are listed in [Table 5–14](#).

**Table 5–14 OracleCommandBuilder Properties**

Property	Description
Container	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">CaseSensitive</a>	Indicates whether or not double quotes are used around Oracle object names when generating SQL statements
<a href="#">CatalogLocation</a>	<i>Not Supported</i>
<a href="#">CatalogSeparator</a>	<i>Not Supported</i>
<a href="#">ConflictOption</a>	<i>Not Supported</i>
<a href="#">DataAdapter</a>	Indicates the <code>OracleDataAdapter</code> for which the SQL statements are generated
<a href="#">QuotePrefix</a>	Specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">QuoteSuffix</a>	Specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">SchemaSeparator</a>	Specifies the character to be used for the separator between the schema identifier and other identifiers <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
Site	Inherited from <code>System.ComponentModel.Component</code>

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

### CaseSensitive

This property indicates whether or not double quotes are used around Oracle object names (for example, tables or columns) when generating SQL statements.

#### Declaration

```
// C#
bool CaseSensitive {get; set;}
```

#### Property Value

A `bool` that indicates whether or not double quotes are used.

#### Remarks

Default = `false`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## CatalogLocation

This property is not supported.

**Declaration**

```
// ADO.NET 2.0: C#  
public override CatalogLocation CatalogLocation {get; set;}
```

**Exceptions**

NotSupportedException - This property is not supported.

**Remarks**

This property is not supported.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## CatalogSeparator

This property is not supported.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string CatalogSeparator {get; set;}
```

**Exceptions**

NotSupportedException - This property is not supported.

**Remarks**

This property is not supported.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## ConflictOption

This property is not supported.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string ConflictOption {get; set;}
```

**Exceptions**

NotSupportedException - This property is not supported.

**Remarks**

This property is not supported.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**DataAdapter**

This property indicates the `OracleDataAdapter` object for which the SQL statements are generated.

**Declaration**

```
// C#  
OracleDataAdapter DataAdapter {get; set;}
```

**Property Value**

An `OracleDataAdapter` object.

**Remarks**

Default = null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**QuotePrefix**

This property specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string QuotePrefix {get; set;}
```

**Property Value**

The beginning character or characters to use. The default value is "\".

**Remarks**

This property is independent of any `OracleConnection` or `OracleCommand` objects.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**QuoteSuffix**

This property specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string QuoteSuffix {get; set;}
```

**Property Value**

The ending character or characters to use. The default value is "\".

**Remarks**

This property is independent of any `OracleConnection` or `OracleCommand` objects.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**SchemaSeparator**

This property specifies the character to be used for the separator between the schema identifier and other identifiers.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string SchemaSeparator {get; set; }
```

**Property Value**

The character to be used as the schema separator.

**Exceptions**

`NotSupportedException` - The input value is not a dot (.).

**Remarks**

The default schema separator is a dot (.). The only acceptable value for this property is a dot (.).

This property is independent of any `OracleConnection` or `OracleCommand` objects.

### Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class SchemaSeperatorSample
{
    static void Main(string[] args)
    {
        try
        {
            OracleCommandBuilder cmdBuilder = new OracleCommandBuilder();

            //schemaSeparator is dot(.)
            Console.WriteLine("schemaSeparator is {0}",
                cmdBuilder.SchemaSeparator);

            //set the schemaseparator, only '.' is allowed.
            cmdBuilder.SchemaSeparator = ".";

            // the only acceptable value for this property is a dot (.)
            // Hence the following line will throw NotSupportedException
            cmdBuilder.SchemaSeparator = "!";
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            Console.WriteLine(ex.StackTrace);
        }
    }
}
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## OracleCommandBuilder Public Methods

OracleCommandBuilder public methods are listed in [Table 5–15](#).

**Table 5–15 OracleCommandBuilder Public Methods**

Public Method	Description
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
Equals	Inherited from System.Object (Overloaded)
<a href="#">GetDeleteCommand</a>	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database
GetHashCode	Inherited from System.Object
<a href="#">GetInsertCommand</a>	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
<a href="#">GetUpdateCommand</a>	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform updates on the database
InitializeLifetimeService	Inherited from System.MarshalByRefObject
<a href="#">QuoteIdentifier</a>	Returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">RefreshSchema</a>	Refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements
<a href="#">UnquoteIdentifier</a>	Returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
ToString	Inherited from System.Object

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

### GetDeleteCommand

This method gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database when an application calls Update() on the OracleDataAdapter.

#### Declaration

```
// C#
public OracleCommand GetDeleteCommand();
```



**Return Value**

An `OracleCommand`.

**Exceptions**

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**GetInsertCommand**

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform insertions on the database when an application calls `Update()` on the `OracleDataAdapter`.

**Declaration**

```
// C#  
public OracleCommand GetInsertCommand();
```

**Return Value**

An `OracleCommand`.

**Exceptions**

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**GetUpdateCommand**

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

**Declaration**

```
// C#  
public OracleCommand GetUpdateCommand();
```

**Return Value**

An `OracleCommand`.

**Exceptions**

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**QuoteIdentifier**

This method returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string QuoteIdentifier(string unquotedIdentifier);
```

**Parameters**

- *UnquotedIdentifier*  
An unquoted identifier string.

**Return Value**

The quoted version of the identifier. Embedded quotes within the identifier are properly escaped.

**Exceptions**

`ArgumentNullException` - The input parameter is null.

**Remarks**

This method is independent of any `OracleConnection` or `OracleCommand` objects.

**Example**

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class QuoteIdentifierSample  
{  
    static void Main(string[] args)  
    {  
        OracleCommandBuilder builder = new OracleCommandBuilder();
```

```

string quoteIdentifier = builder.QuoteIdentifier("US\"ER");

//quoteIdentifier for "US\"ER" is (\\"US\\"ER\\")
Console.WriteLine("quoteIdentifier is {0}" , quoteIdentifier);
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**RefreshSchema**

This method refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements.

**Declaration**

```

// ADO.NET 2.0: C#
public override void RefreshSchema();

```

**Remarks**

An application should call RefreshSchema whenever the SelectCommand value of the OracleDataAdapter object changes.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

**UnquoteIdentifier**

This method returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier.

**Declaration**

```

// ADO.NET 2.0: C#
public override string UnquoteIdentifier(string quotedIdentifier);

```

**Parameters**

- *quotedIdentifier*  
The quoted string identifier.

**Return Value**

The unquoted identifier, with escape notation for any embedded quotes removed.

**Exceptions**

- ArgumentNullException - The input parameter is null.
- ArgumentException - The input parameter is empty.

**Remarks**

This method is independent of any `OracleConnection` or `OracleCommand` objects.

**Example**

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class UnQuoteIdentifierSample
{
    static void Main(string[] args)
    {
        //create an OracleCommandBuilder object.
        OracleCommandBuilder builder = new OracleCommandBuilder();

        string identifier = "US\"ER";
        Console.WriteLine("Identifier is {0}", identifier);

        // quote the identifier
        string quoteIdentifier = builder.QuoteIdentifier(identifier);

        //quoteIdentifier of "US\"ER" is (\\"US\\"ER\\")
        Console.WriteLine("QuotedIdentifier is {0}" , quoteIdentifier);
        string unquoteIdentifier = builder.UnquoteIdentifier(quoteIdentifier);

        //And its unquoteIdentifier is US\"ER
        Console.WriteLine("UnquotedIdentifier is {0}" , unquoteIdentifier);
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## OracleCommandBuilder Events

The `OracleCommandBuilder` event is listed in [Table 5–16](#).

**Table 5–16** *OracleCommandBuilder Event*

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

## OracleConnection Class

An OracleConnection object represents a connection to an Oracle database.

### Class Inheritance

System.Object

System.MarshalByRefObject

System.ComponentModel.Component

System.Data.Common.DbConnection (ADO.NET 2.0 only)

Oracle.DataAccess.Client.OracleConnection

### Declaration

```
// ADO.NET 2.0: C#  
public sealed class OracleConnection : DbConnection, IDbConnection, ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class OracleConnectionSample  
{  
    static void Main()  
    {  
        // Connect  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Execute a SQL SELECT  
        OracleCommand cmd = con.CreateCommand();  
        cmd.CommandText = "select * from emp";  
        OracleDataReader reader = cmd.ExecuteReader();  
  
        // Print all employee numbers  
        while (reader.Read())  
            Console.WriteLine(reader.GetInt32(0));  
  
        // Clean up  
        reader.Dispose();  
        cmd.Dispose();  
        con.Dispose();  
    }  
}
```

**Requirements**

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Members](#)
- [OracleConnection Constructors](#)
- [OracleConnection Static Properties](#)
- [OracleConnection Static Methods](#)
- [OracleConnection Properties](#)
- [OracleConnection Public Methods](#)
- [OracleConnection Events](#)

## OracleConnection Members

OracleConnection members are listed in the following tables.

### OracleConnection Constructors

OracleConnection constructors are listed in [Table 5-17](#).

**Table 5-17 OracleConnection Constructors**

Constructor	Description
<a href="#">OracleConnection Constructors</a>	Instantiates a new instance of the OracleConnection class (Overloaded)

### OracleConnection Static Properties

The OracleConnection static property is listed in [Table 5-19](#).

**Table 5-18 OracleConnection Static Property**

Property	Description
<a href="#">IsAvailable</a>	Indicates whether or not the implicit database connection is available for use

### OracleConnection Static Methods

The OracleConnection static methods are listed in [Table 5-19](#).

**Table 5-19 OracleConnection Static Methods**

Method	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)
<a href="#">ClearPool</a>	Clears the connection pool that is associated with the provided OracleConnection object. Not supported in a .NET stored procedure
<a href="#">ClearAllPools</a>	Clears all connections from all the connection pools Not supported in a .NET stored procedure

### OracleConnection Properties

OracleConnection properties are listed in [Table 5-20](#).

**Table 5-20 OracleConnection Properties**

Property	Description
<a href="#">ActionName</a>	Specifies the action name for the connection
<a href="#">ClientId</a>	Specifies the client identifier for the connection
<a href="#">ClientInfo</a>	Specifies the client information for the connection
<a href="#">ConnectionString</a>	Specifies connection information used to connect to an Oracle database
<a href="#">ConnectionTimeout</a>	Indicates the maximum amount of time that the Open method can take to obtain a pooled connection before the request is terminated
<a href="#">Container</a>	Inherited from System.ComponentModel.Component
<a href="#">Database</a>	<i>Not Supported</i>



**Table 5–20 (Cont.) OracleConnection Properties**

Property	Description
DatabaseDomainName	Specifies the name of the database domain to which the connection is set
DatabaseName	Specifies the name of the database to which the connection is set
DataSource	Specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect
HostName	Specifies the name of the host to which the connection is set
InstanceName	Specifies the name of the instance to which the connection is set
ModuleName	Specifies the module name for the connection
ServerVersion	Specifies the version number of the Oracle database to which the OracleConnection has established a connection
ServiceName	Specifies the name of the service to which the connection is set
Site	Inherited from System.ComponentModel.Component
State	Specifies the current state of the connection
StatementCacheSize	Specifies the current size of the statement cache associated with this connection

### OracleConnection Public Methods

OracleConnection public methods are listed in [Table 5–21](#).

**Table 5–21 OracleConnection Public Methods**

Public Method	Description
BeginTransaction	Begins a local transaction (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i>
ChangeDatabase	<i>Not Supported</i>
Clone	Creates a copy of an OracleConnection object <i>Not supported in a .NET stored procedure</i>
Close	Closes the database connection
CreateCommand	Creates and returns an OracleCommand object associated with the OracleConnection object
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
EnlistDistributedTransaction	Enables applications to explicitly enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i>
EnlistTransaction	Enables applications to enlist in a specified distributed transaction <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i> Not supported in a .NET stored procedure
Equals	Inherited from System.Object (Overloaded)
FlushCache	Flushes all updates and deletes made through REF objects retrieved using this connection

**Table 5–21 (Cont.) OracleConnection Public Methods**

Public Method	Description
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">GetSchema</a>	Returns schema information for the data source of the <code>OracleConnection</code> <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetSessionInfo</a>	Returns or refreshes the property values of the <code>OracleGlobalization</code> object that represents the globalization settings of the session (Overloaded)
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Open</a>	Opens a database connection with the property settings specified by the <code>ConnectionString</code>
<a href="#">OpenWithNewPassword</a>	Opens a new connection with the new password <i>Not supported in a .NET stored procedure for context connection</i>
<a href="#">PurgeStatementCache</a>	Flushes the Statement Cache by closing all open cursors on the database, when statement caching is enabled
<a href="#">SetSessionInfo</a>	Alters the session's globalization settings with the property values provided by the <code>OracleGlobalization</code> object
ToString	Inherited from <code>System.Object</code>

## OracleConnection Events

`OracleConnection` events are listed in [Table 5–22](#).

**Table 5–22 OracleConnection Events**

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Failover</a>	An event that is triggered when an Oracle failover occurs <i>Not supported in a .NET stored procedure</i>
<a href="#">HAEvent</a>	An event that is triggered when an HA event occurs.
<a href="#">InfoMessage</a>	An event that is triggered for any message or warning sent by the database
<a href="#">StateChange</a>	An event that is triggered when the connection state changes

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)

## OracleConnection Constructors

OracleConnection constructors instantiate new instances of the OracleConnection class.

### Overload List:

- [OracleConnection\(\)](#)

This constructor instantiates a new instance of the OracleConnection class using default property values.

- [OracleConnection\(String\)](#)

This constructor instantiates a new instance of the OracleConnection class with the provided connection string.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

### OracleConnection()

This constructor instantiates a new instance of the OracleConnection class using default property values.

### Declaration

```
// C#  
public OracleConnection();
```

### Remarks

The properties for OracleConnection are set to the following default values:

- `ConnectionString` = empty string
- `ConnectionTimeout` = 15 (default value of 0 is used for the implicit database connection)
- `DataSource` = empty string
- `ServerVersion` = empty string

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

### OracleConnection(String)

This constructor instantiates a new instance of the OracleConnection class with the provided connection string.

### Declaration

```
// C#  
public OracleConnection(String connectionString);
```

### Parameters

- *connectionString*

The connection information used to connect to the Oracle database.

### Remarks

The `ConnectionString` property is set to the supplied *connectionString*. The `ConnectionString` property is parsed and an exception is thrown if it contains invalid connection string attributes or attribute values.

The properties of the `OracleConnection` object default to the following values unless they are set by the connection string:

- `ConnectionString` = empty string
- `ConnectionTimeout` = 15 (default value of 0 is used for the implicit database connection)
- `DataSource` = empty string
- `ServerVersion` = empty string

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## OracleConnection Static Properties

The `OracleConnection` static property is listed in [Table 5–23](#).

**Table 5–23 OracleConnection Static Property**

Property	Description
<a href="#">IsAvailable</a>	Indicates whether or not the implicit database connection is available for use

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## IsAvailable

This property indicates whether or the implicit database connection is available for use.

### Declaration

```
// C#
public static bool IsAvailable {get;}
```

### Property Value

Returns `true` if the implicit database connection is available for use.

### Remarks

The availability of the implicit database connection can be checked at run time through this static property. When Oracle Data Provider for .NET is used within a .NET stored procedure, this property always returns `true`. Otherwise, `false` is returned.

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to `"context connection=true"` and invoke the `Open` method.

Note that not all features that are available for an explicit user connection are available for an implicit database connection. See ["Implicit Database Connection"](#) on page 4-2 for details.

### Example

```
// C# (Library/DLL)
using System;
using Oracle.DataAccess.Client;

public class IsAvailableSample
{
    static void MyStoredProcedure()
    {
        OracleConnection con = new OracleConnection();
        if (OracleConnection.IsAvailable)
        {
            // This function is invoked as a stored procedure
        }
    }
}
```

```
        // Obtain the implicit database connection by setting
        //   "context connection=true" in the connection string
        con.ConnectionString = "context connection=true";
    }
    else
    {
        // This function is not invoked as a stored procedure
        // Set the connection string for a normal client connection
        con.ConnectionString = "user id=scott;password=tiger;data source=oracle";
    }

    con.Open();
    Console.WriteLine("connected!");
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## OracleConnection Static Methods

The `OracleConnection` static methods are listed in [Table 5–24](#).

**Table 5–24 OracleConnection Static Methods**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>ClearPool</code>	Clears the connection pool that is associated with the provided <code>OracleConnection</code> object. Not supported in a .NET stored procedure
<code>ClearAllPools</code>	Clears all connections from all the connection pools Not supported in a .NET stored procedure

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## ClearPool

This method clears the connection pool that is associated with the provided `OracleConnection` object.

### Declaration

```
// C#
public static void ClearPool(OracleConnection connection);
```

### Remarks

When this method is invoked, all idle connections are closed and freed from the pool. Currently used connections are not discarded until they are returned to the pool.

The `ClearPool` method should be invoked only when valid connections can be created (that is, the database is up and can be connected to). Otherwise, the `ClearPool` method may just create invalid connections to a downed database instance. Assuming valid database connections, a `ClearPool` invocation creates a connection pool with usable connections. Therefore, connection requests succeed even after the invocation of this method. Connections created after this method invocation are not cleared unless another invocation is made.

This method can be invoked with an `OracleConnection` object before opening the connection as well as after, provided the `ConnectionString` is properly set.

### Exceptions

`InvalidOperationException` – Either the connection pool cannot be found or the provided connection string is invalid.

### Example

```
// C#
// Sample demonstrating the use of ClearPool API in OracleConnection class

using System;
```

```
using Oracle.DataAccess.Client;

class ClearPoolSample
{
    static void Main()
    {
        Console.WriteLine("Running ClearPool sample..." );
        // Set the connection string
        string strConn = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min pool size=5;";
        OracleConnection conn = new OracleConnection(strConn);

        // Open the connection
        conn.Open();

        // Clears the connection pool associated with connection 'conn'
        OracleConnection.ClearPool (conn);

        // This connection will be placed back into the pool
        conn.Close ();

        // Open the connection again to create additional connections in the pool
        conn.Open();

        // Create a new connection object
        OracleConnection connNew = new OracleConnection(strConn);

        // Clears the pool associated with Connection 'connNew'
        // Since the same connection string is set for both the connections,
        // connNew and conn, they will be part of the same connection pool.
        // We need not do an Open() on the connection object before calling
        // ClearPool
        OracleConnection.ClearPool (connNew);

        // cleanup
        conn.Close();
        Console.WriteLine("Done!");
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## ClearAllPools

This method clears all connections from all the connection pools.

**Declaration**

```
// C#
public static void ClearAllPools();
```

**Remarks**

This call is analogous to calling `ClearPool` for all the connection pools that are created for the application.



## Exceptions

`InvalidOperationException` – No connection pool could be found for the application.

## Example

```
// C#
// Sample demonstrating the use of ClearAllPools API in OracleConnection class

using System;
using Oracle.DataAccess.Client;

class ClearAllPoolsSample
{
    static void Main()
    {
        Console.WriteLine("Running ClearAllPools sample..." );
        // Set the connection string
        string strConn = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min pool size=5;";
        OracleConnection conn = new OracleConnection(strConn);

        // Create another connection object with a different connection string
        string strConnNew = "User Id=scott;Password=tiger;Data Source=oracle;";
        OracleConnection connNew = new OracleConnection(strConnNew);

        // Open the connections. Separate pools are created for conn and connNew
        conn.Open();
        connNew.Open();

        // Clears the pools associated with conn and connNew
        OracleConnection.ClearAllPools ();

        // cleanup
        conn.Close();
        connNew.Close();
        Console.WriteLine("Done!");
    }
}
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["ClearPool" on page 5-73](#)

## OracleConnection Properties

OracleConnection properties are listed in [Table 5–25](#)

**Table 5–25 OracleConnection Properties**

Property	Description
<a href="#">ActionName</a>	Specifies the action name for the connection
<a href="#">ClientId</a>	Specifies the client identifier for the connection
<a href="#">ClientInfo</a>	Specifies the client information for the connection
<a href="#">ConnectionString</a>	Specifies connection information used to connect to an Oracle database
<a href="#">ConnectionTimeout</a>	Indicates the maximum amount of time that the <code>Open</code> method can take to obtain a pooled connection before the request is terminated
<code>Container</code>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Database</a>	<i>Not Supported</i>
<a href="#">DatabaseDomainName</a>	Specifies the name of the database domain to which the connection is set
<a href="#">DatabaseName</a>	Specifies the name of the database to which the connection is set
<a href="#">DataSource</a>	Specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect
<a href="#">HostName</a>	Specifies the name of the host to which the connection is set
<a href="#">InstanceName</a>	Specifies the name of the instance to which the connection is set
<a href="#">ModuleName</a>	Specifies the module name for the connection
<a href="#">ServerVersion</a>	Specifies the version number of the Oracle database to which the OracleConnection has established a connection
<a href="#">ServiceName</a>	Specifies the name of the service to which the connection is set
<code>Site</code>	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">State</a>	Specifies the current state of the connection
<a href="#">StatementCacheSize</a>	Specifies the current size of the statement cache associated with this connection

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

### ActionName

This property specifies the action name for the connection.

**Declaration**

```
// C#
public string ActionName {set;}
```

**Property Value**

The string to be used as the action name.

**Remarks**

The default value is `null`.

Using the `ActionName` property allows the application to set the action name in the application context for a given `OracleConnection` object.

The `ActionName` property is reset to `null` when the `Close` or `Dispose` method is called on the `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-16
- *Oracle Database Security Guide*

**ClientId**

This property specifies the client identifier for the connection.

**Declaration**

```
// C#  
public string ClientId {set;}
```

**Property Value**

The string to be used as the client identifier.

**Remarks**

The default value is `null`.

Using the `ClientId` property allows the application to set the client identifier in the application context for a given `OracleConnection` object.

Setting `ClientId` to `null` resets the client identifier for the connection. `ClientId` is set to `null` when the `Close` or `Dispose` method is called on the `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-16
- *Oracle Database Security Guide*

**ClientInfo**

This property specifies the client information for the connection.

**Declaration**

```
// C#  
public string ClientInfo {set;}
```

**Property Value**

The string to be used as the client information.

**Remarks**

The default value is null.

Using the `ClientInfo` property allows the application to set the client information in the application context for a given `OracleConnection` object.

The `ClientInfo` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-16
- *Oracle Database Security Guide*

**ConnectionString**

This property specifies connection information used to connect to an Oracle database.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string ConnectionString{get; set;}
```

**Property Value**

If the connection string is supplied through the constructor, this property is set to that string.

**Implements**

`IDbConnection`

**Exceptions**

`ArgumentException` - An invalid syntax is specified for the connection string.

`InvalidOperationException` - `ConnectionString` is being set while the connection is open.

**Remarks**

The default value is an empty string.

`ConnectionString` must be a string of attribute name and value pairings, separated by a semi-colon, for example:

```
"User Id=scott;password=tiger;data source=oracle"
```

If the `ConnectionString` is not in a proper format, an exception is thrown. All spaces are ignored unless they are within double quotes.

When the `ConnectionString` property is set, the `OracleConnection` object immediately parses the string for errors. An `ArgumentException` is thrown if the `ConnectionString` contains invalid attributes or invalid values. Attribute values for User Id, Password, Proxy User Id, Proxy Password, and Data Source (if provided) are not validated until the `Open` method is called.

The connection must be closed to set the `ConnectionString` property. When the `ConnectionString` property is reset, all previously set values are reinitialized to their default values before the new values are applied.

Starting with ODP.NET 11.1, password and proxy password connection string attribute values are accepted as case-sensitive strings. Thus, they are passed to the database for authentication in the case provided in the connection string. Therefore, if the database is configured to support case-sensitive passwords, passwords must be passed in the correct case.

If a connection string attribute is set more than once, the last setting takes effect and no exceptions are thrown.

Boolean connection string attributes can be set to either `true`, `false`, `yes`, or `no`.

### Remarks (.NET Stored Procedure)

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to `"context connection=true"` and invoke the `Open` method. Other connection string attributes cannot be used in conjunction with `"context connection"` when it is set to `true`.

### Supported Connection String Attributes

[Table 5–26](#) lists the supported connection string attributes.

**Table 5–26 Supported Connection String Attributes**

Connection String Attribute	Description	Default Value
Connection Lifetime	Maximum life time (in seconds) of the connection.  This attribute specifies the lifetime of the connection in seconds. Before the <code>Connection</code> is placed back into the pool, the lifetime of the connection is checked. If the lifetime of the connection exceeds this property value, the connection is closed and disposed of. If this property value is 0, the connection lifetime is never checked. Connections that have exceeded their lifetimes are not closed and disposed of, if doing so brings the number of connections in the pool below the <code>Min Pool Size</code> .	0

**Table 5–26 (Cont.) Supported Connection String Attributes**

Connection String Attribute	Description	Default Value
Connection Timeout	<p>Maximum time (in seconds) to wait for a free connection from the pool.</p> <p>This attribute specifies the maximum amount of time (in seconds) that the <code>Open()</code> method can take to obtain a pooled connection before it terminates the request. This value comes into effect only if no free connection is available from the connection pool and the <code>Max Pool Size</code> is reached. If a free connection is not available within the specified time, an exception is thrown. <code>Connection Timeout</code> does not limit the time required to open new connections.</p> <p>This attribute value takes effect for pooled connection requests and not for new connection requests.</p> <p>(The default value is 0 for the implicit database connection in a .NET stored procedure.)</p>	15
Context Connection	<p>Returns an implicit database connection if set to <code>true</code>.</p> <p>An implicit database connection can only be obtained from within a .NET stored procedure. Other connection string attributes cannot be used in conjunction with "context connection" when it is set to <code>true</code>.</p> <p><i>Supported in a .NET stored procedure only</i></p>	false
Data Source	<p>Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.</p>	empty string
DBA Privilege	<p>Administrative privileges <code>SYSDBA</code> or <code>SYSOPER</code>.</p> <p>This connection string attribute only accepts <code>SYSDBA</code> or <code>SYSOPER</code> as the attribute value. It is case-insensitive.</p>	empty string
Decr Pool Size	<p>Number of connections that are closed when an excessive amount of established connections are unused.</p> <p>This connection string attribute controls the maximum number of unused connections that are closed when the pool regulator makes periodic checks. The regulator thread is spawned every 3 minutes and closes up to <code>Decr Pool Size</code> amount of pooled connections if they are not used. The pool regulator never takes the total number of connections below the <code>Min Pool Size</code> by closing pooled connections.</p>	1
Enlist	<p>Controls the enlistment behavior and capabilities of a connection in context of COM+ transactions or <code>System.Transactions</code>.</p> <p>If this attribute is set to <code>true</code>, the connection is automatically enlisted in the thread's transaction context. If this attribute is <code>false</code>, no enlistments are made. If this attribute is set to <code>dynamic</code>, applications can dynamically enlist in distributed transactions. This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, <code>no</code>, or <code>dynamic</code>.</p>	true

**Table 5–26 (Cont.) Supported Connection String Attributes**

<b>Connection String Attribute</b>	<b>Description</b>	<b>Default Value</b>
HA Events	<p>Enables ODP.NET connection pool to proactively remove connections from the pool when an Oracle RAC service, service member, or node goes down.</p> <p>This feature can only used against an Oracle RAC database and only if "pooling=true".</p> <p>This attribute can be set to true, false, yes, or no.</p>	false
Load Balancing	<p>Enables ODP.NET connection pool to balance work requests across Oracle RAC instances based on the load balancing advisory and service goal.</p> <p>This feature can only used against an Oracle RAC database and only if "pooling=true".</p> <p>This attribute can be set to true, false, yes, or no.</p>	false
Incr Pool Size	<p>Number of new connections to be created when all connections in the pool are in use.</p> <p>This connection string attribute determines the number of new connections that are established when a pooled connection is requested, but no unused connections are available and Max Pool Size is not reached. If new connections have been created for a pool, the regulator thread skips a cycle and does not have an opportunity to close any connections for 6 minutes. Note, however, that some connections can be still be closed during this time if their lifetime has been exceeded.</p>	5
Max Pool Size	<p>Maximum number of connections in a pool.</p> <p>This attribute specifies the maximum number of connections allowed in the particular pool used by that OracleConnection. Simply changing this attribute in the connection string does not change the Max Pool Size restriction on a currently existing pool. Doing so simply creates a new pool with a different Max Pool Size restriction. This attribute must be set to a value greater than the Min Pool Size. This value is ignored unless Pooling is turned on.</p>	100
Metadata Pooling	<p>Caches metadata information.</p> <p>This attribute indicates whether or not metadata information for executed queries are cached for improved performance.</p>	True
Min Pool Size	<p>Minimum number of connections in a pool.</p> <p>This attribute specifies the minimum number of connections to be maintained by the pool during its entire lifetime. Simply changing this attribute in the connection string does not change the Min Pool Size restriction on a currently existing pool. Doing so simply creates a new pool with a different Min Pool Size restriction. This value is ignored unless Pooling is turned on.</p>	1
Password	<p>Password for the user specified by User Id.</p> <p>This attribute specifies an Oracle user's password. Password is case-sensitive by default for Oracle Database 11g release 1 (11.1) and later.</p>	empty string

**Table 5–26 (Cont.) Supported Connection String Attributes**

<b>Connection String Attribute</b>	<b>Description</b>	<b>Default Value</b>
Persist Security Info	Retrieval of the password in the connection string.  If this attribute is set to <code>false</code> , the <code>Password</code> value setting is not returned when the application requests the <code>ConnectionString</code> after the connection is successfully opened by the <code>Open()</code> method. This attribute can be set to either <code>true</code> , <code>false</code> , <code>yes</code> , or <code>no</code> .	<code>false</code>
Pooling	Connection pooling.  This attribute specifies whether or not connection pooling is to be used. Pools are created using an attribute value matching algorithm. This means that connection strings which only differ in the number of spaces in the connection string use the same pool. If two connection strings are identical except that one sets an attribute to a default value while the other does not set that attribute, both requests obtain connections from the same pool. This attribute can be set to either <code>true</code> , <code>false</code> , <code>yes</code> , or <code>no</code> .	<code>true</code>
Promotable Transaction	Promotable to distributed transaction or not.  If "promotable" is specified, the first and all subsequent connections opened in the same <code>TransactionScope</code> enlist in the same distributed transaction. If "local" is specified, the first connection opened in the <code>TransactionScope</code> uses a local transaction.	promotable
Proxy User Id	User name of the proxy user.  This connection string attribute specifies the middle-tier user, or the proxy user, who establishes a connection on behalf of a client user specified by the <code>User Id</code> attribute. ODP.NET attempts to establish a proxy connection if either the <code>Proxy User Id</code> or the <code>Proxy Password</code> attribute is set to a non-empty string.  For the proxy user to connect to an Oracle database using operating system authentication, the <code>Proxy User Id</code> must be set to <code>"/"</code> . The <code>Proxy Password</code> is ignored in this case. The <code>User Id</code> cannot be set to <code>"/"</code> when establishing proxy connections. The case of this attribute value is preserved.	empty string
Proxy Password	Password of the proxy user.  This connection string attribute specifies the password of the middle-tier user or the proxy user. This user establishes a connection on behalf of a client user specified by the <code>User Id</code> attribute. ODP.NET attempts to establish a proxy connection if either the <code>Proxy User Id</code> or the <code>Proxy Password</code> attribute is set to a non-empty string.  The case of this attribute value is preserved if it is surrounded by double quotes.	empty string
Statement Cache Purge	Statement cache purged when the connection goes back to the pool.  If statement caching is enabled, setting this attribute to <code>true</code> purges the <code>Statement Cache</code> when the connection goes back to the pool.	<code>false</code>



**Table 5–26 (Cont.) Supported Connection String Attributes**

Connection String Attribute	Description	Default Value
Statement Cache Size	Statement cache enabled and cache size set size, that is, the maximum number of statements that can be cached.  A value greater than zero enables statement caching and sets the cache size to itself.  This value should not be greater than the value of the OPEN_CURSORS parameter set in the <code>init.ora</code> database configuration file.	0
Self Tuning	Enables or disables self-tuning for the connection.  If self-tuning is enabled, then the <code>StatementCacheSize</code> settings in the registry, configuration files, and connection string are ignored.  If self-tuning is disabled, then a <code>StatementCacheSize</code> value of 0 is used unless <code>StatementCachSize</code> is specified in the registry, configuration file, or connection string.	true
User Id	Oracle user name.  This attribute specifies the Oracle user name. The case of this attribute value is preserved if it is surrounded by double quotes. For the user to connect to an Oracle database using operating system authentication, set the <code>User Id</code> to <code>" / "</code> . Any <code>Password</code> attribute setting is ignored in this case.	empty string
Validate Connection	Validation of connections coming from the pool.  Validation causes a round-trip to the database for each connection. Therefore, it should only be used when necessary.	false

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**ConnectionTimeout**

This property indicates the maximum amount of time that the `Open` method can take to obtain a pooled connection before the request is terminated.

**Declaration**

```
// ADO.NET 2.0: C#
public override int ConnectionTimeout {get;}
```

**Property Value**

The maximum time allowed for a pooled connection request, in seconds.

**Implements**

`IDbConnection`

**Remarks**

This property indicates the connection timeout that has been set using the `ConnectionString` attribute `Connection Timeout`.

This property is read-only.

**Remarks (.NET Stored Procedure)**

There is no connection string specified by the application and a connection on the implicit database is always available, therefore, this property is set to 0.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**Database**

This property is not supported.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string Database {get;}
```

**Property Value**

A string.

**Implements**

`IDbConnection.Database`

**Remarks**

This property is not supported. It always returns an empty string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**DatabaseDomainName**

This property specifies the name of the database domain that this connection is connected to.

**Declaration**

```
// C#  
public string DatabaseDomainName {get;}
```

**Property Value**

The database domain that this connection is connected to.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**DatabaseName**

This property specifies the name of the database that this connection is connected to.

**Declaration**

```
// C#  
public string DatabaseName {get;}
```

**Property Value**

The database that this connection is connected to.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**DataSource**

This property specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect

**Declaration**

```
// ADO.NET 2.0: C#  
public override string DataSource {get;}
```

**Property Value**

Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.

**Remarks (.NET Stored Procedure)**

The value of this property is always an empty string for the implicit database connection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**HostName**

This property specifies the name of the host that this connection is connected to.

**Declaration**

```
// C#  
public string HostName {get;}
```

**Property Value**

The host that this connection is connected to.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**InstanceName**

This property specifies the name of the instance that this connection is connected to.

**Declaration**

```
// C#  
public string InstanceName {get;}
```

**Property Value**

The instance that this connection is connected to.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**ModuleName**

This property specifies the module name for the connection.

**Declaration**

```
// C#  
public string ModuleName {set;}
```

**Property Value**

The string to be used as the module name.

**Remarks**

The default value is null.

Using the `ModuleName` property allows the application to set the module name in the application context for a given `OracleConnection` object.

The `ModuleName` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-16
- *Oracle Database Security Guide*

**ServerVersion**

This property specifies the version number of the Oracle database to which the OracleConnection has established a connection.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string ServerVersion {get;}
```

**Property Value**

The version of the Oracle database.

**Exceptions**

InvalidOperationException - The connection is closed.

**Remarks**

The default is an empty string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**ServiceName**

This property specifies the name of the service that this connection is connected to.

**Declaration**

```
// C#  
public string ServiceName {get;}
```

**Property Value**

The service that this connection is connected to.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**State**

This property specifies the current state of the connection.

**Declaration**

```
// ADO.NET 2.0: C#  
public override ConnectionState State {get;}
```

**Property Value**

The `ConnectionState` of the connection.

**Implements**

`IDbConnection`

**Remarks**

ODP.NET supports `ConnectionState.Closed` and `ConnectionState.Open` for this property. The default value is `ConnectionState.Closed`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**StatementCacheSize**

This property specifies the current size of the statement cache associated with this connection.

**Declaration**

```
// C#  
public int StatementCacheSize{get;}
```

**Property Value**

An integer value indicating the size of the statement cache.

**Remarks**

If self tuning is not enabled, then the default value of this property depends upon the statement cache size specified in the connection string, application configuration file, or the registry. If none of these values are specified, then a default value of 0 is used.

If self tuning is enabled, then the property value is adjusted automatically. Any values specified in the connection string, application configuration file, or the registry are ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## OracleConnection Public Methods

OracleConnection public methods are listed in [Table 5–27](#).

**Table 5–27 OracleConnection Public Methods**

Public Method	Description
<a href="#">BeginTransaction</a>	Begins a local transaction (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i>
<a href="#">ChangeDatabase</a>	<i>Not Supported</i>
<a href="#">Clone</a>	Creates a copy of an OracleConnection object <i>Not supported in a .NET stored procedure</i>
<a href="#">Close</a>	Closes the database connection
<a href="#">CreateCommand</a>	Creates and returns an OracleCommand object associated with the OracleConnection object
<a href="#">CreateObjRef</a>	Inherited from System.MarshalByRefObject
<a href="#">Dispose</a>	Inherited from System.ComponentModel.Component
<a href="#">EnlistDistributedTransaction</a>	Enables applications to explicitly enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i>
<a href="#">EnlistTransaction</a>	Enables applications to enlist in a specified distributed transaction <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i> Not supported in a .NET stored procedure
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)
<a href="#">FlushCache</a>	Flushes all updates and deletes made through REF objects retrieved using this connection
<a href="#">GetHashCode</a>	Inherited from System.Object
<a href="#">GetLifetimeService</a>	Inherited from System.MarshalByRefObject
<a href="#">GetSchema</a>	Returns schema information for the data source of the OracleConnection <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetSessionInfo</a>	Returns or refreshes the property values of the OracleGlobalization object that represents the globalization settings of the session (Overloaded)
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">InitializeLifetimeService</a>	Inherited from System.MarshalByRefObject
<a href="#">Open</a>	Opens a database connection with the property settings specified by the ConnectionString
<a href="#">OpenWithNewPassword</a>	Opens a new connection with the new password <i>Not supported in a .NET stored procedure for context connection</i>
<a href="#">PurgeStatementCache</a>	Flushes the Statement Cache by closing all open cursors on the database, when statement caching is enabled

**Table 5–27 (Cont.) OracleConnection Public Methods**

Public Method	Description
<a href="#">SetSessionInfo</a>	Alters the session's globalization settings with the property values provided by the <code>OracleGlobalization</code> object
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**BeginTransaction**

`BeginTransaction` methods begin local transactions.

**Overload List**

- [BeginTransaction\(\)](#)  
This method begins a local transaction.
- [BeginTransaction\(IsolationLevel\)](#)  
This method begins a local transaction with the specified isolation level.

**BeginTransaction()**

This method begins a local transaction.

**Declaration**

```
// C#
public OracleTransaction BeginTransaction();
```

**Return Value**

An `OracleTransaction` object representing the new transaction.

**Implements**

`IDbConnection`

**Exceptions**

`InvalidOperationException` - A transaction has already been started.

**Remarks**

The transaction is created with its isolation level set to its default value of `IsolationLevel.ReadCommitted`. All further operations related to the transaction must be performed on the returned `OracleTransaction` object.

**Remarks (.NET Stored Procedure)**

Using this method in a .NET stored procedure for context connection causes a `Not Supported` exception.



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**BeginTransaction(IsolationLevel)**

This method begins a local transaction with the specified isolation level.

**Declaration**

```
// C#  
public OracleTransaction BeginTransaction(IsolationLevel isolationLevel);
```

**Parameters**

- *isolationLevel*

The isolation level for the new transaction.

**Return Value**

An OracleTransaction object representing the new transaction.

**Implements**

IDbConnection

**Exceptions**

InvalidOperationException - A transaction has already been started.

ArgumentException - The isolationLevel specified is invalid.

**Remarks**

The following isolation levels are supported: IsolationLevel.ReadCommitted and IsolationLevel.Serializable.

Although the BeginTransaction method supports the IsolationLevel.Serializable isolation level, serializable transactions are not supported when using System.Transactions and TransactionScope.

Requesting other isolation levels causes an exception.

**Remarks (.NET Stored Procedure)**

Using this method in a .NET stored procedure for context connection causes a Not Supported exception.

**Example**

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class BeginTransactionSample  
{  
    static void Main()  
    {
```

```
string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Create an OracleCommand object using the connection object
OracleCommand cmd = con.CreateCommand();

// Start a transaction
OracleTransaction txn = con.BeginTransaction(IsolationLevel.ReadCommitted);

// Update EMP table
cmd.CommandText = "update emp set sal = sal + 100";
cmd.ExecuteNonQuery();

// Rollback transaction
txn.Rollback();
Console.WriteLine("Transaction rolledback");

// Clean up
txn.Dispose();
cmd.Dispose();
con.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## ChangeDatabase

This method is not supported.

**Declaration**

```
// ADO.NET 2.0: C#
public override void ChangeDatabase(string databaseName);
```

**Parameters**

- *databaseName*

The name of the database that replaces the current database name.

**Implements**

`IDbConnection.ChangeDatabase`

**Exceptions**

`NotSupportedException` - Method not supported.

**Remarks**

This method is not supported and throws a `NotSupportedException` if invoked.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## Clone

This method creates a copy of an `OracleConnection` object.

**Declaration**

```
// C#  
public object Clone();
```

**Return Value**

An `OracleConnection` object.

**Implements**

`ICloneable`

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**Remarks (.NET Stored Procedure)**

This method is not supported for an implicit database connection.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class CloneSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Need a proper casting for the return value when cloned  
        OracleConnection clonedCon = (OracleConnection)con.Clone();  
  
        // Cloned connection is always closed, regardless of its source,  
        // But the connection string should be identical  
        clonedCon.Open();  
        if (clonedCon.ConnectionString.Equals(con.ConnectionString))  
            Console.WriteLine("The connection strings are the same.");  
        else  
            Console.WriteLine("The connection strings are different.");  
  
        // Close and Dispose OracleConnection object  
        clonedCon.Dispose();  
    }  
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## Close

This method closes the connection to the database.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void Close();
```

**Implements**

IDbConnection

**Remarks**

Performs the following:

- Rolls back any pending transactions.
- Places the connection to the connection pool if connection pooling is enabled. Even if connection pooling is enabled, the connection can be closed if it exceeds the connection lifetime specified in the connection string. If connection pooling is disabled, the connection is closed.
- Closes the connection to the database.

The connection can be reopened using `Open()`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## CreateCommand

This method creates and returns an `OracleCommand` object associated with the `OracleConnection` object.

**Declaration**

```
// C#  
public OracleCommand CreateCommand();
```

**Return Value**

The `OracleCommand` object.

**Implements**

IDbConnection

**Example**

```
// C#
```

```

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CreateCommandSample
{
    static void Main()
    {
        // Connect
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Execute a SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select * from emp";
        OracleDataReader reader = cmd.ExecuteReader();

        // Print all employee numbers
        while (reader.Read())
            Console.WriteLine(reader.GetInt32(0));

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**EnlistDistributedTransaction**

This method enables applications to explicitly enlist in a specific distributed transaction after a connection has been opened.

**Declaration**

```

// C#
public void EnlistDistributedTransaction(ITransaction transaction);

```

**Parameters**

- *transaction*  
An *ITransaction* interface.

**Exceptions**

*InvalidOperationException* - The connection is part of a local transaction or the connection is closed.

**Remarks**

*EnlistDistributedTransaction* enables objects to enlist in a specific transaction that is passed to the method. The *ITransaction* interface can be obtained by

applying an (ITransaction) cast to the ContextUtil.Transaction property within the component that started the distributed transaction.

The connection must be open before calling this method or an InvalidOperationException is thrown.

If a connection is part of a local transaction that was started implicitly or explicitly while attempting to enlist in a distributed transaction, the local transaction is rolled back and an exception is thrown.

By default, distributed transactions roll back, unless the method-level AutoComplete declaration is set.

Invoking the commit on the ITransaction raises an exception.

Invoking the rollback on the ITransaction method and calling ContextUtil.SetComplete on the same distributed transaction raises an exception.

### Remarks (.NET Stored Procedure)

Using this method causes a Not Supported exception.

### Example

#### Application:

```
// C#

/* This is the class that will utilize the Enterprise Services
   component. This module needs to be built as an executable.

   The Enterprise Services Component DLL must be built first
   before building this module.
   In addition, the DLL needs to be referenced appropriately
   when building this application.
*/

using System;
using System.EnterpriseServices;
using DistribTxnSample;

class DistribTxnSample_App
{
    static void Main()
    {
        DistribTxnSample_Comp comp = new DistribTxnSample_Comp();
        comp.DoWork();
    }
}
```

#### Component:

```
// C#

/* This module needs to be
   1) built as a component DLL/Library
   2) built with a strong name

   This library must be built first before the application is built.
*/

using System;
```

```

using System.Data;
using Oracle.DataAccess.Client;
using System.EnterpriseServices;

namespace DistribTxnSample
{
    [Transaction(TransactionOption.RequiresNew)]
    public class DistribTxnSample_Comp : ServicedComponent
    {
        public void DoWork()
        {
            string constr =
                "User Id=scott;Password=tiger;Data Source=oracle;enlist=false";
            OracleConnection con = new OracleConnection(constr);
            con.Open();

            // Enlist in a distributed transaction
            con.EnlistDistributedTransaction((ITransaction)ContextUtil.Transaction);

            // Update EMP table
            OracleCommand cmd = con.CreateCommand();
            cmd.CommandText = "UPDATE emp set sal = sal + .01";
            cmd.ExecuteNonQuery();

            // Commit
            ContextUtil.SetComplete();

            // Dispose OracleConnection object
            con.Dispose();
        }
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["EnlistTransaction"](#) on page 5-97
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

**EnlistTransaction**

This method enlists the connection to the specified transaction.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

**Declaration**

```

// C#
public override void EnlistTransaction(Transaction transaction)

```

**Parameters**

- *transaction*  
A `System.Transactions.Transaction` object.

**Exceptions**

`InvalidOperationException` - The connection is part of a local transaction or the connection is closed.

**Remarks**

Invocation of this method immediately enlists the connection to a transaction that is specified by the provided transaction parameter.

If `OracleConnection` is still associated with a distributed transaction that has not completed from a previous `EnlistTransaction` method invocation, calling this method will cause an exception to be thrown.

In general, for transaction enlistments to succeed, the "enlist" connection string attribute must be set to either "true" or "dynamic" before invoking the `Open` method. Setting the "enlist" connection string attribute to "true" will implicitly enlist the connection when the `Open` method is called, if the connection is within a transaction context. Setting it to "dynamic" allows the connection to dynamically enlist in transactions when an `EnlistTransaction` or `EnlistDistributedTransaction` method is called. The "enlist" attribute should be set to "false" only if the connection will never enlist in a transaction.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["System.Transactions and Promotable Transactions"](#) on page 3-22
- ["EnlistDistributedTransaction"](#) on page 5-95

**FlushCache**

This method flushes all updates and deletes made through `REF` objects retrieved using this connection.

**Declaration**

```
// c#  
public void FlushCache();
```

**Exceptions**

`InvalidOperationException` - The specified connection is not open.

**Remarks**

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## GetSchema

GetSchema methods return schema information for the data source of the `OracleConnection`.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

**Overload List**

- [GetSchema\(\)](#)  
This method returns schema information for the data source of the `OracleConnection`.
- [GetSchema \(string collectionName\)](#)  
This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name.
- [GetSchema \(string collectionName, string\[\] restrictions\)](#)  
This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name and the specified string array for the restriction values.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## GetSchema()

This method returns schema information for the data source of the `OracleConnection`.

**Declaration**

```
// ADO.NET 2.0: C#  
public override DataTable GetSchema();
```

**Return Value**

A `DataTable` object.

**Exceptions**

`InvalidOperationException` – The connection is closed.

**Remarks**

This method returns a `DataTable` object that contains a row for each metadata collection available from the database.

The method is equivalent to specifying the String value "MetaDataCollections" when using the `GetSchema(String)` method.

**Example**

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get all the schema collections and write to an XML file.
                //The XML file name is Oracle.DataAccess.Client_Schema.xml
                DataTable dtSchema = conn.GetSchema();
                dtSchema.WriteXml(ProviderName + "_Schema.xml");
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine(ex.StackTrace);
            }
        }
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**GetSchema (string collectionName)**

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name.

**Declaration**

```
// ADO.NET 2.0: C#
public override DataTable GetSchema (string collectionName);
```

**Parameters***collectionName*

Name of the collection for which metadata is required.

**Return Value**

A DataTable object.

**Exceptions**

ArgumentException – The requested collection is not defined.

InvalidOperationException – The connection is closed.

InvalidOperationException – The requested collection is not supported by current version of Oracle database.

InvalidOperationException – No population string is specified for requested collection.

**Example**

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get MetaDataCollections and write to an XML file.
                //This is equivalent to GetSchema()
                DataTable dtMetadata =
                    conn.GetSchema(DbMetaDataCollectionNames.MetaDataCollections);
                dtMetadata.WriteXml(ProviderName + "_MetaDataCollections.xml");

                //Get Restrictions and write to an XML file.
                DataTable dtRestrictions =
                    conn.GetSchema(DbMetaDataCollectionNames.Restrictions);
                dtRestrictions.WriteXml(ProviderName + "_Restrictions.xml");

                //Get DataSourceInformation and write to an XML file.
                DataTable dtDataSrcInfo =
                    conn.GetSchema(DbMetaDataCollectionNames.DataSourceInformation);
                dtDataSrcInfo.WriteXml(ProviderName + "_DataSourceInformation.xml");
            }
            catch { }
        }
    }
}
```

```
//data types and write to an XML file.
DataTable dtDataTypes =
    conn.GetSchema(DbMetaDataCollectionNames.DataTypes);
dtDataTypes.WriteXml(ProviderName + "_DataTypes.xml");

//Get ReservedWords and write to an XML file.
DataTable dtReservedWords =
    conn.GetSchema(DbMetaDataCollectionNames.ReservedWords);
dtReservedWords.WriteXml(ProviderName + "_ReservedWords.xml");

//Get all the tables and write to an XML file.
DataTable dtTables = conn.GetSchema("Tables");
dtTables.WriteXml(ProviderName + "_Tables.xml");

//Get all the views and write to an XML file.
DataTable dtViews = conn.GetSchema("Views");
dtViews.WriteXml(ProviderName + "_Views.xml");

//Get all the columns and write to an XML file.
DataTable dtColumns = conn.GetSchema("Columns");
dtColumns.WriteXml(ProviderName + "_Columns.xml");
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**GetSchema (string collectionName, string[] restrictions)**

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name and the specified string array for the restriction values.

**Declaration**

```
// ADO.NET 2.0: C#
public override DataTable GetSchema (string collectionName,
    string[] restrictions);
```

**Parameters**

- *collectionName*  
The name of the collection of metadata being retrieved.
- *restrictions*  
An array of restrictions that apply to the metadata being retrieved.

**Return Value**

A `DataTable` object.

**Exception**

- `ArgumentException` – The requested collection is not defined.
- `InvalidOperationException` – One of the following conditions exist:
  - The connection is closed.
  - The requested collection is not supported by the current version of Oracle database.
  - More restrictions were provided than the requested collection supports.
  - No population string is specified for requested collection.

**Remarks**

This method takes the name of a metadata collection and an array of `String` values that specify the restrictions for filtering the rows in the returned `DataTable`. This returns a `DataTable` that contains only rows from the specified metadata collection that match the specified restrictions.

For example, if the `Columns` collection has three restrictions (`owner`, `tablename`, and `columnname`), to retrieve all the columns for the `EMP` table regardless of schema, the `GetSchema` method must pass in at least these values: `null`, `EMP`.

If no restriction value is passed in, default values are used for that restriction, which is the same as passing in `null`. This differs from passing in an empty string for the parameter value. In this case, the empty string (" ") is considered the value for the specified parameter.

`collectionName` is not case-sensitive, but restrictions (string values) are.

**Example**

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get Restrictions
                DataTable dtRestrictions =
```

```
        conn.GetSchema(DbMetaDataCollectionNames.Restrictions);

        DataView dv = dtRestrictions.DefaultView;

        dv.RowFilter = "CollectionName = 'Columns'";
        dv.Sort = "RestrictionNumber";

        for (int i = 0; i < dv.Count; i++)
            Console.WriteLine("{0} (default) {1}" ,
                dtRestrictions.Rows[i]["RestrictionName"],
                dtRestrictions.Rows[i]["RestrictionDefault"]);

        //Set restriction string array
        string[] restrictions = new string[3];

        //Get all columns from all tables owned by "SCOTT"
        restrictions[0] = "SCOTT";
        DataTable dtAllScottCols = conn.GetSchema("Columns", restrictions);

        // clear collection
        for (int i = 0; i < 3; i++)
            restrictions[i] = null;

        //Get all columns from all tables named "EMP" owned by any
        //owner/schema
        restrictions[1] = "EMP";
        DataTable dtAllEmpCols = conn.GetSchema("Columns", restrictions);

        // clear collection
        for (int i = 0; i < 3; i++)
            restrictions[i] = null;

        //Get columns named "EMPNO" from tables named "EMP",
        //owned by any owner/schema
        restrictions[1] = "EMP";
        restrictions[2] = "EMPNO";
        DataTable dtAllScottEmpCols = conn.GetSchema("Columns", restrictions);

        // clear collection
        for (int i = 0; i < 3; i++)
            restrictions[i] = null;

        //Get columns named "EMPNO" from all
        //tables, owned by any owner/schema
        restrictions[2] = "EMPNO";
        DataTable dtAllEmpNoCols = conn.GetSchema("Columns", restrictions);
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.Message);
        Console.WriteLine(ex.Source);
    }
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**GetSessionInfo**

`GetSessionInfo` returns or refreshes an `OracleGlobalization` object that represents the globalization settings of the session.

**Overload List:**

- [GetSessionInfo\(\)](#)  
This method returns a new instance of the `OracleGlobalization` object that represents the globalization settings of the session.
- [GetSessionInfo\(OracleGlobalization\)](#)  
This method refreshes the provided `OracleGlobalization` object with the globalization settings of the session.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

**GetSessionInfo()**

This method returns a new instance of the `OracleGlobalization` object that represents the globalization settings of the session.

**Declaration**

```
// C#
public OracleGlobalization GetSessionInfo();
```

**Return Value**

The newly created `OracleGlobalization` object.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetSessionInfoSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get session info from connection object
        OracleGlobalization info = con.GetSessionInfo();
    }
}
```

```
// Update session info
info.DateFormat = "YYYY-MM-DD";
con.SetSessionInfo(info);

// Execute SQL SELECT
OracleCommand cmd = con.CreateCommand();
cmd.CommandText = "select TO_CHAR(hiredate) from emp";
Console.WriteLine("Hire Date ({0}): {1}",
    info.DateFormat, cmd.ExecuteScalar());

// Clean up
cmd.Dispose();
con.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## GetSessionInfo(OracleGlobalization)

This method refreshes the provided `OracleGlobalization` object with the globalization settings of the session.

**Declaration**

```
// C#
public void GetSessionInfo(OracleGlobalization oraGlob);
```

**Parameters**

- *oraGlob*

The `OracleGlobalization` object to be updated.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## Open

This method opens a connection to an Oracle database.

**Declaration**

```
// ADO.NET 2.0: C#
public override void Open();
```

**Implements**

`IDbConnection`

**Exceptions**

`ObjectDisposedException` - The object is already disposed.



`InvalidOperationException` - The connection is already opened or the connection string is null or empty.

### Remarks

The connection is obtained from the pool if connection pooling is enabled. Otherwise, a new connection is established.

It is possible that the pool does not contain any unused connections when the `Open()` method is invoked. In this case, a new connection is established.

If no connections are available within the specified connection timeout value, when the `Max Pool Size` is reached, an `OracleException` is thrown.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## OpenWithNewPassword

This method opens a new connection with the new password.

### Declaration

```
// C#  
public void OpenWithNewPassword(string newPassword);
```

### Parameters

- *newPassword*  
A string that contains the new password.

### Remarks

This method uses the `ConnectionString` property settings to establish a new connection. The old password must be provided in the connection string as the `Password` attribute value.

This method can only be called on an `OracleConnection` in the *closed* state.

### Remarks (.NET Stored Procedure)

This method is not supported in a .NET stored procedure for context connection.

---

---

**Note:** If connection pooling is enabled, then invoking the `OpenWithNewPassword` method also clears the connection pool. This closes all idle connections created with the old password.

---

---

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Password Expiration"](#) on page 3-12

## PurgeStatementCache

This method flushes the statement cache by closing all open cursors on the database, when statement caching is enabled.

### Declaration

```
// C#  
public void PurgeStatementCache();
```

### Remarks

Flushing the statement cache repetitively results in decreased performance and may negate the performance benefit gained by enabling the statement cache.

Statement caching remains enabled after the call to `PurgeStatementCache`.

Invocation of this method purges the cached cursors that are associated with the `OracleConnection`. It does not purge all the cached cursors in the database.

### Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class PurgeStatementCacheSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle;" +  
            "Statement Cache Size=20";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand("select * from emp", con);  
        cmd.CommandType = CommandType.Text;  
        OracleDataReader reader = cmd.ExecuteReader();  
  
        // Purge Statement Cache  
        con.PurgeStatementCache();  
  
        // Close and Dispose OracleConnection object  
        Console.WriteLine("Statement Cache Flushed");  
        con.Close();  
        con.Dispose();  
    }  
}
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Statement Caching" on page 3-42](#)
- [ConnectionString on page 5-78](#)

## SetSessionInfo

This method alters the session's globalization settings with all the property values specified in the provided `OracleGlobalization` object.

### Declaration

```
// C#
public void SetSessionInfo(OracleGlobalization oraGlob);
```

### Parameters

- *oraGlob*

An `OracleGlobalization` object.

### Remarks

Calling this method is equivalent to calling an `ALTER SESSION SQL` on the session.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class SetSessionInfoSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get session info from connection object
        OracleGlobalization info = con.GetSessionInfo();

        // Execute SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select TO_CHAR(hiredate) from emp";
        Console.WriteLine("Hire Date ({0}): {1}",
            info.DateFormat, cmd.ExecuteScalar());

        // Update session info
        info.DateFormat = "MM-DD-RR";
        con.SetSessionInfo(info);

        // Execute SQL SELECT again
        Console.WriteLine("Hire Date ({0}): {1}",
            info.DateFormat, cmd.ExecuteScalar());

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

## OracleConnection Events

OracleConnection events are listed in [Table 5–28](#).

**Table 5–28 OracleConnection Events**

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>
<a href="#">Failover</a>	An event that is triggered when an Oracle failover occurs <i>Not supported in a .NET stored procedure</i>
<a href="#">HAEvent</a>	An event that is triggered when an HA event occurs.
<a href="#">InfoMessage</a>	An event that is triggered for any message or warning sent by the database
<a href="#">StateChange</a>	An event that is triggered when the connection state changes

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)

### Failover

This event is triggered when an Oracle failover occurs.

**Declaration**

```
// C#
public event OracleFailoverEventHandler Failover;
```

**Event Data**

The event handler receives an `OracleFailoverEventArgs` object which exposes the following properties containing information about the event.

- `FailoverType`  
Indicates the type of the failover.
- `FailoverEvent`  
Indicates the state of the failover.

**Remarks**

The `Failover` event is raised when a connection to an Oracle instance is unexpectedly severed. The client should create an `OracleFailoverEventHandler` delegate to listen to this event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleFailoverEventArgs Properties"](#) on page 11-7
- ["OracleFailoverEventHandler Delegate"](#) on page 11-9

**HAEvent**

This event is triggered when an HA event occurs.

**Declaration**

```
// C#  
public static event OracleHAEventHandler HAEvent;
```

**Event Data**

The event handler receives an `OracleHAEventArgs` object which exposes the following properties containing information about the event.

- `Source`  
Indicates the source of the event.
- `Status`  
Indicates the status of the event.
- `DatabaseName`  
Indicates the database name affected by this event.
- `DatabaseDomainName`  
Indicates the database domain name affected by this event.
- `HostName`  
Indicates the host name affected by this event.
- `InstanceName`  
Indicates the instance name affected by this event.
- `ServiceName`  
Indicates the service name affected by this event.
- `Time`  
Indicates the time of the event.

**Remarks**

The `HAEvent` is static, which means that any HA Events that happen within the application domain can trigger this event. Note that in order to receive HA event notifications, `OracleConnection` objects that establish connections within the application domain must have `"ha_events=true"` in the application. Otherwise, the application never receives any HA Events.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleHAEventArgs Properties"](#) on page 8-4
- ["OracleHAEventHandler Delegate"](#) on page 8-8

## InfoMessage

This event is triggered for any message or warning sent by the database.

**Declaration**

```
// C#  
public event OracleInfoMessageEventHandler InfoMessage;
```

**Event Data**

The event handler receives an `OracleInfoMessageEventArgs` object which exposes the following properties containing information about the event.

- `Errors`  
The collection of errors generated by the data source.
- `Message`  
The error text generated by the data source.
- `Source`  
The name of the object that generated the error.

**Remarks**

In order to respond to warnings and messages from the database, the client should create an `OracleInfoMessageEventHandler` delegate to listen to this event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleInfoMessageEventArgs Properties"](#) on page 5-243
- ["OracleInfoMessageEventHandler Delegate"](#) on page 5-246

## StateChange

This event is triggered when the connection state changes.

**Declaration**

```
// ADO.NET 2.0: C#  
public override event StateChangeEventHandler StateChange;
```

**Event Data**

The event handler receives a `StateChangeEventArgs` object which exposes the following properties containing information about the event.

- `CurrentState`  
The new state of the connection.
- `OriginalState`  
The original state of the connection.

**Remarks**

The `StateChange` event is raised after a connection changes state, whenever an explicit call is made to `Open`, `Close` or `Dispose`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- Microsoft ADO.NET documentation for a description of `StateChangeEventHandler`



---

## OracleDataAdapter Class

An OracleDataAdapter object represents a data provider object that populates the DataSet and updates changes in the DataSet to the Oracle database.

### Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.ComponentModel.Component
            System.Data.Common.DataAdapter
                System.Data.Common.DbDataAdapter (ADO.NET 2.0 only)
                    Oracle.DataAccess.Client.OracleDataAdapter
```

### Declaration

```
// C#
public sealed class OracleDataAdapter : DbDataAdapter, IDbDataAdapter
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

The following example uses the OracleDataAdapter and the dataset to update the EMP table:

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleDataAdapterSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT empno, sal from emp";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
        // the Command when needed
        OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];
    }
}
```

```
// Indicate DataColumn EMPNO is unique
// This is required by the OracleCommandBuilder to update the EMP table
table.Columns["EMPNO"].Unique = true;

// Get the first row from the EMP table
DataRow row = table.Rows[0];

// Update the salary
double sal = double.Parse(row["SAL"].ToString());
row["SAL"] = sal + .01;

// Now update the EMP using the adapter
// The OracleCommandBuilder will create the UpdateCommand for the
// adapter to update the EMP table
adapter.Update(dataset, "EMP");

Console.WriteLine("Row updated successfully");
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Members](#)
- [OracleDataAdapter Constructors](#)
- [OracleDataAdapter Static Methods](#)
- [OracleDataAdapter Properties](#)
- [OracleDataAdapter Public Methods](#)
- [OracleDataAdapter Events](#)

## OracleDataAdapter Members

OracleDataAdapter members are listed in the following tables.

### OracleDataAdapter Constructors

OracleDataAdapter constructors are listed in [Table 5–29](#).

**Table 5–29 OracleDataAdapter Constructors**

Constructor	Description
<a href="#">OracleDataAdapter Constructors</a>	Instantiates a new instance of OracleDataAdapter class (Overloaded)

### OracleDataAdapter Static Methods

The OracleDataAdapter static method is listed in [Table 5–30](#).

**Table 5–30 OracleDataAdapter Static Method**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleDataAdapter Properties

OracleDataAdapter properties are listed in [Table 5–31](#).

**Table 5–31 OracleDataAdapter Properties**

Property	Description
AcceptChangesDuringFill	Inherited from System.Data.Common.DataAdapter
Container	Inherited from System.ComponentModel.Component
ContinueUpdateOnError	Inherited from System.Data.Common.DataAdapter
<a href="#">DeleteCommand</a>	A SQL statement or stored procedure to delete rows from an Oracle database
<a href="#">InsertCommand</a>	A SQL statement or stored procedure to insert new rows into an Oracle database
MissingMappingAction	Inherited from System.Data.Common.DataAdapter
MissingSchemaAction	Inherited from System.Data.Common.DataAdapter
<a href="#">Requery</a>	Determines whether or not the SelectCommand is reexecuted on the next call to Fill
<a href="#">ReturnProviderSpecificTypes</a>	Determines if the Fill method returns ODP.NET-specific values or .NET common language specification values
<a href="#">SafeMapping</a>	Creates a mapping between column names in the result set to .NET types, to preserve the data
<a href="#">SelectCommand</a>	A SQL statement or stored procedure that returns a single or multiple result set

**Table 5–31 (Cont.) OracleDataAdapter Properties**

Property	Description
Site	Inherited from <code>System.ComponentModel.Component</code>
TableMappings	Inherited from <code>System.Data.Common.DataAdapter</code>
<a href="#">UpdateBatchSize</a>	Specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">UpdateCommand</a>	A SQL statement or stored procedure to update rows from the <code>DataSet</code> to an Oracle database

### OracleDataAdapter Public Methods

OracleDataAdapter public methods are listed in [Table 5–32](#).

**Table 5–32 OracleDataAdapter Public Methods**

Public Method	Description
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Inherited from <code>System.ComponentModel.Component</code>
Equals	Inherited from <code>System.Object (Overloaded)</code>
<a href="#">Fill</a>	Adds or refreshes rows in the <code>DataSet</code> to match the data in the Oracle database (Overloaded)
FillSchema	Inherited from <code>System.Data.Common.DbDataAdapter</code>
GetFillParameters	Inherited from <code>System.Data.Common.DbDataAdapter</code>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
ToString	Inherited from <code>System.Object</code>
Update	Inherited from <code>System.Data.Common.DbDataAdapter</code>

### OracleDataAdapter Events

OracleDataAdapter events are listed in [Table 5–33](#).

**Table 5–33 OracleDataAdapter Events**

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>
FillError	Inherited from <code>System.Data.Common.DbDataAdapter</code>
<a href="#">RowUpdated</a>	This event is raised when row(s) have been updated by the <code>Update()</code> method

**Table 5–33 (Cont.) OracleDataAdapter Events**

Event Name	Description
<a href="#">RowUpdating</a>	This event is raised when row data are about to be updated to the database

## OracleDataAdapter Constructors

OracleDataAdapter constructors create new instances of an OracleDataAdapter class.

### Overload List:

- [OracleDataAdapter\(\)](#)  
This constructor creates an instance of an OracleDataAdapter class.
- [OracleDataAdapter\(OracleCommand\)](#)  
This constructor creates an instance of an OracleDataAdapter class with the provided OracleCommand as the SelectCommand.
- [OracleDataAdapter\(string, OracleConnection\)](#)  
This constructor creates an instance of an OracleDataAdapter class with the provided OracleConnection object and the command text for the SelectCommand.
- [OracleDataAdapter\(string, string\)](#)  
This constructor creates an instance of an OracleDataAdapter class with the provided connection string and the command text for the SelectCommand.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

### OracleDataAdapter()

This constructor creates an instance of an OracleDataAdapter class with no arguments.

### Declaration

```
// C#  
public OracleDataAdapter();
```

### Remarks

Initial values are set for the following OracleDataAdapter properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

### OracleDataAdapter(OracleCommand)

This constructor creates an instance of an OracleDataAdapter class with the provided OracleCommand as the SelectCommand.

**Declaration**

```
// C#
public OracleDataAdapter(OracleCommand selectCommand);
```

**Parameters**

- *selectCommand*

The `OracleCommand` that is to be set as the `SelectCommand` property.

**Remarks**

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

**OracleDataAdapter(string, OracleConnection)**

This constructor creates an instance of an `OracleDataAdapter` class with the provided `OracleConnection` object and the command text for the `SelectCommand`.

**Declaration**

```
// C#
public OracleDataAdapter(string selectCommandText, OracleConnection
    selectConnection);
```

**Parameters**

- *selectCommandText*

The string that is set as the `CommandText` of the `SelectCommand` property of the `OracleDataAdapter`.

- *selectConnection*

The `OracleConnection` to connect to the Oracle database.

**Remarks**

The `OracleDataAdapter` opens and closes the connection, if it is not already open. If the connection is open, it must be explicitly closed.

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## OracleDataAdapter(string, string)

This constructor creates an instance of an `OracleDataAdapter` class with the provided connection string and the command text for the `SelectCommand`.

### Declaration

```
// C#  
public OracleDataAdapter(string selectCommandText, string  
    selectConnectionString);
```

### Parameters

- *selectCommandText*  
The string that is set as the `CommandText` of the `SelectCommand` property of the `OracleDataAdapter`.
- *selectConnectionString*  
The connection string.

### Remarks

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction` = `MissingMappingAction.Passthrough`
- `MissingSchemaAction` = `MissingSchemaAction.Add`

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)



## OracleDataAdapter Static Methods

The `OracleDataAdapter` static method is listed in [Table 5-34](#).

**Table 5-34** *OracleDataAdapter Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## OracleDataAdapter Properties

OracleDataAdapter properties are listed in [Table 5–35](#).

**Table 5–35 OracleDataAdapter Properties**

Property	Description
AcceptChangesDuringFill	Inherited from <code>System.Data.Common.DataAdapter</code>
Container	Inherited from <code>System.ComponentModel.Component</code>
ContinueUpdateOnError	Inherited from <code>System.Data.Common.DataAdapter</code>
DeleteCommand	A SQL statement or stored procedure to delete rows from an Oracle database
InsertCommand	A SQL statement or stored procedure to insert new rows into an Oracle database
MissingMappingAction	Inherited from <code>System.Data.Common.DataAdapter</code>
MissingSchemaAction	Inherited from <code>System.Data.Common.DataAdapter</code>
Requery	Determines whether or not the <code>SelectCommand</code> is reexecuted on the next call to <code>Fill</code>
ReturnProviderSpecificTypes	Determines if the <code>Fill</code> method returns ODP.NET-specific values or .NET common language specification values
SafeMapping	Creates a mapping between column names in the result set to .NET types, to preserve the data
SelectCommand	A SQL statement or stored procedure that returns a single or multiple result set
Site	Inherited from <code>System.ComponentModel.Component</code>
TableMappings	Inherited from <code>System.Data.Common.DataAdapter</code>
UpdateBatchSize	Specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
UpdateCommand	A SQL statement or stored procedure to update rows from the <code>DataSet</code> to an Oracle database

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## DeleteCommand

This property is a SQL statement or stored procedure to delete rows from an Oracle database.

### Declaration

```
// C#  
public OracleCommand DeleteCommand {get; set;}
```

### Property Value

An `OracleCommand` used during the `Update` call to delete rows from tables in the Oracle database, corresponding to the deleted rows in the `DataSet`.

### Remarks

Default = null

If there is primary key information in the `DataSet`, the `DeleteCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## InsertCommand

This property is a SQL statement or stored procedure to insert new rows into an Oracle database.

### Declaration

```
// C#  
public OracleCommand InsertCommand {get; set;}
```

### Property Value

An `OracleCommand` used during the `Update` call to insert rows into a table, corresponding to the inserted rows in the `DataSet`.

### Remarks

Default = null

If there is primary key information in the `DataSet`, the `InsertCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this property.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## Requery

This property determines whether or not the `SelectCommand` is reexecuted on the next call to `Fill`.

### Declaration

```
// C#  
public Boolean Requery {get; set;}
```

### Property Value

Returns `true` if the `SelectCommand` is reexecuted on the next call to `Fill`; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-108

## ReturnProviderSpecificTypes

This property determines if the `Fill` method returns ODP.NET-specific values or .NET common language specification compliant values.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

### Declaration

```
// C#  
public Boolean ReturnProviderSpecificTypes {get; set;}
```

### Property Value

A value that indicates whether or not the `Fill` method returns ODP.NET-specific values.

A value of `false` indicates that the `Fill` method returns .NET common language specification compliant values.

The default is `false`.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## SafeMapping

This property creates a mapping between column names in the result set to .NET types that represent column values in the `DataSet`, to preserve the data.

### Declaration

```
// C#  
public Hashtable SafeMapping {get; set;}
```

**Property Value**

A hash table.

**Remarks**

Default = null

The `SafeMapping` property is used, when necessary, to preserve data in the following types:

- DATE
- TimeStamp (refers to all TimeStamp objects)
- INTERVAL DAY TO SECOND
- NUMBER

**Example**

See the example in ["OracleDataAdapter Safe Type Mapping"](#) on page 3-104.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Safe Type Mapping"](#) on page 3-104

**SelectCommand**

This property is a SQL statement or stored procedure that returns single or multiple result sets.

**Declaration**

```
// C#
public OracleCommand SelectCommand {get; set;}
```

**Property Value**

An `OracleCommand` used during the `Fill` call to populate the selected rows to the `DataSet`.

**Remarks**

Default = null

If the `SelectCommand` does not return any rows, no tables are added to the dataset and no exception is raised.

If the `SELECT` statement selects from a `VIEW`, no key information is retrieved when a `FillSchema()` or a `Fill()` with `MissingSchemaAction.AddWithKey` is invoked.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-108

## UpdateBatchSize

This property specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

### Declaration

```
// C#  
public virtual int UpdateBatchSize {get; set;}
```

### Property Value

An integer that returns the batch size.

### Exceptions

*ArgumentOutOfRangeException* - The value is set to a number < 0.

### Remarks

Update batches executed with large amounts of data may encounter an "PLS-00123: Program too large" error. To avoid this error, reduce the size of `UpdateBatchSize` to a smaller value.

For each row in the `DataSet` that has been modified, added, or deleted, one SQL statement will be executed on the database.

Values are as follows:

- Value = 0  
The data adapter executes all the SQL statements in a single database round-trip
- Value = 1 - Default value  
This value disables batch updating and SQL statements are executed one at a time.
- Value =  $n$  where  $n > 1$   
The data adapter updates  $n$  rows of data per database round-trip.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["Batch Processing Support"](#) on page 3-27

## UpdateCommand

This property is a SQL statement or stored procedure to update rows from the `DataSet` to an Oracle database.

### Declaration

```
// C#  
public OracleCommand UpdateCommand {get; set;}
```

**Property Value**

An `OracleCommand` used during the `Update` call to update rows in the Oracle database, corresponding to the updated rows in the `DataSet`.

**Remarks**

Default = `null`

If there is primary key information in the `DataSet`, the `UpdateCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this property.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-108

## OracleDataAdapter Public Methods

OracleDataAdapter public methods are listed in [Table 5–36](#).

**Table 5–36 OracleDataAdapter Public Methods**

Public Method	Description
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Inherited from <code>System.ComponentModel.Component</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">Fill</a>	Adds or refreshes rows in the <code>DataSet</code> to match the data in the Oracle database (Overloaded)
FillSchema	Inherited from <code>System.Data.Common.DbDataAdapter</code>
GetFillParameters	Inherited from <code>System.Data.Common.DbDataAdapter</code>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
ToString	Inherited from <code>System.Object</code>
Update	Inherited from <code>System.Data.Common.DbDataAdapter</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

### Fill

Fill populates or refreshes the specified `DataTable` or `DataSet`.

**Overload List:**

- [Fill\(DataTable, OracleRefCursor\)](#)  
This method adds or refreshes rows in the specified `DataTable` to match those in the provided `OracleRefCursor` object.
- [Fill\(DataSet, OracleRefCursor\)](#)  
This method adds or refreshes rows in the `DataSet` to match those in the provided `OracleRefCursor` object.
- [Fill\(DataSet, string, OracleRefCursor\)](#)  
This method adds or refreshes rows in the specified source table of the `DataSet` to match those in the provided `OracleRefCursor` object.
- [Fill\(DataSet, int, int, string, OracleRefCursor\)](#)



This method adds or refreshes rows in a specified range in the `DataSet` to match rows in the provided `OracleRefCursor` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

**Fill(DataTable, OracleRefCursor)**

This method adds or refreshes rows in the specified `DataTable` to match those in the provided `OracleRefCursor` object.

**Declaration**

```
// C#  
public int Fill(DataTable dataTable, OracleRefCursor refCursor);
```

**Parameters**

- *dataTable*  
The `DataTable` object being populated.
- *refCursor*  
The `OracleRefCursor` that rows are being retrieved from.

**Return Value**

The number of rows added to or refreshed in the `DataTable`.

**Exceptions**

`ArgumentNullException` - The *dataTable* or *refCursor* parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data.

`NotSupportedException` - The `SafeMapping` type is not supported.

**Remarks**

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-108

**Fill(DataSet, OracleRefCursor)**

This method adds or refreshes rows in the `DataSet` to match those in the provided `OracleRefCursor` object.

**Declaration**

```
// C#
```

```
public int Fill(DataSet dataSet, OracleRefCursor refCursor);
```

**Parameters**

- *dataSet*  
The DataSet object being populated.
- *refCursor*  
The OracleRefCursor that rows are being retrieved from.

**Return Value**

Returns the number of rows added or refreshed in the DataSet.

**Exceptions**

ArgumentNullException - The *dataSet* or *refCursor* parameter is null.

InvalidOperationException - The OracleRefCursor is already being used to fetch data.

InvalidOperationException - The OracleRefCursor is ready to fetch data.

NotSupportedException - The SafeMapping type is not supported.

**Remarks**

If there is no DataTable to refresh, a new DataTable named Table is created and populated using the provided OracleRefCursor object.

No schema or key information is provided, even if the Fill method is called with MissingSchemaAction set to MissingSchemaAction.AddWithKey.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property" on page 3-108](#)

**Fill(DataSet, string, OracleRefCursor)**

This method adds or refreshes rows in the specified source table of the DataSet to match those in the provided OracleRefCursor object.

**Declaration**

```
// C#  
public int Fill(DataSet dataSet, string srcTable, OracleRefCursor  
    refCursor);
```

**Parameters**

- *dataSet*  
The DataSet object being populated.
- *srcTable*  
The name of the source table used in the table mapping.
- *refCursor*

The `OracleRefCursor` that rows are being retrieved from.

### Return Value

Returns the number of rows added or refreshed into the `DataSet`.

### Exceptions

`ArgumentNullException` - The `dataSet` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data or the source table name is invalid.

`NotSupportedException` - The `SafeMapping` type is not supported.

### Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-108

## Fill(DataSet, int, int, string, OracleRefCursor)

This method adds or refreshes rows in a specified range in the `DataSet` to match rows in the provided `OracleRefCursor` object.

### Declaration

```
// C#
public int Fill(DataSet dataSet, int startRecord, int maxRecords,
    string srcTable, OracleRefCursor refCursor);
```

### Parameters

- *dataSet*  
The `DataSet` object being populated.
- *startRecord*  
The record number to start with.
- *maxRecords*  
The maximum number of records to obtain.
- *srcTable*  
The name of the source table used in the table mapping.
- *refCursor*  
The `OracleRefCursor` that rows are being retrieved from.

### Return Value

This method returns the number of rows added or refreshed in the `DataSet`. This does not include rows affected by statements that do not return rows.

### Exceptions

`ArgumentNullException` - The `dataSet` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data or the source table name is invalid.

`NotSupportedException` - The `SafeMapping` type is not supported.

### Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-108

## OracleDataAdapter Events

OracleDataAdapter events are listed in [Table 5–37](#).

**Table 5–37 OracleDataAdapter Events**

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>
FillError	Inherited from <code>System.Data.Common.DbDataAdapter</code>
<a href="#">RowUpdated</a>	This event is raised when row(s) have been updated by the <code>Update()</code> method
<a href="#">RowUpdating</a>	This event is raised when row data are about to be updated to the database

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

## RowUpdated

This event is raised when row(s) have been updated by the `Update()` method.

### Declaration

```
// C#
public event OracleRowUpdatedEventHandler RowUpdated;
```

### Event Data

The event handler receives an `OracleRowUpdatedEventArgs` object which exposes the following properties containing information about the event.

- `Command`  
The `OracleCommand` executed during the `Update`.
- `Errors` (inherited from `RowUpdatedEventArgs`)  
The exception, if any, is generated during the `Update`.
- `RecordsAffected` (inherited from `RowUpdatedEventArgs`)  
The number of rows modified, inserted, or deleted by the execution of the `Command`.
- `Row` (inherited from `RowUpdatedEventArgs`)  
The `DataRow` sent for `Update`.
- `StatementType` (inherited from `RowUpdatedEventArgs`)  
The type of SQL statement executed.
- `Status` (inherited from `RowUpdatedEventArgs`)  
The `UpdateStatus` of the `Command`.
- `TableMapping` (inherited from `RowUpdatedEventArgs`)  
The `DataTableMapping` used during the `Update`.

**Example**

The following example shows how to use the `RowUpdating` and `RowUpdated` events.

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class RowUpdatedSample
{
    // Event handler for RowUpdating event
    protected static void OnRowUpdating(object sender,
                                       OracleRowUpdatingEventArgs e)
    {
        Console.WriteLine("Row updating....");
        Console.WriteLine("Event arguments:");
        Console.WriteLine("Command Text: " + e.Command.CommandText);
        Console.WriteLine("Command Type: " + e.StatementType);
        Console.WriteLine("Status: " + e.Status);
    }

    // Event handler for RowUpdated event
    protected static void OnRowUpdated(object sender,
                                       OracleRowUpdatedEventArgs e)
    {
        Console.WriteLine("Row updated....");
        Console.WriteLine("Event arguments:");
        Console.WriteLine("Command Text: " + e.Command.CommandText);
        Console.WriteLine("Command Type: " + e.StatementType);
        Console.WriteLine("Status: " + e.Status);
    }

    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT EMPNO, ENAME, SAL FROM EMP";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
        // the Command when needed
        OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];

        // Indicate DataColumn EMPNO is unique
        // This is required by the OracleCommandBuilder to update the EMP table
        table.Columns["EMPNO"].Unique = true;

        // Get the first row from the EMP table
        DataRow row = table.Rows[0];
    }
}
```

```

// Update the salary
double sal = double.Parse(row["SAL"].ToString());
row["SAL"] = sal + .01;

// Set the event handlers for the RowUpdated and the RowUpdating event
// the OnRowUpdating() method will be triggered before the update, and
// the OnRowUpdated() method will be triggered after the update
adapter.RowUpdating += new OracleRowUpdatingEventHandler(OnRowUpdating);
adapter.RowUpdated += new OracleRowUpdatedEventHandler(OnRowUpdated);

// Now update the EMP using the adapter
// The OracleCommandBuilder will create the UpdateCommand for the
// adapter to update the EMP table
// The OnRowUpdating() and the OnRowUpdated() methods will be triggered
adapter.Update(dataset, "EMP");
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleRowUpdatedEventHandler Delegate"](#) on page 5-331

**RowUpdating**

This event is raised when row data are about to be updated to the database.

**Declaration**

```

// C#
public event OracleRowUpdatingEventHandler RowUpdating;

```

**Event Data**

The event handler receives an `OracleRowUpdatingEventArgs` object which exposes the following properties containing information about the event.

- **Command**  
The `OracleCommand` executed during the Update.
- **Errors** (inherited from `RowUpdatingEventArgs`)  
The exception, if any, is generated during the Update.
- **Row** (inherited from `RowUpdatingEventArgs`)  
The `DataRow` sent for Update.
- **StatementType** (inherited from `RowUpdatingEventArgs`)  
The type of SQL statement executed.
- **Status** (inherited from `RowUpdatingEventArgs`)  
The `UpdateStatus` of the Command.
- **TableMapping** (inherited from `RowUpdatingEventArgs`)  
The `DataTableMapping` used during the Update.

### **Example**

The example for the `RowUpdated` event also shows how to use the `RowUpdating` event. See `RowUpdated` event "[Example](#)" on page 5-136.

#### **See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleRowUpdatingEventHandler Delegate"](#) on page 5-339



---

## OracleDatabase Class

An OracleDatabase object represents an Oracle Database instance.

### Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleDatabase

### Declaration

```
// C#  
public sealed class OracleDatabase : IDisposable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
namespace Startup  
{  
    class Test  
    {  
        static void Main()  
        {  
            OracleConnection con = null;  
            OracleDatabase db = null;  
            string constring = "dba privilege=sysdba;user id=scott;password=tiger;data  
source=oracle";  
  
            try  
            {  
                // Open a connection to see if the DB is up  
                con = new OracleConnection(constring);  
                con.Open();  
  
                Console.WriteLine("The Oracle database is already up.");  
            }  
            catch (OracleException ex)  
            {  
                // If the database is down, start up the DB  
                if (ex.Number == 1034)  
                {  
                    Console.WriteLine("The Oracle database is down.");  
  
                    // Create an instance of an OracleDatabase object  
                    db = new OracleDatabase(constring);  
  
                    // Start up the database  
                    db.Startup();  
  
                    Console.WriteLine("The Oracle database is now up.");  
                }  
            }  
        }  
    }  
}
```

```
        // Executing Startup() is the same as the following:
        // db.Startup(OracleDBStartupMode.NoRestriction, null, true);
        // which is also the same as:
        // db.Startup(OracleDBStartupMode.NoRestriction, null, false);
        // db.ExecuteNonQuery("ALTER DATABASE MOUNT");
        // db.ExecuteNonQuery("ALTER DATABASE OPEN");

        // Dispose the OracleDatabase object
        db.Dispose();
    }
    else
    {
        Console.WriteLine("Error: " + ex.Message);
    }
}
finally
{
    // Dispose the OracleConnetion object
    con.Dispose();
}
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDatabase Members](#)
- [OracleDatabase Constructor](#)
- [OracleDatabase Properties](#)
- [OracleDatabase Public Methods](#)

## OracleDatabase Members

OracleDatabase members are listed in the following tables.

### OracleDatabase Constructors

The OracleDatabase constructor is listed in [Table 5–38](#).

**Table 5–38 OracleDatabase Constructors**

Constructor	Description
<a href="#">OracleDatabase Constructor</a>	Instantiates a new instance of OracleDatabase class using the supplied connection string

### OracleDatabase Properties

The OracleDatabase properties are listed in [Table 5–39](#).

**Table 5–39 OracleDatabase Properties**

Property	Description
<a href="#">ServerVersion</a>	Specifies the database version number of the Oracle Database instance to which the connection is made

### OracleDatabase Public Methods

The OracleDatabase public methods are listed in [Table 5–40](#).

**Table 5–40 OracleDatabase Public Methods**

Public Method	Description
<a href="#">ExecuteNonQuery</a>	Executes the supplied non-SELECT statement against the database
<a href="#">Shutdown</a>	Shuts down the database (Overloaded)
<a href="#">Startup</a>	Starts up the database (Overloaded)

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)

## OracleDatabase Constructor

The `OracleDatabase` constructor instantiates a new instance of the `OracleDatabase` class using the supplied connection string.

### Declaration

```
// C#  
public OracleDatabase(String connectionString);
```

### Parameters

- *connectionString*

The connection information used to connect to the Oracle Database instance.

### Remarks

The *connectionString* follows the same format used by the `OracleConnection` object. However, the `OracleDatabase` constructor accepts only the `user id`, `password`, `data source`, and `dba privilege connection string` attributes. All other attribute values are ignored. The supplied *connectionString* must contain the `dba privilege connection string` attribute that is set to either `SYSDBA` or `SYSOPER`.

The `OracleDatabase` object creates a connection upon construction and remains connected throughout its lifetime. The connection is destroyed when the `OracleDatabase` object is disposed. This connection is not pooled to be used by another `OracleDatabase` object.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

## OracleDatabase Properties

The OracleDatabase properties are listed in [Table 5–41](#).

**Table 5–41 OracleDatabase Properties**

Property	Description
<a href="#">ServerVersion</a>	Specifies the database version number of the Oracle Database instance to which the connection is made

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

### ServerVersion

This property returns the database version number of the Oracle Database instance to which the connection is made.

**Declaration**

```
Public string ServerVersion {get;}
```

**Property value**

Returns the database version of the Oracle Database instance.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

## OracleDatabase Public Methods

The OracleDatabase public methods are listed in [Table 5–42](#).

**Table 5–42 OracleDatabase Public Methods**

Public Method	Description
<a href="#">ExecuteNonQuery</a>	Executes the supplied non-SELECT statement against the database
<a href="#">Shutdown</a>	Shuts down the database (Overloaded)
<a href="#">Startup</a>	Starts up the database (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

### ExecuteNonQuery

This method executes the supplied non-SELECT statement against the database.

**Declaration**

```
// C#
public void ExecuteNonQuery(string sql);
```

**Exceptions**

OracleException - The command execution has failed.

**Remarks**

This method is meant for execution of DDL statements such as ALTER DATABASE statements to OPEN and MOUNT the database, for example. This method should not be used to execute SQL SELECT statements. This method does not support any parameter binding.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

### Shutdown

Shutdown methods shut down a database instance.

**Overload List**

- [Shutdown\(\)](#)  
This method shuts down the database.
- [Shutdown\(OracleDBShutdownMode, bool\)](#)  
This method shuts down the database using the specified mode.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#) on page 5-356

**Shutdown()**

This method shuts down the database.

**Declaration**

```
// C#
public void Shutdown();
```

**Exceptions**

`OracleException` - The database shutdown request has failed.

**Remarks**

This method shuts down a database instance in the `OracleDBShutdownMode.Default` mode. New connections are refused, and the method waits for the existing connections to end.

---



---

**Note:** As the shutdown is effected using the `OracleDBShutdownMode.Default` mode, the shutdown request may remain pending if there are open connections other than the connection created by the `OracleDatabase` object.

---



---

After the connections have closed, the method closes the database, dismounts the database, and shuts down the instance using the `OracleDBShutdownMode.Final` mode.

This method does not throw exceptions for cases where the database has been already closed, dismounted, or shutdown appropriately. If other errors are encountered, then an exception is thrown.

Invoking this method against an Oracle Real Application Clusters (RAC) database shuts down only that database instance to which the `OracleDatabase` object is connected.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#) on page 5-356

**Shutdown(OracleDBShutdownMode, bool)**

This method shuts down the database instance using the specified mode.

**Declaration**

```
//C#
```

```
public void Shutdown(OracleDBShutdownMode shutdownMode, bool
bCloseDismountAndFinalize);
```

**Parameters**

- *shutdownMode*  
A `OracleDBShutdownMode` enumeration value.
- *bCloseDismountAndFinalize*  
A boolean signifying whether the database is to be closed, dismounted, and finalized.

**Exceptions**

`OracleException` - The database shutdown request has failed.

**Remarks**

This method shuts down a database instance in the specified mode. If the *bCloseDismountAndFinalize* parameter is `true`, then the method also closes the database, dismounts the database, and shuts down the instance using the `OracleDBShutdownMode.Final` mode.

If the *bCloseDismountAndFinalize* parameter is `true`, then this method does not throw exceptions for cases where the database has been already closed, dismounted, or shutdown appropriately. If other errors are encountered, then an exception is thrown.

If the *bCloseDismountAndFinalize* parameter is `false`, then the application needs to explicitly close and dismount the database. The application can then reinvoke the method using the `OracleDBShutdownMode.Final` mode to properly shut down the database. For example, if `db` is an instance of the `OracleDatabase` class, then the application invokes the following:

1. `db.Shutdown(OracleDBShutdownMode.Default, false);`
2. `db.ExecuteNonQuery("ALTER DATABASE CLOSE NORMAL");`
3. `db.ExecuteNonQuery("ALTER DATABASE DISMOUNT");`
4. `db.Shutdown(OracleDBShutdownMode.Final);`

---

---

**Note:**

- The `OracleDBShutdownMode.Final` enumeration value should not be used as the *shutdownMode* for the initial method invocation. The `OracleDBShutdownMode.Final` mode should be used only if the database is already closed and dismounted. Otherwise, the method might wait indefinitely.
  - If the specified *shutdownMode* is `OracleDBShutdownMode.Final`, then the value of the *bCloseDismountAndFinalize* input parameter is ignored, as the database should have been closed and dismounted already.
- 
- 

If the specified *shutdownMode* is `OracleDBShutdownMode.Abort`, then the value of the *bCloseDismountAndFinalize* input parameter is ignored, as the `Abort` mode requires the database to be closed, dismounted, and finalized.



Invoking this method against an Oracle Real Application Clusters (RAC) database shuts down only that database instance to which the OracleDatabase object is connected.

### Example

```
using System;
using Oracle.DataAccess.Client;

namespace Shutdown
{
    class Test
    {
        static void Main()
        {
            OracleConnection con = null;
            OracleDatabase db = null;
            string constring = "user id=scott;password=tiger;data source=oracle;" +
                "pooling=false;dba_privilege=sysdba";

            try
            {
                // Open a connection to see if the DB is up;
                con = new OracleConnection(constring);
                con.Open();

                Console.WriteLine("The Oracle database is currently up.");

                // If open succeeds, we know that the database is up.
                // We have to dispose the connection so that we can
                // shutdown the database.
                con.Dispose();

                // Shutdown the database
                db = new OracleDatabase(constring);
                db.Shutdown();

                Console.WriteLine("The Oracle database is shut down.");

                // Executing Shutdown() above is the same as the following:
                // db.Shutdown(OracleDBShutdownMode.Default, false);
                // db.ExecuteNonQuery("ALTER DATABASE CLOSE NORMAL");
                // db.ExecuteNonQuery("ALTER DATABASE DISMOUNT");
                // db.Shutdown(OracleDBShutdownMode.Final);

                // Dispose the OracleDatabase object
                db.Dispose();
            }
            catch (OracleException ex)
            {
                Console.WriteLine("An error has occurred: {0}", ex.Message);
            }
        }
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#) on page 5-356

## Startup

Startup methods enable a user with database administrator privileges to start a database instance.

**Overload List**

- [Startup\(\)](#)  
This method starts a database instance using the server-side parameter file.
- [Startup\(OracleDBStartupMode, string, bool\)](#)  
This method starts a database instance using the client-side parameter file.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#) on page 5-357

## Startup()

This method starts up the database.

**Declaration**

```
// C#  
public void Startup();
```

**Exceptions**

`OracleException` - The database startup request has failed.

**Remarks**

This method starts a database instance in the `OracleDbStartupMode.Normal` mode using the server-side parameter file (`spfile`). After the database is successfully started, this method also executes the `ALTER DATABASE MOUNT` and `ALTER DATABASE OPEN` statements.

This method does not throw exceptions for cases where the database is already mounted, opened, or started appropriately. If other errors are encountered, then an exception is thrown.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#) on page 5-357

**Startup(OracleDBStartupMode, string, bool)**

This method starts up the database using the specified startup mode.

**Declaration**

```
// C#
public void Startup(OracleDbStartupMode startupMode, string pfile, bool
bMountAndOpen);
```

**Parameters**

- *startupMode*  
An OracleDBStartupMode enumeration value.
- *pfile*  
The location and name of the client-side parameter file. For example, "c:\admin\init.ora".  
  
The name of the parameter file varies depending on the operating system. For example, it can be in mixed case or lowercase, or it can have a logical name or a variation of the name `init.ora`. The default location is usually `ORACLE_HOME/dbs` or `ORACLE_HOME/database`.
- *bMountAndOpen*  
A true/false value signifying whether the database is to be mounted and opened.

**Exceptions**

OracleException - The database startup request has failed.

**Remarks**

This method starts a database instance in the specified mode using the specified client-side parameter file. After the database is successfully started, and if *bMountAndOpen* input parameter is true, this method also executes the ALTER DATABASE MOUNT and ALTER DATABASE OPEN statements.

If *bMountAndOpen* is true, then this method does not throw an exception for cases where the database is already mounted, opened, or started appropriately. If other errors are encountered, then an exception is thrown.

If *bMountAndOpen* is false, then the database must be mounted and opened explicitly by the application. For example, if `db` is an instance of the OracleDatabase class, then the application invokes the following:

1. `db.Startup(OracleDBStartupMode.NoRestriction, null, false);`
2. `db.ExecuteNonQuery("ALTER DATABASE MOUNT");`
3. `db.ExecuteNonQuery("ALTER DATABASE OPEN");`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#) on page 5-357

---

## OracleDataReader Class

An `OracleDataReader` object represents a forward-only, read-only, in-memory result set.

Unlike the `DataSet`, the `OracleDataReader` object stays connected and fetches one row at a time.

The following section contain related information:

- ["Obtaining LONG and LONG RAW Data"](#) on page 3-51.
- ["Obtaining Data from an OracleDataReader Object"](#) on page 3-47.

### Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.Data.Common.DataReader`

`System.Data.Common.DbDataReader (ADO.NET 2.0 only)`

`Oracle.DataAccess.Client.OracleDataReader`

### Declaration

```
// ADO.NET 2.0: C#
public sealed class OracleDataReader : DbDataReader, IEnumerable,
    IDataReader, IDisposable, IDataRecord
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

An `OracleDataReader` instance is constructed by a call to the `ExecuteReader` method of the `OracleCommand` object. The only properties that can be accessed after the `DataReader` is closed or has been disposed, are `IsClosed` and `RecordsAffected`.

To minimize the number of open database cursors, `OracleDataReader` objects should be explicitly disposed.

### Example

The following `OracleDataReader` example retrieves the data from the `EMP` table:

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);
```

```
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
```

```
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleDataReaderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdstr = "SELECT * FROM EMPINFO";
        OracleConnection connection = new OracleConnection(constr);
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        OracleDataReader reader = cmd.ExecuteReader();

        // Declare the variables to retrieve the data in EmpInfo
        short empNo;
        string empName;
        DateTime hireDate;
        double salary;
        string jobDesc;
        byte[] byteCodes = new byte[10];

        // Read the next row until end of row
        while (reader.Read())
        {
            empNo = reader.GetInt16(0);
            Console.WriteLine("Employee number: " + empNo);
            empName = reader.GetString(1);
            Console.WriteLine("Employee name: " + empName);

            // The following columns can have NULL value, so it
            // is important to call IsDBNull before getting the column data
            if (!reader.IsDBNull(2))
            {
                hireDate = reader.GetDateTime(2);
                Console.WriteLine("Hire date: " + hireDate);
            }

            if (!reader.IsDBNull(3))
            {
                salary = reader.GetDouble(3);
                Console.WriteLine("Salary: " + salary);
            }

            if (!reader.IsDBNull(4))
            {
                jobDesc = reader.GetString(4);
            }
        }
    }
}
```

```
        Console.WriteLine("Job Description: " + jobDesc);
    }

    if (!reader.IsDBNull(5))
    {
        long len = reader.GetBytes(5, 0, byteCodes, 0, 10);

        Console.Write("Byte codes: ");
        for (int i = 0; i < len; i++)
            Console.Write(byteCodes[i].ToString("x"));

        Console.WriteLine();
    }

    Console.WriteLine();
}

// Clean up
reader.Dispose();
con.Dispose();
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Members](#)
- [OracleDataReader Static Methods](#)
- [OracleDataReader Properties](#)
- [OracleDataReader Public Methods](#)
- [OracleDataReader SchemaTable](#)

## OracleDataReader Members

OracleDataReader members are listed in the following tables.

### OracleDataReader Static Methods

The OracleDataReader static method is listed in [Table 5-43](#).

**Table 5-43 OracleDataReader Static Method**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleDataReader Properties

OracleDataReader properties are listed in [Table 5-44](#).

**Table 5-44 OracleDataReader Properties**

Property	Description
Depth	Gets a value indicating the depth of nesting for the current row
FetchSize	Specifies the size of OracleDataReader's internal cache
FieldCount	Gets the number of columns in the result set
HasRows	Indicates whether the OracleDataReader has one or more rows
HiddenFieldCount	Gets the number of fields in the OracleDataReader that are hidden <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
IsClosed	Indicates whether or not the data reader is closed
Item	Gets the value of the column (Overloaded)
InitialLOBFetchSize	Specifies the amount that the OracleDataReader initially fetches for LOB columns
InitialLONGFetchSize	Specifies the amount that the OracleDataReader initially fetches for LONG and LONG RAW columns
RecordsAffected	Gets the number of rows changed, inserted, or deleted by execution of the SQL statement
RowSize	Gets the amount of memory the internal cache of the OracleDataReader needs to store one row of data.
VisibleFieldCount	Gets the number of fields in the OracleDataReader that are not hidden <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>

### OracleDataReader Public Methods

OracleDataReader public methods are listed in [Table 5-45](#).

**Table 5-45 OracleDataReader Public Methods**

Public Method	Description
Close	Closes the OracleDataReader
CreateObjRef	Inherited from System.MarshalByRefObject



**Table 5–45 (Cont.) OracleDataReader Public Methods**

<b>Public Method</b>	<b>Description</b>
<a href="#">Dispose</a>	Releases any resources or memory allocated by the object
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">GetBoolean</a>	<i>Not Supported</i>
<a href="#">GetByte</a>	Returns the byte value of the specified column
<a href="#">GetBytes</a>	Populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column
<a href="#">GetChar</a>	<i>Not Supported</i>
<a href="#">GetChars</a>	Populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column
<a href="#">GetData</a>	<i>Not Supported</i>
<a href="#">GetDataTypeName</a>	Returns the ODP.NET type name of the specified column
<a href="#">GetDateTime</a>	Returns the <code>DateTime</code> value of the specified column
<a href="#">GetDecimal</a>	Returns the decimal value of the specified NUMBER column
<a href="#">GetDouble</a>	Returns the double value of the specified NUMBER column or BINARY_DOUBLE column
<a href="#">GetEnumerator</a>	Returns an <code>IEnumerator</code> that can be used to iterate through the collection
<a href="#">GetFieldType</a>	Returns the <code>Type</code> of the specified column
<a href="#">GetFloat</a>	Returns the float value of the specified NUMBER column or BINARY_FLOAT column
<a href="#">GetGuid</a>	<i>Not Supported</i>
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetInt16</a>	Returns the <code>Int16</code> value of the specified NUMBER column
<a href="#">GetInt32</a>	Returns the <code>Int32</code> value of the specified NUMBER column
<a href="#">GetInt64</a>	Returns the <code>Int64</code> value of the specified NUMBER column
<a href="#">GetLifetimeService</a>	Inherited by <code>System.MarshalByRefObject</code>
<a href="#">GetName</a>	Returns the name of the specified column
<a href="#">GetOracleBFile</a>	Returns an <code>OracleBFile</code> object of the specified BFILE column
<a href="#">GetOracleBinary</a>	Returns an <code>OracleBinary</code> structure of the specified column
<a href="#">GetOracleBlob</a>	Returns an <code>OracleBlob</code> object of the specified BLOB column
<a href="#">GetOracleBlobForUpdate</a>	Returns an updatable <code>OracleBlob</code> object of the specified BLOB column
<a href="#">GetOracleClob</a>	Returns an <code>OracleClob</code> object of the specified CLOB column
<a href="#">GetOracleClobForUpdate</a>	Returns an updatable <code>OracleClob</code> object of the specified CLOB column

**Table 5–45 (Cont.) OracleDataReader Public Methods**

Public Method	Description
<a href="#">GetOracleDate</a>	Returns an <code>OracleDate</code> structure of the specified <code>DATE</code> column
<a href="#">GetOracleDecimal</a>	Returns an <code>OracleDecimal</code> structure of the specified <code>NUMBER</code> column
<a href="#">GetOracleIntervalDS</a>	Returns an <code>OracleIntervalDS</code> structure of the specified <code>INTERVAL DAY TO SECOND</code> column
<a href="#">GetOracleIntervalYM</a>	Returns an <code>OracleIntervalYM</code> structure of the specified <code>INTERVAL YEAR TO MONTH</code> column
<a href="#">GetOracleRef</a>	Returns an <code>OracleRef</code> object of the specified <code>REF</code> column
<a href="#">GetOracleString</a>	Returns an <code>OracleString</code> structure of the specified column
<a href="#">GetOracleTimeStamp</a>	Returns an <code>OracleTimeStamp</code> structure of the Oracle <code>TimeStamp</code> column
<a href="#">GetOracleTimeStampLTZ</a>	Returns an <code>OracleTimeStampLTZ</code> structure of the specified Oracle <code>TimeStamp WITH LOCAL TIME ZONE</code> column
<a href="#">GetOracleTimeStampTZ</a>	Returns an <code>OracleTimeStampTZ</code> structure of the specified Oracle <code>TimeStamp WITH TIME ZONE</code> column
<a href="#">GetOracleXmlType</a>	Returns an <code>OracleXmlType</code> object of the specified <code>XMLType</code> column
<a href="#">GetOracleValue</a>	Returns the specified column value as a <code>ODP.NET</code> type
<a href="#">GetOracleValues</a>	Gets all the column values as <code>ODP.NET</code> types
<a href="#">GetOrdinal</a>	Returns the 0-based ordinal (or index) of the specified column name
<a href="#">GetProviderSpecificFieldType</a>	Returns the provider-specific type of the specified column <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetProviderSpecificValue</a>	Returns an object that represents the underlying provider-specific value of the specified ordinal <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetProviderSpecificValues</a>	Returns an array of objects that represent the underlying provider-specific values <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetSchemaTable</a>	Returns a <code>DataTable</code> that describes the column metadata of the <code>OracleDataReader</code>
<a href="#">GetString</a>	Returns the string value of the specified column
<a href="#">GetTimeSpan</a>	Returns the <code>TimeSpan</code> value of the specified <code>INTERVAL DAY TO SECOND</code> column
<a href="#">GetType</a>	Inherited from <code>System.Object</code> class
<a href="#">GetValue</a>	Returns the column value as a <code>.NET</code> type
<a href="#">GetValues</a>	Gets all the column values as <code>.NET</code> types
<a href="#">GetXmlReader</a>	Returns the value of an <code>XMLType</code> column as an instance of an <code>.NET XmlTextReader</code>
<a href="#">IsDBNull</a>	Indicates whether or not the column value is null

**Table 5–45 (Cont.) OracleDataReader Public Methods**

Public Method	Description
<a href="#">NextResult</a>	Advances the data reader to the next result set when reading the results
<a href="#">Read</a>	Reads the next row in the result set
<a href="#">ToString</a>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)

## OracleDataReader Static Methods

The `OracleDataReader` static method is listed in [Table 5-46](#).

**Table 5-46** *OracleDataReader Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## OracleDataReader Properties

OracleDataReader properties are listed in [Table 5–47](#).

**Table 5–47 OracleDataReader Properties**

Property	Description
<a href="#">Depth</a>	Gets a value indicating the depth of nesting for the current row
<a href="#">FetchSize</a>	Specifies the size of OracleDataReader's internal cache
<a href="#">FieldCount</a>	Gets the number of columns in the result set
<a href="#">HasRows</a>	Indicates whether the OracleDataReader has one or more rows
<a href="#">HiddenFieldCount</a>	Gets the number of fields in the OracleDataReader that are hidden <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">IsClosed</a>	Indicates whether or not the data reader is closed
<a href="#">Item</a>	Gets the value of the column (Overloaded)
<a href="#">InitialLOBFetchSize</a>	Specifies the amount that the OracleDataReader initially fetches for LOB columns
<a href="#">InitialLONGFetchSize</a>	Specifies the amount that the OracleDataReader initially fetches for LONG and LONG RAW columns
<a href="#">RecordsAffected</a>	Gets the number of rows changed, inserted, or deleted by execution of the SQL statement
<a href="#">RowSize</a>	Gets the amount of memory the internal cache of the OracleDataReader needs to store one row of data
<a href="#">VisibleFieldCount</a>	Gets the number of fields in the OracleDataReader that are not hidden <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## Depth

This property gets a value indicating the depth of nesting for the current row.

### Declaration

```
// ADO.NET 2.0: C#
public override int Depth {get;}
```

### Property Value

The depth of nesting for the current row.

### Implements

IDataReader

**Exceptions**

`InvalidOperationException` - The reader is closed.

**Remarks**

Default = 0

This property always returns zero because Oracle does not support nesting.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**FetchSize**

This property specifies the size of `OracleDataReader`'s internal cache.

**Declaration**

```
// C#  
public long FetchSize {get; set;}
```

**Property Value**

A `long` that specifies the amount of memory (in bytes) that the `OracleDataReader` uses for its internal cache.

**Exceptions**

`ArgumentException` - The `FetchSize` value specified is invalid.

**Remarks**

Default = The `OracleCommand`'s `FetchSize` property value.

The `FetchSize` property is inherited by the `OracleDataReader` that is created by a command execution returning a result set. The `FetchSize` property on the `OracleDataReader` object determines the amount of data fetched into its internal cache for each database round-trip.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and `XMLType` data. Thus, applications can inadvertently fetch a large number of UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data does not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- OracleDataReader ["RowSize"](#) on page 167
- OracleCommand ["ExecuteReader\(\)"](#) on page 5-34
- OracleCommand ["RowSize"](#) on page 5-23

## FieldCount

This property returns the number of columns in the result set.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int FieldCount {get;}
```

**Property Value**

The number of columns in the result set if one exists, otherwise 0.

**Implements**

IDataRecord

**Exceptions**

InvalidOperationException - The reader is closed.

**Remarks**

Default = 0

This property has a value of 0 for queries that do not return result sets.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## HasRows

This property indicates whether the OracleDataReader has one or more rows.

**Declaration**

```
// ADO.NET 2.0: C#  
public override bool HasRows {get;}
```

**Return Value**

bool

**Remarks**

HasRows indicates whether or not the OracleDataReader has any rows.

The value of `HasRows` does not change based on the row position. For example, even if the application has read all the rows from the result set and the next `Read` method invocation will return false, the `HasRows` property still returns true since the result set was not empty to begin with.

Rows are fetched to determine the emptiness of the `OracleDataReader` when `HasRows` property is accessed for the first time after the creation of the `OracleDataReader` object.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class HasRowsSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand(
            "select * from emp where empno = 9999", con);

        OracleDataReader reader = cmd.ExecuteReader();

        if (!reader.HasRows)
            Console.WriteLine("The result set is empty.");
        else
            Console.WriteLine("The result set is not empty.");

        con.Dispose();
    }
}
```

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

## HiddenFieldCount

This property gets the number of fields in the `OracleDataReader` that are hidden.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

### Declaration

```
// C#
public int HiddenFieldcount { get; }
```



**Property Value**

The number of fields in the `OracleDataReader` that are hidden.

**Exceptions**

`InvalidOperationException` - The reader is closed.

**Remarks**

`OracleDataReader.FieldCount` and `OracleDataReader.VisibleFieldCount` return the visible field count.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["VisibleFieldCount"](#) on page 5-167
- ["FieldCount"](#) on page 5-161

**IsClosed**

This property indicates whether or not the data reader is closed.

**Declaration**

```
// ADO.NET 2.0: C#
public override bool IsClosed {get;}
```

**Property Value**

If the `OracleDataReader` is in a closed state, returns `true`; otherwise, returns `false`.

**Implements**

`IDataReader`

**Remarks**

Default = `true`

`IsClosed` and `RecordsAffected` are the only two properties that are accessible after the `OracleDataReader` is closed.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**Item**

This property gets the value of the column in .NET data type.

**Overload List:**

- [Item \[index\]](#)

This property gets the .NET `Value` of the column specified by the column index.

- [Item \[string\]](#)

This property gets the .NET Value of the column specified by the column name.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## Item [index]

This property gets the .NET Value of the column specified by the column index.

**Declaration**

```
// ADO.NET 2.0: C#  
public override object this[int index] {get;}
```

**Parameters**

- *index*  
The zero-based index of the column.

**Property Value**

The .NET value of the specified column.

**Implements**

IDataRecord

**Remarks**

Default = Not Applicable

In C#, this property is the indexer for this class.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## Item [string]

This property gets the .NET Value of the column specified by the column name.

**Declaration**

```
// ADO.NET 2.0: C#  
public override object this[string columnName] {get;}
```

**Parameters**

- *columnName*  
The name of the column.

**Property Value**

The .NET Value of the specified column.

**Implements**

IDataRecord

**Remarks**

Default = Not Applicable

A case-sensitive search is made to locate the specified column by its name. If this fails, then a case-insensitive search is made.

In C#, this property is the indexer for this class.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**InitialLOBFetchSize**

This property specifies the amount that the `OracleDataReader` initially fetches for LOB columns.

**Declaration**

```
// C#
public int InitialLOBFetchSize {get;}
```

**Property Value**

The size of the chunk to retrieve.

**Exceptions**

`InvalidOperationException` - The reader is closed.

**Remarks**

For Oracle Database 10g release 2 (10.2) and later, the maximum value supported for `InitialLOBFetchSize` is 2 GB.

For releases prior to Oracle Database 10g release 2 (10.2), the maximum value supported for `InitialLOBFetchSize` is 32K.

Default is the `OracleCommand.InitialLOBFetchSize`, from which this value is inherited.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["InitialLOBFetchSize"](#) on page 5-18 for further information on `OracleCommand.InitialLOBFetchSize`
- ["Obtaining LOB Data"](#) on page 3-52

**InitialLONGFetchSize**

This property specifies the amount that the `OracleDataReader` initially fetches for LONG and LONG RAW columns.

**Declaration**

```
// C#  
public long InitialLONGFetchSize {get;}
```

**Property Value**

The size of the chunk to retrieve. The default is 0.

**Exceptions**

`InvalidOperationException` - The reader is closed.

**Remarks**

The maximum value supported for `InitialLONGFetchSize` is 32767. If this property is set to a higher value, the provider resets it to 32767.

Default is `OracleCommand.InitialLONGFetchSize`, from which this value is inherited.

This property is read-only for the `OracleDataReader`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["InitialLONGFetchSize"](#) on page 5-20 for further information on `OracleCommand.InitialLONGFetchSize`
- ["Obtaining LONG and LONG RAW Data"](#) on page 3-51

**RecordsAffected**

This property gets the number of rows changed, inserted, or deleted by execution of the SQL statement.

**Declaration**

```
// C#  
public int RecordsAffected {get;}
```

**Property Value**

The number of rows affected by execution of the SQL statement.

**Implements**

`IDataReader`

**Remarks**

Default = 0

The value of -1 is returned for `SELECT` statements.

`IsClosed` and `RecordsAffected` are the only two properties that are accessible after the `OracleDataReader` is closed.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**RowSize**

This property gets the amount of memory the internal cache of the `OracleDataReader` needs to store one row of data.

**Declaration**

```
// C#
public long RowSize {get;}
```

**Property Value**

A `long` that indicates the amount of memory (in bytes) that an `OracleDataReader` needs to store one row of data for the executed query.

**Remarks**

The `RowSize` property is set to a nonzero value when the `OracleDataReader` object is created. This property can be used at design time or dynamically during run time, to set the `FetchSize` property, based on the number of rows. For example, to enable the `OracleDataReader` object to fetch  $N$  rows for each database round-trip, the `OracleDataReader FetchSize` property can be set dynamically to  $\text{RowSize} * N$ . Note that for the `FetchSize` property to take effect appropriately, it must be set before the first invocation of `OracleDataReader.Read()` for the particular result set.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["FetchSize"](#) on page 160

**VisibleFieldCount**

This property gets the number of fields in the `OracleDataReader` that are not hidden.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

**Declaration**

```
// C#
public override int VisibleFieldcount { get; }
```

**Property Value**

The number of fields that are not hidden.

**Exceptions**

`InvalidOperationException` - The reader is closed.

**Remarks**

If an application sets the `AddRowid` property on an `OracleCommand` object to `true`, then the application can access the `RowId` but it is not a visible field. If `RowId` is added in the select statement list, then it is a visible field.

`OracleDataReader.VisibleFieldCount` and `OracleDataReader.FieldCount` always have the same value.

**Example**

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class VisibleFieldCountSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        DbProviderFactory factory =
            DbProviderFactories.GetFactory("Oracle.DataAccess.Client");

        using (DbConnection conn = factory.CreateConnection())
        {
            conn.ConnectionString = constr;
            try
            {
                conn.Open();
                OracleCommand cmd = (OracleCommand)factory.CreateCommand();
                cmd.Connection = (OracleConnection)conn;

                //to gain access to ROWIDs of the table
                cmd.AddRowid = true;
                cmd.CommandText = "select empno, ename from emp;";

                OracleDataReader reader = cmd.ExecuteReader();

                int visFC = reader.VisibleFieldCount; //Results in 2
                int hidFC = reader.HiddenFieldCount; // Results in 1

                Console.WriteLine("Visible field count: " + visFC);
                Console.WriteLine("Hidden field count: " + hidFC);

                reader.Dispose();
                cmd.Dispose();
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine(ex.StackTrace);
            }
        }
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["VisibleFieldCount"](#) on page 5-167
- ["FieldCount"](#) on page 5-161

## OracleDataReader Public Methods

OracleDataReader public methods are listed in [Table 5–48](#).

**Table 5–48 OracleDataReader Public Methods**

Public Method	Description
<a href="#">Close</a>	Closes the OracleDataReader
<a href="#">CreateObjRef</a>	Inherited from System.MarshalByRefObject
<a href="#">Dispose</a>	Releases any resources or memory allocated by the object
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)
<a href="#">GetBoolean</a>	<i>Not Supported</i>
<a href="#">GetByte</a>	Returns the byte value of the specified column
<a href="#">GetBytes</a>	Populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column
<a href="#">GetChar</a>	<i>Not Supported</i>
<a href="#">GetChars</a>	Populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column
<a href="#">GetData</a>	<i>Not Supported</i>
<a href="#">GetDataTypeName</a>	Returns the ODP.NET type name of the specified column
<a href="#">GetDateTime</a>	Returns the DateTime value of the specified column
<a href="#">GetDecimal</a>	Returns the decimal value of the specified NUMBER column
<a href="#">GetDouble</a>	Returns the double value of the specified NUMBER column or BINARY_DOUBLE column
<a href="#">GetEnumerator</a>	Returns an IEnumerator that can be used to iterate through the collection
<a href="#">GetFieldType</a>	Returns the Type of the specified column
<a href="#">GetFloat</a>	Returns the float value of the specified NUMBER column or BINARY_FLOAT column
<a href="#">GetGuid</a>	<i>Not Supported</i>
<a href="#">GetHashCode</a>	Inherited from System.Object
<a href="#">GetInt16</a>	Returns the Int16 value of the specified NUMBER column
<a href="#">GetInt32</a>	Returns the Int32 value of the specified NUMBER column
<a href="#">GetInt64</a>	Returns the Int64 value of the specified NUMBER column
<a href="#">GetLifetimeService</a>	Inherited by System.MarshalByRefObject
<a href="#">GetName</a>	Returns the name of the specified column
<a href="#">GetOracleBFile</a>	Returns an OracleBFile object of the specified BFILE column
<a href="#">GetOracleBinary</a>	Returns an OracleBinary structure of the specified column
<a href="#">GetOracleBlob</a>	Returns an OracleBlob object of the specified BLOB column



**Table 5–48 (Cont.) OracleDataReader Public Methods**

<b>Public Method</b>	<b>Description</b>
<a href="#">GetOracleBlobForUpdate</a>	Returns an updatable <code>OracleBlob</code> object of the specified BLOB column
<a href="#">GetOracleClob</a>	Returns an <code>OracleClob</code> object of the specified CLOB column
<a href="#">GetOracleClobForUpdate</a>	Returns an updatable <code>OracleClob</code> object of the specified CLOB column
<a href="#">GetOracleDate</a>	Returns an <code>OracleDate</code> structure of the specified DATE column
<a href="#">GetOracleDecimal</a>	Returns an <code>OracleDecimal</code> structure of the specified NUMBER column
<a href="#">GetOracleIntervalDS</a>	Returns an <code>OracleIntervalDS</code> structure of the specified INTERVAL DAY TO SECOND column
<a href="#">GetOracleIntervalYM</a>	Returns an <code>OracleIntervalYM</code> structure of the specified INTERVAL YEAR TO MONTH column
<a href="#">GetOracleRef</a>	Returns an <code>OracleRef</code> object of the specified REF column
<a href="#">GetOracleString</a>	Returns an <code>OracleString</code> structure of the specified column
<a href="#">GetOracleTimeStamp</a>	Returns an <code>OracleTimeStamp</code> structure of the Oracle TimeStamp column
<a href="#">GetOracleTimeStampLTZ</a>	Returns an <code>OracleTimeStampLTZ</code> structure of the specified Oracle TimeStamp WITH LOCAL TIME ZONE column
<a href="#">GetOracleTimeStampTZ</a>	Returns an <code>OracleTimeStampTZ</code> structure of the specified Oracle TimeStamp WITH TIME ZONE column
<a href="#">GetOracleXmlType</a>	Returns an <code>OracleXmlType</code> object of the specified XMLType column
<a href="#">GetOracleValue</a>	Returns the specified column value as a ODP.NET type
<a href="#">GetOracleValues</a>	Gets all the column values as ODP.NET types
<a href="#">GetOrdinal</a>	Returns the 0-based ordinal (or index) of the specified column name
<a href="#">GetProviderSpecificFieldType</a>	Returns the provider-specific type of the specified column <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetProviderSpecificValue</a>	Returns an object that represents the underlying provider-specific value of the specified ordinal <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetProviderSpecificValues</a>	Returns an array of objects that represent the underlying provider-specific values <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">GetSchemaTable</a>	Returns a <code>DataTable</code> that describes the column metadata of the <code>OracleDataReader</code>
<a href="#">GetString</a>	Returns the string value of the specified column
<a href="#">GetTimeSpan</a>	Returns the <code>TimeSpan</code> value of the specified INTERVAL DAY TO SECOND column
<a href="#">GetType</a>	Inherited from <code>System.Object</code> class
<a href="#">GetValue</a>	Returns the column value as a .NET type

**Table 5–48 (Cont.) OracleDataReader Public Methods**

Public Method	Description
<a href="#">GetValues</a>	Gets all the column values as .NET types
<a href="#">GetXmlReader</a>	Returns the value of an XMLType column as an instance of an .NET XmlTextReader
<a href="#">IsDBNull</a>	Indicates whether or not the column value is null
<a href="#">NextResult</a>	Advances the data reader to the next result set when reading the results
<a href="#">Read</a>	Reads the next row in the result set
<a href="#">ToString</a>	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**Close**

This method closes the `OracleDataReader`.

**Declaration**

```
// ADO.NET 2.0: C#
public override void Close();
```

**Implements**

`IDataReader`

**Remarks**

The `Close` method frees all resources associated with the `OracleDataReader`.

**Example**

The code example for the `OracleDataReader` class includes the `Close` method. See [OracleDataReader Overview "Example"](#) on page 5-151.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**Dispose**

This method releases any resources or memory allocated by the object.

**Declaration**

```
// C#
public void Dispose();
```

**Implements**

IDisposable

**Remarks**

The `Dispose` method also closes the `OracleDataReader`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetBoolean**

This method is not supported.

**Declaration**

```
// ADO.NET 2.0: C#  
public override bool GetBoolean(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Implements**

IDataRecord

**Exceptions**

`NotSupportedException` - This property is not supported.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetByte**

This method returns the byte value of the specified column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override byte GetByte(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The value of the column as a byte.

**Implements**

IDataRecord

**Exceptions**

InvalidOperationException - The connection is closed, the reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

IsDBNull should be called to check for NULL values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetBytes**

This method populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override long GetBytes(int index, long fieldOffset, byte[] buffer,  
    int bufferOffset, int length);
```

**Parameters**

- *index*  
The zero-based column index.
- *fieldOffset*  
The offset within the column from which reading begins (in bytes).
- *buffer*  
The byte array that the data is read into.
- *bufferOffset*  
The offset within the buffer to begin reading data into (in bytes).
- *length*  
The maximum number of bytes to read (in bytes).

**Return Value**

The number of bytes read.

**Implements**

IDataRecord

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

### Remarks

This method returns the number of bytes read into the buffer. This may be less than the actual length of the field if the method has been called previously for the same column.

If a null reference is passed for buffer, the length of the field in bytes is returned.

`IsDBNull` should be called to check for `NULL` values before calling this method.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetChar

This method is not supported.

### Declaration

```
// ADO.NET 2.0: C#  
public override long GetChar(int index);
```

### Parameters

- *index*  
The zero based column index.

### Implements

`IDataRecord`

### Exceptions

`NotSupportedException` - This property is not supported.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetChars

This method populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column.

### Declaration

```
// ADO.NET 2.0: C#
```

```
public override long GetChars(int index, long fieldOffset, char[] buffer,
    int bufferOffset, int length);
```

### Parameters

- *index*  
The zero based column index.
- *fieldOffset*  
The index within the column from which to begin reading (in characters).
- *buffer*  
The character array that the data is read into.
- *bufferOffset*  
The index within the buffer to begin reading data into (in characters).
- *length*  
The maximum number of characters to read (in characters).

### Return Value

The number of characters read.

### Implements

IDataRecord

### Exceptions

*InvalidOperationException* - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

*InvalidCastException* - The accessor method is invalid for this column type or the column value is NULL.

### Remarks

This method returns the number of characters read into the buffer. This may be less than the actual length of the field, if the method has been called previously for the same column.

If a null reference is passed for `buffer`, the length of the field in characters is returned.

`IsDBNull` should be called to check for NULL values before calling this method.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetDataTypeName

This method returns the ODP.NET type name of the specified column.

### Declaration

```
// ADO.NET 2.0: C#
```

```
public override string GetDataTypeName(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

The name of the ODP.NET type of the column.

### Implements

IDataRecord

### Exceptions

*InvalidOperationException* - The reader is closed.

*IndexOutOfRangeException* - The column index is invalid.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetDateTime

This method returns the `DateTime` value of the specified column.

### Declaration

```
// ADO.NET 2.0: C#  
public override DateTime GetDateTime(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

The `DateTime` value of the column.

### Implements

IDataRecord

### Exceptions

*InvalidOperationException* - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

*InvalidCastException* - The accessor method is invalid for this column type or the column value is `NULL`.

### Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetDecimal

This method returns the decimal value of the specified NUMBER column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override decimal GetDecimal(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The decimal value of the column.

**Implements**

IDataRecord

**Exceptions**

*InvalidOperationException* - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

*InvalidCastException* - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

`IsDBNull` should be called to check for NULL values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetDouble

This method returns the double value of the specified NUMBER column or BINARY\_DOUBLE column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override double GetDouble(int index);
```

**Parameters**

- *index*



The zero-based column index.

**Return Value**

The double value of the column.

**Implements**

IDataRecord

**Exceptions**

*InvalidOperationException* - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

*InvalidCastException* - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

`IsDBNull` should be called to check for NULL values before calling this method.

Starting with Oracle Database 10g, `GetDouble` now supports retrieval of data from `BINARY_DOUBLE` columns.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetEnumerator**

This method returns an `IEnumerator` that can be used to iterate through the collection (record set).

**Declaration**

```
// ADO.NET 2.0: C#  
public override IEnumerator GetEnumerator();
```

**Return Value**

An `IEnumerator` that can be used to iterate through the collection (record set).

**Exceptions**

*InvalidOperationException* - The reader is closed.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetFieldType**

This method returns the type of the specified column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override Type GetFieldType(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The type of the default .NET type of the column.

**Implements**

`IDataRecord`

**Exceptions**

`InvalidOperationException` - The reader is closed, or the specified column is a UDT but no registered custom type mapping exists for the UDT.

`IndexOutOfRangeException` - The column index is invalid.

**Remarks**

`GetFieldType` returns a type that corresponds to the value that the application obtains after invoking the `GetValue` accessor or `Item` property on the `OracleDataReader`. For example, if the column is a string, this method returns a .NET Type object for a .NET string.

If the attribute is a UDT, this method may return either of the following:

- A .NET Type of the custom type if a custom type mapping exists for the Oracle object or collection.
- A .NET Type of string if the column is an Oracle REF.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetFloat**

This method returns the `float` value of the specified `NUMBER` column or `BINARY_FLOAT` column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override float GetFloat(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `float` value of the column.

**Implements**

IDataRecord

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

Starting with Oracle Database 10g, `GetFloat` now supports retrieval of data from `BINARY_FLOAT` columns.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetGuid**

This method is not supported.

**Declaration**

```
// ADO.NET 2.0: C#
public override Guid GetGuid(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Implements**

IDataRecord

**Exceptions**

`NotSupportedException` - This property is not supported.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetInt16**

This method returns the `Int16` value of the specified `NUMBER` column.

---

**Note:** `short` is equivalent to `Int16`.

---

**Declaration**

```
// ADO.NET 2.0: C#  
public override short GetInt16(int index);
```

**Parameters**

- *index*

The zero-based column index.

**Return Value**

The Int16 value of the column.

**Implements**

IDataRecord

**Exceptions**

*InvalidOperationException* - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

*InvalidCastException* - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

`IsDBNull` should be called to check for NULL values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetInt32**

This method returns the Int32 value of the specified NUMBER column.

---

---

**Note:** `int` is equivalent to `Int32`.

---

---

**Declaration**

```
// ADO.NET 2.0: C#  
public override int GetInt32(int index);
```

**Parameters**

- *index*

The zero-based column index.

**Return Value**

The Int32 value of the column.

**Implements**

IDataRecord

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetInt64**

This method returns the `Int64` value of the specified `NUMBER` column.

---



---

**Note:** `long` is equivalent to `Int64`.

---



---

**Declaration**

```
// ADO.NET 2.0: C#
public override long GetInt64(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `Int64` value of the column.

**Implements**

`IDataRecord`

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetName**

This method returns the name of the specified column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string GetName(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The name of the column.

**Implements**

IDataRecord

**Exceptions**

*InvalidOperationException* - The reader is closed.

*IndexOutOfRangeException* - The column index is invalid.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleBFile**

This method returns an *OracleBFile* object of the specified *BFILE* column.

**Declaration**

```
// C#  
public OracleBFile GetOracleBFile(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The *OracleBFile* value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleBinary**

This method returns an `OracleBinary` structure of the specified column.

**Declaration**

```
// C#  
public OracleBinary GetOracleBinary(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleBinary` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

`GetOracleBinary` is used on the following Oracle types:

- `BFILE`
- `BLOB`
- `LONG RAW`
- `RAW`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleBlob**

This method returns an `OracleBlob` object of the specified BLOB column.

**Declaration**

```
// C#  
public OracleBlob GetOracleBlob(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleBlob` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleBlobForUpdate**

`GetOracleBlobForUpdate` returns an updatable `OracleBlob` object of the specified BLOB column.

**Overload List:**

- [GetOracleBlobForUpdate\(int\)](#)  
This method returns an updatable `OracleBlob` object of the specified BLOB column.
- [GetOracleBlobForUpdate\(int, int\)](#)  
This method returns an updatable `OracleBlob` object of the specified BLOB column using a `WAIT` clause.



## GetOracleBlobForUpdate(int)

This method returns an updatable `OracleBlob` object of the specified BLOB column.

### Declaration

```
// C#
public OracleBlob GetOracleBlobForUpdate(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

An updatable `OracleBlob` object.

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

### Remarks

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleBlobForUpdate()` method incurs a database round-trip to obtain a reference to the current BLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleBlob` obtained from `GetOracleBlob()` can have a different value than the `OracleBlob` obtained from `GetOracleBlobForUpdate()` since it is not obtained from the original snapshot.

The returned `OracleBlob` object can be used to safely update the BLOB because the BLOB column has been locked after a call to this method.

Invoking this method internally executes a `SELECT . . . FOR UPDATE` statement without a `WAIT` clause. Therefore, the statement can wait indefinitely until a lock is acquired for that row.

`IsDBNull` should be called to check for `NULL` values before calling this method.

### Example

The following example gets the `OracleBlob` object for update from the reader, updates the `OracleBlob` object, and then commits the transaction.

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);
```

```
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetOracleBlobForUpdateSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get the ByteCodes for empno = 1
        string cmdstr = "SELECT BYTECODES, EMPNO FROM EMPINFO where EMPNO = 1";
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        // Since we are going to update the OracleBlob object, we will
        //have to create a transaction
        OracleTransaction txn = con.BeginTransaction();

        // Get the reader
        OracleDataReader reader = cmd.ExecuteReader();

        // Declare the variables to retrieve the data in EmpInfo
        OracleBlob byteCodesBlob;

        // Read the first row
        reader.Read();
        if (!reader.IsDBNull(0))
        {
            byteCodesBlob = reader.GetOracleBlobForUpdate(0);

            // Close the reader
            reader.Close();

            // Update the ByteCodes object
            byte[] addedBytes = new byte[2] {0, 0};
            byteCodesBlob.Append(addedBytes, 0, addedBytes.Length);

            // Now commit the transaction
            txn.Commit();
            Console.WriteLine("Blob Column successfully updated");
        }
        else
            reader.Dispose();

        // Close the connection
        con.Dispose();
    }
}
```

```
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

**GetOracleBlobForUpdate(int, int)**

This method returns an updatable `OracleBlob` object of the specified BLOB column using a `WAIT` clause.

**Declaration**

```
// C#
public OracleBlob GetOracleBlobForUpdate(int index, int wait);
```

**Parameters**

- *index*  
The zero-based column index.
- *wait*  
The number of seconds the method waits to acquire a lock.

**Return Value**

An updatable `OracleBlob` object.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleBlobForUpdate()` method incurs a database round-trip to obtain a reference to the current BLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleBlob` obtained from `GetOracleBlob()` can have a different value than the `OracleBlob` obtained from `GetOracleBlobForUpdate()` since it is not obtained from the original snapshot.

`IsDBNull` should be called to check for `NULL` values before calling this method.

The returned `OracleBlob` object can be used to safely update the BLOB because the BLOB column has been locked after a call to this method.

Invoking this method internally executes a `SELECT . . . FOR UPDATE` statement which locks the row.

Different `WAIT` clauses are appended to the statement, depending on the `wait` value. If the `wait` value is:

- 0  
"NOWAIT" is appended at the end of a `SELECT . . FOR UPDATE` statement. The statement executes immediately whether the lock is acquired or not. If the lock is not acquired, an exception is thrown.
- *n*  
"WAIT *n*" is appended at the end of a `SELECT . . FOR UPDATE` statement. The statement executes as soon as the lock is acquired. However, if the lock cannot be acquired by *n* seconds, this method call throws an exception.  
  
The `WAIT n` feature is only available for Oracle9i or later. For any version lower than Oracle9i, *n* is implicitly treated as -1 and nothing is appended at the end of a `SELECT . . FOR UPDATE` statement.
- -1  
Nothing is appended at the end of the `SELECT . . FOR UPDATE`. The statement execution waits indefinitely until a lock can be acquired.

### Example

The `GetOracleBlobForUpdate` methods are comparable. See "Example" on page 5-187 for a code example demonstrating usage.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

## GetOracleClob

This method returns an `OracleClob` object of the specified CLOB column.

### Declaration

```
// C#  
public OracleClob GetOracleClob(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

The `OracleClob` value of the column.

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

### Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

## GetOracleClobForUpdate

`GetOracleClobForUpdate` returns an updatable `OracleClob` object of the specified `CLOB` column.

### Overload List:

- [GetOracleClobForUpdate\(int\)](#)  
This method returns an updatable `OracleClob` object of the specified `CLOB` column.
- [GetOracleClobForUpdate\(int, int\)](#)  
This method returns an updatable `OracleClob` object of the specified `CLOB` column using a `WAIT` clause.

## GetOracleClobForUpdate(int)

This method returns an updatable `OracleClob` object of the specified `CLOB` column.

### Declaration

```
// C#  
public OracleClob GetOracleClobForUpdate(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

An updatable `OracleClob`.

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleClobForUpdate()` method incurs a database round-trip to obtain a reference to the current CLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleClob` obtained from `GetOracleClob()` can have a different value than the `OracleClob` obtained from `GetOracleClobForUpdate()` since it is not obtained from the original snapshot.

The returned `OracleClob` object can be used to safely update the CLOB because the CLOB column is locked after a call to this method.

Invoking this method internally executes a `SELECT . . FOR UPDATE` statement without a `WAIT` clause. Therefore, the statement can wait indefinitely until a lock is acquired for that row.

`IsDBNull` should be called to check for `NULL` values before calling this method.

**Example**

The following example gets the `OracleClob` object for update from the reader, updates the `OracleClob` object, and then commits the transaction.

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetOracleClobForUpdateSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get the job description for empno = 1
        string cmdStr = "SELECT JOBDESCRIPTION, EMPNO FROM EMPINFO where EMPNO = 1";
        OracleCommand cmd = new OracleCommand(cmdStr, con);
```

```

// Since we are going to update the OracleClob object, we will
// have to create a transaction
OracleTransaction txn = con.BeginTransaction();

// Get the reader
OracleDataReader reader = cmd.ExecuteReader();

// Declare the variables to retrieve the data in EmpInfo
OracleClob jobDescClob;

// Read the first row
reader.Read();

if (!reader.IsDBNull(0))
{
    jobDescClob = reader.GetOracleClobForUpdate(0);

    // Close the reader
    reader.Close();

    // Update the job description Clob object
    char[] jobDesc = "-SALES".ToCharArray();
    jobDescClob.Append(jobDesc, 0, jobDesc.Length);

    // Now commit the transaction
    txn.Commit();
    Console.WriteLine("Clob Column successfully updated");
}
else
    reader.Close();

// Close the connection
con.Close();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

**GetOracleClobForUpdate(int, int)**

This method returns an updatable `OracleClob` object of the specified CLOB column using a `WAIT` clause.

**Declaration**

```

// C#
public OracleClob GetOracleClobForUpdate(int index, int wait);

```

**Parameters**

- *index*  
The zero-based column index.

- *wait*

The number of seconds the method waits to acquire a lock.

### Return Value

An updatable `OracleClob`.

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

### Remarks

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleClobForUpdate()` method incurs a database round-trip to obtain a reference to the current CLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleClob` obtained from `GetOracleClob()` can have a different value than the `OracleClob` obtained from `GetOracleClobForUpdate()` since it is not obtained from the original snapshot.

Invoking this method internally executes a `SELECT . . FOR UPDATE` statement which locks the row.

The returned `OracleClob` object can be used to safely update the CLOB because the CLOB column is locked after a call to this method.

Different `WAIT` clauses are appended to the statement, depending on the *wait* value. If the *wait* value is:

- 0

"`NOWAIT`" is appended at the end of a `SELECT . . FOR UPDATE` statement. The statement executes immediately whether the lock is acquired or not. If the lock is not acquired, an exception is thrown.

- *n*

"`WAIT n`" is appended at the end of a `SELECT . . FOR UPDATE` statement. The statement executes as soon as the lock is acquired. However, if the lock cannot be acquired by *n* seconds, this method call throws an exception.

The `WAIT n` feature is only available for Oracle9i or later. For any version lower than Oracle9i, *n* is implicitly treated as -1 and nothing is appended at the end of a `SELECT . . FOR UPDATE` statement.

- -1

Nothing is appended at the end of the `SELECT . . FOR UPDATE`. The statement execution waits indefinitely until a lock can be acquired.

`IsDBNull` should be called to check for `NULL` values before calling this method.

### Example

The `GetOracleClobForUpdate` methods are comparable. See ["Example"](#) on page 5-192 for a code example demonstrating usage.



**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

**GetOracleDate**

This method returns an OracleDate structure of the specified DATE column.

**Declaration**

```
// C#  
public OracleDate GetOracleDate(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The OracleDate value of the column.

**Exceptions**

InvalidOperationException - The connection is closed, the reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

IsDBNull should be called to check for NULL values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

**GetOracleDecimal**

This method returns an OracleDecimal structure of the specified NUMBER column.

**Declaration**

```
// C#  
public OracleDecimal GetOracleDecimal(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleDecimal` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleIntervalDS**

This method returns an `OracleIntervalDS` structure of the specified `INTERVAL DAY TO SECOND` column.

**Declaration**

```
// C#  
public OracleIntervalDS GetOracleIntervalDS(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleIntervalDS` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetOracleIntervalYM

This method returns an `OracleIntervalYM` structure of the specified `INTERVAL YEAR TO MONTH` column.

### Declaration

```
// C#  
public OracleIntervalYM GetOracleIntervalYM(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

The `OracleIntervalYM` value of the column.

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

### Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetOracleRef

This method returns an `OracleRef` object of the specified `REF` column.

### Declaration

```
// C#  
public OracleRef GetOracleRef(int index);
```

### Parameters

- *index*  
The zero-based column index.

### Return Value

The `OracleRef` object of the specified column.

### Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, the `Read` method has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetOracleString

This method returns an `OracleString` structure of the specified column.

**Declaration**

```
// C#  
public OracleString GetOracleString(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleString` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

If the column is an Oracle REF column, the string returned is a hexadecimal value that represents the REF in the database.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetOracleTimeStamp

This method returns an `OracleTimeStamp` structure of the Oracle `TimeStamp` column.

**Declaration**

```
// C#  
public OracleTimeStamp GetOracleTimeStamp(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleTimeStamp` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`GetOracleTimeStamp` is used with the Oracle Type `TimeStamp`.

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleTimeStampLTZ**

This method returns an `OracleTimeStampLTZ` structure of the specified Oracle `TimeStamp WITH LOCAL TIME ZONE` column.

**Declaration**

```
// C#  
public OracleTimeStampLTZ GetOracleTimeStampLTZ(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleTimeStampLTZ` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`GetOracleTimeStampLTZ` is used with the Oracle Type `TimeStamp with Local Time Zone` columns.

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleTimeStampTZ**

This method returns an `OracleTimeStampTZ` structure of the specified Oracle `TimeStamp WITH TIME ZONE` column.

**Declaration**

```
// C#  
public OracleTimeStampTZ GetOracleTimeStampTZ(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleTimeStampTZ` value of the column.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

Used with the Oracle Type `TimeStamp with Local Time Zone` columns

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleXmlType**

This method returns an `OracleXmlType` object of the specified `XMLType` column.

**Declaration**

```
// C#  
public OracleXmlType GetOracleXmlType(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `OracleXmlType` value of the column.

**Exceptions**

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**Requirements**

This property can only be used with Oracle9i Release 2 (9.2) or later.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleValue**

This method returns the specified column value as an ODP.NET type.

**Declaration**

```
// C#  
public object GetOracleValue(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The value of the column as an ODP.NET type.

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

**Remarks**

If the column is an Oracle object or Oracle collection column and a custom type mapping exists, then a custom type is returned.

If the column is an Oracle REF column, then an `OracleRef` is returned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetOracleValues**

This method gets all the column values as ODP.NET types.

**Declaration**

```
// C#  
public int GetOracleValues(object[] values);
```

**Parameters**

- *values*

An array of objects to hold the ODP.NET types as the column values.

**Return Value**

The number of ODP.NET types in the *values* array.

**Exceptions**

*InvalidOperationException* - The connection is closed, the reader is closed, *Read()* has not been called, or all rows have been read.

**Remarks**

This method provides a way to retrieve all column values rather than retrieving each column value individually.

The number of column values retrieved is the minimum of the length of the *values* array and the number of columns in the result set.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-61

**GetOrdinal**

This method returns the 0-based ordinal (or index) of the specified column name.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int GetOrdinal(string name);
```

**Parameters**

- *name*

The specified column name.



**Return Value**

The index of the column.

**Implements**

IDataRecord

**Exceptions**

`InvalidOperationException` - The reader is closed.

`IndexOutOfRangeException` - The column index is invalid.

**Remarks**

A case-sensitive search is made to locate the specified column by its name. If this fails, then a case-insensitive search is made.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetProviderSpecificFieldType**

This method returns the provider-specific type of the specified column.

**Declaration**

```
// ADO.NET 2.0: C#
public override Type GetProviderSpecificFieldType(int index);
```

**Parameters**

- *index*  
A zero-based column index.

**Return Value**

The provider-specific type of the specified column. This is a member of the `Oracle.DataAccess.Types` namespace.

**Exceptions**

`IndexOutOfRangeException` - The column index is invalid.

`InvalidOperationException` - The reader is closed, or the specified column is a UDT but no registered custom type mapping exists for the UDT.

**Remarks**

`GetProviderSpecficFieldType` returns a type that corresponds to the value the application obtains after invoking the `GetProviderSpecificValue` accessor on the `OracleDataReader`. For example, if the column is a string, this method returns a .NET Type object for an `OracleString`.

If the attribute is a UDT, this method may return any of the following:

- A .NET Type of the custom type, if the column is an Oracle object or Oracle collection column and a custom type mapping exists.

- A .NET Type of `OracleRef` if the column is an Oracle REF.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetProviderSpecificValue

This method returns an object that represents the underlying provider-specific value of the specified ordinal.

**Declaration**

```
// ADO.NET 2.0: C#  
public override object GetProviderSpecificValue (int index);
```

**Parameters**

*index*

A zero-based column index.

**Return Value**

An `Object` that is a representation of the underlying provider-specific field type.

**Exceptions**

`IndexOutOfRangeException` - The column index is invalid.

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called or all rows have been read.

**Remarks**

If the column is an Oracle object or collection column, and a custom type mapping exists, a custom type is returned.

If the column is an Oracle REF column, an `OracleRef` is returned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetProviderSpecificValues

This method returns an array of objects that represent the underlying provider-specific values.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int GetProviderSpecificValues(object [ ] values);
```

**Parameters**

- *values*  
An array of objects.

**Return Value**

The number of `Object` instances in the array.

**Exceptions**

`InvalidOperationException` - The reader is closed.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetSchemaTable**

This method returns a `DataTable` that describes the column metadata of the `OracleDataReader`.

**Declaration**

```
// ADO.NET 2.0: C#  
public override DataTable GetSchemaTable();
```

**Return Value**

A `DataTable` that contains the metadata of the result set.

**Implements**

`IDataReader`

**Exceptions**

`InvalidOperationException` - The connection is closed or the reader is closed.

**Remarks**

The `OracleDataReader.GetSchemaTable` method returns the `SchemaTable`.

**OracleDataReader SchemaTable**

The `OracleDataReader SchemaTable` is a `DataTable` that describes the column metadata of the `OracleDataReader`.

The columns of the `SchemaTable` are in the order shown.

**Table 5–49 OracleDataReader SchemaTable**

Name	Name Type	Description
ColumnName	System.String	The name of the column.
ColumnOrdinal	System.Int32	The 0-based ordinal of the column.
ColumnSize	System.Int64	<p>The maximum possible length of a value in the column. ColumnSize value is determined as follows:</p> <ul style="list-style-type: none"> <li>■ CHAR and VARCHAR2 types: <ul style="list-style-type: none"> <li>in bytes - if <code>IsByteSemantic</code> boolean value is <code>true</code></li> <li>in characters - if <code>IsByteSemantic</code> boolean value is <code>false</code></li> </ul> </li> <li>■ All other types: <ul style="list-style-type: none"> <li>in bytes</li> </ul> </li> </ul> <p>See "<a href="#">IsByteSemantic</a>" on page 5-207 for more information.</p>
NumericPrecision	System.Int16	<p>The maximum precision of the column, if the column is a numeric data type.</p> <p>This column has valid values for Oracle NUMBER, Oracle INTERVAL YEAR TO MONTH, and Oracle INTERVAL DAY TO SECOND columns. For all other columns, the value is null.</p>
NumericScale	System.Int16	<p>The scale of the column.</p> <p>This column has valid values for Oracle NUMBER, Oracle INTERVAL DAY TO SECOND, and the Oracle TIMESTAMP columns. For all other columns, the value is null.</p>
IsUnique	System.Boolean	<p>Indicates whether or not the column is unique.</p> <p><code>true</code> if no two rows in the base table can have the same value in this column, where the base table is the table returned in <code>BaseTableName</code>.</p> <p><code>IsUnique</code> is guaranteed to be <code>true</code> if one of the following applies:</p> <ul style="list-style-type: none"> <li>■ the column constitutes a key by itself</li> <li>■ there is a unique constraint or a unique index that applies only to this column and a <code>NOT NULL</code> constraint has been defined on the column</li> <li>■ the column is an explicitly selected <code>ROWID</code></li> </ul> <p><code>IsUnique</code> is <code>false</code> if the column can contain duplicate values in the base table.</p> <p>The default is <code>false</code>.</p> <p>The value of this property is the same for each occurrence of the base table column in the select list.</p>

**Table 5–49 (Cont.) OracleDataReader SchemaTable**

Name	Name Type	Description
IsKey	System.Boolean	<p>Indicates whether or not the column is a key column.</p> <p>true if the column is one of a set of columns in the rowset that, taken together, uniquely identify the row. The set of columns with IsKey set to true must uniquely identify a row in the rowset. There is no requirement that this set of columns is a minimal set of columns.</p> <p>This set of columns can be generated from one of the following in descending order of priority:</p> <ul style="list-style-type: none"> <li>■ A base table primary key.</li> <li>■ Any of the unique constraints or unique indexes with the following condition: A NOT NULL constraint must be defined on the column or on all of the columns, in the case of a composite unique constraint or composite unique index.</li> <li>■ Any of the composite unique constraints or composite unique indexes with the following condition: A NULL constraint must be defined on at least one, but not all, of the columns.</li> </ul> <p>An explicitly selected ROWID. false if the column is not required to uniquely identify the row. The value of this property is the same for each occurrence of the base table column in the select list.</p>
IsRowID	System.Boolean	true if the column is a ROWID, otherwise false.
BaseColumnName	System.String	The name of the column in the database if an alias is used for the column.
BaseSchemaName	System.String	The name of the schema in the database that contains the column.
BaseTableName	System.String	The name of the table or view in the database that contains the column.
DataType	System.RuntimeType	Maps to the common language runtime type.
ProviderType	Oracle.DataAccess.Client.OracleDbType	The database column type (OracleDbType) of the column.
AllowDBNull	System.Boolean	true if null values are allowed, otherwise false.
IsAliased	System.Boolean	true if the column is an alias; otherwise false.
IsByteSemantic	System.Boolean	<p>IsByteSemantic is:</p> <ul style="list-style-type: none"> <li>■ true if the ColumnSize value uses bytes semantics</li> <li>■ false if ColumnSize uses character semantics</li> </ul> <p>This value is always true when connected to a database version earlier than Oracle9i.</p>
IsExpression	System.Boolean	true if the column is an expression; otherwise false.
IsHidden	System.Boolean	true if the column is hidden; otherwise false.
IsReadOnly	System.Boolean	true if the column is read-only; otherwise false.
IsLong	System.Boolean	true if the column is a LONG, LONG RAW, BLOB, CLOB, or BFILE; otherwise false.
UdtTypeName	System.String	The type name of the UDT.

**Example**

This example creates and uses the `SchemaTable` from the reader.

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetSchemaTableSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdstr = "SELECT EMPNO,EMPNAME FROM EMPINFO where EMPNO = 1";
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        //get the reader
        OracleDataReader reader = cmd.ExecuteReader();

        //get the schema table
        DataTable schemaTable = reader.GetSchemaTable();

        //retrieve the first column info.
        DataRow row = schemaTable.Rows[0];

        //print out the column info
        Console.WriteLine("Column name: " + row["COLUMNNAME"]);
        Console.WriteLine("Precision: " + row["NUMERICPRECISION"]);
        Console.WriteLine("Scale: " + row["NUMERICSCALE"]);
        reader.Close();

        // Close the connection
        con.Close();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetString

This method returns the string value of the specified column.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string GetString(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The string value of the column.

**Implements**

IDataRecord

**Exceptions**

*InvalidOperationException* - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

*InvalidCastException* - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

Call the `IsDBNull` method to check for null values before calling this method.

If the column is an Oracle REF column, the string returned is a hexadecimal string that represents the REF in the database.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## GetTimeSpan

This method returns the `TimeSpan` value of the specified `INTERVAL DAY TO SECOND` column.

**Declaration**

```
// C#  
public TimeSpan GetTimeSpan(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The `TimeSpan` value of the column.

**Implements**

`IDataRecord`

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

**Remarks**

`IsDBNull` should be called to check for `NULL` values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetValue**

This method returns the column value as a .NET type.

**Declaration**

```
// ADO.NET 2.0: C#  
public override object GetValue(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

The value of the column as a .NET type.

**Implements**

`IDataRecord`

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, all rows have been read, or no valid custom type mapping has been specified for the Oracle Object or Oracle Collection column.

`IndexOutOfRangeException` - The column index is invalid.



**Remarks**

If the column is an Oracle Object or an Oracle Collection column, the .NET custom type corresponding to the custom type mapping is returned.

If the column is an Oracle REF column, a hexadecimal value is returned as a .NET string that represents the REF in the database.

If the UDT is NULL, `DBNull.Value` is returned

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetValues**

This method gets all the column values as .NET types.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int GetValues(object[ ] values);
```

**Parameters**

- *values*

An array of objects to hold the .NET types as the column values.

**Return Value**

The number of objects in the *values* array.

**Implements**

`IDataRecord`

**Exceptions**

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

**Remarks**

This method provides a way to retrieve all column values rather than retrieving each column value individually.

The number of column values retrieved is the minimum of the length of the values array and the number of columns in the result set.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**GetXmlReader**

This method returns the contents of an `XMLType` column as an instance of an .NET `XmlTextReader` object.

**Declaration**

```
// C#  
public XmlReader GetXmlReader(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

A .NET XmlTextReader.

**Exceptions**

*InvalidCastException* - The accessor method is invalid for this column type or the column value is NULL.

**Remarks**

*IsDBNull* should be called to check for NULL values before calling this method.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

**IsDBNull**

This method indicates whether or not the column value is NULL.

**Declaration**

```
// ADO.NET 2.0: C#  
public override bool IsDBNull(int index);
```

**Parameters**

- *index*  
The zero-based column index.

**Return Value**

Returns *true* if the column is a NULL value; otherwise, returns *false*.

**Implements**

*IDataRecord*

**Exceptions**

*InvalidOperationException* - The reader is closed, *Read()* has not been called, or all rows have been read.

*IndexOutOfRangeException* - The column index is invalid.

**Remarks**

This method should be called to check for NULL values before calling the other accessor methods.

### Example

The code example for the `OracleDataReader` class includes the `IsDBNull` method. See "Example" on page 5-151.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## NextResult

This method advances the data reader to the next result set.

### Declaration

```
// ADO.NET 2.0: C#  
public override bool NextResult();
```

### Return Value

Returns `true` if another result set exists; otherwise, returns `false`.

### Implements

`IDataReader`

### Exceptions

`InvalidOperationException` - The connection is closed or the reader is closed.

### Remarks

`NextResult` is used when reading results from stored procedure execution that return more than one result set.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

## Read

This method reads the next row in the result set.

### Declaration

```
// ADO.NET 2.0: C#  
public override bool Read();
```

### Return Value

Returns `true` if another row exists; otherwise, returns `false`.

### Implements

`IDataReader`

### Exceptions

`InvalidOperationException` - The connection is closed or the reader is closed.

### Remarks

The initial position of the data reader is before the first row. Therefore, the `Read` method must be called to fetch the first row. The row that was just read is considered the *current row*. If the `OracleDataReader` has no more rows to read, it returns `false`.

### Example

The code example for the `OracleDataReader` class includes the `Read` method. See ["Example"](#) on page 5-151.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

---

## OracleError Class

The `OracleError` class represents an error reported by Oracle.

### Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleError`

### Declaration

```
// C#  
public sealed class OracleError
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

The `OracleError` class represents a warning or an error reported by Oracle.

If there are multiple errors, ODP.NET only returns the first error message on the stack.

### Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class OracleErrorsSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Create an OracleCommand object using the connection object  
        OracleCommand cmd = con.CreateCommand();  
  
        try  
        {  
            cmd.CommandText = "insert into notable values (99, 'MyText')";  
            cmd.ExecuteNonQuery();  
        }  
        catch (OracleException ex)  
        {  
            Console.WriteLine("Record is not inserted into the database table.");  
  
            foreach (OracleError error in ex.Errors)  
            {  
                Console.WriteLine("Error Message: " + error.Message);  
                Console.WriteLine("Error Source: " + error.Source);  
            }  
        }  
    }  
}
```

```
    }  
  }  
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleError Members](#)
- [OracleError Static Methods](#)
- [OracleError Properties](#)
- [OracleError Methods](#)

## OracleError Members

OracleError members are listed in the following tables.

### OracleError Static Methods

The OracleError static method is listed in [Table 5-50](#).

**Table 5-50 OracleError Static Method**

Method	Description
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)

### OracleError Properties

OracleError properties are listed in [Table 5-51](#).

**Table 5-51 OracleError Properties**

Property	Description
<a href="#">ArrayBindIndex</a>	Specifies the row number of errors that occurred during the Array Bind execution
<a href="#">DataSource</a>	Specifies the Oracle service name (TNS name) that identifies the Oracle database
<a href="#">Message</a>	Specifies the message describing the error
<a href="#">Number</a>	Specifies the Oracle error number
<a href="#">Procedure</a>	Specifies the stored procedure that causes the error
<a href="#">Source</a>	Specifies the name of the data provider that generates the error

### OracleError Methods

OracleError methods are listed in [Table 5-52](#).

**Table 5-52 OracleError Methods**

Method	Description
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Returns a string representation of the OracleError

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)

## OracleError Static Methods

The `OracleError` static method is listed in [Table 5-53](#).

**Table 5-53 OracleError Static Method**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)



## OracleError Properties

OracleError properties are listed in [Table 5–54](#).

**Table 5–54 OracleError Properties**

Property	Description
<a href="#">ArrayBindIndex</a>	Specifies the row number of errors that occurred during the Array Bind execution
<a href="#">DataSource</a>	Specifies the Oracle service name (TNS name) that identifies the Oracle database
<a href="#">Message</a>	Specifies the message describing the error
<a href="#">Number</a>	Specifies the Oracle error number
<a href="#">Procedure</a>	Specifies the stored procedure that causes the error
<a href="#">Source</a>	Specifies the name of the data provider that generates the error

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

### ArrayBindIndex

This property specifies the row number of errors that occurred during the Array Bind execution.

#### Declaration

```
// C#
public int ArrayBindIndex {get;}
```

#### Property Value

An `int` value that specifies the row number for errors that occurred during the Array Bind execution.

#### Remarks

Default = 0.

This property is used for Array Bind operations only.

`ArrayBindIndex` represents the zero-based row number at which the error occurred during an Array Bind operation. For example, if an array bind execution causes two errors on the 2nd and 4th operations, two `OracleError` objects appear in the `OracleErrorCollection` with the `ArrayBindIndex` property values 2 and 4 respectively.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)
- ["Array Binding"](#) on page 3-39

**DataSource**

This property specifies the Oracle service name (TNS name) that identifies the Oracle database.

**Declaration**

```
// C#  
public string DataSource {get;}
```

**Property Value**

A string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

**Message**

This property specifies the message describing the error.

**Declaration**

```
// C#  
public string Message {get;}
```

**Property Value**

A string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

**Number**

This property specifies the Oracle error number.

**Declaration**

```
// C#  
public int Number {get;}
```

**Property Value**

An int.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

**Procedure**

This property specifies the stored procedure that causes the error.

**Declaration**

```
// C#  
public string Procedure {get;}
```

**Property Value**

The stored procedure name.

**Remarks**

Represents the stored procedure which creates this `OracleError` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

**Source**

This property specifies the name of the data provider that generates the error.

**Declaration**

```
// C#  
public string Source {get;}
```

**Property Value**

A `string`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

## OracleError Methods

OracleError methods are listed in [Table 5–55](#).

**Table 5–55 OracleError Methods**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Returns a string representation of the <code>OracleError</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

### ToString

Overrides `Object`

This method returns a string representation of the `OracleError`.

**Declaration**

```
// C#  
public override string ToString();
```

**Return Value**

Returns a string with the format `Ora- error number: Class.Method name error message stack trace information.`

**Example**

ORA-24333: zero iteration count

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleError Class](#)
- [OracleError Members](#)

---

## OracleErrorCollection Class

An `OracleErrorCollection` class represents a collection of all errors that are thrown by the Oracle Data Provider for .NET.

### Class Inheritance

`System.Object`

`System.ArrayList`

`Oracle.DataAccess.Client.OracleErrorCollection`

### Declaration

```
// C#  
public sealed class OracleErrorCollection : ArrayList
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

A simple `ArrayList` that holds a list of `OracleErrors`.

If there are multiple errors, ODP.NET only returns the first error message on the stack.

### Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class OracleErrorCollectionSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Create an OracleCommand object using the connection object  
        OracleCommand cmd = con.CreateCommand();  
  
        try  
        {  
            cmd.CommandText = "insert into notable values (99, 'MyText')";  
            cmd.ExecuteNonQuery();  
        }  
        catch (OracleException ex)  
        {  
            Console.WriteLine("Record is not inserted into the database table.");  
  
            foreach (OracleError error in ex.Errors)  
            {  
                Console.WriteLine("Error Message: " + error.Message);  
                Console.WriteLine("Error Source: " + error.Source);  
            }  
        }  
    }  
}
```

```
    }  
  }  
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleErrorCollection Members](#)
- [OracleErrorCollection Static Methods](#)
- [OracleErrorCollection Properties](#)
- [OracleErrorCollection Public Methods](#)

## OracleErrorCollection Members

OracleErrorCollection members are listed in the following tables.

### OracleErrorCollection Static Methods

OracleErrorCollection static methods are listed in [Table 5-56](#).

**Table 5-56 OracleErrorCollection Static Methods**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleErrorCollection Properties

OracleErrorCollection properties are listed in [Table 5-57](#).

**Table 5-57 OracleErrorCollection Properties**

Property	Description
Capacity	Inherited from System.Collections.ArrayList
Count	Inherited from System.Collections.ArrayList
IsReadOnly	Inherited from System.Collections.ArrayList
IsSynchronized	Inherited from System.Collections.ArrayList
Item	Inherited from System.Collections.ArrayList

### OracleErrorCollection Public Methods

OracleErrorCollection public methods are listed in [Table 5-58](#).

**Table 5-58 OracleErrorCollection Public Methods**

Public Method	Description
CopyTo	Inherited from System.Collections.ArrayList
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleErrorCollection Class](#)

## OracleErrorCollection Static Methods

The `OracleErrorCollection` static method is listed in [Table 5-59](#).

**Table 5-59 OracleErrorCollection Static Method**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)



## OracleErrorCollection Properties

OracleErrorCollection properties are listed in [Table 5–60](#).

**Table 5–60 OracleErrorCollection Properties**

Property	Description
Capacity	Inherited from <code>System.Collections.ArrayList</code>
Count	Inherited from <code>System.Collections.ArrayList</code>
IsReadOnly	Inherited from <code>System.Collections.ArrayList</code>
IsSynchronized	Inherited from <code>System.Collections.ArrayList</code>
Item	Inherited from <code>System.Collections.ArrayList</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

## OracleErrorCollection Public Methods

OracleErrorCollection public methods are listed in [Table 5–61](#).

**Table 5–61 OracleErrorCollection Public Methods**

Public Method	Description
CopyTo	Inherited from <code>System.Collections.ArrayList</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
GetHashCode	Inherited from <code>System.Object</code>
GetType	Inherited from <code>System.Object</code>
ToString	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

---

## OracleException Class

The `OracleException` class represents an exception that is thrown when the Oracle Data Provider for .NET encounters an error. Each `OracleException` object contains at least one `OracleError` object in the `Error` property that describes the error or warning.

### Class Inheritance

```
System.Object
    System.Exception
        System.SystemException
            System.Runtime.InteropServices.ExternalException (ADO.NET
2.0 only)
                System.Data.Common.DbException (ADO.NET 2.0 only)
                    Oracle.DataAccess.Client.OracleException
```

### Declaration

```
// C#
public sealed class OracleException : SystemException
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

If there are multiple errors, ODP.NET only returns the first error message on the stack.

### Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleExceptionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
            cmd.ExecuteNonQuery();
        }
        catch (OracleException ex)
```

```
{
    Console.WriteLine("Record is not inserted into the database table.");
    Console.WriteLine("Exception Message: " + ex.Message);
    Console.WriteLine("Exception Source: " + ex.Source);
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleException Members](#)
- [OracleException Methods](#)
- [OracleException Static Methods](#)
- [OracleException Static Methods](#)
- [OracleException Properties](#)
- [OracleException Methods](#)

## OracleException Members

OracleException members are listed in the following tables.

### OracleException Static Methods

The OracleException static method is listed in [Table 5–62](#).

**Table 5–62 OracleException Static Method**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleException Properties

OracleException properties are listed in [Table 5–63](#).

**Table 5–63 OracleException Properties**

Property	Description
<a href="#">DataSource</a>	Specifies the TNS name that contains the information for connecting to an Oracle instance
<a href="#">Errors</a>	Specifies a collection of one or more OracleError objects that contain information about exceptions generated by the Oracle database
HelpLink	Inherited from System.Exception
InnerException	Inherited from System.Exception
<a href="#">Message</a>	Specifies the error messages that occur in the exception
<a href="#">Number</a>	Specifies the Oracle error number
<a href="#">Procedure</a>	Specifies the stored procedure that cause the exception
<a href="#">Source</a>	Specifies the name of the data provider that generates the error
StackTrace	Inherited from System.Exception
TargetSite	Inherited from System.Exception

### OracleException Methods

OracleException methods are listed in [Table 5–64](#).

**Table 5–64 OracleException Methods**

Method	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.Exception
GetHashCode	Inherited from System.Object
<a href="#">GetObjectData</a>	Sets the serializable info object with information about the exception
GetType	Inherited from System.Object
<a href="#">ToString</a>	Returns the fully qualified name of this exception

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleException Class](#)

## OracleException Static Methods

The `OracleException` static method is listed in [Table 5–65](#).

**Table 5–65** *OracleException Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

## OracleException Properties

OracleException properties are listed in [Table 5–66](#).

**Table 5–66 OracleException Properties**

Property	Description
<a href="#">DataSource</a>	Specifies the TNS name that contains the information for connecting to an Oracle instance
<a href="#">Errors</a>	Specifies a collection of one or more <code>OracleError</code> objects that contain information about exceptions generated by the Oracle database
<code>HelpLink</code>	Inherited from <code>System.Exception</code>
<code>InnerException</code>	Inherited from <code>System.Exception</code>
<a href="#">Message</a>	Specifies the error messages that occur in the exception
<a href="#">Number</a>	Specifies the Oracle error number
<a href="#">Procedure</a>	Specifies the stored procedure that cause the exception
<a href="#">Source</a>	Specifies the name of the data provider that generates the error
<code>StackTrace</code>	Inherited from <code>System.Exception</code>
<code>TargetSite</code>	Inherited from <code>System.Exception</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

### DataSource

This property specifies the TNS name that contains the information for connecting to an Oracle instance.

**Declaration**

```
// C#
public string DataSource {get;}
```

**Property Value**

The TNS name containing the connect information.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

### Errors

This property specifies a collection of one or more `OracleError` objects that contain information about exceptions generated by the Oracle database.



**Declaration**

```
// C#  
public OracleErrorCollection Errors {get;}
```

**Property Value**

An `OracleErrorCollection`.

**Remarks**

The `Errors` property contains at least one instance of `OracleError` objects.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

**Message**

Overrides `Exception`

This property specifies the error messages that occur in the exception.

**Declaration**

```
// C#  
public override string Message {get;}
```

**Property Value**

A `string`.

**Remarks**

`Message` is a concatenation of all errors in the `Errors` collection. Each error message is concatenated and is followed by a carriage return, except the last one.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

**Number**

This property specifies the Oracle error number.

**Declaration**

```
// C#  
public int Number {get;}
```

**Property Value**

The error number.

**Remarks**

This error number can be the topmost level of error generated by Oracle and can be a provider-specific error number.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

**Procedure**

This property specifies the stored procedure that caused the exception.

**Declaration**

```
// C#  
public string Procedure {get;}
```

**Property Value**

The stored procedure name.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

**Source**

Overrides `Exception`

This property specifies the name of the data provider that generates the error.

**Declaration**

```
// C#  
public override string Source {get;}
```

**Property Value**

The name of the data provider.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

## OracleException Methods

OracleException methods are listed in [Table 5–67](#).

**Table 5–67 OracleException Methods**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetBaseException</code>	Inherited from <code>System.Exception</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<a href="#">GetObjectData</a>	Sets the serializable <code>info</code> object with information about the exception
<code>GetType</code>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Returns the fully qualified name of this exception

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

## GetObjectData

Overrides `Exception`

This method sets the serializable `info` object with information about the exception.

### Declaration

```
// C#
public override void GetObjectData(SerializationInfo info, StreamingContext
    context);
```

### Parameters

- *info*  
A `SerializationInfo` object.
- *context*  
A `StreamingContext` object.

### Remarks

The information includes `DataSource`, `Message`, `Number`, `Procedure`, `Source`, and `StackTrace`.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleException Class](#)
- [OracleException Members](#)

## ToString

Overrides Exception

This method returns the fully qualified name of this exception, the `error` message in the `Message` property, the `InnerException.ToString()` message, and the stack trace.

### Declaration

```
// C#
public override string ToString();
```

### Return Value

The string representation of the exception.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class ToStringSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
            cmd.ExecuteNonQuery(); // This will throw an exception
        }
        catch (OracleException ex)
        {
            Console.WriteLine("Record is not inserted into the database table.");
            Console.WriteLine("ex.ToString() : " + ex.ToString());
        }
    }
}
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleException Class](#)
- [OracleException Members](#)

---

## OracleInfoMessageEventArgs Class

The `OracleInfoMessageEventArgs` class provides event data for the `OracleConnection.InfoMessage` event. When any warning occurs in the database, the `OracleConnection.InfoMessage` event is triggered along with the `OracleInfoMessageEventArgs` object that stores the event data.

### Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleInfoMessageEventArgs`

### Declaration

```
// C#
public sealed class OracleInfoMessageEventArgs
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class InfoMessageSample
{
    public static void WarningHandler(object src,
        OracleInfoMessageEventArgs args)
    {
        Console.WriteLine("Source object is: " + src.GetType().Name);
        Console.WriteLine("InfoMessageArgs.Message is " + args.Message);
        Console.WriteLine("InfoMessageArgs.Source is " + args.Source);
    }
    static void Main()
    {
        OracleConnection con = new OracleConnection("User Id=scott;" +
            "Password=tiger;Data Source=oracle;");

        con.Open();

        OracleCommand cmd = con.CreateCommand();

        //Register to the InfoMessageHandler
        cmd.Connection.InfoMessage +=
            new OracleInfoMessageEventHandler(WarningHandler);

        cmd.CommandText =
            "create or replace procedure SelectWithNoInto( " +
            " empname in VARCHAR2) AS " +
```

```
        "BEGIN " +
        " select * from emp where ename = empname; " +
        "END SelectWithNoInto;";

        // Execute the statement that produces a warning
        cmd.ExecuteNonQuery();

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleInfoMessageEventArgs Members](#)
- [OracleInfoMessageEventArgs Static Methods](#)
- [OracleInfoMessageEventArgs Properties](#)
- [OracleInfoMessageEventArgs Public Methods](#)
- ["OracleConnection Class" on page 5-64](#)

## OracleInfoMessageEventArgs Members

OracleInfoMessageEventArgs members are listed in the following tables.

### OracleInfoMessageEventArgs Static Methods

The OracleInfoMessageEventArgs static methods is listed in [Table 5-68](#).

**Table 5-68 OracleInfoMessageEventArgs Static Method**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleInfoMessageEventArgs Properties

The OracleInfoMessageEventArgs properties are listed in [Table 5-69](#).

**Table 5-69 OracleInfoMessageEventArgs Properties**

Property	Description
<a href="#">Errors</a>	Specifies the collection of errors generated by the data source
<a href="#">Message</a>	Specifies the error text generated by the data source
<a href="#">Source</a>	Specifies the name of the object that generated the error

### OracleInfoMessageEventArgs Public Methods

The OracleInfoMessageEventArgs methods are listed in [Table 5-70](#).

**Table 5-70 OracleInfoMessageEventArgs Public Methods**

Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleInfoMessageEventArgs Class](#)

## OracleInfoMessageEventArgs Static Methods

The `OracleInfoMessageEventArgs` static method is listed in [Table 5-71](#).

**Table 5-71 OracleInfoMessageEventArgs Static Method**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)



## OracleInfoMessageEventArgs Properties

The `OracleInfoMessageEventArgs` properties are listed in [Table 5-72](#).

**Table 5-72 OracleInfoMessageEventArgs Properties**

Property	Description
<a href="#">Errors</a>	Specifies the collection of errors generated by the data source
<a href="#">Message</a>	Specifies the error text generated by the data source
<a href="#">Source</a>	Specifies the name of the object that generated the error

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

### Errors

This property specifies the collection of errors generated by the data source.

**Declaration**

```
// C#
public OracleErrorCollection Errors {get;}
```

**Property Value**

The collection of errors.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

### Message

This property specifies the error text generated by the data source.

**Declaration**

```
// C#
public string Message {get;}
```

**Property Value**

The error text.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

## Source

This property specifies the name of the object that generated the error.

### Declaration

```
// C#  
public string Source {get;}
```

### Property Value

The object that generated the error.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

## OracleInfoMessageEventArgs Public Methods

The OracleInfoMessageEventArgs methods are listed in [Table 5–73](#).

**Table 5–73 OracleInfoMessageEventArgs Public Methods**

Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

## OracleInfoMessageEventHandler Delegate

The `OracleInfoMessageEventHandler` represents the signature of the method that handles the `OracleConnection.InfoMessage` event.

### Declaration

```
// C#  
public delegate void OracleInfoMessageEventHandler(object sender,  
    OracleInfoMessageEventArgs eventArgs);
```

### Parameters

- *sender*

The source of the event.

- *eventArgs*

The `OracleInfoMessageEventArgs` object that contains the event data.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["InfoMessage"](#) on page 5-113

---

## OracleParameter Class

An OracleParameter object represents a parameter for an OracleCommand or a DataSet column.

### Class Inheritance

System.Object

System.MarshalByRefObject

System.Data.Common.DbParameter (ADO.NET 2.0 only)

Oracle.DataAccess.Client.OracleParameter

### Declaration

```
// ADO.NET 2.0: C#
public sealed class OracleParameter : DbParameter, IDisposable, ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Exceptions

ArgumentException - The type binding is invalid.

### Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleParameterSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];

        // Create OracleParameter objects through OracleParameterCollection
        OracleCommand cmd = con.CreateCommand();

        cmd.CommandText = "select max(empno) from emp";
        int maxno = int.Parse(cmd.ExecuteScalar().ToString());

        prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
            maxno + 10, ParameterDirection.Input);
        prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
            "Client", ParameterDirection.Input);
        prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
            10, ParameterDirection.Input);
        cmd.CommandText =
```

```
        "insert into emp(empno, ename, deptno) values(:1, :2, :3)";
        cmd.ExecuteNonQuery();

        Console.WriteLine("Record for employee id {0} has been inserted.",
            maxno + 10);
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Members](#)
- [OracleParameter Constructors](#)
- [OracleParameter Static Methods](#)
- [OracleParameter Properties](#)
- [OracleParameter Public Methods](#)

## OracleParameter Members

OracleParameter members are listed in the following tables.

### OracleParameter Constructors

OracleParameter constructors are listed in [Table 5-74](#).

**Table 5-74 OracleParameter Constructors**

Constructor	Description
<a href="#">OracleParameter Constructors</a>	Instantiates a new instance of OracleParameter class (Overloaded)

### OracleParameter Static Methods

OracleParameter static methods are listed in [Table 5-75](#).

**Table 5-75 OracleParameter Static Methods**

Method	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleParameter Properties

OracleParameter properties are listed in [Table 5-76](#).

**Table 5-76 OracleParameter Properties**

Property	Description
<a href="#">ArrayBindSize</a>	Specifies the input or output size of elements in Value property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
<a href="#">ArrayBindStatus</a>	Specifies the input or output status of elements in Value property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
<a href="#">CollectionType</a>	Specifies whether or not the OracleParameter represents a collection, and if so, specifies the collection type
<a href="#">DbType</a>	Specifies the data type of the parameter using the Data.DbType enumeration type
<a href="#">Direction</a>	Specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter
<a href="#">IsNullable</a>	Not supported
<a href="#">Offset</a>	Specifies the offset to the Value property or offset to the elements in the Value property
<a href="#">OracleDbType</a>	Specifies the Oracle data type
<a href="#">OracleDbTypeEx</a>	Specifies the Oracle data type to bind the parameter as, but returns a .NET type as output
<a href="#">ParameterName</a>	Specifies the name of the parameter
<a href="#">Precision</a>	Specifies the maximum number of digits used to represent the Value property
<a href="#">Scale</a>	Specifies the number of decimal places to which Value property is resolved

**Table 5–76 (Cont.) OracleParameter Properties**

Property	Description
<a href="#">Size</a>	Specifies the maximum size, in bytes or characters, of the data transmitted to or from the database. For PL/SQL Associative Array Bind, <code>Size</code> specifies the maximum number of elements in PL/SQL Associative Array
<a href="#">SourceColumn</a>	Specifies the name of the <code>DataTable</code> Column of the <code>DataSet</code>
<a href="#">SourceColumnNull Mapping</a>	Specifies a value which indicates whether the source column is nullable <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">SourceVersion</a>	Specifies the <code>DataRowVersion</code> value to use when loading the <code>Value</code> property of the parameter
<a href="#">Status</a>	Indicates the status of the execution related to the data in the <code>Value</code> property
<a href="#">UdtTypeName</a>	Specifies the Oracle user-defined type name if the parameter is a user-defined data type
<a href="#">Value</a>	Specifies the value of the <code>Parameter</code>

### OracleParameter Public Methods

`OracleParameter` public methods are listed in [Table 5–77](#).

**Table 5–77 OracleParameter Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a shallow copy of an <code>OracleParameter</code> object
<code>CreateObjRef</code>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Dispose</a>	Releases allocated resources
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">ResetDbType</a>	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">ResetOracleDbType</a>	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<code>ToString</code>	Inherited from <code>System.Object</code> (Overloaded)

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)



## OracleParameter Constructors

OracleParameter constructors instantiate new instances of the OracleParameter class.

### Overload List:

- [OracleParameter\(\)](#)  
This constructor instantiates a new instance of OracleParameter class.
- [OracleParameter \(string, OracleDbType\)](#)  
This constructor instantiates a new instance of OracleParameter class using the supplied parameter name and Oracle data type.
- [OracleParameter\(string, object\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name and parameter value.
- [OracleParameter\(string, OracleDbType, ParameterDirection\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, and parameter direction.
- [OracleParameter\(string, OracleDbType, object, ParameterDirection\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, value, and direction.
- [OracleParameter\(string, OracleDbType, int\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, and size.
- [OracleParameter\(string, OracleDbType, int, string\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, and source column.
- [OracleParameter\(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, direction, null indicator, precision, scale, source column, source version and parameter value.
- [OracleParameter\(string, OracleDbType, int, object, ParameterDirection\)](#)  
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, value, and direction.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

### OracleParameter()

This constructor instantiates a new instance of OracleParameter class.

**Declaration**

```
// C#  
public OracleParameter();
```

**Remarks****Default Values:**

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration" on page 5-360](#)
- ["OracleParameterCollection Class" on page 5-282](#)

**OracleParameter (string, OracleDbType)**

This constructor instantiates a new instance of `OracleParameter` class using the supplied parameter name and Oracle data type.

**Declaration**

```
// C#  
public OracleParameter(string parameterName, OracleDbType oraType);
```

**Parameters**

- *parameterName*  
The parameter name.
- *oraType*  
The data type of the `OracleParameter`.

**Remarks**

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["OracleParameterCollection Class"](#) on page 5-282

**OracleParameter(string, object)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name and parameter value.

**Declaration**

```
// C#  
public OracleParameter(string parameterName, object obj);
```

**Parameters**

- *parameterName*  
The parameter name.
- *obj*  
The value of the `OracleParameter`.

**Remarks**

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- DbType - String

- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["OracleParameterCollection Class"](#) on page 5-282

**OracleParameter(string, OracleDbType, ParameterDirection)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and parameter direction.

**Declaration**

```
// C#  
public OracleParameter(string parameterName, OracleDbType type,  
    ParameterDirection direction);
```

**Parameters**

- `parameterName`  
The parameter name.
- `type`  
The data type of the `OracleParameter`.
- `direction`  
The direction of the `OracleParameter`.

**Remarks**

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- `DbType` - String
- `ParameterDirection` - Input

- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["OracleParameterCollection Class"](#) on page 5-282

**OracleParameter(string, OracleDbType, object, ParameterDirection)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, value, and direction.

**Declaration**

```
// C#  
public OracleParameter(string parameterName, OracleDbType type, object obj,  
    ParameterDirection direction);
```

**Parameters**

- *parameterName*  
The parameter name.
- *type*  
The data type of the `OracleParameter`.
- *obj*  
The value of the `OracleParameter`.
- *direction*  
The `ParameterDirection` value.

**Remarks**

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["OracleParameterCollection Class"](#) on page 5-282

**OracleParameter(string, OracleDbType, int)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and size.

**Declaration**

```
// C#  
public OracleParameter(string parameterName, OracleDbType type,  
    int size);
```

**Parameters**

- *parameterName*  
The parameter name.
- *type*  
The data type of the `OracleParameter`.
- *size*  
The size of the `OracleParameter` value.

**Remarks**

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- DbType - String

- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["OracleParameterCollection Class"](#) on page 5-282

**OracleParameter(string, OracleDbType, int, string)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, and source column.

**Declaration**

```
// C#
public OracleParameter(string parameterName, OracleDbType type, int size,
    string srcColumn);
```

**Parameters**

- *parameterName*  
The parameter name.
- *type*  
The data type of the `OracleParameter`.
- *size*  
The size of the `OracleParameter` value.
- *srcColumn*  
The name of the source column.

**Remarks**

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360

**OracleParameter(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, direction, null indicator, precision, scale, source column, source version and parameter value.

**Declaration**

```
// C#
public OracleParameter(string parameterName, OracleDbType oraType,
    int size, ParameterDirection direction, bool isNullable, byte
    precision, byte scale, string srcColumn, DataRowVersion srcVersion,
    object obj);
```

**Parameters**

- *parameterName*  
The parameter name.
- *oraType*  
The data type of the `OracleParameter`.
- *size*  
The size of the `OracleParameter` value.
- *direction*  
The `ParameterDirection` value.



- *isNullable*  
An indicator that specifies if the parameter value can be null.
- *precision*  
The precision of the parameter value.
- *scale*  
The scale of the parameter value.
- *srcColumn*  
The name of the source column.
- *srcVersion*  
The DataRowVersion value.
- *obj*  
The parameter value.

### Exceptions

*ArgumentException* - The supplied value does not belong to the type of *Value* property in any of the *OracleTypes*.

### Remarks

Unless explicitly set in the constructor, all the properties have the default values.

### Default Values:

- *DbType* - String
- *ParameterDirection* - Input
- *isNullable* - true
- *offset* - 0
- *OracleDbType* - Varchar2
- *ParameterAlias* - Empty string
- *ParameterName* - Empty string
- *Precision* - 0
- *Size* - 0
- *SourceColumn* - Empty string
- *SourceVersion* - Current
- *ArrayBindStatus* - Success
- *Value* - null

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360

**OracleParameter(string, OracleDbType, int, object, ParameterDirection)**

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, value, and direction.

**Declaration**

```
// C#  
public OracleParameter(string parameterName, OracleDbType type, int size,  
    object obj, ParameterDirection direction);
```

**Parameters**

- *parameterName*  
The parameter name.
- *type*  
The data type of the `OracleParameter`.
- *size*  
The size of the `OracleParameter` value.
- *obj*  
The value of the `OracleParameter`.
- *direction*  
The `ParameterDirection` value.

**Remarks**

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

**Default Values:**

- `DbType` - `String`
- `ParameterDirection` - `Input`
- `isNullable` - `true`
- `offset` - `0`
- `OracleDbType` - `Varchar2`
- `ParameterAlias` - `Empty string`
- `ParameterName` - `Empty string`
- `Precision` - `0`
- `Size` - `0`
- `SourceColumn` - `Empty string`
- `SourceVersion` - `Current`
- `ArrayBindStatus` - `Success`
- `Value` - `null`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["OracleParameterCollection Class"](#) on page 5-282

## OracleParameter Static Methods

The `OracleParameter` static method is listed in [Table 5-78](#).

**Table 5-78 OracleParameter Static Method**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## OracleParameter Properties

OracleParameter properties are listed in [Table 5–79](#).

**Table 5–79 OracleParameter Properties**

Property	Description
<a href="#">ArrayBindSize</a>	Specifies the input or output size of elements in <code>Value</code> property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
<a href="#">ArrayBindStatus</a>	Specifies the input or output status of elements in <code>Value</code> property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
<a href="#">CollectionType</a>	Specifies whether or not the <code>OracleParameter</code> represents a collection, and if so, specifies the collection type
<a href="#">DbType</a>	Specifies the data type of the parameter using the <code>Data.DbType</code> enumeration type
<a href="#">Direction</a>	Specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter
<a href="#">IsNullable</a>	Not supported
<a href="#">Offset</a>	Specifies the offset to the <code>Value</code> property or offset to the elements in the <code>Value</code> property
<a href="#">OracleDbType</a>	Specifies the Oracle data type
<a href="#">OracleDbTypeEx</a>	Specifies the Oracle data type to bind the parameter as, but returns a .NET type as output
<a href="#">ParameterName</a>	Specifies the name of the parameter
<a href="#">Precision</a>	Specifies the maximum number of digits used to represent the <code>Value</code> property
<a href="#">Scale</a>	Specifies the number of decimal places to which <code>Value</code> property is resolved
<a href="#">Size</a>	Specifies the maximum size, in bytes or characters, of the data transmitted to or from the database. For PL/SQL Associative Array Bind, <code>Size</code> specifies the maximum number of elements in PL/SQL Associative Array
<a href="#">SourceColumn</a>	Specifies the name of the <code>DataTable Column</code> of the <code>DataSet</code>
<a href="#">SourceColumnNull Mapping</a>	Specifies a value which indicates whether the source column is nullable <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">SourceVersion</a>	Specifies the <code>DataRowVersion</code> value to use when loading the <code>Value</code> property of the parameter
<a href="#">Status</a>	Indicates the status of the execution related to the data in the <code>Value</code> property
<a href="#">UdtTypeName</a>	Specifies the Oracle user-defined type name if the parameter is a user-defined data type
<a href="#">Value</a>	Specifies the value of the <code>Parameter</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## ArrayBindSize

This property specifies the maximum size, in bytes or characters, of the data for each array element transmitted to or from the database. This property is used for Array Bind or PL/SQL Associative Array execution.

**Declaration**

```
// C#  
public int[] ArrayBindSize {get; set; }
```

**Property Value**

An array of `int` values specifying the size.

**Remarks**

Default = `null`.

This property is only used for variable size element types for an Array Bind or PL/SQL Associative Array. For fixed size element types, this property is ignored.

Each element in the `ArrayBindSize` corresponds to the bind size of an element in the `Value` property. Before execution, `ArrayBindSize` specifies the maximum size of each element to be bound in the `Value` property. After execution, it contains the size of each element returned in the `Value` property.

For binding a PL/SQL Associative Array, whose elements are of a variable-length element type, as an `InputOutput`, `Out`, or `ReturnValue` parameter, this property must be set properly. The number of elements in `ArrayBindSize` must be equal to the value specified in the `OracleParameter.Size` property.

**Example**

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class ArrayBindSizeSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleParameter[] prm = new OracleParameter[3];  
  
        // Create OracleParameter objects through OracleParameterCollection  
        OracleCommand cmd = con.CreateCommand();  
  
        cmd.CommandText = "select max(empno) from emp";  
        int maxno = int.Parse(cmd.ExecuteScalar().ToString());  
    }  
}
```

```

// Set the ArrayBindCount for Array Binding
cmd.ArrayBindCount = 2;

prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
    new int[2] {maxno + 10, maxno + 11}, ParameterDirection.Input);
prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
    new string[2] {"Client1xxx", "Client2xxx"}, ParameterDirection.Input);
prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
    new int[2] {10, 10}, ParameterDirection.Input);

// Set the ArrayBindSize for prm[1]
// These sizes indicate the maximum size of the elements in Value property
prm[1].ArrayBindSize = new int[2];
prm[1].ArrayBindSize[0] = 7; // Set ename = "Client1"
prm[1].ArrayBindSize[1] = 7; // Set ename = "Client2"

cmd.CommandText =
    "insert into emp(empno, ename, deptno) values(:1, :2, :3)";

cmd.ExecuteNonQuery();

Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 10);
Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 11);

prm[0].Dispose();
prm[1].Dispose();
prm[2].Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount"](#) on page 5-13
- ["Size"](#) on page 5-272 and ["Value"](#) on page 5-276 for more information on binding Associative Arrays
- ["ArrayBindStatus"](#) on page 5-265

**ArrayBindStatus**

This property specifies the input or output status of each element in the Value property before or after an Array Bind or PL/SQL Associative Array execution.

**Declaration**

```

// C#
public OracleParameterStatus[] ArrayBindStatus { get; set; }

```

**Property Value**

An array of `OracleParameterStatus` enumerated values.

**Exceptions**

`ArgumentOutOfRangeException` - The Status value specified is invalid.

**Remarks**

Default = `null`.

`ArrayBindStatus` is used for Array Bind and PL/SQL Associative Array execution only.

Before execution, `ArrayBindStatus` indicates the bind status of each element in the Value property. After execution, it contains the execution status of each element in the Value property.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount"](#) on page 5-13
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["Value"](#) on page 5-276 for more information on binding Associative Arrays
- ["ArrayBindSize"](#) on page 5-264

**CollectionType**

This property specifies whether or not the `OracleParameter` represents a collection, and if so, specifies the collection type.

**Declaration**

```
// C#  
public OracleCollectionType CollectionType { get; set; }
```

**Property Value**

An `OracleCollectionType` enumerated value.

**Exceptions**

`ArgumentException` - The `OracleCollectionType` value specified is invalid.

**Remarks**

Default = `OracleCollectionType.None`. If `OracleParameter` is used to bind a PL/SQL Associative Array, then `CollectionType` must be set to `OracleCollectionType.PLSQLAssociativeArray`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)



## DbType

This property specifies the data type of the parameter using the `Data.DbType` enumeration type.

### Declaration

```
// ADO.NET 2.0: C#  
public override DbType DbType {get; set; }
```

### Property Value

A `DbType` enumerated value.

### Implements

`IDataParameter`

### Exceptions

`ArgumentException` - The `DbType` value specified is invalid.

### Remarks

Default = `DbType.String`

`DbType` is the data type of each element in the array if the `OracleParameter` object is used for `Array Bind` or `PL/SQL Associative Array Bind` execution.

Due to the link between `DbType` and `OracleDbType` properties, if the `DbType` property is set, the `OracleDbType` property is inferred from `DbType`.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Inference of OracleDbType from DbType"](#) on page 3-34
- ["CollectionType"](#) on page 5-266

## Direction

This property specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter.

### Declaration

```
// ADO.NET 2.0: C#  
public override ParameterDirection Direction { get; set; }
```

### Property Value

A `ParameterDirection` enumerated value.

### Implements

`IDataParameter`

### Exceptions

`ArgumentOutOfRangeException` - The `ParameterDirection` value specified is invalid.

**Remarks**

Default = `ParameterDirection.Input`

Possible values: `Input`, `InputOutput`, `Output`, and `ReturnValue`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**IsNullable**

This property is not supported.

**Declaration**

```
// ADO.NET 2.0: C#  
public override bool IsNullable { get; set; }
```

**Implements**

`IDataParameter`

**Property Value**

This property is not supported.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**Offset**

This property specifies the offset to the `Value` property.

**Declaration**

```
// C#  
public int Offset { get; set; }
```

**Property Value**

An `int` that specifies the offset.

**Exceptions**

`ArgumentOutOfRangeException` - The `Offset` value specified is invalid.

**Remarks**

Default = 0

For `Array Bind` and `PL/SQL Associative Array Bind`, `Offset` applies to every element in the `Value` property.

The `Offset` property is used for binary and string data types. The `Offset` property represents the number of bytes for binary types and the number of characters for strings. The count for strings does not include the terminating character if a null is referenced. The `Offset` property is used by parameters of the following types:

- `OracleDbType.BFile`
- `OracleDbType.Blob`
- `OracleDbType.LongRaw`
- `OracleDbType.Raw`
- `OracleDbType.Char`
- `OracleDbType.Clob`
- `OracleDbType.NClob`
- `OracleDbType.NChar`
- `OracleDbType.NVarchar2`
- `OracleDbType.Varchar2`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**OracleDbType**

This property specifies the Oracle data type.

**Declaration**

```
// C#
public OracleDbType OracleDbType { get; set; }
```

**Property Value**

An `OracleDbType` enumerated value.

**Remarks**

Default = `OracleDbType.Varchar2`

If the `OracleParameter` object is used for Array Bind or PL/SQL Associative Array Bind execution, `OracleDbType` is the data type of each element in the array.

The `OracleDbType` property and `DbType` property are linked. Therefore, setting the `OracleDbType` property changes the `DbType` property to a supporting `DbType`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#) on page 5-358
- ["Inference of DbType from OracleDbType"](#) on page 3-33
- ["CollectionType"](#) on page 5-266

**OracleDbTypeEx**

This property specifies the Oracle data type to bind the parameter as, but returns a .NET type as output.

**Declaration**

```
// C#  
public OracleDbType OracleDbTypeEx { get; set; }
```

**Property Value**

An `OracleDbType` enumerated value.

**Remarks**

This property is used by applications that need to bind a parameter value as an Oracle type, but need a .NET type back for output. This property should be used with an output or input/output parameter. For an input parameter, using `OracleDbTypeEx` has the same affect as using `OracleDbType`. The .NET type that is returned for the output is the .NET type that the Oracle type closely maps to.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#) on page 5-358
- ["OracleDbType"](#) on page 5-269
- ["Inference of DbType from OracleDbType"](#) on page 3-33
- ["CollectionType"](#) on page 5-266

**ParameterName**

This property specifies the name of the parameter.

**Declaration**

```
// ADO.NET 2.0: C#  
public override string ParameterName { get; set; }
```

**Property Value**

String

**Implements**

`IDataParameter`

**Remarks**

Default = null

Oracle supports `ParameterName` up to 30 characters.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## Precision

This property specifies the maximum number of digits used to represent the `Value` property.

### Declaration

```
// C#  
public byte Precision { get; set; }
```

### Property Value

byte

### Remarks

Default = 0

The `Precision` property is used by parameters of type `OracleDbType.Decimal`.

Oracle supports `Precision` range from 0 to 38.

For `Array Bind` and `PL/SQL Associative Array Bind`, `Precision` applies to each element in the `Value` property.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Value" on page 5-276](#)

## Scale

This property specifies the number of decimal places to which `Value` property is resolved.

### Declaration

```
// C#  
public byte Scale { get; set; }
```

### Property Value

byte

### Remarks

Default = 0.

`Scale` is used by parameters of type `OracleDbType.Decimal`.

Oracle supports `Scale` between -84 and 127.

For `Array Bind` and `PL/SQL Associative Array Bind`, `Scale` applies to each element in the `Value` property.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Value"](#) on page 5-276

**Size**

This property specifies the maximum size, in bytes or characters, of the data transmitted to or from the database.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int Size { get; set;}
```

**Property Value**

int

**Exceptions**

*ArgumentOutOfRangeException* - The *Size* value specified is invalid.

*InvalidOperationException* - The *Size* = 0 when the *OracleParameter* object is used to bind a PL/SQL Associative Array.

**Remarks**

For PL/SQL Associative Array Bind, *Size* specifies the maximum number of elements in PL/SQL Associative Array.

If *Size* is not explicitly set, it is inferred from the actual size of the specified parameter value when binding only for input parameters. Output parameters must have their size defined explicitly.

The default value is 0.

Before execution, this property specifies the maximum size to be bound in the *Value* property. After execution, it contains the size of the type in the *Value* property.

*Size* is used for parameters of the following types:

- *OracleDbType.Blob*
- *OracleDbType.Char*
- *OracleDbType.Clob*
- *OracleDbType.LongRaw*
- *OracleDbType.NChar*
- *OracleDbType.NClob*
- *OracleDbType.NVarchar2*
- *OracleDbType.Raw*
- *OracleDbType.Varchar2*

The value of *Size* is handled as follows:

- Fixed length data types: ignored

- Variable length data types: describes the maximum amount of data transmitted to or from the database. For character data, *Size* is in number of characters and for binary data, it is in number of bytes.

If the *Size* is not explicitly set, it is inferred from the actual size of the specified parameter value when binding.

---



---

**Note:** *Size* does not include the null terminating character for the string data.

---



---

If the `OracleParameter` object is used to bind a PL/SQL Associative Array, *Size* specifies the maximum number of elements in the PL/SQL Associative Array. Before the execution, this property specifies the maximum number of elements in the PL/SQL Associative Array. After the execution, it specifies the current number of elements returned in the PL/SQL Associative Array. For `Output` and `InputOutput` parameters and return values, *Size* specifies the maximum number of elements in the PL/SQL Associative Array.

ODP.NET does not support binding an empty PL/SQL Associative Array. Therefore, *Size* cannot be set to 0 when the `OracleParameter` object is used to bind a PL/SQL Associative Array.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#) on page 5-358
- ["CollectionType"](#) on page 5-266
- ["ArrayBindSize"](#) on page 5-264
- ["ArrayBindStatus"](#) on page 5-265
- ["Value"](#) on page 5-276

## SourceColumn

This property specifies the name of the `DataTable` Column of the `DataSet`.

**Declaration**

```
// ADO.NET 2.0: C#
public override string SourceColumn { get; set; }
```

**Property Value**

A string.

**Implements**

`IDataParameter`

**Remarks**

Default = empty string

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**SourceColumnNullMapping**

This property specifies a value which indicates whether the source column is nullable.

**Declaration**

```
// ADO.NET 2.0: C#  
public bool SourceColumnNullMapping { get; set; }
```

**Property Value**

Returns `true` if the source column can be nullified; otherwise, returns `false`.

**Remarks**

The default value is `false`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**SourceVersion**

This property specifies the `DataRowVersion` value to use when loading the `Value` property of the parameter.

**Declaration**

```
// ADO.NET 2.0: C#  
public override DataRowVersion SourceVersion { get; set; }
```

**Property Value**

`DataRowVersion`

**Implements**

`IDataParameter`

**Exceptions**

`ArgumentOutOfRangeException` - The `DataRowVersion` value specified is invalid.

**Remarks**

Default = `DataRowVersion.Current`

`SourceVersion` is used by the `OracleDataAdapter.UpdateCommand()` during the `OracleDataAdapter.Update` to determine whether the original or current value is used for a parameter value. This allows primary keys to be updated. This



property is ignored by the `OracleDataAdapter.InsertCommand()` and the `OracleDataAdapter.DeleteCommand()`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## Status

This property indicates the status of the execution related to the data in the `Value` property.

**Declaration**

```
// C#  
public OracleParameterStatus Status { get; set; }
```

**Property Value**

An `OracleParameterStatus` enumerated value.

**Exceptions**

`ArgumentOutOfRangeException` - The `Status` value specified is invalid.

**Remarks**

Default = `OracleParameterStatus.Success`

Before execution, this property indicates the bind status related to the `Value` property. After execution, it returns the status of the execution.

`Status` indicates if:

- A `NULL` is fetched from a column.
- Truncation has occurred during the fetch; then `Value` was not big enough to hold the data.
- A `NULL` is to be inserted into a database column; then `Value` is ignored, and a `NULL` is inserted into a database column.

This property is ignored for `Array Bind` and `PL/SQL Associative Array Bind`. Instead, `ArrayBindStatus` property is used.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 5-360
- ["ArrayBindStatus"](#) on page 5-265

## UdtTypeName

This property specifies the Oracle user-defined type name if the parameter is a user-defined data type.

**Declaration**

```
// C#  
public string UdtTypeName {get; set;}
```

**Property Value**

Name of the Oracle UDT.

**Remarks**

The `UdtTypeName` property corresponds to the user-defined type name of the parameter. This property must always be specified if the parameter is a user-defined type.

Note that when a custom object is provided as an input parameter value, it is converted to the Oracle UDT that is specified by the custom type mapping on the connection used to execute the command.

The Oracle UDT specified by the custom type mapping and by the `OracleParameter.UdtTypeName` property differs if the application binds a custom object that represents a subtype of the parameter type.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**Value**

This property specifies the value of the Parameter.

**Declaration**

```
// ADO.NET 2.0: C#  
public override object Value { get; set; }
```

**Property Value**

An object.

**Implements**

`IDataParameter`

**Exceptions**

`ArgumentException` - The Value property specified is invalid.

`InvalidArgumentException`- The Value property specified is invalid.

**Remarks**

Default = null

If the `OracleParameter` object is used for Array Bind or PL/SQL Associative Array, Value is an array of parameter values.

The Value property can be overwritten by `OracleDataAdapter.Update()`.

The provider attempts to convert any type of value if it supports the `IConvertible` interface. Conversion errors occur if the specified type is not compatible with the value.

When sending a null parameter value to the database, the user must specify `DBNull`, not `null`. The null value in the system is an empty object that has no value. `DBNull` is used to represent null values. The user can also specify a null value by setting `Status` to `OracleParameterStatus.NullValue`. In this case, the provider sends a null value to the database.

If neither `OracleDbType` nor `DbType` are set, their values can be inferred by `Value`. Please see the following for related information:

- Tables in section ["Inference of DbType and OracleDbType from Value"](#) on page 3-34
- ["ArrayBindCount"](#) on page 5-13
- ["ArrayBindSize"](#) on page 5-264
- ["ArrayBindStatus"](#) on page 5-265
- ["OracleDbType Enumeration"](#) on page 5-358

For input parameters the value is:

- Bound to the `OracleCommand` that is sent to the database.
- Converted to the data type specified in `OracleDbType` or `DbType` when the provider sends the data to the database.

For output parameters the value is:

- Set on completion of the `OracleCommand` (true for return value parameters also).
- Set to the data from the database, to the data type specified in `OracleDbType` or `DbType`.

When array binding is used with:

- Input parameter - `Value` should be set to an array of values. `OracleCommand.ArrayBindCount` should be set to a value that is greater than zero to indicate the number of elements to be bound.

The number of elements in the array should be equal to the `OracleCommand.ArrayBindCount` property; otherwise, their minimum value is used to bind the elements in the array.

- Output parameter - `OracleCommand.ArrayBindCount` should be set to a value that is greater than zero to indicate the number of elements to be retrieved (for `SELECT` statements).

When PL/SQL Associative Array binding is used with:

- Input parameter – `Value` should be set to an array of values. `CollectionType` should be set to `OracleCollection.PLSQLAssociativeArray`. `Size` should be set to specify the possible maximum number of array elements in the PL/SQL Associative Array. If `Size` is smaller than the number of elements in `Value`, then `Size` specifies the number of elements in the `Value` property to be bound.
- Output parameter - `CollectionType` should be set to `OracleCollection.PLSQLAssociativeArray`. `Size` should be set to specify the maximum number of array elements in PL/SQL Associative Array.

Each parameter should have a value. To bind a parameter with a null value, set `Value` to `DBNull.Value`, or set `Status` to `OracleParameterStatus.NullInsert`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount"](#) on page 5-13
- ["OracleParameterStatus Enumeration"](#) on page 5-360

## OracleParameter Public Methods

OracleParameter public methods are listed in [Table 5–80](#).

**Table 5–80 OracleParameter Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a shallow copy of an OracleParameter object
CreateObjRef	Inherited from System.MarshalByRefObject
<a href="#">Dispose</a>	Releases allocated resources
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
<a href="#">ResetDbType</a>	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">ResetOracleDbType</a>	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
ToString	Inherited from System.Object (Overloaded)

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## Clone

This method creates a shallow copy of an OracleParameter object.

### Declaration

```
// C#
public object Clone();
```

### Return Value

An OracleParameter object.

### Implements

ICloneable

### Remarks

The cloned object has the same property values as that of the object being cloned.

**Example**

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CloneSample
{
    static void Main()
    {
        OracleParameter prm1 = new OracleParameter();

        // Prints "prm1.ParameterName = "
        Console.WriteLine("prm1.ParameterName = " + prm1.ParameterName);

        // Set the ParameterName before cloning
        prm1.ParameterName = "MyParam";

        // Clone the OracleParameter
        OracleParameter prm2 = (OracleParameter) prm1.Clone();

        // Prints "prm2.ParameterName = MyParam"
        Console.WriteLine("prm2.ParameterName = " + prm2.ParameterName);

        prm1.Dispose();
        prm2.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

**Dispose**

This method releases resources allocated for an `OracleParameter` object.

**Declaration**

```
// C#
public void Dispose();
```

**Implements**

`IDisposable`

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## ResetDbType

This method resets the type associated with the parameter so that it can infer its type from the value passed in the parameter.

### Declaration

```
// ADO.NET 2.0: C#  
public override void ResetDbType();
```

### Remarks

If an application does not set the `DbType` or `OracleDbType` properties of an `OracleParameter` object, then these values are inferred from the value set by the application to that `OracleParameter` object. Calling `ResetDbType` method resets these properties so that `OracleParameter` can again infer its type from the value passed into the `OracleParameter`. Calling this method affects both the `DbType` and `OracleDbType` properties of the `OracleParameter` object.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## ResetOracleDbType

This method resets the type associated with the parameter so that it can infer its type from the value passed in the parameter.

### Declaration

```
// ADO.NET 2.0: C#  
public override void ResetOracleDbType();
```

### Remarks

If an application does not set the `DbType` or `OracleDbType` properties of an `OracleParameter` object, then these values are inferred from the value set by the application to that `OracleParameter` object. Calling the `ResetOracleDbType` method resets these properties so that `OracleParameter` can again infer its type from the value passed into the `OracleParameter`. Calling this method affects both the `DbType` and `OracleDbType` properties of the `OracleParameter` object.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

## OracleParameterCollection Class

An `OracleParameterCollection` class represents a collection of all parameters relevant to an `OracleCommand` object and their mappings to `DataSet` columns.

### Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.Data.Common.DbParameterCollection` (ADO.NET 2.0 only)

`Oracle.DataAccess.Client.OracleParameterCollection`

### Declaration

```
// ADO.NET 2.0: C#
public sealed class OracleParameterCollection : DbParameterCollection,
    IDataParameterCollection, IList, ICollection, IEnumerable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

The position of an `OracleParameter` added into the `OracleParameterCollection` is the binding position in the SQL statement. Position is 0-based and is used only for positional binding. If named binding is used, the position of an `OracleParameter` in the `OracleParameterCollection` is ignored.

### Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleParameterCollectionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];

        // Create OracleParameter objects through OracleParameterCollection
        OracleCommand cmd = con.CreateCommand();

        cmd.CommandText = "select max(empno) from emp";
        int maxno = int.Parse(cmd.ExecuteScalar().ToString());

        prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
            maxno + 10, ParameterDirection.Input);
        prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
```



```
        "Client", ParameterDirection.Input);
prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
    10, ParameterDirection.Input);
cmd.CommandText =
    "insert into emp(empno, ename, deptno) values(:1, :2, :3)";
cmd.ExecuteNonQuery();

Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 10);

// Remove all parameters from OracleParameterCollection
cmd.Parameters.Clear();

prm[0].Dispose();
prm[1].Dispose();
prm[2].Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Members](#)
- [OracleParameterCollection Static Methods](#)
- [OracleParameterCollection Properties](#)
- [OracleParameterCollection Public Methods](#)

## OracleParameterCollection Members

OracleParameterCollection members are listed in the following tables.

### OracleParameterCollection Static Methods

OracleParameterCollection static methods are listed in [Table 5–81](#).

**Table 5–81 OracleParameterCollection Static Methods**

Method	Description
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)

### OracleParameterCollection Properties

OracleParameterCollection properties are listed in [Table 5–82](#).

**Table 5–82 OracleParameterCollection Properties**

Property	Description
<a href="#">Count</a>	Specifies the number of <code>OracleParameters</code> in the collection
<a href="#">Item</a>	Gets and sets the <code>OracleParameter</code> object (Overloaded)

### OracleParameterCollection Public Methods

OracleParameterCollection public methods are listed in [Table 5–83](#).

**Table 5–83 OracleParameterCollection Public Methods**

Public Method	Description
<a href="#">Add</a>	Adds objects to the collection (Overloaded)
<a href="#">AddRange</a>	Adds elements to the end of the <code>OracleParameterCollection</code> <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">Clear</a>	Removes all the <code>OracleParameter</code> objects from the collection
<a href="#">Contains</a>	Indicates whether or not objects exist in the collection (Overloaded)
<a href="#">CopyTo</a>	Copies <code>OracleParameter</code> objects from the collection, starting with the supplied index to the supplied array
<code>CreateObjRef</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">IndexOf</a>	Returns the index of the objects in the collection (Overloaded)

**Table 5–83 (Cont.) OracleParameterCollection Public Methods**

Public Method	Description
<a href="#">Insert</a>	Inserts the supplied <code>OracleParameter</code> to the collection at the specified <code>index</code>
<a href="#">Remove</a>	Removes objects from the collection
<a href="#">RemoveAt</a>	Removes objects from the collection by location (Overloaded)
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)

## OracleParameterCollection Static Methods

The `OracleParameterCollection` static method is listed in [Table 5–84](#).

**Table 5–84 OracleParameterCollection Static Method**

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## OracleParameterCollection Properties

OracleParameterCollection properties are listed in [Table 5–85](#).

**Table 5–85 OracleParameterCollection Properties**

Property	Description
<a href="#">Count</a>	Specifies the number of OracleParameters in the collection
<a href="#">Item</a>	Gets and sets the OracleParameter object (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

### Count

This property specifies the number of OracleParameter objects in the collection.

**Declaration**

```
// ADO.NET 2.0: C#
public override int Count {get;}
```

**Property Value**

The number of OracleParameter objects.

**Implements**

ICollection

**Remarks**

Default = 0

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

### Item

Item gets and sets the OracleParameter object.

**Overload List:**

- [Item\[int\]](#)  
This property gets and sets the OracleParameter object at the index specified by the supplied parameterIndex.
- [Item\[string\]](#)  
This property gets and sets the OracleParameter object using the parameter name specified by the supplied parameterName.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Item[int]**

This property gets and sets the `OracleParameter` object at the index specified by the supplied `parameterIndex`.

**Declaration**

```
// C#  
public object Item[int parameterIndex] {get; set;}
```

**Property Value**

An object.

**Implements**

`IList`

**Exceptions**

`IndexOutOfRangeException` - The supplied index does not exist.

**Remarks**

The `OracleParameterCollection` class is a zero-based index.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Item[string]**

This property gets and sets the `OracleParameter` object using the parameter name specified by the supplied `parameterName`.

**Declaration**

```
// C#  
public OracleParameter Item[string parameterName] {get; set;};
```

**Property Value**

An `OracleParameter`.

**Implements**

`IDataParameterCollection`

**Exceptions**

`IndexOutOfRangeException` - The supplied parameter name does not exist.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## OracleParameterCollection Public Methods

OracleParameterCollection public methods are listed in [Table 5–86](#).

**Table 5–86 OracleParameterCollection Public Methods**

Public Method	Description
<a href="#">Add</a>	Adds objects to the collection (Overloaded)
<a href="#">AddRange</a>	Adds elements to the end of the OracleParameterCollection <i>Supported Only in ADO.NET 2.0-Compliant ODP.NET</i>
<a href="#">Clear</a>	Removes all the OracleParameter objects from the collection
<a href="#">Contains</a>	Indicates whether or not objects exist in the collection (Overloaded)
<a href="#">CopyTo</a>	Copies OracleParameter objects from the collection, starting with the supplied index to the supplied array
CreateObjRef	Inherited from System.MarshalByRefObject
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
<a href="#">IndexOf</a>	Returns the index of the objects in the collection (Overloaded)
<a href="#">Insert</a>	Inserts the supplied OracleParameter to the collection at the specified index
<a href="#">Remove</a>	Removes objects from the collection
<a href="#">RemoveAt</a>	Removes objects from the collection by location (Overloaded)
Tostring	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

### Add

Add adds objects to the collection.

**Overload List:**

- [Add\(object\)](#)  
This method adds the supplied object to the collection.
- [Add\(OracleParameter\)](#)



This method adds the supplied `OracleParameter` object to the collection.

- [Add\(string, object\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name and object value.

- [Add\(string, OracleDbType\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name and database type.

- [Add\(string, OracleDbType, ParameterDirection\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and direction.

- [Add\(string, OracleDbType, object, ParameterDirection\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, parameter value, and direction.

- [Add\(string, OracleDbType, int, object, ParameterDirection\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, parameter value, and direction.

- [Add\(string, OracleDbType, int\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and size.

- [Add\(string, OracleDbType, int, string\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, and source column.

- [Add\(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, direction, null indicator, precision, scale, source column, source version, and parameter value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## Add(object)

This method adds the supplied object to the collection.

**Declaration**

```
// ADO.NET 2.0: C#
public override int Add(object obj);
```

**Parameters**

- *obj*

The supplied object.

**Return Value**

The index at which the new `OracleParameter` is added.

**Implements**

`IList`

**Remarks**

`InvalidCastException` - The supplied `obj` cannot be cast to an `OracleParameter` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Add(OracleParameter)**

This method adds the supplied `OracleParameter` object to the collection.

**Declaration**

```
// C#  
public OracleParameter Add(OracleParameter paramObj);
```

**Parameters**

- `paramObj`  
The supplied `OracleParameter` object.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Add(string, object)**

This method adds an `OracleParameter` object to the collection using the supplied name and object value

**Declaration**

```
// C#  
public OracleParameter Add(string name, object val);
```

**Parameters**

- `name`  
The parameter name.
- `val`  
The `OracleParameter` value.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Add(string, OracleDbType)**

This method adds an `OracleParameter` object to the collection using the supplied name and database type.

**Declaration**

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType);
```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the `OracleParameter`.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Add(string, OracleDbType, ParameterDirection)**

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and direction.

**Declaration**

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType,  
    ParameterDirection direction);
```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the `OracleParameter`.
- *direction*  
The `OracleParameter` direction.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#) on page 5-358

**Add(string, OracleDbType, object, ParameterDirection)**

This method adds an `OracleParameter` object to the collection using the supplied name, database type, parameter value, and direction.

**Declaration**

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, object val,
    ParameterDirection dir);
```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the `OracleParameter`.
- *val*  
The `OracleParameter` value.
- *dir*  
The `ParameterDirection` value.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**Example**

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class AddSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm = cmd.Parameters.Add(
            "MyParam", OracleDbType.Decimal, 1, ParameterDirection.Input);

        // Prints "cmd.Parameters.Count = 1"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);
    }
}
```

```

        prm.Dispose();
        cmd.Dispose();
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#) on page 5-358

**Add(string, OracleDbType, int, object, ParameterDirection)**

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, parameter value, and direction.

**Declaration**

```

// C#
public OracleParameter Add(string name, OracleDbType dbType, int size,
    object val, ParameterDirection dir;

```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the `OracleParameter`.
- *size*  
The size of `OracleParameter`.
- *val*  
The `OracleParameter` value.
- *dir*  
The `ParameterDirection` value.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#) on page 5-358

**Add(string, OracleDbType, int)**

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and size.

**Declaration**

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType, int size);
```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the OracleParameter.
- *size*  
The size of OracleParameter.

**Return Value**

The newly created OracleParameter object which was added to the collection.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class AddSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add parameter to the OracleParameterCollection  
        OracleParameter prm = cmd.Parameters.Add(  
            "MyParam", OracleDbType.Varchar2, 10);  
  
        // Prints "cmd.Parameters.Count = 1"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        prm.Dispose();  
        cmd.Dispose();  
    }  
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Add (string, OracleDbType, int, string)**

This method adds an OracleParameter object to the collection using the supplied name, database type, size, and source column.

**Declaration**

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType, int size,  
    string srcColumn);
```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the OracleParameter.
- *size*  
The size of OracleParameter.
- *srcColumn*  
The name of the source column.

**Return Value**

An OracleParameter.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Add(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)**

This method adds an OracleParameter object to the collection using the supplied name, database type, size, direction, null indicator, precision, scale, source column, source version, and parameter value.

**Declaration**

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, int size,
    ParameterDirection dir, bool isNullable, byte precision,
    byte scale, string srcColumn, DataRowVersion version, object val);
```

**Parameters**

- *name*  
The parameter name.
- *dbType*  
The data type of the OracleParameter.
- *size*  
The size of OracleParameter.
- *dir*  
The ParameterDirection value.
- *isNullable*  
An indicator that specifies if the parameter value can be null.
- *precision*  
The precision of the parameter value.

- *scale*  
The scale of the parameter value.
- *srcColumn*  
The name of the source column.
- *version*  
The DataRowVersion value.
- *val*  
The parameter value.

**Return Value**

The newly created `OracleParameter` object which was added to the collection.

**Exceptions**

`ArgumentException` - The type of supplied *val* does not belong to the type of `Value` property in any of the ODP.NET Types.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**AddRange**

This method adds elements to the end of the `OracleParameterCollection`.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void AddRange(Array paramArray );
```

**Parameters**

*paramArray*

An array of `OracleParameter` objects.

**Exceptions**

`ArgumentNullException` - The input parameter is null.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Clear**

This method removes all the `OracleParameter` objects from the collection.

**Declaration**

```
// ADO.NET 2.0: C#
```



```
public override void Clear();
```

## Implements

`IList`

## Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class ClearSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);

        // Prints "cmd.Parameters.Count = 1"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

        // Clear all parameters in the OracleParameterCollection
        cmd.Parameters.Clear();

        // Prints "cmd.Parameters.Count = 0"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

        prm.Dispose();
        cmd.Dispose();
    }
}
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## Contains

`Contains` indicates whether or not the supplied object exists in the collection.

### Overload List:

- [Contains\(object\)](#)

This method indicates whether or not the supplied object exists in the collection.
- [Contains\(string\)](#)

This method indicates whether or not an `OracleParameter` object exists in the collection using the supplied string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Contains(object)**

This method indicates whether or not the supplied object exists in the collection.

**Declaration**

```
// ADO.NET 2.0: C#  
public override bool Contains(object obj)
```

**Parameters**

- *obj*  
The object.

**Return Value**

A bool that indicates whether or not the OracleParameter specified is inside the collection.

**Implements**

IList

**Exceptions**

InvalidCastException - The supplied *obj* is not an OracleParameter object.

**Remarks**

Returns true if the collection contains the OracleParameter object; otherwise, returns false.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ContainsSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add parameter to the OracleParameterCollection  
        OracleParameter prm1 = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);  
  
        // Check if the OracleParameterCollection contains prm1  
        bool bContains = cmd.Parameters.Contains(prm1);  
  
        // Prints "bContains = True"  
        Console.WriteLine("bContains = " + bContains);  
  
        OracleParameter prm2 = new OracleParameter();  
    }  
}
```

```

// Check if the OracleParameterCollection contains prm2
bContains = cmd.Parameters.Contains(prm2);

// Prints "bContains = False"
Console.WriteLine("bContains = " + bContains);

prm1.Dispose();
prm2.Dispose();
cmd.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Contains(string)**

This method indicates whether or not an `OracleParameter` object exists in the collection using the supplied string.

**Declaration**

```

// ADO.NET 2.0: C#
public override bool Contains(string name);

```

**Parameters**

- *name*

The name of `OracleParameter` object.

**Return Value**

Returns `true` if the collection contains the `OracleParameter` object with the specified parameter name; otherwise, returns `false`.

**Implements**

`IDataParameterCollection`

**Example**

```

// C#
using System;
using Oracle.DataAccess.Client;

class ContainsSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);

        // Check if the OracleParameterCollection contains "MyParam"
        bool bContains = cmd.Parameters.Contains("MyParam");
    }
}

```

```
// Prints "bContains = True"
Console.WriteLine("bContains = " + bContains);

// Check if the OracleParameterCollection contains "NoParam"
bContains = cmd.Parameters.Contains("NoParam");

// Prints "bContains = False"
Console.WriteLine("bContains = " + bContains);

prm.Dispose();
cmd.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## CopyTo

This method copies `OracleParameter` objects from the collection, starting with the supplied index to the supplied array.

**Declaration**

```
// ADO.NET 2.0: C#
public override void CopyTo(Array array, int index);
```

**Parameters**

- *array*  
The specified array.
- *index*  
The array index.

**Implements**

`ICollection`

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## IndexOf

`IndexOf` returns the index of the `OracleParameter` object in the collection.

**Overload List:**

- [IndexOf\(object\)](#)  
This method returns the index of the `OracleParameter` object in the collection.
- [IndexOf\(String\)](#)

This method returns the index of the `OracleParameter` object with the specified name in the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**IndexOf(object)**

This method returns the index of the `OracleParameter` object in the collection.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int IndexOf(object obj);
```

**Parameters**

- *obj*  
The specified object.

**Return Value**

Returns the index of the `OracleParameter` object in the collection.

**Implements**

`IList`

**Exceptions**

`InvalidCastException` - The supplied *obj* cannot be cast to an `OracleParameter` object.

**Remarks**

Returns the index of the supplied `OracleParameter` *obj* in the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**IndexOf(String)**

This method returns the index of the `OracleParameter` object with the specified name in the collection.

**Declaration**

```
// ADO.NET 2.0: C#  
public override int IndexOf(String name);
```

**Parameters**

- *name*  
The name of parameter.

**Return Value**

Returns the index of the supplied `OracleParameter` in the collection.

**Implements**

`IDataParameterCollection`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Insert**

This method inserts the supplied `OracleParameter` object to the collection at the specified index.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void Insert(int index, object obj);
```

**Parameters**

- *index*  
The specified index.
- *obj*  
The `OracleParameter` object.

**Implements**

`IList`

**Remarks**

An `InvalidCastException` is thrown if the supplied *obj* cannot be cast to an `OracleParameter` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**Remove**

This method removes the supplied `OracleParameter` from the collection.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void Remove(object obj);
```

**Parameters**

- *obj*  
The specified object to remove.

**Implements**

ICollection

**Exceptions**

InvalidCastException - The supplied *obj* cannot be cast to an OracleParameter object.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;

class RemoveSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add 2 parameters to the OracleParameterCollection
        OracleParameter prm1 = cmd.Parameters.Add("MyParam1", OracleDbType.Decimal);
        OracleParameter prm2 = cmd.Parameters.Add("MyParam2", OracleDbType.Decimal);

        // Prints "cmd.Parameters.Count = 2"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

        // Remove the 1st parameter from the OracleParameterCollection
        cmd.Parameters.Remove(prm1);

        // Prints "cmd.Parameters.Count = 1"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

        // Prints "cmd.Parameters[0].ParameterName = MyParam2"
        Console.WriteLine("cmd.Parameters[0].ParameterName = " +
            cmd.Parameters[0].ParameterName);

        prm1.Dispose();
        prm2.Dispose();
        cmd.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

**RemoveAt**

RemoveAt removes the OracleParameter object from the collection by location.

**Overload List:**

- [RemoveAt\(int\)](#)

This method removes from the collection the `OracleParameter` object located at the index specified by the supplied index.

- [RemoveAt\(String\)](#)

This method removes from the collection the `OracleParameter` object specified by the supplied name.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## RemoveAt(int)

This method removes from the collection the `OracleParameter` object located at the index specified by the supplied index.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void RemoveAt(int index);
```

**Parameters**

- *index*

The specified index from which the `OracleParameter` is to be removed.

**Implements**

`IList`

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## RemoveAt(String)

This method removes from the collection the `OracleParameter` object specified by the supplied name.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void RemoveAt(String name);
```

**Parameters**

- *name*

The name of the `OracleParameter` object to be removed from the collection.

**Implements**

`IDataParameterCollection`



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

## OraclePermission Class

An `OraclePermission` object enables ODP.NET to enforce imperative security and helps ensure that a user has a security level adequate for accessing data.

### Class Inheritance

`System.Object`

`System.Security.CodeAccessPermission`

`System.Data.Common.DBDataPermission`

`Oracle.DataAccess.Client.OraclePermission`

### Declaration

```
// ADO.NET 2.0: C#  
public class OraclePermission: DBDataPermission
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OraclePermission Members](#)
- [OraclePermission Constructor](#)
- [OraclePermission Static Methods](#)
- [OraclePermission Public Properties](#)
- [OraclePermission Public Methods](#)

## OraclePermission Members

OraclePermission members are listed in the following tables.

### OraclePermission Constructors

The OraclePermission constructor is listed in [Table 5–87](#).

**Table 5–87 OraclePermission Constructor**

Constructor	Description
<a href="#">OraclePermission Constructor</a>	Instantiates a new instance of the OraclePermission class.

### OraclePermission Static Methods

The OraclePermission static methods are listed in [Table 5–88](#).

**Table 5–88 OraclePermission Static Methods**

Static Method	Description
Equals	Inherited from System.Object
ReferenceEquals	Inherited from System.Object
RevertAll	Inherited from CodeAccessPermission
RevertAssert	Inherited from CodeAccessPermission
RevertDeny	Inherited from CodeAccessPermission
RevertPermitOnly	Inherited from CodeAccessPermission

### OraclePermission Public Properties

The OraclePermission public methods are listed in [Table 5–92](#).

**Table 5–89 OraclePermission Public Properties**

Public Properties	Description
AllowBlankPassword	Inherited from DBDataPermission OraclePermission does not support this property.

### OraclePermission Public Methods

The OraclePermission public methods are listed in [Table 5–90](#).

**Table 5–90 OraclePermission Public Methods**

Public Method	Description
<a href="#">Add</a>	Adds a new connection string fragment and a list of restricted keywords to the OraclePermission object
Assert	Inherited from CodeAccessPermission
<a href="#">Copy</a>	Returns a copy of the current permission object
Demand	Inherited from CodeAccessPermission
Deny	Inherited from CodeAccessPermission

**Table 5–90 (Cont.) OraclePermission Public Methods**

<b>Public Method</b>	<b>Description</b>
Equals	Inherited from <code>CodeAccessPermission</code>
FromXml	Inherited from <code>DBDataPermission</code>
GetHashCode	Inherited from <code>CodeAccessPermission</code>
GetType	Inherited from <code>System.Object</code>
Intersect	Inherited from <code>DBDataPermission</code>
<a href="#">IsSubsetOf</a>	Returns a boolean value that indicates whether or not the current permission is a subset of the target permission
IsUnrestricted	Inherited from <code>DBDataPermission</code>
PermitOnly	Inherited from <code>CodeAccessPermission</code>
ToString	Inherited from <code>CodeAccessPermission</code>
ToXml	Inherited from <code>DBDataPermission</code>
Union	Inherited from <code>DBDataPermission</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)

## OraclePermission Constructor

The `OraclePermission` constructor instantiates a new instance of the `OraclePermission` class.

### Declaration

```
// C#  
public OraclePermission (PermissionState state);
```

### Parameters

- *state*

The *state* parameter takes one of the following two values:  
`PermissionState.None` or `PermissionState.Unrestricted`.

### Exceptions

`ArgumentException` - The `PermissionState` value is invalid.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

## OraclePermission Static Methods

The `OraclePermission` static methods are listed in [Table 5-91](#).

**Table 5-91** *OraclePermission Static Methods*

Static Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
<code>ReferenceEquals</code>	Inherited from <code>System.Object</code>
<code>RevertAll</code>	Inherited from <code>CodeAccessPermission</code>
<code>RevertAssert</code>	Inherited from <code>CodeAccessPermission</code>
<code>RevertDeny</code>	Inherited from <code>CodeAccessPermission</code>
<code>RevertPermitOnly</code>	Inherited from <code>CodeAccessPermission</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)
- [OraclePermission Members](#)

## OraclePermission Public Properties

The `OraclePermission` public methods are listed in [Table 5–92](#).

**Table 5–92 OraclePermission Public Properties**

Public Properties	Description
<code>AllowBlankPassword</code>	Inherited from <code>DBDataPermission</code> <code>OraclePermission</code> ignores the value of this property. Any value set for this property, for an <code>OraclePermission</code> object, is ignored.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)
- [OraclePermission Members](#)

## OraclePermission Public Methods

The `OraclePermission` public methods are listed in [Table 5–93](#).

**Table 5–93 OraclePermission Public Methods**

Public Method	Description
<a href="#">Add</a>	Adds a new connection string fragment and a list of restricted keywords to the <code>OraclePermission</code> object
<code>Assert</code>	Inherited from <code>CodeAccessPermission</code>
<a href="#">Copy</a>	Returns a copy of the current permission object
<code>Demand</code>	Inherited from <code>CodeAccessPermission</code>
<code>Deny</code>	Inherited from <code>CodeAccessPermission</code>
<code>Equals</code>	Inherited from <code>CodeAccessPermission</code>
<code>FromXml</code>	Inherited from <code>DBDataPermission</code>
<code>GetHashCode</code>	Inherited from <code>CodeAccessPermission</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>Intersect</code>	Inherited from <code>DBDataPermission</code>
<a href="#">IsSubsetOf</a>	Returns a boolean value that indicates whether or not the current permission is a subset of the target permission
<code>IsUnrestricted</code>	Inherited from <code>DBDataPermission</code>
<code>PermitOnly</code>	Inherited from <code>CodeAccessPermission</code>
<code>ToString</code>	Inherited from <code>CodeAccessPermission</code>
<code>ToXml</code>	Inherited from <code>DBDataPermission</code>
<code>Union</code>	Inherited from <code>DBDataPermission</code>

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)
- [OraclePermission Members](#)

## Add

This method adds a new connection string fragment and a list of restricted keywords to the `OraclePermission` object.

### Declaration

```
// C#
public void Add(string connStr, string keyRestrict,
    KeyRestrictionBehavior behavior);
```

### Parameters

- *connStr*



The connection string fragment.

- *keyRestrict*

The key restrictions.

- *behavior*

One of the following `KeyRestrictionBehavior` enumerations:

- `AllowOnly`
- `PreventUsage`

### Exceptions

`ArgumentException` - The `KeyRestrictionBehavior` value or the format of the `connStr` or `keyRestrict` string is invalid.

### Remarks

The `Add` method configures the connection strings allowed or disallowed by the permission object.

Opening an `OracleConnection` is allowed or denied based upon the connection string fragment, key restrictions combination, and the key restriction behavior.

In the following example, `KeyRestrictionBehavior.AllowOnly` allows connection strings that use `orcl` as the `Data Source` with any `User Id` and `Password` combination but no other connection string keywords. Connection string keywords other than `User Id` and `Password` cause security exceptions.

```
orclPermission.Add("Data Source=orcl;", "User Id=;Password=;",
    KeyRestrictionBehavior.AllowOnly);
```

In the next example, `KeyRestrictionBehavior.PreventUsage` restricts connection strings that use the keyword `Pooling`. Use of the `Pooling` keyword causes an exception.

```
orclPermission.Add("Data Source=orcl;", "Pooling=;",
    KeyRestrictionBehavior.PreventUsage)
```

As a general rule, in an unrestricted environment, any connection string that is not allowed is restricted and throws a security exception.

If a connection string fragment contains key-value pairs for the `password` and `proxy password` attributes, then values for these attributes are ignored. However, the presence of the attributes themselves is still checked. This means that the connection is allowed only if the `password` and `proxy` attributes keywords are allowed in the connection string.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)
- [OraclePermission Members](#)

## Copy

This method returns a copy of the current permission object.

**Declaration**

```
// C#  
public override IPermission Copy();
```

**Return Value**

A copy of the `OraclePermission` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)
- [OraclePermission Members](#)

**IsSubsetOf**

This method returns a boolean value that indicates whether or not the current permission is a subset of the target permission.

**Declaration**

```
// C#  
public override bool IsSubsetOf(IPermission target);
```

**Parameters**

- *target*

A permission that must be of type `OraclePermission`.

**Return Value**

A `bool` value that indicates whether or not the current permission is a subset of the target permission.

**Exceptions**

`ArgumentException` - The permission is not of the `OraclePermission` type.

**Remarks**

The `AllowBlankPassword` property is ignored when evaluating whether or not the current permission is a subset of the target permission.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermission Class](#)
- [OraclePermission Members](#)

---

## OraclePermissionAttribute Class

An `OraclePermissionAttribute` object enables ODP.NET to enforce declarative security and helps ensure that a user has a security level adequate for accessing data.

### Class Inheritance

`System.Object`

`System.Attribute`

`System.Security.Permissions.SecurityAttribute`

`System.Security.Permissions.CodeAccessSecurityAttribute`

`System.Data.Common.DBDataPermissionAttribute`

`Oracle.DataAccess.Client.OraclePermissionAttribute`

### Declaration

```
// ADO.NET 2.0:C#  
[Serializable, AttributeUsage(AttributeTargets.Method |  
AttributeTargets.Constructor | AttributeTargets.Class | AttributeTargets.Struct |  
AttributeTargets.Assembly, AllowMultiple = true, Inherited = false)]  
public sealed class OraclePermissionAttribute: DBDataPermissionAttribute
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess`

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OraclePermissionAttribute Members](#)
- [OraclePermissionAttribute Constructor](#)
- [OraclePermissionAttribute Static Methods](#)
- [OraclePermissionAttribute Public Properties](#)
- [OraclePermissionAttribute Public Methods](#)

## OraclePermissionAttribute Members

OraclePermissionAttribute members are listed in the following tables.

### OraclePermissionAttribute Constructor

The OraclePermissionAttribute constructor is listed in [Table 5–94](#).

**Table 5–94 OraclePermission Constructor**

Constructor	Description
<a href="#">OraclePermissionAttribute Constructor</a>	Instantiates a new instance of the OraclePermissionAttribute class.

### OraclePermissionAttribute Static Methods

The OraclePermissionAttribute static methods are listed in [Table 5–95](#).

**Table 5–95 OraclePermissionAttribute Static Methods**

Static Methods	Description
GetCustomAttribute	Inherited from System.Attribute (Overloaded)
GetCustomAttributes	Inherited from System.Attribute(Overloaded)
IsDefined	Inherited from System.Attribute(Overloaded)
ReferenceEquals	Inherited from System.Object

### OraclePermissionAttribute Public Properties

The OraclePermissionAttribute public properties are listed in [Table 5–96](#).

**Table 5–96 OraclePermissionAttribute Public Properties**

Public Properties	Description
Action	Inherited from SecurityAttribute
AllowBlankPassword	Inherited from DBDataPermissionAttribute. OraclePermissionAttribute ignores this property. Any value set for this property, for an OraclePermissionAttribute object, is ignored.
ConnectionString	Inherited from DBDataPermissionAttribute
KeyRestrictionBehavior	Inherited from DBDataPermissionAttribute
KeyRestrictions	Inherited from DBDataPermissionAttribute
TypeId	Inherited from System.Attribute
Unrestricted	Inherited from SecurityAttribute

### OraclePermissionAttribute Public Methods

The OraclePermissionAttribute public methods are listed in [Table 5–97](#).

**Table 5–97 OraclePermissionAttribute Public Methods**

Public Methods	Description
<a href="#">CreatePermission</a>	Returns a new OraclePermissionAttribute object that is configured based on the attributes set
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ShouldSerializeConnectionString	Inherited from DBDataPermissionAttribute
ShouldSerializeKeyRestrictions	Inherited from DBDataPermissionAttribute
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermissionAttribute Class](#)

## OraclePermissionAttribute Constructor

The `OraclePermissionAttribute` constructor instantiates new instances of the `OraclePermissionAttribute` class.

### Declaration

```
// C#  
public OraclePermissionAttribute (SecurityAction action);
```

### Parameters

- *action*

A `System.Security.Permissions.SecurityAction` value representing an action that can be performed using declarative security.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

## OraclePermissionAttribute Static Methods

The `OraclePermissionAttribute` static methods are listed in [Table 5-98](#).

**Table 5-98** *OraclePermissionAttribute Static Methods*

Static Methods	Description
<code>GetCustomAttribute</code>	Inherited from <code>System.Attribute</code> (Overloaded)
<code>GetCustomAttributes</code>	Inherited from <code>System.Attribute</code> (Overloaded)
<code>IsDefined</code>	Inherited from <code>System.Attribute</code> (Overloaded)
<code>ReferenceEquals</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

## OraclePermissionAttribute Public Properties

The `OraclePermissionAttribute` public properties are listed in [Table 5–99](#).

**Table 5–99** *OraclePermissionAttribute Public Properties*

Public Properties	Description
Action	Inherited from <code>SecurityAttribute</code>
AllowBlankPassword	Inherited from <code>DBDataPermissionAttribute</code> . <code>OraclePermissionAttribute</code> ignores this property. Any value set for this property, for an <code>OraclePermissionAttribute</code> object, is ignored.
ConnectionString	Inherited from <code>DBDataPermissionAttribute</code>
KeyRestrictionBehavior	Inherited from <code>DBDataPermissionAttribute</code>
KeyRestrictions	Inherited from <code>DBDataPermissionAttribute</code>
TypeId	Inherited from <code>System.Attribute</code>
Unrestricted	Inherited from <code>SecurityAttribute</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)



## OraclePermissionAttribute Public Methods

The OraclePermissionAttribute public methods are listed in [Table 5–100](#).

**Table 5–100 OraclePermissionAttribute Public Methods**

Public Methods	Description
<a href="#">CreatePermission</a>	Returns a new OraclePermissionAttribute object that is configured based on the attributes set
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ShouldSerializeConnectionString	Inherited from DBDataPermissionAttribute
ShouldSerializeKeyRestrictions	Inherited from DBDataPermissionAttribute
ToString	Inherited from System.Object

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

### CreatePermission

This method returns a new OraclePermissionAttribute object that is configured based on the attributes set.

### Declaration

```
// C#
public override IPermission CreatePermission();
```

### Return Value

An OraclePermission object.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

## OracleRowUpdatedEventArgs Class

The `OracleRowUpdatedEventArgs` class provides event data for the `OracleDataAdapter.RowUpdated` event.

### Class Inheritance

`System.Object`

`System.EventArgs`

`System.RowUpdatedEventArgs`

`System.OracleRowUpdatedEventArgs`

### Declaration

```
// C#  
public sealed class OracleRowUpdatedEventArgs : RowUpdatedEventArgs
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

The example for the `RowUpdated` event shows how to use `OracleRowUpdatedEventArgs`. See `RowUpdated` event ["Example"](#) on page 5-136.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatedEventArgs Members](#)
- [OracleRowUpdatedEventArgs Constructor](#)
- [OracleRowUpdatedEventArgs Static Methods](#)
- [OracleRowUpdatedEventArgs Properties](#)
- [OracleRowUpdatedEventArgs Public Methods](#)
- [OracleDataAdapter Class](#) on page 5-115

## OracleRowUpdatedEventArgs Members

OracleRowUpdatedEventArgs members are listed in the following tables.

### OracleRowUpdatedEventArgs Constructors

OracleRowUpdatedEventArgs constructors are listed in [Table 5–101](#).

**Table 5–101 OracleRowUpdatedEventArgs Constructors**

Constructor	Description
<a href="#">OracleRowUpdatedEventArgs Constructor</a>	Instantiates a new instance of OracleRowUpdatedEventArgs class

### OracleRowUpdatedEventArgs Static Methods

The OracleRowUpdatedEventArgs static method is listed in [Table 5–102](#).

**Table 5–102 OracleRowUpdatedEventArgs Static Method**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleRowUpdatedEventArgs Properties

The OracleRowUpdatedEventArgs properties are listed in [Table 5–103](#).

**Table 5–103 OracleRowUpdatedEventArgs Properties**

Property	Description
<a href="#">Command</a>	Specifies the OracleCommand that is used when OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatedEventArgs
RecordsAffected	Inherited from System.Data.Common.RowUpdatedEventArgs
Row	Inherited from System.Data.Common.RowUpdatedEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatedEventArgs
Status	Inherited from System.Data.Common.RowUpdatedEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatedEventArgs

### OracleRowUpdatedEventArgs Public Methods

The OracleRowUpdatedEventArgs properties are listed in [Table 5–104](#).

**Table 5–104 OracleRowUpdatedEventArgs Public Methods**

Public Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object

**Table 5–104 (Cont.) OracleRowUpdatedEventArgs Public Methods**

Public Method	Description
ToString	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatedEventArgs Class](#)

## OracleRowUpdatedEventArgs Constructor

The `OracleRowUpdatedEventArgs` constructor creates a new `OracleRowUpdatedEventArgs` instance.

### Declaration

```
// C#  
public OracleRowUpdatedEventArgs(DataRow row, IDbCommand command,  
    StatementType statementType, DataTableMapping tableMapping);
```

### Parameters

- *row*  
The `DataRow` sent for Update.
- *command*  
The `IDbCommand` executed during the Update.
- *statementType*  
The `StatementType` Enumeration value indicating the type of SQL statement executed.
- *tableMapping*  
The `DataTableMapping` used for the Update.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

## OracleRowUpdatedEventArgs Static Methods

The `OracleRowUpdatedEventArgs` static method is listed in [Table 5–105](#).

**Table 5–105** *OracleRowUpdatedEventArgs Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

## OracleRowUpdatedEventArgs Properties

The `OracleRowUpdatedEventArgs` properties are listed in [Table 5–106](#).

**Table 5–106 OracleRowUpdatedEventArgs Properties**

Property	Description
<a href="#">Command</a>	Specifies the <code>OracleCommand</code> that is used when <code>OracleDataAdapter.Update()</code> is called
<code>Errors</code>	Inherited from <code>System.Data.Common.RowUpdatedEventArgs</code>
<code>RecordsAffected</code>	Inherited from <code>System.Data.Common.RowUpdatedEventArgs</code>
<code>Row</code>	Inherited from <code>System.Data.Common.RowUpdatedEventArgs</code>
<code>StatementType</code>	Inherited from <code>System.Data.Common.RowUpdatedEventArgs</code>
<code>Status</code>	Inherited from <code>System.Data.Common.RowUpdatedEventArgs</code>
<code>TableMapping</code>	Inherited from <code>System.Data.Common.RowUpdatedEventArgs</code>

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

## Command

This property specifies the `OracleCommand` that is used when `OracleDataAdapter.Update()` is called.

### Declaration

```
// C#
public new OracleCommand Command {get;}
```

### Property Value

The `OracleCommand` executed when `Update` is called.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

## OracleRowUpdatedEventArgs Public Methods

The `OracleRowUpdatedEventArgs` properties are listed in [Table 5–107](#).

**Table 5–107** *OracleRowUpdatedEventArgs Public Methods*

Public Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)



## OracleRowUpdatedEventHandler Delegate

The `OracleRowUpdatedEventHandler` delegate represents the signature of the method that handles the `OracleDataAdapter.RowUpdated` event.

### Declaration

```
// C#  
public delegate void OracleRowUpdatedEventHandler(object sender,  
    OracleRowUpdatedEventArgs eventArgs);
```

### Parameters

- *sender*  
The source of the event.
- *eventArgs*  
The `OracleRowUpdatedEventArgs` object that contains the event data.

### Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified after a row is updated.

In the .NET framework, the convention of an event delegate requires two parameters: the object that raises the event and the event data.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- ["RowUpdated" on page 5-135](#)

## OracleRowUpdatingEventArgs Class

The `OracleRowUpdatingEventArgs` class provides event data for the `OracleDataAdapter.RowUpdating` event.

### Class Inheritance

`System.Object`

`System.EventArgs`

`System.RowUpdatingEventArgs`

`System.OracleRowUpdatingEventArgs`

### Declaration

```
// C#  
public sealed class OracleRowUpdatingEventArgs : RowUpdatingEventArgs
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

The example for the `RowUpdated` event shows how to use `OracleRowUpdatingEventArgs`. See `RowUpdated` event ["Example"](#) on page 5-136.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatingEventArgs Members](#)
- [OracleRowUpdatingEventArgs Constructor](#)
- [OracleRowUpdatingEventArgs Static Methods](#)
- [OracleRowUpdatingEventArgs Properties](#)
- [OracleRowUpdatingEventArgs Public Methods](#)
- ["OracleDataAdapter Class"](#) on page 5-115

## OracleRowUpdatingEventArgs Members

OracleRowUpdatingEventArgs members are listed in the following tables.

### OracleRowUpdatingEventArgs Constructors

OracleRowUpdatingEventArgs constructors are listed in [Table 5-108](#).

**Table 5-108 OracleRowUpdatingEventArgs Constructors**

Constructor	Description
<a href="#">OracleRowUpdatingEventArgs Constructor</a>	Instantiates a new instance of OracleRowUpdatingEventArgs class (Overloaded)

### OracleRowUpdatingEventArgs Static Methods

The OracleRowUpdatingEventArgs static methods are listed in [Table 5-109](#).

**Table 5-109 OracleRowUpdatingEventArgs Static Methods**

Method	Description
Equals	Inherited from System.Object (Overloaded)

### OracleRowUpdatingEventArgs Properties

The OracleRowUpdatingEventArgs properties are listed in [Table 5-110](#).

**Table 5-110 OracleRowUpdatingEventArgs Properties**

Property	Description
<a href="#">Command</a>	Specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatingEventArgs
Row	Inherited from System.Data.Common.RowUpdatingEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatingEventArgs
Status	Inherited from System.Data.Common.RowUpdatingEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatingEventArgs

### OracleRowUpdatingEventArgs Public Methods

The OracleRowUpdatingEventArgs public methods are listed in [Table 5-111](#).

**Table 5-111 OracleRowUpdatingEventArgs Public Methods**

Public Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatingEventArgs Class](#)

## OracleRowUpdatingEventArgs Constructor

The `OracleRowUpdatingEventArgs` constructor creates a new instance of the `OracleRowUpdatingEventArgs` class using the supplied data row, `IDbCommand`, type of SQL statement, and table mapping.

### Declaration

```
// C#  
public OracleRowUpdatingEventArgs(DataRow row, IDbCommand command,  
    StatementType statementType, DataTableMapping tableMapping);
```

### Parameters

- *row*  
The `DataRow` sent for Update.
- *command*  
The `IDbCommand` executed during the Update.
- *statementType*  
The `StatementType` enumeration value indicating the type of SQL statement executed.
- *tableMapping*  
The `DataTableMapping` used for the Update.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

## OracleRowUpdatingEventArgs Static Methods

The `OracleRowUpdatingEventArgs` static method is listed in [Table 5–112](#).

**Table 5–112** *OracleRowUpdatingEventArgs Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

## OracleRowUpdatingEventArgs Properties

The OracleRowUpdatingEventArgs properties are listed in [Table 5–113](#).

**Table 5–113 OracleRowUpdatingEventArgs Properties**

Property	Description
<a href="#">Command</a>	Specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatingEventArgs
Row	Inherited from System.Data.Common.RowUpdatingEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatingEventArgs
Status	Inherited from System.Data.Common.RowUpdatingEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatingEventArgs

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

### Command

This property specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called.

**Declaration**

```
// C#
public new OracleCommand Command {get; set;}
```

**Property Value**

The OracleCommand executed when Update is called.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

## OracleRowUpdatingEventArgs Public Methods

The `OracleRowUpdatingEventArgs` public methods are listed in [Table 5–114](#).

**Table 5–114** *OracleRowUpdatingEventArgs Public Methods*

Public Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)



---

## OracleRowUpdatingEventHandler Delegate

The `OracleRowUpdatingEventHandler` delegate represents the signature of the method that handles the `OracleDataAdapter.RowUpdating` event.

### Declaration

```
// C#  
public delegate void OracleRowUpdatingEventHandler (object sender,  
    OracleRowUpdatingEventArgs eventArgs);
```

### Parameters

- *sender*  
The source of the event.
- *eventArgs*  
The `OracleRowUpdatingEventArgs` object that contains the event data.

### Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified after a row is updated.

In the .NET framework, the convention of an event delegate requires two parameters: the object that raises the event and the event data.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["RowUpdating"](#) on page 5-137

## OracleTransaction Class

An OracleTransaction object represents a local transaction.

### Class Inheritance

System.Object

System.MarshalByRefObject

System.Data.Common.DbTransaction (ADO.NET 2.0 only)

Oracle.DataAccess.Client.OracleTransaction

### Declaration

```
// ADO.NET 2.0: C#
public sealed class OracleTransaction : DbTransaction

// C#
public sealed class OracleTransaction : MarshalByRefObject,
    IDbTransaction, IDisposable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

The application calls `BeginTransaction` on the `OracleConnection` object to create an `OracleTransaction` object. The `OracleTransaction` object can be created in Read Committed mode only. Any other mode results in an exception.

The execution of a **DDL** statement in the context of a transaction is not recommended since it results in an implicit commit that is not reflected in the state of the `OracleTransaction` object.

All operations related to **savepoints** pertain to the current local transaction. Operations like commit and rollback performed on the transaction have no effect on data in any existing `DataSet`.

### Example

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);
--CREATE TABLE MyTable (MyColumn NUMBER PRIMARY KEY);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleTransactionSample
{
```

```
static void Main()
{
    // Drop & Create MyTable as indicated Database Setup, at beginning

    // This sample starts a transaction and inserts two records with the same
    // value for MyColumn into MyTable.
    // If MyColumn is not a primary key, the transaction will commit.
    // If MyColumn is a primary key, the second insert will violate the
    // unique constraint and the transaction will rollback.

    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    OracleCommand cmd = con.CreateCommand();

    // Check the number of rows in MyTable before transaction
    cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
    int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

    // Print the number of rows in MyTable
    Console.WriteLine("myTableCount = " + myTableCount);

    // Start a transaction
    OracleTransaction txn = con.BeginTransaction(
        IsolationLevel.ReadCommitted);

    try
    {
        // Insert the same row twice into MyTable
        cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
        cmd.ExecuteNonQuery();
        cmd.ExecuteNonQuery(); // This may throw an exception
        txn.Commit();
    }
    catch (Exception e)
    {
        // Print the exception message
        Console.WriteLine("e.Message = " + e.Message);

        // Rollback the transaction
        txn.Rollback();
    }

    // Check the number of rows in MyTable after transaction
    cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
    myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

    // Prints the number of rows
    // If MyColumn is not a PRIMARY KEY, the value should increase by two.
    // If MyColumn is a PRIMARY KEY, the value should remain same.
    Console.WriteLine("myTableCount = " + myTableCount);

    txn.Dispose();
    cmd.Dispose();

    con.Close();
    con.Dispose();
}
```

```
}
```

### **Requirements**

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

#### **See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleTransaction Members](#)
- [OracleTransaction Static Methods](#)
- [OracleTransaction Properties](#)

## OracleTransaction Members

OracleTransaction members are listed in the following tables.

### OracleTransaction Static Methods

The OracleTransaction static method is listed in [Table 5-115](#).

**Table 5-115 OracleTransaction Static Method**

Method	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleTransaction Properties

OracleTransaction properties are listed in [Table 5-116](#).

**Table 5-116 OracleTransaction Properties**

Property	Description
<a href="#">IsolationLevel</a>	Specifies the isolation level for the transaction
<a href="#">Connection</a>	Specifies the connection that is associated with the transaction

### OracleTransaction Public Methods

OracleTransaction public methods are listed in [Table 5-117](#).

**Table 5-117 OracleTransaction Public Methods**

Public Method	Description
<a href="#">Commit</a>	Commits the database transaction
<a href="#">CreateObjRef</a>	Inherited from System.MarshalByRefObject
<a href="#">Dispose</a>	Frees the resources used by the OracleTransaction object
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)
<a href="#">GetHashCode</a>	Inherited from System.Object
<a href="#">GetLifetimeService</a>	Inherited from System.MarshalByRefObject
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">InitializeLifetimeService</a>	Inherited from System.MarshalByRefObject
<a href="#">Rollback</a>	Rolls back a database transaction (Overloaded)
<a href="#">Save</a>	Creates a savepoint within the current transaction
<a href="#">ToString</a>	Inherited from System.Object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)

## OracleTransaction Static Methods

The `OracleTransaction` static method is listed in [Table 5–118](#).

**Table 5–118** *OracleTransaction Static Method*

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

## OracleTransaction Properties

OracleTransaction properties are listed in [Table 5–119](#).

**Table 5–119 OracleTransaction Properties**

Property	Description
<a href="#">IsolationLevel</a>	Specifies the isolation level for the transaction
<a href="#">Connection</a>	Specifies the connection that is associated with the transaction

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

### IsolationLevel

This property specifies the isolation level for the transaction.

**Declaration**

```
// ADO.NET 2.0: C#
public override IsolationLevel IsolationLevel {get;}
```

**Property Value**

IsolationLevel

**Implements**

IDbTransaction

**Exceptions**

InvalidOperationException - The transaction has already completed.

**Remarks**

Default = IsolationLevel.ReadCommitted

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

### Connection

This property specifies the connection that is associated with the transaction.

**Declaration**

```
// C#
public OracleConnection Connection {get;}
```

**Property Value**

Connection

### **Implements**

IDbTransaction

### **Remarks**

This property indicates the `OracleConnection` object that is associated with the transaction.

#### **See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)



## OracleTransaction Public Methods

OracleTransaction public methods are listed in [Table 5–120](#).

**Table 5–120 OracleTransaction Public Methods**

Public Method	Description
<a href="#">Commit</a>	Commits the database transaction
CreateObjRef	Inherited from System.MarshalByRefObject
<a href="#">Dispose</a>	Frees the resources used by the OracleTransaction object
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
<a href="#">Rollback</a>	Rolls back a database transaction (Overloaded)
<a href="#">Save</a>	Creates a savepoint within the current transaction
ToString	Inherited from System.Object

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

## Commit

This method commits the database transaction.

### Declaration

```
// ADO.NET 2.0: C#
public override void Commit();
```

### Implements

IDbTransaction

### Exceptions

InvalidOperationException - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

### Remarks

Upon a successful commit, the transaction enters a completed state.

### Example

```
// Database Setup, if you have not done so yet
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
```

```
CREATE TABLE MyTable (MyColumn NUMBER);
--CREATE TABLE MyTable (MyColumn NUMBER PRIMARY KEY);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CommitSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated in Database Setup, at beginning

        // This sample starts a transaction and inserts two records with the same
        // value for MyColumn into MyTable.
        // If MyColumn is not a primary key, the transaction will commit.
        // If MyColumn is a primary key, the second insert will violate the
        // unique constraint and the transaction will rollback.

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = con.CreateCommand();

        // Check the number of rows in MyTable before transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Print the number of rows in MyTable
        Console.WriteLine("myTableCount = " + myTableCount);

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(
            IsolationLevel.ReadCommitted);

        try
        {
            // Insert the same row twice into MyTable
            cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
            cmd.ExecuteNonQuery();
            cmd.ExecuteNonQuery(); // This may throw an exception
            txn.Commit();
        }
        catch (Exception e)
        {
            // Print the exception message
            Console.WriteLine("e.Message = " + e.Message);

            // Rollback the transaction
            txn.Rollback();
        }

        // Check the number of rows in MyTable after transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
    }
}
```

```

myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows
// If MyColumn is not a PRIMARY KEY, the value should increase by two.
// If MyColumn is a PRIMARY KEY, the value should remain same.
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

**Dispose**

This method frees the resources used by the `OracleTransaction` object.

**Declaration**

```
// C#
public void Dispose();
```

**Implements**

`IDisposable`

**Remarks**

This method releases both the managed and unmanaged resources held by the `OracleTransaction` object. If the transaction is not in a completed state, an attempt to rollback the transaction is made.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

**Rollback**

Rollback rolls back a database transaction.

**Overload List:**

- [Rollback\(\)](#)  
This method rolls back a database transaction.
- [Rollback\(string\)](#)  
This method rolls back a database transaction to a **savepoint** within the current transaction.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

**Rollback()**

This method rolls back a database transaction.

**Declaration**

```
// ADO.NET 2.0: C#  
public override void Rollback();
```

**Implements**

IDbTransaction

**Exceptions**

InvalidOperationException - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

**Remarks**

After a `Rollback()`, the `OracleTransaction` object can no longer be used because the `Rollback` ends the transaction.

**Example**

```
// Database Setup, if you have not done so yet.  
/*  
connect scott/tiger@oracle  
DROP TABLE MyTable;  
CREATE TABLE MyTable (MyColumn NUMBER);  
  
*/  
  
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class RollbackSample  
{  
    static void Main()  
    {  
        // Drop & Create MyTable as indicated previously in Database Setup  
  
        // This sample starts a transaction and inserts one record into MyTable.  
        // It then rollsback the transaction, the number of rows remains the same  
  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = con.CreateCommand();  
  
        // Check the number of rows in MyTable before transaction
```

```

cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Print the number of rows in MyTable
Console.WriteLine("myTableCount = " + myTableCount);

// Start a transaction
OracleTransaction txn = con.BeginTransaction(
    IsolationLevel.ReadCommitted);

// Insert a row into MyTable
cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
cmd.ExecuteNonQuery();

// Rollback the transaction
txn.Rollback();

// Check the number of rows in MyTable after transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows, should remain the same
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

**Rollback(string)**

This method rolls back a database transaction to a **savepoint** within the current transaction.

**Declaration**

```
// ADO.NET 2.0: C#
public override void Rollback(string savepointName);
```

**Parameters**

- *savepointName*

The name of the savepoint to rollback to, in the current transaction.

**Exceptions**

*InvalidOperationException* - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

**Remarks**

After a rollback to a savepoint, the current transaction remains active and can be used for further operations.

The *savepointName* specified does not have to match the case of the *savepointName* created using the *Save* method, since savepoints are created in the database in a case-insensitive manner.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

**Save**

This method creates a **savepoint** within the current transaction.

**Declaration**

```
// C#
public void Save(string savepointName);
```

**Parameters**

- *savepointName*

The name of the savepoint being created in the current transaction.

**Exceptions**

*InvalidOperationException* - The transaction has already been completed.

**Remarks**

After creating a savepoint, the transaction does not enter a completed state and can be used for further operations.

The *savepointName* specified is created in the database in a case-insensitive manner. Calling the *Rollback* method rolls back to *savepointName*. This allows portions of a transaction to be rolled back, instead of the entire transaction.

**Example**

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class SaveSample
{
    static void Main()
```

```
{
    // Drop & Create MyTable as indicated in Database Setup, at beginning

    // This sample starts a transaction and creates a savepoint after
    // inserting one record into MyTable.
    // After inserting the second record it rollsback to the savepoint
    // and commits the transaction. Only the first record will be inserted

    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    OracleCommand cmd = con.CreateCommand();

    // Check the number of rows in MyTable before transaction
    cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
    int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

    // Print the number of rows in MyTable
    Console.WriteLine("myTableCount = " + myTableCount);

    // Start a transaction
    OracleTransaction txn = con.BeginTransaction(
        IsolationLevel.ReadCommitted);

    // Insert a row into MyTable
    cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
    cmd.ExecuteNonQuery();

    // Create a savepoint
    txn.Save("MySavePoint");

    // Insert another row into MyTable
    cmd.CommandText = "insert into mytable values (2)";
    cmd.ExecuteNonQuery();

    // Rollback to the savepoint
    txn.Rollback("MySavePoint");

    // Commit the transaction
    txn.Commit();

    // Check the number of rows in MyTable after transaction
    cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
    myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

    // Prints the number of rows, should have increased by 1
    Console.WriteLine("myTableCount = " + myTableCount);

    txn.Dispose();
    cmd.Dispose();

    con.Close();
    con.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)



---

## OracleCollectionType Enumeration

OracleCollectionType enumerated values specify whether or not the OracleParameter object represents a collection, and if so, specifies the collection type.

[Table 5–121](#) lists all the OracleCollectionType enumeration values with a description of each enumerated value.

**Table 5–121 OracleCollectionType Enumeration Values**

Member Name	Description
None	Is not a collection type
PLSQLAssociativeArray	Indicates that the collection type is a PL/SQL Associative Array (or PL/SQL Index-By Table)

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleParameter Class"](#) on page 5-247
- ["CollectionType"](#) on page 5-266

---

## OracleDBShutdownMode Enumeration

`OracleDBShutdownMode` enumerated values specify the database shutdown options.

[Table 5–123](#) lists all the `OracleDBShutdownMode` enumeration values with a description of each enumerated value.

**Table 5–122** *OracleDBShutdownMode Enumeration Values*

Member Name	Description
<code>Default</code>	Refuses new connections and waits for existing connections to end.
<code>Transactional</code>	Refuses new connections and does not allow any new transactions. Waits for active transactions to commit.
<code>TransactionalLocal</code>	Refuses new connections and does not allow any new transactions. Waits for only local transactions to commit.
<code>Immediate</code>	Does not wait for current calls to complete or users to disconnect from the database. All uncommitted transactions are terminated and rolled back.
<code>Final</code>	Shuts down the database. Used in the second call for shutdown after the database has been closed and dismounted.
<code>Abort</code>	Does not wait for current calls to complete or users to disconnect from the database. All uncommitted transactions are terminated and are not rolled back.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleConnection Class"](#) on page 5-64
- ["Shutdown"](#) on page 5-144

---

## OracleDBStartupMode Enumeration

OracleDBStartupMode enumerated values specify the database startup options.

[Table 5–123](#) lists all the OracleDBStartupMode enumeration values with a description of each enumerated value.

**Table 5–123 OracleDBStartupMode Enumeration Values**

Member Name	Description
NoRestriction	Starts the database and allows access to all users.
Restrict	Starts the database and allows database access only to users having the CREATE SESSION and RESTRICTED SESSION privileges. These privileges are normally assigned to database administrators.
Force	Shuts down a running instance in abort mode and starts a new instance.

### Requirements

Namespace: Oracle.DataAccess.Client

Assembly: Oracle.DataAccess.dll

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleConnection Class"](#) on page 5-64
- ["Startup"](#) on page 5-148

## OracleDbType Enumeration

OracleDbType enumerated values are used to explicitly specify the OracleDbType of an OracleParameter.

[Table 5–124](#) lists all the OracleDbType enumeration values with a description of each enumerated value.

**Table 5–124 OracleDbType Enumeration Values**

Member Name	Description
Array	Oracle Collection (VArray or Nested Table)
BFile	Oracle BFILE type
BinaryFloat	Oracle BINARY_FLOAT type
BinaryDouble	Oracle BINARY_DOUBLE type
Blob	Oracle BLOB type
Byte	byte type
Char	Oracle CHAR type
Clob	Oracle CLOB type
Date	Oracle DATE type
Decimal	Oracle NUMBER type
Double	8-byte FLOAT type
Int16	2-byte INTEGER type
Int32	4-byte INTEGER type
Int64	8-byte INTEGER type
IntervalDS	Oracle INTERVAL DAY TO SECOND type
IntervalYM	Oracle INTERVAL YEAR TO MONTH type
Long	Oracle LONG type
LongRaw	Oracle LONG RAW type
NChar	Oracle NCHAR type
NClob	Oracle NCLOB type
NVarchar2	Oracle NVARCHAR2 type
Object	Oracle Object
Raw	Oracle RAW type
Ref	Oracle REF
RefCursor	Oracle REF CURSOR type
Single	4-byte FLOAT type, supports 6 precisions
TimeStamp	Oracle TIMESTAMP type
TimeStampLTZ	Oracle TIMESTAMP WITH LOCAL TIME ZONE type
TimeStampTZ	Oracle TIMESTAMP WITH TIME ZONE type
Varchar2	Oracle VARCHAR2 type

**Table 5–124 (Cont.) OracleDbType Enumeration Values**

Member Name	Description
XmlType	Oracle XMLType type

**Requirements**

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleParameter Class"](#) on page 5-247
- ["OracleParameterCollection Class"](#) on page 5-282
- `OracleParameter` ["OracleDbType"](#) on page 5-269

## OracleParameterStatus Enumeration

The `OracleParameterStatus` enumeration type indicates whether a `NULL` value is fetched from a column, or truncation has occurred during the fetch, or a `NULL` value is to be inserted into a database column.

[Table 5–125](#) lists all the `OracleParameterStatus` enumeration values with a description of each enumerated value.

**Table 5–125** *OracleParameterStatus Members*

Member Name	Description
<code>Success</code>	Indicates that (for input parameters) the input value has been assigned to the column. For output parameter, it indicates that the provider assigned an intact value to the parameter.
<code>NullFetched</code>	Indicates that a <code>NULL</code> value has been fetched from a column or an <code>OUT</code> parameter.
<code>NullInsert</code>	Indicates that a <code>NULL</code> value is to be inserted into a column.
<code>Truncation</code>	Indicates that truncation has occurred when fetching the data from the column.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleParameter Class"](#) on page 5-247
- OracleParameter ["ArrayBindStatus"](#) on page 5-265
- OracleParameter ["Value"](#) on page 5-276

---

---

## Oracle Data Provider for .NET XML-Related Classes

This chapter describes ODP.NET XML-related classes and enumerations.

This chapter contains these topics:

- [OracleXmlCommandType Enumeration](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlStream Class](#)
- [OracleXmlType Class](#)

All offsets are 0-based for `OracleXmlStream` object parameters.

## OracleXmlCommandType Enumeration

The `OracleXmlCommandType` enumeration specifies the values that are allowed for the `XmlCommandType` property of the `OracleCommand` class. It is used to specify the type of XML operation.

[Table 6-1](#) lists all the `OracleXmlCommandType` enumeration values with a description of each enumerated value.

**Table 6-1** *OracleXmlCommandType Members*

Member Name	Description
None	No XML operation is desired
Query	The command text is a SQL query and the result of the query is an XML document. The SQL query needs to be a select statement
Insert	The command text is an XML document containing rows to insert.
Update	The command text is an XML document containing rows to update.
Delete	The command text is an XML document containing rows to delete.

**See Also:** ["Oracle.DataAccess.Client Namespace"](#) on page 1-4



## OracleXmlQueryProperties Class

An `OracleXmlQueryProperties` object represents the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Query`.

### Class Inheritance

`System.Object`

`System.OracleXmlQueryProperties`

### Declaration

```
public sealed class OracleXmlQueryProperties : ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

`OracleXmlQueryProperties` can be accessed, and modified using the `XmlQueryProperties` property of the `OracleCommand` class. Each `OracleCommand` object has its own instance of the `OracleXmlQueryProperties` class in the `XmlQueryProperties` property.

Use the default constructor to get a new instance of the `OracleXmlQueryProperties`. Use the `OracleXmlQueryProperties.Clone()` method to get a copy of an `OracleXmlQueryProperties` instance.

### Example

This example retrieves relational data as XML.

```
// C#

using System;
using System.IO;
using System.Data;
using System.Xml;
using System.Text;
using Oracle.DataAccess.Client;

class OracleXmlQueryPropertiesSample
{
    static void Main()
    {
        int rows = 0;
        StreamReader sr = null;

        // Define the XSL document for doing the transform.
        string xslstr = "<?xml version='1.0'?>\n" +
            "<xsl:stylesheet version='1.0'\n" +
            "  xmlns:xsl='http://www.w3.org/1999/XSL/Transform'\n" +
            "  <xsl:output encoding='utf-8'/>\n" +
            "  <xsl:template match='/'>\n" +
            "    <EMPLOYEES>\n" +
            "      <xsl:apply-templates select='ROWSET'/>\n" +
            "    </EMPLOYEES>\n" +
```

```
" </xsl:template>\n" +
" <xsl:template match=\"ROWSET\">\n" +
"   <xsl:apply-templates select=\"ROW\"/>\n" +
" </xsl:template>\n" +
" <xsl:template match=\"ROW\">\n" +
"   <EMPLOYEE>\n" +
"     <EMPLOYEE_ID>\n" +
"       <xsl:apply-templates select=\"EMPNO\"/>\n" +
"     </EMPLOYEE_ID>\n" +
"     <EMPLOYEE_NAME>\n" +
"       <xsl:apply-templates select=\"ENAME\"/>\n" +
"     </EMPLOYEE_NAME>\n" +
"     <HIRE_DATE>\n" +
"       <xsl:apply-templates select=\"HIREDATE\"/>\n" +
"     </HIRE_DATE>\n" +
"     <JOB_TITLE>\n" +
"       <xsl:apply-templates select=\"JOB\"/>\n" +
"     </JOB_TITLE>\n" +
"   </EMPLOYEE>\n" +
" </xsl:template>\n" +
"</xsl:stylesheet>\n";

// Create the connection.
string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Set the date, and timestamp formats for Oracle 9i Release 2, or later.
// This is just needed for queries.
if (!con.ServerVersion.StartsWith("9.0") &&
    !con.ServerVersion.StartsWith("8.1"))
{
    OracleGlobalization sessionParams = con.GetSessionInfo();
    sessionParams.DateFormat = "YYYY-MM-DD\"T\"HH24:MI:SS";
    sessionParams.TimeStampFormat = "YYYY-MM-DD\"T\"HH24:MI:SS.FF3";
    sessionParams.TimeStampTZFormat = "YYYY-MM-DD\"T\"HH24:MI:SS.FF3";
    con.SetSessionInfo(sessionParams);
}

// Create the command.
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to query.
cmd.XmlCommandType = OracleXmlCommandType.Query;

// Set the SQL query.
cmd.CommandText = "select * from emp e where e.empno = :empno";

// Set command properties that affect XML query behaviour.
cmd.BindByName = true;

// Bind values to the parameters in the SQL query.
Int32 empNum = 7369;
cmd.Parameters.Add("empno", OracleDbType.Int32, empNum,
    ParameterDirection.Input);

// Set the XML query properties.
cmd.XmlQueryProperties.MaxRows = 1;
cmd.XmlQueryProperties.RootTag = "ROWSET";
cmd.XmlQueryProperties.RowTag = "ROW";
```

```

cmd.XmlQueryProperties.Xslt = xslstr;

// Test query execution without returning a result.
Console.WriteLine("SQL query: select * from emp e where e.empno = 7369");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("Return Value from OracleCommand.ExecuteNonQuery():");
rows = cmd.ExecuteNonQuery();
Console.WriteLine(rows);
Console.WriteLine("\n");

// Get the XML document as an XmlReader.
Console.WriteLine("SQL query: select * from emp e where e.empno = 7369");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("XML Document from OracleCommand.ExecuteXmlReader():");

XmlReader xmlReader = cmd.ExecuteXmlReader();
XmlDocument xmlDocument = new XmlDocument();
xmlDocument.PreserveWhitespace = true;
xmlDocument.Load(xmlReader);
Console.WriteLine(xmlDocument.OuterXml);
Console.WriteLine("\n");

// Change the SQL query, and set the maximum number of rows to 2.
cmd.CommandText = "select * from emp e";
cmd.Parameters.Clear();
cmd.XmlQueryProperties.MaxRows = 2;

// Get the XML document as a Stream.
Console.WriteLine("SQL query: select * from emp e");
Console.WriteLine("Maximum rows: 2");
Console.WriteLine("XML Document from OracleCommand.ExecuteStream():");
Stream stream = cmd.ExecuteStream();
sr = new StreamReader(stream, Encoding.Unicode);
Console.WriteLine(sr.ReadToEnd());
Console.WriteLine("\n");

// Get all the rows.
cmd.XmlQueryProperties.MaxRows = -1;

// Append the XML document to an existing Stream.
Console.WriteLine("SQL query: select * from emp e");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("XML Document from OracleCommand.ExecuteToStream():");
MemoryStream mstream = new MemoryStream(32);
cmd.ExecuteToStream(mstream);
mstream.Seek(0, SeekOrigin.Begin);
sr = new StreamReader(mstream, Encoding.Unicode);
Console.WriteLine(sr.ReadToEnd());
Console.WriteLine("\n");

// Clean up.
cmd.Dispose();
con.Close();
con.Dispose();
}
}

```

**Requirements**

Namespace: Oracle.DataAccess.Client

Assembly: Oracle.DataAccess.dll

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Members](#)
- [OracleXmlQueryProperties Constructor](#)
- [OracleXmlQueryProperties Properties](#)
- [OracleXmlQueryProperties Public Methods](#)

## OracleXmlQueryProperties Members

OracleXmlQueryProperties members are listed in the following tables.

### OracleXmlQueryProperties Constructors

The OracleXmlQueryProperties constructors are listed in [Table 6-2](#).

**Table 6-2 OracleXmlQueryProperties Constructors**

Constructor	Description
<a href="#">OracleXmlQueryProperties Constructor</a>	Instantiates a new instance of the OracleXmlQueryProperties class

### OracleXmlQueryProperties Properties

The OracleXmlQueryProperties properties are listed in [Table 6-3](#).

**Table 6-3 OracleXmlQueryProperties Properties**

Name	Description
<a href="#">MaxRows</a>	Specifies the maximum number of rows from the result set of the query that can be represented in the result XML document
<a href="#">RootTag</a>	Specifies the root element of the result XML document
<a href="#">RowTag</a>	Specifies the value of the XML element which identifies a row of data from the result set in an XML document
<a href="#">Xslt</a>	Specifies the XSL document used for XML transformation using XSLT
<a href="#">XsltParams</a>	Specifies parameters for the XSL document

### OracleXmlQueryProperties Public Methods

The OracleXmlQueryProperties public methods are listed in [Table 6-4](#).

**Table 6-4 OracleXmlQueryProperties Public Methods**

Name	Description
<a href="#">Clone</a>	Creates a copy of an OracleXmlQueryProperties object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlQueryProperties Class](#)

## OracleXmlQueryProperties Constructor

The `OracleXmlQueryProperties` constructor instantiates a new instance of the `OracleXmlQueryProperties` class.

### Declaration

```
// C#  
public OracleXmlQueryProperties();
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

## OracleXmlQueryProperties Properties

The `OracleXmlQueryProperties` properties are listed in [Table 6–5](#).

**Table 6–5 OracleXmlQueryProperties Properties**

Name	Description
<a href="#">MaxRows</a>	Specifies the maximum number of rows from the result set of the query that can be represented in the result XML document
<a href="#">RootTag</a>	Specifies the root element of the result XML document
<a href="#">RowTag</a>	Specifies the value of the XML element which identifies a row of data from the result set in an XML document
<a href="#">Xslt</a>	Specifies the XSL document used for XML transformation using XSLT
<a href="#">XsltParams</a>	Specifies parameters for the XSL document

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

## MaxRows

This property specifies the maximum number of rows from the result set of the query that can be represented in the result XML document.

### Declaration

```
// C#
public int MaxRows {get; set;}
```

### Property Value

The maximum number of rows.

### Exceptions

`ArgumentException` - The new value for `MaxRows` is not valid.

### Remarks

Default value is -1.

Possible values are:

- -1 (all rows).
- A number greater than or equal to 0.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

## RootTag

This property specifies the root element of the result XML document.

### Declaration

```
// C#  
public string RootTag {get; set;}
```

### Property Value

The root element of the result XML document.

### Remarks

The default root tag is ROWSET.

To indicate that no root tag is be used in the result XML document, set this property to null or " " or `String.Empty`.

If both `RootTag` and `RowTag` are set to null, an XML document is returned only if the result set returns one row and one column.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

## RowTag

This property specifies the value of the XML element which identifies a row of data from the result set in an XML document.

### Declaration

```
// C#  
public string RowTag {get; set;}
```

### Property Value

The value of the XML element.

### Remarks

The default is ROW.

To indicate that no row tag is be used in the result XML document, set this property to null or " " or `String.Empty`.

If both `RootTag` and `RowTag` are set to null, an XML document is returned only if the result set returns one row and one column.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

## Xslt

This property specifies the XSL document used for XML transformation using XSLT.



**Declaration**

```
// C#  
public string Xslt {get; set;}
```

**Property Value**

The XSL document used for XML transformation.

**Remarks**

Default value is null.

The XSL document is used for XML transformation of the XML document generated from the result set of the query.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

**XsltParams**

This property specifies parameters for the XSL document.

**Declaration**

```
// C#  
public string XsltParams {get; set;}
```

**Property Value**

The parameters for the XSL document.

**Remarks**

Default value is null.

The parameters are specified as a string of "name=value" pairs of the form "param1=value1; param2=value2; ..." delimited by semicolons.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

## OracleXmlQueryProperties Public Methods

The `OracleXmlQueryProperties` public methods are listed in [Table 6–6](#).

**Table 6–6 OracleXmlQueryProperties Public Methods**

Name	Description
<a href="#">Clone</a>	Creates a copy of an <code>OracleXmlQueryProperties</code> object

### Clone

This method creates a copy of an `OracleXmlQueryProperties` object.

#### Declaration

```
// C#  
public object Clone();
```

#### Return Value

An `OracleXmlQueryProperties` object

#### Implements

`ICloneable`

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

---

## OracleXmlSaveProperties Class

An `OracleXmlSaveProperties` object represents the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.

### Class Inheritance

`System.Object`

`System.OracleXmlSaveProperties`

### Declaration

```
public sealed class OracleXmlSaveProperties : ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

`OracleXmlSaveProperties` can be accessed and modified using the `XmlSaveProperties` property of the `OracleCommand` class. Each `OracleCommand` object has its own instance of the `OracleXmlSaveProperties` class in the `XmlSaveProperties` property.

Use the default constructor to get a new instance of `OracleXmlSaveProperties`. Use the `OracleXmlSaveProperties.Clone()` method to get a copy of an `OracleXmlSaveProperties` instance.

### Example

This sample demonstrates how to do inserts, updates, and deletes to a relational table or view using an XML document.

```
// C#
/* -- If HR account is being locked, you need to log on as a DBA
   -- to unlock the account first. Unlock a locked users account:

ALTER USER hr ACCOUNT UNLOCK;
*/

using System;
using Oracle.DataAccess.Client;

class OracleXmlSavePropertiesSample
{
    static void Main()
    {
        string[] KeyColumnsList = null;
        string[] UpdateColumnsList = null;
        int rows = 0;

        // Create the connection.
        string constr = "User Id=hr;Password=hr;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
```

```
// Create the command.
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to insert.
cmd.XmlCommandType = OracleXmlCommandType.Insert;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Smith</LAST_NAME>\n" +
    "    <EMAIL>Smith@Oracle.com</EMAIL>\n" +
    "    <HIRE_DATE>1982-01-23T00:00:00.000</HIRE_DATE>\n" +
    "    <JOB_ID>IT_PROG</JOB_ID>\n" +
    "  </MYROW>\n" +
    "  <MYROW num = \"2\">\n" +
    "    <EMPLOYEE_ID>1235</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Barney</LAST_NAME>\n" +
    "    <EMAIL>Barney@Oracle.com</EMAIL>\n" +
    "    <HIRE_DATE>1982-01-23T00:00:00.000</HIRE_DATE>\n" +
    "    <JOB_ID>IT_PROG</JOB_ID>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
KeyColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList = new string[5];
UpdateColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList[1] = "LAST_NAME";
UpdateColumnsList[2] = "EMAIL";
UpdateColumnsList[3] = "HIRE_DATE";
UpdateColumnsList[4] = "JOB_ID";
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.RowTag = "MYROW";
cmd.XmlSaveProperties.Table = "employees";
cmd.XmlSaveProperties.UpdateColumnsList = UpdateColumnsList;
cmd.XmlSaveProperties.Xslt = null;
cmd.XmlSaveProperties.XsltParams = null;

// Do the inserts.
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Set the XML command type to update.
cmd.XmlCommandType = OracleXmlCommandType.Update;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Adams</LAST_NAME>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
```

```

KeyColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList = new string[1];
UpdateColumnsList[0] = "LAST_NAME";
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.UpdateColumnsList = UpdateColumnsList;
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Set the XML command type to delete.
cmd.XmlCommandType = OracleXmlCommandType.Delete;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "  </MYROW>\n" +
    "  <MYROW num = \"2\">\n" +
    "    <EMPLOYEE_ID>1235</EMPLOYEE_ID>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
KeyColumnsList[0] = "EMPLOYEE_ID";
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.UpdateColumnsList = null;

// Do the deletes.
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Clean up.
cmd.Dispose();
con.Close();
con.Dispose();
}
}

```

## Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlSaveProperties Members](#)
- [OracleXmlSaveProperties Constructor](#)
- [OracleXmlSaveProperties Properties](#)
- [OracleXmlSaveProperties Public Methods](#)

## OracleXmlSaveProperties Members

OracleXmlSaveProperties members are listed in the following tables.

### OracleXmlSaveProperties Constructor

OracleXmlSaveProperties constructors are listed in [Table 6-7](#)

**Table 6-7 OracleXmlSaveProperties Constructor**

Constructor	Description
<a href="#">OracleXmlSaveProperties Constructor</a>	Instantiates a new instance of the OracleXmlSaveProperties class

### OracleXmlSaveProperties Properties

The OracleXmlSaveProperties properties are listed in [Table 6-8](#).

**Table 6-8 OracleXmlSaveProperties Properties**

Name	Description
<a href="#">KeyColumnsList</a>	Specifies the list of columns used as a key to locate existing rows for update or delete using an XML document
<a href="#">RowTag</a>	Specifies the value for the XML element that identifies a row of data in an XML document
<a href="#">Table</a>	Specifies the name of the table or view to which changes are saved
<a href="#">UpdateColumnsList</a>	Specifies the list of columns to update or insert
<a href="#">Xslt</a>	Specifies the XSL document used for XML transformation using XSLT
<a href="#">XsltParams</a>	Specifies the parameters for the XSLT document specified in the Xslt property

### OracleXmlSaveProperties Public Methods

The OracleXmlSaveProperties public methods are listed in [Table 6-9](#).

**Table 6-9 OracleXmlSaveProperties Public Methods**

Name	Description
<a href="#">Clone</a>	Creates a copy of an OracleXmlSaveProperties object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## OracleXmlSaveProperties Constructor

The `OracleXmlSaveProperties` constructor instantiates a new instance of `OracleXmlSaveProperties` class.

### Declaration

```
// C#  
public OracleXmlSaveProperties;
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## OracleXmlSaveProperties Properties

The `OracleXmlSaveProperties` properties are listed in [Table 6–10](#).

**Table 6–10 OracleXmlSaveProperties Properties**

Name	Description
<a href="#">KeyColumnsList</a>	Specifies the list of columns used as a key to locate existing rows for update or delete using an XML document
<a href="#">RowTag</a>	Specifies the value for the XML element that identifies a row of data in an XML document
<a href="#">Table</a>	Specifies the name of the table or view to which changes are saved
<a href="#">UpdateColumnsList</a>	Specifies the list of columns to update or insert
<a href="#">Xslt</a>	Specifies the XSL document used for XML transformation using XSLT
<a href="#">XsltParams</a>	Specifies the parameters for the XSLT document specified in the <code>Xslt</code> property

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

### KeyColumnsList

This property specifies the list of columns used as a key to locate existing rows for update or delete using an XML document.

**Declaration**

```
// C#
public string[] KeyColumnsList {get; set;}
```

**Property Value**

The list of columns.

**Remarks**

Default value is null.

The first null value (if any) terminates the list.

`KeyColumnsList` usage with `XMLCommandType` property values:

- `Insert` - `KeyColumnsList` is ignored and can be null.
- `Update` - `KeyColumnsList` must be specified; it identifies the columns to use to find the rows to be updated.
- `Delete` - If `KeyColumnsList` is null, all the column values in each row element in the XML document are used to locate the rows to delete. Otherwise, `KeyColumnsList` specifies the columns used to identify the rows to delete.



**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## RowTag

This property specifies the value for the XML element that identifies a row of data in an XML document.

**Declaration**

```
// C#  
public string RowTag {get; set;}
```

**Property Value**

An XML element name.

**Remarks**

The default value is ROW.

Each element in the XML document identifies one row in a table or view.

If RowTag is set to " " or null, no row tag is used in the XML document. In this case, the XML document is assumed to contain only one row.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## Table

This property specifies the name of the table or view to which changes are saved.

**Declaration**

```
// C#  
public string Table {get; set;}
```

**Property Value**

A table name.

**Remarks**

Default value is null.

The property must be set to a valid table or view name.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## UpdateColumnsList

This property specifies the list of columns to update or insert.

### Declaration

```
// C#  
public string[] UpdateColumnsList {get; set;}
```

### Property Value

A list of columns.

### Remarks

Default value is null.

The first null value (if any) terminates the list.

UpdateColumnList usage with XMLCommandType property values:

- Insert - UpdateColumnList indicates which columns are assigned values when a new row is created. If UpdateColumnList is null, then all columns are assigned values. If a column is on the UpdateColumnList, but no value is specified for the row in the XML file, then NULL is used. If a column is not on the UpdateColumnList, then the default value for that column is used.
- Update - UpdateColumnList specifies columns to modify for each row of data in the XML document. If UpdateColumnList is null, all the values in each XML element in the XML document are used to modify the columns.
- Delete - UpdateColumnsList is ignored and can be null.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## Xslt

This property specifies the XSL document used for XML transformation using XSLT.

### Declaration

```
// C#  
public string Xslt {get; set;}
```

### Property Value

The XSL document used for XML transformation.

### Remarks

Default = null.

The XSL document is used for XSLT transformation of a given XML document. The transformed XML document is used to save changes to the table or view.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

**XsltParams**

This property specifies the parameters for the XSLT document specified in the `Xslt` property.

**Declaration**

```
// C#  
public string XsltParams {get; set;}
```

**Property Value**

The parameters for the XSLT document.

**Remarks**

Default is null.

This property is a string delimited by semicolons in "name=value" pairs of the form "param1=value1; param2=value2; ...".

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

## OracleXmlSaveProperties Public Methods

The `OracleXmlSaveProperties` public methods are listed in [Table 6–11](#).

**Table 6–11** *OracleXmlSaveProperties Public Methods*

Name	Description
<a href="#">Clone</a>	Creates a copy of an <code>OracleXmlSaveProperties</code> object

### Clone

This method creates a copy of an `OracleXmlSaveProperties` object.

#### Declaration

```
// C#  
public object Clone();
```

#### Return Value

An `OracleXmlSaveProperties` object

#### Implements

`ICloneable`

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

---

## OracleXmlStream Class

An `OracleXmlStream` object represents a read-only stream of XML data stored in an `OracleXmlType` object.

### Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.Stream
            System.OracleXmlStream
```

### Declaration

```
// C#
public sealed class OracleXmlStream : IDisposable, ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Members](#)
- [OracleXmlStream Constructor](#)
- [OracleXmlStream Static Methods](#)
- [OracleXmlStream Instance Properties](#)
- [OracleXmlStream Instance Methods](#)

## OracleXmlStream Members

OracleXmlStream members are listed in the following tables.

### OracleXmlStream Constructors

The OracleXmlStream constructors are listed in [Table 6–12](#).

**Table 6–12 OracleXmlStream Constructors**

Constructor	Description
<a href="#">OracleXmlStream Constructor</a>	Creates an instance of an OracleXmlStream object which provides a Stream representation of the XML data stored in an OracleXmlType

### OracleXmlStream Static Methods

The OracleXmlStream static methods are listed in [Table 6–13](#).

**Table 6–13 OracleXmlStream Static Methods**

Methods	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleXmlStream Instance Properties

The OracleXmlStream instance properties are listed in [Table 6–14](#).

**Table 6–14 OracleXmlStream Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the XML stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operation can be performed
<a href="#">CanWrite</a>	<i>Not Supported</i>
<a href="#">Connection</a>	Indicates the OracleConnection that is used to retrieve the XML data
<a href="#">Length</a>	Indicates the number of bytes in the XML stream
<a href="#">Position</a>	Gets or sets the byte position within the stream
<a href="#">Value</a>	Returns the XML data, starting from the first character in the stream as a string

### OracleXmlStream Instance Methods

The OracleXmlStream instance methods are listed in [Table 6–15](#).

**Table 6–15 OracleXmlStream Instance Methods**

Methods	Description
<a href="#">BeginRead</a>	Inherited from System.IO.Stream
<a href="#">BeginWrite</a>	Inherited from System.IO.Stream
<a href="#">Clone</a>	Creates a copy of an OracleXmlStream object
<a href="#">Close</a>	Closes the current stream and releases any resources associated with it

**Table 6–15 (Cont.) OracleXmlStream Instance Methods**

<b>Methods</b>	<b>Description</b>
<a href="#">Dispose</a>	Releases resources allocated by this object
EndRead	Inherited from <code>System.IO.Stream</code>
EndWrite	Inherited from <code>System.IO.Stream</code>
Equals	Inherited from <code>System.Object</code>
Flush	<i>Not Supported</i>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Read</a>	Reads a specified amount from the current stream instance and populates the array buffer (Overloaded)
ReadByte	Inherited from <code>System.IO.Stream</code>
<a href="#">Seek</a>	Sets the position within the current stream and returns the new position within the current stream
SetLength	<i>Not Supported</i>
ToString	Inherited from <code>System.Object</code>
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)

## OracleXmlStream Constructor

This constructor creates an instance of an `OracleXmlStream` object which provides a Stream representation of the XML data stored in an `OracleXmlType` object.

### Declaration

```
// C#  
public OracleXmlStream(OracleXmlType xmlType);
```

### Parameters

- *xmlType*  
The `OracleXmlType` object.

### Remarks

The `OracleXmlStream` implicitly uses the `OracleConnection` object from the `OracleXmlType` object from which it was constructed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)



## OracleXmlStream Static Methods

The `OracleXmlStream` static methods are listed in [Table 6-16](#).

**Table 6-16** *OracleXmlStream Static Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

## OracleXmlStream Instance Properties

The `OracleXmlStream` instance properties are listed in [Table 6–17](#).

**Table 6–17 OracleXmlStream Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the XML stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operation can be performed
<code>CanWrite</code>	<i>Not Supported</i>
<a href="#">Connection</a>	Indicates the <code>OracleConnection</code> that is used to retrieve the XML data
<a href="#">Length</a>	Indicates the number of bytes in the XML stream
<a href="#">Position</a>	Gets or sets the byte position within the stream
<a href="#">Value</a>	Returns the XML data, starting from the first character in the stream as a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

### CanRead

Overrides `Stream`

This property indicates whether or not the XML stream can be read.

**Declaration**

```
// C#
public override bool CanRead{get;}
```

**Property Value**

If the XML stream is can be read, returns `true`; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

### CanSeek

Overrides `Stream`

This property indicates whether or not forward and backward seek operation can be performed.

**Declaration**

```
// C#
```

```
public override bool CanSeek{get;}
```

### Property Value

If forward and backward seek operations can be performed, this property returns true. Otherwise, returns false.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

## Connection

This instance property indicates the `OracleConnection` that is used to retrieve the XML data.

### Declaration

```
// C#  
public OracleConnection Connection {get;}
```

### Property Value

An `OracleConnection`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

## Length

Overrides `Stream`

This property indicates the number of bytes in the XML stream.

### Declaration

```
// C#  
public override Int64 Length{get;}
```

### Property Value

An `Int64` value representing the number of bytes in the XML stream. An empty stream has a length of 0 bytes.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Position**

Overrides Stream

This property gets or sets the byte position within the stream.

**Declaration**

```
// C#  
public override Int64 Position{get; set;}
```

**Property Value**

An `Int64` that indicates the current position in the stream.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.

**Remarks**

The beginning of the stream is represented by position 0. Seeking to any location beyond the length of the stream is supported.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Value**

This property returns the XML data, starting from the first character of the stream as a string.

**Declaration**

```
// C#  
public string Value{get; set;}
```

**Property Value**

A `string`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The value of `Position` is neither used nor changed by using this property.

The maximum length of the string that can be returned by this property is 2 GB.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

## OracleXmlStream Instance Methods

The `OracleXmlStream` instance methods are listed in [Table 6–18](#).

**Table 6–18 OracleXmlStream Instance Methods**

Methods	Description
<code>BeginRead</code>	Inherited from <code>System.IO.Stream</code>
<code>BeginWrite</code>	Inherited from <code>System.IO.Stream</code>
<a href="#">Clone</a>	Creates a copy of an <code>OracleXmlStream</code> object
<a href="#">Close</a>	Closes the current stream and releases any resources associated with it
<a href="#">Dispose</a>	Releases resources allocated by this object
<code>EndRead</code>	Inherited from <code>System.IO.Stream</code>
<code>EndWrite</code>	Inherited from <code>System.IO.Stream</code>
<code>Equals</code>	Inherited from <code>System.Object</code>
<code>Flush</code>	<i>Not Supported</i>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Read</a>	Reads a specified amount from the current XML stream instance and populates the array buffer (Overloaded)
<code>ReadByte</code>	Inherited from <code>System.IO.Stream</code>
<a href="#">Seek</a>	Sets the position within the current stream and returns the new position within the current stream
<code>SetLength</code>	<i>Not Supported</i>
<code>ToString</code>	Inherited from <code>System.Object</code>
<code>Write</code>	<i>Not Supported</i>
<code>WriteByte</code>	<i>Not Supported</i>

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

### Clone

This method creates a copy of an `OracleXmlStream` object.

**Declaration**

```
// C#
public object Clone();
```

**Return Value**

An OracleXmlStream object.

**Implements**

ICloneable

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Close**

Overrides Stream

This method closes the current stream and releases any resources associated with it.

**Declaration**

```
// C#  
public override void Close();
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Dispose**

This public method releases resources allocated by this object.

**Declaration**

```
// C#  
public void Dispose();
```

**Implements**

IDisposable

**Remarks**

The object cannot be reused after being disposed. Although some properties can still be accessed, their values cannot be accountable. Since resources are freed, method calls can lead to exceptions.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Read**

This method reads a specified amount from the current XML stream instance and populates the array buffer.

**Overload List:**

- [Read\(byte\[ \], int, int\)](#)

This method reads a specified amount of unicode bytes from the current instance, advances the position within the stream, and populates the byte array buffer.

- [Read\(char\[ \], int, int\)](#)

This method reads a specified amount of characters from the current instance, advances the position within the stream, and populates the character array buffer.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Read(byte[ ], int, int)**

Overrides `Stream`

This method reads a specified amount of unicode bytes from the current instance, advances the position within the stream, and populates the byte array buffer.

**Declaration**

```
// C#  
public override int Read(byte[ ] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
The byte array buffer that is populated.
- *offset*  
The zero-based offset (in bytes) at which the buffer is populated.
- *count*  
The maximum amount of bytes to be read.

**Return Value**

The number of unicode bytes read into the given `byte[ ]` buffer or 0 if the end of the stream has been reached.



**Remarks**

This method reads a maximum of *count* bytes from the current stream and stores them in buffer beginning at *offset*. The current position within the stream is advanced by the number of bytes read. However, if an exception occurs, the current position within the stream remains unchanged.

The XML data is read starting from the position specified by the `Position` property.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

**Read(char[ ], int, int)**

Overrides `Stream`

This method reads a specified amount of characters from the current instance, advances the position within the stream, and populates the character array buffer.

**Declaration**

```
// C#  
public override int Read(char[ ] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
The character array buffer to be populated.
- *offset*  
The zero-based offset (in characters) in the buffer at which the buffer is populated.
- *count*  
The maximum amount of characters to be read from the stream.

**Return Value**

The return value indicates the number of characters read from the stream or 0 if the end of the stream has been reached.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

This method requires that the `Position` on the stream instance be zero or an even number.

The XML data is read starting from the position specified by the `Position` property.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

## Seek

Overrides `Stream`.

This method sets the position within the current stream and returns the new position within the current stream.

### Declaration

```
// C#  
public long Seek(long offset, SeekOrigin origin);
```

### Parameters

- *offset*  
A byte offset relative to origin.
  - If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.
  - If *offset* is zero, the new position is the position specified by *origin*.
  - If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.
- *origin*  
A value of type `SeekOrigin` indicating the reference point used to obtain the new position.

### Return Value

The new `Position` within the current stream.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object

### Remarks

Use the `CanSeek` property to determine whether or not the current instance supports seeking. Seeking to any location beyond the length of the stream is supported.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

---

## OracleXmlType Class

An `OracleXmlType` object represents an Oracle `XMLType` instance.

### Class Inheritance

`System.Object`

`System.OracleXmlType`

### Declaration

```
// C#  
public sealed class OracleXmlType : IDisposable, INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

`OracleXmlType` objects can be used for well-formed XML documents with or without XML schemas or XML fragments.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Members](#)
- [OracleXmlType Constructors](#)
- [OracleXmlType Static Methods](#)
- [OracleXmlType Instance Properties](#)
- [OracleXmlType Instance Methods](#)

## OracleXmlType Members

OracleXmlType members are listed in the following tables.

### OracleXmlType Constructors

The OracleXmlType constructors are listed in [Table 6–19](#).

**Table 6–19 OracleXmlType Constructors**

Constructor	Description
<a href="#">OracleXmlType Constructors</a>	Creates an instance of the OracleXmlType class (Overloaded)

### OracleXmlType Static Methods

The OracleXmlType static methods are listed in [Table 6–20](#).

**Table 6–20 OracleXmlType Static Methods**

Methods	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleXmlType Instance Properties

The OracleXmlType instance properties are listed in [Table 6–21](#).

**Table 6–21 OracleXmlType Instance Properties**

Properties	Description
<a href="#">Connection</a>	Indicates the OracleConnection that is used to retrieve and store XML data in the OracleXmlType
<a href="#">IsEmpty</a>	Indicates whether or not the OracleXmlType is empty
<a href="#">IsFragment</a>	Indicates whether the XML data is a collection of XML elements or a well-formed XML document
<a href="#">IsSchemaBased</a>	Indicates whether or not the XML data represented by the OracleXmlType is based on an XML schema
<a href="#">RootElement</a>	Represents the name of the top-level element of the schema-based XML data contained in the OracleXmlType
<a href="#">Schema</a>	Represents the XML schema of the XML data contained in the OracleXmlType
<a href="#">SchemaUrl</a>	Represents in the database for the XML schema of the XML data contained in the OracleXmlType.
<a href="#">Value</a>	Returns the XML data starting from the first character in the current instance as a string

### OracleXmlType Instance Methods

The OracleXmlType instance methods are listed in [Table 6–22](#).

**Table 6–22 OracleXmlType Instance Methods**

Methods	Description
<a href="#">Clone</a>	Creates a copy of the OracleXmlType instance
<a href="#">Dispose</a>	Releases the resources allocated by this OracleXmlType object

**Table 6–22 (Cont.) OracleXmlType Instance Methods**

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
<code>Extract</code>	Extracts a subset from the XML data using the given XPath expression (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetStream</code>	Returns an instance of <code>OracleXmlStream</code> which provides a read-only stream of the XML data stored in this <code>OracleXmlType</code> instance
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>GetXmlDocument</code>	Returns a <code>XmlDocument</code> object containing the XML data stored in this <code>OracleXmlType</code> instance
<code>GetXmlReader</code>	Returns a <code>XmlTextReader</code> object that can be used to manipulate XML data directly using the .NET Framework classes and methods
<code>IsExists</code>	Checks for the existence of a particular set of nodes identified by the given XPath expression in the XMLdata (Overloaded)
<code>ToString</code>	Inherited from <code>System.Object</code>
<code>Transform</code>	Transforms the <code>OracleXmlType</code> into another <code>OracleXmlType</code> instance using the given XSL document (Overloaded)
<code>Update</code>	Updates the XML node or fragment identified by the given XPath expression in the current <code>OracleXmlType</code> instance (Overloaded)
<code>Validate</code>	Validates whether or not the XML data in the <code>OracleXmlType</code> object conforms to the given XML schema.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)

## OracleXmlType Constructors

OracleXmlType constructors create instances of the OracleXmlType class.

### Overload List:

- [OracleXmlType\(OracleClob\)](#)

This constructor creates an instance of the OracleXmlType class using the XML data contained in an OracleClob object.

- [OracleXmlType\(OracleConnection, string\)](#)

This constructor creates an instance of the OracleXmlType class using the XML data contained in the .NET String.

- [OracleXmlType\(OracleConnection, XmlReader\)](#)

This constructor creates an instance of the OracleXmlType class using the contents of the .NET XmlReader object.

- [OracleXmlType\(OracleConnection, XmlDocument\)](#)

This constructor creates an instance of the OracleXmlType object using the contents of the XML **DOM** document in the .NET XmlDocument object.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

### OracleXmlType(OracleClob)

This constructor creates an instance of the OracleXmlType class using the XML data contained in an OracleClob object.

### Declaration

```
// C#  
public OracleXmlType(OracleClob oraClob);
```

### Parameters

- *oraClob*  
An OracleClob object.

### Exceptions

ArgumentNullException - The OracleClob object is null.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

### Remarks

The CLOB data depends on a valid connection object and the new OracleXMLType uses the OracleConnection in the OracleClob object to store data for the current instance.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**OracleXmlType(OracleConnection, string)**

This constructor creates an instance of the `OracleXmlType` class using the XML data contained in the .NET `String`.

**Declaration**

```
// C#  
public OracleXmlType(OracleConnection con, string xmlData);
```

**Parameters**

- *con*  
An `OracleConnection` object.
- *xmlData*  
A string containing the XML data.

**Exceptions**

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The `xmlData` argument is an empty string.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The new `OracleXmlType` uses the given `OracleConnection` object to store data for the current instance.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**OracleXmlType(OracleConnection, XmlReader)**

This constructor creates an instance of the `OracleXmlType` class using the contents of the .NET `XmlReader` object.

**Declaration**

```
// C#  
public OracleXmlType(OracleConnection con, XmlReader reader);
```

**Parameters**

- *con*  
An `OracleConnection` object.

- *reader*

An `XmlReader` object.

### Exceptions

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The *reader* argument contains no data.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The new `OracleXMLType` uses the given `OracleConnection` object to store data for the current instance.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## OracleXmlType(OracleConnection, XmlDocument)

This constructor creates an instance of the `OracleXmlType` object using the contents of the XML **DOM** document in the `.NET XmlDocument` object.

### Declaration

```
// C#  
public OracleXmlType(OracleConnection con, XmlDocument domDoc);
```

### Parameters

- *con*  
An `OracleConnection` object.
- *domDoc*  
An XML document.

### Exceptions

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The *domDoc* argument contains no data.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The new `OracleXMLType` uses the given `OracleConnection` object to store data for the current instance.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)



## OracleXmlType Static Methods

The OracleXmlType static methods are listed in [Table 6-23](#).

**Table 6-23 OracleXmlType Static Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## OracleXmlType Instance Properties

The `OracleXmlType` instance properties are listed in [Table 6–24](#).

**Table 6–24 OracleXmlType Instance Properties**

Properties	Description
<a href="#">Connection</a>	Indicates the <code>OracleConnection</code> that is used to retrieve and store XML data in the <code>OracleXmlType</code>
<a href="#">IsEmpty</a>	Indicates whether or not the <code>OracleXmlType</code> is empty
<a href="#">IsFragment</a>	Indicates whether the XML data is a collection of XML elements or a well-formed XML document
<a href="#">IsSchemaBased</a>	Indicates whether or not the XML data represented by the <code>OracleXmlType</code> is based on an XML schema
<a href="#">RootElement</a>	Represents the name of the top-level element of the schema-based XML data contained in the <code>OracleXmlType</code>
<a href="#">Schema</a>	Represents the XML schema of the XML data contained in the <code>OracleXmlType</code>
<a href="#">SchemaUrl</a>	Represents <b>URL</b> in the database for the XML schema of the XML data contained in the <code>OracleXmlType</code>
<a href="#">Value</a>	Returns the XML data starting from the first character in the current instance as a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

### Connection

This property indicates the `OracleConnection` that is used to retrieve and store XML data in the `OracleXmlType`.

**Declaration**

```
// C#
public OracleConnection Connection {get;}
```

**Property Value**

An `OracleConnection` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The connection must explicitly be opened by the user before creating or using `OracleXmlType`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## IsEmpty

This property indicates whether or not the `OracleXmlType` is empty.

**Declaration**

```
// C#  
public bool IsEmpty {get;}
```

**Property Value**

Returns `true` if the `OracleXmlType` represents an empty XML document. Returns `false` otherwise.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## IsFragment

This property indicates whether the XML data is a collection of XML elements or a well-formed XML document.

**Declaration**

```
// C#  
public bool IsFragment {get;}
```

**Property Value**

Returns `true` if the XML data contained in the `OracleXmlType` object is a collection of XML elements with no root element. Returns `false` otherwise.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## IsSchemaBased

This property indicates whether or not the XML data represented by the `OracleXmlType` is based on an XML schema.

### Declaration

```
// C#  
public bool IsSchemaBased {get;}
```

### Property Value

Returns `true` if the XML data represented by the `OracleXmlType` is based on an XML schema. Returns `false` otherwise.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## RootElement

This property represents the name of the top-level or root element of the schema-based XML data contained in the `OracleXmlType`.

### Declaration

```
// C#  
public string RootElement{get;}
```

### Property Value

A string that represents the name of the top-level or root element of the XML data contained in the `OracleXmlType`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

### Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an empty string.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Schema

This property represents the XML schema for the XML data contained in the `OracleXmlType`.

**Declaration**

```
// C#  
public OracleXmlType Schema {get;}
```

**Property Value**

An `OracleXmlType` instance that represents the XML schema for the XML data contained in the `OracleXmlType`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an `OracleXmlType` instance representing an empty XML document.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**SchemaUrl**

This property represents the XML schema in the database for the XML schema of the XML data contained in the `OracleXmlType`.

**Declaration**

```
// C#  
public string SchemaUrl {get;}
```

**Property Value**

A string that represents the URL in the database for the XML schema of the XML data.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**Value**

This property returns the XML data starting from the first character in the current instance as a `string`.

### Declaration

```
// C#  
public string RootElement{get;}
```

### Property Value

The entire XML data as a string.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## OracleXmlType Instance Methods

The `OracleXmlType` instance methods are listed in [Table 6–25](#).

**Table 6–25 OracleXmlType Instance Methods**

Methods	Description
<a href="#">Clone</a>	Creates a copy of the <code>OracleXmlType</code> instance
<a href="#">Dispose</a>	Releases the resources allocated by this <code>OracleXmlType</code> object
<code>Equals</code>	Inherited from <code>System.Object</code>
<a href="#">Extract</a>	Extracts a subset from the XML data using the given XPath expression (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<a href="#">GetStream</a>	Returns an instance of <code>OracleXmlStream</code> which provides a read-only stream of the XML data stored in this <code>OracleXmlType</code> instance
<code>GetType</code>	Inherited from <code>System.Object</code>
<a href="#">GetXmlDocument</a>	Returns a <code>XmlDocument</code> object containing the XML data stored in this <code>OracleXmlType</code> instance
<a href="#">GetXmlReader</a>	Returns a <code>XmlTextReader</code> object that can be used to manipulate XML data directly using the .NET Framework classes and methods
<a href="#">IsExists</a>	Checks for the existence of a particular set of nodes identified by the given XPath expression in the XML data (Overloaded)
<code>ToString</code>	Inherited from <code>System.Object</code>
<a href="#">Transform</a>	Transforms the <code>OracleXmlType</code> into another <code>OracleXmlType</code> instance using the given XSL document (Overloaded)
<a href="#">Update</a>	Updates the XML node or fragment identified by the given XPath expression in the current <code>OracleXmlType</code> instance (Overloaded)
<a href="#">Validate</a>	Validates whether or not the XML data in the <code>OracleXmlType</code> object conforms to the given XML schema.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Clone

This method creates a copy of this `OracleXmlType` instance.

### Declaration

```
// C#
public object Clone();
```

### Implements

`ICloneable`

**Return Value**

An `OracleXmlType` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**Dispose**

This method releases the resources allocated by this object.

**Declaration**

```
// C#  
public void Dispose();
```

**Implements**

`IDisposable`

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**Extract**

This method extracts a subset from the XML data using the given XPath expression.

**Overload List:**

- [Extract\(string, string\)](#)

This method extracts a subset from the XML data represented by the `OracleXmlType` object using the given XPath expression and a string parameter for namespace resolution.

- [Extract\(string, XmlNameSpaceManager\)](#)

This method extracts a subset from the XML data represented by the `OracleXmlType` object, using the given XPath expression and a `.NET XmlNameSpaceManager` object for namespace resolution.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)



## Extract(string, string)

This method extracts a subset from the XML data represented by the `OracleXmlType` object using the given XPath expression and a string parameter for namespace resolution.

### Declaration

```
// C#
public OracleXmlType Extract(string xpathExpr, string nsMap);
```

### Parameters

- *xpathExpr*  
The XPath expression.
- *nsMap*  
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null. For example:

```
xmlns:nsi="http://www.company1.com" xmlns:nsz="http://www.company2.com"
```

### Return Value

An `OracleXmlType` object.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Extract(string, XmlNamespaceManager)

This public method extracts a subset from the XML data represented by the `OracleXmlType` object, using the given XPath expression and a .NET `XmlNamespaceManager` object for namespace resolution.

### Declaration

```
// C#
public OracleXmlType Extract(string xpathExpr, XmlNamespaceManager nsMgr);
```

### Parameters

- *xpathExpr*  
The XPath expression.
- *nsMgr*

The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. `nsMgr` can be null.

**Return Value**

An `OracleXmlType`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The `xpathExpr` is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The default namespace is ignored if its value is an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## GetStream

This public method returns an instance of `OracleXmlStream` which provides a read-only stream of the XML data stored in this `OracleXmlType` instance.

**Declaration**

```
// C#  
public Stream GetStream();
```

**Return Value**

A `Stream` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## GetXmlDocument

This public method returns a `XmlDocument` object containing the XML data stored in this `OracleXmlType` instance.

**Declaration**

```
// C#  
public XmlDocument GetXmlDocument();
```

**Return Value**

An `XmlDocument` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The XML data in the `XmlDocument` object is a copy of the XML data in the `OracleXmlType` instance and modifying it does not automatically modify the XML data in the `OracleXmlType` instance. The `XmlDocument` instance returned has the `PreserveWhitespace` property set to `true`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**GetXmlReader**

This public method returns a `XmlTextReader` object that can be used to manipulate XML data directly using the .NET Framework classes and methods.

**Declaration**

```
// C#  
public XmlTextReader GetXmlReader();
```

**Return Value**

An `XmlTextReader` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The `XmlTextReader` is a read-only, forward-only representation of the XML data stored in the `OracleXmlType` instance.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**IsExists**

`IsExists` checks for the existence of a particular set of nodes identified by the XPath expression in the XML data.

**Overload List:**■ [IsExists\(string, string\)](#)

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML data represented by the current `OracleXmlType` instance using a string parameter for namespace resolution.

■ [IsExists\(string, XmlNamespaceManager\)](#)

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML document represented by the current `OracleXmlType` instance using a .NET `XmlNamespaceManager` object for namespace resolution.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**IsExists(string, string)**

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML data represented by the current `OracleXmlType` instance using a string parameter for namespace resolution.

**Declaration**

```
// C#  
public bool IsExists(string xpathExpr, string nsMap);
```

**Parameters**

- *xpathExpr*  
The XPath expression.
- *nsMap*  
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null.

**Return Value**

Returns `true` if the required set of nodes exists; otherwise, returns `false`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The default namespace is ignored if its value is an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**IsExists(string, XmlNameSpaceManager)**

This method checks the existence of a particular set of nodes identified by the XPath expression in the XML document represented by the current `OracleXmlType` instance using a .NET `XmlNameSpaceManager` object for namespace resolution.

**Declaration**

```
// C#
public bool IsExists(string xpathExpr, XmlNameSpaceManager nsMgr);
```

**Parameters**

- *xpathExpr*  
The XPath expression.
- *nsMgr*  
The .NET `XmlNameSpaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.

**Return Value**

Returns `true` if the required set of nodes exists; otherwise, returns `false`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The default namespace is ignored if its value is an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**Transform**

This method transforms the `OracleXmlType` into another `OracleXmlType` instance using the given XSL document.

**Overload List:**

- [Transform\(OracleXmlType, string\)](#)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document (as an `OracleXmlType` object) and a string of XSLT parameters.

- [Transform\(string, string\)](#)

This public method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Transform(OracleXmlType, string)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

**Declaration**

```
// C#  
public OracleXmlType Transform(OracleXmlType xslDoc, string paramMap);
```

**Parameters**

- *xslDoc*  
The XSL document as an `OracleXmlType` object.
- *paramMap*  
A string which provides the parameters for the XSL document.  
For this release, *paramMap* is ignored.

**Return Value**

An `OracleXmlType` object containing the transformed XML document.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xslDoc* parameter is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Transform(string, string)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

### Declaration

```
// C#
public OracleXmlType Transform(string xslDoc, string paramMap);
```

### Parameters

- *xslDoc*  
The XSL document to be used for XSLT.
- *paramMap*  
A string which provides the parameters for the XSL document.  
For this release, *paramMap* is ignored.

### Return Value

An `OracleXmlType` object containing the transformed XML document.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xslDoc* parameter is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Update

This method updates the XML node or fragment identified by the given XPath expression in the current `OracleXmlType` instance.

### Overload List:

- [Update\(string, string, string\)](#)  
This method updates the XML nodes identified by the given XPath expression with the given string value and a string parameter for namespace resolution.
- [Update\(string, XmlNameSpaceManager, string\)](#)  
This method updates the XML nodes identified by the given XPath expression with the given string value and a .NET `XmlNameSpaceManager` object for namespace resolution.
- [Update\(string, string, OracleXmlType\)](#)  
This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a string parameter for namespace resolution.

- [Update\(string, XmlNamespaceManager, OracleXmlType\)](#)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a `.NET XmlNamespaceManager` object for namespace resolution.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

### Update(string, string, string)

This method updates the XML nodes identified by the given XPath expression with the given string value and a string parameter for namespace resolution.

**Declaration**

```
// C#  
public void Update(string xpathExpr, string nsMap, string value);
```

**Parameters**

- *xpathExpr*

The XPath expression that identifies the nodes to update.

- *nsMap*

The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null. For example:

```
xmlns:nsi="http://www.company1.com" xmlns:nsz="http://www.company2.com"
```

- *value*

The new value as a string.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The default namespace is ignored if its value is an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)



## Update(string, XmlNamespaceManager, string)

This method updates the XML nodes identified by the given XPath expression with the given string value and a .NET `XmlNamespaceManager` object for namespace resolution.

### Declaration

```
// C#
public void Update(string xpathExpr, XmlNamespaceManager nsMgr, string
    value);
```

### Parameters

- *xpathExpr*  
The XPath expression that identifies the nodes to update.
- *nsMgr*  
The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.
- *value*  
The new value as a string.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The default namespace is ignored if its value is an empty string.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Update(string, string, OracleXmlType)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a string parameter for namespace resolution.

### Declaration

```
// C#
public void Update(string xpathExpr, string nsMap, OracleXmlType value);
```

### Parameters

- *xpathExpr*  
The XPath expression that identifies the nodes to update.
- *nsMap*

The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null.

- *value*

The new value as an `OracleXmlType` object.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The default namespace is ignored if its value is an empty string.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

## Update(string, XmlNameSpaceManager, OracleXmlType)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a .NET `XmlNameSpaceManager` object for namespace resolution.

### Declaration

```
// C#
public void Update(string xpathExpr, XmlNameSpaceManager nsMgr, OracleXmlType value);
```

### Parameters

- *xpathExpr*

The XPath expression that identifies the nodes to update.

- *nsMgr*

The .NET `XmlNameSpaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.

- *value*

The new value as an `OracleXmlType` object.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The default namespace is ignored if its value is an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

**Validate**

This methods validates whether or not the XML data in the `OracleXmlType` object conforms to the given XML schema.

**Declaration**

```
// C#  
public bool Validate(String schemaUrl);
```

**Parameters**

- `schemaUrl`  
A string representing the [URL](#) in the database of the XML schema.

**Return Value**

Returns true if the XML data conforms to the XML schema; otherwise, returns false.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentNullException` - The `schemaUrl` argument is null or an empty string.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)



---

---

## ADO.NET 2.0 Classes

This chapter describes the following Oracle Data Provider for .NET classes that support the ADO.NET 2.0 specification.

**See Also:** ["ADO.NET 2.0 Features"](#) on page 3-18

- [OracleClientFactory Class](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleDataSourceEnumerator Class](#)

## OracleClientFactory Class

An `OracleClientFactory` object allows applications to instantiate ODP.NET classes in a generic way.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

### Class Inheritance

`System.Object`

`System.Data.Common.DbProviderFactory`

`Oracle.DataAccess.Client.OracleClientFactory`

### Declaration

```
// C#
public sealed class OracleClientFactory : DbProviderFactory
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class FactorySample
{
    static void Main()
    {
        string constr = "user id=scott;password=tiger;data source=oracle";

        DbProviderFactory factory =
            DbProviderFactories.GetFactory("Oracle.DataAccess.Client");

        DbConnection conn = factory.CreateConnection();

        try
        {
            conn.ConnectionString = constr;
            conn.Open();

            DbCommand cmd = factory.CreateCommand();
            cmd.Connection = conn;
            cmd.CommandText = "select * from emp";

            DbDataReader reader = cmd.ExecuteReader();
            while (reader.Read())
                Console.WriteLine(reader["EMPNO"] + " : " + reader["ENAME"]);
        }
        catch (Exception ex)
        {
        }
    }
}
```

```
        Console.WriteLine(ex.Message);  
        Console.WriteLine(ex.StackTrace);  
    }  
}  
}
```

**Requirements**

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleClientFactory Members](#)
- [OracleClientFactory Public Properties](#)
- [OracleClientFactory Public Methods](#)

## OracleClientFactory Members

OracleClientFactory members are listed in the following tables.

### OracleClientFactory Public Properties

The OracleClientFactory public properties are listed in [Table 7-1](#).

**Table 7-1 OracleClientFactory Public Properties**

Property	Description
<a href="#">CanCreateDataSourceEnumerator</a>	Indicates whether or not the CreateDataSourceEnumerator method is supported

### OracleClientFactory Public Methods

OracleClientFactory Public Methods are listed in [Table 7-2](#).

**Table 7-2 OracleClientFactory Public Method**

Method	Description
<a href="#">CreateCommand</a>	Returns a DbCommand object that represents an OracleCommand object
<a href="#">CreateCommandBuilder</a>	Returns a DbCommandBuilder object that represents an OracleCommandBuilder object
<a href="#">CreateConnection</a>	Returns a DbConnection object that represents an OracleConnection object
<a href="#">CreateConnectionStringBuilder</a>	Returns a DbConnectionStringBuilder object that represents an OracleConnectionStringBuilder object
<a href="#">CreateDataAdapter</a>	Returns a DbDataAdapter object that represents an OracleDataAdapter object
<a href="#">CreateDataSourceEnumerator</a>	Returns a DbDataSourceEnumerator object that represents an OracleDataSourceEnumerator object
<a href="#">CreateParameter</a>	Returns a DbParameter object that represents an OracleParameter object
<a href="#">CreatePermission</a>	Returns a CodeAccessPermission object that represents an OraclePermission object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)



## OracleClientFactory Public Properties

The `OracleClientFactory` public properties are listed in [Table 7-3](#).

**Table 7-3 OracleClientFactory Public Properties**

Property	Description
<a href="#">CanCreateDataSourceEnumerator</a>	Indicates whether or not the <code>CreateDataSourceEnumerator</code> method is supported

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

### CanCreateDataSourceEnumerator

This property indicates whether or not the `CreateDataSourceEnumerator` method is supported.

**Declaration**

```
// C#  
public override bool CanCreateDataSourceEnumerator { get; }
```

**Property Value**

Returns `true`.

**Remarks**

ODP.NET supports the `OracleDataSourceEnumerator` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

## OracleClientFactory Public Methods

The `OracleClientFactory` public method is listed in [Table 7-4](#).

**Table 7-4 OracleClientFactory Public Method**

Method	Description
<a href="#">CreateCommand</a>	Returns a <code>DbCommand</code> object that represents an <code>OracleCommand</code> object
<a href="#">CreateCommandBuilder</a>	Returns a <code>DbCommandBuilder</code> object that represents an <code>OracleCommandBuilder</code> object
<a href="#">CreateConnection</a>	Returns a <code>DbConnection</code> object that represents an <code>OracleConnection</code> object
<a href="#">CreateConnectionStringBuilder</a>	Returns a <code>DbConnectionStringBuilder</code> object that represents an <code>OracleConnectionStringBuilder</code> object
<a href="#">CreateDataAdapter</a>	Returns a <code>DbDataAdapter</code> object that represents an <code>OracleDataAdapter</code> object
<a href="#">CreateDataSourceEnumerator</a>	Returns a <code>DbDataSourceEnumerator</code> object that represents an <code>OracleDataSourceEnumerator</code> object
<a href="#">CreateParameter</a>	Returns a <code>DbParameter</code> object that represents an <code>OracleParameter</code> object
<a href="#">CreatePermission</a>	Returns a <code>CodeAccessPermission</code> object that represents an <code>OraclePermission</code> object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

### CreateCommand

This method returns a `DbCommand` object that represents an `OracleCommand` object.

**Declaration**

```
// C#
public override DbCommand CreateCommand();
```

**Return Value**

A `DbCommand` object that represents an `OracleCommand` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

## CreateCommandBuilder

This method returns a `DbCommandBuilder` object that represents an `OracleCommandBuilder` object.

### Declaration

```
// C#  
public override DbCommandBuilder CreateCommandBuilder();
```

### Return Value

A `DbCommandBuilder` object that represents an `OracleCommandBuilder` object.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

## CreateConnection

This method returns a `DbConnection` object that represents an `OracleConnection` object.

### Declaration

```
// C#  
public override DbConnection CreateConnection();
```

### Return Value

A `DbConnection` object that represents an `OracleConnection` object.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

## CreateConnectionStringBuilder

This method returns a `DbConnectionStringBuilder` object that represents an `OracleConnectionStringBuilder` object.

### Declaration

```
// C#  
public override DbConnectionStringBuilder CreateConnectionStringBuilder();
```

### Return Value

A `DbConnectionStringBuilder` object that represents an `OracleConnectionStringBuilder` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

**CreateDataAdapter**

This method returns a `DbDataAdapter` object that represents an `OracleDataAdapter` object.

**Declaration**

```
// C#  
public override DbDataAdapter CreateDataAdapter();
```

**Return Value**

A `DbDataAdapter` object that represents an `OracleDataAdapter` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

**CreateDataSourceEnumerator**

This method returns a `DbDataSourceEnumerator` object that represents an `OracleDataSourceEnumerator` object.

**Declaration**

```
// C#  
public override DbDataSourceEnumerator CreateDataSourceEnumerator();
```

**Return Value**

A `DbDataSourceEnumerator` object that represents an `OracleDataSourceEnumerator` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)
- ["OracleDataSourceEnumerator Class"](#) on page 7-36

**CreateParameter**

This method returns a `DbParameter` object that represents an `OracleParameter` object.

**Declaration**

```
// C#  
public override DbParameter CreateParameter();
```

**Return Value**

A `DbParameter` object that represents an `OracleParameter` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

**CreatePermission**

This method returns a `CodeAccessPermission` object that represents an `OraclePermission` object.

**Declaration**

```
// C#  
public override System.Security.CodeAccessPermission CreatePermission(  
    System.Security.Permissions.PermissionState state);
```

**Parameter**

- *state*

A `PermissionState` object.

**Return Value**

A `CodeAccessPermission` object that represents an `OraclePermission` object.

**Remarks**

This method enables users, writing provider-independent code, to get a `CodeAccessPermission` instance that represents an `OraclePermission` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

---

## OracleConnectionStringBuilder Class

An `OracleConnectionStringBuilder` object allows applications to create or modify connection strings.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

### Class Inheritance

`System.Object`

`System.Data.Common.DbConnectionStringBuilder`

`Oracle.DataAccess.Client.OracleConnectionStringBuilder`

### Declaration

```
// C#  
public sealed class OracleConnectionStringBuilder : DbConnectionStringBuilder
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

The following rules must be followed for setting values with reserved characters:

1. Values containing characters enclosed within single quotes  
If the value contains characters that are enclosed within single quotation marks, then the entire value must be enclosed within double quotation marks.  
For example, `password = "'scoTT' "` where the value is `'scoTT'`.
2. Values containing characters enclosed within double quotes  
Values should be enclosed in double quotation marks to preserve the case and to avoid the upper casing of values.  
If the value contains characters enclosed in double quotation marks, then it must be enclosed in single quotation marks.  
For example, `password = "'scoTT" '` where the value is `"scoTT"`.
3. Values containing characters enclosed in both single and double quotes  
If the value contains characters enclosed in both single and double quotation marks, the quotation mark used to enclose the value must be doubled each time it occurs within the value.  
For example, `password = '"sco''TT"'` where the value is `"sco'TT"`.
4. Values containing spaces  
All leading and trailing spaces are ignored, but the spaces between the value are recognized. If the value needs to have leading or trailing spaces then it must be enclosed in double quotation marks.  
For example, `User ID = Sco TT` where the value is `<Sco TT>`.  
For example, `User ID = "Sco TT "` where the value is `<Sco TT>`.

## 5. Keywords occurring multiple times in a connection string

If a specific keyword occurs multiple times in a connection string, the last occurrence listed is used in the value set.

For example, with "User ID = scott; password = tiger; User ID = david" connection string, User ID value is david.

### Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;
using System.Collections;

class ConnectionStringBuilderSample
{
    static void Main(string[] args)
    {
        string connString = "user id=scott;password=tiger;Data source=oracle;";
        bool bRet = false;

        // Create an instance of OracleConnectionStringBuilder
        OracleConnectionStringBuilder connStrBuilder =
            new OracleConnectionStringBuilder(connString);

        // Add a new key/value to the connection string
        connStrBuilder.Add("pooling", false);

        // Modify the existing value
        connStrBuilder["Data source"] = "inst1";

        // Remove an entry from the connection string
        bRet = connStrBuilder.Remove("pooling");

        //ContainsKey indicates whether or not the specific key exist
        //returns true even if the user has not specified it explicitly
        Console.WriteLine("Enlist exist: " +
            connStrBuilder.ContainsKey("Enlist"));

        //returns false
        connStrBuilder.ContainsKey("Invalid");

        // ShouldSerialize indicates whether or not a specific key
        // exists in connection string inherited from DbConnectionStringBuilder.
        // returns true if the key is explicitly added the user otherwise false;
        // this will return false as this key doesn't exist.
        connStrBuilder.ShouldSerialize("user");

        // returns false because this key is not added by user explicitly.
        connStrBuilder.ShouldSerialize("Enlist");

        // IsFixedSize [read-only property]
        Console.WriteLine("Connection String is fixed size only: "
            + connStrBuilder.IsFixedSize);
        Console.WriteLine("Key/Value Pair Count: " + connStrBuilder.Count);

        //adding a new key which is not supported by the provider
```

```
//is not allowed.
try
{
    //this will throw an exception.
    connStrBuilder.Add("NewKey", "newValue");
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}

Console.WriteLine("Key/Value Pair Count: " + connStrBuilder.Count);

//modifying a existing key is allowed.
connStrBuilder.Add("Enlist", false);
Console.WriteLine("Key/Value Pair Count: " + connStrBuilder.Count);

// Get all the keys and values supported by the provider.
ICollection keyCollection = connStrBuilder.Keys;
ICollection valueCollection = connStrBuilder.Values;

IEnumerator keys = keyCollection.GetEnumerator();
IEnumerator values = valueCollection.GetEnumerator();

while (keys.MoveNext())
{
    values.MoveNext();
    Console.WriteLine("Key: {0}      Value: {1} \n"
        ,keys.Current ,values.Current);
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Members](#)
- [OracleConnectionStringBuilder Constructors](#)
- [OracleConnectionStringBuilder Public Properties](#)
- [OracleConnectionStringBuilder Public Methods](#)



## OracleConnectionStringBuilder Members

OracleConnectionStringBuilder members are listed in the following tables.

### OracleConnectionStringBuilder Constructors

OracleConnectionStringBuilder constructors are listed in [Table 7-5](#).

**Table 7-5 OracleConnectionStringBuilder Constructors**

Constructor	Description
<a href="#">OracleConnectionStringBuilder Constructors</a>	Instantiates a new instance of OracleConnectionStringBuilder class (Overloaded)

### OracleConnectionStringBuilder Public Properties

OracleConnectionStringBuilder instance properties are listed in [Table 7-6](#).

**Table 7-6 OracleConnectionStringBuilder Public Properties**

Properties	Description
BrowsableConnectionString	Inherited from System.Data.Common.DbConnectionStringBuilder
<a href="#">ConnectionLifetime</a>	Specifies the value corresponding to the Connection Lifetime attribute in the ConnectionString property
ConnectionString	Inherited from System.Data.Common.DbConnectionStringBuilder
<a href="#">ConnectionTimeout</a>	Specifies the value corresponding to the Connection Timeout attribute in the ConnectionString property
<a href="#">ContextConnection</a>	Specifies the value corresponding to the Context Connection attribute in the ConnectionString property
Count	Inherited from System.Data.Common.DbConnectionStringBuilder
<a href="#">DataSource</a>	Specifies the value corresponding to the Data Source attribute in the ConnectionString property
<a href="#">DBAPrivilege</a>	Specifies the value corresponding to the DBA Privilege attribute in the ConnectionString property
<a href="#">DecrPoolSize</a>	Specifies the value corresponding to the Decr Pool Size attribute in the ConnectionString property
<a href="#">Enlist</a>	Specifies the value corresponding to the Enlist attribute in the ConnectionString property
<a href="#">HAEvents</a>	Specifies the value corresponding to the HA Events attribute in the ConnectionString property
<a href="#">IncrPoolSize</a>	Specifies the value corresponding to the Incr Pool Size attribute in the ConnectionString property
<a href="#">IsFixedSize</a>	Indicates whether or not the Connection String Builder has a fixed size
IsReadOnly	Inherited from System.Data.Common.DbConnectionStringBuilder

**Table 7–6 (Cont.) OracleConnectionStringBuilder Public Properties**

Properties	Description
<a href="#">Item</a>	Specifies the value associated with the specified attribute
<a href="#">Keys</a>	Specifies a collection of attributes contained in the Connection String Builder
<a href="#">LoadBalancing</a>	Specifies the value corresponding to the Load Balancing attribute in the ConnectionString property
<a href="#">MaxPoolSize</a>	Specifies the value corresponding to the Max Pool Size attribute in the ConnectionString property
<a href="#">MetadataPooling</a>	Specifies the value that corresponds to the Metadata Pooling attribute in the ConnectionString property
<a href="#">MinPoolSize</a>	Specifies the value corresponding to the Min Pool Size attribute in the ConnectionString property
<a href="#">Password</a>	Specifies the value corresponding to the Password attribute in the ConnectionString property
<a href="#">PersistSecurityInfo</a>	Specifies the value corresponding to the Persist Security Info attribute in the ConnectionString property
<a href="#">Pooling</a>	Specifies the value corresponding to the Pooling attribute in the ConnectionString property
<a href="#">ProxyPassword</a>	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
<a href="#">ProxyUserId</a>	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
<a href="#">SelfTuning</a>	Specifies the value corresponding to the Self Tuning attribute in the ConnectionString property
<a href="#">StatementCachePurge</a>	Specifies the value corresponding to the Statement Cache Purge attribute in the ConnectionString property
<a href="#">StatementCacheSize</a>	Specifies the value corresponding to the Statement Cache Size attribute in the ConnectionString property
<a href="#">UserID</a>	Specifies the value corresponding to the User Id attribute in the ConnectionString property
<a href="#">ValidateConnection</a>	Specifies the value corresponding to the Validate Connection attribute in the ConnectionString property
<a href="#">Values</a>	Specifies a collection of values contained in the Connection String Builder

### OracleConnectionStringBuilder Public Methods

OracleConnectionStringBuilder instance methods are listed in [Table 7–7](#).

**Table 7–7 OracleConnectionStringBuilder Public Methods**

Methods	Description
<a href="#">Add</a>	Inherited from System.Data.Common.DbConnectionStringBuilder
<a href="#">Clear</a>	Clears the connection string contents

**Table 7-7 (Cont.) OracleConnectionStringBuilder Public Methods**

Methods	Description
<a href="#">ContainsKey</a>	Indicates whether or not a specific attribute in the connection string is supported by ODP.NET
EquivalentTo	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
<a href="#">Remove</a>	Removes the entry corresponding to the specified attribute from the connection string
ShouldSerialize	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
ToString	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
<a href="#">TryGetValue</a>	Returns the value corresponding to the supplied attribute, as an output parameter

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)

## OracleConnectionStringBuilder Constructors

OracleConnectionStringBuilder constructors instantiate new instances of the OracleConnectionStringBuilder class.

### Overload List:

- [OracleConnectionStringBuilder\(\)](#)  
This constructor instantiates a new instance of OracleConnectionStringBuilder class.
- [OracleConnectionStringBuilder\(string\)](#)  
This constructor instantiates a new instance of the OracleConnectionStringBuilder class with the provided connection string.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

### OracleConnectionStringBuilder()

This constructor instantiates a new instance of the OracleConnectionStringBuilder class.

### Declaration

```
// C#  
public OracleConnectionStringBuilder();
```

### Remarks

The `ConnectionString` property is empty after the object is created.

**See Also:** ["Oracle.DataAccess.Client Namespace"](#) on page 1-4

### OracleConnectionStringBuilder(string)

This constructor instantiates a new instance of the OracleConnectionStringBuilder class with the provided connection string.

### Declaration

```
// C#  
public OracleConnectionStringBuilder(string connectionString);
```

### Parameters

- *connectionString*  
The connection information.

### Exceptions

ArgumentNullException - The *connectionString* parameter is null.

ArgumentException - The *connectionString* parameter is invalid.

**Remarks**

The `ConnectionString` property of this instance is set to the supplied connection string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## OracleConnectionStringBuilder Public Properties

OracleConnectionStringBuilder public properties are listed in [Table 7–8](#).

**Table 7–8 OracleConnectionStringBuilder Public Properties**

Properties	Description
BrowsableConnectionString	Inherited from System.Data.Common.DbConnectionStringBuilder
ConnectionLifetime	Specifies the value corresponding to the Connection Lifetime attribute in the ConnectionString property
ConnectionString	Inherited from System.Data.Common.DbConnectionStringBuilder
ConnectionTimeout	Specifies the value corresponding to the Connection Timeout attribute in the ConnectionString property
ContextConnection	Specifies the value corresponding to the Context Connection attribute in the ConnectionString property
Count	Inherited from System.Data.Common.DbConnectionStringBuilder
DataSource	Specifies the value corresponding to the Data Source attribute in the ConnectionString property
DBAPrivilege	Specifies the value corresponding to the DBA Privilege attribute in the ConnectionString property
DecrPoolSize	Specifies the value corresponding to the Decr Pool Size attribute in the ConnectionString property
Enlist	Specifies the value corresponding to the Enlist attribute in the ConnectionString property
HAEvents	Specifies the value corresponding to the HA Events attribute in the ConnectionString property
IncrPoolSize	Specifies the value corresponding to the Incr Pool Size attribute in the ConnectionString property
IsFixedSize	Indicates whether or not the Connection String Builder has a fixed size
IsReadOnly	Inherited from System.Data.Common.DbConnectionStringBuilder
Item	Specifies the value associated with the specified attribute
Keys	Specifies a collection of attributes contained in the Connection String Builder
LoadBalancing	Specifies the value corresponding to the Load Balancing attribute in the ConnectionString property
MaxPoolSize	Specifies the value corresponding to the Max Pool Size attribute in the ConnectionString property
MetadataPooling	Specifies the value that corresponds to the Metadata Pooling attribute in the ConnectionString property
MinPoolSize	Specifies the value corresponding to the Min Pool Size attribute in the ConnectionString property

**Table 7–8 (Cont.) OracleConnectionStringBuilder Public Properties**

Properties	Description
<a href="#">Password</a>	Specifies the value corresponding to the Password attribute in the ConnectionString property
<a href="#">PersistSecurityInfo</a>	Specifies the value corresponding to the Persist Security Info attribute in the ConnectionString property
<a href="#">Pooling</a>	Specifies the value corresponding to the Pooling attribute in the ConnectionString property
<a href="#">ProxyPassword</a>	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
<a href="#">ProxyUserId</a>	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
<a href="#">SelfTuning</a>	Specifies the value corresponding to the Self Tuning attribute in the ConnectionString property
<a href="#">StatementCachePurge</a>	Specifies the value corresponding to the Statement Cache Purge attribute in the ConnectionString property
<a href="#">StatementCacheSize</a>	Specifies the value corresponding to the Statement Cache Size attribute in the ConnectionString property
<a href="#">UserID</a>	Specifies the value corresponding to the User Id attribute in the ConnectionString property
<a href="#">ValidateConnection</a>	Specifies the value corresponding to the Validate Connection attribute in the ConnectionString property
<a href="#">Values</a>	Specifies a collection of values contained in the Connection String Builder

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**ConnectionLifetime**

This property specifies the value corresponding to the Connection Lifetime attribute in the ConnectionString property.

**Declaration**

```
// C#
public int ConnectionLifetime{get; set;}
```

**Property Value**

An int that represents the value of the supplied attribute.

**Exceptions**

OracleException - The specified value is less than zero.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**ConnectionTimeout**

This property specifies the value corresponding to the `Connection Timeout` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public int ConnectionTimeout {get; set;}
```

**Property Value**

An `int` that represents the value of the supplied attribute.

**Exceptions**

`OracleException` - The specified value is less than zero.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**ContextConnection**

This property specifies the value corresponding to the `Context Connection` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool ContextConnection {get; set;}
```

**Property Value**

A `bool` that represents the value of the supplied attribute.



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**DataSource**

This property specifies the value corresponding to the `Data Source` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string DataSource{get; set;}
```

**Property Value**

A string that represents the value of the supplied attribute.

**Exceptions**

`ArgumentNullException` - The specified value is null.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**DBAPrivilege**

This property specifies the value corresponding to the `DBA Privilege` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string DBAPrivilege{get; set;}
```

**Property Value**

A string that represents the value of the supplied attribute.

Possible values are `SYSDBA` or `SYSOPER`.

**Exceptions**

`ArgumentNullException` - The specified value is null.

`OracleException` - The specified value is invalid.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**DecrPoolSize**

This property specifies the value corresponding to the `Decr Pool Size` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public int DecrPoolSize{get; set;}
```

**Property Value**

An `int` that represents the value of the supplied attribute.

**Exceptions**

`OracleException` - The specified value is less than 1.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Enlist**

This property specifies the value corresponding to the `Enlist` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string Enlist{get; set;};
```

**Property Value**

A string that represents the value of the supplied attribute. Values are case-insensitive. Possible values are: `dynamic`, `true`, `false`, `yes`, and `no`.

**Exceptions**

`ArgumentNullException` - The specified value is null.

`OracleException` - The supplied value is not one of following: `dynamic`, `true`, `false`, `yes`, or `no`.

### Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## HAEvents

This property specifies the value corresponding to the `HA Events` attribute in the `ConnectionString` property.

### Declaration

```
// C#  
public bool HAEvents{get; set;}
```

### Property Value

A `bool` that represents the value of the supplied attribute.

### Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## IncrPoolSize

This property specifies the value corresponding to the `Incr Pool Size` attribute in the `ConnectionString` property.

### Declaration

```
// C#  
public int IncrPoolSize{get; set;}
```

### Property Value

An `int` that represents the value of the supplied attribute.

### Exceptions

`OracleException` - The specified value is less than 1.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**IsFixedSize**

Indicates whether or not the Connection String Builder has a fixed size.

**Declaration**

```
// C#  
public override bool IsFixedSize{get;}
```

**Property Value**

Returns `true` if the Connection String Builder has a fixed size; otherwise, returns `false`.

**Remarks**

Attributes cannot be added or removed. They can only be modified for connection strings with a fixed size.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Item**

This property specifies the value associated with the specified attribute.

**Declaration**

```
// C#  
public override object this[string keyword]{get; set;}
```

**Property Value**

An object value corresponding to the attribute.

**Exceptions**

`ArgumentNullException` - The specified attribute is null.

`OracleException` - The specified attribute is not supported or the specified value is invalid.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Keys**

This property specifies a collection of attributes contained in the Connection String Builder.

**Declaration**

```
// C#  
public override ICollection Keys{get;}
```

**Property Value**

Returns an `ICollection` that represents the attributes in the Connection String Builder.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**LoadBalancing**

This property specifies the value corresponding to the Load Balancing attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool LoadBalancing {get; set;}
```

**Property Value**

A `bool` that contains the value of the supplied attribute.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**MaxPoolSize**

This property specifies the value corresponding to the Max Pool Size attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public int MaxPoolSize{get; set;}
```

**Property Value**

An `int` that represents the value of the supplied attribute.

**Exceptions**

`OracleException` - The specified value is less than 1.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**MetadataPooling**

This property specifies the value that corresponds to the `Metadata Pooling` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool MetadataPooling{get; set;};
```

**Property Value**

A `bool` containing the value of the supplied attribute.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**MinPoolSize**

This property specifies the value corresponding to the `Min Pool Size` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public int MinPoolSize{get; set;}
```

**Property Value**

An `int` that contains the value of the supplied attribute.

**Exceptions**

`OracleException` - The specified value is less than 0.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Password**

This property specifies the value corresponding to the `Password` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string Password{get; set;}
```

**Property Value**

A `string` that contains the value of the supplied attribute.

**Exception**

`ArgumentNullException` - The specified value is null.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**PersistSecurityInfo**

This property specifies the value corresponding to the `Persist Security Info` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool PersistSecurityInfo{get; set;}
```

**Property Value**

A `bool` that represents the value of the supplied attribute.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property gets set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Pooling**

This property specifies the value corresponding to the `Pooling` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool Pooling {get; set;}
```

**Property Value**

A `bool` that represents the value of the supplied attribute.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**ProxyPassword**

This property specifies the value corresponding to the `Proxy Password` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string ProxyPassword {get; set;}
```

**Property Value**

A `string` that represents the value of the supplied attribute.

**Exception**

`ArgumentNullException` - The specified value is null.



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## ProxyUserId

This property specifies the value corresponding to the `Proxy User Id` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string ProxyUserId {get; set;}
```

**Property Value**

A string that represents the value of the supplied attribute.

**Exception**

`ArgumentNullException` - The specified value is null.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## SelfTuning

This property specifies the value corresponding to the `Self Tuning` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool SelfTuning {get; set;}
```

**Property Value**

A `bool` that represents the value of the supplied attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## StatementCachePurge

This property specifies the value corresponding to the `Statement Cache Purge` attribute in the `ConnectionString` property.

**Declaration**

```
// C#
```

```
public bool StatementCachePurge {get; set;}
```

**Property Value**

A `bool` that represents the value of the supplied attribute.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**StatementCacheSize**

This property specifies the value corresponding to the `Statement Cache Size` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public int StatementCacheSize{get; set;}
```

**Property Value**

An `int` that represents the value of the supplied attribute.

**Exceptions**

`OracleException` - The specified value is less than zero.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**UserID**

This property specifies the value corresponding to the `User Id` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public string UserID{get; set;}
```

**Property Value**

A string that represents the value of the supplied attribute.

**Exception**

`ArgumentNullException` - The specified value is null.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**ValidateConnection**

This property specifies the value corresponding to the `ValidateConnection` attribute in the `ConnectionString` property.

**Declaration**

```
// C#  
public bool ValidateConnection{get; set;}
```

**Property Value**

A `bool` that represents the value of the supplied attribute.

**Remarks**

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Values**

This property specifies a collection of values contained in the `ConnectionStringBuilder`.

**Declaration**

```
// C#  
public override ICollection Values{get;}
```

**Property Value**

Returns an `ICollection` that represents the values in the `ConnectionStringBuilder`.

**Remarks**

The order of the values in the `ICollection` is unspecified, but is the same as the associated attributes in the `ICollection` returned by the `Keys` property.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## OracleConnectionStringBuilder Public Methods

OracleConnectionStringBuilder public methods are listed in [Table 7-9](#).

**Table 7-9 OracleConnectionStringBuilder Public Methods**

Methods	Description
Add	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
<a href="#">Clear</a>	Clears the connection string contents
<a href="#">ContainsKey</a>	Indicates whether or not a specific attribute in the connection string is supported by ODP.NET
EquivalentTo	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
<a href="#">Remove</a>	Removes the entry corresponding to the specified attribute from the connection string
ShouldSerialize	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
ToString	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
<a href="#">TryGetValue</a>	Returns the value corresponding to the supplied attribute, as an output parameter

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

### Clear

This method clears the connection string contents.

#### Declaration

```
// C#
public override void Clear();
```

#### Remarks

All key/value pairs are removed from the `OracleConnectionStringBuilder` object and the `ConnectionString` property is set to `Empty`.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

### ContainsKey

This method indicates whether or not a specific attribute in the connection string is supported by ODP.NET.

**Declaration**

```
// C#  
public override bool ContainsKey(string keyword);
```

**Parameters**

- *keyword*

The attribute being verified.

**Return Value**

Returns `true` if the specified attribute exists; otherwise, returns `false`.

**Exceptions**

`ArgumentNullException` - The specified attribute is null.

**Remarks**

This method indicates if the attribute is part of the provider-supported attributes. It does not indicate if the user added the attribute to the connection string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

**Remove**

This method removes the entry corresponding to the specified attribute from the connection string.

**Declaration**

```
// C#  
public override bool Remove(string keyword);
```

**Parameters**

- *keyword*

The attribute that specifies the entry to be removed.

**Return Value**

Returns `true` if the attribute existed in the connection string and the corresponding entry was removed; otherwise, returns `false`.

**Exceptions**

`ArgumentNullException` - The specified attribute is null.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## TryGetValue

This method returns the value corresponding to the supplied attribute, as an output parameter.

### Declaration

```
// C#  
public override bool TryGetValue(string keyword, out object value);
```

### Parameters

- *keyword*  
The attribute for which the value is being retrieved.
- *value*  
The value of the supplied attribute.  
Sets *value* to the default value if the attribute is not present in the connection string.

### Return Value

Returns `true` if the value that corresponds to the attribute has been successfully retrieved; otherwise, returns `false`. If the attribute is not present in the connection string, returns `false` and sets the *value* to null.

### Exceptions

`ArgumentNullException` - The specified attribute is null.

### Remarks

If the function returns `false`, sets *value* to null.

If the attribute is not present in the connection string, sets *value* to the default value.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

## OracleDataSourceEnumerator Class

An `OracleDataSourceEnumerator` object allows applications to generically obtain a collection of data sources to connect to.

*Supported Only in ADO.NET 2.0-Compliant ODP.NET*

### Class Inheritance

`System.Object`

`System.DbDataSourceEnumerator`

`Oracle.DataAccess.Client.OracleDataSourceEnumerator`

### Declaration

```
// C#  
public sealed class OracleDataSourceEnumerator : DbDataSourceEnumerator
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class DataSourceEnumSample  
{  
    static void Main()  
    {  
        string ProviderName = "Oracle.DataAccess.Client";  
  
        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);  
  
        if (factory.CanCreateDataSourceEnumerator)  
        {  
            DbDataSourceEnumerator dsenum = factory.CreateDataSourceEnumerator();  
            DataTable dt = dsenum.GetDataSources();  
  
            // Print the first column/row entry in the DataTable  
            Console.WriteLine(dt.Columns[0] + " : " + dt.Rows[0][0]);  
            Console.WriteLine(dt.Columns[1] + " : " + dt.Rows[0][1]);  
            Console.WriteLine(dt.Columns[2] + " : " + dt.Rows[0][2]);  
            Console.WriteLine(dt.Columns[3] + " : " + dt.Rows[0][3]);  
            Console.WriteLine(dt.Columns[4] + " : " + dt.Rows[0][4]);  
        }  
        else  
            Console.WriteLine("Data source enumeration is not supported by provider");  
    }  
}
```



**Requirements**

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDataSourceEnumerator Members](#)
- [OracleDataSourceEnumerator Public Methods](#)

## OracleDataSourceEnumerator Members

OracleDataSourceEnumerator members are listed in the following tables.

### OracleDataSourceEnumerator Public Methods

OracleDataSourceEnumerator Public Methods are listed in [Table 7-10](#).

**Table 7-10** OracleDataSourceEnumerator Method

Method	Description
<a href="#">GetDataSources</a>	Returns a DataTable object with information on all the TNS alias entries in the tnsnames.ora file

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataSourceEnumerator Class](#)

## OracleDataSourceEnumerator Public Methods

The `OracleDataSourceEnumerator` static method is listed in [Table 7-11](#).

**Table 7-11 OracleDataSourceEnumerator Method**

Method	Description
<a href="#">GetDataSources</a>	Returns a <code>DataTable</code> object with information on all the TNS alias entries in the <code>tnsnames.ora</code> file

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

### GetDataSources

This method returns a `DataTable` object with information on all the TNS alias entries in the `tnsnames.ora` file.

**Declaration**

```
// C#
public override DataTable GetDataSources();
```

**Return Value**

A `DataTable` object.

**Remarks**

This method returns a `DataTable` object for each TNS Alias entry that exists in the `tnsnames.ora` file.

If the `tnsnames.ora` file is not found, then the returned `DataTable` object is empty.

The following columns are returned for each row, but only the `InstanceName` column is populated.

- `InstanceName` (type: `System.String`)
- `ServerName` (type: `System.String`)
- `ServiceName` (type: `System.String`)
- `Protocol` (type: `System.String`)
- `Port` (type: `System.String`)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)



---

---

# Oracle Data Provider for .NET HA Event Classes

This chapter describes the following ODP.NET HA event class and enumerations:

- [OracleHAEventArgs Class](#)
- [OracleHAEventHandler Delegate](#)
- [OracleHAEventSource Enumeration](#)
- [OracleHAEventStatus Enumeration](#)

## OracleHAEventArgs Class

The `OracleHAEventArgs` class provides event data for the `OracleConnection.HAEvent` event.

### Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleHAEventArgs`

### Declaration

```
// C#  
public sealed class OracleHAEventArgs
```

### Thread Safety

All public methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

When any HA event occurs for a service, service member, host, node, or instance that an `OracleConnection` object is set to with `"ha_events=true"`, the `OracleConnection.HAEvent` is triggered and passes an instance of `OracleHAEventArgs` to all the delegates that have registered with the event.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version 2.0 or later.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Members](#)
- [OracleHAEventArgs Properties](#)
- ["OracleConnection Class"](#) on page 5-64
- ["HAEvent"](#) on page 5-112

## OracleHAEventArgs Members

OracleHAEventArgs members are listed in the following table.

### OracleHAEventArgs Properties

The OracleHAEventArgs properties are listed in [Table 8-2](#).

**Table 8-1 OracleHAEventArgs Properties**

Name	Description
<a href="#">DatabaseDomainName</a>	Specifies the domain name of the database affected by the HAevent
<a href="#">DatabaseName</a>	Specifies the database affected by the HAevent
<a href="#">HostName</a>	Specifies the host that triggered the event
<a href="#">InstanceName</a>	Specifies the instance that triggered the event
<a href="#">ServiceName</a>	Specifies the service that triggered the event
<a href="#">Source</a>	Specifies the source that triggered the event
<a href="#">Status</a>	Specifies the status of the source that triggered the event
<a href="#">Time</a>	Specifies the time when the event was triggered on the server

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- ["HAEvent"](#) on page 5-112

## OracleHAEventArgs Properties

The OracleHAEventArgs properties are listed in [Table 8-2](#).

**Table 8-2 OracleHAEventArgs Properties**

Name	Description
<a href="#">DatabaseDomainName</a>	Specifies the domain name of the database affected by the HAevent
<a href="#">DatabaseName</a>	Specifies the database affected by the HAevent
<a href="#">HostName</a>	Specifies the host that triggered the event
<a href="#">InstanceName</a>	Specifies the instance that triggered the event
<a href="#">ServiceName</a>	Specifies the service that triggered the event
<a href="#">Source</a>	Specifies the source that triggered the event
<a href="#">Status</a>	Specifies the status of the source that triggered the event
<a href="#">Time</a>	Specifies the time when the event was triggered on the server

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)

### DatabaseDomainName

This property specifies the domain name of the database that is affected by the HA event.

**Declaration**

```
// C#
public string DatabaseDomainName {get;}
```

**Property Value**

The domain name of the database that is affected by the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

### DatabaseName

This property specifies the database that is affected by the HA event.

**Declaration**

```
// C#
public string DatabaseName {get;}
```



**Property Value**

This property specifies the database name that is affected by the HA event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

**HostName**

This property specifies the host that triggered the HA event.

**Declaration**

```
// C#  
public string HostName {get;}
```

**Property Value**

The host that is affected by the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

**InstanceName**

This property specifies the instance that triggered the HA event.

**Declaration**

```
// C#  
public string InstanceName {get;}
```

**Property Value**

The instance that is affected by the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

**ServiceName**

This property specifies the service that triggered the HA event.

**Declaration**

```
// C#  
public string ServiceName {get;}
```

**Property Value**

The service that is affected by the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

**Source**

This property specifies the source that triggered the HA event.

**Declaration**

```
// C#  
public OracleHAEventSource Source {get;}
```

**Property Value**

The source that triggered the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

**Status**

This property specifies the status of the source that triggered the HA event.

**Declaration**

```
// C#  
public OracleHAEventStatus Status {get;}
```

**Property Value**

The status of the source that triggered the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

## Time

This property specifies the time when the HA event was triggered on the server.

### Declaration

```
// C#  
public DateTime Time {get;}
```

### Property Value

The time that the HA Event was triggered.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 5-112

## OracleHAEventHandler Delegate

The `OracleHAEventHandler` delegate represents the signature of the method that handles the `OracleConnection.HAEvent` event.

### Declaration

```
// C#  
public delegate void OracleHAEventHandler(object sender, OracleHAEventArgs  
    EventArgs);
```

### Parameters

- *sender*  
The source of the event.
- *EventArgs*  
The `OracleHAEventArgs` object that contains the event data.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version 2.0 or later.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleHAEventArgs Class](#)
- ["HAEvent" on page 5-112](#)

---

## OracleHAEventSource Enumeration

The `OracleHAEventSource` enumeration indicates the source of the HA event.

[Table 8–3](#) lists all the `OracleHAEventSource` enumeration values with a description of each enumerated value.

**Table 8–3 OracleHAEventSource Enumeration Member Values**

Member Name	Description
Service	The source of the HA Event is a service.
ServiceMember	The source of the HA Event is a service member.
Database	The source of the HA Event is a database.
Host	The source of the HA Event is a host.
Instance	The source of the HA Event is an instance.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- ["Source"](#) on page 8-6

## OracleHAEventStatus Enumeration

The `OracleHAEventStatus` enumeration indicates the status of the HA event source.

[Table 8-4](#) lists all the `OracleHAEventStatus` enumeration values with a description of each enumerated value.

**Table 8-4 OracleHAEventStatus Enumeration Values**

Member Name	Description
Up	The source of the HA Event is up.
Down	The source of the HA Event is down.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleHAEventArgs Class](#)
- ["Status"](#) on page 8-6

---

---

# Database Change Notification

This chapter describes Oracle Data Provider for .NET Change Notification Classes, Event Delegates, and Enumerations, which support Continuous Query Notification.

---

---

**Note:** Database Change Notification is known as Continuous Query Notification in Oracle database documentation.

---

---

**See Also:** ["Database Change Notification Support"](#) on page 3-97

This chapter contains these topics:

- [OracleDependency Class](#)
- [OracleNotificationRequest Class](#)
- [OracleNotificationEventArgs Class](#)
- [OnChangeEventHandler Delegate](#)
- [OracleRowidInfo Enumeration](#)
- [OracleNotificationType Enumeration](#)
- [OracleNotificationSource Enumeration](#)
- [OracleNotificationInfo Enumeration](#)

## OracleDependency Class

An `OracleDependency` class represents a dependency between an application and an Oracle database, enabling the application to get notifications whenever the data of interest or the state of the Oracle database changes.

### Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleDependency`

### Declaration

```
// C#  
public sealed class OracleDependency
```

### Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDependency Members](#)
- [OracleDependency Constructors](#)
- [OracleDependency Static Fields](#)
- [OracleDependency Static Methods](#)
- [OracleDependency Methods](#)
- [OracleDependency Properties](#)
- [OracleDependency Events](#)



## OracleDependency Members

OracleDependency members are listed in the following tables.

### OracleDependency Constructors

OracleDependency constructors are listed in [Table 9-1](#).

**Table 9-1 OracleDependency Constructors**

Constructors	Description
<a href="#">OracleDependency Constructors</a>	Instantiates a new instance of OracleDependency class (Overloaded)

### OracleDependency Static Fields

The OracleDependency static field is listed in [Table 9-2](#).

**Table 9-2 OracleDependency Static Field**

Static Field	Description
<a href="#">Port</a>	Indicates the port number that the notification listener listens on, for database notifications

### OracleDependency Static Methods

OracleDependency static methods are listed in [Table 9-3](#).

**Table 9-3 OracleDependency Static Methods**

Static Methods	Description
<a href="#">Equals</a>	Inherited from System.Object
<a href="#">GetOracleDependency</a>	Returns an OracleDependency instance based on the specified unique identifier

### OracleDependency Properties

OracleDependency properties are listed in [Table 9-4](#).

**Table 9-4 OracleDependency Properties**

Properties	Description
<a href="#">DataSource</a>	Indicates the data source associated with the OracleDependency instance
<a href="#">HasChanges</a>	Indicates whether or not there is any change in the database associated with this dependency
<a href="#">Id</a>	Represents the unique identifier for the OracleDependency instance
<a href="#">IsEnabled</a>	Specifies whether or not the dependency is enabled between the application and the database
<a href="#">QueryBasedNotification</a>	Specifies whether the change notification registration is object-based or query-based
<a href="#">RegisteredQueryIDs</a>	Provides a list of CHANGE_NOTIFICATION_QUERY_IDS
<a href="#">RegisteredResources</a>	Indicates the database resources that are registered in the notification registration

**Table 9–4 (Cont.) OracleDependency Properties**

Properties	Description
<a href="#">RowidInfo</a>	Specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database
<a href="#">UserName</a>	Indicates the database user name associated with the OracleDependency instance

### OracleDependency Methods

OracleDependency methods are listed in [Table 9–5](#).

**Table 9–5 OracleDependency Methods**

Methods	Description
<a href="#">AddCommandDependency</a>	Binds the OracleDependency instance to the specified OracleCommand instance
<a href="#">Equals</a>	Inherited from System.Object
<a href="#">GetHashCode</a>	Inherited from System.Object
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">RemoveRegistration</a>	Removes the specified dependency between the application and the database
<a href="#">ToString</a>	Inherited from System.Object

### OracleDependency Events

The OracleDependency event is listed in [Table 9–6](#).

**Table 9–6 OracleDependency Events**

Event	Description
<a href="#">OnChange</a>	An event that is sent when a database notification associated with the dependency is received from the database

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)

## OracleDependency Constructors

OracleDependency constructors create instances of the OracleDependency class.

### Overload List:

- [OracleDependency \(\)](#)

This constructor creates an instance of the OracleDependency class.

- [OracleDependency\(OracleCommand\)](#)

This constructor creates an instance of the OracleDependency class and binds it to the specified OracleCommand instance.

- [OracleDependency\(OracleCommand, bool, int, bool\)](#)

This constructor creates an instance of the OracleDependency class and binds it to the specified OracleCommand instance, specifying whether or not a notification is to be removed upon notification, the timeout value of the notification registration, and the persistence of the notification.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

### OracleDependency ()

This constructor creates an instance of the OracleDependency class.

### Declaration

```
// C#  
public OracleDependency ()
```

### Remarks

Using this constructor does not bind any OracleCommand to the newly constructed OracleDependency. Use the AddCommandDependency method to do so.

---

**Note:** The dependency between the application and the database is not established when the OracleDependency instance is created. The dependency is established when the command that is associated with this dependency is executed.

---

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

### OracleDependency(OracleCommand)

This constructor creates an instance of the OracleDependency class and binds it to an OracleCommand instance.

**Declaration**

```
// C#  
public OracleDependency (OracleCommand cmd)
```

**Parameters**

- *cmd*

The command that the `OracleDependency` object binds to.

**Exceptions**

`ArgumentNullException` - The *cmd* parameter is null.

`InvalidOperationException` - The specified `OracleCommand` instance already contains a notification request.

**Remarks**

When this `OracleDependency` constructor binds the `OracleCommand` instance to an `OracleDependency` instance, it causes the creation of an `OracleNotificationRequest` instance and then sets that `OracleNotificationRequest` instance to the `OracleCommand.Notification` property.

The Continuous Query Notification is registered with the database, when the command is executed. Any of the command execution methods (for example, `ExecuteNonQuery`, `ExecuteReader`, and so on) will register the notification request. An `OracleDependency` may be bound to more than one `OracleCommand`. When one of these `OracleCommand` object statements is executed, the statement is registered with the associated `OracleCommand`. Although the registration happens on each `OracleCommand` separately, one `OracleDependency` can be responsible for detecting and sending notifications that occur for all `OracleCommand` objects that the `OracleDependency` is associated with. The `OnChangeEventArgs` that is passed to the application for the `OnChange` event provides information on what has changed in the database.

The `OracleNotificationRequest` instance that is created by this constructor has the following default property values:

- `IsNotifiedOnce` is set to the value `True`.
- `Timeout` is set to 50,000 seconds.
- `IsPersistent` is set to the value `False`, that is, the invalidation message is not persistent, but is stored in an in-memory queue before delivery.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

**OracleDependency(OracleCommand, bool, int, bool)**

This constructor creates an instance of the `OracleDependency` class and binds it to the specified `OracleCommand` instance, while specifying whether or not a registration is to be removed upon notification, the timeout value of the notification registration, and the persistence of the notification.

## Declaration

```
// C#  
public OracleDependency (OracleCommand cmd, bool isNotifiedOnce, long timeout,  
    bool isPersistent)
```

## Parameters

- *cmd*  
The command associated with the Continuous Query Notification request.
- *isNotifiedOnce*  
An indicator that specifies whether or not the registration is removed automatically once the notification occurs.
- *timeout*  
The amount of time, in seconds, that the registration stays active. When *timeout* is set to 0, the registration never expires. The valid values for *timeout* are between 0 and 4294967295.
- *isPersistent*  
Indicates whether or not the invalidation message should be queued persistently in the database before delivery. If the *isPersistent* parameter is set to `True`, the message is queued persistently in the database and cannot be lost upon database failures or shutdowns. If the *isPersistent* property is set to `False`, the message is stored in an in-memory queue before delivery and might be lost.  
  
Database performance is faster if the message is stored in an in-memory queue rather than in the database queue.

## Exceptions

`ArgumentNullException` - The *cmd* parameter is null.

`ArgumentOutOfRangeException` - The specified *timeout* is invalid.

`InvalidOperationException` - The specified `OracleCommand` instance already contains a notification request.

## Remarks

When this `OracleDependency` constructor binds the `OracleCommand` instance to an `OracleDependency` instance, it causes the creation of an `OracleNotificationRequest` instance and then sets that `OracleNotificationRequest` instance to the `OracleCommand.Notification` property.

The Continuous Query Notification is registered with the database, when the command is executed. Any of the command execution methods (for example, `ExecuteNonQuery`, `ExecuteReader`, and so on) will register the notification request. An `OracleDependency` may be bound to more than one `OracleCommand`. When one of these `OracleCommand` object statements is executed, the statement is registered with the associated `OracleCommand`. Although the registration happens on each `OracleCommand` separately, one `OracleDependency` can be responsible for detecting and sending notifications that occur for all `OracleCommand` objects that the `OracleDependency` is associated with. The `OnChangeEventArgs` that is passed to the application for the `OnChange` event provides information on what has changed in the database.

The `OracleNotificationRequest` instance that is created by this constructor has the following default property values:

- `IsNotifiedOnce` is set to the specified value.
- `Timeout` is set to the specified value.
- `IsPersistent` is set to the specified value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## OracleDependency Static Fields

The `OracleDependency` static field is listed in [Table 9-7](#).

**Table 9-7 OracleDependency Static Field**

Static Field	Description
<a href="#">Port</a>	Indicates the port number that the notification listener listens on, for database notifications

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## Port

This static field indicates the port number that the notification listener listens on, for database notifications.

### Declaration

```
// C#
public static int Port{get; set}
```

### Property Value

An `int` value that represents the number of the port that listens for the database notifications. If the port number is set to `-1`, a random port number is assigned for the listener when the listener is started. Otherwise, the specified port number is used to start the listener.

### Exceptions

`ArgumentOutOfRangeException` - The port number is set to a negative value.

`InvalidOperationException` - The port number is being changed after the listener has started.

### Remarks

The port number specified by the `OracleDependency.Port` static field is used by the notification listener that runs within the same application domain as ODP.NET. This port number receives Continuous Query Notifications from the database. One notification listener is capable of listening to all Continuous Query Notifications and therefore, only one notification listener is created for each application domain.

The notification listener is created when a command associated with an `OracleDependency` object is executed for the first time during the application domain lifetime. The port number specified for the `OracleDependency.Port` static field is used by the listener for its lifetime. The `OracleDependency.Port` static field can be changed after the creation of the notification listener, but doing so does not affect the actual port number that the notification listener listens on.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)



## OracleDependency Static Methods

OracleDependency static methods are listed in [Table 9–8](#).

**Table 9–8 OracleDependency Static Methods**

Static Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
<a href="#">GetOracleDependency</a>	Returns an <code>OracleDependency</code> instance based on the specified unique identifier

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

### GetOracleDependency

This static method returns an `OracleDependency` instance based on the specified unique identifier.

**Declaration**

```
// C#
public static OracleDependency GetOracleDependency(string guid)
```

**Parameters**

- *guid*  
The string representation of the unique identifier of an `OracleDependency` instance.

**Exceptions**

`ArgumentException` - The specified unique identifier cannot locate an `OracleDependency` instance.

**Return Value**

An `OracleDependency` instance that has the specified *guid* parameter.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## OracleDependency Properties

OracleDependency properties are listed in [Table 9-9](#).

**Table 9-9 OracleDependency Properties**

Properties	Description
<a href="#">DataSource</a>	Indicates the data source associated with the OracleDependency instance
<a href="#">HasChanges</a>	Indicates whether or not there is any change in the database associated with this dependency
<a href="#">Id</a>	Represents the unique identifier for the OracleDependency instance
<a href="#">IsEnabled</a>	Specifies whether or not the dependency is enabled between the application and the database
<a href="#">QueryBasedNotification</a>	Specifies whether the change notification registration is object-based or query-based
<a href="#">RegisteredQueryIDs</a>	Provides a list of CHANGE_NOTIFICATION_QUERY_IDS
<a href="#">RegisteredResources</a>	Indicates the database resources that are registered in the notification registration
<a href="#">RowidInfo</a>	Specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database
<a href="#">UserName</a>	Indicates the database user name associated with the OracleDependency instance

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

### DataSource

This property indicates the data source associated with the OracleDependency instance.

**Declaration**

```
// C#
public string DataSource{get;}
```

**Property Value**

A string that indicates the data source associated with the OracleDependency instance.

**Remarks**

The DataSource property is populated with the data source once the OracleCommand associated with the OracleDependency executes and registers for the notification successfully.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## HasChanges

This property indicates whether or not there is any change in the database associated with this dependency.

**Declaration**

```
// C#  
public bool HasChanges{get;}
```

**Property Value**

A `bool` value that returns `True` if the database has detected changes that are associated with this dependency; otherwise, returns `False`.

**Remarks**

As an alternative to using the `OnChange` event, applications can check the `HasChanges` property to determine if there are any changes in the database associated with this dependency.

Once the `HasChanges` property is accessed, its value is reset to `False` so that the next notification can then be acknowledged.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## Id

This property represents the unique identifier for the `OracleDependency` instance.

**Declaration**

```
// C#  
public string Id{get;}
```

**Property Value**

A string that represents the unique identifier that was generated for the `OracleDependency` instance when it was created.

**Remarks**

This property is set when the `OracleDependency` instance is created.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

**IsEnabled**

This property specifies whether or not the dependency is enabled between the application and the database.

**Declaration**

```
// C#  
public bool IsEnabled {get;}
```

**Property Value**

A `bool` value that specifies whether or not dependency is enabled between the application and the database.

**Remarks**

The dependency between the application and the database is not established when the `OracleDependency` instance is created. The dependency is established when the command that is associated with this dependency is executed, at which time the notification request is registered with the database. The dependency ends when the notification registration is removed from the database or when it times out.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

**QueryBasedNotification**

This instance property specifies whether the change notification registration is object-based or query-based.

**Declaration**

```
// C#  
public bool QueryBasedNotification{get; set;}
```

**Property Value**

Specifies whether the change notification registration is object-based or not.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

This property value will be ignored if it is set after the command execution that registers the command for change notification.

By default, this property is true.

ODP.NET developers can register their queries on the row level, not just the object level, beginning with Oracle Data Provider for .NET release 11.1 and Oracle Database 11g release 1 (11.1). The application only receives notification when the selected row or rows change. Query-based notifications provide developers more granularity for using client-side cached data, as they can be more specific about what changes the application needs to be notified of.

OracleNotificationType enumeration is set to Query for query-based notifications.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## RegisteredQueryIDs

This instance property provides a list of CHANGE\_NOTIFICATION\_QUERY\_IDS.

**Declaration**

```
// C#
public ArrayList RegisteredQueryIDs {get;}
```

**Property Value**

This property is an ArrayList of CHANGE\_NOTIFICATION\_QUERY\_IDS.

**Exceptions**

ObjectDisposedException - The object is already disposed.

**Remarks**

This property provides a list of CHANGE\_NOTIFICATION\_QUERY\_IDS that uniquely identify the query that has been registered for change notification. The notification returned from the database will also contain these IDs, allowing applications to determine the query that the notifications are for.

The QueryId at index *n* in RegisteredQueryIDs is for the statement at index *n* the RegisteredResources at index *n*.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## RegisteredResources

This property indicates the database resources that are registered in the notification registration.

**Declaration**

```
// C#
public ArrayList RegisteredResources{get;}
```

**Property Value**

The registered resources in the notification registration.

**Remarks**

The `ArrayList` contains all the command statement or statements that are registered for notification through this `OracleDependency` object. It is appropriately updated when the Continuous Query Notification is registered by a command execution.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

**RowidInfo**

This property specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database.

**Declaration**

```
// C#  
public OracleRowidInfo RowidInfo {get; set;};
```

**Property Value**

An `OracleRowidInfo` enumeration type that determines the inclusion of ROWID in the change notification event.

**Remarks**

There are three `OracleRowidInfo` enumeration types that are valid for this property:

- `Default` includes ROWID information in the change notification event only if `OracleCommand.AddRowid` property is set to `true` or if ROWID is in the select list of the query that is registered for change notification.
- `Include` includes ROWID information regardless of whether or not ROWID is in the select-list for the query.
- `Exclude` excludes ROWID information regardless of whether or not ROWID is in the select-list.

For change notification registrations that involve stored procedure executions, change notification events related to the REF CURSOR contain ROWID information only if `RowidInfo` property is set to `OracleRowidInfo.Include`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)
- ["OracleRowidInfo Enumeration"](#) on page 9-41

**UserName**

This property indicates the database user name associated with the `OracleDependency` instance.

**Declaration**

```
// C#  
public string UserName{get;}
```

**Property Value**

A string that indicates the database user name associated with the `OracleDependency` instance. This database user registers the Continuous Query Notification request with the database.

**Remarks**

The `UserName` property is populated with the user name once the `OracleCommand` associated with the `OracleDependency` executes and registers for the notification successfully. Only the database user who creates the notification registration, or the database system administrator, can remove the registration.

The user specified by this property must have the `CHANGE NOTIFICATION` privilege to register successfully for the Continuous Query Notification with the database.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## OracleDependency Methods

OracleDependency methods are listed in [Table 9–10](#).

**Table 9–10 OracleDependency Methods**

Methods	Description
<a href="#">AddCommandDependency</a>	Binds the OracleDependency instance to the specified OracleCommand instance
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
<a href="#">RemoveRegistration</a>	Removes the specified dependency between the application and the database
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

### AddCommandDependency

This instance method binds the OracleDependency instance to the specified OracleCommand instance.

**Declaration**

```
// C#
Public void AddCommandDependency (OracleCommand cmd);
```

**Parameters**

- *cmd*

The command that is to be bound to the OracleDependency object.

**Exceptions**

ArgumentNullException - The *cmd* parameter is null.

InvalidOperationException - The specified OracleCommand instance already contains a notification request.

**Remarks**

An OracleDependency instance can bind to multiple OracleCommand instances.

While it binds an existing OracleDependency instance to an OracleCommand instance, the AddCommandDependency method creates an OracleNotificationRequest instance, and sets it to the specified OracleCommand.Notification property.

When this method creates an OracleNotificationRequest instance, the following OracleNotificationRequest properties are set:



- `IsNotifiedOnce` is set to the value `True`.
- `Timeout` is set to 50,000 seconds.
- `IsPersistent` is set to the value `False`, indicating that the invalidation message is stored in an in-memory queue before delivery.

With this method, multiple commands can be associated with a single `Continuous Query Notification` registration request. Furthermore, the `OracleNotificationRequest` attribute values assigned to the `OracleCommand` can be changed once the association between the `OracleCommand` and the `OracleDependency` is established.

However, when multiple `OracleCommand` objects are associated with a single `OracleDependency` object, the `OracleNotificationRequest` attributes (`Timeout`, `IsPersistent`, and `IsNotifiedOnce`) of the first executed `OracleCommand` object are used for registration, the attributes associated with subsequent `OracleCommand` executions will be ignored.

Furthermore, once a command associated with an `OracleDependency` is executed and registered, all other subsequent command executions and registration associated with the same `OracleDependency` must use a connection with the same "User Id" and "Data Source" connection string attribute value settings.

Otherwise, an exception will be thrown.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)
- ["OracleDependency\(OracleCommand\)"](#) on page 9-5 for `OracleNotificationRequest` property value

## RemoveRegistration

This instance method removes the specified dependency between the application and the database. Once the registration of the dependency is removed from the database, the `OracleDependency` is no longer able to detect any changes that the database undergoes.

#### Declaration

```
// C#
public void RemoveRegistration(OracleConnection con)
```

#### Parameters

- `con`  
The connection associated with the `OracleDependency` instance.

#### Exceptions

`InvalidOperationException` - The associated connection is not open.

**Remarks**

The notification registration associated with the `OracleDependency` instance is removed from the database.

The `OracleConnection` parameter must be in an *opened state*. This instance method does not open the connection implicitly for the application.

An exception is thrown if the dependency is not valid.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## OracleDependency Events

The OracleDependency event is listed in [Table 9–11](#).

**Table 9–11 OracleDependency Event**

Event	Description
<a href="#">OnChange</a>	An event that is sent when a database notification associated with the dependency is received from the database

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

### OnChange

The OnChange event is sent when a database notification associated with the dependency is received from the database. The information related to the notification is stored in the OracleChangeNotificationEventArgs class.

**Declaration**

```
// C#
public event OnChangeEventHandler OnChange;
```

**Remarks**

The OnChange event occurs if any result set associated with the dependency changes. For objects that are part of a Transaction, notifications will be received for each modified object. This event also occurs for other actions related to database or registration status, such as database shutdowns and startups, or registration timeouts.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleDependency Class](#)
- [OracleDependency Members](#)

## OracleNotificationRequest Class

An `OracleNotificationRequest` class represents a notification request to be subscribed in the database. It contains information about the request and the characteristics of the notification. Using the `OracleNotificationRequest` class, Oracle Data Provider for .NET can create the notification registration in the database.

### Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleNotificationRequest`

### Declaration

```
// C#  
public sealed class OracleNotificationRequest
```

### Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Static Methods](#)
- [OracleNotificationRequest Properties](#)
- [OracleNotificationRequest Methods](#)

## OracleNotificationRequest Members

OracleNotificationRequest members are listed in the following tables.

### OracleNotificationRequest Static Method

The OracleNotificationRequest static method is listed in [Table 9–12](#).

**Table 9–12 OracleNotificationRequest Static Method**

Static Method	Description
Equals	Inherited from System.Object

### OracleNotificationRequest Properties

OracleNotificationRequest properties are listed in [Table 9–13](#).

**Table 9–13 OracleNotificationRequest Properties**

Properties	Description
<a href="#">IsNotifiedOnce</a>	Indicates whether or not the registration is to be removed upon notification
<a href="#">IsPersistent</a>	Indicates whether or not the notification message should be queued persistently in the database before delivery
<a href="#">Timeout</a>	Specifies the time that the registration remains alive
<a href="#">GroupingNotificationEnabled</a>	Specifies whether grouping notification is enabled or not
<a href="#">GroupingType</a>	Specifies the type of grouping notification
<a href="#">GroupingInterval</a>	Specifies the interval between grouping notifications, in seconds

### OracleNotificationRequest Methods

OracleNotificationRequest methods are listed in [Table 9–14](#).

**Table 9–14 OracleNotificationRequest Methods**

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

## OracleNotificationRequest Static Methods

The `OracleNotificationRequest` static method is listed in [Table 9–15](#).

**Table 9–15** *OracleNotificationRequest Static Method*

Static Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

## OracleNotificationRequest Properties

The `OracleNotificationRequest` properties are listed in [Table 9–16](#).

**Table 9–16 OracleNotificationRequest Properties**

Properties	Description
<a href="#">IsNotifiedOnce</a>	Indicates whether or not the registration is to be removed upon notification
<a href="#">IsPersistent</a>	Indicates whether or not the notification message should be queued persistently in the database before delivery
<a href="#">Timeout</a>	Specifies the time that the registration remains alive
<a href="#">GroupingNotificationEnabled</a>	Specifies whether grouping notification is enabled or not
<a href="#">GroupingType</a>	Specifies the type of grouping notification
<a href="#">GroupingInterval</a>	Specifies the interval between grouping notifications, in seconds

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

## IsNotifiedOnce

This property indicates whether or not the registration is to be removed upon notification.

### Declaration

```
// C#
public bool IsNotifiedOnce{get; set;}
```

### Property Value

A `bool` value that indicates whether or not the registration is to be removed upon notification.

### Remarks

The default value is `false` for AQ. This is different from change notification where the default value is `true`.

Modifying this property after the completion of a successful registration has no effect.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

## IsPersistent

This property indicates whether or not the notification message should be queued persistently in the database until delivery.

### Declaration

```
// C#  
public bool IsPersistent{get; set;}
```

### Property Value

A `bool` value that indicates whether or not the notifications should be stored persistently in the database until delivery.

When the `IsPersistent` property is set to `True`, the message is queued persistently in the database and cannot be lost upon database failures or shutdowns. When the `IsPersistent` property is set to `False`, the message is stored in an in-memory queue before delivery and could be lost.

This property does not apply to `NotificationRegistration` which is always persistent.

This property only applies to the notification message after it has been sent.

### Remarks

The default value is `false`.

The database performs faster if the message is stored in an in-memory queue rather than a database queue.

Modifying this property after the completion of a successful registration has no effect.

This property is ignored for grouping notifications.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

## Timeout

This property specifies the time, in seconds, that the registration remains alive.

### Declaration

```
// C#  
public long Timeout{get; set;}
```

### Property Value

A `long` value that specifies the time, in seconds, that the registration remains alive. The valid values for the `Timeout` property are between 0 and 4294967295.

### Exceptions

`ArgumentOutOfRangeException` - The specified `Timeout` is invalid.



**Remarks**

The default value is 0 (infinite) for AQ and 50000 for change notification. If the `Timeout` property is set to 0, then the registration does not expire.

If the registration is removed because the `Timeout` value has been reached, then the database sends a notification indicating the expiration.

Modifying this property after the completion of a successful registration has no effect.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

**GroupingNotificationEnabled**

This property specifies whether grouping notification is enabled or not.

**Declaration**

```
// C#
public bool GroupingNotificationEnabled {get; set}
```

**Property Value**

A `true` value indicates that grouping notification is enabled. A `false` value indicates that grouping notification is disabled.

**Remarks**

The default value is `false`.

Modifying this property after the completion of a successful registration has no effect.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

**GroupingType**

This property specifies the type of grouping notification.

**Declaration**

```
// C#
public OracleAQNotificationGroupingType GroupingType {get; set}
```

**Property Value**

An `OracleAQNotificationGroupingType` enum value

**Remarks**

The default value is `OracleAQNotificationGroupingType.Summary`.

Modifying this property after the completion of a successful registration has no effect.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

**GroupingInterval**

This property specifies the interval of grouping notification in seconds. The group notifications are delivered at intervals specified by this property.

**Declaration**

```
// C#  
public int GroupingInterval {get; set}
```

**Property Value**

An integer specifying the grouping interval in seconds.

**Remarks**

The default value is 600 seconds.

The range of GroupingInterval is from 0 to `Int32.MaxValue`.

Modifying this property after the completion of a successful registration has no effect.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

## OracleNotificationRequest Methods

OracleNotificationRequest methods are listed in [Table 9-17](#).

**Table 9-17 OracleNotificationRequest Methods**

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

---

## OracleNotificationEventArgs Class

The `OracleNotificationEventArgs` class provides event data for a notification.

### Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleNotificationEventArgs`

### Declaration

```
// C#  
public sealed class OracleNotificationEventArgs
```

### Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleNotificationEventArgs Members](#)
- [OracleNotificationEventArgs Static Fields](#)
- [OracleNotificationEventArgs Static Methods](#)
- [OracleNotificationEventArgs Properties](#)
- [OracleNotificationEventArgs Methods](#)

## OracleNotificationEventArgs Members

OracleNotificationEventArgs members are listed in the following tables.

### OracleNotificationEventArgs Static Fields

The OracleNotificationEventArgs static field is listed in [Table 9–18](#).

**Table 9–18 OracleNotificationEventArgs Static Field**

Static Field	Description
Empty	Inherited from System.EventArgs

### OracleNotificationEventArgs Static Methods

The OracleNotificationEventArgs static method is listed in [Table 9–19](#).

**Table 9–19 OracleNotificationEventArgs Static Method**

Static Method	Description
Equals	Inherited from System.Object

### OracleNotificationEventArgs Properties

OracleNotificationEventArgs properties are listed in [Table 9–20](#).

**Table 9–20 OracleNotificationEventArgs Properties**

Properties	Description
<a href="#">Details</a>	Contains detailed information about the current notification
<a href="#">Info</a>	Indicates the database events for the notification
<a href="#">ResourceNames</a>	Indicates the database resources related to the current notification
<a href="#">Source</a>	Returns the database event source for the notification
<a href="#">Type</a>	Returns the database event type for the notification

### OracleNotificationEventArgs Methods

OracleNotificationEventArgs methods are listed in [Table 9–21](#).

**Table 9–21 OracleNotificationEventArgs Methods**

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)

## OracleNotificationEventArgs Static Fields

The `OracleNotificationEventArgs` static field is listed in [Table 9-22](#).

**Table 9-22** *OracleNotificationEventArgs Static Field*

Static Field	Description
<code>Empty</code>	Inherited from <code>System.EventArgs</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

## OracleNotificationEventArgs Static Methods

The `OracleNotificationEventArgs` static method is listed in [Table 9-23](#).

**Table 9-23** *OracleNotificationEventArgs Static Method*

Static Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

## OracleNotificationEventArgs Properties

OracleNotificationEventArgs properties are listed in [Table 9–24](#).

**Table 9–24 OracleNotificationEventArgs Properties**

Properties	Description
<a href="#">Details</a>	Contains detailed information about the current notification
<a href="#">Info</a>	Indicates the database events for the notification
<a href="#">ResourceNames</a>	Indicates the database resources related to the current notification
<a href="#">Source</a>	Returns the database event source for the notification
<a href="#">Type</a>	Returns the database event type for the notification

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

## Details

This property contains detailed information about the current notification.

### Declaration

```
// C#
Public DataTable Details{get;}
```

### Property Value

A `DataTable` instance that contains detailed information about the current notification.

### Remarks

The returned `DataTable` object contains column data about the current notification in order as shown in [Table 9–25](#).

**Table 9–25 DataTable Object Column Data**

Name	Type	Description
ResourceName	System.String	The resource name of the invalidated object in the format <Schema_name>.<object_name>
Info	OracleNotificationInfo	The information about the database event that occurs on a resource
Rowid	System.String	The rowid for the invalidated table row
QueryId	Int32	The CHANGE_NOTIFICATION_QUERY_ID

The `QueryId` column contains the `CHANGE_NOTIFICATION_QUERY_ID` that corresponds to the pseudo-column that may have been retrieved by a `SELECT` statement at the time of the query-based notification. Also, the `OracleDependency`



object maintains all the `CHANGE_NOTIFICATION_QUERY_IDS` that are registered with it.

For Continuous Query Notification:

- The `Details` property indicates changes for each invalidated object in the notification in the data table.
- If ROWID information is requested, then the ROWID information is populated into the `Rowid` column. However, if many rows are modified in a table, then the whole table is invalidated, and ROWID information is not provided. Therefore, the `Rowid` column contains all `Null` values.
- If the database event is related to a DDL change of the table or a table drop, then the `Rowid` column is set to `Null`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

## Info

This property indicates the database events for the notification.

### Declaration

```
// C#
public OracleNotificationInfo Info{get;}
```

### Property Value

An `OracleNotificationInfo` value that indicates the database event for the notification.

### Remarks

The `OracleNotificationInfo` value is an enumeration type. If several events are received from the invalidation message, the `Info` property is set to one of the `OracleNotificationInfo` enumeration values associated with the database events. For example, if a table has been altered and a new row has been inserted into another table, the `Info` property is set to either `OracleNotificationInfo.Altered` or `OracleNotificationInfo.Insert`.

To obtain more detailed information from the invalidation message, use the `Details` and the `ResourceNames` properties.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["Details"](#) on page 9-34
- ["ResourceNames"](#) on page 9-36
- ["OracleNotificationInfo Enumeration"](#) on page 9-44

## ResourceNames

This property indicates the database resources related to the current notification.

### Declaration

```
// C#  
public string[] ResourceNames{get;}
```

### Property Value

A string array that indicates the database resources related to the current notification.

### Remarks

For Continuous Query Notification, the `ResourceNames` property contains information about the invalidated object names in the format `<schema_name>.<object_name>`. To obtain more detailed information about the changes for invalidated objects, use the `Details` property.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["Details"](#) on page 9-34

## Source

This property returns the database event source for the notification.

### Declaration

```
// C#  
public OracleNotificationSource Source{get;}
```

### Property Value

The `OracleNotificationSource` value for the notification.

### Remarks

The `OracleNotificationSource` value is an enumeration type. If several event sources are received from the notification message, the `Source` property is set to one of the `OracleNotificationSource` enumeration values related to the database event source. For example, if a table has been altered (by the `ALTER TABLE` command) and a new row has been inserted into the same table, the `Source` property is set to either `OracleNotificationSource.Object` or `OracleNotificationSource.Data`.

For Continuous Query Notification:

- When the `Source` property is set to `OracleNotificationSource.Data`:
  - The `Info` property is set to one of the following:
    - \* `OracleNotificationInfo.Insert`
    - \* `OracleNotificationInfo.Delete`
    - \* `OracleNotificationInfo.Update`

- The `ResourceNames` property is set, and the elements are set to the invalidated object names.
  - The `Details` property contains detailed information on the change of each invalidated table.
  - When the `Source` property is set to `OracleNotificationSource.Database`:
    - The `Info` property is set to one of the following:
      - \* `OracleNotificationInfo.Startup`
      - \* `OracleNotificationInfo.Shutdown`
      - \* `OracleNotificationInfo.Shutdown_Any`
      - \* `OracleNotificationInfo.Dropped`
  - When the `Source` property is set to `OracleNotificationSource.Object`:
    - The `Info` property is set to either `OracleNotificationInfo.Altered` or `OracleNotificationInfo.Dropped`.
    - The `ResourceNames` property is set, and the array elements of the `ResourceNames` property are set to the object names that have been altered or dropped.
    - The `Details` property contains detailed information on the changes of the object.
  - When the `Source` property is set to `OracleNotificationSource.Subscription`:
    - The `Info` property is set to the following:
      - \* `OracleNotificationInfo.End`
- See Also:**
- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
  - [OracleNotificationEventArgs Class](#)
  - [OracleNotificationEventArgs Members](#)
  - ["OracleNotificationSource Enumeration"](#) on page 9-43

## Type

This property returns the database event type for the notification.

### Declaration

```
// C#
public OracleNotificationType Type{get;}
```

### Property Value

An `OracleNotificationType` enumeration value that represents the type of the database event notification.

### Remarks

The `OracleNotificationType` value is an enumeration type. If several event types are received from the notification message, then the `Type` property is set to one of the `OracleNotificationType` enumeration values related to the database event type.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["OracleNotificationType Enumeration"](#) on page 9-42

## OracleNotificationEventArgs Methods

OracleNotificationEventArgs methods are listed in [Table 9–26](#).

**Table 9–26 OracleNotificationEventArgs Methods**

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

## OnChangeEventHandler Delegate

The `OnChangeEventHandler` delegate represents the signature of the method that handles the notification.

### Declaration

```
// C#  
public delegate void OnChangeEventHandler(object sender,  
    OracleNotificationEventArgs args);
```

### Parameters

- *sender*  
The source of the event.
- *args*  
The `OracleNotificationEventArgs` instance that contains the event data.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

## OracleRowidInfo Enumeration

OracleRowidInfo enumeration values specify whether ROWID information is included as part of the ChangeNotificationEventArgs or not.

Table 9–28 lists all the OracleRowidInfo enumeration values with a description of each enumerated value.

**Table 9–27 OracleRowidInfo Members**

Member Name	Description
Default	ROWID information is included only if <code>OracleCommand.AddRowid</code> property is set to true or if ROWID column is explicitly included in the query.
Include	ROWID information is included regardless of whether ROWID is included in the select-list of the query or not.
Exclude	ROWID information is not included regardless of whether ROWID is included in the select-list of the query or not.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["RowidInfo"](#) on page 9-16

## OracleNotificationType Enumeration

OracleNotificationType enumerated values specify the different types that cause the notification.

[Table 9–28](#) lists all the OracleNotificationType enumeration values with a description of each enumerated value.

**Table 9–28 OracleNotificationType Members**

Member Name	Description
Change	A change occurs in the database.
Subscribe	A change occurs in the subscription.
Query	A query-based change occurs in the database

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:** ["Oracle.DataAccess.Client Namespace"](#) on page 1-4



---

## OracleNotificationSource Enumeration

OracleNotificationSource enumerated values specify the different sources that cause notification.

[Table 9–29](#) lists all the OracleNotificationSource enumeration values with a description of each enumerated value.

**Table 9–29 OracleNotificationSource Members**

Member Name	Description
Data	The data in a table has changed.
Database	A database event such as a database startup or shutdown occurs.
Object	A database object is altered or dropped.
Subscription	The subscription is changed.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:** ["Oracle.DataAccess.Client Namespace"](#) on page 1-4

---

## OracleNotificationInfo Enumeration

OracleNotificationInfo enumerated values specify the database event that causes the notification.

[Table 9–30](#) lists all the OracleNotificationInfo enumeration values with a description of each enumerated value.

**Table 9–30 OracleNotificationInfo Members**

Member Name	Description
Insert	A row is inserted.
Delete	A row is deleted.
Update	A row is updated.
Startup	A database starts.
Shutdown	A database shuts down.
Shutdown_Any	A database instance in a Real Application Cluster (RAC) environment shuts down.
Alter	An object is altered.
Drop	An object or database is dropped.
End	A registration is removed.
Error	A notification error occurs.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:** ["Oracle.DataAccess.Client Namespace"](#) on page 1-4

# 10

---

---

## Oracle Data Provider for .NET Globalization Classes

This chapter describes the ODP.NET globalization classes.

This chapter contains these topics:

- [OracleGlobalization Class](#)

## OracleGlobalization Class

The `OracleGlobalization` class is used to obtain and set the Oracle globalization settings of the session, thread, and local computer (read-only).

### Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleGlobalization`

### Declaration

```
public sealed class OracleGlobalization : ICloneable, IDisposable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

An exception is thrown for invalid property values. All newly set property values are validated, except the `TimeZone` property.

Changing the `OracleGlobalization` object properties does not change the globalization settings of the session or the thread. Either the `SetSessionInfo` method of the `OracleConnection` object or the `SetThreadInfo` method of the `OracleGlobalization` object must be called to alter the session's and thread's globalization settings, respectively.

### Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class OracleGlobalizationSample  
{  
    static void Main()  
    {  
        // Get thread's globalization info  
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();  
  
        // Prints "glob.Language = AMERICAN"  
        Console.WriteLine("glob.Language = " + glob.Language);  
  
        // Set language on thread's globalization info  
        glob.Language = "FRENCH";  
        OracleGlobalization.SetThreadInfo(glob);  
        OracleGlobalization.GetThreadInfo(glob);  
  
        // Prints "glob.Language = FRENCH"  
        Console.WriteLine("glob.Language = " + glob.Language);  
  
        glob.Dispose();  
    }  
}
```

**Requirements**

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later  
Microsoft .NET Framework Version:  
2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Members](#)
- [OracleGlobalization Static Methods](#)
- [OracleGlobalization Properties](#)
- [OracleGlobalization Public Methods](#)
- *Oracle Database SQL Reference*
- *Oracle Database Globalization Support Guide*

## OracleGlobalization Members

OracleGlobalization members are listed in the following tables.

### OracleGlobalization Static Methods

The OracleGlobalization static methods are listed in [Table 10-1](#).

**Table 10-1 OracleGlobalization Static Methods**

Name	Description
<a href="#">GetClientInfo</a>	Returns an OracleGlobalization object that represents the Oracle globalization settings of the local computer (Overloaded)
<a href="#">GetThreadInfo</a>	Returns or refreshes an OracleGlobalization instance that represents Oracle globalization settings of the current thread (Overloaded)
<a href="#">SetThreadInfo</a>	Sets Oracle globalization parameters to the current thread

### OracleGlobalization Properties

The OracleGlobalization properties are listed in [Table 10-2](#).

**Table 10-2 OracleGlobalization Properties**

Name	Description
<a href="#">Calendar</a>	Specifies the calendar system
<a href="#">ClientCharacterSet</a>	Specifies a client character set
<a href="#">Comparison</a>	Specifies a method of comparison for WHERE clauses and comparison in PL/SQL blocks
<a href="#">Currency</a>	Specifies the string to use as a local currency symbol for the L number format element
<a href="#">DateFormat</a>	Specifies the date format for Oracle Date type as a string
<a href="#">DateLanguage</a>	Specifies the language used to spell day and month names and date abbreviations
<a href="#">DualCurrency</a>	Specifies the dual currency symbol, such as <i>Euro</i> , for the U number format element
<a href="#">ISOCurrency</a>	Specifies the string to use as an international currency symbol for the C number format element
<a href="#">Language</a>	Specifies the default language of the database
<a href="#">LengthSemantics</a>	Enables creation of CHAR and VARCHAR2 columns using either byte or character (default) length semantics
<a href="#">NCharConversionException</a>	Determines whether or not data loss during an implicit or explicit character type conversion reports an error
<a href="#">NumericCharacters</a>	Specifies the characters used for the decimal character and the group separator character for numeric values in strings
<a href="#">Sort</a>	Specifies the collating sequence for ORDER by clause
<a href="#">Territory</a>	Specifies the name of the territory
<a href="#">TimeStampFormat</a>	Specifies the string format for TimeStamp types
<a href="#">TimeStampTZFormat</a>	Specifies the string format for TimeStampTZ types
<a href="#">TimeZone</a>	Specifies the time zone region name

## OracleGlobalization Public Methods

OracleGlobalization public methods are listed in [Table 10–3](#).

**Table 10–3 OracleGlobalization Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a copy of an OracleGlobalization object
Dispose	Inherited from System.ComponentModel.Component

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## OracleGlobalization Static Methods

The `OracleGlobalization` static methods are listed in [Table 10–4](#).

**Table 10–4 OracleGlobalization Static Methods**

Name	Description
<a href="#">GetClientInfo</a>	Returns an <code>OracleGlobalization</code> object that represents the Oracle globalization settings of the local computer (Overloaded)
<a href="#">GetThreadInfo</a>	Returns or refreshes an <code>OracleGlobalization</code> instance that represents Oracle globalization settings of the current thread (Overloaded)
<a href="#">SetThreadInfo</a>	Sets Oracle globalization parameters to the current thread

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

### GetClientInfo

`GetClientInfo` returns an `OracleGlobalization` object instance that represents the Oracle globalization settings of the local computer.

**Overload List:**

- [GetClientInfo\(\)](#)  
This method returns an `OracleGlobalization` instance that represents the globalization settings of the local computer.
- [GetClientInfo\(OracleGlobalization\)](#)  
This method refreshes the provided `OracleGlobalization` object with the globalization settings of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

### GetClientInfo()

This method returns an `OracleGlobalization` instance that represents the globalization settings of the local computer.

**Declaration**

```
// C#
public static OracleGlobalization GetClientInfo();
```

**Return Value**

An `OracleGlobalization` instance.



**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetClientInfoSample
{
    static void Main()
    {
        // Get client's globalization info
        OracleGlobalization glob = OracleGlobalization.GetClientInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**GetClientInfo(OracleGlobalization)**

This method refreshes the provided `OracleGlobalization` object with the globalization settings of the local computer.

**Declaration**

```
// C#
public static void GetClientInfo(OracleGlobalization oraGlob);
```

**Parameters**

- *oraGlob*  
The `OracleGlobalization` object being updated.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetClientInfoSample
{
    static void Main()
    {
        // Get client's globalization info
        OracleGlobalization glob = OracleGlobalization.GetClientInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        // Get client's globalization info using overload
        OracleGlobalization.GetClientInfo(glob);
    }
}
```

```
// Prints "glob.Language = AMERICAN"
Console.WriteLine("glob.Language = " + glob.Language);

glob.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## GetThreadInfo

GetThreadInfo returns or refreshes an OracleGlobalization instance.

**Overload List:**

- [GetThreadInfo\(\)](#)

This method returns an OracleGlobalization object instance of the current thread.

- [GetThreadInfo\(OracleGlobalization\)](#)

This method refreshes the OracleGlobalization object instance with the globalization settings of the current thread.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## GetThreadInfo()

This method returns an OracleGlobalization instance of the current thread.

**Declaration**

```
// C#
public static OracleGlobalization GetThreadInfo();
```

**Return Value**

An OracleGlobalization instance.

**Remarks**

Initially, GetThreadInfo() returns an OracleGlobalization object that has the same property values as that returned by GetClientInfo(), unless the application changes it by invoking SetThreadInfo().

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
```

```

class GetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        // Get thread's globalization info using overloaded
        OracleGlobalization.GetThreadInfo(glob);

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**GetThreadInfo(OracleGlobalization)**

This method refreshes the `OracleGlobalization` object with the globalization settings of the current thread.

**Declaration**

```

// C#
public static void GetThreadInfo(OracleGlobalization oraGlob);

```

**Parameters**

- *oraGlob*

The `OracleGlobalization` object being updated.

**Remarks**

Initially `GetThreadInfo()` returns an `OracleGlobalization` object that has the same property values as that returned by `GetClientInfo()`, unless the application changes it by invoking `SetThreadInfo()`.

**Example**

```

// C#

using System;
using Oracle.DataAccess.Client;

class GetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info

```

```
OracleGlobalization glob = OracleGlobalization.GetThreadInfo();

// Prints "glob.Language = AMERICAN"
Console.WriteLine("glob.Language = " + glob.Language);

// Get thread's globalization info using overloaded
OracleGlobalization.GetThreadInfo(glob);

// Prints "glob.Language = AMERICAN"
Console.WriteLine("glob.Language = " + glob.Language);

glob.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## SetThreadInfo

This method sets Oracle globalization parameters to the current thread.

**Declaration**

```
// C#
public static void SetThreadInfo(OracleGlobalization oraGlob);
```

**Parameters**

- *oraGlob*  
An `OracleGlobalization` object.

**Remarks**

Any .NET string conversions to and from ODP.NET Types, as well as ODP.NET Type constructors, use the globalization property values where applicable. For example, when constructing an `OracleDate` structure from a .NET string, that string is expected to be in the format specified by the `OracleGlobalization.DateFormat` property of the thread.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;

class SetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob1 = OracleGlobalization.GetThreadInfo();

        // Prints "glob1.Language = AMERICAN"
        Console.WriteLine("glob1.Language = " + glob1.Language);
    }
}
```

```
// Set language on thread's globalization info
glob1.Language = "FRENCH";
OracleGlobalization.SetThreadInfo(glob1);
OracleGlobalization glob2 = OracleGlobalization.GetThreadInfo();

// Prints "glob2.Language = FRENCH"
Console.WriteLine("glob2.Language = " + glob2.Language);

glob1.Dispose();
glob2.Dispose();
}
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## OracleGlobalization Properties

The `OracleGlobalization` properties are listed in [Table 10-5](#).

**Table 10-5 OracleGlobalization Properties**

Name	Description
<a href="#">Calendar</a>	Specifies the calendar system
<a href="#">ClientCharacterSet</a>	Specifies a client character set
<a href="#">Comparison</a>	Specifies a method of comparison for <code>WHERE</code> clauses and comparison in PL/SQL blocks
<a href="#">Currency</a>	Specifies the string to use as a local currency symbol for the L number format element
<a href="#">DateFormat</a>	Specifies the date format for Oracle <code>Date</code> type as a string
<a href="#">DateLanguage</a>	Specifies the language used to spell day and month names and date abbreviations
<a href="#">DualCurrency</a>	Specifies the dual currency symbol, such as <i>Euro</i> , for the U number format element
<a href="#">ISOCurrency</a>	Specifies the string to use as an international currency symbol for the C number format element
<a href="#">Language</a>	Specifies the default language of the database
<a href="#">LengthSemantics</a>	Enables creation of <code>CHAR</code> and <code>VARCHAR2</code> columns using either byte or character (default) length semantics
<a href="#">NCharConversionException</a>	Determines whether or not data loss during an implicit or explicit character type conversion reports an error
<a href="#">NumericCharacters</a>	Specifies the characters used for the decimal character and the group separator character for numeric values in strings
<a href="#">Sort</a>	Specifies the collating sequence for <code>ORDER BY</code> clause
<a href="#">Territory</a>	Specifies the name of the territory
<a href="#">TimeStampFormat</a>	Specifies the string format for <code>TimeStamp</code> types
<a href="#">TimeStampTZFormat</a>	Specifies the string format for <code>TimeStampTZ</code> types
<a href="#">TimeZone</a>	Specifies the time zone region name

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

### Calendar

This property specifies the calendar system.

**Declaration**

```
// C#
public string Calendar {get; set;}
```

**Property Value**

A string representing the Calendar.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_CALENDAR` setting of the local computer. This value is the same regardless of whether or not the `OracleGlobalization` object represents the settings of the client, thread, or session.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**ClientCharacterSet**

This property specifies a client character set.

**Declaration**

```
// C#  
public string ClientCharacterSet {get;}
```

**Property Value**

A string that the provides the name of the character set of the local computer.

**Remarks**

The default value is the character set of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**Comparison**

This property represents a method of comparison for `WHERE` clauses and comparison in PL/SQL blocks.

**Declaration**

```
// C#  
public string Comparison {get; set;}
```

**Property Value**

A string that provides the name of the method of comparison.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the NLS\_COMP setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**Currency**

This property specifies the string to use as a local currency symbol for the L number format element.

**Declaration**

```
// C#  
public string Currency {get; set;}
```

**Property Value**

The string to use as a local currency symbol for the L number format element.

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

**Remarks**

The default value is the NLS\_CURRENCY setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Reference* for further information on the L number format element

**DateFormat**

This property specifies the date format for Oracle Date type as a string.

**Declaration**

```
// C#  
public string DateFormat {get; set;}
```

**Property Value**

The date format for Oracle Date type as a string

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

**Remarks**

The default value is the NLS\_DATE\_FORMAT setting of the local computer.



**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## DateLanguage

This property specifies the language used to spell names of days and months, and date abbreviations (for example: a.m., p.m., AD, BC).

**Declaration**

```
// C#  
public string DateLanguage {get; set;}
```

**Property Value**

A string specifying the language.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_DATE_LANGUAGE` setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## DualCurrency

This property specifies the dual currency symbol, such as *Euro*, for the U number format element.

**Declaration**

```
// C#  
public string DualCurrency {get; set;}
```

**Property Value**

A string that provides the dual currency symbol.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_DUAL_CURRENCY` setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Reference* for further information on the U number format element

## ISOCurrency

This property specifies the string to use as an international currency symbol for the C number format element.

**Declaration**

```
// C#  
public string ISOCurrency {get; set;}
```

**Property Value**

The string used as an international currency symbol.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_ISO_CURRENCY` setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Reference* for further information on the C number format element

## Language

This property specifies the default language of the database.

**Declaration**

```
// C#  
public string Language {get; set;}
```

**Property Value**

The default language of the database.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_LANGUAGE` setting of the local computer.

Language is used for messages, day and month names, and sorting algorithms. It also determines NLS\_DATE\_LANGUAGE and NLS\_SORT parameter values.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## LengthSemantics

This property indicates whether or not CHAR and VARCHAR2 columns use byte or character (default) length semantics.

**Declaration**

```
// C#
public string LengthSemantics {get; set;}
```

**Property Value**

A string that indicates either byte or character length semantics.

**Exceptions**

ObjectDisposedException - The object is already disposed.

**Remarks**

The default value is the NLS\_LENGTH\_SEMANTICS setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## NCharConversionException

This property determines whether or not data loss during an implicit or explicit character type conversion reports an error.

**Declaration**

```
// C#
public bool NCharConversionException {get; set;}
```

**Property Value**

A string that indicates whether or not a character type conversion causes an error message.

**Exceptions**

ObjectDisposedException - The object is already disposed.

**Remarks**

The default value of NLS\_NCHAR\_CONV\_EXCP is False, unless it is overridden by a setting in the INIT.ORA file.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**NumericCharacters**

This property specifies the characters used for the decimal character and the group separator character for numeric values in strings.

**Declaration**

```
// C#  
public string NumericCharacters {get; set;}
```

**Property Value**

A string that represents the characters used.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_NUMERIC_CHARACTERS` setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

**Sort**

This property specifies the collating sequence for `ORDER by` clause.

**Declaration**

```
// C#  
public string Sort {get; set;}
```

**Property Value**

A string that indicates the collating sequence.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_SORT` setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## Territory

This property specifies the name of the territory.

### Declaration

```
// C#  
public string Territory {get; set;}
```

### Property Value

A string that provides the name of the territory.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

### Remarks

The default value is the `NLS_TERRITORY` setting of the local computer.

Changing this property changes other globalization properties.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database Globalization Support Guide.*

## TimeStampFormat

This property specifies the string format for `TimeStamp` types.

### Declaration

```
// C#  
public string TimeStampFormat {get; set;}
```

### Property Value

The string format for `TimeStamp` types.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

### Remarks

The default value is the `NLS_TIMESTAMP_FORMAT` setting of the local computer.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## TimeStampTZFormat

This property specifies the string format for `TimeStampTZ` types.

**Declaration**

```
// C#  
public string TimeStampTZFormat {get; set;}
```

**Property Value**

The string format for `TimeStampTZ` types.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the `NLS_TIMESTAMP_TZ_FORMAT` setting of the local computer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## TimeZone

This property specifies the time zone region name or hour offset.

**Declaration**

```
// C#  
public string TimeZone {get; set;}
```

**Property Value**

The string represents the time zone region name or the time zone offset.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is the time zone region name of the local computer

`TimeZone` is only used when the thread constructs one of the `TimeStamp` structures. `TimeZone` has no effect on the session.

`TimeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

---

**Note:** PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleGlobalization`.

---

This property returns an empty string if the `OracleGlobalization` object is obtained using `GetSessionInfo()` or `GetSessionInfo(OracleGlobalization)`. Initially, by default, the time zone of the session is identical to the time zone of the thread. Therefore, given that the session time zone is not changed by invoking `ALTER SESSION` calls, the session time zone can be fetched from the client's globalization settings.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

## OracleGlobalization Public Methods

OracleGlobalization public methods are listed in [Table 10–6](#).

**Table 10–6 OracleGlobalization Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a copy of an OracleGlobalization object
Dispose	Inherited from <code>System.ComponentModel.Component</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

### Clone

This method creates a copy of an OracleGlobalization object.

**Declaration**

```
// C#  
public object Clone();
```

**Return Value**

An OracleGlobalization object.

**Implements**

ICloneable

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)



---

---

## Oracle Data Provider for .NET Failover Classes

This chapter describes the ODP.NET failover classes and enumerations.

This chapter contains these topics:

- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventHandler Delegate](#)
- [FailoverEvent Enumeration](#)
- [FailoverReturnCode Enumeration](#)
- [FailoverType Enumeration](#)

## OracleFailoverEventArgs Class

The `OracleFailoverEventArgs` class provides event data for the `OracleConnection.Failover` event. When database failover occurs, the `OracleConnection.Failover` event is triggered along with the `OracleFailoverEventArgs` object that stores the event data.

### Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleFailoverEventArgs`

### Declaration

```
// C#
public sealed class OracleFailoverEventArgs
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example (Oracle.DataAccess.Client only)

```
// Transparent Application Failover (TAF) Setup
// Refer Oracle® Database Net Services Administrator's Guide

// C#

using System;
using System.Threading;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class FailoverSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Register the event handler OnFailover
        con.Failover += new OracleFailoverEventHandler(OnFailover);

        Console.WriteLine("Wait for a failover for 5 seconds");
        Thread.Sleep(5000);

        con.Close();
        con.Dispose();
    }

    // TAF callback function
    static FailoverReturnCode OnFailover(object sender,
        OracleFailoverEventArgs eventArgs)
    {
        switch (eventArgs.FailoverEvent)

```

```
{
    case FailoverEvent.Begin:
    {
        Console.WriteLine("FailoverEvent.Begin - Failover is starting");
        Console.WriteLine("FailoverType = " + eventArgs.FailoverType);
        break;
    }
    case FailoverEvent.End:
    {
        Console.WriteLine("FailoverEvent.End - Failover was successful");
        break;
    }
    case FailoverEvent.Reauth:
    {
        Console.WriteLine("FailoverEvent.Reauth - User reauthenticated");
        break;
    }
    case FailoverEvent.Error:
    {
        Console.WriteLine("FailoverEvent.Error - Failover was unsuccessful");

        // Sleep for 3 sec and Retry
        Thread.Sleep(3000);
        return FailoverReturnCode.Retry;
    }
    case FailoverEvent.Abort:
    {
        Console.WriteLine("FailoverEvent.Abort - Failover was unsuccessful");
        break;
    }
    default:
    {
        Console.WriteLine("Invalid FailoverEvent : " + eventArgs.FailoverEvent);
        break;
    }
}
return FailoverReturnCode.Success;
}
```

**Requirements**

Namespace: Oracle.DataAccess.Client

Assembly: Oracle.DataAccess.dll

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleFailoverEventArgs Members](#)
- [OracleFailoverEventArgs Static Methods](#)
- [OracleFailoverEventArgs Properties](#)
- [OracleFailoverEventArgs Public Methods](#)
- ["OracleConnection Class"](#) on page 5-64
- *Oracle Net Services Administrator's Guide*

## OracleFailoverEventArgs Members

OracleFailoverEventArgs members are listed in the following tables.

### OracleFailoverEventArgs Static Methods

The OracleFailoverEventArgs static methods are listed in [Table 11-1](#).

**Table 11-1 OracleFailoverEventArgs Static Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)

### OracleFailoverEventArgs Properties

The OracleFailoverEventArgs properties are listed in [Table 11-2](#).

**Table 11-2 OracleFailoverEventArgs Properties**

Name	Description
<a href="#">FailoverType</a>	Specifies the type of failover the client has requested
<a href="#">FailoverEvent</a>	Indicates the state of the failover

### OracleFailoverEventArgs Public Methods

The OracleFailoverEventArgs public methods are listed in [Table 11-3](#).

**Table 11-3 OracleFailoverEventArgs Public Methods**

Name	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleFailoverEventArgs Class](#)
- ["FailoverType Enumeration"](#) on page 11-12

## OracleFailoverEventArgs Static Methods

The `OracleFailoverEventArgs` static methods are listed in [Table 11-1](#).

**Table 11-4** *OracleFailoverEventArgs Static Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

## OracleFailoverEventArgs Properties

The `OracleFailoverEventArgs` properties are listed in [Table 11–5](#).

**Table 11–5 OracleFailoverEventArgs Properties**

Name	Description
<a href="#">FailoverType</a>	Specifies the type of failover the client has requested
<a href="#">FailoverEvent</a>	Indicates the state of the failover

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

### FailoverType

This property indicates the state of the failover.

**Declaration**

```
// C#
public FailoverType FailoverType {get;}
```

**Property Value**

A `FailoverType` enumeration value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["FailoverType Enumeration"](#) on page 11-12

### FailoverEvent

This property indicates the state of the failover.

**Declaration**

```
// C#
public FailoverEvent FailoverEvent {get;}
```

**Property Value**

A `FailoverEvent` enumerated value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["FailoverEvent Enumeration"](#) on page 11-10

## OracleFailoverEventArgs Public Methods

The `OracleFailoverEventArgs` public methods are listed in [Table 11-6](#).

**Table 11-6** *OracleFailoverEventArgs Public Methods*

Name	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)



---

## OracleFailoverEventHandler Delegate

The `OracleFailoverEventHandler` represents the signature of the method that handles the `OracleConnection.Failover` event.

### Declaration

```
// C#  
public delegate FailoverReturnCode OracleFailoverEventHandler(object sender,  
    OracleFailoverEventArgs eventArgs);
```

### Parameter

- *sender*  
The source of the event.
- *eventArgs*  
The `OracleFailoverEventArgs` object that contains the event data.

### Return Type

An `int`.

### Remarks

To receive failover notifications, a callback function can be registered as follows:

```
ConObj.Failover += new OracleFailoverEventHandler(OnFailover);
```

The definition of the callback function `OnFailover` can be as follows:

```
public FailoverReturnCode OnFailover(object sender, OracleFailoverEventArgs  
eventArgs)
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

Comment: Not supported in a .NET stored procedure

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["Failover" on page 5-111](#)

## FailoverEvent Enumeration

FailoverEvent enumerated values are used to specify the state of the failover.

[Table 11-7](#) lists all the FailoverEvent enumeration values with a description of each enumerated value.

**Table 11-7 FailoverEvent Enumeration Values**

Member Names	Description
FailoverEvent.Begin	Indicates that failover has detected a lost connection and that failover is starting.
FailoverEvent.End	Indicates successful completion of failover.
FailoverEvent.Abort	Indicates that failover was unsuccessful, and there is no option of retrying.
FailoverEvent.Error	Indicates that failover was unsuccessful, and it gives the application the opportunity to handle the error and retry failover. The application can retry failover by returning <code>FailoverReturnCode.Retry</code> for the event notification.
FailoverEvent.Reauth	Indicates that a user handle has been reauthenticated. This applies to the situation where a client has multiple user sessions on a single server connection. During the initial failover, only the active user session is failed over. Other sessions are failed over when the application tries to use them. This is the value passed to the callback during these subsequent failovers.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- [FailoverEvent Enumeration](#) on page 11-10
- ["OracleFailoverEventArgs Class"](#) on page 11-2
- ["FailoverEvent"](#) on page 11-7
- *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Net Services Reference Guide*

## FailoverReturnCode Enumeration

FailoverReturnCode enumerated values are passed back by the application to the ODP.NET provider to request a retry in case of a failover error, or to continue in case of a successful failover.

Table 11–8 lists the FailoverReturnCode enumeration values with a description of each enumerated value.

**Table 11–8 FailoverReturnCode Enumeration Values**

Member Names	Description
FailoverReturnCode.Retry	Requests ODP.NET to retry failover in case FailoverEvent.Error is passed to the application
FailoverReturnCode.Success	Requests ODP.NET to proceed so that the application receive more notifications, if any

### Requirements

Namespace: Oracle.DataAccess.Client

Assembly: Oracle.DataAccess.dll

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- [FailoverEvent Enumeration](#) on page 11-10
- ["OracleFailoverEventArgs Class"](#) on page 11-2
- ["FailoverEvent"](#) on page 11-7
- *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Net Services Reference Guide*

## FailoverType Enumeration

FailoverType enumerated values are used to indicate the type of failover event that was raised.

[Table 11-9](#) lists all the FailoverType enumeration values with a description of each enumerated value.

**Table 11-9 FailoverType Enumeration Values**

Member Names	Description
FailoverType.Session	Indicates that the user has requested only session failover.
FailoverType.Select	Indicates that the user has requested select and session failover.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- [FailoverEvent Enumeration](#) on page 11-10
- ["OracleFailoverEventArgs Class"](#) on page 11-2
- ["FailoverType"](#) on page 11-7
- *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Net Services Reference Guide*

---

---

## Advanced Queuing Support

This chapter describes the following Oracle Data Provider for .NET classes:

- [OracleAQAgent Class](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQMessage Class](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventHandler Delegate](#)
- [OracleAQQueue Class](#)
- [OracleAQDequeueMode Enumeration](#)
- [OracleAQMessageDeliveryMode Enumeration](#)
- [OracleAQMessageState Enumeration](#)
- [OracleAQMessageType Enumeration](#)
- [OracleAQNavigationMode Enumeration](#)
- [OracleAQNotificationGroupingType Enumeration](#)
- [OracleAQNotificationType Enumeration](#)
- [OracleAQVisibilityMode Enumeration](#)

## OracleAQAgent Class

The `OracleAQAgent` class represents agents that may be senders or recipients of a message.

### Class Inheritance

`System.Object`

`OracleAQAgent`

### Declaration

```
// C#  
public sealed class OracleAQAgent
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

An agent may be a consumer, another queue, or a consumer of another queue. The queue may be either local or remote. A remote queue is specified through a database link.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQAgent Members](#)
- [OracleAQAgent Constructors](#)
- [OracleAQAgent Properties](#)

## OracleAQAgent Members

OracleAQAgent members are listed in the following tables.

### OracleAQAgent Constructors

OracleAQAgent constructors are listed in [Table 12-1](#).

**Table 12-1 OracleAQAgent Constructors**

Constructor	Description
<a href="#">OracleAQAgent Constructors</a>	Instantiates a new instance of the OracleAQAgent class (Overloaded).

### OracleAQAgent Properties

OracleAQAgent properties are listed in [Table 12-2](#).

**Table 12-2 OracleAQAgent Properties**

Property	Description
<a href="#">Address</a>	Specifies the address of the agent.
<a href="#">Name</a>	Specifies the name of the agent.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQAgent Class](#)

## OracleAQAgent Constructors

OracleAQAgent constructors instantiate new instances of the OracleAQAgent class.

### Overload List:

- [OracleAQAgent \(string\)](#)

This constructor instantiates the OracleAQAgent class using the specified name.

- [OracleAQAgent \(string, string\)](#)

This constructor instantiates the OracleAQAgent class using the specified name and address.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

### OracleAQAgent (string)

This constructor instantiates the OracleAQAgent class using the specified name.

### Declaration

```
// C#  
public OracleAQAgent(string name);
```

### Parameters

- *name*

The name of the agent.

### Exceptions

ArgumentNullException - The *name* parameter is null.

ArgumentException - The *name* parameter is empty.

### Remarks

The agent name signifies the name of a producer or consumer of a message. In the context of functionality exposed by `Listen`, an agent name corresponds to the name of a consumer for which a message is expected on a multiconsumer queue. It may also be set on a message to signify sender identification or intended recipients of the message.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

### OracleAQAgent (string, string)

This constructor instantiates the OracleAQAgent class using the specified name and address.



## Declaration

```
// C#  
public OracleAQAgent(string name, string address);
```

## Parameters

- *name*  
The name of the agent.
- *address*  
The address is of the form [*schema.*]*queue*[*@dblink*].

## Exceptions

`ArgumentNullException` - The *address* parameter is null.

`ArgumentException` - The *address* parameter is empty.

## Remarks

The agent name signifies the name of a producer or consumer of a message. In the context of functionality exposed by `Listen`, an agent name corresponds to the name of a consumer for which a message is expected on a multiconsumer queue.

The *name* parameter can be specified as `null` in this constructor. In such a scenario, the agent only has an *address*.

The *address* parameter signifies the name of the queue against which this agent listens for new messages. The *address* represents a queue at a local or remote database. The validity of the *address* is not checked implicitly. The exceptions due to wrong *address* are thrown only during database operations such as `Listen`.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

## OracleAQAgent Properties

OracleAQAgent properties are listed in [Table 12-3](#).

**Table 12-3 OracleAQAgent Properties**

Property	Description
<a href="#">Address</a>	Specifies the address of the agent.
<a href="#">Name</a>	Specifies the name of the agent.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

### Address

This instance property specifies the address of the agent.

**Declaration**

```
// C#  
public string Address {get; }
```

**Property Value**

A *string* that specifies the agent address.

**Remarks**

The address represents a queue at a local or remote database. The default value is *null*. The address of the agent is of the form *[schema.]queue[@dblink]*. The string length can be up to 128 characters.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

### Name

This instance property specifies the name of the agent.

**Declaration**

```
// C#  
public string Name {get; }
```

**Property Value**

A *string*.

**Remarks**

The default is `null`. The string length can be up to 30 characters. A non-`null` value implies that this agent name either corresponds to a consumer name in a multiconsumer queue, or a recipient as specified in message properties.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

---

## OracleAQDequeueOptions Class

An `OracleAQDequeueOptions` object represents the options available when dequeuing a message from an `OracleAQQueue` object.

### Class Inheritance

`System.Object`

`OracleAQDequeueOptions`

### Declaration

```
// C#  
public sealed class OracleAQDequeueOptions : ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQDequeueOptions Members](#)
- [OracleAQDequeueOptions Constructor](#)
- [OracleAQDequeueOptions Properties](#)
- [OracleAQDequeueOptions Public Methods](#)

## OracleAQDequeueOptions Members

OracleAQDequeueOptions members are listed in the following tables.

### OracleAQDequeueOptions Constructor

The OracleAQDequeueOptions constructor is listed in [Table 12–4](#).

**Table 12–4 OracleAQDequeueOptions Constructor**

Constructor	Description
<a href="#">OracleAQDequeueOptions Constructor</a>	Instantiates a new instance of the OracleAQDequeueOptions class

### OracleAQDequeueOptions Properties

OracleAQDequeueOptions properties are listed in [Table 12–5](#).

**Table 12–5 OracleAQDequeueOptions Properties**

Property	Description
<a href="#">ConsumerName</a>	Specifies the consumer name for which to dequeue the message
<a href="#">Correlation</a>	Specifies the correlation identifier of the message to be dequeued
<a href="#">DeliveryMode</a>	Specifies the expected delivery mode of the message being dequeued
<a href="#">DequeueMode</a>	Specifies the locking behavior associated with the dequeue operation
<a href="#">MessageId</a>	Specifies the message identifier of the message to be dequeued
<a href="#">NavigationMode</a>	Specifies the position of the message that will be retrieved
<a href="#">ProviderSpecificType</a>	Specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type
<a href="#">Visibility</a>	Specifies whether or not the new message is dequeued as part of the current transaction
<a href="#">Wait</a>	Specifies the wait time, in seconds, for a message that matches the search criteria

### OracleAQDequeueOptions Public Methods

OracleAQDequeueOptions public methods are listed in [Table 12–6](#).

**Table 12–6 OracleAQDequeueOptions Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a copy of an OracleAQDequeueOptions object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQDequeueOptions Class](#)

## OracleAQDequeueOptions Constructor

The `OracleAQDequeueOptions` constructor creates an instance of the `OracleAQDequeueOptions` class and sets all its properties to their default values.

### Declaration

```
// C#  
public OracleAQDequeueOptions();
```

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

## OracleAQDequeueOptions Properties

OracleAQDequeueOptions properties are listed in [Table 12–7](#).

**Table 12–7 OracleAQDequeueOptions Properties**

Property	Description
<a href="#">ConsumerName</a>	Specifies the consumer name for which to dequeue the message
<a href="#">Correlation</a>	Specifies the correlation identifier of the message to be dequeued
<a href="#">DeliveryMode</a>	Specifies the expected delivery mode of the message being dequeued
<a href="#">DequeueMode</a>	Specifies the locking behavior associated with the dequeue operation
<a href="#">MessageId</a>	Specifies the message identifier of the message to be dequeued
<a href="#">NavigationMode</a>	Specifies the position of the message that will be retrieved
<a href="#">ProviderSpecificType</a>	Specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type
<a href="#">Visibility</a>	Specifies whether or not the new message is dequeued as part of the current transaction
<a href="#">Wait</a>	Specifies the wait time, in seconds, for a message that matches the search criteria

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

### ConsumerName

This instance property specifies the consumer name for which to dequeue the message.

**Declaration**

```
// C#
public string ConsumerName {get;set;}
```

**Property Value**

A string.

**Remarks**

The `ConsumerName` property only accesses those messages that match the consumer name. If a queue is not set up for multiple consumers, then this field should be set to null.



**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

**Correlation**

This instance property specifies the correlation identifier of the message to be dequeued.

**Declaration**

```
// C#
public string Correlation {get;set;}
```

**Property Value**

A string.

**Remarks**

This property specifies the identification of the message to be dequeued. Special pattern matching characters, such as the percent sign (%) and the underscore (\_) can be used. If more than one message satisfies the pattern, then the order of dequeuing is undetermined.

The maximum length of `Correlation` is 128.

`MessageId` and `Correlation` are two independent identifiers. While `MessageId` is unique for a message, a group of messages can be assigned the same `Correlation`. Also, pattern matching is possible only with `Correlation`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

**DeliveryMode**

This instance property specifies the expected delivery mode of the message being dequeued.

**Declaration**

```
// C#
public OracleAQMessageDeliveryMode DeliveryMode {get;set;}
```

**Property Value**

An `OracleAQMessageDeliveryMode` enumerated value.

**Remarks**

This property specifies the type of messages to be dequeued. It can be set to dequeue either persistent or buffered messages, or both from a queue. The following values are valid:

- `OracleAQMessageDeliveryMode.Persistent`

- `OracleAQMessageDeliveryMode.Buffered`
- `OracleAQMessageDeliveryMode.PersistentOrBuffered`

The default value is `OracleAQMessageDeliveryMode.Persistent`.

Buffered messaging is supported in all queue tables created with a database compatibility level of 8.1 or higher.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

## DequeueMode

This instance property specifies the locking behavior associated with the dequeue operation.

**Declaration**

```
// C#  
public OracleAQDequeueMode DequeueMode {get;set;}
```

**Property Value**

An `OracleAQDequeueMode` enumerated value.

**Exceptions**

`ArgumentOutOfRangeException` - The specified `DequeueMode` value is invalid.

**Remarks**

The default value is `OracleAQDequeueMode.Remove`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

## MessageId

This instance property specifies the message identifier of the message to be dequeued.

**Declaration**

```
// C#  
public byte[] MessageId {get;set;}
```

**Property Value**

A `byte[ ]`.

**Remarks**

The dequeue operation succeeds only if the message ID of the message being dequeued matches with the message ID specified.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

**NavigationMode**

This instance property specifies the position of the message that will be retrieved.

**Declaration**

```
// C#
public OracleAQNavigationMode NavigationMode {get;set;}
```

**Property Value**

An `OracleAQNavigationMode` enumerated value.

**Exceptions**

`ArgumentOutOfRangeException` - The specified `NavigationMode` value is invalid.

**Remarks**

The default value is `OracleAQNavigationMode.NextMessage`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

**ProviderSpecificType**

This property specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type.

**Declaration**

```
// C#
public bool ProviderSpecificType {get;set;}
```

**Property Value**

A `bool`.

**Remarks**

The default value of this property is `false`. For a discussion of how this property affects payload type, refer to ["MessageType"](#) under the `OracleAQQueue` class.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)
- ["MessageType"](#) on page 12-60

## Visibility

This instance property specifies whether or not the new message is dequeued as part of the current transaction.

### Declaration

```
// C#  
public OracleAQVisibilityMode Visibility {get;set;}
```

### Property Value

An `OracleAQVisibilityMode` enumerated value.

### Exceptions

`ArgumentOutOfRangeException` - The `Visibility` value specified is invalid.

### Remarks

The default value is `OracleAQVisibilityMode.OnCommit`. You must use transactions when using the default value for this property. This ensures that applications do not lose messages and the messages are appropriately removed from the queue after the dequeue operation is successful. If transactions are not used when using the default visibility mode of `OracleAQVisibilityMode.OnCommit`, then messages are not removed from the queue.

Using the alternative visibility mode value, `OracleAQVisibilityMode.Immediate` can eliminate the need to create, commit, and rollback a transaction. However, if an error occurs during the dequeue operation, then the message may be lost.

The visibility parameter is ignored when `DequeueMode` is set to `OracleAQDequeueMode.Browse`.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

## Wait

This instance property specifies the wait time, in seconds, for a message that matches the search criteria.

### Declaration

```
// C#  
public int Wait {get;set;}
```

### Property Value

Any positive integer value or 0 or -1.

### Exceptions

`ArgumentOutOfRangeException` - The specified `Wait` value is invalid.

### Remarks

The default value is -1, which implies an infinite wait. The following values are valid:

- Positive integer: Wait time in seconds.
- -1: Wait forever.
- 0: Do not wait.

A value of less than -1 raises an `ArgumentOutOfRangeException`.

This parameter is ignored if messages in the same group are being dequeued.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

## OracleAQDequeueOptions Public Methods

The `OracleAQDequeueOptions` public method is listed in [Table 12–8](#).

**Table 12–8 OracleAQDequeueOptions Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a copy of an <code>OracleAQDequeueOptions</code> object

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

### Clone

This method creates a copy of an `OracleAQDequeueOptions` object.

**Declaration**

```
// C#  
public object Clone();
```

**Return Value**

An `OracleAQDequeueOptions` object.

**Implements**

`ICloneable`.

**Remarks**

The cloned object has the same property values as the object being cloned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

## OracleAQEnqueueOptions Class

The `OracleAQEnqueueOptions` class represents the options available when enqueueing a message to an `OracleAQQueue`.

### Class Inheritance

`System.Object`

`OracleAQEnqueueOptions`

### Declaration

```
// C#  
public sealed class OracleAQEnqueueOptions : ICloneable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQEnqueueOptions Members](#)
- [OracleAQEnqueueOptions Constructor](#)
- [OracleAQEnqueueOptions Properties](#)
- [OracleAQEnqueueOptions Public Methods](#)

## OracleAQEnqueueOptions Members

The OracleAQEnqueueOptions members are listed in the following tables.

### OracleAQEnqueueOptions Constructor

OracleAQEnqueueOptions constructor is listed in [Table 12-9](#).

**Table 12-9 OracleAQEnqueueOptions Constructor**

Constructor	Description
<a href="#">OracleAQEnqueueOptions Constructor</a>	Instantiates a new instance of the OracleAQEnqueueOptions class.

### OracleAQEnqueueOptions Properties

OracleAQEnqueueOptions properties are listed in [Table 12-10](#).

**Table 12-10 OracleAQEnqueueOptions Properties**

Property	Description
<a href="#">DeliveryMode</a>	Specifies the delivery mode of the message being enqueued.
<a href="#">Visibility</a>	Specifies whether or not the new message is enqueued as part of the current transaction.

### OracleAQEnqueueOptions Public Methods

The OracleAQEnqueueOptions public method is listed in [Table 12-11](#).

**Table 12-11 OracleAQEnqueueOptions Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a copy of an OracleAQEnqueueOptions object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)



## OracleAQEnqueueOptions Constructor

This constructor creates an instance of the `OracleAQEnqueueOptions` class with default property values.

### Declaration

```
// C#  
public OracleAQEnqueueOptions();
```

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

## OracleAQEnqueueOptions Properties

OracleAQEnqueueOptions properties are listed in [Table 12–12](#).

**Table 12–12 OracleAQEnqueueOptions Properties**

Property	Description
<a href="#">DeliveryMode</a>	Specifies the delivery mode of the message being enqueued.
<a href="#">Visibility</a>	Specifies whether or not the new message is enqueued as part of the current transaction.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

### DeliveryMode

This instance property specifies the delivery mode of the message being enqueued.

**Declaration**

```
// C#
public OracleAQMessageDeliveryMode DeliveryMode {get;set;}
```

**Exceptions**

`ArgumentOutOfRangeException` - The specified `Visibility` value is invalid.

**Remarks**

The valid values can be any of the following enumerated values:

- `OracleAQMessageDeliveryMode.Persistent`
- `OracleAQMessageDeliveryMode.Buffered`

The default is `OracleAQMessageDeliveryMode.Persistent`.

`OracleAQMessageDeliveryMode.PersistentOrBuffered` cannot be set on this property.

`OracleAQMessageDeliveryMode.Buffered` can be specified only with Oracle Database 10g release 2 (10.2) or higher. Buffered messaging is supported in all queue tables created with a database compatibility level of 8.1 or higher.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

### Visibility

This instance property specifies whether or not the new message is enqueued as part of the current transaction.

**Declaration**

```
// C#  
public OracleAQVisibilityMode Visibility {get;set;}
```

**Property Value**

An `OracleAQVisibilityMode` enumerated value.

**Exceptions**

`ArgumentOutOfRangeException` - The specified `Visibility` value is invalid.

**Remarks**

The default value is `OracleAQVisibilityMode.OnCommit`. You must use transactions when using the default value. If transactions are not used when using the default visibility mode of `OracleAQVisibilityMode.OnCommit`, then messages are not enqueued to the queue.

Using the alternative visibility mode value, `OracleAQVisibilityMode.Immediate` eliminates the need to use a transaction. The queue is not affected in case the enqueue operation fails. The message does not get enqueued to the queue for such cases.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

## OracleAQEnqueueOptions Public Methods

OracleAQEnqueueOptions public method is listed in [Table 12–13](#).

**Table 12–13 OracleAQEnqueueOptions Public Methods**

Public Method	Description
<a href="#">Clone</a>	Creates a copy of an OracleAQEnqueueOptions object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

### Clone

This method creates a copy of an OracleAQEnqueueOptions object.

**Declaration**

```
// C#  
public object Clone();
```

**Return Value**

An OracleAQEnqueueOptions object.

**Implements**

ICloneable.

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

---

## OracleAQMessage Class

An `OracleAQMessage` object represents a message to be enqueued and dequeued.

### Class Inheritance

`System.Object`

`OracleAQMessage`

### Declaration

```
// C#  
public sealed class OracleAQMessage
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

An `OracleAQMessage` object consists of control information (metadata) and Payload (data). The control information is exposed by various properties on the `OracleAQMessage` object and is used by Oracle Streams Advanced Queuing to manage messages. The payload is the information stored in the queue.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessage Members](#)
- [OracleAQMessage Constructors](#)
- [OracleAQMessage Properties](#)

## OracleAQMessage Members

OracleAQMessage members are listed in the following tables.

### OracleAQMessage Constructor

OracleAQMessage constructors are listed in [Table 12-14](#).

**Table 12-14 OracleAQMessage Constructors**

Constructor	Description
<a href="#">OracleAQMessage Constructors</a>	Instantiates a new instance of the <code>OracleAQMessage</code> class (Overloaded).

### OracleAQMessage Properties

OracleAQMessage properties are listed in [Table 12-15](#).

**Table 12-15 OracleAQMessage Properties**

Property	Description
<a href="#">Correlation</a>	Specifies an identification for the message.
<a href="#">Delay</a>	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
<a href="#">DeliveryMode</a>	Specifies the delivery mode of the dequeued message.
<a href="#">DequeueAttempts</a>	Returns the number of attempts that have been made to dequeue the message.
<a href="#">EnqueueTime</a>	Specifies the time when the message was enqueued.
<a href="#">ExceptionQueue</a>	Specifies the name of the queue that the message should be moved to if it cannot be processed successfully.
<a href="#">Expiration</a>	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing.
<a href="#">MessageId</a>	Returns the message identifier.
<a href="#">OriginalMessageId</a>	Specifies the identifier of the message in the last queue that generated this message.
<a href="#">Payload</a>	Specifies the payload of the message.
<a href="#">Priority</a>	Specifies the priority of the message.
<a href="#">Recipients</a>	Specifies the list of recipients that overrides the default queue subscribers.
<a href="#">SenderId</a>	Identifies the original sender of the message.
<a href="#">State</a>	Specifies the state of the message at the time of dequeue.
<a href="#">TransactionGroup</a>	Specifies the transaction group for the dequeued message.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessage Class](#)

## OracleAQMessage Constructors

OracleAQMessage constructors create new instances of the OracleAQMessage class.

### Overload List:

- [OracleAQMessage\(\)](#)

This constructor instantiates the OracleAQMessage class.

- [OracleAQMessage\(Object\)](#)

This constructor instantiates the OracleAQMessage class using the object provided as the payload.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

### OracleAQMessage()

This constructor instantiates the OracleAQMessage class.

#### Declaration

```
// C#  
public OracleAQMessage();
```

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

### OracleAQMessage(Object)

This constructor instantiates the OracleAQMessage class using the Object provided as the *payload*.

#### Declaration

```
// C#  
public OracleAQMessage(Object payload);
```

#### Parameters

- *payload*

An Object specifying *payload*. It can be one of the following types:

- byte[]
- IOracleCustomType
- OracleBinary
- OracleXmlType
- String



- XmlReader

**Exceptions**

`ArgumentException` - The specified *payload* value is of invalid type.

**Remarks**

The ODP.NET AQ implementation currently does not support user defined types with LOB attributes. It also does not support other variants of user defined types such as `VARRAY` and nested tables, as Oracle Streams AQ does not support them inherently.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

## OracleAQMessage Properties

OracleAQMessage properties are listed in [Table 12–16](#).

**Table 12–16 OracleAQMessage Properties**

Property	Description
<a href="#">Correlation</a>	Specifies an identification for the message.
<a href="#">Delay</a>	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
<a href="#">DeliveryMode</a>	Specifies the delivery mode of the dequeued message.
<a href="#">DequeueAttempts</a>	Returns the number of attempts that have been made to dequeue the message.
<a href="#">EnqueueTime</a>	Specifies the time when the message was enqueued.
<a href="#">ExceptionQueue</a>	Specifies the name of the queue that the message should be moved to if it cannot be processed successfully.
<a href="#">Expiration</a>	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing.
<a href="#">MessageId</a>	Returns the message identifier.
<a href="#">OriginalMessageId</a>	Specifies the identifier of the message in the last queue that generated this message.
<a href="#">Payload</a>	Specifies the payload of the message.
<a href="#">Priority</a>	Specifies the priority of the message.
<a href="#">Recipients</a>	Specifies the list of recipients that overrides the default queue subscribers.
<a href="#">SenderId</a>	Identifies the original sender of the message.
<a href="#">State</a>	Specifies the state of the message at the time of dequeue.
<a href="#">TransactionGroup</a>	Specifies the transaction group for the dequeued message.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

### Correlation

This instance property specifies an identification for the message.

**Declaration**

```
// C#
public string Correlation {get;set;}
```

**Property Value**

A string that specifies the identification for the message.

**Remarks**

The producer of a message can set this property at the time of enqueueing. The consumer can then use this identification to dequeue specific messages by setting the `Correlation` property of an `OracleAQDequeueOptions` object. For more information regarding dequeuing messages based on `Correlation`, refer to "[Correlation](#)" under the `OracleAQDequeueOptions` class.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)
- ["Correlation"](#) on page 12-13

**Delay**

This instance property specifies the duration, in seconds, after which an enqueued message is available for dequeuing.

**Declaration**

```
// C#
public int Delay {get;set;}
```

**Property Value**

An integer that indicates the number of seconds after which an enqueued message is available for dequeuing.

**Exceptions**

`ArgumentException` - The value specified is less than 0.

**Remarks**

This property delays the immediate consumption of an enqueued message. The following are valid values for this property:

- Positive integer - Indicates the delay in seconds.
- 0 - indicates that the message is immediately available for dequeuing.

The default value is 0. The `Delay` property is not supported with buffered messaging.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**DeliveryMode**

This instance property specifies the delivery mode of the dequeued message.

**Declaration**

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;}
```

**Property Value**

An `OracleAQMessageDeliveryMode` enumerated value (`OracleAQMessageDeliveryMode.Persistent` or `OracleAQMessageDeliveryMode.Buffered`).

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**DequeueAttempts**

This instance property returns the number of attempts that have been made to dequeue the message.

**Declaration**

```
// C#  
public int DequeueAttempts {get;}
```

**Property Value**

An `integer` that indicates the number of dequeue attempts.

**Remarks**

This property is available in an `OracleAQMessage` after the message has been dequeued from a queue.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**EnqueueTime**

This instance property specifies the time when the message was enqueued.

**Declaration**

```
// C#  
public DateTime EnqueueTime {get;}
```

**Property Value**

A `DateTime` object.

**Remarks**

This property is available after the message is dequeued. It provides the enqueue time of a dequeued message.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

## ExceptionQueue

This instance property specifies the name of the queue that the message should be moved to if it cannot be processed successfully.

**Declaration**

```
// C#  
public string ExceptionQueue {get;set;}
```

**Property Value**

The name of the queue that a message should be moved to if it cannot be processed successfully. The default value is null.

**Remarks**

This property specifies the queue that a message should be moved to if the message has expired or if the number of unsuccessful dequeue attempts have exceeded the `max_retries` value for the queue.

If this property is not set or the specified exception queue name does not exist, then the default exception queue associated with the queue table is used.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

## Expiration

This instance property specifies the duration, in seconds, for which an enqueued message is available for dequeuing.

**Declaration**

```
// C#  
public int Expiration {get;set;}
```

**Property Value**

An integer that specifies the number of seconds an enqueued message is available for dequeuing.

**Exceptions**

`ArgumentException` - The value specified is less than -1.

**Remarks**

The value specified is an offset from the value specified in the `Delay` property.

The following are valid values for the property:

- Positive integer - Indicates the expiration in seconds.

- -1 - Indicates that the message never expires.

The default value is -1. When a message expires, the message moves from the `READY` state to the `EXPIRED` state.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

## MessageId

This instance property returns the message identifier.

**Declaration**

```
// C#  
public byte[] MessageId {get;}
```

**Property Value**

A `byte[]` that specifies the message identifier.

**Remarks**

This property is available after an enqueue or dequeue operation. Dequeued buffered messages have a `null` value for `MessageId`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

## OriginalMessageId

This instance property specifies the identifier of the message in the last queue that generated this message.

**Declaration**

```
// C#  
public byte[] OriginalMessageId {get;}
```

**Property Value**

A `byte[]` that specifies the original message identifier.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

## Payload

This instance property specifies the payload of the message.

**Declaration**

```
// C#
public Object Payload {get;set;}
```

**Property Value**

An `Object` that specifies the payload of the message.

**Exceptions**

`ArgumentException` - The specified object is not one of the allowed types.

**Remarks**

For a complete discussion of various payload types, refer to ["MessageType"](#) under the `OracleAQQueue` class.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)
- ["MessageType"](#) on page 12-60

**Priority**

This instance property specifies the priority of the message.

**Declaration**

```
// C#
public int Priority {get;set;}
```

**Property Value**

An `integer` that specifies the priority of the message.

**Remarks**

The default value is 0. In order to take effect, this property must be set prior to enqueueing the message.

Smaller values indicate higher priority for the message. Negative values may also be used.

The priority of an enqueued message is useful for priority-based dequeuing.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**Recipients**

This instance property specifies the list of recipients that overrides the default queue subscribers.

**Declaration**

```
// C#
```

```
public OracleAQAgent[] Recipients {get; set}
```

**Property Value**

An `OracleAQAgent []`.

**Remarks**

This recipient list is valid only for messages being enqueued to multiconsumer queues. The list of recipients is not returned with the message at the time of dequeuing.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**SenderId**

This instance property identifies the original sender of the message.

**Declaration**

```
// C#  
public OracleAQAgent SenderId {get; set}
```

**Property Value**

An `OracleAQAgent` object.

**Remarks**

Sender identification is supported in all queue tables created with a database compatibility level of 8.1 or higher.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**State**

This instance property specifies the state of the message at the time of dequeue.

**Declaration**

```
// C#  
public OracleAQMessageState State {get;}
```

**Property Value**

An `OracleAQMessageState` enumerated value.

**Remarks**

This property is available after the message is dequeued.

The state of buffered messages dequeued by specifying `Correlation` under dequeue options is always `OracleAQMessageState.Ready`.



**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

**TransactionGroup**

This instance property specifies the transaction group for the dequeued message.

**Declaration**

```
// C#  
public string TransactionGroup {get;}
```

**Property Value**

A *string* that specifies the transaction group.

**Remarks**

This property is set only after the call to `DequeueArray`. This property is supported only when using Oracle Database 10g database or higher.

Messages belonging to one queue can be grouped to form a set that can only be consumed by one user at a time. This requires that the queue be created in a queue table that is enabled for message grouping. All messages belonging to a group must be created in the same transaction. Also, all messages created in one transaction belong to the same group.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

---

## OracleAQMessageAvailableEventArgs Class

The `OracleAQMessageAvailableEventArgs` class provides event data for the `OracleAQQueue.MessageAvailable` event.

### Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleAQMessageAvailableEventArgs`

### Declaration

```
// C#  
public sealed class OracleAQMessageAvailableEventArgs
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

This class cannot be inherited.

For detailed information on all the inherited properties and methods, please read the documentation provided by Microsoft's .NET Documentation.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Members](#)
- [OracleAQMessageAvailableEventArgs Properties](#)

## OracleAQMessageAvailableEventArgs Members

OracleAQMessageAvailableEventArgs members are listed in the following tables.

### OracleAQMessageAvailableEventArgs Properties

OracleAQMessageAvailableEventArgs properties are listed in [Table 12–17](#).

**Table 12–17 OracleAQMessageAvailableEventArgs Properties**

Property	Description
<a href="#">AvailableMessages</a>	Specifies the number of messages that raised this notification.
<a href="#">ConsumerName</a>	Provides the name of the consumer for which the message is available for dequeuing.
<a href="#">Correlation</a>	Provides the name of the consumer for which the message is available for dequeuing.
<a href="#">Delay</a>	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
<a href="#">DeliveryMode</a>	Specifies the delivery mode of the message.
<a href="#">EnqueueTime</a>	Specifies the time when the message was enqueued.
<a href="#">ExceptionQueue</a>	Specifies the name of the queue that the message is moved to if it cannot be processed successfully.
<a href="#">Expiration</a>	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.
<a href="#">MessageId</a>	Returns an array of message identifiers.
<a href="#">NotificationType</a>	Indicates the type of notification such as regular, grouping, or timeout.
<a href="#">OriginalMessageId</a>	Specifies the ID of the message, in the last queue, that generated this message.
<a href="#">Priority</a>	Specifies the priority of the message.
<a href="#">QueueName</a>	Indicates the name of the queue that contains the message to be dequeued.
<a href="#">SenderId</a>	Identifies the original sender of the message.
<a href="#">State</a>	Specifies the state of the message.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)

## OracleAQMessageAvailableEventArgs Properties

OracleAQMessageAvailableEventArgs properties are listed in [Table 12–18](#).

**Table 12–18 OracleAQMessageAvailableEventArgs Properties**

Property	Description
<a href="#">AvailableMessages</a>	Specifies the number of messages that raised this notification.
<a href="#">ConsumerName</a>	Provides the name of the consumer for which the message is available for dequeuing.
<a href="#">Correlation</a>	Provides the name of the consumer for which the message is available for dequeuing.
<a href="#">Delay</a>	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
<a href="#">DeliveryMode</a>	Specifies the delivery mode of the message.
<a href="#">EnqueueTime</a>	Specifies the time when the message was enqueued.
<a href="#">ExceptionQueue</a>	Specifies the name of the queue that the message is moved to if it cannot be processed successfully.
<a href="#">Expiration</a>	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.
<a href="#">MessageId</a>	Returns an array of message identifiers.
<a href="#">NotificationType</a>	Indicates the type of notification such as regular, grouping, or timeout.
<a href="#">OriginalMessageId</a>	Specifies the ID of the message, in the last queue, that generated this message.
<a href="#">Priority</a>	Specifies the priority of the message.
<a href="#">QueueName</a>	Indicates the name of the queue that contains the message to be dequeued.
<a href="#">SenderId</a>	Identifies the original sender of the message.
<a href="#">State</a>	Specifies the state of the message.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

### AvailableMessages

This instance property specifies the number of messages that raised this notification.

**Declaration**

```
// C#
public int AvailableMessages{get;}
```

**Property Value**

An integer indicating the number of messages that raised this notification.

**Remarks**

The property value is 1 for a regular notification type. The notification type can be specified using the `OracleAQQueue.Notification` property.

This property is not relevant if the `NotificationType` is `OracleAQNotificationType.Timeout`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**ConsumerName**

This property provides the name of the consumer for which the message is available for dequeuing.

**Declaration**

```
// C#  
public string ConsumerName {get;}
```

**Property Value**

A string that identifies the name of the consumer.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**Correlation**

This instance property specifies the identification for the message.

**Declaration**

```
// C#  
public string Correlation {get;}
```

**Property Value**

A string that specifies the identification for the message.

**Remarks**

This property specifies the correlation of the message for which the notification is raised. The consumer can then use this identification to dequeue specific messages by setting the ["Correlation"](#) property of the `OracleAQDequeueOptions` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)
- ["Correlation"](#) on page 13

**Delay**

This instance property specifies the duration, in seconds, after which an enqueued message is available for dequeuing.

**Declaration**

```
// C#  
public int Delay {get;}
```

**Property Value**

An *integer* that indicates the duration, in seconds, after which an enqueued message is available for dequeuing.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**DeliveryMode**

This instance property specifies the delivery mode of the message.

**Declaration**

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;}
```

**Property Value**

An *OracleAQMessageDeliveryMode* enumerated value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**EnqueueTime**

This instance property specifies the time when the message was enqueued.

**Declaration**

```
// C#  
public DateTime EnqueueTime {get;}
```

**Property Value**

A *DateTime* object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**ExceptionQueue**

This instance property specifies the name of the queue that the message is moved to if it cannot be processed successfully.

**Declaration**

```
// C#
public string ExceptionQueue {get;}
```

**Property Value**

The name of the queue that a message to is moved if it cannot be processed successfully.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**Expiration**

This instance property specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.

**Declaration**

```
// C#
public int Expiration {get;}
```

**Property Value**

An integer that specifies the duration, in seconds, for which an enqueued message is available for dequeuing.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**MessageId**

This instance property returns an array of message identifiers.

**Declaration**

```
// ADO.NET 2.0: C#
public byte[ ][ ] MessageId{get;}
```

**Property Value**

A `byte[ ][ ]` that specifies the message identifiers received as part of the notification.

**Remarks**

This property specifies the message identifiers of the messages that raise the notification.

The size of the `MessageId` array is 1 for regular notifications. The size of the `MessageId` array is 1 for grouping notifications if the notification grouping type is `OracleAQNotificationGroupingType.Last`.

This property is not relevant if the `NotificationType` is `OracleAQNotificationType.Timeout`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**NotificationType**

This property indicates the type of notification such as regular, grouping, or timeout.

**Declaration**

```
// C#  
public OracleAQNotificationType NotificationType {get;}
```

**Property Value**

An `OracleAQNotificationType` enum value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**OriginalMessageId**

This property specifies the ID of the message, in the last queue, that generated this message.

**Declaration**

```
// C#  
public byte[] OriginalMessageId {get;}
```

**Property Value**

A `byte[ ]` that specifies the original message ID.



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**Priority**

This instance property specifies the priority of the message.

**Declaration**

```
// C#  
public int Priority {get;}
```

**Property Value**

An integer that specifies the priority of the message.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**QueueName**

This property indicates the name of the queue that contains the message to be dequeued.

**Declaration**

```
// C#  
public string QueueName {get;}
```

**Property Value**

A string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

**SenderId**

This property identifies the original sender of the message.

**Declaration**

```
// C#  
public OracleAQAgent SenderId {get;}
```

**Property Value**

An OracleAQAgent object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

## State

This instance property specifies the state of the message.

**Declaration**

```
// C#  
public OracleAQMessageState State {get;}
```

**Property Value**

An `OracleAQMessageState` enumerated value.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

---

## OracleAQMessageAvailableEventHandler Delegate

The `OracleAQMessageAvailableEventHandler` delegate represents the signature of the method that handles the `OracleAQQueue.MessageAvailable` event.

### Declaration

```
// C#  
public delegate void OracleAQMessageAvailableEventHandler (object  
    sender, OracleAQMessageAvailableEventArgs eventArgs);
```

### Parameters

- *sender*

The source of the event.

- *eventArgs*

The `OracleAQMessageAvailableEventArgs` object that contains the event data.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["MessageAvailable Event"](#) on page 12-79

## OracleAQQueue Class

An OracleAQQueue object represents a queue.

### Class Inheritance

System.Object

OracleAQQueue

### Declaration

```
// C#  
public class OracleAQQueue : IDisposable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

A queue is a repository of messages and may either be a user queue, or an exception queue. A user queue is for normal message processing. A message is moved from a user queue to an exception queue if it cannot be retrieved and processed for some reason.

### Requirements

Namespace: Oracle.DataAccess.Client

Assembly: Oracle.DataAccess.dll

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Members](#)
- [OracleAQQueue Constructors](#)
- [OracleAQQueue Static Methods](#)
- [OracleAQQueue Properties](#)
- [OracleAQQueue Public Methods](#)
- [OracleAQQueue Events](#)

## OracleAQQueue Members

OracleAQQueue members are listed in the following tables.

### OracleAQQueue Constructors

OracleAQQueue constructors are listed in [Table 12-19](#).

**Table 12-19 OracleAQQueue Constructors**

Constructor	Description
<a href="#">OracleAQQueue Constructors</a>	Instantiate a new instance of the OracleAQQueue class (Overloaded).

### OracleAQQueue Static Methods

The OracleAQQueue static method is listed in [Table 12-20](#).

**Table 12-20 OracleAQQueue Static Methods**

Static Method	Description
<a href="#">Listen</a>	Listens for messages on one or more queues for one or more consumers, as specified in the array of OracleAQAgent objects (Overloaded).

### OracleAQQueue Properties

OracleAQQueue properties are listed in [Table 12-21](#).

**Table 12-21 OracleAQQueue Properties**

Property	Description
<a href="#">Connection</a>	Specifies the OracleConnection object associated with the queue.
<a href="#">DequeueOptions</a>	Specifies the dequeueing options to use when dequeuing a message from a queue.
<a href="#">EnqueueOptions</a>	Specifies the enqueueing options used to enqueue a message to a queue.
<a href="#">MessageType</a>	Specifies the type of queue table associated with this queue.
<a href="#">Name</a>	Returns the name of the queue.
<a href="#">Notification</a>	Specifies the various notification options for notifications that are registered using the MessageAvailable event.
<a href="#">NotificationConsumers</a>	Specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.
<a href="#">UdtTypeName</a>	Specifies the type name on which the queue and the corresponding queue table is based if the MessageType is OracleAQMessageType.UDT.

## OracleAQQueue Public Methods

The OracleAQQueue public methods are listed in [Table 12–22](#).

**Table 12–22 OracleAQQueue Public Methods**

Public Method	Description
<a href="#">Dequeue</a>	Dequeues messages from queues (Overloaded).
<a href="#">DequeueArray</a>	Dequeues multiple messages from queues (Overloaded).
<a href="#">Dispose</a>	Releases any resources or memory allocated by the object
<a href="#">Enqueue</a>	Enqueues messages to queues (Overloaded).
<a href="#">EnqueueArray</a>	Enqueues multiple messages to a queue (Overloaded).
<a href="#">Listen</a>	Listens for messages on the queue on behalf of <code>listenConsumers</code> (Overloaded).

## OracleAQQueue Events

The OracleAQQueue event is listed in [Table 12–23](#).

**Table 12–23 OracleAQQueue Events**

Event Name	Description
<a href="#">MessageAvailable Event</a>	Notifies when a message is available in the queue for <code>NotificationConsumers</code> .

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)

## OracleAQQueue Constructors

OracleAQQueue constructors create new instances of the OracleAQQueue class.

### Overload List:

- [OracleAQQueue\(string\)](#)

This constructor takes a queue name to initialize a queue object.

- [OracleAQQueue\(string, OracleConnection\)](#)

This constructor takes a queue name and connection to initialize a queue object. The connection does not need be open during the queue object construction.

- [OracleAQQueue\(string, OracleConnection, OracleAQMessageType\)](#)

This constructor takes a queue name, connection, and message type enumeration to initialize a queue object.

- [OracleAQQueue\(string, OracleConnection, OracleAQMessageType, string\)](#)

This constructor takes a queue name, connection, message type enumeration, and UDT type name to initialize a queue object.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### OracleAQQueue(string)

This constructor takes a queue name to initialize a queue object.

#### Declaration

```
// C#
public OracleAQQueue(string name);
```

#### Parameters

- *name*

The name of the queue as specified in the database.

#### Exceptions

ArgumentNullException - The queue name is null.

ArgumentException - The queue name is empty.

#### Remarks

The operation of creating an OracleAQQueue object does not involve checking for the existence of the queue in the database.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQQueue(string, OracleConnection)

This constructor takes a queue name and connection to initialize a queue object. The connection does not need to be open during the queue object construction.

### Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con);
```

### Parameters

- *name*  
Name of the queue as specified in the database.
- *con*  
An `OracleConnection` object that connects to the queue.

### Exceptions

`ArgumentNullException` - Either the connection is null or queue name is null.

`ArgumentException` - Queue name is empty.

### Remarks

The connection can be accessed using the `Connection` property, and it must be opened before calling any operational APIs such as `Enqueue` and `Dequeue`.

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQQueue(string, OracleConnection, OracleAQMessageType)

This constructor takes a queue name, connection and message type enumeration to initialize a queue object. The connection does not need to be open during the queue object construction.

### Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con, OracleAQMessageType  
    messageType);
```

### Parameters

- *name*  
The name of the queue as specified in the database.
- *con*  
An `OracleConnection` object that is used to connect to the queue.
- *messageType*



An *OracleAQMessageType* enumeration specifying the type of the message that is enqueued or dequeued from this queue.

### Exceptions

*ArgumentNullException* - Either the connection is null or queue name is null.

*ArgumentException* - Queue name is empty or the specified message type is not valid.

### Remarks

Creating an *OracleAQQueue* object does not check for the existence of the queue in the database.

You need to set the *UdtTypeName* property before using the queue object if the *messageType* is a UDT. Another approach is to create a queue using the other constructor overload by supplying the *udtTypeName*.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### **OracleAQQueue(string, OracleConnection, OracleAQMessageType, string)**

This constructor takes a queue name, connection, message type enumeration, and UDT type name to initialize a queue object. The connection does not need to be open during the queue object construction.

### Declaration

```
// C#
public OracleAQQueue(string name, OracleConnection con, OracleAQMessageType
    messageType, string udtTypeName);
```

### Parameters

- *name*  
The name of the queue as specified in the database.
- *con*  
An *OracleConnection* object that is used to connect to the queue.
- *messageType*  
An *OracleAQMessageType* enumeration specifying the type of the message that is enqueued or dequeued from this queue.
- *udtTypeName*  
The name of the database object type used if the *messageType* is UDT. The *udtTypeName* parameter represents the type on which the queue is based.

### Exceptions

*ArgumentNullException* - The connection is null or the queue name is null.

*ArgumentException* - The queue name is empty or the specified *messageType* is not valid.

**Remarks**

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQQueue Static Methods

OracleAQQueue static methods are listed in [Table 12–24](#).

**Table 12–24 OracleAQQueue Static Methods**

Static Method	Description
<a href="#">Listen</a>	Listens for messages on one or more queues for one or more consumers, as specified in the array of OracleAQAgent objects (Overloaded).

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### Listen

Listen methods listen for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.

**Overload list**

- [Listen\(OracleConnection, OracleAQAgent\[ \]\)](#)  
This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.
- [Listen\(OracleConnection, OracleAQAgent\[ \], int\)](#)  
This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects. It also specifies a wait time.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### Listen(OracleConnection, OracleAQAgent[ ])

This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.

**Declaration**

```
// C#
public static OracleAQAgent Listen(OracleConnection con, OracleAQAgent[]
    listenConsumers);
```

**Parameters**

- *con*  
An OracleConnection instance.
- *listenConsumers*

The array of consumers being listened for. The name of the `OracleAQAgent` object must be `null` or empty for single consumer queues.

**Return Value**

An `OracleAQAgent` object.

**Exceptions**

`ArgumentNullException` - The `con` or `listenConsumers` parameter is null.

`InvalidOperationException` - The connection is not open.

**Remarks**

`Listen` is useful in situations where one needs to monitor multiple queues until a message is available for a consumer in one of the queues. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property represents the name of the queue.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the list. It returns an `OracleAQAgent` object which specifies the consumer and queue for which a message is ready to be dequeued.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**Listen(OracleConnection, OracleAQAgent[ ], int)**

This static method listens for messages on one or more queues for one or more consumers as specified in the array of `OracleAQAgent` objects. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property of the `OracleAQAgent` object represents the name of the queue.

In case of timeout, this method returns `null`.

**Declaration**

```
// C#  
public static OracleAQAgent Listen(OracleConnection con, OracleAQAgent[]  
    listenConsumers, int waitTime);
```

**Parameters**

- `con`  
An `OracleConnection` instance.
- `listenConsumers`  
The array of consumers being listened for. The name of the `OracleAQAgent` object must be `null` or empty for single consumer queues.
- `waitTime`  
Wait time in seconds.

**Return Value**

An `OracleAQAgent` object.

**Exceptions**

`ArgumentNullException` - The `con` or `listenConsumers` parameter is null.

`InvalidOperationException` - The connection is not open.

`ArgumentException` - `waitTime` is less than -1.

**Remarks**

`Listen` is useful in situations where one needs to monitor multiple queues until a message is available for a consumer in one of the queues. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property of the `OracleAQAgent` object represents the name of the queue.

A `waitTime` of -1 implies an infinite wait time.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the list. It returns an `OracleAQAgent` object which specifies the consumer and queue for which a message is ready to be dequeued.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQQueue Properties

OracleAQQueue properties are listed in [Table 12–25](#).

**Table 12–25 OracleAQQueue Properties**

Property	Description
<a href="#">Connection</a>	Specifies the <code>OracleConnection</code> object associated with the queue.
<a href="#">DequeueOptions</a>	Specifies the dequeuing options to use when dequeuing a message from a queue.
<a href="#">EnqueueOptions</a>	Specifies the enqueueing options used to enqueue a message to a queue.
<a href="#">MessageType</a>	Specifies the type of queue table associated with this queue.
<a href="#">Name</a>	Returns the name of the queue.
<a href="#">Notification</a>	Specifies the various notification options for notifications that are registered using the <code>MessageAvailable</code> event.
<a href="#">NotificationConsumers</a>	Specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.
<a href="#">UdtTypeName</a>	Specifies the type name on which the queue and the corresponding queue table is based if the <code>MessageType</code> is <code>OracleAQMessageType.UDT</code> .

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### Connection

This property specifies the `OracleConnection` object associated with the queue.

**Declaration**

```
// C#
public OracleConnection Connection {get; set;}
```

**Property Value**

An `OracleConnection` object that indicates the connection associated with the queue.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

This connection must be opened before calling methods like `Enqueue` and `Dequeue`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## DequeueOptions

This instance property specifies the dequeueing options to use when dequeuing a message from a queue.

**Declaration**

```
// C#  
public OracleAQDequeueOptions DequeueOptions {get; set}
```

**Property Value**

An `OracleAQDequeueOptions` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is an `OracleAQDequeueOptions` object with default property values. Setting this property to `null` resets all dequeue options to their default values.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## EnqueueOptions

This instance property specifies the enqueueing options used to enqueue a message to a queue.

**Declaration**

```
// C#  
public OracleAQEnqueueOptions EnqueueOptions {get; set}
```

**Property Value**

An `OracleAQEnqueueOptions` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The default value is an `OracleAQEnqueueOptions` object with default property values. Setting this property to `null` resets all enqueue options to their default values.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**MessageType**

This instance property specifies the type of queue table associated with this queue.

**Declaration**

```
// C#
public OracleAQMessageType MessageType {get; set;}
```

**Property Value**

An `OracleAQMessageType` enumerated value.

**Exceptions**

`ArgumentOutOfRangeException` - The type value specified is invalid.

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The `MessageType` property also dictates the type of message payloads that are enqueued or dequeued from the queue. It is possible to enqueue a variety of payloads depending on the `MessageType`.

[Table 12–26](#) lists the allowed payload types for various message types.

**Table 12–26 Message Types and Payloads**

<b>OracleAQQueue.MessageType</b>	<b>Allowed OracleAQMessage.Payload type to Enqueue</b>
<code>OracleAQMessageType.Raw</code>	<code>OracleBinary, byte[]</code>
<code>OracleAQMessageType.Xml</code>	<code>OracleXmlType, XmlReader, String</code>
<code>OracleAQMessageType.UDT</code>	UDT Custom Object

[Table 12–27](#) lists the payload types for dequeued messages.

**Table 12–27 Payload Types for Dequeued Messages**

<b>OracleAQQueue.MessageType</b>	<b>DequeueOptions.ProviderSpecificType</b>	<b>OracleAQMessage.Payload of dequeued message</b>
<code>OracleAQMessageType.Xml</code>	true	<code>OracleXmlType</code>
<code>OracleAQMessageType.Xml</code>	false	<code>XmlReader</code>
<code>OracleAQMessageType.Raw</code>	true	<code>OracleBinary</code>
<code>OracleAQMessageType.Raw</code>	false	<code>Byte[]</code>
<code>OracleAQMessageType.UDT</code>	N.A.	UDT Custom Object



**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**Name**

This instance property returns the name of the queue.

**Declaration**

```
// C#  
public string Name {get;}
```

**Property Value**

A string that indicates the name of the queue.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**Notification**

This instance property specifies the various notification options for notifications that are registered using the `MessageAvailable` event.

**Declaration**

```
// C#  
public OracleNotificationRequest Notification {get;}
```

**Property Value**

Specifies an `OracleNotificationRequest` object whose properties can be changed to alter the notification behavior.

**Remarks**

This property can be used to change various notification options. The notification options must be changed before registering with the `MessageAvailable` event. This property can be modified again only after unregistering from the `MessageAvailable` event.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## NotificationConsumers

This instance property specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.

### Declaration

```
// C#  
public string[] NotificationConsumers {get; set;}
```

### Property Value

Specifies an array of consumer name strings for which the notifications are delivered.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - `MessageAvailable` registration is active.

### Remarks

The consumer names must be in uppercase. This functionality only supports queues with uppercase names.

The list of consumers is used in the `MessageAvailable` event. The list must be set before registering for the event. This property cannot be modified after registering for the `MessageAvailable` event. This property can be modified again only after unregistering from `MessageAvailable` event.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## UdtTypeName

This instance property specifies the type name on which the queue and the corresponding queue table is based if the `MessageType` is `OracleAQMessageType.UDT`.

### Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

### Property Value

Specifies the Oracle user-defined type name if the `MessageType` is `OracleAQMessageType.UDT`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

### Remarks

The `UdtTypeName` property corresponds to the user-defined type name of the payload. This property must always be specified if the payload is a user-defined type. This property need not be set for other payload types.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQQueue Public Methods

OracleAQQueue public methods are listed in [Table 12–28](#).

**Table 12–28 OracleAQQueue Public Methods**

Public Method	Description
<a href="#">Dequeue</a>	Dequeues messages from queues (Overloaded).
<a href="#">DequeueArray</a>	Dequeues multiple messages from queues (Overloaded).
<a href="#">Dispose</a>	Releases any resources or memory allocated by the object
<a href="#">Enqueue</a>	Enqueues messages to queues (Overloaded).
<a href="#">EnqueueArray</a>	Enqueues multiple messages to a queue (Overloaded).
<a href="#">Listen</a>	Listens for messages on the queue on behalf of <code>listenConsumers</code> (Overloaded).

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### Dequeue

Dequeue methods dequeue messages from queues.

**Overload List**

- [Dequeue\(\)](#)  
This instance method dequeues messages from a queue using the `DequeueOptions` for the instance.
- [Dequeue\(OracleAQDequeueOptions\)](#)  
This instance method dequeues messages from a queue using the supplied dequeue options.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

### Dequeue()

This instance method is used to dequeue a message from a queue using the `DequeueOptions` for the instance.

**Declaration**

```
// C#
```

```
public OracleAQMessage Dequeue();
```

### Return Value

An `OracleAQMessage` instance representing the dequeued message.

### Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than `-1`.

### Remarks

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

Dequeued buffered messages always have null `MessageId` values.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## Dequeue(OracleAQDequeueOptions)

This instance method dequeues messages from a queue using the supplied dequeue options.

### Declaration

```
// C#
public OracleAQMessage Dequeue(OracleAQDequeueOptions dequeueOptions);
```

### Parameters

- *dequeueOptions*

An `OracleAQDequeueOptions` object.

### Return Value

An `OracleAQMessage` instance representing the dequeued message.

### Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than `-1`.

**Remarks**

If the supplied `dequeueOptions` object is `null`, then the dequeue options default values are used. The queue object's `DequeueOptions` property is ignored for this operation.

Calling this method does not change the `DequeueOptions` property of the queue.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

Dequeued buffered messages always have `null` `MessageId` values.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**DequeueArray**

`DequeueArray` methods dequeue multiple messages from queues.

**Overload List**

- [DequeueArray\(int\)](#)

This instance method dequeues multiple messages from a queue using the `DequeueOptions` of the instance.

- [DequeueArray\(int, OracleAQDequeueOptions\)](#)

This instance method dequeues multiple messages from a queue using the supplied dequeue options.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**DequeueArray(int)**

This instance method dequeues multiple messages from a queue using the `DequeueOptions` of the instance.

**Declaration**

```
// C#  
public OracleAQMessage[] DequeueArray(int dequeueCount);
```

**Parameters**

- *dequeueCount*

An integer specifying the numbers of messages to dequeue.

**Return Value**

An array of `OracleAQMessage` instances representing the dequeued messages.

**Exceptions**

`ArgumentOutOfRangeException` - `dequeueCount` is less than or equal to 0.

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

**Remarks**

This method is supported for Oracle Database 10g and higher releases.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

The size of the returned array may be less than the `dequeueCount`. It depends on the actual number of messages present in the queue.

For database versions earlier than Oracle Database 11g Release 2 (11.2), the `MessageId` property of persistent `OracleAQMessage` objects retrieved using `DequeueArray` is always null.

Dequeued buffered messages always have null `MessageId` values irrespective of the database version.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**DequeueArray(int, OracleAQDequeueOptions)**

This instance method dequeues multiple messages from a queue using the supplied dequeue options.

**Declaration**

```
// C#
public OracleAQMessage[] DequeueArray(int dequeueCount, OracleAQDequeueOptions
dequeueOptions);
```

**Parameters**

- *dequeueCount*  
An integer specifying the numbers of messages to dequeue.
- *dequeueOptions*  
An `OracleAQDequeueOptions` object.

**Return Value**

An array of `OracleAQMessage` instances representing the dequeued messages.

**Exceptions**

`ArgumentOutOfRangeException` - `dequeueCount` is less than or equal to 0.

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than `-1`.

### Remarks

This method is supported for Oracle Database 10g Release 1 (10.1) and higher releases. Calling this method does not change the `DequeueOptions` property of the queue.

If the supplied `dequeueOptions` object is `null`, then the dequeue options default values are used. The `DequeueOptions` property of the queue object is ignored in this operation.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

The size of the returned array may be less than the `dequeueCount`. It depends on the actual number of messages present in the queue.

For database versions earlier than Oracle Database 11g Release 2 (11.2), the `MessageId` property of persistent `OracleAQMessage` objects retrieved using `DequeueArray` is always `null`.

Dequeued buffered messages always have `null` `MessageId` values irrespective of the database version.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## Dispose

This method releases any resources or memory allocated by the object.

### Declaration

```
// C#  
public void Dispose();
```

### Implements

`IDisposable`.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## Enqueue

Enqueue instance methods enqueue messages to queues.



**Overload List**

- [Enqueue\(OracleAQMessage\)](#)

This instance method enqueues messages to a queue using the `EnqueueOptions` of the instance.

- [Enqueue\(OracleAQMessage, OracleAQEnqueueOptions\)](#)

This instance method enqueues messages to a queue using the supplied enqueue options.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**Enqueue(OracleAQMessage)**

This instance method enqueues messages to a queue using the `EnqueueOptions` of the instance.

**Declaration**

```
// C#
public void Enqueue(OracleAQMessage message);
```

**Parameters**

- *message*  
An `OracleAQMessage` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The connection is not open.

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - The message payload is `OracleXmlType` and the connection used to create `OracleXmlType` is different from the queue's connection.

**Remarks**

`MessageId` of the enqueued message is populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values.

The `MessageType` property needs to be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## Enqueue(OracleAQMessage, OracleAQEnqueueOptions)

This instance method enqueues messages to a queue using the supplied enqueue options.

### Declaration

```
// C#  
public void Enqueue(OracleAQMessage message, OracleAQEnqueueOptions  
enqueueOptions);
```

### Parameters

- *message*  
An OracleAQMessage object.
- *enqueueOptions*  
An OracleAQEnqueueOptions object.

### Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The connection is not open.

ArgumentNullException - The message parameter is null.

ArgumentException - The message payload is OracleXmlType and the connection used to create OracleXmlType is different from the queue's connection.

### Remarks

If the supplied enqueueOptions object is null, then the enqueue options default values are used. The EnqueueOptions property of the queue object is ignored in this operation.

The MessageId of the enqueued message is populated after the call to Enqueue completes. Enqueued buffered messages always have null MessageId values. Calling this method does not change the EnqueueOptions property of the queue.

The MessageType property must be set appropriately before calling this function. If the MessageType is OracleAQMessageType.UDT, then the UdtTypeName property must also be set.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## EnqueueArray

EnqueueArray instance methods enqueue multiple messages to a queue.

### Overload List

- [EnqueueArray\(OracleAQMessage\[ \]\)](#)  
This instance method enqueues multiple messages to a queue using the EnqueueOptions of the instance.
- [EnqueueArray\(OracleAQMessage\[ \], OracleAQEnqueueOptions\)](#)

This instance method enqueues multiple messages to a queue using the supplied enqueue options.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## EnqueueArray(OracleAQMessage[ ])

This instance method enqueues multiple messages to a queue using the `EnqueueOptions` of the instance.

**Declaration**

```
// C#
public int EnqueueArray(OracleAQMessage[] messages);
```

**Parameters**

- *messages*

An array of `OracleAQMessage` objects.

**Return Value**

An integer representing the number of messages actually enqueued.

**Exceptions**

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - At least one of the `OracleAQMessage[]` elements is null, or at least one of the `OracleAQMessage[]` elements has a payload of `OracleXmlType`, which is created using a connection that is different from the queue's connection.

`InvalidOperationException` - The `OracleAQMessage` array is empty or the connection is not open.

`ObjectDisposedException` - The object is already disposed.

**Remarks**

This method is supported by Oracle Database 10g and higher releases. The `MessageId` properties of the enqueued messages are populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## EnqueueArray(OracleAQMessage[ ], OracleAQEnqueueOptions)

This instance method enqueues multiple messages to a queue using the supplied enqueue options.

### Declaration

```
// C#  
public int EnqueueArray(OracleAQMessage[] messages, OracleAQEnqueueOptions  
    enqueueOptions);
```

### Parameters

- *messages*  
An array of OracleAQMessage objects.
- *enqueueOptions*  
An OracleAQEnqueueOptions object.

### Return Value

An integer representing the number of messages actually enqueued.

### Exceptions

ArgumentNullException - The message parameter is null.

ArgumentException - At least one of the OracleAQMessage[] elements is null, or at least one of the OracleAQMessage[] elements has a payload of OracleXmlType, which is created using a connection that is different from the queue's connection.

InvalidOperationException - The OracleAQMessage array is empty or the connection is not open.

ObjectDisposedException - The object is already disposed.

### Remarks

This method is supported by Oracle Database 10g and higher releases. MessageId properties of the enqueued messages are populated after the call to Enqueue completes. Enqueued buffered messages always have null MessageId values. Calling this method does not change the EnqueueOptions property of the queue.

If the supplied enqueueOptions object is null, then the enqueue options default values are used. The EnqueueOptions property of the queue object is ignored in this operation.

The MessageType property must be set appropriately before calling this function. If the MessageType is OracleAQMessageType.UDT, then the UdtTypeName property must also be set.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## Listen

Listen methods listen for messages on the queue on behalf of listenConsumers.

**Overload List**

- [Listen\(string\[\]\)](#)

This method listens for messages on the queue on behalf of `listenConsumers`.

- [Listen \(string\[\], int\)](#)

This method listens for messages on behalf of `listenConsumers` for a specified time.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**Listen(string[])**

This method listens for messages on the queue on behalf of `listenConsumers`.

**Declaration**

```
// C#
public string Listen(string[] listenConsumers);
```

**Parameters**

- *listenConsumers*

An array of consumers to listen for on this queue. This parameter should be null in case of single consumer queues.

**Return Value**

A `string`.

**Exceptions**

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

**Remarks**

This call blocks the calling thread until there is a message ready for consumption for a consumer in the `listenConsumers` array. It returns a `string` representing the consumer name for which the message is ready.

`Listen` is useful in situations that require waiting until a message is available in the queue for consumers whose names are specified in `listenConsumers`.

**Example**

The following example demonstrates using the `Listen` method. The first part of the example performs the requisite database setup for the database user, `SCOTT`. The second part of the example demonstrates how a thread can listen and wait until a message is enqueued.

```
-- Part I: Database setup required for this demo
```

```
-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
```

```
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PLSQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PLSQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);

  DBMS_AQADM.DROP_QUEUE_TABLE(
    queue_table => 'scott.test_q_tab',
    force => FALSE,
    auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Demonstrates using the Listen method
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;
using System.Threading;

namespace ODPSample
{
  /// <summary>
  /// Demonstrates how a thread can listen and wait until a message is enqueued.
  /// Once a message is enqueued, the listening thread returns from the
  /// blocked Listen() method invocation and dequeues the message.
  /// </summary>
  class EnqueueDequeue
  {
    static bool s_bListenReturned = false;

    static void Main(string[] args)
    {
```

```
// Create connection
string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
OracleConnection con = new OracleConnection(constr);

// Create queue
OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

try
{
    // Open connection
    con.Open();

    // Set message type for the queue
    queue.MessageType = OracleAQMessageType.Raw;

    // Spawning a thread which will listen for a message
    ThreadStart ts = new ThreadStart(TestListen);
    Thread t = new Thread(ts);
    t.Start();

    System.Threading.Thread.Sleep(2000);

    // Begin transaction for enqueue
    OracleTransaction txn = con.BeginTransaction();

    // Prepare message and RAW payload
    OracleAQMessage enqMsg = new OracleAQMessage();
    byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
    enqMsg.Payload = bytePayload;

    // Prepare to Enqueue
    queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

    Console.WriteLine("[Main Thread]   Enqueuing a message...");
    Console.WriteLine("[Main Thread]   Enqueued Message Payload       : "
        + ByteArrayToString(enqMsg.Payload as byte[]));
    Console.WriteLine();

    // Enqueue message
    queue.Enqueue(enqMsg);

    // Enqueue transaction commit
    txn.Commit();

    // Loop till Listen returns
    while (!s_bListenReturned)
        System.Threading.Thread.Sleep(1000);
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}
}
```

```
static void TestListen()
{
    // Create connection
    string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
    OracleConnection conListen = new OracleConnection(constr);

    // Create queue
    OracleAQQueue queueListen = new OracleAQQueue("scott.test_q", conListen);

    try
    {
        // Open the connection for Listen thread.
        // Connection blocked on Listen thread can not be used for other DB
        // operations
        conListen.Open();

        // Set message type for the queue
        queueListen.MessageType = OracleAQMessageType.Raw;

        // Listen
        queueListen.Listen(null);

        Console.WriteLine("[Listen Thread] Listen returned... Dequeuing...");

        // Begin txn for Dequeue
        OracleTransaction txn = conListen.BeginTransaction();

        // Prepare to Dequeue
        queueListen.DequeueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
        queueListen.DequeueOptions.Wait = 10;

        // Dequeue message
        OracleAQMessage deqMsg = queueListen.Dequeue();
        Console.WriteLine("[Listen Thread] Dequeued Message Payload      : "
            + ByteArrayToString(deqMsg.Payload as byte[]));

        // Dequeue txn commit
        txn.Commit();

        // Allow the main thread to exit
        s_bListenReturned = true;
    }
    catch (Exception e)
    {
        Console.WriteLine("Error: {0}", e.Message);
    }
    finally
    {
        // Close/Dispose objects
        queueListen.Dispose();
        conListen.Close();
        conListen.Dispose();
    }
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
```



```

        for (int n = 0; n < byteArray.Length; n++)
        {
            sb.Append((int.Parse(byteArray[n].ToString()).ToString("X"));
        }
        return sb.ToString();
    }
}
}

```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

**Listen (string[], int)**

This method listens for messages on behalf of `listenConsumers` for a specified time.

**Declaration**

```

// C#
public string Listen(string[] listenConsumers, int waitTime);

```

**Parameters**

- *listenConsumers*  
Array of consumers for which to listen on this queue.
- *waitTime*  
Wait time in seconds.

**Return Value**

A string

**Exceptions**

`InvalidOperationException` - The connection is not open.  
`ArgumentException` - `waitTime` is less than -1.  
`ObjectDisposedException` - The object is already disposed.

**Remarks**

`Listen` is useful in situations that require waiting until a message is available in the queue for consumers whose names are specified in `listenConsumers`.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the `listenConsumers` array. It returns a string representing the consumer name for which the message is ready. The method returns null if a timeout occurs.

The `listenConsumers` parameter should be null for single consumer queues. An empty string is returned in such cases.

A `waitTime` of -1 implies infinite wait time.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQQueue Events

The OracleAQQueue event is listed in [Table 12-29](#).

**Table 12-29 OracleAQQueue Events**

Event Name	Description
<a href="#">MessageAvailable Event</a>	Notifies when a message is available in the queue for NotificationConsumers.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## MessageAvailable Event

This event is notified when a message is available in the queue for NotificationConsumers.

### Declaration

```
// C#
public event OracleAQMessageAvailableEventHandler MessageAvailable;
```

### Event Data

The event handler receives an OracleAQMessageAvailableEventArgs object.

### Exceptions

InvalidOperationException - The connection is not open.

### Remarks

Asynchronous notification is supported in all queue tables created with a database compatibility level of 8.1 or higher.

In order to receive the notification about message availability, the client must create an OracleAQMessageAvailableEventHandler delegate to listen to this event. The delegate should be added to this event only after setting the [NotificationConsumers](#) and [Notification](#) properties.

The notification registration takes place after the first delegate is added to the event. The notification is unregistered when the last delegate is removed from the event. Notifications set on an OracleAQQueue object get cancelled automatically when the object gets disposed.

Oracle Data Provider for .NET opens a port to listen for notifications. HA events, load balancing, and database change notification features also share the same port. This port can be configured centrally by setting the database notification port in an application or Web configuration file. The following example code specifies a port number of 1200:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
```

```
        <add name="DbNotificationPort" value="1200"/>
    </settings>
</oracle.dataaccess.client>
</configuration>
```

If the configuration file does not exist or the db notification port is not specified, then ODP.NET uses a valid and random port number. The configuration file may also request for a random port number by specifying a db notification port value of -1.

The notification listener, which runs in the same application domain as ODP.NET, uses the specified port number to listen to notifications from the database. A notification listener gets created when the application registers with `OracleAQQueue.MessageAvailable` event. One notification listener can listen to all notification types. Only one notification listener is created for each application domain.

### Example

The following example demonstrates application notification. The first part of the example performs the requisite database setup for the database user, SCOTT. The second part of the example demonstrates how an application is notified when a message is available in the queue.

```
-- Part I: Database setup required for this demo

-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
SQL> GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PLSQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PLSQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);

  DBMS_AQADM.DROP_QUEUE_TABLE(
```

```

        queue_table => 'scott.test_q_tab',
        force => FALSE,
        auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Demonstrates application notification
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

namespace ODPSample
{
    /// <summary>
    /// Demonstrates how the application can be notified when a message is
    /// available in a queue.
    /// </summary>
    class Notification
    {
        static bool isNotified = false;

        static void Main(string[] args)
        {
            // Create connection
            string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
            OracleConnection con = new OracleConnection(constr);

            // Create queue
            OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

            try
            {
                // Open connection
                con.Open();

                // Set message type for the queue
                queue.MessageType = OracleAQMessageType.Raw;

                // Add the event handler to handle the notification. The
                // MsgReceived method will be invoked when a message is enqueued
                queue.MessageAvailable +=
                    new OracleAQMessageAvailableEventHandler(Notification.MsgReceived);

                Console.WriteLine("Notification registered...");

                // Begin txn for enqueue
                OracleTransaction txn = con.BeginTransaction();

                Console.WriteLine("Now enqueueing message...");

                // Prepare message and RAW payload
                OracleAQMessage enqMsg = new OracleAQMessage();
                byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
                enqMsg.Payload = bytePayload;

                // Prepare to Enqueue
                queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
            }
            catch { }
        }
    }
}

```

```
// Enqueue message
queue.Enqueue(enqMsg);

Console.WriteLine("Enqueued Message Payload      : "
    + ByteArrayToString(enqMsg.Payload as byte[]));
Console.WriteLine("MessageId of Enqueued Message : "
    + ByteArrayToString(enqMsg.MessageId));
Console.WriteLine();

// Enqueue txn commit
txn.Commit();

// Loop while waiting for notification
while (isNotified == false)
{
    System.Threading.Thread.Sleep(2000);
}
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}
}

static void MsgReceived(object src, OracleAQMessageAvailableEventArgs arg)
{
    try
    {
        Console.WriteLine("Notification Received...");
        Console.WriteLine("QueueName : {0}", arg.QueueName);
        Console.WriteLine("Notification Type : {0}", arg.NotificationType);

        //following type-cast to "byte[]" is required only for .NET 1.x
        byte[] notifiedMsgId = (byte[]) arg.MessageId[0];
        Console.WriteLine("MessageId of Notified Message : "
            + ByteArrayToString(notifiedMsgId));
        isNotified = true;
    }
    catch (Exception e)
    {
        Console.WriteLine("Error: {0}", e.Message);
    }
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString()).ToString("X"));
    }
}
```

```
        return sb.ToString();  
    }  
}
```

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

## OracleAQDequeueMode Enumeration

Table 12–30 lists all the `OracleAQDequeueMode` enumeration values with a description of each enumerated value.

**Table 12–30** *OracleAQDequeueMode Members*

Member Name	Description
Browse	Reads the message without acquiring any lock on the message. This is equivalent to a <code>SELECT</code> statement.
Locked	Reads and obtains a write lock on the message. The lock lasts for the duration of the transaction. This is equivalent to a <code>SELECT FOR UPDATE</code> statement.
Remove	Reads the message and updates or deletes it. This is the default. The message can be retained in the queue table based on the retention properties
RemoveNoData	Confirms receipt of the message but does not deliver the actual message content.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleAQDequeueOptions Class"](#) on page 12-8
- ["DequeueMode"](#) on page 12-14



## OracleAQMessageDeliveryMode Enumeration

The `OracleAQMessageDeliveryMode` enumeration type specifies the delivery mode of the message.

[Table 12–31](#) lists all the `OracleAQMessageDeliveryMode` enumeration values with a description of each enumerated value.

**Table 12–31 OracleAQMessageDeliveryMode Members**

Member Name	Description
<code>Buffered</code>	<p>Indicates a buffered message.</p> <p>Both enqueue and dequeue buffered messaging operations must be in <code>IMMEDIATE</code> visibility mode. This means that these operations cannot be part of another transaction. You cannot specify <code>delay</code> when enqueueing buffered messages.</p> <p>Dequeueing applications can choose to dequeue persistent messages only, buffered messages only, or both types.</p> <p>Buffered messages can be queried using the <code>AQ\$Queue_Table_Name</code> view. These messages appear with states, <code>IN-MEMORY</code> or <code>SPILLED</code>.</p> <p>Buffered messaging is supported in Oracle Database 10g release 2 (10.2) and higher releases. Recipient lists are supported for buffered messaging.</p> <p>Buffered messaging is supported in all queue tables created with a database compatibility level of 8.1 or higher. Transaction grouping queues and array enqueues are not supported for buffered messages in Oracle Database 11g release 1 (11.1). One can still use the array enqueue procedure to enqueue buffered messages, but the array size must be set to 1. Array dequeue is not supported for buffered messaging, but one can still use the array dequeue procedure by setting array size to 1.</p> <p>Buffered messaging is faster than persistent messaging. Use buffered messaging for applications that do not require the reliability and transaction support of Oracle Streams AQ persistent messaging.</p>
<code>Persistent</code>	<p>Indicates a persistent message.</p> <p>Persistent messaging ensures reliability and support transactions. It is slower than buffered messaging.</p>
<code>PersistentOrBuffered</code>	<p>Indicates a persistent or buffered message.</p> <p>This is used with <code>Dequeue()</code> when a consumer wants to dequeue a message irrespective of whether it is <code>Persistent</code> or <code>Buffered</code>.</p>

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleAQDequeueOptions Class"](#) on page 12-8
- ["DeliveryMode"](#) on page 12-13

---

## OracleAQMessageState Enumeration

The `OracleAQMessageState` enumeration type identifies the state of the message at the time of dequeue.

[Table 12-32](#) lists all the `OracleAQMessageState` enumeration values with a description of each enumerated value.

**Table 12-32** *OracleAQMessageState Members*

Member Name	Description
Expired	Indicates that the message has been moved to the exception queue.
Processed	Indicates that the message has been processed and retained.
Ready	Indicates that the message is ready to be processed.
Waiting	Indicates that the message delay has not been reached.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleAQMessage Class"](#) on page 12-25
- ["State"](#) on page 12-36

---

## OracleAQMessageType Enumeration

The `OracleAQMessageType` enumeration type specifies the message payload type.

[Table 12-33](#) lists all the `OracleAQMessageType` enumeration values with a description of each enumerated value.

**Table 12-33 OracleAQMessageType Members**

Member Name	Description
Raw	Indicates the Raw message type. The data type of the payload must be either <code>OracleBinary</code> or <code>byte[]</code> to enqueue the message.
UDT	Indicates the Oracle UDT message type. The ODP.NET AQ implementation currently does not support user defined types with LOB attributes. It also does not support other variants of user defined types such as VARRAY and nested tables, as Oracle Streams AQ does not support them inherently.
XML	Indicates the XML message type. The data type of the payload must be <code>OracleXmlType</code> , <code>XmlReader</code> , or <code>String</code> in order to enqueue the message.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleAQQueue Class"](#) on page 12-48
- ["OracleAQQueue Constructors"](#) on page 12-51
- ["MessageType"](#) on page 12-60

## OracleAQNavigationMode Enumeration

Table 12–34 lists all the `OracleAQNavigationMode` enumeration values with a description of each enumerated value.

**Table 12–34 OracleAQNavigationMode Members**

Member Name	Description
<code>FirstMessage</code>	Retrieves the first message that is available and matches the search criteria. This resets the position to the beginning of the queue.
<code>FirstMessageMultiGroup</code>	Indicates that a call to <code>DequeueArray</code> resets the position to the beginning of the queue, and dequeues messages that are available and match the search criteria. Messages are dequeued till the <code>dequeueCount</code> limit is reached. The dequeued messages can belong to different transaction groups.  You can use the <code>OracleAQMessage.TransactionGroup</code> property to distinguish between messages from different transaction groups. All messages from the same transaction group have the same value for the <code>OracleAQMessage.TransactionGroup</code> property.
<code>NextMessage</code>	Retrieves the next message that is available and matches the search criteria. If the previous message belongs to a message group, AQ retrieves the next available message that matches the search criteria and belongs to the message group.
<code>NextMessageMultiGroup</code>	Indicates that a call to <code>DequeueArray</code> dequeues the next set of messages that are available and match the search criteria. Messages are dequeued till the <code>dequeueCount</code> limit is reached. The dequeued messages can belong to different transaction groups.  You can use the <code>OracleAQMessage.TransactionGroup</code> property to distinguish between messages from different transaction groups. All messages from the same transaction group have the same value for the <code>OracleAQMessage.TransactionGroup</code> property.
<code>NextTransaction</code>	Skips the remainder of the current transaction group (if any) and retrieves the first message of the next transaction group.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleAQDequeueOptions Class"](#) on page 12-8
- ["NavigationMode"](#) on page 12-15

## OracleAQNotificationGroupingType Enumeration

The `OracleAQNotificationGroupingType` enumeration type specifies the notification grouping type.

[Table 12-35](#) lists all the `OracleAQNotificationGroupingType` enumeration values with a description of each enumerated value.

**Table 12-35 OracleAQNotificationGroupingType Members**

Member Name	Description
<code>Last</code>	Indicates that only details of the last message in the notification group are provided.
<code>Summary</code>	Indicates that the <code>Summary</code> of all messages in the notification group is provided.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleNotificationRequest Class"](#) on page 9-22

---

## OracleAQNotificationType Enumeration

The `OracleAQNotificationType` enumeration type specifies the notification type of the received notification.

[Table 12-36](#) lists all the `OracleAQNotificationType` enumeration values with a description of each enumerated value.

**Table 12-36** *OracleAQNotificationType Members*

Member Name	Description
Group	Indicates that the received notification is a grouping notification.
Regular	Indicates that the received notification is a regular notification.
Timeout	Indicates that the received notification is raised due to a timeout.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4

## OracleAQVisibilityMode Enumeration

[Table 12-37](#) lists all the `OracleAQVisibilityMode` enumeration values with a description of each enumerated value.

**Table 12-37 OracleAQVisibilityMode Members**

Member Name	Description
<code>Immediate</code>	Indicates that the enqueue or dequeue operation is not part of the current transaction. The operation constitutes a transaction of its own.
<code>OnCommit</code>	Indicates that the enqueue or dequeue operation is part of the current transaction. This is the default case.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4



---

---

## Oracle Data Provider for .NET Types Classes

This chapter describes the large object and `REF CURSOR` objects provided by Oracle Data Provider for .NET.

This chapter contains these topics:

- ODP.NET Types (ODP.NET LOB objects) consisting of these object classes:
  - [OracleBFile Class](#)
  - [OracleBlob Class](#)
  - [OracleClob Class](#)
- [OracleRefCursor Class](#)

All offsets are 0-based for all ODP.NET LOB object parameters.

## OracleBFile Class

An `OracleBFile` is an object that has a reference to BFILE data. It provides methods for performing operations on BFILES.

---

---

**Note:** `OracleBFile` is supported for applications running against Oracle8.x and later.

---

---

### Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.IO.Stream`

`Oracle.DataAccess.Types.OracleBFile`

### Declaration

```
// C#
public sealed class OracleBFile : Stream, ICloneable, INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

`OracleBFile` is supported for applications running against Oracle8.x and later.

### Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleBFileSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
    }
}
```

```
OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

// Open the OracleBFile
bFile.OpenFile();

// Read 7 bytes into readBuffer, starting at buffer offset 0
byte[] readBuffer = new byte[7];
int bytesRead = bFile.Read(readBuffer, 0, 7);

// Prints "bytesRead = 7"
Console.WriteLine("bytesRead = " + bytesRead);

// Prints "readBuffer = 65666768656667"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a byte pattern {66,67}
// starting from byte offset 1 in the OracleBFile
byte[] pattern = new byte[2] {66, 67};
long posFound = bFile.Search(pattern, 1, 2);

// Prints "posFound = 6"
Console.WriteLine("posFound = " + posFound);

// Close the OracleBFile
bFile.CloseFile();

bFile.Close();
bFile.Dispose();

con.Close();
con.Dispose();
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Members](#)
- [OracleBFile Constructors](#)
- [OracleBFile Static Fields](#)
- [OracleBFile Static Methods](#)
- [OracleBFile Instance Properties](#)
- [OracleBFile Instance Methods](#)

## OracleBFile Members

OracleBFile members are listed in the following tables.

### OracleBFile Constructors

OracleBFile constructors are listed in [Table 13-1](#).

**Table 13-1 OracleBFile Constructors**

Constructor	Description
<a href="#">OracleBFile Constructors</a>	Creates an instance of the OracleBFile class (Overloaded)

### OracleBFile Static Fields

OracleBFile static fields are listed in [Table 13-2](#).

**Table 13-2 OracleBFile Static Fields**

Field	Description
<a href="#">MaxSize</a>	The static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 ( $2^{32} - 1$ ) bytes
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleBFile instance

### OracleBFile Static Methods

OracleBFile static methods are listed in [Table 13-3](#).

**Table 13-3 OracleBFile Static Methods**

Methods	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleBFile Instance Properties

OracleBFile instance properties are listed in [Table 13-4](#).

**Table 13-4 OracleBFile Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the LOB stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operations can be performed
<a href="#">CanWrite</a>	Indicates whether or not the LOB object supports writing
<a href="#">Connection</a>	Indicates the connection used to read from a BFILE
<a href="#">DirectoryName</a>	Indicates the directory alias of the BFILE
<a href="#">FileExists</a>	Indicates whether or not the specified BFILE exists
<a href="#">FileName</a>	Indicates the name of the BFILE
<a href="#">IsEmpty</a>	Indicates whether the BFILE is empty or not

**Table 13–4 (Cont.) OracleBFile Instance Properties**

Properties	Description
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsOpen</a>	Indicates whether the BFILE has been opened by this instance or not
<a href="#">Length</a>	Indicates the size of the BFILE data in bytes
<a href="#">Position</a>	Indicates the current read position in the LOB stream
<a href="#">Value</a>	Returns the data, starting from the first byte in BFILE, as a byte array

### OracleBFile Instance Methods

OracleBFile instance methods are listed in [Table 13–5](#).

**Table 13–5 OracleBFile Instance Methods**

Methods	Description
<a href="#">BeginRead</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">BeginWrite</a>	<i>Not Supported</i>
<a href="#">Clone</a>	Creates a copy of an OracleBFile object
<a href="#">Close</a>	Closes the current stream and releases any resources associated with the stream
<a href="#">CloseFile</a>	Closes the BFILE referenced by the current BFILE instance
<a href="#">Compare</a>	Compares data referenced by the two OracleBFiles
<a href="#">CreateObjRef</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">CopyTo</a>	Copies data as specified (Overloaded)
<a href="#">Dispose</a>	Releases resources allocated by this object
<a href="#">EndRead</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">EndWrite</a>	<i>Not Supported</i>
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">Flush</a>	<i>Not Supported</i>
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">InitializeLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">IsEqual</a>	Compares the LOB references
<a href="#">OpenFile</a>	Opens the BFILE specified by the <code>FileName</code> and <code>DirectoryName</code>
<a href="#">Read</a>	Reads a specified amount of bytes from the OracleBFile instance and populates the buffer
<a href="#">ReadByte</a>	Inherited from <code>System.IO.Stream</code>

**Table 13–5 (Cont.) OracleBFile Instance Methods**

<b>Methods</b>	<b>Description</b>
<a href="#">Search</a>	Searches for a binary pattern in the current instance of an OracleBFile
<a href="#">Seek</a>	Sets the position on the current LOB stream
SetLength	<i>Not Supported</i>
ToString	Inherited from <code>System.Object</code>
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Members](#)

## OracleBFile Constructors

OracleBFile constructors create new instances of the OracleBFile class.

### Overload List:

- [OracleBFile\(OracleConnection\)](#)

This constructor creates an instance of the OracleBFile class with an OracleConnection object.

- [OracleBFile\(OracleConnection, string, string\)](#)

This constructor creates an instance of the OracleBFile class with an OracleConnection object, the location of the BFILE, and the name of the BFILE.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

### OracleBFile(OracleConnection)

This constructor creates an instance of the OracleBFile class with an OracleConnection object.

### Declaration

```
// C#  
public OracleBFile(OracleConnection con);
```

### Parameters

- *con*  
The OracleConnection object.

### Exceptions

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

### Remarks

The connection must be opened explicitly by the application. OracleBFile does not open the connection implicitly.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

### OracleBFile(OracleConnection, string, string)

This constructor creates an instance of the OracleBFile class with an OracleConnection object, the location of the BFILE, and the name of the BFILE.

### Declaration

```
// C#  
public OracleBFile(OracleConnection con, string directoryName, string  
    fileName);
```

### Parameters

- *con*  
The `OracleConnection` object.
- *directoryName*  
The directory alias created by the `CREATE DIRECTORY SQL` statement.
- *fileName*  
The name of the external LOB.

### Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The `OracleConnection` must be opened explicitly by the application. `OracleBFile` does not open the connection implicitly.

To initialize a `BFILE` column using an `OracleBFile` instance as an input parameter of a `SQL INSERT` statement, *directoryName* and *fileName* must be properly set.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)



## OracleBFile Static Fields

OracleBFile static fields are listed in [Table 13–6](#).

**Table 13–6 OracleBFile Static Fields**

Field	Description
<a href="#">MaxSize</a>	The static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 (2 <sup>32</sup> - 1) bytes
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleBFile instance

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

### MaxSize

This static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 (2<sup>32</sup> - 1) bytes.

### Declaration

```
// C#
public static readonly Int64 MaxSize = 4294967295;
```

### Remarks

This field is useful in code that checks whether or not the operation exceeds the maximum length allowed.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

### Null

This static field represents a null value that can be assigned to the value of an OracleBFile instance.

### Declaration

```
// C#
public static readonly OracleBFile Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## OracleBFile Static Methods

OracleBFile static methods are listed in [Table 13-7](#).

**Table 13-7 OracleBFile Static Methods**

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## OracleBFile Instance Properties

OracleBFile instance properties are listed in [Table 13–8](#).

**Table 13–8 OracleBFile Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the LOB stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operations can be performed
<a href="#">CanWrite</a>	Indicates whether or not the LOB object supports writing
<a href="#">Connection</a>	Indicates the connection used to read from a BFILE
<a href="#">DirectoryName</a>	Indicates the directory alias of the BFILE
<a href="#">FileExists</a>	Indicates whether or not the specified BFILE exists
<a href="#">FileName</a>	Indicates the name of the BFILE
<a href="#">IsEmpty</a>	Indicates whether the BFILE is empty or not
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsOpen</a>	Indicates whether the BFILE has been opened by this instance or not
<a href="#">Length</a>	Indicates the size of the BFILE data in bytes
<a href="#">Position</a>	Indicates the current read position in the LOB stream
<a href="#">Value</a>	Returns the data, starting from the first byte in BFILE, as a byte array

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

### CanRead

Overrides `Stream`

This instance property indicates whether or not the LOB stream can be read.

**Declaration**

```
// C#
public override bool CanRead{get;}
```

**Property Value**

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

### Declaration

```
// C#  
public override bool CanSeek{get;}
```

### Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

### Declaration

```
// C#  
public override bool CanWrite{get;}
```

### Property Value

BFILE is read only.

### Remarks

BFILE is read-only, therefore, the boolean value is always `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## Connection

This instance property indicates the connection used to read from a BFILE.

### Declaration

```
// C#  
public OracleConnection Connection {get;}
```

### Property Value

An object of `OracleConnection`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**DirectoryName**

This instance property indicates the directory alias of the BFILE.

**Declaration**

```
// C#  
public string DirectoryName {get;set;}
```

**Property Value**

A string.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The value of the `DirectoryName` changed while the BFILE is open.

**Remarks**

The maximum length of a `DirectoryName` is 30 bytes.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**FileExists**

This instance property indicates whether or not the BFILE specified by the `DirectoryName` and `FileName` exists.

**Declaration**

```
// C#  
public bool FileExists {get;}
```

**Property Value**

bool

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

Unless a connection, file name, and directory name are provided, this property is set to false by default.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**FileName**

This instance property indicates the name of the BFILE.

**Declaration**

```
// C#  
public string FileName {get;set}
```

**Property Value**

A string that contains the BFILE name.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The value of the `DirectoryName` changed while the BFILE is open.

**Remarks**

The maximum length of a `FileName` is 255 bytes.

Changing the `FileName` property while the BFILE object is opened causes an exception.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**IsEmpty**

This instance property indicates whether the BFILE is empty or not.

**Declaration**

```
// C#  
public bool IsEmpty {get;}
```

**Property Value**

bool

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**IsNull**

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#  
public bool IsNull{get;}
```

**Property Value**

Returns `true` if the current instance has a null value; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**IsOpen**

This instance property indicates whether the `BFILE` has been opened by this instance or not.

**Declaration**

```
// C#  
public bool IsOpen {get;}
```

**Property Value**

A `bool`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Length**

Overrides `Stream`

This instance property indicates the size of the `BFILE` data in bytes.

**Declaration**

```
// C#  
public override Int64 Length {get;}
```

**Property Value**

`Int64`



**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Position**

Overrides `Stream`

This instance property indicates the current read position in the LOB stream.

**Declaration**

```
// C#
public override Int64 Position{get; set;}
```

**Property Value**

An `Int64` value that indicates the read position.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The value is less than 0.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Value**

This instance property returns the data, starting from the first byte in `BFILE`, as a byte array.

**Declaration**

```
// C#
public byte[] Value{get;}
```

**Property Value**

A byte array.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The length of data is bound by the maximum length of the byte array. The current value of the `Position` property is not used or changed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## OracleBFile Instance Methods

OracleBFile instance methods are listed in [Table 13–9](#).

**Table 13–9 OracleBFile Instance Methods**

Methods	Description
BeginRead	Inherited from <code>System.IO.Stream</code>
BeginWrite	<i>Not Supported</i>
Clone	Creates a copy of an OracleBFile object
Close	Closes the current stream and releases any resources associated with the stream
CloseFile	Closes the BFILE referenced by the current BFILE instance
Compare	Compares data referenced by the two OracleBFiles
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
CopyTo	Copies data as specified (Overloaded)
Dispose	Releases resources allocated by this object
EndRead	Inherited from <code>System.IO.Stream</code>
EndWrite	<i>Not Supported</i>
Equals	Inherited from <code>System.Object</code> (Overloaded)
Flush	<i>Not Supported</i>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
IsEqual	Compares the LOB references
OpenFile	Opens the BFILE specified by the <code>FileName</code> and <code>DirectoryName</code>
Read	Reads a specified amount of bytes from the OracleBFile instance and populates the buffer
ReadByte	Inherited from <code>System.IO.Stream</code>
Search	Searches for a binary pattern in the current instance of an OracleBFile
Seek	Sets the position on the current LOB stream
SetLength	<i>Not Supported</i>
ToString	Inherited from <code>System.Object</code>
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## Clone

This instance method creates a copy of an `OracleBFile` object.

**Declaration**

```
// C#  
public object Clone();
```

**Return Value**

An `OracleBFile` object.

**Implements**

`ICloneable`

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**Example**

```
// Database Setup, if you have not done so yet.  
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.  
  
CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';  
  
*/  
  
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class CloneSample  
{  
    static void Main()  
    {  
        // Create MYDIR directory object as indicated previously and create a file  
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.  
        // Note that the byte representation of the ABCDABC is 65666768656667  
  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleBFile bFile1 = new OracleBFile(con, "MYDIR", "MyFile.txt");
```

```

// Prints "bFile1.Position = 0"
Console.WriteLine("bFile1.Position = " + bFile1.Position);

// Set the Position before calling Clone()
bFile1.Position = 1;

// Clone the OracleBFile
OracleBFile bFile2 = (OracleBFile) bFile1.Clone();

// Prints "bFile2.Position = 1"
Console.WriteLine("bFile2.Position = " + bFile2.Position);

bFile1.Close();
bFile1.Dispose();

bFile2.Close();
bFile2.Dispose();

con.Close();
con.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Close**

Overrides Stream

This instance method closes the current stream and releases any resources associated with it.

**Declaration**

```

// C#
public override void Close();

```

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**CloseFile**

This instance method closes the BFILE referenced by the current BFILE instance.

**Declaration**

```
// C#  
public void CloseFile();
```

**Remarks**

No error is returned if the BFILE exists, but is not opened.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Compare**

This instance method compares data referenced by the two OracleBFiles.

**Declaration**

```
// C#  
public int Compare(Int64 src_offset, OracleBFile obj, Int64 dst_offset,  
    Int64 amount);
```

**Parameters**

- *src\_offset*  
The offset of the current instance.
- *obj*  
The provided OracleBFile object.
- *dst\_offset*  
The offset of the OracleBFile object.
- *amount*  
The number of bytes to compare.

**Return Value**

Returns a number that is:

- Less than zero: if the BFILE data of the current instance is less than that of the provided BFILE data.
- Zero: if both the BFILES store the same data.
- Greater than zero: if the BFILE data of the current instance is greater than that of the provided BFILE data.

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The *src\_offset*, the *dst\_offset*, or the *amount* is less than 0.

**Remarks**

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

The `BFILE` needs to be opened using `OpenFile` before the operation.

**Example**

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CompareSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile1 = new OracleBFile(con, "MYDIR", "MyFile.txt");
        OracleBFile bFile2 = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFiles
        bFile1.OpenFile();
        bFile2.OpenFile();

        // Compare 2 bytes from the 1st byte of bFile1 and
        // the 5th byte of bFile2 onwards
        int result = bFile1.Compare(1, bFile2, 5, 2);

        // Prints "result = 0" (Indicates the data is identical)
        Console.WriteLine("result = " + result);

        // Close the OracleBFiles
        bFile1.CloseFile();
        bFile2.CloseFile();

        bFile1.Close();
        bFile1.Dispose();

        bFile2.Close();
        bFile2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CopyTo

CopyTo copies data from the current instance to the provided object.

**Overload List:**

- [CopyTo\(OracleBlob\)](#)

This instance method copies data from the current instance to the provided OracleBlob object.
- [CopyTo\(OracleBlob, Int64\)](#)

This instance method copies data from the current OracleBFile instance to the provided OracleBlob object with the specified destination offset.
- [CopyTo\(Int64, OracleBlob, Int64, Int64\)](#)

This instance method copies data from the current OracleBFile instance to the provided OracleBlob object with the specified source offset, destination offset, and character amounts.
- [CopyTo\(OracleClob\)](#)

This instance method copies data from the current OracleBFile instance to the provided OracleClob object.
- [CopyTo\(OracleClob, Int64\)](#)

This instance method copies data from the current OracleBFile instance to the provided OracleClob object with the specified destination offset.
- [CopyTo\(Int64, OracleClob, Int64, Int64\)](#)

This instance method copies data from the current OracleBFile instance to the provided OracleClob object with the specified source offset, destination offset, and amount of characters.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CopyTo(OracleBlob)

This instance method copies data from the current instance to the provided OracleBlob object.

**Declaration**

```
// C#  
public Int64 CopyTo(OracleBlob obj);
```



### Parameters

- *obj*

The `OracleBlob` object to which the data is copied.

### Return Value

The return value is the amount copied.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

### Remarks

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CopyTo(OracleBlob, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified destination offset.

### Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj, Int64 dst_offset);
```

### Parameters

- *obj*

The `OracleBlob` object to which the data is copied.

- *dst\_offset*

The offset (in bytes) at which the `OracleBlob` object is copied.

### Return Value

The return value is the amount copied.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst\_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

**Remarks**

If the `dst_offset` is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**CopyTo(Int64, OracleBlob, Int64, Int64)**

This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

**Declaration**

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleBlob obj, Int64 dst_offset,
    Int64 amount);
```

**Parameters**

- `src_offset`  
The offset (in bytes) in the current instance, from which the data is read.
- `obj`  
An `OracleBlob` object to which the data is copied.
- `dst_offset`  
The offset (in bytes) to which the `OracleBlob` object is copied.
- `amount`  
The amount of data to be copied.

**Return Value**

The return value is the amount copied.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The `src_offset`, the `dst_offset`, or the `amount` is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

### Remarks

If the `dst_offset` is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CopyTo(OracleClob)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object.

### Declaration

```
// C#
public Int64 CopyTo(OracleClob obj);
```

### Parameters

- *obj*  
The `OracleClob` object to which the data is copied.

### Return Value

The return value is the amount copied.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

### Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**CopyTo(OracleClob, Int64)**

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified destination offset.

**Declaration**

```
// C#  
public Int64 CopyTo(OracleClob obj, Int64 dst_offset);
```

**Parameters**

- *obj*  
The `OracleClob` object that the data is copied to.
- *dst\_offset*  
The offset (in characters) at which the `OracleClob` object is copied to.

**Return Value**

The amount copied.

**Exceptions****Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst\_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

**Remarks**

If the *dst\_offset* is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the *dst\_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## CopyTo(Int64, OracleClob, Int64, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified source offset, destination offset, and amount of characters.

### Declaration

```
// C#  
public Int64 CopyTo(Int64 src_offset, OracleClob obj, Int64 dst_offset,  
    Int64 amount);
```

### Parameters

- *src\_offset*  
The offset (in characters) in the current instance, from which the data is read.
- *obj*  
An `OracleClob` object that the data is copied to.
- *dst\_offset*  
The offset (in characters) at which the `OracleClob` object is copied to.
- *amount*  
The amount of data to be copied.

### Return Value

The return value is the amount copied.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *src\_offset*, the *dst\_offset*, or the *amount* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

### Remarks

If the *dst\_offset* is beyond the end of the current `OracleClob` data, spaces are written into the `OracleClob` until the *dst\_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## Dispose

This instance method releases resources allocated by this object.

### Declaration

```
// C#  
public void Dispose();
```

### Implements

IDisposable

### Remarks

Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls may lead to exceptions. The object cannot be reused after being disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## IsEqual

This instance method compares the LOB references.

### Declaration

```
// C#  
public bool IsEqual(OracleBFile obj);
```

### Parameters

- *obj*  
The provided OracleBFile object.

### Return Value

Returns `true` if the current OracleBFile and the provided OracleBFile object refer to the same external LOB. Returns `false` otherwise.

### Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

### Remarks

Note that this method can return `true` even if the two OracleBFile objects return `false` for `==` or `Equals()` since two different OracleBFile instances can refer to the same external LOB.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## OpenFile

This instance method opens the BFILE specified by the `FileName` and `DirectoryName`.

**Declaration**

```
// C#  
public void OpenFile();
```

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

Many operations, such as `Compare()`, `CopyTo()`, `Read()`, and `Search()` require that the BFILE be opened using `OpenFile` before the operation.

Calling `OpenFile` on an opened BFILE is not operational.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## Read

Overrides `Stream`

This instance method reads a specified amount of bytes from the `OracleBFile` instance and populates the `buffer`.

**Declaration**

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
The byte array buffer to be populated.
- *offset*  
The offset of the byte array buffer to be populated.
- *count*  
The amount of bytes to read.

**Return Value**

The return value indicates the number of bytes read from the BFILE, that is, the external LOB.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - Either the *offset* or the *count* parameter is less than 0 or the *offset* is greater than or equal to the *buffer.Length* or the *offset* and the *count* together are greater than *buffer.Length*.

**Remarks**

The LOB data is read starting from the position specified by the `Position` property.

**Example**

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Read 7 bytes into readBuffer, starting at buffer offset 0
        byte[] readBuffer = new byte[7];
        int bytesRead = bFile.Read(readBuffer, 0, 7);

        // Prints "bytesRead = 7"
        Console.WriteLine("bytesRead = " + bytesRead);

        // Prints "readBuffer = 65666768656667"
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
```



```

    {
        Console.Write(readBuffer[index]);
    }
    Console.WriteLine();

    // Close the OracleBFile
    bFile.CloseFile();

    bFile.Close();
    bFile.Dispose();

    con.Close();
    con.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Search**

This instance method searches for a binary pattern in the current instance of an OracleBFile.

**Declaration**

```

// C#
public int Search(byte[] val, Int64 offset, Int64 nth);

```

**Parameters**

- *val*  
The binary pattern being searched for.
- *offset*  
The 0-based offset (in bytes) starting from which the OracleBFile is searched.
- *nth*  
The specific occurrence (1-based) of the match for which the offset is returned.

**Return Value**

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - Either the *offset* is less than 0 or *nth* is less than or equal to 0 or *val.Length* is greater than 16383 or *nth* is greater than or equal to OracleBFile.MaxSize or *offset* is greater than or equal to OracleBFile.MaxSize.

**Remarks**

The limit of the search pattern is 16383 bytes.

**Example**

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Search for the 2nd occurrence of a byte pattern {66,67}
        // starting from byte offset 1 in the OracleBFile
        byte[] pattern = new byte[2] {66, 67};
        long posFound = bFile.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);

        // Close the OracleBFile
        bFile.CloseFile();

        bFile.Close();
        bFile.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

**Seek**

Overrides Stream

This instance method sets the position on the current LOB stream.

**Declaration**

```
// C#
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

**Parameters**

- *offset*  
A byte offset relative to origin.
- *origin*  
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

**Return Value**

Returns an `Int64` that indicates the position.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

**Example**

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#
```

```
using System;
using System.IO;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SeekSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Set the Position to 2 with respect to SeekOrigin.Begin
        long newPosition = bFile.Seek(2, SeekOrigin.Begin);

        // Prints "newPosition      = 2"
        Console.WriteLine("newPosition      = " + newPosition);

        // Prints "bFile.Position = 2"
        Console.WriteLine("bFile.Position = " + bFile.Position);

        // Read 2 bytes into readBuffer, starting at buffer offset 1
        byte[] readBuffer = new byte[4];
        int bytesRead = bFile.Read(readBuffer, 1, 2);

        // Prints "bytesRead      = 2"
        Console.WriteLine("bytesRead      = " + bytesRead);

        // Prints "readBuffer      = 067680"
        Console.Write("readBuffer      = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        // Close the OracleBFile
        bFile.CloseFile();

        bFile.Close();
        bFile.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

## OracleBlob Class

An `OracleBlob` object is an object that has a reference to BLOB data. It provides methods for performing operations on BLOBs.

### Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.IO.Stream`

`Oracle.DataAccess.Types.OracleBlob`

### Declaration

```
// C#
public sealed class OracleBlob : Stream, ICloneable, INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleBlobSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 4 bytes from writeBuffer, starting at buffer offset 0
        byte[] writeBuffer = new byte[4] {1, 2, 3, 4};
        blob.Write(writeBuffer, 0, 4);

        // Append first 2 bytes from writeBuffer {1, 2} to the oracleBlob
        blob.Append(writeBuffer, 0, 2);

        // Prints "blob.Length = 6"
        Console.WriteLine("blob.Length = " + blob.Length);

        // Reset the Position for the Read
        blob.Position = 0;

        // Read 6 bytes into readBuffer, starting at buffer offset 0
        byte[] readBuffer = new byte[6];
        int bytesRead = blob.Read(readBuffer, 0, 6);

        // Prints "bytesRead = 6"
```

```

Console.WriteLine("bytesRead    = " + bytesRead);

// Prints "readBuffer    = 123412"
Console.Write("readBuffer    = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a byte pattern '12'
// starting from byte offset 0 in the OracleBlob
byte[] pattern = new byte[2] {1, 2};
long posFound = blob.Search(pattern, 0, 2);

// Prints "posFound      = 5"
Console.WriteLine("posFound      = " + posFound);

// Erase 4 bytes of data starting at byte offset 1
// Sets bytes to zero
blob.Erase(1, 4);

byte[] erasedBuffer = blob.Value;

//Prints "erasedBuffer = 100002"
Console.Write("erasedBuffer = ");
for(int index = 0; index < erasedBuffer.Length; index++)
{
    Console.Write(erasedBuffer[index]);
}
Console.WriteLine();

blob.Close();
blob.Dispose();

con.Close();
con.Dispose();
}
}

```

**Requirements**

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Members](#)
- [OracleBlob Constructors](#)
- [OracleBlob Static Fields](#)
- [OracleBlob Static Methods](#)
- [OracleBlob Instance Properties](#)
- [OracleBlob Instance Methods](#)

## OracleBlob Members

OracleBlob members are listed in the following tables.

### OracleBlob Constructors

OracleBlob constructors are listed in [Table 13-10](#).

**Table 13-10 OracleBlob Constructors**

Constructor	Description
<a href="#">OracleBlob Constructors</a>	Creates an instance of the OracleBlob class (Overloaded)

### OracleBlob Static Fields

OracleBlob static fields are listed in [Table 13-11](#).

**Table 13-11 OracleBlob Static Fields**

Field	Description
<a href="#">MaxSize</a>	Holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 (2 <sup>32</sup> - 1) bytes
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleBlob instance

### OracleBlob Static Methods

OracleBlob static methods are listed in [Table 13-12](#).

**Table 13-12 OracleBlob Static Methods**

Methods	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleBlob Instance Properties

OracleBlob instance properties are listed in [Table 13-13](#).

**Table 13-13 OracleBlob Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the LOB stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operations be performed
<a href="#">CanWrite</a>	Indicates whether or not the LOB object supports writing
<a href="#">Connection</a>	Indicates the OracleConnection that is used to retrieve and write BLOB data
<a href="#">IsEmpty</a>	Indicates whether the BLOB is empty or not
<a href="#">IsInChunkWriteMode</a>	Indicates whether or not the BLOB has been opened to defer index updates
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value



**Table 13–13 (Cont.) OracleBlob Instance Properties**

Properties	Description
<a href="#">IsTemporary</a>	Indicates whether or not the current instance is bound to a temporary BLOB
<a href="#">Length</a>	Indicates the size of the BLOB data
<a href="#">OptimumChunkSize</a>	Indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance
<a href="#">Position</a>	Indicates the current read or write position in the LOB stream
<a href="#">Value</a>	Returns the data, starting from the first byte in BLOB, as a byte array

### OracleBlob Instance Methods

OracleBlob instance methods are listed in [Table 13–14](#).

**Table 13–14 OracleBlob Instance Methods**

Methods	Description
<a href="#">Append</a>	Appends the supplied data to the current OracleBlob instance (Overloaded)
<a href="#">BeginChunkWrite</a>	Opens the BLOB
<a href="#">BeginRead</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">BeginWrite</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">Clone</a>	Creates a copy of an OracleBlob object
<a href="#">Close</a>	Closes the current stream and releases any resources associated with it
<a href="#">Compare</a>	Compares data referenced by the current instance and that of the supplied object
<a href="#">CopyTo</a>	Copies from the current OracleBlob instance to an OracleBlob object (Overloaded)
<a href="#">CreateObjRef</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Dispose</a>	Releases resources allocated by this object
<a href="#">EndChunkWrite</a>	Closes the BLOB referenced by the current OracleBlob instance
<a href="#">EndRead</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">EndWrite</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">Erase</a>	Erases data (Overloaded)
<a href="#">Flush</a>	<i>Not supported</i>
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">InitializedLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>

**Table 13–14 (Cont.) OracleBlob Instance Methods**

Methods	Description
<a href="#">IsEqual</a>	Compares the LOB data referenced by the two OracleBlobs
<a href="#">Read</a>	Reads a specified amount of bytes from the ODP.NET LOB Type instance and populates the buffer
ReadByte	Inherited from <code>System.IO.Stream</code>
<a href="#">Search</a>	Searches for a binary pattern in the current instance of an OracleBlob
<a href="#">Seek</a>	Sets the position in the current LOB stream
<a href="#">SetLength</a>	Trims or truncates the BLOB value to the specified length
ToString	Inherited from <code>System.Object</code>
<a href="#">Write</a>	Writes the supplied buffer into the OracleBlob
WriteByte	Inherited from <code>System.IO.Stream</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Members](#)

## OracleBlob Constructors

OracleBlob constructors are listed in [Table 13-10](#).

### Overload List:

- [OracleBlob\(OracleConnection\)](#)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object.

- [OracleBlob\(OracleConnection, bool\)](#)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object and a boolean value for caching.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

### OracleBlob(OracleConnection)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object.

#### Declaration

```
// C#  
public OracleBlob(OracleConnection con);
```

#### Parameters

- *con*  
The OracleConnection object.

#### Exceptions

InvalidOperationException - The OracleConnection is not opened.

#### Remarks

The connection must be opened explicitly by the application. OracleBlob does not open the connection implicitly.

The temporary BLOB utilizes the provided connection to store BLOB data. Caching is not turned on by this constructor.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## OracleBlob(OracleConnection, bool)

This constructor creates an instance of the `OracleBlob` class bound to a temporary BLOB with an `OracleConnection` object and a boolean value for caching.

### Declaration

```
// C#  
public OracleBlob(OracleConnection con, bool bCaching);
```

### Parameters

- *con*  
The `OracleConnection` object.
- *bCaching*  
A flag for enabling or disabling server-side caching.

### Exceptions

`InvalidOperationException` - The `OracleConnection` is not opened.

### Remarks

The connection must be opened explicitly by the application. `OracleBlob` does not open the connection implicitly.

The temporary BLOB uses the provided connection to store BLOB data. The *bCaching* input parameter determines whether or not server-side caching is used.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## OracleBlob Static Fields

OracleBlob static fields are listed in [Table 13–15](#).

**Table 13–15 OracleBlob Static Fields**

Field	Description
<a href="#">MaxSize</a>	Holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 (2 <sup>32</sup> - 1) bytes
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleBlob instance

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## MaxSize

The `MaxSize` field holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 (2<sup>32</sup> - 1) bytes.

### Declaration

```
// C#
public static readonly Int64 MaxSize = 4294967295;
```

### Remarks

This field can be useful in code that checks whether or not the operation exceeds the maximum length allowed.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Null

This static field represents a null value that can be assigned to the value of an OracleBlob instance.

### Declaration

```
// C#
public static readonly OracleBlob Null;
```

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## OracleBlob Static Methods

OracleBlob static methods are listed in [Table 13–16](#).

**Table 13–16 OracleBlob Static Methods**

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## OracleBlob Instance Properties

OracleBlob instance properties are listed in [Table 13–17](#).

**Table 13–17 OracleBlob Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the LOB stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operations be performed
<a href="#">CanWrite</a>	Indicates whether or not the LOB object supports writing
<a href="#">Connection</a>	Indicates the <a href="#">OracleConnection</a> that is used to retrieve and write BLOB data
<a href="#">IsEmpty</a>	Indicates whether the BLOB is empty or not
<a href="#">IsInChunkWriteMode</a>	Indicates whether or not the BLOB has been opened to defer index updates
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsTemporary</a>	Indicates whether or not the current instance is bound to a temporary BLOB
<a href="#">Length</a>	Indicates the size of the BLOB data
<a href="#">OptimumChunkSize</a>	Indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance
<a href="#">Position</a>	Indicates the current read or write position in the LOB stream
<a href="#">Value</a>	Returns the data, starting from the first byte in BLOB, as a byte array

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## CanRead

Overrides [Stream](#)

This instance property indicates whether or not the LOB stream can be read.

### Declaration

```
// C#
public override bool CanRead{get;}
```

### Property Value

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

### Declaration

```
// C#  
public override bool CanSeek{get;}
```

### Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

### Declaration

```
// C#  
public override bool CanWrite{get;}
```

### Property Value

If the LOB stream can be written, returns `true`; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Connection

This instance property indicates the `OracleConnection` that is used to retrieve and write BLOB data.

### Declaration

```
// C#  
public OracleConnection Connection {get;}
```

### Property Value

An object of `OracleConnection`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## IsEmpty

This instance property indicates whether the BLOB is empty or not.

**Declaration**

```
// C#  
public bool IsEmpty {get;}
```

**Property Value**

A `bool` that indicates whether or not the BLOB is empty.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## IsInChunkWriteMode

This instance property indicates whether or not the BLOB has been opened to defer index updates.

**Declaration**

```
// C#  
public bool IsInChunkWriteMode{get;}
```

**Property Value**

If the BLOB has been opened, returns `true`; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## IsNull

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#  
public bool IsNull{get;}
```

**Property Value**

Returns `true` if the current instance has a null value; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**IsTemporary**

This instance property indicates whether or not the current instance is bound to a temporary BLOB.

**Declaration**

```
// C#  
public bool IsTemporary {get;}
```

**Property Value**

`bool`

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**Length**

Overrides `Stream`

This instance property indicates the size of the BLOB data in bytes.

**Declaration**

```
// C#  
public override Int64 Length {get;}
```

**Property Value**

A number indicating the size of the BLOB data in bytes.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## OptimumChunkSize

This instance property indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance.

### Declaration

```
// C#  
public int OptimumChunkSize{get;}
```

### Property Value

A number representing the minimum bytes to retrieve or send.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Position

Overrides `Stream`

This instance property indicates the current read or write position in the LOB stream.

### Declaration

```
// C#  
public override Int64 Position{get; set;}
```

### Property Value

An `Int64` that indicates the read or write position.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Value

This instance property returns the data, starting from the first byte in the BLOB, as a byte array.

### Declaration

```
// C#  
public Byte[] Value{get;}
```

**Property Value**

A byte array.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Value` is less than 0.

**Remarks**

The value of `Position` is not used or changed by using this property. 2 GB is the maximum byte array length that can be returned by this property.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## OracleBlob Instance Methods

OracleBlob instance methods are listed in [Table 13–18](#).

**Table 13–18 OracleBlob Instance Methods**

Methods	Description
<a href="#">Append</a>	Appends the supplied data to the current OracleBlob instance (Overloaded)
<a href="#">BeginChunkWrite</a>	Opens the BLOB
BeginRead	Inherited from <code>System.IO.Stream</code>
BeginWrite	Inherited from <code>System.IO.Stream</code>
<a href="#">Clone</a>	Creates a copy of an OracleBlob object
<a href="#">Close</a>	Closes the current stream and releases any resources associated with it
<a href="#">Compare</a>	Compares data referenced by the current instance and that of the supplied object
<a href="#">CopyTo</a>	Copies from the current OracleBlob instance to an OracleBlob object (Overloaded)
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Dispose</a>	Releases resources allocated by this object
<a href="#">EndChunkWrite</a>	Closes the BLOB referenced by the current OracleBlob instance
EndRead	Inherited from <code>System.IO.Stream</code>
EndWrite	Inherited from <code>System.IO.Stream</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">Erase</a>	Erases data (Overloaded)
Flush	<i>Not supported</i>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializedLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">IsEqual</a>	Compares the LOB data referenced by the two OracleBlobs
<a href="#">Read</a>	Reads a specified amount of bytes from the ODP.NET LOB Type instance and populates the <code>buffer</code>
ReadByte	Inherited from <code>System.IO.Stream</code>
<a href="#">Search</a>	Searches for a binary pattern in the current instance of an OracleBlob
<a href="#">Seek</a>	Sets the position in the current LOB stream
<a href="#">SetLength</a>	Trims or truncates the BLOB value to the specified length
ToString	Inherited from <code>System.Object</code>
<a href="#">Write</a>	Writes the supplied buffer into the OracleBlob
WriteByte	Inherited from <code>System.IO.Stream</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Append

Append appends the supplied data to the end of the current `OracleBlob` instance.

**Overload List:**

- [Append\(OracleBlob\)](#)

This instance method appends the BLOB data referenced by the provided `OracleBlob` object to the current `OracleBlob` instance.

- [Append\(byte\[ \], int, int\)](#)

This instance method appends data from the supplied byte array buffer to the end of the current `OracleBlob` instance.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Append(OracleBlob)

This instance method appends the BLOB data referenced by the provided `OracleBlob` object to the current `OracleBlob` instance.

**Declaration**

```
// C#  
public void Append(OracleBlob obj);
```

**Parameters**

- *obj*  
An object of `OracleBlob`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

**Remarks**

No character set conversions are made.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**Append(byte[ ], int, int)**

This instance method appends data from the supplied byte array buffer to the end of the current `OracleBlob` instance.

**Declaration**

```
// C#
public void Append(byte[] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
An array of bytes.
- *offset*  
The zero-based byte offset in the buffer from which data is read.
- *count*  
The number of bytes to be appended.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class AppendSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Append 2 bytes {4, 5} to the OracleBlob
        byte[] buffer = new byte[3] {4, 5, 6};
        blob.Append(buffer, 0, 2);

        byte[] appendBuffer = blob.Value;

        // Prints "appendBuffer = 45"
        Console.Write("appendBuffer = ");
```

```
        for(int index = 0; index < appendBuffer.Length; index++)
        {
            Console.Write(appendBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## BeginChunkWrite

This instance method opens the BLOB.

**Declaration**

```
// C#
public void BeginChunkWrite();
```

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

**Remarks**

*BeginChunkWrite* does not need to be called before manipulating the BLOB data. This is provided for performance reasons.

After this method is called, write operations do not cause the domain or function-based index on the column to be updated. Index updates occur only once after *EndChunkWrite* is called.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Clone

This instance method creates a copy of an *OracleBlob* object.

**Declaration**

```
// C#
public object Clone();
```



**Return Value**

An OracleBlob object.

**Implements**

ICloneable

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CloneSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob1 = new OracleBlob(con);

        // Prints "blob1.Position = 0"
        Console.WriteLine("blob1.Position = " + blob1.Position);

        // Set the Position before calling Clone()
        blob1.Position = 1;

        // Clone the OracleBlob
        OracleBlob blob2 = (OracleBlob)blob1.Clone();

        // Prints "blob2.Position = 1"
        Console.WriteLine("blob2.Position = " + blob2.Position);

        blob1.Close();
        blob1.Dispose();

        blob2.Close();
        blob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Close

Overrides `Stream`

This instance method closes the current stream and releases any resources associated with it.

**Declaration**

```
// C#  
public override void Close();
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Compare

This instance method compares data referenced by the current instance and that of the supplied object.

**Declaration**

```
// C#  
public int Compare(Int64 src_offset, OracleBlob obj, Int64 dst_offset,  
    Int64 amount);
```

**Parameters**

- *src\_offset*  
The comparison starting point (in bytes) for the current instance.
- *obj*  
The provided `OracleBlob` object.
- *dst\_offset*  
The comparison starting point (in bytes) for the provided `OracleBlob`.
- *amount*  
The number of bytes to compare.

**Return Value**

Returns a value that is:

- Less than zero: if the data referenced by the current instance is less than that of the supplied instance
- Zero: if both objects reference the same data
- Greater than zero: if the data referenced by the current instance is greater than that of the supplied instance

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The *src\_offset*, the *dst\_offset*, or the *amount* parameter is less than 0.

**Remarks**

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**CopyTo**

`CopyTo` copies data from the current instance to the provided `OracleBlob` object.

**Overload List:**

- [CopyTo\(OracleBlob\)](#)

This instance method copies data from the current instance to the provided `OracleBlob` object.

- [CopyTo\(OracleBlob, Int64\)](#)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified destination offset.

- [CopyTo\(Int64, OracleBlob, Int64, Int64\)](#)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**CopyTo(OracleBlob)**

This instance method copies data from the current instance to the provided `OracleBlob` object.

**Declaration**

```
// C#
public Int64 CopyTo(OracleBlob obj);
```

**Parameters**

- *obj*

The `OracleBlob` object to which the data is copied.

**Return Value**

The return value is the amount copied.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

**Remarks**

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**CopyTo(OracleBlob, Int64)**

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified destination offset.

**Declaration**

```
// C#  
public Int64 CopyTo(OracleBlob obj, Int64 dst_offset);
```

**Parameters**

- *obj*  
The `OracleBlob` object to which the data is copied.
- *dst\_offset*  
The offset (in bytes) at which the `OracleBlob` object is copied.

**Return Value**

The return value is the amount copied.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst\_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.

- The LOB object parameter has a different connection than the object.

### Remarks

If the *dst\_offset* is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the *dst\_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## CopyTo(Int64, OracleBlob, Int64, Int64)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

### Declaration

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleBlob obj, Int64 dst_offset,
    Int64 amount);
```

### Parameters

- *src\_offset*  
The offset (in bytes) in the current instance, from which the data is read.
- *obj*  
The `OracleBlob` object to which the data is copied.
- *dst\_offset*  
The offset (in bytes) at which the `OracleBlob` object is copied.
- *amount*  
The amount of data to be copied.

### Return Value

The return value is the amount copied.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The *src\_offset*, the *dst\_offset*, or the *amount* parameter is less than 0.

**Remarks**

If the *dst\_offset* is beyond the end of the OracleBlob data, spaces are written into the OracleBlob until the *dst\_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CopyToSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob1 = new OracleBlob(con);
        OracleBlob blob2 = new OracleBlob(con);

        // Write 4 bytes, starting at buffer offset 0
        byte[] buffer = new byte[4] {1, 2, 3, 4};
        blob1.Write(buffer, 0, 4);

        // Copy 2 bytes from byte 0 of blob1 to byte 1 of blob2
        blob1.CopyTo(0, blob2, 1, 2);

        byte[] copyBuffer = blob2.Value;

        //Prints "Value = 012"
        Console.WriteLine("Value = ");
        for(int index = 0; index < copyBuffer.Length; index++)
        {
            Console.WriteLine(copyBuffer[index]);
        }
        Console.WriteLine();

        blob1.Close();
        blob1.Dispose();

        blob2.Close();
        blob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Dispose

This instance method releases resources allocated by this object.

**Declaration**

```
// C#  
public void Dispose();
```

**Implements**

IDisposable

**Remarks**

Once `Dispose()` is called, the object of `OracleBlob` is in an uninitialized state.

Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls may lead to exceptions. The object cannot be reused after being disposed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## EndChunkWrite

This instance method closes the BLOB referenced by the current `OracleBlob` instance.

**Declaration**

```
// C#  
public void EndChunkWrite();
```

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

Index updates occur immediately if there is write operation(s) deferred by the `BeginChunkWrite` method.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Erase

Erase erases a portion or all data.

### Overload List:

- [Erase\(\)](#)

This instance method erases all data.

- [Erase\(Int64, Int64\)](#)

This instance method erases a specified portion of data.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Erase()

This instance method erases all data.

### Declaration

```
// C#  
public Int64 Erase();
```

### Return Value

The number of bytes erased.

### Remarks

Erase() replaces all data with zero-byte fillers.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Erase(Int64, Int64)

This instance method erases a specified portion of data.

### Declaration

```
// C#  
public Int64 Erase(Int64 offset, Int64 amount);
```

### Parameters

- *offset*

The offset from which to erase.

- *amount*

The quantity (in bytes) to erase.



**Return Value**

The number of bytes erased.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The *offset* or *amount* parameter is less than 0.

**Remarks**

Replaces the specified *amount* of data with zero-byte fillers.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**IsEqual**

This instance method compares the LOB data referenced by the two `OracleBlobs`.

**Declaration**

```
// C#  
public bool IsEqual(OracleBlob obj);
```

**Parameters**

- *obj*  
An `OracleBlob` object.

**Return Value**

If the current `OracleBlob` and the provided `OracleBlob` refer to the same LOB, returns `true`. Returns `false` otherwise.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

Note that this method can return `true` even if the two `OracleBlob` objects return `false` for `==` or `Equals()` because two different `OracleBlob` instances can refer to the same LOB.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**Read**

Overrides `Stream`

This instance method reads a specified amount of bytes from the ODP.NET LOB instance and populates the `buffer`.

**Declaration**

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
The byte array buffer to be populated.
- *offset*  
The starting offset (in bytes) at which the buffer is populated.
- *count*  
The amount of bytes to read.

**Return Value**

The return value indicates the number of bytes read from the LOB.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* parameter is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than the *buffer.Length*.

**Remarks**

The LOB data is read starting from the position specified by the `Position` property.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class ReadSample
```

```

{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 3 bytes, starting at buffer offset 1
        byte[] writeBuffer = new byte[4] {1, 2, 3, 4};
        blob.Write(writeBuffer, 1, 3);

        // Reset the Position for Read
        blob.Position = 1;

        // Read 2 bytes into buffer starting at buffer offset 1
        byte[] readBuffer = new byte[4];
        int bytesRead = blob.Read(readBuffer, 1, 2);

        // Prints "bytesRead = 2"
        Console.WriteLine("bytesRead = " + bytesRead);

        // Prints "readBuffer = 0340"
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**Search**

This instance method searches for a binary pattern in the current instance of an OracleBlob.

**Declaration**

```
// C#
public Int64 Search(byte[] val, int64 offset, int64 nth);
```

**Parameters**

- *val*

The binary pattern being searched for.

- *offset*  
The 0-based offset (in bytes) starting from which the OracleBlob is searched.
- *nth*  
The specific occurrence (1-based) of the match for which the absolute offset (in bytes) is returned.

**Return Value**

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *val.Length* is greater than 16383.
- The *nth* is greater than or equal to OracleBlob.MaxSize.
- The *offset* is greater than or equal to OracleBlob.MaxSize.

**Remarks**

The limit of the search pattern is 16383 bytes.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 7 bytes, starting at buffer offset 0
        byte[] buffer = new byte[7] {1, 2, 3, 4, 1, 2, 3};
        blob.Write(buffer, 0, 7);

        // Search for the 2nd occurrence of a byte pattern '23'
        // starting at offset 1 in the OracleBlob
        byte[] pattern = new byte[2] {2, 3};
        long posFound = blob.Search(pattern, 1, 2);
    }
}
```

```

// Prints "posFound = 6"
Console.WriteLine("posFound = " + posFound);

blob.Close();
blob.Dispose();

con.Close();
con.Dispose();
}
}

```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

**Seek**

Overrides Stream

This instance method sets the position on the current LOB stream.

**Declaration**

```

// C#
public override Int64 Seek(Int64 offset, SeekOrigin origin);

```

**Parameters**

- *offset*  
A byte offset relative to origin.
- *origin*  
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

**Return Value**

Returns `Int64` for the position.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## SetLength

Overrides Stream

This instance method trims or truncates the BLOB value to the specified length (in bytes).

**Declaration**

```
// C#  
public override void SetLength(Int64 newlen);
```

**Parameters**

- *newlen*

The desired length of the current stream in bytes.

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

*ArgumentOutOfRangeException* - The *newlen* parameter is less than 0.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

## Write

Overrides Stream

This instance method writes the supplied buffer into the OracleBlob.

**Declaration**

```
// C#  
public override void Write(byte[] buffer, int offset, int count);
```

**Parameters**

- *buffer*

The byte array *buffer* that provides the data.

- *offset*

The 0-based offset (in bytes) from which the *buffer* is read.

- *count*

The amount of data (in bytes) that is to be written into the OracleBlob.

## Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than *buffer.Length*.

## Remarks

Destination *offset* in the `OracleBlob` can be specified by the `Position` property.

## Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class WriteSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Set the Position for the Write
        blob.Position = 0;

        // Begin ChunkWrite to improve performance
        // Index updates occur only once after EndChunkWrite
        blob.BeginChunkWrite();

        // Write to the OracleBlob in 5 chunks of 2 bytes each
        byte[] b = new byte[2] {1, 2};
        for(int index = 0; index < 5; index++)
        {
            blob.Write(b, 0, b.Length);
        }
        blob.EndChunkWrite();

        byte[] chunkBuffer = blob.Value;

        // Prints "chunkBuffer = 1212121212"
        Console.WriteLine("chunkBuffer = ");
        for(int index = 0; index < chunkBuffer.Length; index++)
        {
            Console.Write(chunkBuffer[index]);
        }
        Console.WriteLine();
    }
}
```

```
blob.Close();  
blob.Dispose();  
  
con.Close();  
con.Dispose();  
}  
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)



---

## OracleClob Class

An OracleClob is an object that has a reference to CLOB data. It provides methods for performing operations on CLOBs.

---

**Note:** The OracleClob object uses the client side character set when retrieving or writing CLOB data using a .NET Framework byte array.

---

### Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.IO.Stream
            Oracle.DataAccess.Types.OracleClob
```

### Declaration

```
// C#
public sealed class OracleClob : Stream, ICloneable, INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleClobSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 4 chars from writeBuffer, starting at buffer offset 0
        char[] writeBuffer = new char[4] {'a', 'b', 'c', 'd'};
        clob.Write(writeBuffer, 0, 4);

        // Append first 2 chars from writeBuffer {'a', 'b'} to the oracleClob
        clob.Append(writeBuffer, 0, 2);

        // Prints "clob.Length = 12"
        Console.WriteLine("clob.Length = " + clob.Length);

        // Reset the Position for the Read
        clob.Position = 0;
    }
}
```

```
// Read 6 chars into readBuffer, starting at buffer offset 0
char[] readBuffer = new char[6];
int charsRead = clob.Read(readBuffer, 0, 6);

// Prints "charsRead = 6"
Console.WriteLine("charsRead = " + charsRead);

// Prints "readBuffer = abcdab"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a char pattern 'ab'
// starting from char offset 0 in the OracleClob
char[] pattern = new char[2] {'a', 'b'};
long posFound = clob.Search(pattern, 0, 2);

// Prints "posFound = 5"
Console.WriteLine("posFound = " + posFound);

// Erase 4 chars of data starting at char offset 1
// Sets chars to ''
clob.Erase(1, 4);

//Prints "clob.Value = a b"
Console.WriteLine("clob.Value = " + clob.Value);

clob.Close();
clob.Dispose();

con.Close();
con.Dispose();
}
}
```

**Requirements**Namespace: `Oracle.DataAccess.Types`Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Members](#)
- [OracleClob Constructors](#)
- [OracleClob Static Fields](#)
- [OracleClob Static Methods](#)
- [OracleClob Instance Properties](#)
- [OracleClob Instance Methods](#)

## OracleClob Members

OracleClob members are listed in the following tables.

### OracleClob Constructors

OracleClob constructors are listed in [Table 13–19](#).

**Table 13–19 OracleClob Constructors**

Constructor	Description
<a href="#">OracleClob Constructors</a>	Creates an instance of the OracleClob class bound to a temporary CLOB (Overloaded)

### OracleClob Static Fields

OracleClob static fields are listed in [Table 13–20](#).

**Table 13–20 OracleClob Static Fields**

Field	Description
<a href="#">MaxSize</a>	Holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2 <sup>32</sup> - 1) bytes
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleClob instance

### OracleClob Static Methods

OracleClob static methods are listed in [Table 13–21](#).

**Table 13–21 OracleClob Static Methods**

Methods	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleClob Instance Properties

OracleClob instance properties are listed in [Table 13–22](#).

**Table 13–22 OracleClob Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the LOB stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operations can be performed
<a href="#">CanWrite</a>	Indicates whether or not the LOB stream can be written
<a href="#">Connection</a>	Indicates the OracleConnection that is used to retrieve and write CLOB data
<a href="#">IsEmpty</a>	Indicates whether the CLOB is empty or not
<a href="#">IsInChunkWriteMode</a>	Indicates whether or not the CLOB has been opened
<a href="#">IsNCLOB</a>	Indicates whether or not the OracleClob object represents an NCLOB.

**Table 13–22 (Cont.) OracleClob Instance Properties**

Properties	Description
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsTemporary</a>	Indicates whether or not the current instance is bound to a temporary CLOB
<a href="#">Length</a>	Indicates the size of the CLOB data in bytes
<a href="#">OptimumChunkSize</a>	Indicates the minimum number of bytes to retrieve or send from the database during a read or write operation
<a href="#">Position</a>	Indicates the current read or write position in the LOB stream in bytes
<a href="#">Value</a>	Returns the data, starting from the first character in the CLOB or NCLOB, as a string

### OracleClob Instance Methods

The OracleClob instance methods are listed in [Table 13–23](#).

**Table 13–23 OracleClob Instance Methods**

Methods	Description
<a href="#">Append</a>	Appends data to the current OracleClob instance (Overloaded)
<a href="#">BeginChunkWrite</a>	Opens the CLOB
<a href="#">BeginRead</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">BeginWrite</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">Clone</a>	Creates a copy of an OracleClob object
<a href="#">Close</a>	Closes the current stream and releases resources associated with it
<a href="#">Compare</a>	Compares data referenced by the current instance to that of the supplied object
<a href="#">CopyTo</a>	Copies the data to an OracleClob (Overloaded)
<a href="#">CreateObjRef</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Dispose</a>	Releases resources allocated by this object
<a href="#">EndChunkWrite</a>	Closes the CLOB referenced by the current OracleClob instance
<a href="#">EndRead</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">EndWrite</a>	Inherited from <code>System.IO.Stream</code>
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">Erase</a>	Erases the specified amount of data (Overloaded)
<a href="#">Flush</a>	<i>Not supported</i>
<a href="#">GetHashCode</a>	Returns a hash code for the current instance
<a href="#">GetLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">InitializeLifetimeService</a>	Inherited from <code>System.MarshalByRefObject</code>

**Table 13–23 (Cont.) OracleClob Instance Methods**

Methods	Description
<a href="#">IsEqual</a>	Compares the LOB data referenced by two <code>OracleClob</code> s
<a href="#">Read</a>	Reads from the current instance (Overloaded)
<code>ReadByte</code>	Inherited from <code>System.IO.Stream</code>
<a href="#">Search</a>	Searches for a character pattern in the current instance of <code>OracleClob</code> (Overloaded)
<a href="#">Seek</a>	Sets the position in the current LOB stream
<a href="#">SetLength</a>	Trims or truncates the CLOB value
<code>ToString</code>	Inherited from <code>System.Object</code>
<a href="#">Write</a>	Writes the provided buffer into the <code>OracleClob</code> (Overloaded)
<code>WriteByte</code>	Inherited from <code>System.IO.Stream</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)

## OracleClob Constructors

OracleClob constructors create instances of the OracleClob class bound to a temporary CLOB.

### Overload List:

- [OracleClob\(OracleConnection\)](#)

This constructor creates an instance of the OracleClob class bound to a temporary CLOB with an OracleConnection object.

- [OracleClob\(OracleConnection, bool, bool\)](#)

This constructor creates an instance of the OracleClob class that is bound to a temporary CLOB, with an OracleConnection object, a boolean value for caching, and a boolean value for NCLOB.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

### OracleClob(OracleConnection)

This constructor creates an instance of the OracleClob class bound to a temporary CLOB with an OracleConnection object.

### Declaration

```
// C#  
public OracleClob(OracleConnection con);
```

### Parameters

- *con*

The OracleConnection object.

### Exceptions

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

### Remarks

The connection must be opened explicitly by the application. OracleClob does not open the connection implicitly. The temporary CLOB utilizes the provided connection to store CLOB data. Caching is not enabled by default.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## OracleClob(OracleConnection, bool, bool)

This constructor creates an instance of the `OracleClob` class that is bound to a temporary CLOB, with an `OracleConnection` object, a boolean value for caching, and a boolean value for NCLOB.

### Declaration

```
// C#  
public OracleClob(OracleConnection con, bool bCaching, bool bNCLOB);
```

### Parameters

- *con*  
The `OracleConnection` object connection.
- *bCaching*  
A flag that indicates whether or not server-side caching is enabled.
- *bNCLOB*  
A flag that is set to `true` if the instance is a NCLOB or `false` if it is a CLOB.

### Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

The connection must be opened explicitly by the application. `OracleClob` does not open the connection implicitly. The temporary CLOB or NCLOB uses the provided connection to store CLOB data.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## OracleClob Static Fields

OracleClob static fields are listed in [Table 13–24](#).

**Table 13–24 OracleClob Static Fields**

Field	Description
<a href="#">MaxSize</a>	Holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2 <sup>32</sup> - 1) bytes
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleClob instance

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

### MaxSize

The `MaxSize` field holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2<sup>32</sup> - 1) bytes.

**Declaration**

```
// C#  
public static readonly Int64 MaxSize = 4294967295;
```

**Remarks**

This field is useful in code that checks whether or not your operation exceeds the maximum length (in bytes) allowed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

### Null

This static field represents a null value that can be assigned to the value of an OracleClob instance.

**Declaration**

```
// C#  
public static readonly OracleClob Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)



## OracleClob Static Methods

OracleClob static methods are listed in [Table 13–25](#).

**Table 13–25 OracleClob Static Methods**

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## OracleClob Instance Properties

OracleClob instance properties are listed in [Table 13–26](#).

**Table 13–26 OracleClob Instance Properties**

Properties	Description
<a href="#">CanRead</a>	Indicates whether or not the LOB stream can be read
<a href="#">CanSeek</a>	Indicates whether or not forward and backward seek operations can be performed
<a href="#">CanWrite</a>	Indicates whether or not the LOB stream can be written
<a href="#">Connection</a>	Indicates the <code>OracleConnection</code> that is used to retrieve and write CLOB data
<a href="#">IsEmpty</a>	Indicates whether the CLOB is empty or not
<a href="#">IsInChunkWriteMode</a>	Indicates whether or not the CLOB has been opened
<a href="#">IsNCLOB</a>	Indicates whether or not the <code>OracleClob</code> object represents an NCLOB.
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsTemporary</a>	Indicates whether or not the current instance is bound to a temporary CLOB
<a href="#">Length</a>	Indicates the size of the CLOB data in bytes
<a href="#">OptimumChunkSize</a>	Indicates the minimum number of bytes to retrieve or send from the database during a read or write operation
<a href="#">Position</a>	Indicates the current read or write position in the LOB stream in bytes
<a href="#">Value</a>	Returns the data, starting from the first character in the CLOB or NCLOB, as a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

### CanRead

Overrides `Stream`

This instance property indicates whether or not the LOB stream can be read.

**Declaration**

```
// C#
public override bool CanRead{get;}
```

**Property Value**

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**CanSeek**

Overrides Stream

This instance property indicates whether or not forward and backward seek operations can be performed.

**Declaration**

```
// C#  
public override bool CanSeek{get;}
```

**Property Value**

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**CanWrite**

Overrides Stream

This instance property indicates whether or not the LOB object supports writing.

**Declaration**

```
// C#  
public override bool CanWrite{get;}
```

**Property Value**

If the LOB stream can be written, returns `true`; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Connection**

This instance property indicates the `OracleConnection` that is used to retrieve and write CLOB data.

**Declaration**

```
// C#  
public OracleConnection Connection {get;}
```

### Property Value

An `OracleConnection`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## IsEmpty

This instance property indicates whether the CLOB is empty or not.

### Declaration

```
// C#  
public bool IsEmpty {get;}
```

### Property Value

A `bool`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## IsInChunkWriteMode

This instance property indicates whether or not the CLOB has been opened to defer index updates.

### Declaration

```
// C#  
public bool IsInChunkWriteMode{get;}
```

### Property Value

If the CLOB has been opened, returns `true`; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## IsNCLOB

This instance property indicates whether or not the `OracleClob` object represents an NCLOB.

**Declaration**

```
// C#  
public bool IsNCLOB {get;}
```

**Property Value**

A `bool`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**IsNull**

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#  
public bool IsNull{get;}
```

**Property Value**

Returns `true` if the current instance has a null value; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**IsTemporary**

This instance property indicates whether or not the current instance is bound to a temporary CLOB.

**Declaration**

```
// C#  
public bool IsTemporary {get;}
```

**Property Value**

A `bool`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**Length**

Overrides `Stream`

This instance property indicates the size of the CLOB data in bytes.

**Declaration**

```
// C#  
public override Int64 Length {get;}
```

**Property Value**

An `Int64` that indicates the size of the CLOB in bytes.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**OptimumChunkSize**

This instance property indicates the minimum number of bytes to retrieve or send from the database during a read or write operation.

**Declaration**

```
// C#  
public int OptimumChunkSize{get;}
```

**Property Value**

A number representing the minimum bytes to retrieve or send.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**Position**

Overrides `Stream`

This instance property indicates the current read or write position in the LOB stream in bytes.

**Declaration**

```
// C#  
public override Int64 Position{get; set;}
```

**Property Value**

An `Int64` that indicates the read or write position.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## Value

This instance property returns the data, starting from the first character in the CLOB or NCLOB, as a string.

### Declaration

```
// C#  
public string Value{get;}
```

### Property Value

A string.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Value` is less than 0.

### Remarks

The value of `Position` is neither used nor changed by using this property.

The maximum string length that can be returned by this property is 2 GB.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## OracleClob Instance Methods

The OracleClob instance methods are listed in [Table 13-27](#).

**Table 13-27 OracleClob Instance Methods**

Methods	Description
<a href="#">Append</a>	Appends data to the current OracleClob instance (Overloaded)
<a href="#">BeginChunkWrite</a>	Opens the CLOB
BeginRead	Inherited from <code>System.IO.Stream</code>
BeginWrite	Inherited from <code>System.IO.Stream</code>
<a href="#">Clone</a>	Creates a copy of an OracleClob object
<a href="#">Close</a>	Closes the current stream and releases resources associated with it
<a href="#">Compare</a>	Compares data referenced by the current instance to that of the supplied object
<a href="#">CopyTo</a>	Copies the data to an OracleClob (Overloaded)
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">Dispose</a>	Releases resources allocated by this object
<a href="#">EndChunkWrite</a>	Closes the CLOB referenced by the current OracleClob instance
EndRead	Inherited from <code>System.IO.Stream</code>
EndWrite	Inherited from <code>System.IO.Stream</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">Erase</a>	Erases the specified amount of data (Overloaded)
Flush	<i>Not supported</i>
<a href="#">GetHashCode</a>	Returns a hash code for the current instance
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
<a href="#">IsEqual</a>	Compares the LOB data referenced by two OracleClobs
<a href="#">Read</a>	Reads from the current instance (Overloaded)
ReadByte	Inherited from <code>System.IO.Stream</code>
<a href="#">Search</a>	Searches for a character pattern in the current instance of OracleClob (Overloaded)
<a href="#">Seek</a>	Sets the position in the current LOB stream
<a href="#">SetLength</a>	Trims or truncates the CLOB value
ToString	Inherited from <code>System.Object</code>
<a href="#">Write</a>	Writes the provided buffer into the OracleClob (Overloaded)
WriteByte	Inherited from <code>System.IO.Stream</code>



**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**Append**

This instance method appends data to the current `OracleClob` instance.

**Overload List:**

- [Append\(OracleClob\)](#)

This instance method appends the CLOB data referenced by the provided `OracleClob` object to the current `OracleClob` instance.

- [Append\(byte \[ \], int, int\)](#)

This instance method appends data at the end of the CLOB, from the supplied byte array buffer, starting from offset (in bytes) of the supplied byte array buffer.

- [Append\(char \[ \], int, int\)](#)

This instance method appends data from the supplied character array buffer to the end of the current `OracleClob` instance, starting at the offset (in characters) of the supplied character buffer.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**Append(OracleClob)**

This instance method appends the CLOB data referenced by the provided `OracleClob` object to the current `OracleClob` instance.

**Declaration**

```
// C#
public void Append(OracleClob obj);
```

**Parameters**

- *obj*  
An `OracleClob` object.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

**Remarks**

No character set conversions are made.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**Append(byte [ ], int, int)**

This instance method appends data at the end of the CLOB, from the supplied byte array buffer, starting from offset (in bytes) of the supplied byte array buffer.

**Declaration**

```
// C#  
public int Append(byte[] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
An array of bytes, representing a Unicode string.
- *offset*  
The zero-based byte offset in the buffer from which data is read.
- *count*  
The number of bytes to be appended.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - Either the *offset* or the *count* parameter is not even.

**Remarks**

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**Append(char [ ], int, int)**

This instance method appends data from the supplied character array buffer to the end of the current `OracleClob` instance, starting at the offset (in characters) of the supplied character buffer.

## Declaration

```
// C#  
public void Append(char[] buffer, int offset, int count);
```

## Parameters

- *buffer*  
An array of characters.
- *offset*  
The zero-based offset (in characters) in the buffer from which data is read.
- *count*  
The number of characters to be appended.

## Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

## Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class AppendSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleClob clob = new OracleClob(con);  
  
        // Append 2 chars {'d', 'e'} to the OracleClob  
        char[] buffer = new char[3] {'d', 'e', 'f'};  
        clob.Append(buffer, 0, 2);  
  
        // Prints "clob.Value = de"  
        Console.WriteLine("clob.Value = " + clob.Value);  
  
        clob.Close();  
        clob.Dispose();  
  
        con.Close();  
        con.Dispose();  
    }  
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**BeginChunkWrite**

This instance method opens the CLOB.

**Declaration**

```
// C#  
public void BeginChunkWrite();
```

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

**Remarks**

*BeginChunkWrite* does not need to be called before manipulating the CLOB data. This is provided for performance reasons.

After this method is called, write operations do not cause the domain or function-based index on the column to be updated. Index updates occur only once after *EndChunkWrite* is called.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Clone**

This instance method creates a copy of an *OracleClob* object.

**Declaration**

```
// C#  
public object Clone();
```

**Return Value**

An *OracleClob* object.

**Implements**

*ICloneable*

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

## Remarks

The cloned object has the same property values as that of the object being cloned.

## Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CloneSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob1 = new OracleClob(con);

        // Prints "clob1.Position = 0"
        Console.WriteLine("clob1.Position = " + clob1.Position);

        // Set the Position before calling Clone()
        clob1.Position = 1;

        // Clone the OracleClob
        OracleClob clob2 = (OracleClob)clob1.Clone();

        // Prints "clob2.Position = 1"
        Console.WriteLine("clob2.Position = " + clob2.Position);

        clob1.Close();
        clob1.Dispose();

        clob2.Close();
        clob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## Close

Overrides Stream

This instance method closes the current stream and releases resources associated with it.

**Declaration**

```
// C#  
public override void Close();
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Compare**

This instance method compares data referenced by the current instance to that of the supplied object.

**Declaration**

```
// C#  
public int Compare(Int64 src_offset, OracleClob obj, Int64 dst_offset,  
    Int64 amount);
```

**Parameters**

- *src\_offset*  
The comparison starting point (in characters) for the current instance.
- *obj*  
The provided `OracleClob` object.
- *dst\_offset*  
The comparison starting point (in characters) for the provided `OracleClob`.
- *amount*  
The number of characters to compare.

**Return Value**

The method returns a value that is:

- Less than zero: if the data referenced by the current instance is less than that of the supplied instance.
- Zero: if both objects reference the same data.
- Greater than zero: if the data referenced by the current instance is greater than that of the supplied instance.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - Either the *src\_offset*, *dst\_offset*, or *amount* parameter is less than 0.

**Remarks**

The character set of the two `OracleClob` objects being compared should be the same for a meaningful comparison.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**CopyTo**

`CopyTo` copies data from the current instance to the provided `OracleClob` object.

**Overload List:**

- [CopyTo\(OracleClob\)](#)

This instance method copies data from the current instance to the provided `OracleClob` object.
- [CopyTo\(OracleClob, Int64\)](#)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified destination offset.
- [CopyTo\(Int64, OracleClob, Int64, Int64\)](#)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified source offset, destination offset, and character amounts.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

**CopyTo(OracleClob)**

This instance method copies data from the current instance to the provided `OracleClob` object.

**Declaration**

```
// C#  
public Int64 CopyTo(OracleClob obj);
```

**Parameters**

- *obj*

The `OracleClob` object to which the data is copied.

**Return Value**

The return value is the amount copied.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

**Remarks**

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**CopyTo(OracleClob, Int64)**

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified destination offset.

**Declaration**

```
// C#  
public Int64 CopyTo(OracleClob obj, Int64 dst_offset);
```

**Parameters**

- *obj*  
The `OracleClob` object to which the data is copied.
- *dst\_offset*  
The offset (in characters) at which the `OracleClob` object is copied.

**Return Value**

The return value is the amount copied.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst\_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

**Remarks**

If the *dst\_offset* is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the *dst\_offset* is met.



The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

### CopyTo(Int64, OracleClob, Int64, Int64)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified source offset, destination offset, and character amounts.

**Declaration**

```
// C#  
public Int64 CopyTo(Int64 src_offset, OracleClob obj, Int64 dst_offset,  
    Int64 amount);
```

**Parameters**

- *src\_offset*  
The offset (in characters) in the current instance, from which the data is read.
- *obj*  
The `OracleClob` object to which the data is copied.
- *dst\_offset*  
The offset (in characters) at which the `OracleClob` object is copied.
- *amount*  
The amount of data to be copied.

**Return Value**

The return value is the amount copied.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The *src\_offset*, the *dst\_offset*, or the *amount* parameter is less than 0.

**Remarks**

If the *dst\_offset* is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the *dst\_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CopyToSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob1 = new OracleClob(con);
        OracleClob clob2 = new OracleClob(con);

        // Write 4 chars, starting at buffer offset 0
        char[] buffer = new char[4] {'a', 'b', 'c', 'd'};
        clob1.Write(buffer, 0, 4);

        // Copy 2 chars from char 0 of clob1 to char 1 of clob2
        clob1.CopyTo(0, clob2, 1, 2);

        //Prints "clob2.Value = ab"
        Console.WriteLine("clob2.Value = " + clob2.Value);

        clob1.Close();
        clob1.Dispose();

        clob2.Close();
        clob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Dispose**

This instance method releases resources allocated by this object.

**Declaration**

```
public void Dispose();
```

**Implements**

```
IDisposable
```

### Remarks

The object cannot be reused after being disposed. Although some properties can still be accessed, their values cannot be accountable. Since resources are freed, method calls can lead to exceptions.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## EndChunkWrite

This instance method closes the CLOB referenced by the current `OracleClob` instance.

### Declaration

```
// C#  
public void EndChunkWrite();
```

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

Index updates occur immediately if write operation(s) are deferred by the `BeginChunkWrite` method.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## Erase

`Erase` erases part or all data.

### Overload List:

- [Erase\(\)](#)

This instance method erases all data.

- [Erase\(Int64, Int64\)](#)

This instance method replaces the specified amount of data (in characters) starting from the specified `offset` with zero-byte fillers (in characters).

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## Erase()

This instance method erases all data.

### Declaration

```
// C#  
public Int64 Erase();
```

### Return Value

The number of characters erased.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## Erase(Int64, Int64)

This instance method replaces the specified amount of data (in characters) starting from the specified *offset* with zero-byte fillers (in characters).

### Declaration

```
// C#  
public Int64 Erase(Int64 offset, Int64 amount);
```

### Parameters

- *offset*  
The offset.
- *amount*  
The amount of data.

### Return Value

The actual number of characters erased.

### Exceptions

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

*ArgumentOutOfRangeException* - The *offset* or *amount* parameter is less than 0.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## GetHashCode

Overrides *Object*

This method returns a hash code for the current instance.

#### Declaration

```
// C#  
public override int GetHashCode();
```

#### Return Value

An `int` representing a hash code.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## IsEqual

This instance method compares the LOB data referenced by two `OracleClob`s.

#### Declaration

```
// C#  
public bool IsEqual(OracleClob obj);
```

#### Parameters

- *obj*  
An `OracleClob` object.

#### Return Value

Returns `true` if the current `OracleClob` and the provided `OracleClob` refer to the same LOB. Otherwise, returns `false`.

#### Remarks

Note that this method can return `true` even if the two `OracleClob` objects returns `false` for `==` or `Equals()` because two different `OracleClob` instances can refer to the same LOB.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleClob Class](#)
- [OracleClob Members](#)

## Read

`Read` reads a specified amount from the current instance and populates the array buffer.

#### Overload List:

- [Read\(byte \[\], int, int\)](#)

This instance method reads a specified amount of bytes from the current instance and populates the byte array `buffer`.

- [Read\(char \[ \], int, int\)](#)

This instance method reads a specified amount of characters from the current instance and populates the character array buffer.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## Read(byte [ ], int, int)

Overrides `Stream`

This instance method reads a specified amount of bytes from the current instance and populates the byte array `buffer`.

### Declaration

```
// C#  
public override int Read(byte [ ] buffer, int offset, int count);
```

### Parameters

- *buffer*  
The byte array buffer that is populated.
- *offset*  
The offset (in bytes) at which the buffer is populated.
- *count*  
The amount of bytes to be read.

### Return Value

The number of bytes read from the CLOB.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

### Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

The LOB data is read starting from the position specified by the `Position` property, which must also be an even number.

`OracleClob` is free to return fewer bytes than requested, even if the end of the stream has not been reached.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Read(char [ ], int, int)**

This instance method reads a specified amount of characters from the current instance and populates the character array buffer.

**Declaration**

```
// C#  
public int Read(char[ ] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
The character array buffer that is populated.
- *offset*  
The offset (in characters) at which the buffer is populated.
- *count*  
The amount of characters to be read.

**Return Value**

The return value indicates the number of characters read from the CLOB.

**Exceptions**

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

*ArgumentOutOfRangeException* - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than *buffer.Length*.

**Remarks**

Handles all CLOB and NCLOB data as Unicode.

The LOB data is read starting from the position specified by the *Position* property.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class ReadSample
```

```
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 3 chars, starting at buffer offset 1
        char[] writeBuffer = new char[4] {'a', 'b', 'c', 'd'};
        clob.Write(writeBuffer, 1, 3);

        // Reset the Position (in bytes) for Read
        clob.Position = 2;

        // Read 2 chars into buffer starting at buffer offset 1
        char[] readBuffer = new char[4];
        int charsRead = clob.Read(readBuffer, 1, 2);

        // Prints "charsRead = 2"
        Console.WriteLine("charsRead = " + charsRead);

        // Prints "readBuffer = cd "
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        clob.Close();
        clob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## Search

Search searches for a character pattern in the current instance of OracleClob.

**Overload List:**

- [Search\(byte\[\] , Int64, Int64\)](#)

This instance method searches for a character pattern, represented by the byte array, in the current instance of OracleClob.
- [Search\(char\[\] , Int64, Int64\)](#)

This instance method searches for a character pattern in the current instance of OracleClob.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Search(byte[ ], Int64, Int64)**

This instance method searches for a character pattern, represented by the byte array, in the current instance of OracleClob.

**Declaration**

```
// C#  
public int Search(byte[ ] val, Int64 offset, Int64 nth);
```

**Parameters**

- *val*  
A Unicode byte array.
- *offset*  
The 0-based offset (in characters) starting from which the OracleClob is searched.
- *nth*  
The specific occurrence (1-based) of the match for which the absolute offset (in characters) is returned.

**Return Value**

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *nth* is greater than or equal to OracleClob.MaxSize.
- The *offset* is greater than or equal to OracleClob.MaxSize.

**Remarks**

The `byte[ ]` is converted to Unicode before the search is made.

The limit of the search pattern is 16383 bytes.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Search(char[ ], Int64, Int64)**

This instance method searches for a character pattern in the current instance of `OracleClob`.

**Declaration**

```
// C#  
public Int64 Search(char [ ] val, Int64 offset, Int64 nth);
```

**Parameters**

- *val*  
The Unicode string being searched for.
- *offset*  
The 0-based offset (in characters) starting from which the `OracleClob` is searched.
- *nth*  
The specific occurrence (1-based) of the match for which the absolute offset (in characters) is returned.

**Return Value**

Returns the absolute *offset* of the start of the matched pattern (in characters) for the *nth* occurrence of the match. Otherwise, 0 is returned.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *val.Length* doubled is greater than 16383.
- The *nth* is greater than or equal to `OracleClob.MaxSize`.
- The *offset* is greater than or equal to `OracleClob.MaxSize`.

**Remarks**

The limit of the search pattern is 16383 bytes.

**Example**

```
// C#
```

```

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 7 chars, starting at buffer offset 0
        char[] buffer = new char[7] {'a', 'b', 'c', 'd', 'a', 'b', 'c'};
        clob.Write(buffer, 0, 7);

        // Search for the 2nd occurrence of a char pattern 'bc'
        // starting at offset 1 in the OracleBlob
        char[] pattern = new char[2] {'b', 'c'};
        long posFound = clob.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);

        clob.Close();
        clob.Dispose();

        con.Close();
        con.Dispose();
    }
}

```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Seek**

Overrides Stream

This instance method sets the position on the current LOB stream.

**Declaration**

```

// C#
public override Int64 Seek(Int64 offset, SeekOrigin origin);

```

**Parameters**

- *offset*  
A byte offset relative to origin.
- *origin*  
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

**Return Value**

Returns an `Int64` that indicates the position.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

**Remarks**

If *offset* is negative, the new position precedes the position specified by *origin* by the number of characters specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of characters specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**SetLength**

Overrides `Stream`

This instance method trims or truncates the CLOB value to the specified length (in characters).

**Declaration**

```
// C#  
public override void SetLength(Int64 newlen);
```

**Parameters**

- *newlen*

The desired length of the current stream in characters.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The *newlen* parameter is greater than 0.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Write**

This instance method writes data from the provided array buffer into the OracleClob.

**Overload List:**

- [Write\(byte\[ \], int, int\)](#)

This instance method writes data from the provided byte array buffer into the OracleClob.

- [Write\(char\[ \], int, int\)](#)

This instance method writes data from the provided character array buffer into the OracleClob.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

**Write(byte[ ], int, int)**

Overrides Stream

This instance method writes data from the provided byte array buffer into the OracleClob.

**Declaration**

```
// C#  
public override void Write(byte[ ] buffer, int offset, int count);
```

**Parameters**

- *buffer*  
The byte array buffer that represents a Unicode string.
- *offset*  
The offset (in bytes) from which the *buffer* is read.
- *count*  
The amount of data (in bytes) from the buffer to be written into the OracleClob.

**Exceptions**

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

*ArgumentOutOfRangeException* - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than the *buffer.Length*.
- The *offset*, the *count*, or the *Position* is not even.

### Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

The LOB data is read starting from the position specified by the *Position* property. The *Position* property must be an even number.

If necessary, proper data conversion is carried out from the client character set to the database character set.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

## Write(char[ ], int, int)

This instance method writes data from the provided character array buffer into the *OracleClob*.

### Declaration

```
// C#  
public void Write(char[ ] buffer, int offset, int count);
```

### Parameters

- *buffer*  
The character array buffer that is written to the *OracleClob*.
- *offset*  
The offset (in characters) from which the *buffer* is read.
- *count*  
The amount (in characters) from the buffer that is to be written into the *OracleClob*.

### Exceptions

*ObjectDisposedException* - The object is already disposed.

*InvalidOperationException* - The *OracleConnection* is not open or has been closed during the lifetime of the object.

*ArgumentOutOfRangeException* - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.

- The *offset* and the *count* together are greater than *buffer.Length*.
- The *Position* is not even.

### Remarks

Handles all CLOB and NCLOB data as Unicode.

The LOB data is read starting from the position specified by the *Position* property.

If necessary, proper data conversion is carried out from the client character set to the database character set.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class WriteSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Set the Position for the Write;
        clob.Position = 0;

        // Begin ChunkWrite to improve performance
        // Index updates occur only once after EndChunkWrite
        clob.BeginChunkWrite();

        // Write to the OracleClob in 5 chunks of 2 chars each
        char[] c = new char[2] {'a', 'b'};
        for (int index = 0; index < 5; index++)
        {
            clob.Write(c, 0, c.Length);
        }
        clob.EndChunkWrite();

        // Prints "clob.Value = ababababab"
        Console.WriteLine("clob.Value = " + clob.Value);

        clob.Close();
        clob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleClob Class](#)
- [OracleClob Members](#)



---

## OracleRefCursor Class

An OracleRefCursor object represents an Oracle REF CURSOR.

### Class Inheritance

```
System.Object
    System.MarshalRefByObject
        Oracle.DataAccess.Types.OracleRefCursor
```

### Declaration

```
// C#
public sealed class OracleRefCursor : MarshalByRefObject, IDisposable, INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

To minimize the number of open server cursors, OracleRefReader objects should be explicitly disposed.

### Example

```
// Database Setup
/*
connect scott/tiger@oracle
CREATE OR REPLACE FUNCTION MyFunc(refcur_out OUT SYS_REFCURSOR)
    RETURN SYS_REFCURSOR IS refcur_ret SYS_REFCURSOR;
BEGIN
    OPEN refcur_ret FOR SELECT * FROM EMP;
    OPEN refcur_out FOR SELECT * FROM DEPT;
    RETURN refcur_ret;
END MyFunc;
/
*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleRefCursorSample
{
    static void Main()
    {
        // Example demonstrates how to use REF CURSORS returned from
        // PL/SQL Stored Procedures or Functions
        // Create the PL/SQL Function MyFunc as defined previously

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
```

```
// Create an OracleCommand
OracleCommand cmd = new OracleCommand("MyFunc", con);
cmd.CommandType = CommandType.StoredProcedure;

// Bind the parameters
// p1 is the RETURN REF CURSOR bound to SELECT * FROM EMP;
OracleParameter p1 =
    cmd.Parameters.Add("refcur_ret", OracleDbType.RefCursor);
p1.Direction = ParameterDirection.ReturnValue;

// p2 is the OUT REF CURSOR bound to SELECT * FROM DEPT
OracleParameter p2 =
    cmd.Parameters.Add("refcur_out", OracleDbType.RefCursor);
p2.Direction = ParameterDirection.Output;

// Execute the command
cmd.ExecuteNonQuery();

// Construct an OracleDataReader from the REF CURSOR
OracleDataReader reader1 = ((OracleRefCursor)p1.Value).GetDataReader();

// Prints "reader1.GetName(0) = EMPNO"
Console.WriteLine("reader1.GetName(0) = " + reader1.GetName(0));

// Construct an OracleDataReader from the REF CURSOR
OracleDataReader reader2 = ((OracleRefCursor)p2.Value).GetDataReader();

// Prints "reader2.GetName(0) = DEPTNO"
Console.WriteLine("reader2.GetName(0) = " + reader2.GetName(0));

reader1.Close();
reader1.Dispose();

reader2.Close();
reader2.Dispose();

p1.Dispose();
p2.Dispose();

cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRefCursor Members](#)
- [OracleRefCursor Static Methods](#)
- [OracleRefCursor Properties](#)
- [OracleRefCursor Instance Methods](#)

## OracleRefCursor Members

OracleRefCursor members are listed in the following tables.

### OracleRefCursor Static Methods

OracleRefCursor static methods are listed in [Table 13–28](#).

**Table 13–28 OracleRefCursor Static Methods**

Methods	Description
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)

### OracleRefCursor Properties

OracleRefCursor properties are listed in [Table 13–29](#).

**Table 13–29 OracleRefCursor Properties**

Properties	Description
<a href="#">Connection</a>	A reference to the <code>OracleConnection</code> used to fetch the REF CURSOR data
<a href="#">FetchSize</a>	Specifies the size that the <code>OracleDataReader</code> internal cache needs to store result set data
<a href="#">RowSize</a>	Specifies the amount of memory the <code>OracleRefcursor</code> internal cache needs to store one row of data

### OracleRefCursor Instance Methods

OracleRefCursor instance methods are listed in [Table 13–30](#).

**Table 13–30 OracleRefCursor Instance Methods**

Methods	Description
<a href="#">Dispose</a>	Disposes the resources allocated by the <code>OracleRefCursor</code> object
<a href="#">Equals</a>	Inherited from <code>System.Object</code> (Overloaded)
<a href="#">GetDataReader</a>	Returns an <code>OracleDataReader</code> object for the REF CURSOR
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Inherited from <code>System.Object</code>

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)

## OracleRefCursor Static Methods

OracleRefCursor static methods are listed in [Table 13–31](#).

**Table 13–31 OracleRefCursor Static Methods**

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

## OracleRefCursor Properties

OracleRefCursor properties are listed in [Table 13–32](#).

**Table 13–32 OracleRefCursor Properties**

Properties	Description
<a href="#">Connection</a>	A reference to the <code>OracleConnection</code> used to fetch the REF CURSOR data
<a href="#">FetchSize</a>	Specifies the size that the <code>OracleDataReader</code> internal cache needs to store result set data
<a href="#">RowSize</a>	Specifies the amount of memory the <code>OracleRefcursor</code> internal cache needs to store one row of data

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

### Connection

This property refers to the `OracleConnection` used to fetch the REF CURSOR data.

**Declaration**

```
// C#
public OracleConnection Connection {get;}
```

**Property Value**

An `OracleConnection`.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

This property is bound to a REF CURSOR once it is set. After the `OracleRefCursor` object is created by the constructor, this property is initially null. An `OracleRefCursor` object can be bound to a REF CURSOR after a command execution.

If the connection is closed or returned to the connection pool, the `OracleRefCursor` is placed in an uninitialized state and no operation can be carried out from it. However, the uninitialized `OracleRefCursor` can be reassigned to another REF CURSOR.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

## FetchSize

This property specifies the size that the `OracleDataReader` internal cache needs to store result set data.

### Declaration

```
// C#  
public long FetchSize {get; set;}
```

### Property Value

A `long` that specifies the size (in bytes) of the `OracleRefCursor` internal cache.

### Exceptions

`ArgumentException` - The `FetchSize` value specified is invalid.

### Remarks

Default = 131072.

The `FetchSize` property value is inherited by the `OracleCommand` that created the `OracleRefCursor` object. The `FetchSize` property on the `OracleDataReader` object determines the amount of data the `OracleRefCursor` fetches into its internal cache for each database round-trip.

This property is useful if the `OracleRefCursor` is explicitly used to fill the `DataSet` or `DataTable` through the `OracleDataAdapter`, because it can provide control on how the data of the `REF CURSOR` is fetched.

If an `OracleDataReader` object is created from the `OracleRefCursor`, the resulting `OracleDataReader` object inherits the `FetchSize` value of the `OracleDataReader` object. However, the inherited value can be overridden, if it is set before the first invocation of the `OracleDataReader` `Read` method for the given result set, by setting the `OracleDataReader` `FetchSize` property.

The `RowSize` and `FetchSize` properties handle `UDT` and `XMLType` data differently than other scalar data types. Because only a reference to the `UDT` and `XMLType` data is stored in the `ODP.NET`'s internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the `UDT` and `XMLType` data. Thus, applications can inadvertently fetch a large number of `UDT` or `XMLType` instances from the database in a single database round-trip. This is because the actual size of `UDT` and `XMLType` data does not count against the `FetchSize`, and it would require numerous `UDT` and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching `UDT` or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of `UDT` and `XMLType` instances that are to be fetched, rather than the amount of the actual `UDT` and `XMLType` data to be fetched.

NOTE: For `LOB` and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each `LOB` in the select list.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

## RowSize

This property specifies the amount of memory the `OracleRefcursor` internal cache needs to store one row of data.

### Declaration

```
// C#  
public long RowSize {get;}
```

### Property Value

A `long` that indicates the amount of memory (in bytes) that an `OracleRefcursor` needs to store one row of data for the executed query.

### Remarks

The `RowSize` property is set to a nonzero value when the `OracleRefcursor` object is created. This property can be used at design time or dynamically during run time, to set the `FetchSize`, based on number of rows. For example, to enable the `OracleRefcursor` to fetch  $N$  rows for each database round-trip, the `OracleRefcursor FetchSize` property can be set dynamically to  $\text{RowSize} * N$ . Note that for the `FetchSize` to take effect appropriately, it must be set before the it is used to fill the `DataSet/DataTable` using `OracleDataAdapter`.

If an `OracleDataReader` is obtained from the `OracleRefCursor` through the `GetDataReader` method, the resulting `OracleDataReader` will have its `FetchSize` property set to the `FetchSize` value of the `OracleRefCursor`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)



## OracleRefCursor Instance Methods

OracleRefCursor instance methods are listed in [Table 13–33](#).

**Table 13–33 OracleRefCursor Instance Methods**

Methods	Description
<a href="#">Dispose</a>	Disposes the resources allocated by the OracleRefCursor object
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)
<a href="#">GetDataReader</a>	Returns an OracleDataReader object for the REF CURSOR
<a href="#">GetHashCode</a>	Inherited from System.Object
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">ToString</a>	Inherited from System.Object

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

## Dispose

This instance method disposes of the resources allocated by the OracleRefCursor object.

### Declaration

```
// C#
public void Dispose();
```

### Implements

IDisposable

### Remarks

The object cannot be reused after being disposed.

Once `Dispose()` is called, the object of OracleRefCursor is in an uninitialized state. Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls can lead to exceptions.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

## GetDataReader

This instance method returns an OracleDataReader object for the REF CURSOR.

### Declaration

```
// C#
```

```
public OracleDataReader GetDataReader();
```

**Return Value**

OracleDataReader

**Remarks**

Using the `OracleDataReader`, rows can be fetched from the `REF CURSOR`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

---

---

## Oracle Data Provider for .NET Types Structures

This chapter describes the ODP.NET Types structures.

This chapter contains these topics:

- [OracleBinary Structure](#)
- [OracleDate Structure](#)
- [OracleDecimal Structure](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalYM Structure](#)
- [OracleString Structure](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampTZ Structure](#)
- [INullable Interface](#)

## OracleBinary Structure

The `OracleBinary` structure represents a variable-length stream of binary data to be stored in or retrieved from a database.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleBinary`

### Declaration

```
// ADO.NET 2.0: C#  
public struct OracleBinary : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class OracleBinarySample  
{  
    static void Main(string[] args)  
    {  
        // Initialize the OracleBinary structures  
        OracleBinary binary1= new OracleBinary(new byte[] {1,2,3,4,5});  
        OracleBinary binary2 = new OracleBinary(new byte[] {1,2,3});  
        OracleBinary binary3 = new OracleBinary(new byte[] {4,5});  
        OracleBinary binary4 = binary2 + binary3;  
  
        // Compare binary1 and binary4; they're equal  
        if (binary1 == binary4)  
            Console.WriteLine("The two OracleBinary structs are equal");  
        else  
            Console.WriteLine("The two OracleBinary structs are different");  
    }  
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Members](#)
- [OracleBinary Constructor](#)
- [OracleBinary Static Fields](#)
- [OracleBinary Static Methods](#)
- [OracleBinary Static Operators](#)
- [OracleBinary Static Type Conversion Operators](#)
- [OracleBinary Properties](#)
- [OracleBinary Instance Methods](#)

## OracleBinary Members

OracleBinary members are listed in the following tables:

### OracleBinary Constructors

OracleBinary constructors are listed in [Table 14-1](#)

**Table 14-1 OracleBinary Constructors**

Constructor	Description
<a href="#">OracleBinary Constructor</a>	Instantiates a new instance of OracleBinary structure

### OracleBinary Static Fields

The OracleBinary static fields are listed in [Table 14-2](#).

**Table 14-2 OracleBinary Static Fields**

Field	Description
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleBinary structure

### OracleBinary Static Methods

The OracleBinary static methods are listed in [Table 14-3](#).

**Table 14-3 OracleBinary Static Methods**

Methods	Description
<a href="#">Concat</a>	Returns the concatenation of two OracleBinary structures
<a href="#">Equals</a>	Determines if two OracleBinary values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two OracleBinary values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleBinary values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleBinary values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleBinary values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleBinary values are not equal

### OracleBinary Static Operators

The OracleBinary static operators are listed in [Table 14-4](#).

**Table 14-4 OracleBinary Static Operators**

Operator	Description
<a href="#">operator +</a>	Concatenates two OracleBinary values
<a href="#">operator ==</a>	Determines if two OracleBinary values are equal

**Table 14–4 (Cont.) OracleBinary Static Operators**

Operator	Description
<code>operator &gt;</code>	Determines if the first of two <code>OracleBinary</code> values is greater than the second
<code>operator &gt;=</code>	Determines if the first of two <code>OracleBinary</code> values is greater than or equal to the second
<code>operator !=</code>	Determines if two <code>OracleBinary</code> values are not equal
<code>operator &lt;</code>	Determines if the first of two <code>OracleBinary</code> value is less than the second
<code>operator &lt;=</code>	Determines if the first of two <code>OracleBinary</code> value is less than or equal to the second

### OracleBinary Static Type Conversion Operators

The `OracleBinary` static type conversion operators are listed in [Table 14-5](#).

**Table 14–5 OracleBinary Static Type Conversion Operators**

Operator	Description
<code>explicit operator byte[]</code>	Converts an instance value to a byte array
<code>implicit operator OracleBinary</code>	Converts an instance value to an <code>OracleBinary</code> structure

### OracleBinary Properties

The `OracleBinary` properties are listed in [Table 14-6](#).

**Table 14–6 OracleBinary Properties**

Properties	Description
<code>IsNull</code>	Indicates whether or not the current instance has a null value
<code>Item</code>	Obtains the particular <code>byte</code> in an <code>OracleBinary</code> structure using an index
<code>Length</code>	Returns the length of the binary data
<code>Value</code>	Returns the binary data that is stored in an <code>OracleBinary</code> structure

### OracleBinary Instance Methods

The `OracleBinary` instance methods are listed in [Table 14-7](#).

**Table 14–7 OracleBinary Instance Methods**

Methods	Description
<code>CompareTo</code>	Compares the current instance to an object and returns an integer that represents their relative values
<code>Equals</code>	Determines if two objects contain the same binary data (Overloaded)
<code>GetHashCode</code>	Returns a hash code for the current instance
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Converts the current <code>OracleBinary</code> structure to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)



## OracleBinary Constructor

The `OracleBinary` constructor instantiates a new instance of the `OracleBinary` structure and sets its value to the provided array of bytes.

### Declaration

```
// C#  
public OracleBinary(byte[ ] bytes);
```

### Parameters

- *bytes*

A byte array.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## OracleBinary Static Fields

The `OracleBinary` static fields are listed in [Table 14–8](#).

**Table 14–8** *OracleBinary Static Fields*

Field	Description
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the <code>OracleBinary</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### Null

This static field represents a null value that can be assigned to an instance of the `OracleBinary` structure.

**Declaration**

```
// C#  
public static readonly OracleBinary Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## OracleBinary Static Methods

The `OracleBinary` static methods are listed in [Table 14-9](#).

**Table 14-9 OracleBinary Static Methods**

Methods	Description
<a href="#">Concat</a>	Returns the concatenation of two <code>OracleBinary</code> structures
<a href="#">Equals</a>	Determines if two <code>OracleBinary</code> values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two <code>OracleBinary</code> values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two <code>OracleBinary</code> values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two <code>OracleBinary</code> values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two <code>OracleBinary</code> values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two <code>OracleBinary</code> values are not equal

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## Concat

This method returns the concatenation of two `OracleBinary` structures.

### Declaration

```
// C#
public static OracleBinary Concat(OracleBinary value1, OracleBinary value2);
```

### Parameters

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

### Return Value

An `OracleBinary`.

### Remarks

If either argument has a null value, the returned `OracleBinary` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## Equals

This method determines if two `OracleBinary` values are equal.

**Declaration**

```
// C#  
public static bool Equals(OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if two `OracleBinary` values are equal; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## GreaterThan

This method determines whether or not the first of two `OracleBinary` values is greater than the second.

**Declaration**

```
// C#  
public static bool GreaterThan(OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

### Return Value

Returns `true` if the first of two `OracleBinary` values is greater than the second; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

### Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class GreaterThanSample  
{  
    static void Main(string[] args)  
    {  
        OracleBinary binary1 = OracleBinary.Null;  
        OracleBinary binary2 = new OracleBinary(new byte[] {1});  
  
        // Compare two OracleBinary structs; binary1 < binary2  
        if (OracleBinary.GreaterThan(binary1, binary2))  
            Console.WriteLine("binary1 > binary2");  
        else  
            Console.WriteLine("binary1 < binary2");  
    }  
}
```

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## GreaterThanOrEqual

This method determines whether or not the first of two `OracleBinary` values is greater than or equal to the second.

### Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleBinary value1, OracleBinary value2);
```

### Parameters

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if the first of two `OracleBinary` values is greater than or equal to the second; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**LessThan**

This method determines whether or not the first of two `OracleBinary` values is less than the second.

**Declaration**

```
// C#  
public static bool LessThan(OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if the first of two `OracleBinary` values is less than the second; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## LessThanOrEqual

This method determines whether or not the first of two `OracleBinary` values is less than or equal to the second.

### Declaration

```
// C#  
public static bool LessThanOrEqual(OracleBinary value1, OracleBinary value2);
```

### Parameters

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

### Return Value

Returns `true` if the first of two `OracleBinary` values is less than or equal to the second; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## NotEquals

This method determines whether or not two `OracleBinary` values are not equal.

### Declaration

```
// C#  
public static bool NotEquals(OracleBinary value1, OracleBinary value2);
```

### Parameters

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

### Return Value

Returns `true` if two `OracleBinary` values are not equal; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)



## OracleBinary Static Operators

The OracleBinary static operators are listed in [Table 14–10](#).

**Table 14–10 OracleBinary Static Operators**

Operator	Description
<a href="#">operator +</a>	Concatenates two OracleBinary values
<a href="#">operator ==</a>	Determines if two OracleBinary values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleBinary values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleBinary values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if two OracleBinary values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two OracleBinary value is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two OracleBinary value is less than or equal to the second

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### operator +

This method concatenates two OracleBinary values.

#### Declaration

```
// C#
public static OracleBinary operator + (OracleBinary value1, OracleBinary value2);
```

#### Parameters

- *value1*  
The first OracleBinary.
- *value2*  
The second OracleBinary.

#### Return Value

OracleBinary

#### Remarks

If either argument has a null value, the returned OracleBinary structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**operator ==**

This method determines if two `OracleBinary` values are equal.

**Declaration**

```
// C#  
public static bool operator == (OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if they are the same; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**operator >**

This method determines if the first of two `OracleBinary` values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if the first of two `OracleBinary` values is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**Example**

```
// C#
using System;
using Oracle.DataAccess.Types;

class OperatorSample
{
    static void Main(string[] args)
    {
        OracleBinary binary1 = OracleBinary.Null;
        OracleBinary binary2 = new OracleBinary(new byte[] {1});

        // Compare two OracleBinary structs; binary1 < binary2
        if (binary1 > binary2)
            Console.WriteLine("binary1 > binary2");
        else
            Console.WriteLine("binary1 < binary2");
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**operator >=**

This method determines if the first of two `OracleBinary` values is greater than or equal to the second.

**Declaration**

```
// C#
public static bool operator >= (OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if the first of two `OracleBinary` values is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**operator !=**

This method determines if two `OracleBinary` values are not equal.

**Declaration**

```
// C#  
public static bool operator != (OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*  
The first `OracleBinary`.
- *value2*  
The second `OracleBinary`.

**Return Value**

Returns `true` if the two `OracleBinary` values are not equal; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**operator <**

This method determines if the first of two `OracleBinary` values is less than the second.

**Declaration**

```
// C#  
public static bool operator < ( OracleBinary value1, OracleBinary value2);
```

**Parameters**

- *value1*

The first `OracleBinary`.

- *value2*

The second `OracleBinary`.

### Return Value

Returns `true` if the first of two `OracleBinary` values is less than the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## operator <=

This method determines if the first of two `OracleBinary` values is less than or equal to the second.

### Declaration

```
// C#
public static bool operator <= (OracleBinary value1, OracleBinary value2);
```

### Parameters

- *value1*

The first `OracleBinary`.

- *value2*

The second `OracleBinary`.

### Return Value

Returns `true` if the first of two `OracleBinary` values is less than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## OracleBinary Static Type Conversion Operators

The `OracleBinary` static type conversion operators are listed in [Table 14–11](#).

**Table 14–11 OracleBinary Static Type Conversion Operators**

Operator	Description
<a href="#">explicit operator byte[ ]</a>	Converts an instance value to a byte array
<a href="#">implicit operator OracleBinary</a>	Converts an instance value to an <code>OracleBinary</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### explicit operator byte[ ]

This method converts an `OracleBinary` value to a byte array.

**Declaration**

```
// C#
public static explicit operator byte[ ] (OracleBinary val);
```

**Parameters**

- *val*  
An `OracleBinary`.

**Return Value**

A byte array.

**Exceptions**

`OracleNullValueException` - The `OracleBinary` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### implicit operator OracleBinary

This method converts a byte array to an `OracleBinary` structure.

**Declaration**

```
// C#
public static implicit operator OracleBinary(byte[ ] bytes);
```

**Parameters**

- *bytes*

A byte array.

**Return Value**

OracleBinary

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)



## OracleBinary Properties

The `OracleBinary` properties are listed in [Table 14–12](#).

**Table 14–12 OracleBinary Properties**

Properties	Description
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Item</a>	Obtains the particular <code>byte</code> in an <code>OracleBinary</code> structure using an index
<a href="#">Length</a>	Returns the length of the binary data
<a href="#">Value</a>	Returns the binary data that is stored in an <code>OracleBinary</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### IsNull

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#
public bool IsNull {get;}
```

**Property Value**

Returns `true` if the current instance has a null value; otherwise returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### Item

This property obtains the particular `byte` in an `OracleBinary` structure using an index.

**Declaration**

```
// C#
public byte this[int index] {get;}
```

**Property Value**

A `byte` in the specified index.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Types;

class ItemSample
{
    static void Main(string[] args)
    {
        OracleBinary binary = new OracleBinary(new byte[] {1,2,3,4});

        // Prints the value 4
        Console.WriteLine(binary.Length - 1);
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## Length

This property returns the length of the binary data.

**Declaration**

```
// C#
public int length {get;}
```

**Property Value**

Length of the binary data.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Types;

class LengthSample
{
    static void Main(string[] args)
    {
        OracleBinary binary = new OracleBinary(new byte[] {1,2,3,4});

        // Prints the value 4
        Console.WriteLine(binary.Length);
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**Value**

This property returns the binary data that is stored in the `OracleBinary` structure.

**Declaration**

```
// C#  
public byte[] Value {get;}
```

**Property Value**

Binary data.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

## OracleBinary Instance Methods

The `OracleBinary` instance methods are listed in [Table 14–13](#).

**Table 14–13 OracleBinary Instance Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current instance to an object and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines if two objects contain the same binary data (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the current instance
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Converts the current <code>OracleBinary</code> structure to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

### CompareTo

This method compares the current instance to an object and returns an integer that represents their relative values

**Declaration**

```
// C#
public int CompareTo(object obj);
```

**Parameters**

- *obj*  
The object being compared.

**Return Value**

The method returns a number that is:

- Less than zero: if the current `OracleBinary` instance value is less than *obj*.
- Zero: if the current `OracleBinary` instance and *obj* values have the same binary data.
- Greater than zero: if the current `OracleBinary` instance value is greater than *obj*.

**Implements**

`Comparable`

**Exceptions**

`ArgumentException` - The parameter is not of type `OracleBinary`.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleBinary`s. For example, comparing an `OracleBinary` instance with an `OracleTimeStamp` instance is not allowed. When an `OracleBinary` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**Example**

```
// C#
using System;
using Oracle.DataAccess.Types;

class CompareToSample
{
    static void Main(string[] args)
    {
        OracleBinary binary1 = new OracleBinary(new byte[] {1,2,3});
        OracleBinary binary2 = new OracleBinary(new byte[] {1,2,3,4});

        // Compare
        if (binary1.CompareTo(binary2) == 0)
            Console.WriteLine("binary1 is the same as binary2");
        else
            Console.WriteLine("binary1 is different from binary2");
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**Equals**

This method determines whether or not an object is an instance of `OracleBinary`, and has the same binary data as the current instance.

**Declaration**

```
// C#
public override bool Equals(object obj);
```

**Parameters**

- *obj*  
The object being compared.

**Return Value**

Returns `true` if *obj* is an instance of `OracleBinary`, and has the same binary data as the current instance; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**GetHashCode**

Overrides `Object`

This method returns a hash code for the `OracleBinary` instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

An `int` that represents the hash.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

**ToString**

Overrides `Object`

This method converts an `OracleBinary` instance to a string instance.

**Declaration**

```
// C#  
public override string ToString();
```

**Return Value**

`string`

**Remarks**

If the current `OracleBinary` instance has a null value, the returned string "null".

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

---

## OracleDate Structure

The `OracleDate` structure represents the Oracle `DATE` data type to be stored in or retrieved from a database. Each `OracleDate` stores the following information: year, month, day, hour, minute, and second.

### Class Inheritance

```
System.Object
    System.ValueType
        Oracle.DataAccess.Types.OracleDate
```

### Declaration

```
// ADO.NET 2.0: C#
public struct OracleDate : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Initialize the dates to the lower and upper boundaries
        OracleDate date1 = OracleDate.MinValue;
        OracleDate date2 = OracleDate.MaxValue;
        OracleDate date3 = new OracleDate(DateTime.MinValue);
        OracleDate date4 = new OracleDate(DateTime.MaxValue);

        // Set the thread's DateFormat for output
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "DD-MON-YYYY BC";
        OracleGlobalization.SetThreadInfo(info);

        // Print the lower and upper boundaries
        Console.WriteLine("OracleDate ranges from\n{0}\nto\n{1}\n",
            date1, date2);
        Console.WriteLine(".NET DateTime ranges from\n{0}\nto\n{1}\n",
            date3, date4);
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Members](#)
- [OracleDate Constructors](#)
- [OracleDate Static Fields](#)
- [OracleDate Static Methods](#)
- [OracleDate Static Operators](#)
- [OracleDate Static Type Conversions](#)
- [OracleDate Properties](#)
- [OracleDate Methods](#)



## OracleDate Members

OracleDate members are listed in the following tables:

### OracleDate Constructors

OracleDate constructors are listed in [Table 14-14](#)

**Table 14-14 OracleDate Constructors**

Constructor	Description
<a href="#">OracleDate Constructors</a>	Instantiates a new instance of OracleDate structure (Overloaded)

### OracleDate Static Fields

The OracleDate static fields are listed in [Table 14-15](#).

**Table 14-15 OracleDate Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleDate structure, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleDate structure instance

### OracleDate Static Methods

The OracleDate static methods are listed in [Table 14-16](#).

**Table 14-16 OracleDate Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleDate values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two OracleDate values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleDate values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleDate values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleDate values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleDate values are not equal
<a href="#">GetSysDate</a>	Returns an OracleDate structure that represents the current date and time
<a href="#">Parse</a>	Returns an OracleDate structure and sets its value using a string

### OracleDate Static Operators

The OracleDate static operators are listed in [Table 14-17](#).

**Table 14–17 OracleDate Static Operators**

Operator	Description
<code>operator ==</code>	Determines if two <code>OracleDate</code> values are the same
<code>operator &gt;</code>	Determines if the first of two <code>OracleDate</code> values is greater than the second
<code>operator &gt;=</code>	Determines if the first of two <code>OracleDate</code> values is greater than or equal to the second
<code>operator !=</code>	Determines if the two <code>OracleDate</code> values are not equal
<code>operator &lt;</code>	Determines if the first of two <code>OracleDate</code> values is less than the second
<code>operator &lt;=</code>	Determines if the first of two <code>OracleDate</code> values is less than or equal to the second

### OracleDate Static Type Conversions

The `OracleDate` static type conversions are listed in [Table 14–18](#).

**Table 14–18 OracleDate Static Type Conversions**

Operator	Description
<code>explicit operator DateTime</code>	Converts a structure to a <code>DateTime</code> structure
<code>explicit operator OracleDate</code>	Converts a structure to an <code>OracleDate</code> structure (Overloaded)

### OracleDate Properties

The `OracleDate` properties are listed in [Table 14–19](#).

**Table 14–19 OracleDate Properties**

Properties	Description
<code>BinData</code>	Gets an array of bytes that represents an Oracle <code>DATE</code> in Oracle internal format
<code>Day</code>	Gets the day component of an <code>OracleDate</code> method
<code>IsNull</code>	Indicates whether or not the current instance has a null value
<code>Hour</code>	Gets the hour component of an <code>OracleDate</code>
<code>Minute</code>	Gets the minute component of an <code>OracleDate</code>
<code>Month</code>	Gets the month component of an <code>OracleDate</code>
<code>Second</code>	Gets the second component of an <code>OracleDate</code>
<code>Value</code>	Gets the date and time that is stored in the <code>OracleDate</code> structure
<code>Year</code>	Gets the year component of an <code>OracleDate</code>

### OracleDate Methods

The `OracleDate` methods are listed in [Table 14–20](#).

**Table 14–20 OracleDate Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current <code>OracleDate</code> instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleDate</code> instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleDate</code> instance
<a href="#">GetDaysBetween</a>	Calculates the number of days between the current <code>OracleDate</code> instance and an <code>OracleDate</code> structure
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToOracleTimeStamp</a>	Converts the current <code>OracleDate</code> structure to an <code>OracleTimeStamp</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleDate</code> structure to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)

## OracleDate Constructors

The `OracleDate` constructors instantiates a new instance of the `OracleDate` structure.

### Overload List:

- [OracleDate\(DateTime\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleDate\(string\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value using the supplied string.
- [OracleDate\(int, int, int\)](#)

This constructor creates a new instance of the `OracleDate` structure and set its value for date using the supplied year, month, and day.
- [OracleDate\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleDate` structure and set its value for time using the supplied year, month, day, hour, minute, and second.
- [OracleDate\(byte \[ \]\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value to the provided byte array, which is in the internal Oracle `DATE` format.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

### OracleDate(DateTime)

This constructor creates a new instance of the `OracleDate` structure and sets its value for date and time using the supplied `DateTime` value.

### Declaration

```
// C#  
public OracleDate (DateTime dt);
```

### Parameters

- *dt*

The provided `DateTime` value.

### Remarks

The `OracleDate` structure only supports up to a second precision. The time value in the provided `DateTime` structure that has a precision smaller than second is ignored.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

**OracleDate(string)**

This constructor creates a new instance of the `OracleDate` structure and sets its value using the supplied string.

**Declaration**

```
// C#  
public OracleDate (string dateStr);
```

**Parameters**

- *dateStr*  
A string that represents an Oracle DATE.

**Exceptions**

`ArgumentException` - The *dateStr* is an invalid string representation of an Oracle DATE or the *dateStr* is not in the date format specified by the thread's `OracleGlobalization.DateFormat` property, which represents the Oracle NLS\_DATE\_FORMAT parameter.

`ArgumentNullException` - The *dateStr* is null.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class OracleDateSample  
{  
    static void Main(string[] args)  
    {  
        // Set the thread's DateFormat for the OracleDate constructor  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.DateFormat = "YYYY-MON-DD";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // construct OracleDate from a string using the DateFormat specified.  
        OracleDate date = new OracleDate("1999-DEC-01");  
  
        // Set a different DateFormat for the thread  
        info.DateFormat = "MM/DD/YYYY";  
        OracleGlobalization.SetThreadInfo(info);  
    }  
}
```

```
// Print "12/01/1999"  
Console.WriteLine(date.ToString());  
}  
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- *Oracle Database SQL Reference* for further information on date format elements

**OracleDate(int, int, int)**

This constructor creates a new instance of the `OracleDate` structure and set its value for date using the supplied year, month, and day.

**Declaration**

```
// C#  
public OracleDate (int year, int month, int day);
```

**Parameters**

- *year*  
The supplied year. Range of *year* is (-4712 to 9999).
- *month*  
The supplied month. Range of *month* is (1 to 12).
- *day*  
The supplied day. Range of *day* is (1 to 31).

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleDate` (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**OracleDate(int, int, int, int, int, int)**

This constructor creates a new instance of the `OracleDate` structure and set its value for time using the supplied year, month, day, hour, minute, and second.

**Declaration**

```
// C#
```

```
public OracleDate (int year, int month, int day, int hour, int minute, int second);
```

### Parameters

- *year*  
The supplied year. Range of *year* is (-4712 to 9999).
- *month*  
The supplied month. Range of *month* is (1 to 12).
- *day*  
The supplied day. Range of *day* is (1 to 31).
- *hour*  
The supplied hour. Range of *hour* is (0 to 23).
- *minute*  
The supplied minute. Range of *minute* is (0 to 59).
- *second*  
The supplied second. Range of *second* is (0 to 59).

### Exceptions

*ArgumentOutOfRangeException* - The argument value for one or more of the parameters is out of the specified range.

*ArgumentException* - The argument values of the parameters cannot be used to construct a valid *OracleDate* (that is, the day is out of range for the month).

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## OracleDate(byte [ ])

This constructor creates a new instance of the *OracleDate* structure and sets its value to the provided byte array, which is in the internal Oracle DATE format.

### Declaration

```
// C#  
public OracleDate(byte [] bytes);
```

### Parameters

- *bytes*  
A byte array that represents Oracle DATE in the internal Oracle DATE format.

### Exceptions

*ArgumentException* - *bytes* is null or *bytes* is not in internal Oracle DATE format or *bytes* is not a valid Oracle DATE.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)



## OracleDate Static Fields

The OracleDate static fields are listed in [Table 14–21](#).

**Table 14–21 OracleDate Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleDate structure, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to the value of an OracleDate structure instance

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### MaxValue

This static field represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59.

**Declaration**

```
// C#
public static readonly OracleDate MaxValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### MinValue

This static field represents the minimum valid date for an OracleDate structure, which is January 1, -4712.

**Declaration**

```
// C#
public static readonly OracleDate MinValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Null

This static field represents a null value that can be assigned to the value of an `OracleDate` instance.

### Declaration

```
// C#  
public static readonly OracleDate Null;
```

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## OracleDate Static Methods

The OracleDate static methods are listed in [Table 14–22](#).

**Table 14–22 OracleDate Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleDate values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two OracleDate values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleDate values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleDate values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleDate values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleDate values are not equal
<a href="#">GetSysDate</a>	Returns an OracleDate structure that represents the current date and time
<a href="#">Parse</a>	Returns an OracleDate structure and sets its value using a string

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Equals

Overloads Object

This method determines if two OracleDate values are equal.

### Declaration

```
// C#
public static bool Equals(OracleDate value1, OracleDate value2);
```

### Parameters

- *value1*  
The first OracleDate.
- *value2*  
The second OracleDate.

### Return Value

Returns true if two OracleDate values are equal; otherwise, returns false.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## GreaterThan

This method determines if the first of two `OracleDate` values is greater than the second.

**Declaration**

```
// C#  
public static bool GreaterThan(OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first `OracleDate`.
- *value2*  
The second `OracleDate`.

**Return Value**

Returns `true` if the first of two `OracleDate` values is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## GreaterThanOrEqual

This method determines if the first of two `OracleDate` values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool GreaterThanOrEqual(OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first OracleDate.
- *value2*  
The second OracleDate.

**Return Value**

Returns `true` if the first of two OracleDate values is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

**LessThan**

This method determines if the first of two OracleDate values is less than the second.

**Declaration**

```
// C#  
public static bool LessThan(OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first OracleDate.
- *value2*  
The second OracleDate.

**Return Value**

Returns `true` if the first of two OracleDate values is less than the second. Otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## LessThanOrEqual

This method determines if the first of two `OracleDate` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool LessThanOrEqual(OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first `OracleDate`.
- *value2*  
The second `OracleDate`.

**Return Value**

Returns `true` if the first of two `OracleDate` values is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## NotEquals

This method determines if two `OracleDate` values are not equal.

**Declaration**

```
// C#  
public static bool NotEquals(OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first `OracleDate`.
- *value2*

The second `OracleDate`.

### Return Value

Returns `true` if two `OracleDate` values are not equal; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## GetSysDate

This method gets an `OracleDate` structure that represents the current date and time.

### Declaration

```
// C#  
public static OracleDate GetSysDate ();
```

### Return Value

An `OracleDate` structure that represents the current date and time.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Parse

This method gets an `OracleDate` structure and sets its value for date and time using the supplied string.

### Declaration

```
// C#  
public static OracleDate Parse (string dateStr);
```

### Parameters

- *dateStr*  
A string that represents an Oracle DATE.

### Return Value

An `OracleDate` structure.

### Exceptions

**ArgumentException** - The *dateStr* is an invalid string representation of an Oracle DATE or the *dateStr* is not in the date format specified by the thread's `OracleGlobalization.DateFormat` property, which represents the Oracle NLS\_DATE\_FORMAT parameter.

**ArgumentNullException** - The *dateStr* is null.

### Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // Construct OracleDate from a string using the DateFormat specified
        OracleDate date = OracleDate.Parse("1999-DEC-01");

        // Set a different DateFormat on the thread for ToString()
        info.DateFormat = "MM-DD-YY";
        OracleGlobalization.SetThreadInfo(info);

        // Print "12-01-1999"
        Console.WriteLine(date.ToString());
    }
}
```

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class" on page 10-2](#)
- ["Globalization Support" on page 3-110](#)
- *Oracle Database SQL Reference* for further information on datetime format elements



## OracleDate Static Operators

The OracleDate static operators are listed in [Table 14–23](#).

**Table 14–23 OracleDate Static Operators**

Operator	Description
<code>operator ==</code>	Determines if two OracleDate values are the same
<code>operator &gt;</code>	Determines if the first of two OracleDate values is greater than the second
<code>operator &gt;=</code>	Determines if the first of two OracleDate values is greater than or equal to the second
<code>operator !=</code>	Determines if the two OracleDate values are not equal
<code>operator &lt;</code>	Determines if the first of two OracleDate values is less than the second
<code>operator &lt;=</code>	Determines if the first of two OracleDate values is less than or equal to the second

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### `operator ==`

This method determines if two OracleDate values are the same.

#### Declaration

```
// C#
public static bool operator == (OracleDate value1, OracleDate value2);
```

#### Parameters

- *value1*  
The first OracleDate.
- *value2*  
The second OracleDate.

#### Return Value

Returns true if they are the same; otherwise, returns false.

#### Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**operator >**

This method determines if the first of two `OracleDate` values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first `OracleDate`.
- *value2*  
The second `OracleDate`.

**Return Value**

Returns `true` if the first of two `OracleDate` values is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**operator >=**

This method determines if the first of two `OracleDate` values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool operator >= (OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first `OracleDate`.
- *value2*

The second `OracleDate`.

### Return Value

Returns `true` if the first of two `OracleDate` values is greater than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## operator !=

This method determines if the two `OracleDate` values are not equal.

### Declaration

```
// C#  
public static bool operator != (OracleDate value1, OracleDate value2);
```

### Parameters

- *value1*  
The first `OracleDate`.
- *value2*  
The second `OracleDate`.

### Return Value

Returns `true` if the two `OracleDate` values are not equal; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## operator <

This method determines if the first of two `OracleDate` values is less than the second.

**Declaration**

```
// C#  
public static bool operator < (OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first OracleDate.
- *value2*  
The second OracleDate.

**Return Value**

Returns `true` if the first of two OracleDate values is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**operator <=**

This method determines if the first of two OracleDate values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool operator <= (OracleDate value1, OracleDate value2);
```

**Parameters**

- *value1*  
The first OracleDate.
- *value2*  
The second OracleDate.

**Return Value**

Returns `true` if the first of two OracleDate values is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.

- Two `OracleDates` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## OracleDate Static Type Conversions

The `OracleDate` static type conversions are listed in [Table 14–24](#).

**Table 14–24 OracleDate Static Type Conversions**

Operator	Description
<a href="#">explicit operator DateTime</a>	Converts a structure to a <code>DateTime</code> structure
<a href="#">explicit operator OracleDate</a>	Converts a structure to an <code>OracleDate</code> structure (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### explicit operator DateTime

This method converts an `OracleDate` structure to a `DateTime` structure.

**Declaration**

```
// C#  
public static explicit operator DateTime(OracleDate val);
```

**Parameters**

- `val`  
An `OracleDate` structure.

**Return Value**

A `DateTime` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### explicit operator OracleDate

`explicit operator OracleDate` converts the provided structure to an `OracleDate` structure.

**Overload List:**

- [explicit operator OracleDate\(DateTime\)](#)  
This method converts a `DateTime` structure to an `OracleDate` structure.
- [explicit operator OracleDate\(OracleTimeStamp\)](#)  
This method converts an `OracleTimeStamp` structure to an `OracleDate` structure.
- [explicit operator OracleDate\(string\)](#)

This method converts the supplied string to an `OracleDate` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

### explicit operator `OracleDate(DateTime)`

This method converts a `DateTime` structure to an `OracleDate` structure.

**Declaration**

```
// C#  
public static explicit operator OracleDate(DateTime dt);
```

**Parameters**

- *dt*  
A `DateTime` structure.

**Return Value**

An `OracleDate` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

### explicit operator `OracleDate(OracleTimeStamp)`

This method converts an `OracleTimeStamp` structure to an `OracleDate` structure.

**Declaration**

```
// C#  
public explicit operator OracleDate(OracleTimeStamp ts);
```

**Parameters**

- *ts*  
`OracleTimeStamp`

**Return Value**

The returned `OracleDate` structure contains the date and time in the `OracleTimeStamp` structure.

**Remarks**

The precision of the `OracleTimeStamp` value can be lost during the conversion.

If the `OracleTimeStamp` structure has a null value, the returned `OracleDate` structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**explicit operator OracleDate(string)**

This method converts the supplied string to an OracleDate structure.

**Declaration**

```
// C#  
public explicit operator OracleDate (string dateStr);
```

**Parameters**

- *dateStr*  
A string representation of an Oracle DATE.

**Return Value**

The returned OracleDate structure contains the date and time in the string *dateStr*.

**Exceptions**

ArgumentNullException - The *dateStr* is null.

ArgumentException - This exception is thrown if any of the following conditions exist:

- The *dateStr* is an invalid string representation of an Oracle DATE.
- The *dateStr* is not in the date format specified by the thread's OracleGlobalization.DateFormat property, which represents the Oracle NLS\_DATE\_FORMAT parameter.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleDateSample  
{  
    static void Main(string[] args)  
    {  
        // Set the thread's DateFormat to a specific format  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.DateFormat = "YYYY-MON-DD";  
        OracleGlobalization.SetThreadInfo(info);  
    }  
}
```



```
// Construct OracleDate from a string using the DateFormat specified
OracleDate date = (OracleDate)"1999-DEC-01";

// Set a different DateFormat on the thread for ToString()
info.DateFormat = "MON DD YY";
OracleGlobalization.SetThreadInfo(info);

// Prints "DEC 01 99"
Console.WriteLine(date.ToString());
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## OracleDate Properties

The OracleDate properties are listed in [Table 14–25](#).

**Table 14–25 OracleDate Properties**

Properties	Description
<a href="#">BinData</a>	Gets an array of bytes that represents an Oracle DATE in Oracle internal format
<a href="#">Day</a>	Gets the day component of an OracleDate method
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Hour</a>	Gets the hour component of an OracleDate
<a href="#">Minute</a>	Gets the minute component of an OracleDate
<a href="#">Month</a>	Gets the month component of an OracleDate
<a href="#">Second</a>	Gets the second component of an OracleDate
<a href="#">Value</a>	Gets the date and time that is stored in the OracleDate structure
<a href="#">Year</a>	Gets the year component of an OracleDate

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### BinData

This property gets a array of bytes that represents an Oracle DATE in Oracle internal format.

**Declaration**

```
// C#  
public byte[] BinData{get;}
```

**Property Value**

An array of bytes.

**Exceptions**

OracleNullValueException - OracleDate has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

### Day

This property gets the day component of an OracleDate.

**Declaration**

```
// C#  
public int Day{get;}
```

**Property Value**

A number that represents the day. Range of Day is (1 to 31).

**Exceptions**

OracleNullValueException - OracleDate has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**IsNull**

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#  
public bool IsNull{get;}
```

**Property Value**

Returns true if the current instance has a null value; otherwise, returns false.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**Hour**

This property gets the hour component of an OracleDate.

**Declaration**

```
// C#  
public int Hour {get;}
```

**Property Value**

A number that represents Hour. Range of Hour is (0 to 23).

**Exceptions**

OracleNullValueException - OracleDate has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Minute

This property gets the minute component of an `OracleDate`.

### Declaration

```
// C#  
public int Minute {get;}
```

### Property Value

A number that represents `Minute`. Range of `Minute` is (0 to 59).

### Exceptions

`OracleNullValueException` - `OracleDate` has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Month

This property gets the month component of an `OracleDate`.

### Declaration

```
// C#  
public int Month {get;}
```

### Property Value

A number that represents `Month`. Range of `Month` is (1 to 12).

### Exceptions

`OracleNullValueException` - `OracleDate` has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Second

This property gets the second component of an `OracleDate`.

### Declaration

```
// C#  
public int Second {get;}
```

### Property Value

A number that represents `Second`. Range of `Second` is (0 to 59).

### Exceptions

`OracleNullValueException` - `OracleDate` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

**Value**

This property specifies the date and time that is stored in the `OracleDate` structure.

**Declaration**

```
// C#  
public DateTime Value {get;}
```

**Property Value**

A `DateTime`.

**Exceptions**

`OracleNullValueException` - `OracleDate` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

**Year**

This property gets the year component of an `OracleDate`.

**Declaration**

```
// C#  
public int Year {get;}
```

**Property Value**

A number that represents `Year`. Range of `Year` is (-4712 to 9999).

**Exceptions**

`OracleNullValueException` - `OracleDate` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

## OracleDate Methods

The `OracleDate` methods are listed in [Table 14–26](#).

**Table 14–26 OracleDate Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current <code>OracleDate</code> instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleDate</code> instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleDate</code> instance
<a href="#">GetDaysBetween</a>	Calculates the number of days between the current <code>OracleDate</code> instance and an <code>OracleDate</code> structure
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToOracleTimeStamp</a>	Converts the current <code>OracleDate</code> structure to an <code>OracleTimeStamp</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleDate</code> structure to a string

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## CompareTo

This method compares the current `OracleDate` instance to an object, and returns an integer that represents their relative values.

### Declaration

```
// C#
public int CompareTo(object obj);
```

### Parameters

- *obj*  
An object.

### Return Value

The method returns:

- Less than zero: if the current `OracleDate` instance value is less than that of *obj*.
- Zero: if the current `OracleDate` instance and *obj* values are equal.
- Greater than zero: if the current `OracleDate` instance value is greater than *obj*.

### Implements

`IComparable`

### Exceptions

`ArgumentException` - The *obj* parameter is not an instance of `OracleDate`.

### Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleDates`. For example, comparing an `OracleDate` instance with an `OracleBinary` instance is not allowed. When an `OracleDate` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## Equals

This method determines whether or not an object has the same date and time as the current `OracleDate` instance.

### Declaration

```
// C#  
public override bool Equals( object obj);
```

### Parameters

- *obj*  
An object.

### Return Value

Returns `true` if *obj* has the same type as the current instance and represents the same date and time; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

## GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleDate` instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

A number that represents the hash code.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

**GetDaysBetween**

This method calculates the number of days between the current `OracleDate` instance and the supplied `OracleDate` structure.

**Declaration**

```
// C#  
public int GetDaysBetween (OracleDate val);
```

**Parameters**

- *val*  
An `OracleDate` structure.

**Return Value**

The number of days between the current `OracleDate` instance and the `OracleDate` structure.

**Exceptions**

`OracleNullValueException` - The current instance or the supplied `OracleDate` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

**ToOracleTimeStamp**

This method converts the current `OracleDate` structure to an `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

**Return Value**

An `OracleTimeStamp` structure.



**Remarks**

The returned `OracleTimeStamp` structure has date and time in the current instance.

If the `OracleDate` instance has a null value, the returned `OracleTimeStamp` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)

**ToString**

Overrides `ValueType`

This method converts the current `OracleDate` structure to a string.

**Declaration**

```
// C#
public override string ToString();
```

**Return Value**

A string.

**Remarks**

The returned value is a string representation of the `OracleDate` in the format specified by the thread's `OracleGlobalization.DateFormat` property. The names and abbreviations used for months and days are in the language specified by the thread's `OracleGlobalization.DateLanguage` and `OracleGlobalization.Calendar` properties. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ToStringSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat to a specific format
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // Construct OracleDate from a string using the DateFormat specified
        OracleDate date = (OracleDate)"1999-DEC-01";

        // Set a different DateFormat on the thread for ToString()
        info.DateFormat = "YYYY/MM/DD";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999/12/01"
```

```
        Console.WriteLine(date.ToString());  
    }  
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

---

## OracleDecimal Structure

The `OracleDecimal` structure represents an Oracle `NUMBER` in the database or any Oracle numeric value.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleDecimal`

### Declaration

```
// ADO.NET 2.0: C#
public struct OracleDecimal : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

`OracleDecimal` can store up to 38 precision, while the `.NET` `Decimal` data type can only hold up to 28 precision. When accessing the `OracleDecimal.Value` property from an `OracleDecimal` that has a value greater than 28 precision, an exception is thrown. To retrieve the actual value of `OracleDecimal`, use the `OracleDecimal.ToString()` method. Another approach is to obtain the `OracleDecimal` value as a byte array in an internal Oracle `NUMBER` format through the `BinData` property.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleDecimalSample
{
    static void Main(string[] args)
    {
        // Illustrates the range of OracleDecimal vs. .NET decimal
        OracleDecimal decimal1 = OracleDecimal.MinValue;
        OracleDecimal decimal2 = OracleDecimal.MaxValue;
        OracleDecimal decimal3 = new OracleDecimal(decimal.MinValue);
        OracleDecimal decimal4 = new OracleDecimal(decimal.MaxValue);

        // Print the ranges
        Console.WriteLine("OracleDecimal can range from\n{0}\nto\n{1}\n",
            decimal1, decimal2);
        Console.WriteLine(".NET decimal can range from\n{0}\nto\n{1}",
            decimal3, decimal4);
    }
}
```

## Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Constructors](#)
- [OracleDecimal Static Fields](#)
- [OracleDecimal Static \(Comparison\) Methods](#)
- [OracleDecimal Static \(Manipulation\) Methods](#)
- [OracleDecimal Static \(Logarithmic\) Methods](#)
- [OracleDecimal Static \(Trigonometric\) Methods](#)
- [OracleDecimal Static \(Comparison\) Operators](#)
- [OracleDecimal Static Operators \(Conversion from .NET Type to OracleDecimal\)](#)
- [OracleDecimal Static Operators \(Conversion from OracleDecimal to .NET\)](#)
- [OracleDecimal Properties](#)
- [OracleDecimal Instance Methods](#)

## OracleDecimal Members

OracleDecimal members are listed in the following tables:

### OracleDecimal Constructors

OracleDecimal constructors are listed in [Table 14-27](#)

**Table 14-27 OracleDecimal Constructors**

Constructor	Description
<a href="#">OracleDecimal Constructors</a>	Instantiates a new instance of OracleDecimal structure (Overloaded)

### OracleDecimal Static Fields

The OracleDecimal static fields are listed in [Table 14-28](#).

**Table 14-28 OracleDecimal Static Fields**

Field	Description
<a href="#">MaxPrecision</a>	A constant representing the maximum precision, which is 38
<a href="#">MaxScale</a>	A constant representing the maximum scale, which is 127
<a href="#">MaxValue</a>	A constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$
<a href="#">MinScale</a>	A constant representing the minimum scale, which is -84
<a href="#">MinValue</a>	A constant representing the minimum value for this structure, which is $-1.0 \times 10^{130}$
<a href="#">NegativeOne</a>	A constant representing the negative one value
<a href="#">Null</a>	Represents a null value that can be assigned to an OracleDecimal instance
<a href="#">One</a>	A constant representing the positive one value
<a href="#">Pi</a>	A constant representing the numeric Pi value
<a href="#">Zero</a>	A constant representing the zero value

### OracleDecimal Static (Comparison) Methods

The OracleDecimal static (comparison) methods are listed in [Table 14-29](#).

**Table 14-29 OracleDecimal Static (Comparison) Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleDecimal values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two OracleDecimal values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleDecimal values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleDecimal values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleDecimal values is less than or equal to the second.

**Table 14–29 (Cont.) OracleDecimal Static (Comparison) Methods**

Methods	Description
<a href="#">NotEquals</a>	Determines if two OracleDecimal values are not equal

**OracleDecimal Static (Manipulation) Methods**

The OracleDecimal static (manipulation) methods are listed in [Table 14–30](#).

**Table 14–30 OracleDecimal Static (Manipulation) Methods**

Methods	Description
<a href="#">Abs</a>	Returns the absolute value of an OracleDecimal
<a href="#">Add</a>	Adds two OracleDecimal structures
<a href="#">AdjustScale</a>	Returns a new OracleDecimal with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than original
<a href="#">Ceiling</a>	Returns a new OracleDecimal structure with its value set to the ceiling of an OracleDecimal structure
<a href="#">ConvertToPrecScale</a>	Returns a new OracleDecimal structure with a new precision and scale
<a href="#">Divide</a>	Divides one OracleDecimal value by another
<a href="#">Floor</a>	Returns a new OracleDecimal structure with its value set to the floor of an OracleDecimal structure
<a href="#">Max</a>	Returns the maximum value of the two supplied OracleDecimal structures
<a href="#">Min</a>	Returns the minimum value of the two supplied OracleDecimal structures
<a href="#">Mod</a>	Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures
<a href="#">Multiply</a>	Returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures
<a href="#">Negate</a>	Returns a new OracleDecimal structure with its value set to the negation of the supplied OracleDecimal structure
<a href="#">Parse</a>	Converts a string to an OracleDecimal
<a href="#">Round</a>	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure and rounded off to the specified place
<a href="#">SetPrecision</a>	Returns a new OracleDecimal structure with a new specified precision.
<a href="#">Shift</a>	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right
<a href="#">Sign</a>	Determines the sign of an OracleDecimal structure
<a href="#">Sqrt</a>	Returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure
<a href="#">Subtract</a>	Returns a new OracleDecimal structure with its value set to result of subtracting one OracleDecimal structure from another
<a href="#">Truncate</a>	Truncates the OracleDecimal at a specified position

## OracleDecimal Static (Logarithmic) Methods

The OracleDecimal static (logarithmic) methods are listed in [Table 14–31](#).

**Table 14–31 OracleDecimal Static (Logarithmic) Methods**

Methods	Description
<a href="#">Exp</a>	Returns a new OracleDecimal structure with its value set to e raised to the supplied power
<a href="#">Log</a>	Returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure (Overloaded)
<a href="#">Pow</a>	Returns a new OracleDecimal structure with its value set to the supplied OracleDecimal structure raised to the supplied power (Overloaded)

## OracleDecimal Static (Trigonometric) Methods

The OracleDecimal static (trigonometric) methods are listed in [Table 14–32](#).

**Table 14–32 OracleDecimal Static (Trigonometric) Methods**

Methods	Description
<a href="#">Acos</a>	Returns an angle in radians whose cosine is the supplied OracleDecimal structure
<a href="#">Asin</a>	Returns an angle in radians whose sine is the supplied OracleDecimal structure
<a href="#">Atan</a>	Returns an angle in radians whose tangent is the supplied OracleDecimal structure
<a href="#">Atan2</a>	Returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures
<a href="#">Cos</a>	Returns the cosine of the supplied angle in radians
<a href="#">Sin</a>	Returns the sine of the supplied angle in radians
<a href="#">Tan</a>	Returns the tangent of the supplied angle in radians
<a href="#">Cosh</a>	Returns the hyperbolic cosine of the supplied angle in radians
<a href="#">Sinh</a>	Returns the hyperbolic sine of the supplied angle in radians
<a href="#">Tanh</a>	Returns the hyperbolic tangent of the supplied angle in radians

## OracleDecimal Static (Comparison) Operators

The OracleDecimal static (comparison) operators are listed in [Table 14–33](#).

**Table 14–33 OracleDecimal Static (Comparison) Operators**

Operator	Description
<a href="#">operator +</a>	Adds two OracleDecimal values
<a href="#">operator /</a>	Divides one OracleDecimal value by another
<a href="#">operator ==</a>	Determines if the two OracleDecimal values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleDecimal values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleDecimal values is greater than or equal to the second

**Table 14–33 (Cont.) OracleDecimal Static (Comparison) Operators**

Operator	Description
operator !=	Determines if the two OracleDecimal values are not equal
operator <	Determines if the first of two OracleDecimal values is less than the second
operator <=	Determines if the first of two OracleDecimal values is less than or equal to the second
operator *	Multiplies two OracleDecimal structures
operator -	Subtracts one OracleDecimal structure from another
operator -	Negates an OracleDecimal structure
operator %	Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures.

### OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

The OracleDecimal static operators (Conversion from .NET Type to OracleDecimal) are listed in [Table 14–34](#).

**Table 14–34 OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)**

Operator	Description
implicit operator OracleDecimal	Converts an instance value to an OracleDecimal structure (Overloaded)
explicit operator OracleDecimal	Converts an instance value to an OracleDecimal structure (Overloaded)

### OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

The OracleDecimal static operators (Conversion from OracleDecimal to .NET) are listed in [Table 14–35](#).

**Table 14–35 OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)**

Operator	Description
explicit operator byte	Returns the byte representation of the OracleDecimal value
explicit operator decimal	Returns the decimal representation of the OracleDecimal value
explicit operator double	Returns the double representation of the OracleDecimal value
explicit operator short	Returns the short representation of the OracleDecimal value
explicit operator int	Returns the int representation of the OracleDecimal value
explicit operator long	Returns the long representation of the OracleDecimal value
explicit operator float	Returns the float representation of the OracleDecimal value

### OracleDecimal Properties

The OracleDecimal properties are listed in [Table 14–36](#).



**Table 14–36 OracleDecimal Properties**

Properties	Description
<a href="#">BinData</a>	Returns a byte array that represents the Oracle NUMBER in Oracle internal format
<a href="#">Format</a>	Specifies the format for <code>Tostring()</code>
<a href="#">IsInt</a>	Indicates whether or not the current instance is an integer
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsPositive</a>	Indicates whether or not the current instance is greater than 0
<a href="#">IsZero</a>	Indicates whether or not the current instance has a zero value
<a href="#">Value</a>	Returns a decimal value

### OracleDecimal Instance Methods

The `OracleDecimal` instance methods are listed in [Table 14–37](#).

**Table 14–37 OracleDecimal Instance Methods**

Method	Description
<a href="#">CompareTo</a>	Compares the current instance to the supplied object and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object is an instance of <code>OracleDecimal</code> , and whether or not the value of the object is equal to the current instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the current instance
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToByte</a>	Returns the <code>byte</code> representation of the current instance
<a href="#">ToDouble</a>	Returns the <code>double</code> representation of the current instance
<a href="#">ToInt16</a>	Returns the <code>Int16</code> representation of the current instance
<a href="#">ToInt32</a>	Returns the <code>Int32</code> representation of the current instance
<a href="#">ToInt64</a>	Returns the <code>Int64</code> representation of the current instance
<a href="#">ToSingle</a>	Returns the <code>Single</code> representation of the current instance
<a href="#">ToString</a>	Overloads <code>Object.ToString()</code> Returns the <code>string</code> representation of the current instance

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Structure](#)

## OracleDecimal Constructors

The `OracleDecimal` constructors instantiate a new instance of the `OracleDecimal` structure.

### Overload List:

- [OracleDecimal\(byte \[ \]\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied byte array, which is in an Oracle `NUMBER` format.
- [OracleDecimal\(decimal\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Decimal` value.
- [OracleDecimal\(double\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `double` value.
- [OracleDecimal\(int\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int32` value.
- [OracleDecimal\(float\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Single` value.
- [OracleDecimal\(long\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int64` value.
- [OracleDecimal\(string\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `string` value.
- [OracleDecimal\(string, string\)](#)

This constructor creates a new instance of the `OracleDecimal` structure with the supplied `string` value and number format.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### OracleDecimal(byte [ ])

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied byte array, which is in an Oracle `NUMBER` format.

### Declaration

```
// C#  
public OracleDecimal(byte [] bytes);
```

### Parameters

- *bytes*

A byte array that represents an Oracle NUMBER in an internal Oracle format.

### Exceptions

*ArgumentException* - The *bytes* parameter is not in a internal Oracle NUMBER format or *bytes* has an invalid value.

*ArgumentNullException* - The *bytes* parameter is null.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal(decimal)

This constructor creates a new instance of the *OracleDecimal* structure and sets its value to the supplied *Decimal* value.

### Declaration

```
// C#  
public OracleDecimal(decimal decX);
```

### Parameters

- *decX*

The provided *Decimal* value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal(double)

This constructor creates a new instance of the *OracleDecimal* structure and sets its value to the supplied *double* value.

### Declaration

```
// C#  
public OracleDecimal(double doubleX)
```

### Parameters

- *doubleX*

The provided *double* value.

### Exceptions

*OverflowException* - The value of the supplied *double* is greater than the maximum value or less than the minimum value of *OracleDecimal*.

**Remarks**

OracleDecimal contains the following values depending on the provided double value:

- `double.PositiveInfinity`: positive infinity value
- `double.NegativeInfinity`: negative infinity value.
- `double.NaN`: null value

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**OracleDecimal(int)**

This constructor creates a new instance of the OracleDecimal structure and sets its value to the supplied Int32 value.

**Declaration**

```
// C#  
public OracleDecimal(int intX);
```

**Parameters**

- *intX*

The provided Int32 value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**OracleDecimal(float)**

This constructor creates a new instance of the OracleDecimal structure and sets its value to the supplied Single value.

**Declaration**

```
// C#  
public OracleDecimal(float floatX);
```

**Parameters**

- *floatX*

The provided float value.

**Remarks**

OracleDecimal contains the following values depending on the provided float value:

`float.PositiveInfinity`: positive infinity value

`float.NegativeInfinity`: negative infinity value

`float.NaN`: null value

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal(long)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int64` value.

**Declaration**

```
// C#  
public OracleDecimal(long longX);
```

**Parameters**

- *longX*

The provided `Int64` value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal(string)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `string` value.

**Declaration**

```
// C#  
public OracleDecimal(string numStr);
```

**Parameters**

- *numStr*

The provided `string` value.

**Exceptions**

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal`.

`ArgumentNullException` - The *numStr* parameter is null.

`OverflowException` - The value of *numStr* is greater than the maximum value or less than the minimum value of `OracleDecimal`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**OracleDecimal(string, string)**

This constructor creates a new instance of the `OracleDecimal` structure with the supplied `string` value and number format.

**Declaration**

```
// C#  
public OracleDecimal(string numStr, string format);
```

**Parameters**

- *numStr*  
The provided `string` value.
- *format*  
The provided number format.

**Exceptions**

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal` or the *numStr* is not in the numeric format specified by *format*.

`ArgumentNullException` - The *numStr* parameter is null.

`OverflowException` - The value of *numStr* parameter is greater than the maximum value or less than the minimum value of `OracleDecimal`.

**Remarks**

If the numeric format includes decimal and group separators, then the provided string must use those characters defined by the `OracleGlobalization.NumericCharacters` of the thread.

If the numeric format includes the currency symbol, ISO currency symbol, or the dual currency symbol, then the provided string must use those symbols defined by the `OracleGlobalization.Currency`, `OracleGlobalization.ISOCurrency`, and `OracleGlobalization.DualCurrency` properties respectively.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleDecimalSample  
{  
    static void Main(string[] args)  
    {
```

```
// Set the nls parameters related to currency
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.Currency = "$";
info.NumericCharacters = ".";
OracleGlobalization.SetThreadInfo(info);

// Construct an OracleDecimal using a valid numeric format
OracleDecimal dec = new OracleDecimal("$2,222.22", "L9G999D99");

// Print "$2,222.22"
Console.WriteLine(dec.ToString());
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## OracleDecimal Static Fields

The `OracleDecimal` static fields are listed in [Table 14–38](#).

**Table 14–38 OracleDecimal Static Fields**

Field	Description
<a href="#">MaxPrecision</a>	A constant representing the maximum precision, which is 38
<a href="#">MaxScale</a>	A constant representing the maximum scale, which is 127
<a href="#">MaxValue</a>	A constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$
<a href="#">MinScale</a>	A constant representing the minimum scale, which is -84
<a href="#">MinValue</a>	A constant representing the minimum value for this structure, which is $-1.0 \times 10^{130}$
<a href="#">NegativeOne</a>	A constant representing the negative one value
<a href="#">Null</a>	Represents a null value that can be assigned to an <code>OracleDecimal</code> instance
<a href="#">One</a>	A constant representing the positive one value
<a href="#">Pi</a>	A constant representing the numeric Pi value
<a href="#">Zero</a>	A constant representing the zero value

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### MaxPrecision

This static field represents the maximum precision, which is 38.

**Declaration**

```
// C#
public static readonly byte MaxPrecision;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### MaxScale

This static field a constant representing the maximum scale, which is 127.

**Declaration**

```
// C#
public static readonly byte MaxScale;
```



**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## MaxValue

This static field indicates a constant representing the maximum value for this structure, which is  $9.9\dots9 \times 10^{125}$  (38 nines followed by 88 zeroes).

**Declaration**

```
// C#  
public static readonly OracleDecimal MaxValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## MinScale

This static field indicates a constant representing the maximum scale, which is -84.

**Declaration**

```
// C#  
public static readonly int MinScale;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## MinValue

This static field indicates a constant representing the minimum value for this structure, which is  $-1.0 \times 10^{130}$ .

**Declaration**

```
// C#  
public static readonly OracleDecimal MinValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## NegativeOne

This static field indicates a constant representing the negative one value.

**Declaration**

```
// C#  
public static readonly OracleDecimal NegativeOne;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Null**

This static field represents a null value that can be assigned to an `OracleDecimal` instance.

**Declaration**

```
// C#  
public static readonly OracleDecimal Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**One**

This static field indicates a constant representing the positive one value.

**Declaration**

```
// C#  
public static readonly OracleDecimal One;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Pi**

This static field indicates a constant representing the numeric Pi value.

**Declaration**

```
// C#  
public static readonly OracleDecimal Pi;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Zero

This static field indicates a constant representing the zero value.

### Declaration

```
// C#  
public static readonly OracleDecimal Zero;
```

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Static (Comparison) Methods

The `OracleDecimal` static (comparison) methods are listed in [Table 14–39](#).

**Table 14–39 OracleDecimal Static (Comparison) Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two <code>OracleDecimal</code> values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two <code>OracleDecimal</code> values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two <code>OracleDecimal</code> values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two <code>OracleDecimal</code> values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two <code>OracleDecimal</code> values is less than or equal to the second.
<a href="#">NotEquals</a>	Determines if two <code>OracleDecimal</code> values are not equal

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### Equals

This method determines if two `OracleDecimal` values are equal.

**Declaration**

```
// C#
public static bool Equals(OracleDecimal value1, OracleDecimal value2);
```

**Parameters**

- *value1*  
The first `OracleDecimal`.
- *value2*  
The second `OracleDecimal`.

**Return Value**

Returns `true` if two `OracleDecimal` values are equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## GreaterThan

This method determines if the first of two `OracleDecimal` values is greater than the second.

**Declaration**

```
// C#  
public static bool GreaterThan(OracleDecimal value1, OracleDecimal value2);
```

**Parameters**

- *value1*  
The first `OracleDecimal`.
- *value2*  
The second `OracleDecimal`.

**Return Value**

Returns `true` if the first of two `OracleDecimal` values is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## GreaterThanOrEqual

This method determines if the first of two `OracleDecimal` values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool GreaterThanOrEqual(OracleDecimal value1, OracleDecimal value2);
```

**Parameters**

- *value1*  
The first `OracleDecimal`.
- *value2*

The second `OracleDecimal`.

**Return Value**

Returns `true` if the first of two `OracleDecimal` values is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## LessThan

This method determines if the first of two `OracleDecimal` values is less than the second.

**Declaration**

```
// C#  
public static bool LessThan(OracleDecimal value1, OracleDecimal value2);
```

**Parameters**

- *value1*  
The first `OracleDecimal`.
- *value2*  
The second `OracleDecimal`.

**Return Value**

Returns `true` if the first of two `OracleDecimal` values is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## LessThanOrEqual

This method determines if the first of two `OracleDecimal` values is less than or equal to the second.

### Declaration

```
// C#  
public static bool LessThanOrEqual(OracleDecimal value1, OracleDecimal value2);
```

### Parameters

- *value1*  
The first `OracleDecimal`.
- *value2*  
The second `OracleDecimal`.

### Return Value

Returns `true` if the first of two `OracleDecimal` values is less than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## NotEquals

This method determines if two `OracleDecimal` values are not equal.

### Declaration

```
// C#  
public static bool NotEquals(OracleDecimal value1, OracleDecimal value2);
```

### Parameters

- *value1*  
The first `OracleDecimal`.
- *value2*  
The second `OracleDecimal`.

### Return Value

Returns `true` if two `OracleDecimal` values are not equal; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)



## OracleDecimal Static (Manipulation) Methods

The OracleDecimal static (manipulation) methods are listed in [Table 14–40](#).

**Table 14–40 OracleDecimal Static (Manipulation) Methods**

Methods	Description
<a href="#">Abs</a>	Returns the absolute value of an OracleDecimal
<a href="#">Add</a>	Adds two OracleDecimal structures
<a href="#">AdjustScale</a>	Returns a new OracleDecimal with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than original
<a href="#">Ceiling</a>	Returns a new OracleDecimal structure with its value set to the ceiling of an OracleDecimal structure
<a href="#">ConvertToPrecScale</a>	Returns a new OracleDecimal structure with a new precision and scale
<a href="#">Divide</a>	Divides one OracleDecimal value by another
<a href="#">Floor</a>	Returns a new OracleDecimal structure with its value set to the floor of an OracleDecimal structure
<a href="#">Max</a>	Returns the maximum value of the two supplied OracleDecimal structures
<a href="#">Min</a>	Returns the minimum value of the two supplied OracleDecimal structures
<a href="#">Mod</a>	Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures
<a href="#">Multiply</a>	Returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures
<a href="#">Negate</a>	Returns a new OracleDecimal structure with its value set to the negation of the supplied OracleDecimal structure
<a href="#">Parse</a>	Converts a string to an OracleDecimal
<a href="#">Round</a>	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure and rounded off to the specified place
<a href="#">SetPrecision</a>	Returns a new OracleDecimal structure with a new specified precision.
<a href="#">Shift</a>	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right
<a href="#">Sign</a>	Determines the sign of an OracleDecimal structure
<a href="#">Sqrt</a>	Returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure
<a href="#">Subtract</a>	Returns a new OracleDecimal structure with its value set to result of subtracting one OracleDecimal structure from another
<a href="#">Truncate</a>	Truncates the OracleDecimal at a specified position

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Abs**

This method returns the absolute value of an `OracleDecimal`.

**Declaration**

```
// C#  
public static OracleDecimal Abs(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal`.

**Return Value**

The absolute value of an `OracleDecimal`.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Add**

This method adds two `OracleDecimal` structures.

**Declaration**

```
// C#  
public static OracleDecimal Add(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first `OracleDecimal`.
- *val2*  
The second `OracleDecimal`.

**Return Value**

Returns an `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## AdjustScale

This method returns a new `OracleDecimal` with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than the original.

**Declaration**

```
// C#
public static OracleDecimal AdjustScale(OracleDecimal val, int digits,
    bool fRound);
```

**Parameters**

- *val*  
An `OracleDecimal`.
- *digits*  
The number of digits.
- *fRound*  
Indicates whether or not to round or truncate the number. Setting it to `true` rounds the number and setting it to `false` truncates the number.

**Return Value**

An `OracleDecimal`.

**Remarks**

If the supplied `OracleDecimal` has a null value, the returned `OracleDecimal` has a null value.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Types;

class AdjustScaleSample
{
    static void Main(string[] args)
    {
        OracleDecimal dec1 = new OracleDecimal(5.555);

        // Adjust Scale to 2 with rounding off
        OracleDecimal dec2 = OracleDecimal.AdjustScale(dec1, 2, true);

        // Prints 5.56
        Console.WriteLine(dec2.ToString());

        // Adjust Scale to 2 with truncation
        OracleDecimal dec3 = OracleDecimal.AdjustScale(dec1, 2, false);
```

```
// Prints 5.55
Console.WriteLine(dec3.ToString());
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Ceiling

This method returns a new `OracleDecimal` structure with its value set to the ceiling of the supplied `OracleDecimal`.

**Declaration**

```
// C#
public static OracleDecimal Ceiling(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal`.

**Return Value**

A new `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## ConvertToPrecScale

This method returns a new `OracleDecimal` structure with a new precision and scale.

**Declaration**

```
// C#
public static OracleDecimal ConvertToPrecScale(OracleDecimal val
    int precision, int scale);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.
- *precision*  
The precision. Range of precision is 1 to 38.

- *scale*

The number of digits to the right of the decimal point. Range of scale is -84 to 127.

**Return Value**

A new `OracleDecimal` structure.

**Remarks**

If the supplied `OracleDecimal` has a null value, the returned `OracleDecimal` has a null value.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Types;

class ConvertToPrecScaleSample
{
    static void Main(string[] args)
    {
        OracleDecimal dec1 = new OracleDecimal(555.6666);

        // Set the precision of od to 5 and scale to 2
        OracleDecimal dec2 = OracleDecimal.ConvertToPrecScale(dec1,5,2);

        // Prints 555.67
        Console.WriteLine(dec2.ToString());

        // Set the precision of od to 3 and scale to 0
        OracleDecimal dec3 = OracleDecimal.ConvertToPrecScale(dec1,3,0);

        // Prints 556
        Console.WriteLine(dec3.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Divide

This method divides one `OracleDecimal` value by another.

**Declaration**

```
// C#
public static OracleDecimal Divide(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
An `OracleDecimal`.
- *val2*

An `OracleDecimal`.

**Return Value**

A new `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Floor**

This method returns a new `OracleDecimal` structure with its value set to the floor of the supplied `OracleDecimal` structure.

**Declaration**

```
// C#  
public static OracleDecimal Floor(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.

**Return Value**

A new `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Max**

This method returns the maximum value of the two supplied `OracleDecimal` structures.

**Declaration**

```
// C#  
public static OracleDecimal Max(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
An `OracleDecimal` structure.
- *val2*

An OracleDecimal structure.

**Return Value**

An OracleDecimal structure that has the greater value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Min**

This method returns the minimum value of the two supplied OracleDecimal structures.

**Declaration**

```
// C#  
public static OracleDecimal Min(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
An OracleDecimal structure.
- *val2*  
An OracleDecimal structure.

**Return Value**

An OracleDecimal structure that has the smaller value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Mod**

This method returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures.

**Declaration**

```
// C#  
public static OracleDecimal Mod(OracleDecimal val1, OracleDecimal divider);
```

**Parameters**

- *val1*  
An OracleDecimal structure.
- *divider*  
An OracleDecimal structure.

**Return Value**

An `OracleDecimal`.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Multiply

This method returns a new `OracleDecimal` structure with its value set to the result of multiplying two `OracleDecimal` structures.

**Declaration**

```
// C#  
public static OracleDecimal Multiply(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
An `OracleDecimal` structure.
- *val2*  
An `OracleDecimal` structure.

**Return Value**

A new `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Negate

This method returns a new `OracleDecimal` structure with its value set to the negation of the supplied `OracleDecimal` structures.

**Declaration**

```
// C#  
public static OracleDecimal Negate(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.



**Return Value**

A new `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Parse**

This method converts a `string` to an `OracleDecimal`.

**Declaration**

```
// C#  
public static OracleDecimal Parse (string str);
```

**Parameters**

- *str*  
The string being converted.

**Return Value**

A new `OracleDecimal` structure.

**Exceptions**

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal`.

`ArgumentNullException` - The *numStr* parameter is null.

`OverflowException` - The value of *numStr* is greater than the maximum value or less than the minimum value of `OracleDecimal`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**Round**

This method returns a new `OracleDecimal` structure with its value set to that of the supplied `OracleDecimal` structure and rounded off to the specified place.

**Declaration**

```
// C#  
public static OracleDecimal Round(OracleDecimal val, int decplace);
```

**Parameters**

- *val*  
An OracleDecimal structure.
- *decplace*  
The specified decimal place. If the value is positive, the function rounds the OracleDecimal structure to the right of the decimal point. If the value is negative, the function rounds to the left of the decimal point.

**Return Value**

An OracleDecimal structure.

**Remarks**

If the supplied OracleDecimal structure has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**SetPrecision**

This method returns a new OracleDecimal structure with a new specified precision.

**Declaration**

```
// C#  
public static OracleDecimal SetPrecision(OracleDecimal val, int precision);
```

**Parameters**

- *val*  
An OracleDecimal structure.
- *precision*  
The specified precision. Range of precision is 1 to 38.

**Return Value**

An OracleDecimal structure.

**Remarks**

The returned OracleDecimal is rounded off if the specified precision is smaller than the precision of *val*.

If *val* has a null value, the returned OracleDecimal has a null value.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class SetPrecisionSample
```

```
{
    static void Main(string[] args)
    {
        OracleDecimal dec1 = new OracleDecimal(555.6666);

        // Set the precision of dec1 to 3
        OracleDecimal dec2 = OracleDecimal.SetPrecision(dec1, 3);

        // Prints 556
        Console.WriteLine(dec2.ToString());

        // Set the precision of dec1 to 4
        OracleDecimal dec3 = OracleDecimal.SetPrecision(dec1, 4);

        // Prints 555.7
        Console.WriteLine(dec3.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)"Oracle.DataAccess.Types Namespace" on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Shift

This method returns a new `OracleDecimal` structure with its value set to that of the supplied `OracleDecimal` structure, and its decimal place shifted to the specified number of places to the right.

**Declaration**

```
// C#
public static OracleDecimal Shift(OracleDecimal val, int decplaces);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.
- *decplaces*  
The specified number of places to be shifted.

**Return Value**

An `OracleDecimal` structure.

**Remarks**

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

If *decplaces* is negative, the shift is to the left.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Sign

This method determines the sign of an `OracleDecimal` structure.

**Declaration**

```
// C#  
public static int Sign(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.

**Return Value**

- -1: if the supplied `OracleDecimal` < 0
- 0: if the supplied `OracleDecimal` == 0
- 1: if the supplied `OracleDecimal` > 0

**Exceptions**

`OracleNullValueException` - The argument has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Sqrt

This method returns a new `OracleDecimal` structure with its value set to the square root of the supplied `OracleDecimal` structure.

**Declaration**

```
// C#  
public static OracleDecimal Sqrt(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.

**Return Value**

An `OracleDecimal` structure.

**Exceptions**

`ArgumentOutOfRangeException` - The provided `OracleDecimal` structure is less than zero.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Subtract**

This method returns a new `OracleDecimal` structure with its value set to result of subtracting one `OracleDecimal` structure from another.

**Declaration**

```
// C#  
public static OracleDecimal Subtract(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
An `OracleDecimal` structure.
- *val2*  
An `OracleDecimal` structure.

**Return Value**

An `OracleDecimal` structure.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Truncate**

This method truncates the `OracleDecimal` at a specified position.

**Declaration**

```
// C#  
public static OracleDecimal Truncate(OracleDecimal val, int pos);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.
- *pos*  
The specified position. If the value is positive, the function truncates the `OracleDecimal` structure to the right of the decimal point. If the value is

negative, it truncates the `OracleDecimal` structure to the left of the decimal point.

**Return Value**

An `OracleDecimal` structure.

**Remarks**

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Static (Logarithmic) Methods

The OracleDecimal static (logarithmic) methods are listed in [Table 14–41](#).

**Table 14–41 OracleDecimal Static (Logarithmic) Methods**

Methods	Description
<a href="#">Exp</a>	Returns a new OracleDecimal structure with its value set to e raised to the supplied power
<a href="#">Log</a>	Returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure (Overloaded)
<a href="#">Pow</a>	Returns a new OracleDecimal structure with its value set to the supplied OracleDecimal structure raised to the supplied power (Overloaded)

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Exp

This method returns a new OracleDecimal structure with its value set to e raised to the supplied OracleDecimal.

### Declaration

```
// C#
public static OracleDecimal Exp(OracleDecimal val);
```

### Parameters

- *val*  
An OracleDecimal structure.

### Return Value

An OracleDecimal structure.

### Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Log

Log returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure.

### Overload List:

- [Log\(OracleDecimal\)](#)

This method returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of the supplied `OracleDecimal` structure.

- [Log\(OracleDecimal, int\)](#)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

- [Log\(OracleDecimal, OracleDecimal\)](#)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Log(OracleDecimal)

This method returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of the supplied `OracleDecimal` structure.

**Declaration**

```
// C#  
public static OracleDecimal Log(OracleDecimal val);
```

**Parameters**

- *val*

An `OracleDecimal` structure whose logarithm is to be calculated.

**Return Value**

Returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of *val*.

**Exceptions**

`ArgumentOutOfRangeException` - The supplied `OracleDecimal` value is less than zero.

**Remarks**

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

If the supplied `OracleDecimal` structure has zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)



## Log(OracleDecimal, int)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

### Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val, int logBase);
```

### Parameters

- *val*  
An `OracleDecimal` structure whose logarithm is to be calculated.
- *logBase*  
An `int` that specifies the base of the logarithm.

### Return Value

A new `OracleDecimal` structure with its value set to the logarithm of *val* in the supplied base.

### Exceptions

`ArgumentOutOfRangeException` - Either argument is less than zero.

### Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

If both arguments have zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Log(OracleDecimal, OracleDecimal)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

### Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val, OracleDecimal logBase);
```

### Parameters

- *val*  
An `OracleDecimal` structure whose logarithm is to be calculated.
- *logBase*  
An `OracleDecimal` structure that specifies the base of the logarithm.

### Return Value

Returns the logarithm of *val* in the supplied base.

**Exceptions**

`ArgumentOutOfRangeException` - Either the *val* or *logBase* parameter is less than zero.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

If both arguments have zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Pow**

`Pow` returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied power.

**Overload List:**

- [Pow\(OracleDecimal, int\)](#)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` value raised to the supplied `Int32` power.
- [Pow\(OracleDecimal, OracleDecimal\)](#)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied `OracleDecimal` power.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Pow(OracleDecimal, int)**

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` value raised to the supplied `Int32` power.

**Declaration**

```
// C#  
public static OracleDecimal Pow(OracleDecimal val, int power);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.
- *power*  
An `int` value that specifies the power.

**Return Value**

An `OracleDecimal` structure.

**Remarks**

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Pow(OracleDecimal, OracleDecimal)**

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied `OracleDecimal` power.

**Declaration**

```
// C#  
public static OracleDecimal Pow(OracleDecimal val, OracleDecimal power);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.
- *power*  
An `OracleDecimal` structure that specifies the power.

**Return Value**

An `OracleDecimal` structure.

**Remarks**

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Static (Trigonometric) Methods

The `OracleDecimal` static (trigonometric) methods are listed in [Table 14–42](#).

**Table 14–42 OracleDecimal Static (Trigonometric) Methods**

Methods	Description
<a href="#">Acos</a>	Returns an angle in radians whose cosine is the supplied <code>OracleDecimal</code> structure
<a href="#">Asin</a>	Returns an angle in radians whose sine is the supplied <code>OracleDecimal</code> structure
<a href="#">Atan</a>	Returns an angle in radians whose tangent is the supplied <code>OracleDecimal</code> structure
<a href="#">Atan2</a>	Returns an angle in radians whose tangent is the quotient of the two supplied <code>OracleDecimal</code> structures
<a href="#">Cos</a>	Returns the cosine of the supplied angle in radians
<a href="#">Sin</a>	Returns the sine of the supplied angle in radians
<a href="#">Tan</a>	Returns the tangent of the supplied angle in radians
<a href="#">Cosh</a>	Returns the hyperbolic cosine of the supplied angle in radians
<a href="#">Sinh</a>	Returns the hyperbolic sine of the supplied angle in radians
<a href="#">Tanh</a>	Returns the hyperbolic tangent of the supplied angle in radians

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Acos

This method returns an angle in radians whose cosine is the supplied `OracleDecimal` structure.

### Declaration

```
// C#
public static OracleDecimal Acos(OracleDecimal val);
```

### Parameters

- *val*  
An `OracleDecimal` structure. Range is (-1 to 1).

### Return Value

An `OracleDecimal` structure that represents an angle in radians.

### Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Asin**

This method returns an angle in radians whose sine is the supplied `OracleDecimal` structure.

**Declaration**

```
// C#  
public static OracleDecimal Asin(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure. Range is (-1 to 1).

**Return Value**

An `OracleDecimal` structure that represents an angle in radians.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Atan**

This method returns an angle in radians whose tangent is the supplied `OracleDecimal` structure.

**Declaration**

```
// C#  
public static OracleDecimal Atan(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal`.

**Return Value**

An `OracleDecimal` structure that represents an angle in radians.

**Remarks**

If the argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Atan2**

This method returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures.

**Declaration**

```
// C#  
public static OracleDecimal Atan2(OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
An OracleDecimal structure that represents the y-coordinate.
- *val2*  
An OracleDecimal structure that represents the x-coordinate.

**Return Value**

An OracleDecimal structure that represents an angle in radians.

**Remarks**

If either argument has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Cos**

This method returns the cosine of the supplied angle in radians.

**Declaration**

```
// C#  
public static OracleDecimal Cos(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure that represents an angle in radians.

**Return Value**

An OracleDecimal instance.

**Exceptions**

*ArgumentOutOfRangeException* - The *val* parameter is positive or negative infinity.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Sin**

This method returns the sine of the supplied angle in radians.

**Declaration**

```
// C#  
public static OracleDecimal Sin(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure.

**Return Value**

An `OracleDecimal` structure that represents an angle in radians.

**Exceptions**

`ArgumentOutOfRangeException` - The *val* parameter is positive or negative infinity.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Tan**

This method returns the tangent of the supplied angle in radians.

**Declaration**

```
// C#  
public static OracleDecimal Tan(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure that represents an angle in radians.

**Return Value**

An `OracleDecimal` instance.

**Exceptions**

`ArgumentOutOfRangeException` - The `val` parameter is positive or negative infinity.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Cosh**

This method returns the hyperbolic cosine of the supplied angle in radians.

**Declaration**

```
// C#  
public static OracleDecimal Cosh(OracleDecimal val);
```

**Parameters**

- `val`  
An `OracleDecimal` structure that represents an angle in radians.

**Return Value**

An `OracleDecimal` instance.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Sinh**

This method returns the hyperbolic sine of the supplied angle in radians.

**Declaration**

```
// C#  
public static OracleDecimal Sinh(OracleDecimal val);
```

**Parameters**

- `val`  
An `OracleDecimal` structure that represents an angle in radians.

**Return Value**

An `OracleDecimal` instance.



**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Tanh**

This method returns the hyperbolic tangent of the supplied angle in radians.

**Declaration**

```
// C#  
public static OracleDecimal Tanh(OracleDecimal val);
```

**Parameters**

- *val*  
An `OracleDecimal` structure that represents an angle in radians.

**Return Value**

An `OracleDecimal` instance.

**Remarks**

If either argument has a null value, the returned `OracleDecimal` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Static (Comparison) Operators

The `OracleDecimal` static (comparison) operators are listed in [Table 14-43](#).

**Table 14-43 OracleDecimal Static (Comparison) Operators**

Operator	Description
<code>operator +</code>	Adds two <code>OracleDecimal</code> values
<code>operator /</code>	Divides one <code>OracleDecimal</code> value by another
<code>operator ==</code>	Determines if the two <code>OracleDecimal</code> values are equal
<code>operator &gt;</code>	Determines if the first of two <code>OracleDecimal</code> values is greater than the second
<code>operator &gt;=</code>	Determines if the first of two <code>OracleDecimal</code> values is greater than or equal to the second
<code>operator !=</code>	Determines if the two <code>OracleDecimal</code> values are not equal
<code>operator &lt;</code>	Determines if the first of two <code>OracleDecimal</code> values is less than the second
<code>operator &lt;=</code>	Determines if the first of two <code>OracleDecimal</code> values is less than or equal to the second
<code>operator *</code>	Multiplies two <code>OracleDecimal</code> structures
<code>operator -</code>	Subtracts one <code>OracleDecimal</code> structure from another
<code>operator -</code>	Negates an <code>OracleDecimal</code> structure
<code>operator %</code>	Returns a new <code>OracleDecimal</code> structure with its value set to the modulus of two <code>OracleDecimal</code> structures.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### operator +

This method adds two `OracleDecimal` values.

#### Declaration

```
// C#
public static OracleDecimal operator + (OracleDecimal val1, OracleDecimal val2);
```

#### Parameters

- `val1`  
The first `OracleDecimal`.
- `val2`  
The second `OracleDecimal`.

#### Return Value

An `OracleDecimal` structure.

**Remarks**

If either operand has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator /**

This method divides one OracleDecimal value by another.

**Declaration**

```
/ C#  
public static OracleDecimal operator / (OracleDecimal val1, OracleDecimal val2)
```

**Parameters**

- *val1*  
The first OracleDecimal.
- *val2*  
The second OracleDecimal.

**Return Value**

An OracleDecimal structure.

**Remarks**

If either operand has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator ==**

This method determines if two OracleDecimal values are equal.

**Declaration**

```
// C#  
public static bool operator == (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first OracleDecimal.
- *val2*  
The second OracleDecimal.

**Return Value**

Returns `true` if their values are equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator >**

This method determines if the first of two `OracleDecimal` values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first `OracleDecimal`.
- *val2*  
The second `OracleDecimal`.

**Return Value**

Returns `true` if the two `OracleDecimal` values are not equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator >=**

This method determines if the first of two `OracleDecimal` values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool operator >= (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first OracleDecimal.
- *val2*  
The second OracleDecimal.

**Return Value**

Returns true if the first of two OracleDecimal values is greater than or equal to the second; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator !=**

This method determines if the first of two OracleDecimal values are not equal.

**Declaration**

```
// C#  
public static bool operator != (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first OracleDecimal.
- *val2*  
The second OracleDecimal.

**Return Value**

Returns true if the two OracleDecimal values are not equal; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.

- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator <**

This method determines if the first of two `OracleDecimal` values is less than the second.

**Declaration**

```
// C#  
public static bool operator < (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first `OracleDecimal`.
- *val2*  
The second `OracleDecimal`.

**Return Value**

Returns `true` if the first of two `OracleDecimal` values is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator <=**

This method determines if the first of two `OracleDecimal` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool operator <= (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first `OracleDecimal`.

- *val2*  
The second OracleDecimal.

### Return Value

Returns `true` if the first of two OracleDecimal values is less than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## operator \*

This method multiplies two OracleDecimal structures.

### Declaration

```
// C#  
public static OracleDecimal operator * (OracleDecimal val1, OracleDecimal val2);
```

### Parameters

- *val1*  
The first OracleDecimal.
- *val2*  
The second OracleDecimal.

### Return Value

A new OracleDecimal structure.

### Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## operator -

This method subtracts one OracleDecimal structure from another.

**Declaration**

```
// C#  
public static OracleDecimal operator - (OracleDecimal val1, OracleDecimal val2);
```

**Parameters**

- *val1*  
The first OracleDecimal.
- *val2*  
The second OracleDecimal.

**Return Value**

A new OracleDecimal structure.

**Remarks**

If either operand has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator -**

This method negates the supplied OracleDecimal structure.

**Declaration**

```
// C#  
public static OracleDecimal operator - (OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal.

**Return Value**

A new OracleDecimal structure.

**Remarks**

If the supplied OracleDecimal structure has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**operator%**

This method returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures.



**Declaration**

```
// C#  
public static OracleDecimal operator % (OracleDecimal val,  
    OracleDecimal divider);
```

**Parameters**

- *val*  
An OracleDecimal.
- *divider*  
An OracleDecimal.

**Return Value**

A new OracleDecimal structure.

**Remarks**

If either operand has a null value, the returned OracleDecimal has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

The `OracleDecimal` static operators (Conversion from .NET Type to `OracleDecimal`) are listed in [Table 14–44](#).

**Table 14–44 OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)**

Operator	Description
<a href="#">implicit operator OracleDecimal</a>	Converts an instance value to an <code>OracleDecimal</code> structure (Overloaded)
<a href="#">explicit operator OracleDecimal</a>	Converts an instance value to an <code>OracleDecimal</code> structure (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### implicit operator OracleDecimal

`implicit operator OracleDecimal` returns the `OracleDecimal` representation of a value.

**Overload List:**

- [implicit operator OracleDecimal\(decimal\)](#)  
This method returns the `OracleDecimal` representation of a decimal value.
- [implicit operator OracleDecimal\(int\)](#)  
This method returns the `OracleDecimal` representation of an `int` value.
- [implicit operator OracleDecimal\(long\)](#)  
This method returns the `OracleDecimal` representation of a long value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### implicit operator OracleDecimal(decimal)

This method returns the `OracleDecimal` representation of a decimal value.

**Declaration**

```
// C#
public static implicit operator OracleDecimal(decimal val);
```

**Parameters**

- `val`  
A decimal value.

**Return Value**

An OracleDecimal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**implicit operator OracleDecimal(int)**

This method returns the OracleDecimal representation of an int value.

**Declaration**

```
// C#  
public static implicit operator OracleDecimal(int val);
```

**Parameters**

- *val*  
An int value.

**Return Value**

An OracleDecimal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**implicit operator OracleDecimal(long)**

This method returns the OracleDecimal representation of a long value.

**Declaration**

```
// C#  
public static implicit operator OracleDecimal(long val);
```

**Parameters**

- *val*  
A long value.

**Return Value**

An OracleDecimal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## explicit operator OracleDecimal

OracleDecimal returns the OracleDecimal representation of a value.

### Overload List:

- [explicit operator OracleDecimal\(double\)](#)  
This method returns the OracleDecimal representation of a double.
- [explicit operator OracleDecimal\(string\)](#)  
This method returns the OracleDecimal representation of a string.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## explicit operator OracleDecimal(double)

This method returns the OracleDecimal representation of a double.

### Declaration

```
// C#  
public static explicit operator OracleDecimal(double val);
```

### Parameters

- *val*  
A double.

### Return Value

An OracleDecimal.

### Exceptions

OverflowException - The value of the supplied double is greater than the maximum value of OracleDecimal or less than the minimum value of OracleDecimal.

### Remarks

OracleDecimal contains the following values depending on the provided double value:

- `double.PositiveInfinity`: positive infinity value
- `double.NegativeInfinity`: negative infinity value.
- `double.NaN`: null value

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**explicit operator OracleDecimal(string)**

This method returns the `OracleDecimal` representation of a string.

**Declaration**

```
// C#  
public static explicit operator OracleDecimal(string numStr);
```

**Parameters**

- *numStr*

A string that represents a numeric value.

**Return Value**

An `OracleDecimal`.

**Exceptions**

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

The `OracleDecimal` static operators (Conversion from OracleDecimal to .NET) are listed in [Table 14–45](#).

**Table 14–45 OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)**

Operator	Description
<a href="#">explicit operator byte</a>	Returns the <code>byte</code> representation of the <code>OracleDecimal</code> value
<a href="#">explicit operator decimal</a>	Returns the <code>decimal</code> representation of the <code>OracleDecimal</code> value
<a href="#">explicit operator double</a>	Returns the <code>double</code> representation of the <code>OracleDecimal</code> value
<a href="#">explicit operator short</a>	Returns the <code>short</code> representation of the <code>OracleDecimal</code> value
<a href="#">explicit operator int</a>	Returns the <code>int</code> representation of the <code>OracleDecimal</code> value
<a href="#">explicit operator long</a>	Returns the <code>long</code> representation of the <code>OracleDecimal</code> value
<a href="#">explicit operator float</a>	Returns the <code>float</code> representation of the <code>OracleDecimal</code> value

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### explicit operator byte

This method returns the `byte` representation of the `OracleDecimal` value.

**Declaration**

```
// C#
public static explicit operator byte(OracleDecimal val);
```

**Parameters**

- `val`  
An `OracleDecimal` structure.

**Return Value**

A `byte`.

**Exceptions**

`OracleNullValueException` - `OracleDecimal` has a null value.

`OverflowException`- The `byte` cannot represent the supplied `OracleDecimal` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**explicit operator decimal**

This method returns the decimal representation of the OracleDecimal value.

**Declaration**

```
// C#  
public static explicit operator decimal(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure.

**Return Value**

A decimal.

**Exceptions**

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The decimal cannot represent the supplied OracleDecimal structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**explicit operator double**

This method returns the double representation of the OracleDecimal value.

**Declaration**

```
// C#  
public static explicit operator double(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure.

**Return Value**

A double.

**Exceptions**

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The double cannot represent the supplied OracleDecimal structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### explicit operator short

This method returns the short representation of the OracleDecimal value.

**Declaration**

```
// C#  
public static explicit operator short(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure.

**Return Value**

A short.

**Exceptions**

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The short cannot represent the supplied OracleDecimal structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### explicit operator int

This method returns the int representation of the OracleDecimal value.

**Declaration**

```
// C#  
public static explicit operator int(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure.

**Return Value**

An int.

**Exceptions**

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The int cannot represent the supplied OracleDecimal structure.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**explicit operator long**

This method returns the long representation of the OracleDecimal value.

**Declaration**

```
// C#  
public static explicit operator long(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure.

**Return Value**

A long.

**Exceptions**

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The long cannot represent the supplied OracleDecimal structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**explicit operator float**

This method returns the float representation of the OracleDecimal value.

**Declaration**

```
// C#  
public static explicit operator float(OracleDecimal val);
```

**Parameters**

- *val*  
An OracleDecimal structure.

**Return Value**

A float.

**Exceptions**

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The float cannot represent the supplied OracleDecimal structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Properties

The `OracleDecimal` properties are listed in [Table 14–46](#).

**Table 14–46 OracleDecimal Properties**

Properties	Description
<a href="#">BinData</a>	Returns a byte array that represents the Oracle NUMBER in Oracle internal format
<a href="#">Format</a>	Specifies the format for <code>Tostring()</code>
<a href="#">IsInt</a>	Indicates whether or not the current instance is an integer
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">IsPositive</a>	Indicates whether or not the current instance is greater than 0
<a href="#">IsZero</a>	Indicates whether or not the current instance has a zero value
<a href="#">Value</a>	Returns a decimal value

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### BinData

This property returns a byte array that represents the Oracle NUMBER in an internal Oracle format.

**Declaration**

```
// C#
public byte[] BinData {get;}
```

**Property Value**

A byte array that represents the Oracle NUMBER in an internal Oracle format.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

### Format

This property specifies the format for `Tostring()`.

**Declaration**

```
// C#
public string Format {get; set;}
```

**Property Value**

The string which specifies the format.

**Remarks**

`Format` is used when `ToString()` is called on an instance of an `OracleDecimal`. It is useful if the `ToString()` method needs a specific currency symbol, group, or decimal separator as part of a string.

By default, this property is `null` which indicates that no special formatting is used.

The decimal and group separator characters are specified by the thread's `OracleGlobalization.NumericCharacters`.

The currency symbols are specified by the following thread properties:

- `OracleGlobalization.Currency`
- `OracleGlobalization.ISOCurrency`
- `OracleGlobalization.DualCurrency`

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**IsInt**

This property indicates whether or not the current instance is an integer value.

**Declaration**

```
// C#  
public bool IsInt {get;}
```

**Property Value**

A `bool` value that returns `true` if the current instance is an integer value; otherwise, returns `false`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**IsNull**

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#
```

```
public bool IsNull {get;}
```

### Property Value

A `bool` value that returns `true` if the current instance has a null value; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## IsPositive

This property indicates whether or not the value of the current instance is greater than 0.

### Declaration

```
// C#  
public bool IsPositive {get;}
```

### Property Value

A `bool` value that returns `true` if the current instance is greater than 0; otherwise, returns `false`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## IsZero

This property indicates whether or not the current instance has a zero value.

### Declaration

```
// C#  
public bool IsZero{get;}
```

### Property Value

A `bool` value that returns `true` if the current instance has a zero value; otherwise, returns `false`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## Value

This method returns a decimal value.

### Declaration

```
// C#  
public decimal Value {get;}
```

### Property Value

A decimal value.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

`OverflowException` - The decimal cannot represent the supplied `OracleDecimal` structure.

### Remarks

Precision can be lost when the decimal value is obtained from an `OracleDecimal`. See Remarks under "[OracleDecimal Structure](#)" on page 14-65 for further information.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## OracleDecimal Instance Methods

The `OracleDecimal` instance methods are listed in [Table 14–47](#).

**Table 14–47 OracleDecimal Instance Methods**

Method	Description
<a href="#">CompareTo</a>	Compares the current instance to the supplied object and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object is an instance of <code>OracleDecimal</code> , and whether or not the value of the object is equal to the current instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the current instance
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToByte</a>	Returns the <code>byte</code> representation of the current instance
<a href="#">ToDouble</a>	Returns the <code>double</code> representation of the current instance
<a href="#">ToInt16</a>	Returns the <code>Int16</code> representation of the current instance
<a href="#">ToInt32</a>	Returns the <code>Int32</code> representation of the current instance
<a href="#">ToInt64</a>	Returns the <code>Int64</code> representation of the current instance
<a href="#">ToSingle</a>	Returns the <code>Single</code> representation of the current instance
<a href="#">ToString</a>	Overloads <code>Object.ToString()</code> Returns the <code>string</code> representation of the current instance

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

## CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

### Declaration

```
// C#
public int CompareTo(object obj);
```

### Parameters

- *obj*  
The supplied instance.

### Return Value

The method returns a number:

- Less than zero: if the value of the current instance is less than *obj*.
- Zero: if the value of the current instance is equal to *obj*.
- Greater than zero: if the value of the current instance is greater than *obj*.

**Implements**

IComparable

**Exceptions**

ArgumentException - The parameter is not of type OracleDecimal.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between OracleDecimals. For example, comparing an OracleDecimal instance with an OracleBinary instance is not allowed. When an OracleDecimal is compared with a different type, an ArgumentException is thrown.
- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**Equals**

Overrides Object

This method determines whether or not an object is an instance of OracleDecimal, and whether or not the value of the object is equal to the current instance.

**Declaration**

```
// C#  
public override bool Equals(object obj);
```

**Parameters**

- *obj*  
An OracleDecimal instance.

**Return Value**Returns true if *obj* is an instance of OracleDecimal, and the value of *obj* is equal to the current instance; otherwise, returns false.**Remarks**

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**GetHashCode**

Overrides Object

This method returns a hash code for the current instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

Returns a hash code.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToByte**

This method returns the byte representation of the current instance.

**Declaration**

```
// C#  
public byte ToByte();
```

**Return Value**

A byte.

**Exceptions**

*OverflowException* - The byte cannot represent the current instance.

*OracleNullValueException* - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToDouble**

This method returns the double representation of the current instance.

**Declaration**

```
// C#  
public double ToDouble();
```

**Return Value**

A double.

**Exceptions**

`OverflowException` - The double cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToInt16**

This method returns the `Int16` representation of the current instance.

**Declaration**

```
// C#  
public short ToInt16();
```

**Return Value**

A short.

**Exceptions**

`OverflowException` - The short cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToInt32**

This method returns the `Int32` representation of the current instance.

**Declaration**

```
// C#  
public int ToInt32();
```

**Return Value**

An int.

**Exceptions**

`OverflowException` - The int cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToInt64**

This method returns the `Int64` representation of the current instance.

**Declaration**

```
// C#  
public long ToInt64();
```

**Return Value**

A `long`.

**Exceptions**

`OverflowException` - The `long` cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToSingle**

This method returns the `Single` representation of the current instance.

**Declaration**

```
// C#  
public float ToSingle();
```

**Return Value**

A `float`.

**Exceptions**

`OverflowException` - The `float` cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

**ToString**

Overrides `Object`

This method returns the `string` representation of the current instance.

**Declaration**

```
// C#  
public override string ToString();
```

**Return Value**

Returns the number in a string.

**Remarks**

If the current instance has a null value, the returned string is "null".

The returned value is a string representation of an `OracleDecimal` in the numeric format specified by the `Format` property.

The decimal and group separator characters are specified by the thread's `OracleGlobalization.NumericCharacters`.

The currency symbols are specified by the following thread properties:

- `OracleGlobalization.Currency`
- `OracleGlobalization.ISOCurrency`
- `OracleGlobalization.DualCurrency`

If the numeric format is not specified, an Oracle default value is used.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class" on page 10-2](#)
- ["Globalization Support" on page 3-110](#)

---

## OracleIntervalDS Structure

The `OracleIntervalDS` structure represents the Oracle `INTERVAL DAY TO SECOND` data type to be stored in or retrieved from a database. Each `OracleIntervalDS` stores a period of time in term of days, hours, minutes, seconds, and fractional seconds.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleIntervalDS`

### Declaration

```
// ADO.NET 2.0: C#
public struct OracleIntervalDS : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleIntervalDSSample
{
    static void Main()
    {
        OracleIntervalDS iDSMax = OracleIntervalDS.MaxValue;
        double totalDays = iDSMax.TotalDays;

        totalDays -= 1;
        OracleIntervalDS iDSMax_1 = new OracleIntervalDS(totalDays);

        // Calculate the difference
        OracleIntervalDS iDSDiff = iDSMax - iDSMax_1;

        // Prints "iDSDiff.ToString() = +000000000 23:59:59.999999999"
        Console.WriteLine("iDSDiff.ToString() = " + iDSDiff.ToString());
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Members](#)
- [OracleIntervalDS Constructors](#)
- [OracleIntervalDS Static Fields](#)
- [OracleIntervalDS Static Methods](#)
- [OracleIntervalDS Static Operators](#)
- [OracleIntervalDS Type Conversions](#)
- [OracleIntervalDS Properties](#)
- [OracleIntervalDS Methods](#)

## OracleIntervalDS Members

OracleIntervalDS members are listed in the following tables:

### OracleIntervalDS Constructors

OracleIntervalDS constructors are listed in [Table 14-48](#)

**Table 14-48 OracleIntervalDS Constructors**

Constructor	Description
<a href="#">OracleIntervalDS Constructors</a>	Instantiates a new instance of OracleIntervalDS structure (Overloaded)

### OracleIntervalDS Static Fields

The OracleIntervalDS static fields are listed in [Table 14-49](#).

**Table 14-49 OracleIntervalDS Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid time interval for an OracleIntervalDS structure
<a href="#">MinValue</a>	Represents the minimum valid time interval for an OracleIntervalDS structure
<a href="#">Null</a>	Represents a null value that can be assigned to an OracleIntervalDS instance
<a href="#">Zero</a>	Represents a zero value for an OracleIntervalDS structure

### OracleIntervalDS Static Methods

The OracleIntervalDS static methods are listed in [Table 14-50](#).

**Table 14-50 OracleIntervalDS Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines whether or not two OracleIntervalDS values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines whether or not one OracleIntervalDS value is greater than another
<a href="#">GreaterThanOrEqual</a>	Determines whether or not one OracleIntervalDS value is greater than or equal to another
<a href="#">LessThan</a>	Determines whether or not one OracleIntervalDS value is less than another
<a href="#">LessThanOrEqual</a>	Determines whether or not one OracleIntervalDS value is less than or equal to another
<a href="#">NotEquals</a>	Determines whether or not two OracleIntervalDS values are not equal
<a href="#">Parse</a>	Returns an OracleIntervalDS structure and sets its value for time interval using a string

**Table 14–50 (Cont.) OracleIntervalDS Static Methods**

Methods	Description
<a href="#">SetPrecision</a>	Returns a new instance of an OracleIntervalDS with the specified day precision and fractional second precision

### OracleIntervalDS Static Operators

The OracleIntervalDS static operators are listed in [Table 14–51](#).

**Table 14–51 OracleIntervalDS Static Operators**

Operator	Description
<a href="#">operator +</a>	Adds two OracleIntervalDS values
<a href="#">operator ==</a>	Determines whether or not two OracleIntervalDS values are equal
<a href="#">operator &gt;</a>	Determines whether or not one OracleIntervalDS value is greater than another
<a href="#">operator &gt;=</a>	Determines whether or not one OracleIntervalDS value is greater than or equal to another
<a href="#">operator !=</a>	Determines whether or not two OracleIntervalDS values are not equal
<a href="#">operator &lt;</a>	Determines whether or not one OracleIntervalDS value is less than another
<a href="#">operator &lt;=</a>	Determines whether or not one OracleIntervalDS value is less than or equal to another
<a href="#">operator -</a>	Subtracts one OracleIntervalDS value from another
<a href="#">operator -</a>	Negates an OracleIntervalDS structure
<a href="#">operator *</a>	Multiplies an OracleIntervalDS value by a number
<a href="#">operator /</a>	Divides an OracleIntervalDS value by a number

### OracleIntervalDS Type Conversions

The OracleIntervalDS type conversions are listed in [Table 14–52](#).

**Table 14–52 OracleIntervalDS Type Conversions**

Operator	Description
<a href="#">explicit operator TimeSpan</a>	Converts an OracleIntervalDS structure to a TimeSpan structure
<a href="#">explicit operator OracleIntervalDS</a>	Converts a string to an OracleIntervalDS structure
<a href="#">implicit operator OracleIntervalDS</a>	Converts a TimeSpan structure to an OracleIntervalDS structure

### OracleIntervalDS Properties

The OracleIntervalDS properties are listed in [Table 14–53](#).



**Table 14–53 OracleIntervalDS Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format
<a href="#">Days</a>	Gets the days component of an OracleIntervalDS
<a href="#">Hours</a>	Gets the hours component of an OracleIntervalDS
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Milliseconds</a>	Gets the milliseconds component of an OracleIntervalDS
<a href="#">Minutes</a>	Gets the minutes component of an OracleIntervalDS
<a href="#">Nanoseconds</a>	Gets the nanoseconds component of an OracleIntervalDS
<a href="#">Seconds</a>	Gets the seconds component of an OracleIntervalDS
<a href="#">TotalDays</a>	Returns the total number, in days, that represent the time period in the OracleIntervalDS structure
<a href="#">Value</a>	Specifies the time interval that is stored in the OracleIntervalDS structure

### OracleIntervalDS Methods

The OracleIntervalDS methods are listed in [Table 14–54](#).

**Table 14–54 OracleIntervalDS Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current OracleIntervalDS instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the OracleIntervalDS instance
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">ToString</a>	Converts the current OracleIntervalDS structure to a string

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)

## OracleIntervalDS Constructors

OracleIntervalDS constructors create a new instance of the OracleIntervalDS structure.

### Overload List:

- [OracleIntervalDS\(TimeSpan\)](#)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using a TimeSpan structure.
- [OracleIntervalDS\(string\)](#)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using a string that indicates a period of time.
- [OracleIntervalDS\(double\)](#)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using the total number of days.
- [OracleIntervalDS\(int, int, int, int, double\)](#)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using the supplied days, hours, minutes, seconds and milliseconds.
- [OracleIntervalDS\(int, int, int, int, int\)](#)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using the supplied days, hours, minutes, seconds, and nanoseconds.
- [OracleIntervalDS\(byte\[\]\)](#)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value to the provided byte array, which is in an internal Oracle INTERVAL DAY TO SECOND format.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### OracleIntervalDS(TimeSpan)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using a TimeSpan structure.

### Declaration

```
// C#  
public OracleIntervalDS(TimeSpan ts);
```

### Parameters

- *ts*

A TimeSpan structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**OracleIntervalDS(string)**

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using a string that indicates a period of time.

**Declaration**

```
// C#
public OracleIntervalDS(string intervalStr);
```

**Parameters**

- *intervalStr*  
A string representing the Oracle INTERVAL DAY TO SECOND.

**Exceptions**

`ArgumentException` - The *intervalStr* parameter is not in the valid format or has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

**Remarks**

The value specified in the supplied *intervalStr* must be in Day HH:MI:SSxFF format.

**Example**

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes, 4 seconds, and 990 milliseconds or 1 day, 2 hours, 3 minutes, 4 seconds, and 990000000 nanoseconds.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**OracleIntervalDS(double)**

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the total number of days.

**Declaration**

```
// C#
public OracleIntervalDS(double totalDays);
```

**Parameters**

- *totalDays*  
The supplied total number of days for a time interval. Range of days is  $-1000,000,000 < totalDays < 1000,000,000$ .

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**OracleIntervalDS(int, int, int, int, double)**

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and milliseconds.

**Declaration**

```
// C#  
public OracleIntervalDS (int days, int hours, int minutes, int seconds,  
    double milliseconds);
```

**Parameters**

- *days*  
The days provided. Range of day is (-999,999,999 to 999,999,999).
- *hours*  
The hours provided. Range of hour is (-23 to 23).
- *minutes*  
The minutes provided. Range of minute is (-59 to 59).
- *seconds*  
The seconds provided. Range of second is (-59 to 59).
- *milliseconds*  
The milliseconds provided. Range of millisecond is (- 999.999999 to 999.999999).

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

**Remarks**

The sign of all the arguments must be the same.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS(int, int, int, int, int)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and nanoseconds.

### Declaration

```
// C#
public OracleIntervalDS (int days, int hours, int minutes, int seconds,
    int nanoseconds);
```

### Parameters

- *days*  
The days provided. Range of day is (-999,999,999 to 999,999,999).
- *hours*  
The hours provided. Range of hour is (-23 to 23).
- *minutes*  
The minutes provided. Range of minute is (-59 to 59).
- *seconds*  
The seconds provided. Range of second is (-59 to 59).
- *nanoseconds*  
The nanoseconds provided. Range of nanosecond is (-999,999,999 to 999,999,999)

### Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

### Remarks

The sign of all the arguments must be the same.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS(byte[ ])

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

### Declaration

```
// C#
public OracleIntervalDS (byte[ ] bytes);
```

### Parameters

- *bytes*

A byte array that is in an internal Oracle INTERVAL DAY TO SECOND format.

### Exceptions

`ArgumentException` - *bytes* is not in internal Oracle INTERVAL DAY TO SECOND format, or *bytes* is not a valid Oracle INTERVAL DAY TO SECOND.

`ArgumentNullException` - *bytes* is null.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS Static Fields

The OracleIntervalDS static fields are listed in [Table 14–55](#).

**Table 14–55 OracleIntervalDS Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid time interval for an OracleIntervalDS structure
<a href="#">MinValue</a>	Represents the minimum valid time interval for an OracleIntervalDS structure
<a href="#">Null</a>	Represents a null value that can be assigned to an OracleIntervalDS instance
<a href="#">Zero</a>	Represents a zero value for an OracleIntervalDS structure

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### MaxValue

This static field represents the maximum value for an OracleIntervalDS structure.

#### Declaration

```
// C#
public static readonly OracleIntervalDS MaxValue;
```

#### Remarks

Maximum values:

- Day: 999999999
- hour: 23
- minute is 59
- second: 59
- nanosecond: 999999999

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### MinValue

This static field represents the minimum value for an OracleIntervalDS structure.

#### Declaration

```
// C#
public static readonly OracleIntervalDS MinValue;
```

**Remarks**

Minimum values:

- Day: -999999999
- hour: -23
- minute: -59
- second: -59
- nanosecond: -999999999

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Null**

This static field represents a null value that can be assigned to an OracleIntervalDS instance.

**Declaration**

```
// C#  
public static readonly OracleIntervalDS Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Zero**

This static field represents a zero value for an OracleIntervalDS structure.

**Declaration**

```
// C#  
public static readonly OracleIntervalDS Zero;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)



## OracleIntervalDS Static Methods

The OracleIntervalDS static methods are listed in [Table 14–56](#).

**Table 14–56 OracleIntervalDS Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines whether or not two OracleIntervalDS values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines whether or not one OracleIntervalDS value is greater than another
<a href="#">GreaterThanOrEqual</a>	Determines whether or not one OracleIntervalDS value is greater than or equal to another
<a href="#">LessThan</a>	Determines whether or not one OracleIntervalDS value is less than another
<a href="#">LessThanOrEqual</a>	Determines whether or not one OracleIntervalDS value is less than or equal to another
<a href="#">NotEquals</a>	Determines whether or not two OracleIntervalDS values are not equal
<a href="#">Parse</a>	Returns an OracleIntervalDS structure and sets its value for time interval using a string
<a href="#">SetPrecision</a>	Returns a new instance of an OracleIntervalDS with the specified day precision and fractional second precision

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## Equals

This static method determines whether or not two OracleIntervalDS values are equal.

### Declaration

```
// C#
public static bool Equals(OracleIntervalDS val1, OracleIntervalDS val2);
```

### Parameters

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

### Return Value

If the two OracleIntervalDS structures represent the same time interval, returns true; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**GreaterThan**

This static method determines whether or not the first of two `OracleIntervalDS` values is greater than the second.

**Declaration**

```
// C#
public static bool GreaterThan(OracleIntervalDS val1, OracleIntervalDS
    val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.
- *val2*  
The second `OracleIntervalDS`.

**Return Value**

Returns `true` if the first of two `OracleIntervalDS` values is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**GreaterThanOrEqual**

This static method determines whether or not the first of two `OracleIntervalDS` values is greater than or equal to the second.

**Declaration**

```
// C#
public static bool GreaterThanOrEqual(OracleIntervalDS val1,
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns true if the first of two OracleIntervalDS values is greater than or equal to the second; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**LessThan**

This static method determines whether or not the first of two OracleIntervalDS values is less than the second.

**Declaration**

```
// C#
public static bool LessThan(OracleIntervalDS val1, OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns true if the first of two OracleIntervalDS values is less than the second; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## LessThanOrEqual

This static method determines whether or not the first of two `OracleIntervalDS` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool LessThanOrEqual(OracleIntervalDS val1, OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.
- *val2*  
The second `OracleIntervalDS`.

**Return Value**

Returns `true` if the first of two `OracleIntervalDS` values is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## NotEquals

This static method determines whether or not two `OracleIntervalDS` values are not equal.

**Declaration**

```
// C#  
public static bool NotEquals(OracleIntervalDS val1, OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns true if two OracleIntervalDS values are not equal; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Parse**

This static method returns an OracleIntervalDS instance and sets its value for time interval using a string.

**Declaration**

```
// C#
public static OracleIntervalDS Parse(string intervalStr);
```

**Parameters**

- *intervalStr*  
A string representing the Oracle INTERVAL DAY TO SECOND.

**Return Value**

Returns an OracleIntervalDS instance representing the time interval from the supplied string.

**Exceptions**

ArgumentException - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

ArgumentNullException - The *intervalStr* parameter is null.

**Remarks**

The value specified in *intervalStr* must be in Day HH:MI:SSxFF format.

**Example**

"1 2 : 3 : 4 . 99" means 1 day, 2 hours, 3 minutes, 4 seconds, and 990 milliseconds or 1 day, 2 hours, 3 minutes, 4 seconds, and 990000000 nanoseconds.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**SetPrecision**

This static method returns a new instance of an `OracleIntervalDS` with the specified day precision and fractional second precision.

**Declaration**

```
// C#  
public static OracleIntervalDS SetPrecision(OracleIntervalDS value1,  
    int dayPrecision, int fracSecPrecision);
```

**Parameters**

- *value1*  
An `OracleIntervalDS` structure.
- *dayPrecision*  
The day precision provided. Range of day precision is (0 to 9).
- *fracSecPrecision*  
The fractional second precision provided. Range of fractional second precision is (0 to 9).

**Return Value**

An `OracleIntervalDS` instance.

**Exceptions**

`ArgumentOutOfRangeException` - An argument value is out of the specified range.

**Remarks**

Depending on the value specified in the supplied *dayPrecision*, 0 or more leading zeros are displayed in the string returned by `ToString()`.

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleIntervalDS` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

**Example**

The `OracleIntervalDS` with a value of "1 2 : 3 : 4 . 99" results in the string "001 2 : 3 : 4 . 99000" when `SetPrecision()` is called, with the day precision set to 3 and fractional second precision set to 5.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS Static Operators

The OracleIntervalDS static operators are listed in [Table 14–57](#).

**Table 14–57 OracleIntervalDS Static Operators**

Operator	Description
<code>operator +</code>	Adds two OracleIntervalDS values
<code>operator ==</code>	Determines whether or not two OracleIntervalDS values are equal
<code>operator &gt;</code>	Determines whether or not one OracleIntervalDS value is greater than another
<code>operator &gt;=</code>	Determines whether or not one OracleIntervalDS value is greater than or equal to another
<code>operator !=</code>	Determines whether or not two OracleIntervalDS values are not equal
<code>operator &lt;</code>	Determines whether or not one OracleIntervalDS value is less than another
<code>operator &lt;=</code>	Determines whether or not one OracleIntervalDS value is less than or equal to another
<code>operator -</code>	Subtracts one OracleIntervalDS value from another
<code>operator -</code>	Negates an OracleIntervalDS structure
<code>operator *</code>	Multiplies an OracleIntervalDS value by a number
<code>operator /</code>	Divides an OracleIntervalDS value by a number

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### operator +

This static operator adds two OracleIntervalDS values.

**Declaration**

```
// C#
public static OracleIntervalDS operator + (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

**Parameters**

- `val1`  
The first OracleIntervalDS.
- `val2`  
The second OracleIntervalDS.

**Return Value**

An OracleIntervalDS.



**Remarks**

If either argument has a null value, the returned `OracleIntervalDS` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator ==**

This static operator determines if two `OracleIntervalDS` values are equal.

**Declaration**

```
// C#
public static bool operator == (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.
- *val2*  
The second `OracleIntervalDS`.

**Return Value**

Returns `true` if the two `OracleIntervalDS` values are the same; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator >**

This static operator determines if the first of two `OracleIntervalDS` values is greater than the second.

**Declaration**

```
// C#
public static bool operator > (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns `true` if one OracleIntervalDS value is greater than another; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator >=**

This static operator determines if the first of two OracleIntervalDS values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool operator >= (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns `true` if the first of two OracleIntervalDS values is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator !=**

This static operator determines if the two `OracleIntervalDS` values are not equal.

**Declaration**

```
// C#  
public static bool operator != (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.
- *val2*  
The second `OracleIntervalDS`.

**Return Value**

Returns `true` if the two `OracleIntervalDS` values are not equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator <**

This static operator determines if the first of two `OracleIntervalDS` values is less than the second.

**Declaration**

```
// C#  
public static bool operator < (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.

- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns `true` if the first of two OracleIntervalDS values is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator <=**

This static operator determines if the first of two OracleIntervalDS values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool operator <= (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

Returns `true` if the first of two OracleIntervalDS values is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator -**

This static operator subtracts one OracleIntervalDS structure from another.

**Declaration**

```
// C#  
public static OracleIntervalDS operator - (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

**Parameters**

- *val1*  
The first OracleIntervalDS.
- *val2*  
The second OracleIntervalDS.

**Return Value**

An OracleIntervalDS structure.

**Remarks**

If either argument has a null value, the returned OracleIntervalDS structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator -**

This static operator negates the supplied OracleIntervalDS structure.

**Declaration**

```
// C#  
public static OracleIntervalDS operator - (OracleIntervalDS val);
```

**Parameters**

- *val*  
An OracleIntervalDS.

**Return Value**

An OracleIntervalDS structure.

**Remarks**

If the supplied `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator \***

This static operator multiplies an `OracleIntervalDS` value by a number.

**Declaration**

```
// C#
public static OracleIntervalDS operator * (OracleIntervalDS val1,
    int multiplier);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.
- *multiplier*  
A multiplier.

**Return Value**

A new `OracleIntervalDS` instance.

**Remarks**

If the `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**operator /**

This static operator divides an `OracleIntervalDS` value by a number.

**Declaration**

```
// C#
public static OracleIntervalDS operator / (OracleIntervalDS val1,
    int divisor);
```

**Parameters**

- *val1*  
The first `OracleIntervalDS`.
- *divisor*

A divisor.

**Return Value**

An `OracleIntervalDS` structure.

**Remarks**

If the `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS Type Conversions

The `OracleIntervalDS` type conversions are listed in [Table 14–58](#).

**Table 14–58 OracleIntervalDS Type Conversions**

Operator	Description
<a href="#">explicit operator TimeSpan</a>	Converts an <code>OracleIntervalDS</code> structure to a <code>TimeSpan</code> structure
<a href="#">explicit operator OracleIntervalDS</a>	Converts a string to an <code>OracleIntervalDS</code> structure
<a href="#">implicit operator OracleIntervalDS</a>	Converts a <code>TimeSpan</code> structure to an <code>OracleIntervalDS</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### explicit operator TimeSpan

This type conversion operator converts an `OracleIntervalDS` structure to a `TimeSpan` structure.

**Declaration**

```
// C#
public static explicit operator TimeSpan(OracleIntervalDS val);
```

**Parameters**

- *val*  
An `OracleIntervalDS` instance.

**Return Value**

A `TimeSpan` structure.

**Exceptions**

`OracleNullValueException` - The `OracleIntervalDS` structure has a null value.

**Remarks**

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### explicit operator OracleIntervalDS

This type conversion operator converts a string to an `OracleIntervalDS` structure.



**Declaration**

```
// C#
public static explicit operator OracleIntervalDS (string intervalStr);
```

**Parameters**

- *intervalStr*

A string representation of an Oracle INTERVAL DAY TO SECOND.

**Return Value**

An OracleIntervalDS structure.

**Exceptions**

*ArgumentException* - The supplied *intervalStr* parameter is not in the correct format or has an invalid value.

*ArgumentNullException* - The *intervalStr* parameter is null.

**Remarks**

The returned OracleIntervalDS structure contains the same time interval represented by the supplied *intervalStr*. The value specified in the supplied *intervalStr* must be in Day HH:MI:SSxFF format.

**Example**

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes 4 seconds and 990 milliseconds or 1 day, 2 hours, 3 minutes 4 seconds and 990000000 nanoseconds.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**implicit operator OracleIntervalDS**

This type conversion operator converts a TimeSpan structure to an OracleIntervalDS structure.

**Declaration**

```
// C#
public static implicit operator OracleIntervalDS(TimeSpan val);
```

**Parameters**

- *val*

A TimeSpan instance.

**Return Value**

An OracleIntervalDS structure.

**Remarks**

The returned OracleIntervalDS structure contains the same days, hours, seconds, and milliseconds as the supplied TimeSpan val.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS Properties

The OracleIntervalDS properties are listed in [Table 14-59](#).

**Table 14-59 OracleIntervalDS Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format
<a href="#">Days</a>	Gets the days component of an OracleIntervalDS
<a href="#">Hours</a>	Gets the hours component of an OracleIntervalDS
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Milliseconds</a>	Gets the milliseconds component of an OracleIntervalDS
<a href="#">Minutes</a>	Gets the minutes component of an OracleIntervalDS
<a href="#">Nanoseconds</a>	Gets the nanoseconds component of an OracleIntervalDS
<a href="#">Seconds</a>	Gets the seconds component of an OracleIntervalDS
<a href="#">TotalDays</a>	Returns the total number, in days, that represent the time period in the OracleIntervalDS structure
<a href="#">Value</a>	Specifies the time interval that is stored in the OracleIntervalDS structure

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## BinData

This property returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format.

### Declaration

```
// C#
public byte[] BinData {get;}
```

### Property Value

A byte array that represents an Oracle INTERVAL DAY TO SECOND in Oracle internal format.

### Exceptions

OracleNullValueException - The current instance has a null value.

**Remarks****See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Days**

This property gets the days component of an `OracleIntervalDS`.

**Declaration**

```
// C#  
public int Days {get;}
```

**Property Value**

An `int` representing the days component.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Hours**

This property gets the hours component of an `OracleIntervalDS`.

**Declaration**

```
// C#  
public int Hours {get;}
```

**Property Value**

An `int` representing the hours component.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**IsNull**

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#
```

```
public bool IsNull {get;}
```

### Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## Milliseconds

This property gets the milliseconds component of an `OracleIntervalDS`.

### Declaration

```
// C#  
public double Milliseconds {get;}
```

### Property Value

A `double` that represents milliseconds component.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## Minutes

This property gets the minutes component of an `OracleIntervalDS`.

### Declaration

```
// C#  
public int Minutes {get;}
```

### Property Value

A `int` that represents minutes component.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## Nanoseconds

This property gets the nanoseconds component of an `OracleIntervalDS`.

### Declaration

```
// C#  
public int Nanoseconds {get;}
```

### Property Value

An `int` that represents nanoseconds component.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## Seconds

This property gets the seconds component of an `OracleIntervalDS`.

### Declaration

```
// C#  
public int Seconds {get;}
```

### Property Value

An `int` that represents seconds component.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## TotalDays

This property returns the total number, in days, that represent the time period in the `OracleIntervalDS` structure.

### Declaration

```
// C#  
public double TotalDays {get;}
```

### Property Value

A `double` that represents the total number of days.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Value**

This property specifies the time interval that is stored in the `OracleIntervalDS` structure.

**Declaration**

```
// C#  
public TimeSpan Value {get;}
```

**Property Value**

A time interval.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

## OracleIntervalDS Methods

The `OracleIntervalDS` methods are listed in [Table 14–60](#).

**Table 14–60 OracleIntervalDS Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current <code>OracleIntervalDS</code> instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleIntervalDS</code> instance
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Converts the current <code>OracleIntervalDS</code> structure to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

### CompareTo

This method compares the current `OracleIntervalDS` instance to an object, and returns an integer that represents their relative values.

**Declaration**

```
// C#
public int CompareTo(object obj);
```

**Parameters**

- *obj*  
The object being compared to.

**Return Value**

The method returns:

- Less than zero: if the current `OracleIntervalDS` represents a shorter time interval than *obj*.
- Zero: if the current `OracleIntervalDS` and *obj* represent the same time interval.
- Greater than zero: if the current `OracleIntervalDS` represents a longer time interval than *obj*.

**Implements**

`IComparable`

**Exceptions**

`ArgumentException` - The *obj* parameter is not of type `OracleIntervalDS`.



**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleIntervalDS`s. For example, comparing an `OracleIntervalDS` instance with an `OracleBinary` instance is not allowed. When an `OracleIntervalDS` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**Equals**

This method determines whether or not the specified `object` has the same time interval as the current instance.

**Declaration**

```
// C#
public override bool Equals(object obj);
```

**Parameters**

- *obj*  
The specified object.

**Return Value**

Returns `true` if *obj* is of type `OracleIntervalDS` and has the same time interval as the current instance; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**GetHashCode**

Overrides `Object`

This method returns a hash code for the `OracleIntervalDS` instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

**ToString**

Overrides Object

This method converts the current OracleIntervalDS structure to a string.

**Declaration**

```
// C#  
public override string ToString();
```

**Return Value**

Returns a `string`.

**Remarks**

If the current instance has a null value, the returned string contains "null".

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

---

## OracleIntervalYM Structure

The `OracleIntervalYM` structure represents the Oracle `INTERVAL YEAR TO MONTH` data type to be stored in or retrieved from a database. Each `OracleIntervalYM` stores a period of time in years and months.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleIntervalYM`

### Declaration

```
// C#
public struct OracleIntervalYM : IComparable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleIntervalYMSample
{
    static void Main()
    {
        OracleIntervalYM iyMMax = OracleIntervalYM.MaxValue;
        double totalYears = iyMMax.TotalYears;

        totalYears -= 1;
        OracleIntervalYM iyMMax_1 = new OracleIntervalYM(totalYears);

        // Calculate the difference
        OracleIntervalYM iyMDiff = iyMMax - iyMMax_1;

        // Prints "iyMDiff.ToString() = +000000001-00"
        Console.WriteLine("iyMDiff.ToString() = " + iyMDiff.ToString());
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Members](#)
- [OracleIntervalYM Constructors](#)
- [OracleIntervalYM Static Fields](#)
- [OracleIntervalYM Static Methods](#)
- [OracleIntervalYM Static Operators](#)
- [OracleIntervalYM Type Conversions](#)
- [OracleIntervalYM Properties](#)
- [OracleIntervalYM Methods](#)

## OracleIntervalYM Members

OracleIntervalYM members are listed in the following tables:

### OracleIntervalYM Constructors

OracleIntervalYM constructors are listed in [Table 14–61](#)

**Table 14–61 OracleIntervalYM Constructors**

Constructor	Description
<a href="#">OracleIntervalYM Constructors</a>	Instantiates a new instance of OracleIntervalYM structure (Overloaded)

### OracleIntervalYM Static Fields

The OracleIntervalYM static fields are listed in [Table 14–62](#).

**Table 14–62 OracleIntervalYM Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum value for an OracleIntervalYM structure
<a href="#">MinValue</a>	Represents the minimum value for an OracleIntervalYM structure
<a href="#">Null</a>	Represents a null value that can be assigned to an OracleIntervalYM instance
<a href="#">Zero</a>	Represents a zero value for an OracleIntervalYM structure

### OracleIntervalYM Static Methods

The OracleIntervalYM static methods are listed in [Table 14–63](#).

**Table 14–63 OracleIntervalYM Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines whether or not two OracleIntervalYM values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines whether or not one OracleIntervalYM value is greater than another
<a href="#">GreaterThanOrEqual</a>	Determines whether or not one OracleIntervalYM value is greater than or equal to another
<a href="#">LessThan</a>	Determines whether or not one OracleIntervalYM value is less than another
<a href="#">LessThanOrEqual</a>	Determines whether or not one OracleIntervalYM value is less than or equal to another
<a href="#">NotEquals</a>	Determines whether two OracleIntervalYM values are not equal
<a href="#">Parse</a>	Returns an OracleIntervalYM structure and sets its value for time interval using a string

**Table 14–63 (Cont.) OracleIntervalYM Static Methods**

Methods	Description
<a href="#">SetPrecision</a>	Returns a new instance of an OracleIntervalYM with the specified year precision.

### OracleIntervalYM Static Operators

The OracleIntervalYM static operators are listed in [Table 14–64](#).

**Table 14–64 OracleIntervalYM Static Operators**

Operator	Description
<a href="#">operator +</a>	Adds two OracleIntervalYM values
<a href="#">operator ==</a>	Determines whether or not two OracleIntervalYM values are equal
<a href="#">operator &gt;</a>	Determines whether or not one OracleIntervalYM value is greater than another
<a href="#">operator &gt;=</a>	Determines whether or not one OracleIntervalYM value is greater than or equal to another
<a href="#">operator !=</a>	Determines whether two OracleIntervalYM values are not equal
<a href="#">operator &lt;</a>	Determines whether or not one OracleIntervalYM value is less than another
<a href="#">operator &lt;=</a>	Determines whether or not one OracleIntervalYM value is less than or equal to another
<a href="#">operator -</a>	Subtracts one OracleIntervalYM value from another
<a href="#">operator -</a>	Negates an OracleIntervalYM structure
<a href="#">operator *</a>	Multiplies an OracleIntervalYM value by a number
<a href="#">operator /</a>	Divides an OracleIntervalYM value by a number

### OracleIntervalYM Type Conversions

The OracleIntervalYM conversions are listed in [Table 14–65](#).

**Table 14–65 OracleIntervalYM Type Conversions**

Operator	Description
<a href="#">explicit operator long</a>	Converts an OracleIntervalYM structure to a number
<a href="#">explicit operator OracleIntervalYM</a>	Converts a string to an OracleIntervalYM structure
<a href="#">implicit operator OracleIntervalYM</a>	Converts the number of months to an OracleIntervalYM structure

### OracleIntervalYM Properties

The OracleIntervalYM properties are listed in [Table 14–66](#).

**Table 14–66 OracleIntervalYM Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in an Oracle internal format
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Months</a>	Gets the months component of an OracleIntervalYM
<a href="#">TotalYears</a>	Returns the total number, in years, that represents the period of time in the current OracleIntervalYM structure
<a href="#">Value</a>	Specifies the total number of months that is stored in the OracleIntervalYM structure
<a href="#">Years</a>	Gets the years component of an OracleIntervalYM

### OracleIntervalYM Methods

The OracleIntervalYM methods are listed in [Table 14–67](#).

**Table 14–67 OracleIntervalYM Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the OracleIntervalYM instance
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">ToString</a>	Converts the current OracleIntervalYM structure to a string

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)

## OracleIntervalYM Constructors

The `OracleIntervalYM` constructors creates a new instance of the `OracleIntervalYM` structure.

### Overload List:

- [OracleIntervalYM\(long\)](#)

This method creates a new instance of the `OracleIntervalYM` structure using the supplied total number of months for a period of time.
- [OracleIntervalYM\(string\)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the supplied string.
- [OracleIntervalYM\(double\)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the total number of years.
- [OracleIntervalYM\(int, int\)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using years and months.
- [OracleIntervalYM\(byte\[\] \)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### OracleIntervalYM(long)

This method creates a new instance of the `OracleIntervalYM` structure using the supplied total number of months for a period of time.

### Declaration

```
// C#  
public OracleIntervalYM (long totalMonths);
```

### Parameters

- *totalMonths*

The number of total months for a time interval. Range is  $-12,000,000,000 < totalMonths < 12,000,000,000$ .

### Exceptions

`ArgumentOutOfRangeException` - The *totalMonths* parameter is out of the specified range.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**OracleIntervalYM(string)**

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the supplied string.

**Declaration**

```
// C#
public OracleIntervalYM (string intervalStr);
```

**Parameters**

- *intervalStr*  
A string representing the Oracle INTERVAL YEAR TO MONTH.

**Remarks**

The value specified in the supplied *intervalStr* must be in Year-Month format.

**Exceptions**

`ArgumentException` - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

**Example**

"1-2" means 1 year and 2 months.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**OracleIntervalYM(double)**

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the total number of years.

**Declaration**

```
// C#
public OracleIntervalYM (double totalYears);
```

**Parameters**

- *totalYears*  
Number of total years. Range is  $-1,000,000,000 < totalYears > 1,000,000,000$ .

**Exceptions**

`ArgumentOutOfRangeException` - The *totalYears* parameter is out of the specified range.

`ArgumentException` - The *totalYears* parameter cannot be used to construct a valid `OracleIntervalYM`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**OracleIntervalYM(int, int)**

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using years and months.

**Declaration**

```
// C#  
public OracleIntervalYM (int years, int months);
```

**Parameters**

- *years*  
Number of years. Range of year is (-999,999,999 to 999,999,999).
- *months*  
Number of months. Range of month is (-11 to 11).

**Remarks**

The sign of all the arguments must be the same.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalYM`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**OracleIntervalYM(byte[ ])**

This method creates a new instance of the `OracleIntervalYM` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

**Declaration**

```
// C#  
public OracleIntervalYM (byte[] bytes);
```

**Parameters**

- *bytes*

A byte array that is in an internal Oracle INTERVAL YEAR TO MONTH format.

**Exceptions**

*ArgumentException* - The supplied byte array is not in an internal Oracle INTERVAL YEAR TO MONTH format or the supplied byte array has an invalid value.

*ArgumentNullException* - *bytes* is null.

**Remarks**

The supplied byte array must be in an internal Oracle INTERVAL YEAR TO MONTH format.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## OracleIntervalYM Static Fields

The `OracleIntervalYM` static fields are listed in [Table 14–68](#).

**Table 14–68** *OracleIntervalYM Static Fields*

Field	Description
<a href="#">MaxValue</a>	Represents the maximum value for an <code>OracleIntervalYM</code> structure
<a href="#">MinValue</a>	Represents the minimum value for an <code>OracleIntervalYM</code> structure
<a href="#">Null</a>	Represents a null value that can be assigned to an <code>OracleIntervalYM</code> instance
<a href="#">Zero</a>	Represents a zero value for an <code>OracleIntervalYM</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### MaxValue

This static field represents the maximum value for an `OracleIntervalYM` structure.

**Declaration**

```
// C#  
public static readonly OracleIntervalYM MaxValue;
```

**Remarks**

Year is 999999999 and Month is 11.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### MinValue

This static field represents the minimum value for an `OracleIntervalYM` structure.

**Declaration**

```
// C#  
public static readonly OracleIntervalYM MinValue;
```

**Remarks**

Year is -999999999 and Month is -11.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**Null**

This static field represents a null value that can be assigned to an `OracleIntervalYM` instance.

**Declaration**

```
// C#  
public static readonly OracleIntervalYM Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**Zero**

This static field represents a zero value for an `OracleIntervalYM` structure.

**Declaration**

```
// C#  
public static readonly OracleIntervalDS Zero;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## OracleIntervalYM Static Methods

The `OracleIntervalYM` static methods are listed in [Table 14–69](#).

**Table 14–69 OracleIntervalYM Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines whether or not two <code>OracleIntervalYM</code> values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines whether or not one <code>OracleIntervalYM</code> value is greater than another
<a href="#">GreaterThanOrEqual</a>	Determines whether or not one <code>OracleIntervalYM</code> value is greater than or equal to another
<a href="#">LessThan</a>	Determines whether or not one <code>OracleIntervalYM</code> value is less than another
<a href="#">LessThanOrEqual</a>	Determines whether or not one <code>OracleIntervalYM</code> value is less than or equal to another
<a href="#">NotEquals</a>	Determines whether two <code>OracleIntervalYM</code> values are not equal
<a href="#">Parse</a>	Returns an <code>OracleIntervalYM</code> structure and sets its value for time interval using a string
<a href="#">SetPrecision</a>	Returns a new instance of an <code>OracleIntervalYM</code> with the specified year precision.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## Equals

This static method determines whether or not two `OracleIntervalYM` values are equal.

### Declaration

```
// C#
public static bool Equals(OracleIntervalYM val1, OracleIntervalYM val2);
```

### Parameters

- *val1*  
An `OracleIntervalYM` structure.
- *val2*  
An `OracleIntervalYM` structure.

### Return Value

Returns `true` if two `OracleIntervalYM` values represent the same time interval, otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## GreaterThan

This static method determines whether or not the first of two `OracleIntervalYM` values is greater than the second.

### Declaration

```
// C#  
public static bool GreaterThan(OracleIntervalYM val1, OracleIntervalYM val2);
```

### Parameters

- *val1*  
The first `OracleIntervalYM`.
- *val2*  
The second `OracleIntervalYM`.

### Return Value

Returns `true` if the first of two `OracleIntervalYM` values is greater than the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## GreaterThanOrEqual

This static method determines whether or not the first of two `OracleIntervalYM` values is greater than or equal to the second.

### Declaration

```
// C#
```

```
public static bool GreaterThanOrEqualTo(OracleIntervalYM val1,  
    OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first OracleIntervalYM.
- *val2*  
The second OracleIntervalYM.

**Return Value**

Returns `true` if the first of two OracleIntervalYM values is greater than or equal to the second; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## LessThan

This static method determines whether or not the first of two OracleIntervalYM values is less than the second.

**Declaration**

```
// C#  
public static bool LessThan(OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first OracleIntervalYM.
- *val2*  
The second OracleIntervalYM.

**Return Value**

Returns `true` if the first of two OracleIntervalYM values is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.



- Two `OracleIntervalYM`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## LessThanOrEqual

This static method determines whether or not the first of two `OracleIntervalYM` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool LessThanOrEqual(OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalYM`.
- *val2*  
The second `OracleIntervalYM`.

**Return Value**

Returns `true` if the first of two `OracleIntervalYM` values is less than or equal to the second. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYM`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## NotEquals

This static method determines whether two `OracleIntervalYM` values are not equal.

**Declaration**

```
// C#  
public static bool NotEquals(OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalYM`.

- *val2*  
The second OracleIntervalYM.

**Return Value**

Returns `true` if two OracleIntervalYM values are not equal. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**Parse**

This static method returns an OracleIntervalYM structure and sets its value for time interval using a string.

**Declaration**

```
// C#  
public static OracleIntervalYM Parse (string intervalStr);
```

**Parameters**

- *intervalStr*  
A string representing the Oracle INTERVAL YEAR TO MONTH.

**Return Value**

Returns an OracleIntervalYM structure.

**Exceptions**

*ArgumentException* - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

*ArgumentNullException* - The *intervalStr* parameter is null.

**Remarks**

The value specified in the supplied *intervalStr* must be in the Year-Month format.

**Example**

"1-2" means 1 year and 2 months.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## SetPrecision

This static method returns a new instance of an `OracleIntervalYM` with the specified year precision.

**Declaration**

```
// C#  
public static OracleIntervalYM SetPrecision(OracleIntervalYM value1,  
    int yearPrecision);
```

**Parameters**

- *value1*  
An `OracleIntervalYM` structure.
- *yearPrecision*  
The year precision provided. Range of year precision is (0 to 9).

**Return Value**

An `OracleIntervalDS` instance.

**Exceptions**

`ArgumentOutOfRangeException` - *yearPrecision* is out of the specified range.

**Remarks**

Depending on the value specified in the supplied *yearPrecision*, 0 or more leading zeros are displayed in the string returned by `ToString()`.

**Example**

An `OracleIntervalYM` with a value of "1-2" results in the string "001-2" when `SetPrecision()` is called with the year precision set to 3.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## OracleIntervalYM Static Operators

The OracleIntervalYM static operators are listed in [Table 14–70](#).

**Table 14–70 OracleIntervalYM Static Operators**

Operator	Description
<code>operator +</code>	Adds two OracleIntervalYM values
<code>operator ==</code>	Determines whether or not two OracleIntervalYM values are equal
<code>operator &gt;</code>	Determines whether or not one OracleIntervalYM value is greater than another
<code>operator &gt;=</code>	Determines whether or not one OracleIntervalYM value is greater than or equal to another
<code>operator !=</code>	Determines whether two OracleIntervalYM values are not equal
<code>operator &lt;</code>	Determines whether or not one OracleIntervalYM value is less than another
<code>operator &lt;=</code>	Determines whether or not one OracleIntervalYM value is less than or equal to another
<code>operator -</code>	Subtracts one OracleIntervalYM value from another
<code>operator -</code>	Negates an OracleIntervalYM structure
<code>operator *</code>	Multiplies an OracleIntervalYM value by a number
<code>operator /</code>	Divides an OracleIntervalYM value by a number

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### operator +

This static operator adds two OracleIntervalYM values.

**Declaration**

```
// C#
public static OracleIntervalYM operator + (OracleIntervalYM val1,
    OracleIntervalYM val2);
```

**Parameters**

- `val1`  
The first OracleIntervalYM.
- `val2`  
The second OracleIntervalYM.

**Return Value**

OracleIntervalYM

**Remarks**

If either argument has a null value, the returned `OracleIntervalYM` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**operator ==**

This static operator determines if two `OracleIntervalYM` values are equal.

**Declaration**

```
// C#  
public static bool operator == (OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalYM`.
- *val2*  
The second `OracleIntervalYM`.

**Return Value**

Returns `true` if they are equal; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**operator >**

This static operator determines if the first of two `OracleIntervalYM` values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalYM`.

- *val2*  
The second OracleIntervalYM.

**Return Value**

Returns `true` if one OracleIntervalYM value is greater than another; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**operator >=**

This static operator determines if the first of two OracleIntervalYM values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool operator >= (OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first OracleIntervalYM.
- *val2*  
The second OracleIntervalYM.

**Return Value**

Returns `true` if one OracleIntervalYM value is greater than or equal to another; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## operator !=

This static operator determines whether two `OracleIntervalYM` values are not equal.

### Declaration

```
// C#  
public static bool operator != (OracleIntervalYM val1, OracleIntervalYM val2)
```

### Parameters

- *val1*  
The first `OracleIntervalYM`.
- *val2*  
The second `OracleIntervalYM`.

### Return Value

Returns `true` if two `OracleIntervalYM` values are not equal; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## operator <

This static operator determines if the first of two `OracleIntervalYM` values is less than the second.

### Declaration

```
// C#  
public static bool operator < (OracleIntervalYM val1, OracleIntervalYM val2);
```

### Parameters

- *val1*  
The first `OracleIntervalYM`.
- *val2*  
The second `OracleIntervalYM`.

### Return Value

Returns `true` if the first of two `OracleIntervalYM` values is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**operator <=**

This static operator determines if the first of two `OracleIntervalYM` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool operator <= (OracleIntervalYM val1, OracleIntervalYM val2);
```

**Parameters**

- *val1*  
The first `OracleIntervalYM`.
- *val2*  
The second `OracleIntervalYM`.

**Return Value**

Returns `true` if the first of two `OracleIntervalYM` values is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**operator -**

This static operator subtracts one `OracleIntervalYM` structure from another.

**Declaration**

```
// C#  
public static OracleIntervalYM operator - (OracleIntervalYM val1, OracleIntervalYM
```



```
val2);
```

### Parameters

- *val1*  
The first OracleIntervalYM.
- *val2*  
The second OracleIntervalYM.

### Return Value

An OracleIntervalYM structure.

### Remarks

If either argument has a null value, the returned OracleIntervalYM structure has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## operator -

This static operator negates an OracleIntervalYM structure.

### Declaration

```
// C#
public static OracleIntervalYM operator - (OracleIntervalYM val);
```

### Parameters

- *val*  
An OracleIntervalYM.

### Return Value

An OracleIntervalYM structure.

### Remarks

If the supplied OracleIntervalYM structure has a null value, the returned OracleIntervalYM structure has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## operator \*

This static operator multiplies an OracleIntervalYM value by a number.

**Declaration**

```
// C#  
public static OracleIntervalYM operator * (OracleIntervalYM val1, int multiplier);
```

**Parameters**

- *val1*  
The first OracleIntervalYM.
- *multiplier*  
A multiplier.

**Return Value**

An OracleIntervalYM structure.

**Remarks**

If the supplied OracleIntervalYM structure has a null value, the returned OracleIntervalYM structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**operator /**

This static operator divides an OracleIntervalYM value by a number.

**Declaration**

```
// C#  
public static OracleIntervalYM operator / (OracleIntervalYM val1, int divisor);
```

**Parameters**

- *val1*  
The first OracleIntervalYM.
- *divisor*  
A divisor.

**Return Value**

An OracleIntervalYM structure.

**Remarks**

If the supplied OracleIntervalYM structure has a null value, the returned OracleIntervalYM structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## OracleIntervalYM Type Conversions

The OracleIntervalYM conversions are listed in [Table 14-71](#).

**Table 14-71 OracleIntervalYM Type Conversions**

Operator	Description
<a href="#">explicit operator long</a>	Converts an OracleIntervalYM structure to a number
<a href="#">explicit operator OracleIntervalYM</a>	Converts a string to an OracleIntervalYM structure
<a href="#">implicit operator OracleIntervalYM</a>	Converts the number of months to an OracleIntervalYM structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### explicit operator long

This type conversion operator converts an OracleIntervalYM to a number that represents the number of months in the time interval.

**Declaration**

```
// C#
public static explicit operator long (OracleIntervalYM val);
```

**Parameters**

- *val*  
An OracleIntervalYM structure.

**Return Value**

A long number in months.

**Exceptions**

OracleNullValueException - The OracleIntervalYM structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### explicit operator OracleIntervalYM

This type conversion operator converts the string *intervalStr* to an OracleIntervalYM structure.

**Declaration**

```
// C#  
public static explicit operator OracleIntervalYM (string intervalStr);
```

**Parameters**

- *intervalStr*

A string representation of an Oracle INTERVAL YEAR TO MONTH.

**Return Value**

An OracleIntervalYM structure.

**Exceptions**

*ArgumentException* - The supplied *intervalStr* parameter is not in the correct format or has an invalid value.

*ArgumentNullException* - The *intervalStr* parameter is null.

**Remarks**

The returned OracleIntervalDS structure contains the same time interval represented by the supplied *intervalStr*. The value specified in the supplied *intervalStr* must be in Year-Month format.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**implicit operator OracleIntervalYM**

This type conversion operator converts the total number of months as time interval to an OracleIntervalYM structure.

**Declaration**

```
// C#  
public static implicit operator OracleIntervalYM (long months);
```

**Parameters**

- *months*

The number of months to be converted. Range is  $(-999,999,999 * 12) - 11 \leq months \leq (999,999,999 * 12) + 11$ .

**Return Value**

An OracleIntervalYM structure.

**Exceptions**

*ArgumentOutOfRangeException* - The *months* parameter is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## OracleIntervalYM Properties

The `OracleIntervalYM` properties are listed in [Table 14-72](#).

**Table 14-72 OracleIntervalYM Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents the Oracle <code>INTERVAL YEAR TO MONTH</code> in an Oracle internal format
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Months</a>	Gets the months component of an <code>OracleIntervalYM</code>
<a href="#">TotalYears</a>	Returns the total number, in years, that represents the period of time in the current <code>OracleIntervalYM</code> structure
<a href="#">Value</a>	Specifies the total number of months that is stored in the <code>OracleIntervalYM</code> structure
<a href="#">Years</a>	Gets the years component of an <code>OracleIntervalYM</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### BinData

This property returns an array of bytes that represents the Oracle `INTERVAL YEAR TO MONTH` in Oracle internal format.

**Declaration**

```
// C#
public byte[] BinData {get;}
```

**Property Value**

A byte array that represents an Oracle `INTERVAL YEAR TO MONTH` in Oracle internal format.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

### IsNull

This property indicates whether or not the value has a null value.

**Declaration**

```
// C#
```

```
public bool IsNull {get;}
```

### Property Value

Returns `true` if value has a null value; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## Months

This property gets the months component of an `OracleIntervalYM`.

### Declaration

```
// C#  
public int Months {get;}
```

### Property Value

An `int` representing the months component.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## TotalYears

This property returns the total number, in years, that represents the period of time in the current `OracleIntervalYM` structure.

### Declaration

```
// C#  
public double TotalYears {get;}
```

### Property Value

A `double` representing the total number of years.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## Value

This property gets the total number of months that is stored in the OracleIntervalYM structure.

### Declaration

```
// C#  
public long Value {get;}
```

### Property Value

The total number of months representing the time interval.

### Exceptions

OracleNullValueException - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## Years

This property gets the years component of an OracleIntervalYM.

### Declaration

```
// C#  
public int Years {get;}
```

### Property Value

An int representing the years component.

### Exceptions

OracleNullValueException - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)



## OracleIntervalYM Methods

The `OracleIntervalYM` methods are listed in [Table 14–73](#).

**Table 14–73 OracleIntervalYM Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current <code>OracleIntervalYM</code> instance to the supplied object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleIntervalYM</code> instance
<code>GetType</code>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Converts the current <code>OracleIntervalYM</code> structure to a string

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## CompareTo

This method compares the current `OracleIntervalYM` instance to the supplied object, and returns an integer that represents their relative values.

### Declaration

```
// C#
public int CompareTo(object obj);
```

### Parameters

- *obj*  
The supplied object.

### Return Value

The method returns a number:

Less than zero: if the current `OracleIntervalYM` represents a shorter time interval than *obj*.

Zero: if the current `OracleIntervalYM` and *obj* represent the same time interval.

Greater than zero: if the current `OracleIntervalYM` represents a longer time interval than *obj*.

### Implements

`Comparable`

### Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleIntervalYM`.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleIntervalYM`s. For example, comparing an `OracleIntervalYM` instance with an `OracleBinary` instance is not allowed. When an `OracleIntervalYM` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYM`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**Equals**

Overrides `Object`

This method determines whether or not the specified object has the same time interval as the current instance.

**Declaration**

```
// C#  
public override bool Equals(object obj);
```

**Parameters**

- *obj*  
The supplied object.

**Return Value**

Returns `true` if the specified object instance is of type `OracleIntervalYM` and has the same time interval; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYM`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**GetHashCode**

Overrides `Object`

This method returns a hash code for the `OracleIntervalYM` instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

An int representing a hash code.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

**ToString**

Overrides Object

This method converts the current OracleIntervalYM structure to a string.

**Declaration**

```
// C#  
public override string ToString();
```

**Return Value**

A string that represents the current OracleIntervalYM structure.

**Remarks**

If the current instance has a null value, the returned string contain "null".

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

## OracleString Structure

The `OracleString` structure represents a variable-length stream of characters to be stored in or retrieved from a database.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleString`

### Declaration

```
// ADO.NET 2.0: C#
```

```
public struct OracleString : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#
```

```
using System;
```

```
using Oracle.DataAccess.Types;
```

```
class OracleStringSample
```

```
{
```

```
    static void Main()
```

```
    {
```

```
        // Initialize OracleString structs
```

```
        OracleString string1 = new OracleString("AAA");
```

```
        // Display the string "AAA"
```

```
        Console.WriteLine("{0} has length of {1}", string1, string1.Length);
```

```
        // Contatenate characters to string1 until the length is 5
```

```
        while (string1.Length < 5)
```

```
            string1 = OracleString.Concat(string1, "a");
```

```
        // Display the string of "AAAAa"
```

```
        Console.WriteLine("{0} has length of {1}", string1, string1.Length);
```

```
    }
```

```
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Members](#)
- [OracleString Constructors](#)
- [OracleString Static Fields](#)
- [OracleString Static Methods](#)
- [OracleString Static Operators](#)
- [OracleString Type Conversions](#)
- [OracleString Properties](#)
- [OracleString Methods](#)

## OracleString Members

OracleString members are listed in the following tables:

### OracleString Constructors

OracleString constructors are listed in [Table 14-74](#)

**Table 14-74 OracleString Constructors**

Constructor	Description
<a href="#">OracleString Constructors</a>	Instantiates a new instance of OracleString structure (Overloaded)

### OracleString Static Fields

The OracleString static fields are listed in [Table 14-75](#).

**Table 14-75 OracleString Static Fields**

Field	Description
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleString structure

### OracleString Static Methods

The OracleString static methods are listed in [Table 14-76](#).

**Table 14-76 OracleString Static Methods**

Methods	Description
<a href="#">Concat</a>	Concatenates two OracleString instances and returns a new OracleString instance that represents the result
<a href="#">Equals</a>	Determines if two OracleString values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines whether or not the first of two OracleString values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines whether or not the first of two OracleString values is greater than or equal to the second
<a href="#">LessThan</a>	Determines whether or not the first of two OracleString values is less than the second
<a href="#">LessThanOrEqual</a>	Determines whether or not the first of two OracleString values is less than or equal to the second
<a href="#">NotEquals</a>	Determines whether two OracleString values are not equal

### OracleString Static Operators

The OracleString static operators are listed in [Table 14-77](#).

**Table 14–77 OracleString Static Operators**

Operator	Description
<a href="#">operator +</a>	Concatenates two <code>OracleString</code> values
<a href="#">operator ==</a>	Determines if two <code>OracleString</code> values are equal
<a href="#">operator &gt;</a>	Determines if the first of two <code>OracleString</code> values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two <code>OracleString</code> values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if the two <code>OracleString</code> values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two <code>OracleString</code> values is less than the second
<a href="#">operator &lt;=</a>	Determines if two <code>OracleString</code> values are not equal

### OracleString Type Conversions

The `OracleString` type conversions are listed in [Table 14–78](#).

**Table 14–78 OracleString Type Conversions**

Operator	Description
<a href="#">explicit operator string</a>	Converts the supplied <code>OracleString</code> to a <code>string</code> instance
<a href="#">implicit operator OracleString</a>	Converts the supplied <code>string</code> to an <code>OracleString</code> instance

### OracleString Properties

The `OracleString` properties are listed in [Table 14–79](#).

**Table 14–79 OracleString Properties**

Properties	Description
<a href="#">IsCaseIgnored</a>	Indicates whether or not case should be ignored when performing string comparison
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Item</a>	Obtains the particular character in an <code>OracleString</code> using an index.
<a href="#">Length</a>	Returns the length of the <code>OracleString</code>

### OracleString Methods

The `OracleString` methods are listed in [Table 14–80](#).

**Table 14–80 OracleString Methods**

Methods	Description
<a href="#">Clone</a>	Returns a copy of the current <code>OracleString</code> instance

**Table 14–80 (Cont.) OracleString Methods**

Methods	Description
<a href="#">CompareTo</a>	Compares the current <code>OracleString</code> instance to the supplied object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same string value as the current <code>OracleString</code> structure (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleString</code> instance
<a href="#">GetNonUnicodeBytes</a>	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in the client character set format
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">GetUnicodeBytes</a>	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in Unicode format
<a href="#">ToString</a>	Converts the current <code>OracleString</code> instance to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)



## OracleString Constructors

The `OracleString` constructors create new instances of the `OracleString` structure.

### Overload List:

- [OracleString\(string\)](#)  
This constructor creates a new instance of the `OracleString` structure and sets its value using a string.
- [OracleString\(string, bool\)](#)  
This constructor creates a new instance of the `OracleString` structure and sets its value using a string and specifies if case is ignored in comparison.
- [OracleString\(byte \[ \], bool\)](#)  
This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies if the supplied byte array is Unicode encoded.
- [OracleString\(byte \[ \], bool, bool\)](#)  
This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies the following: if the supplied byte array is Unicode encoded and if case is ignored in comparison.
- [OracleString\(byte \[ \], int, int, bool\)](#)  
This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, and if the supplied byte array is Unicode encoded.
- [OracleString\(byte \[ \], int, int, bool, bool\)](#)  
This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, if the supplied byte array is Unicode encoded, and if case is ignored in comparison.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

### OracleString(string)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string.

### Declaration

```
// C#
public OracleString(string data);
```

### Parameters

- *data*

A string value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

### OracleString(string, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string and specifies if case is ignored in comparison.

**Declaration**

```
// C#  
public OracleString(string data, bool isCaseIgnored);
```

**Parameters**

- *data*

A string value.

- *isCaseIgnored*

Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

### OracleString(byte [ ], bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies if the supplied byte array is Unicode encoded.

**Declaration**

```
// C#  
public OracleString(byte[] data, bool fUnicode);
```

**Parameters**

- *data*

Byte array data for the new `OracleString`.

- *fUnicode*

Specifies if the supplied data is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.

**Exceptions**

`ArgumentNullException` - The *data* parameter is null.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**OracleString(byte [ ], bool, bool)**

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies the following: if the supplied byte array is Unicode encoded and if case is ignored in comparison.

**Declaration**

```
// C#  
public OracleString(byte[] data, bool fUnicode, bool isCaseIgnored);
```

**Parameters**

- *data*  
Byte array data for the new `OracleString`.
- *fUnicode*  
Specifies if the supplied *data* is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.
- *isCaseIgnored*  
Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.

**Exceptions**

`ArgumentNullException` - The *data* parameter is null.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**OracleString(byte [ ], int, int, bool)**

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, and if the supplied byte array is Unicode encoded.

**Declaration**

```
// C#  
public OracleString(byte[] data, int index, int count, bool fUnicode);
```

**Parameters**

- *data*  
Byte array data for the new `OracleString`.
- *index*

The starting index to copy from *data*.

- *count*

The number of bytes to copy.

- *fUnicode*

Specifies if the supplied data is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.

### Exceptions

`ArgumentNullException` - The *data* parameter is null.

`ArgumentOutOfRangeException` - The *count* parameter is less than zero.

`IndexOutOfRangeException` - The *index* parameter is greater than or equal to the length of *data* or less than zero.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## OracleString(byte [, ], int, int, bool, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, if the supplied byte array is Unicode encoded, and if case is ignored in comparison.

### Declaration

```
// C#
public OracleString(byte[] data, int index, int count, bool fUnicode,
    bool isCaseIgnored);
```

### Parameters

- *data*

Byte array data for the new `OracleString`.

- *index*

The starting index to copy from *data*.

- *count*

The number of bytes to copy.

- *fUnicode*

Specifies if the supplied data is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.

- *isCaseIgnored*

Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.

### Exceptions

`ArgumentNullException` - The *data* parameter is null.

`ArgumentOutOfRangeException` - The *count* parameter is less than zero.

`IndexOutOfRangeException` - The *index* parameter is greater than or equal to the length of *data* or less than zero.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## OracleString Static Fields

The `OracleString` static fields are listed in [Table 14–81](#).

**Table 14–81** *OracleString Static Fields*

Field	Description
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the <code>OracleString</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

### Null

This static field represents a null value that can be assigned to an instance of the `OracleString` structure.

**Declaration**

```
// C#  
public static readonly OracleString Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

## OracleString Static Methods

The `OracleString` static methods are listed in [Table 14–82](#).

**Table 14–82 OracleString Static Methods**

Methods	Description
<a href="#">Concat</a>	Concatenates two <code>OracleString</code> instances and returns a new <code>OracleString</code> instance that represents the result
<a href="#">Equals</a>	Determines if two <code>OracleString</code> values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines whether or not the first of two <code>OracleString</code> values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines whether or not the first of two <code>OracleString</code> values is greater than or equal to the second
<a href="#">LessThan</a>	Determines whether or not the first of two <code>OracleString</code> values is less than the second
<a href="#">LessThanOrEqual</a>	Determines whether or not the first of two <code>OracleString</code> values is less than or equal to the second
<a href="#">NotEquals</a>	Determines whether two <code>OracleString</code> values are not equal

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

## Concat

This static method concatenates two `OracleString` instances and returns a new `OracleString` instance that represents the result.

### Declaration

```
// C#
public static OracleString Concat(OracleString str1, OracleString str2);
```

### Parameters

- *str1*  
The first `OracleString`.
- *str2*  
The second `OracleString`.

### Return Value

An `OracleString`.

### Remarks

If either argument has a null value, the returned `OracleString` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## Equals

Overloads `Object`

This static method determines whether or not the two `OracleStrings` being compared are equal.

**Declaration**

```
// C#  
public static bool Equals(OracleString str1, OracleString str2);
```

**Parameters**

- *str1*  
The first `OracleString`.
- *str2*  
The second `OracleString`.

**Return Value**

Returns `true` if the two `OracleStrings` being compared are equal; returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## GreaterThan

This static method determines whether or not the first of two `OracleString` values is greater than the second.

**Declaration**

```
// C#  
public static bool GreaterThan(OracleString str1, OracleString str2);
```

**Parameters**

- *str1*  
The first `OracleString`.



- *str2*  
The second `OracleString`.

### Return Value

Returns `true` if the first of two `OracleStrings` is greater than the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## GreaterThanOrEqual

This static method determines whether or not the first of two `OracleString` values is greater than or equal to the second.

### Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleString str1,  
    OracleString str2);
```

### Parameters

- *str1*  
The first `OracleString`.
- *str2*  
The second `OracleString`.

### Return Value

Returns `true` if the first of two `OracleStrings` is greater than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## LessThan

This static method determines whether or not the first of two `OracleString` values is less than the second.

**Declaration**

```
// C#  
public static bool LessThan(OracleString str1, OracleString str2);
```

**Parameters**

- *str1*  
The first `OracleString`.
- *str2*  
The second `OracleString`.

**Return Value**

Returns `true` if the first is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## LessThanOrEqual

This static method determines whether or not the first of two `OracleString` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool LessThanOrEqual(OracleString str1, OracleString str2);
```

**Parameters**

- *str1*  
The first `OracleString`.
- *str2*

The second `OracleString`.

**Return Value**

Returns `true` if the first is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## NotEquals

This static method determines whether two `OracleString` values are not equal.

**Declaration**

```
// C#  
public static bool NotEquals(OracleString str1, OracleString str2);
```

**Parameters**

- *str1*  
The first `OracleString`.
- *str2*  
The second `OracleString`.

**Return Value**

Returns `true` if the two `OracleString` instances are not equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## OracleString Static Operators

The `OracleString` static operators are listed in [Table 14–83](#).

**Table 14–83** *OracleString Static Operators*

Operator	Description
<code>operator +</code>	Concatenates two <code>OracleString</code> values
<code>operator ==</code>	Determines if two <code>OracleString</code> values are equal
<code>operator &gt;</code>	Determines if the first of two <code>OracleString</code> values is greater than the second
<code>operator &gt;=</code>	Determines if the first of two <code>OracleString</code> values is greater than or equal to the second
<code>operator !=</code>	Determines if the two <code>OracleString</code> values are not equal
<code>operator &lt;</code>	Determines if the first of two <code>OracleString</code> values is less than the second
<code>operator &lt;=</code>	Determines if two <code>OracleString</code> values are not equal

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

### `operator +`

This static operator concatenates two `OracleString` values.

**Declaration**

```
// C#
public static OracleString operator + (OracleString value1, OracleString value2);
```

**Parameters**

- *value1*  
The first `OracleString`.
- *value2*  
The second `OracleString`.

**Return Value**

An `OracleString`.

**Remarks**

If either argument has a null value, the returned `OracleString` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**operator ==**

This static operator determines if two `OracleString` values are equal.

**Declaration**

```
// C#  
public static bool operator == (OracleString value1, OracleString value2);
```

**Parameters**

- *value1*  
The first `OracleString`.
- *value2*  
The second `OracleString`.

**Return Value**

Returns `true` if two `OracleString` values are equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**operator >**

This static operator determines if the first of two `OracleString` values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleString value1, OracleString value2);
```

**Parameters**

- *value1*  
The first `OracleString`.
- *value2*  
The second `OracleString`.

**Return Value**

Returns `true` if the first of two `OracleString` values is greater than the second; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**operator >=**

This static operator determines if the first of two `OracleString` values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool operator >= (OracleString value1, OracleString value2);
```

**Parameters**

- *value1*  
The first `OracleString`.
- *value2*  
The second `OracleString`.

**Return Value**

Returns `true` if the first of two `OracleString` values is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**operator !=**

This static operator determines if two `OracleString` values are not equal.

**Declaration**

```
// C#
public static bool operator != (OracleString value1, OracleString value2);
```

**Parameters**

- *value1*  
The first OracleString.
- *value2*  
The second OracleString.

**Return Value**

Returns true if two OracleString values are not equal; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleString that has a value is greater than an OracleString that has a null value.
- Two OracleStrings that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

**operator <**

This static operator determines if the first of two OracleStrings is less than the second.

**Declaration**

```
// C#
public static bool operator < (OracleString value1, OracleString value2);
```

**Parameters**

- *value1*  
The first OracleString.
- *value2*  
The second OracleString.

**Return Value**

Returns true if the first of two OracleStrings is less than the second; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleString that has a value is greater than an OracleString has a null value.

- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**operator <=**

This static operator determines if the first of two `OracleString` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool operator <= (OracleString value1, OracleString value1);
```

**Parameters**

- *value1*  
The first `OracleString`.
- *value2*  
The second `OracleString`.

**Return Value**

Returns `true` if the first of two `OracleString` values is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)



## OracleString Type Conversions

The `OracleString` type conversions are listed in [Table 14–84](#).

**Table 14–84 OracleString Type Conversions**

Operator	Description
<a href="#">explicit operator string</a>	Converts the supplied <code>OracleString</code> to a <code>string</code> instance
<a href="#">implicit operator OracleString</a>	Converts the supplied <code>string</code> to an <code>OracleString</code> instance

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

### explicit operator string

This type conversion operator converts the supplied `OracleString` to a `string`.

**Declaration**

```
//C#
public static explicit operator string (OracleString value1);
```

**Parameters**

- *value1*  
The supplied `OracleString`.

**Return Value**

`string`

**Exceptions**

`OracleNullValueException` - The `OracleString` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

### implicit operator OracleString

This type conversion operator converts the supplied `string` to an `OracleString`.

**Declaration**

```
// C#
public static implicit operator OracleString (string value1);
```

**Parameters**

- *value1*

The supplied string.

**Return Value**

An `OracleString`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## OracleString Properties

The `OracleString` properties are listed in [Table 14–85](#).

**Table 14–85** *OracleString Properties*

Properties	Description
<a href="#">IsCaseIgnored</a>	Indicates whether or not case should be ignored when performing string comparison
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Item</a>	Obtains the particular character in an <code>OracleString</code> using an index.
<a href="#">Length</a>	Returns the length of the <code>OracleString</code>

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

## IsCaseIgnored

This property indicates whether or not case should be ignored when performing string comparison.

### Declaration

```
//C#
public bool IsCaseIgnored {get;set;}
```

### Property Value

Returns `true` if string comparison must ignore case; otherwise `false`.

### Remarks

Default value is `true`.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class IsCaseIgnoredSample
{
    static void Main()
    {
        OracleString string1 = new OracleString("aAaAa");
        OracleString string2 = new OracleString("AaAaA");

        // Ignore case for comparisons
        string1.IsCaseIgnored = true;
        string2.IsCaseIgnored = true;

        // Same; Prints 0
        Console.WriteLine(string1.CompareTo(string2));
    }
}
```

```
// Make comparisons case sensitive
// Note that IsCaseIgnored must be set to false for both
//   OracleStrings; otherwise an exception is thrown
string1.IsCaseIgnored = false;
string2.IsCaseIgnored = false;

// Different; Prints nonzero value
Console.WriteLine(string1.CompareTo(string2));
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

## IsNull

This property indicates whether or not the current instance contains a null value.

**Declaration**

```
// C#
public bool IsNull {get;}
```

**Property Value**

Returns `true` if the current instance contains has a null value; otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

## Item

This property obtains the particular character in an `OracleString` using an index.

**Declaration**

```
// C#
public char Item {get;}
```

**Property Value**

A `char` value.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

**Length**

This property returns the length of the `OracleString`.

**Declaration**

```
// C#  
public int Length {get;}
```

**Property Value**

A `int` value.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## OracleString Methods

The `OracleString` methods are listed in [Table 14–86](#).

**Table 14–86** *OracleString Methods*

Methods	Description
<a href="#">Clone</a>	Returns a copy of the current <code>OracleString</code> instance
<a href="#">CompareTo</a>	Compares the current <code>OracleString</code> instance to the supplied object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same string value as the current <code>OracleString</code> structure (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleString</code> instance
<a href="#">GetNonUnicodeBytes</a>	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in the client character set format
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">GetUnicodeBytes</a>	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in Unicode format
<a href="#">ToString</a>	Converts the current <code>OracleString</code> instance to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

### Clone

This method creates a copy of an `OracleString` instance.

**Declaration**

```
// C#
public OracleString Clone();
```

**Return Value**

An `OracleString` structure.

**Remarks**

The cloned object has the same property values as that of the object being cloned.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Types;

class CloneSample
{
    static void Main()
    {
        OracleString str1 = new OracleString("aAaAa");
    }
}
```

```
OracleString str2 = str1.Clone();

// The OracleStrings are same; Prints 0
Console.WriteLine(str1.CompareTo(str2));
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

## CompareTo

This method compares the current `OracleString` instance to the supplied object, and returns an integer that represents their relative values.

**Declaration**

```
// C#
public int CompareTo(object obj);
```

**Parameters**

- *obj*  
The object being compared to the current instance.

**Return Value**

The method returns a number that is:

- Less than zero: if the current `OracleString` value is less than *obj*.
- Zero: if the current `OracleString` value is equal to *obj*.
- Greater than zero: if the current `OracleString` value is greater than *obj*.

**Implements**

`IComparable`

**Exceptions**

`ArgumentException` - The *obj* parameter is not of type `OracleString`.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleStrings`. For example, comparing an `OracleString` instance with an `OracleBinary` instance is not allowed. When an `OracleString` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## Equals

This method determines whether or not supplied object is an instance of `OracleString` and has the same values as the current `OracleString` instance.

**Declaration**

```
// C#  
public override bool Equals(object obj);
```

**Parameters**

- *obj*  
An object being compared.

**Return Value**

Returns `true` if the supplied object is an instance of `OracleString` and has the same values as the current `OracleString` instance; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

## GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleString` instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

A number that represents the hash code.



**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

**GetNonUnicodeBytes**

This method returns an array of bytes, containing the contents of the `OracleString`, in the client character set format.

**Declaration**

```
// C#  
public byte[] GetNonUnicodeBytes();
```

**Return Value**

A byte array that contains the contents of the `OracleString` in the client character set format.

**Remarks**

If the current instance has a null value, an `OracleNullValueException` is thrown.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

**GetUnicodeBytes**

This method returns an array of bytes, containing the contents of the `OracleString` in Unicode format.

**Declaration**

```
// C#  
public byte[] GetUnicodeBytes();
```

**Return Value**

A byte array that contains the contents of the `OracleString` in Unicode format.

**Remarks**

If the current instance has a null value, an `OracleNullValueException` is thrown.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleString Structure](#)
- [OracleString Members](#)

**ToString**

Overrides `Object`

This method converts the current `OracleString` instance to a string.

### Declaration

```
// C#  
public override string ToString();
```

### Return Value

A `string`.

### Remarks

If the current `OracleString` instance has a null value, the string contains "null".

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleString Structure](#)
- [OracleString Members](#)

---

## OracleTimeStamp Structure

The `OracleTimeStamp` structure represents the Oracle `TIMESTAMP` data type to be stored in or retrieved from a database. Each `OracleTimeStamp` stores the following information: year, month, day, hour, minute, second, and nanosecond.

### Class Inheritance

```
System.Object
    System.ValueType
        Oracle.DataAccess.Types.OracleTimeStamp
```

### Declaration

```
// ADO.NET 2.0: C#
public struct OracleTimeStamp : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#
using System;
using Oracle.DataAccess.Types;

class OracleTimeStampSample
{
    static void Main()
    {
        OracleTimeStamp tsCurrent1 = OracleTimeStamp.GetSysDate();
        OracleTimeStamp tsCurrent2 = DateTime.Now;

        // Calculate the difference between tsCurrent1 and tsCurrent2
        OracleIntervalDS idsDiff = tsCurrent2.GetDaysBetween(tsCurrent1);

        // Calculate the difference using AddNanoseconds()
        int nanoDiff = 0;
        while (tsCurrent2 > tsCurrent1)
        {
            nanoDiff += 10;
            tsCurrent1 = tsCurrent1.AddNanoseconds(10);
        }
        Console.WriteLine("idsDiff.Nanoseconds = " + idsDiff.Nanoseconds);
        Console.WriteLine("nanoDiff = " + nanoDiff);
    }
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Members](#)
- [OracleTimeStamp Constructors](#)
- [OracleTimeStamp Static Fields](#)
- [OracleTimeStamp Static Methods](#)
- [OracleTimeStamp Static Operators](#)
- [OracleTimeStamp Static Type Conversions](#)
- [OracleTimeStamp Properties](#)
- [OracleTimeStamp Methods](#)

## OracleTimeStamp Members

OracleTimeStamp members are listed in the following tables:

### OracleTimeStamp Constructors

OracleTimeStamp constructors are listed in [Table 14–87](#)

**Table 14–87 OracleTimeStamp Constructors**

Constructor	Description
<a href="#">OracleTimeStamp Constructors</a>	Instantiates a new instance of OracleTimeStamp structure (Overloaded)

### OracleTimeStamp Static Fields

The OracleTimeStamp static fields are listed in [Table 14–88](#).

**Table 14–88 OracleTimeStamp Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleTimeStamp structure, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleTimeStamp structure

### OracleTimeStamp Static Methods

The OracleTimeStamp static methods are listed in [Table 14–89](#).

**Table 14–89 OracleTimeStamp Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleTimeStamp values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two OracleTimeStamp values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleTimeStamp values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleTimeStamp values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleTimeStamp values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleTimeStamp values are not equal
<a href="#">GetSysDate</a>	Gets an OracleTimeStamp structure that represents the current date and time
<a href="#">Parse</a>	Gets an OracleTimeStamp structure and sets its value using the supplied string

**Table 14–89 (Cont.) OracleTimeStamp Static Methods**

Methods	Description
<a href="#">SetPrecision</a>	Returns a new instance of an <code>OracleTimeStamp</code> with the specified fractional second precision

### OracleTimeStamp Static Operators

The `OracleTimeStamp` static operators are listed in [Table 14–90](#).

**Table 14–90 OracleTimeStamp Static Operators**

Operator	Description
<a href="#">operator +</a>	Adds the supplied instance value to the supplied <code>OracleTimeStamp</code> and returns a new <code>OracleTimeStamp</code> structure (Overloaded)
<a href="#">operator ==</a>	Determines if two <code>OracleTimeStamp</code> values are equal
<a href="#">operator &gt;</a>	Determines if the first of two <code>OracleTimeStamp</code> values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two <code>OracleTimeStamp</code> values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if the two <code>OracleTimeStamp</code> values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two <code>OracleTimeStamp</code> values is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two <code>OracleTimeStamp</code> values is less than or equal to the second
<a href="#">operator -</a>	Subtracts the supplied instance value from the supplied <code>OracleTimeStamp</code> and returns a new <code>OracleTimeStamp</code> structure (Overloaded)

### OracleTimeStamp Static Type Conversions

The `OracleTimeStamp` static type conversions are listed in [Table 14–91](#).

**Table 14–91 OracleTimeStamp Static Type Conversions**

Operator	Description
<a href="#">explicit operator OracleTimeStamp</a>	Converts an instance value to an <code>OracleTimeStamp</code> structure (Overloaded)
<a href="#">implicit operator OracleTimeStamp</a>	Converts an instance value to an <code>OracleTimeStamp</code> structure (Overloaded)
<a href="#">explicit operator DateTime</a>	Converts an <code>OracleTimeStamp</code> value to a <code>DateTime</code> structure

### OracleTimeStamp Properties

The `OracleTimeStamp` properties are listed in [Table 14–92](#).

**Table 14–92 OracleTimeStamp Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents an Oracle <code>TIMESTAMP</code> in Oracle internal format

**Table 14–92 (Cont.) OracleTimeStamp Properties**

Properties	Description
Day	Specifies the day component of an OracleTimeStamp
IsNull	Indicates whether or not the OracleTimeStamp instance has a null value
Hour	Specifies the hour component of an OracleTimeStamp
Millisecond	Specifies the millisecond component of an OracleTimeStamp
Minute	Specifies the minute component of an OracleTimeStamp
Month	Specifies the month component of an OracleTimeStamp
Nanosecond	Specifies the nanosecond component of an OracleTimeStamp
Second	Specifies the second component of an OracleTimeStamp
Value	Specifies the date and time that is stored in the OracleTimeStamp structure
Year	Specifies the year component of an OracleTimeStamp

### OracleTimeStamp Methods

The OracleTimeStamp methods are listed in [Table 14–93](#).

**Table 14–93 OracleTimeStamp Methods**

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance
CompareTo	Compares the current OracleTimeStamp instance to an object, and returns an integer that represents their relative values

**Table 14–93 (Cont.) OracleTimeStamp Methods**

Methods	Description
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleTimeStamp</code> instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleTimeStamp</code> instance
<a href="#">GetDaysBetween</a>	Subtracts an <code>OracleTimeStamp</code> value from the current instance and returns an <code>OracleIntervalDS</code> that represents the time difference between the supplied <code>OracleTimeStamp</code> and the current instance
<a href="#">GetYearsBetween</a>	Subtracts <code>value1</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the difference between <code>value1</code> and the current instance using <code>OracleIntervalYM</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToOracleDate</a>	Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleDate</code> structure
<a href="#">ToOracleTimeStampLTZ</a>	Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleTimeStampLTZ</code> structure
<a href="#">ToOracleTimeStampTZ</a>	Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleTimeStampTZ</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleTimeStamp</code> structure to a string

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)



## OracleTimeStamp Constructors

The `OracleTimeStamp` constructors create new instances of the `OracleTimeStamp` structure.

### Overload List:

- [OracleTimeStamp\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStamp\(string\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value using the supplied string.
- [OracleTimeStamp\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date using year, month, and day.
- [OracleTimeStamp\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStamp\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStamp\(int, int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStamp\(byte \[ \]\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value to the provided byte array, which is in the internal `Oracle TIMESTAMP` format.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### OracleTimeStamp(DateTime)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using the supplied `DateTime` value.

### Declaration

```
// C#  
public OracleTimeStamp (DateTime dt);
```

**Parameters**

- *dt*  
The supplied `DateTime` value.

**Exceptions**

`ArgumentException` - The *dt* parameter cannot be used to construct a valid `OracleTimeStamp`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**OracleTimeStamp(string)**

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value using the supplied string.

**Declaration**

```
// C#  
public OracleTimeStamp (string tsStr);
```

**Parameters**

- *tsStr*  
A string that represents an Oracle `TIMESTAMP`.

**Exceptions**

`ArgumentException` - The *tsStr* value is an invalid string representation of an Oracle `TIMESTAMP` or the supplied *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The *tsStr* value is null.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class OracleTimeStampSample  
{  
    static void Main()  
    {  
        // Set the nls_timestamp_format for the OracleTimeStamp(string)  
        // constructor  
    }  
}
```

```

OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStamp from a string using the format specified.
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}

```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110
- *Oracle Database SQL Reference* for further information on date format elements

**OracleTimeStamp(int, int, int)**

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date using year, month, and day.

**Declaration**

```
// C#
public OracleTimeStamp(int year, int month, int day);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**OracleTimeStamp(int, int, int, int, int, int)**

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, and second.

**Declaration**

```
// C#  
public OracleTimeStamp (int year, int month, int day, int hour,  
    int minute, int second);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**OracleTimeStamp(int, int, int, int, int, int, double)**

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

### Declaration

```
// C#
public OracleTimeStamp(int year, int month, int day, int hour,
    int minute, int second, double millisecond);
```

### Parameters

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *milliSeconds*  
The milliseconds provided. Range of *millisecond* is (0 to 999.999999).

### Exceptions

*ArgumentOutOfRangeException* - The argument value for one or more of the parameters is out of the specified range.

*ArgumentException* - The argument values of the parameters cannot be used to construct a valid *OracleTimeStamp* (that is, the day is out of range for the month).

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### OracleTimeStamp(int, int, int, int, int, int, int)

This constructor creates a new instance of the *OracleTimeStamp* structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

### Declaration

```
// C#
public OracleTimeStamp (int year, int month, int day, int hour,
    int minute, int second, int nanosecond);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *nanosecond*  
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

**Exceptions**

*ArgumentOutOfRangeException* - The argument value for one or more of the parameters is out of the specified range.

*ArgumentException* - The argument values of the parameters cannot be used to construct a valid *OracleTimeStamp* (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**OracleTimeStamp(byte [ ])**

This constructor creates a new instance of the *OracleTimeStamp* structure and sets its value to the provided byte array, which is in the internal Oracle *TIMESTAMP* format.

**Declaration**

```
// C#  
public OracleTimeStamp (byte[] bytes);
```

**Parameters**

- *bytes*  
A byte array that represents an Oracle *TIMESTAMP* in Oracle internal format.

**Exceptions**

*ArgumentException* - *bytes* is not in an internal Oracle *TIMESTAMP* format or *bytes* is not a valid Oracle *TIMESTAMP*.

*ArgumentNullException* - *bytes* is null.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## OracleTimeStamp Static Fields

The `OracleTimeStamp` static fields are listed in [Table 14–94](#).

**Table 14–94** *OracleTimeStamp Static Fields*

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an <code>OracleTimeStamp</code> structure, which is December 31, 9999 23:59:59.999999999
<a href="#">MinValue</a>	Represents the minimum valid date for an <code>OracleTimeStamp</code> structure, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the <code>OracleTimeStamp</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### MaxValue

This static field represents the maximum valid date and time for an `OracleTimeStamp` structure, which is December 31, 9999 23:59:59.999999999.

**Declaration**

```
// C#
public static readonly OraTimestamp MaxValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### MinValue

This static field represents the minimum valid date and time for an `OracleTimeStamp` structure, which is January 1, -4712 0:0:0.

**Declaration**

```
// C#
public static readonly OracleTimeStamp MinValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)



## Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStamp` structure.

### Declaration

```
// C#  
public static readonly OracleTimeStamp Null;
```

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## OracleTimeStamp Static Methods

The `OracleTimeStamp` static methods are listed in [Table 14–95](#).

**Table 14–95 OracleTimeStamp Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two <code>OracleTimeStamp</code> values are equal (Overloaded)
<a href="#">GreaterThan</a>	Determines if the first of two <code>OracleTimeStamp</code> values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two <code>OracleTimeStamp</code> values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two <code>OracleTimeStamp</code> values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two <code>OracleTimeStamp</code> values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two <code>OracleTimeStamp</code> values are not equal
<a href="#">GetSysDate</a>	Gets an <code>OracleTimeStamp</code> structure that represents the current date and time
<a href="#">Parse</a>	Gets an <code>OracleTimeStamp</code> structure and sets its value using the supplied string
<a href="#">SetPrecision</a>	Returns a new instance of an <code>OracleTimeStamp</code> with the specified fractional second precision

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### Equals

This static method determines if two `OracleTimeStamp` values are equal.

**Declaration**

```
// C#
public static bool Equals(OracleTimeStamp value1, OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

**Return Value**

Returns `true` if two `OracleTimeStamp` values are equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**GreaterThan**

This static method determines if the first of two `OracleTimeStamp` values is greater than the second.

**Declaration**

```
// C#  
public static bool GreaterThan(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

**Return Value**

Returns `true` if the first of two `OracleTimeStamp` values is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**GreaterThanOrEqual**

This static method determines if the first of two `OracleTimeStamp` values is greater than or equal to the second.

**Declaration**

```
// C#
public static bool GreaterThanOrEqual(OracleTimeStamp value1,
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first OracleTimeStamp.
- *value2*  
The second OracleTimeStamp.

**Return Value**

Returns true if the first of two OracleTimeStamp values is greater than or equal to the second; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**LessThan**

This static method determines if the first of two OracleTimeStamp values is less than the second.

**Declaration**

```
// C#
public static bool LessThan(OracleTimeStamp value1,
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first OracleTimeStamp.
- *value2*  
The second OracleTimeStamp.

**Return Value**

Returns true if the first of two OracleTimeStamp values is less than the second. Returns false otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## LessThanOrEqual

This static method determines if the first of two `OracleTimeStamp` values is less than or equal to the second.

**Declaration**

```
// C#
public static bool LessThanOrEqual(OracleTimeStamp value1,
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

**Return Value**

Returns `true` if the first of two `OracleTimeStamp` values is less than or equal to the second. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## NotEquals

This static method determines if two `OracleTimeStamp` values are not equal.

**Declaration**

```
// C#
public static bool NotEquals(OracleTimeStamp value1,
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first OracleTimeStamp.
- *value2*  
The second OracleTimeStamp.

**Return Value**

Returns `true` if two OracleTimeStamp values are not equal. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**GetSysDate**

This static method gets an OracleTimeStamp structure that represents the current date and time.

**Declaration**

```
// C#  
public static OracleTimeStamp GetSysDate();
```

**Return Value**

An OracleTimeStamp structure that represents the current date and time.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**Parse**

This static method gets an OracleTimeStamp structure and sets its value using the supplied string.

**Declaration**

```
// C#  
public static OracleTimeStamp Parse(string datetime);
```

**Parameters**

- *datetime*

A string that represents an Oracle `TIMESTAMP`.

### Return Value

An `OracleTimeStamp` structure.

### Exceptions

`ArgumentException` - The `tsStr` is an invalid string representation of an Oracle `TIMESTAMP` or the supplied `tsStr` is not in the timestamp format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The `tsStr` value is null.

### Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts =
            OracleTimeStamp.Parse("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## SetPrecision

This static method returns a new instance of an `OracleTimeStamp` with the specified fractional second precision.

### Declaration

```
// C#
public static OracleTimeStamp SetPrecision(OracleTimeStamp value1,
    int fracSecPrecision);
```

### Parameters

- *value1*  
The provided `OracleTimeStamp` object.
- *fracSecPrecision*  
The fractional second precision provided. Range of fractional second precision is (0 to 9).

### Return Value

An `OracleTimeStamp` structure with the specified fractional second precision.

### Exceptions

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

### Remarks

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleTimeStamp` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

### Example

The `OracleTimeStamp` with a value of "December 31, 9999 23:59:59.99" results in the string "December 31, 9999 23:59:59.99000" when `SetPrecision()` is called with the fractional second precision set to 5.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)



## OracleTimeStamp Static Operators

The OracleTimeStamp static operators are listed in [Table 14–96](#).

**Table 14–96 OracleTimeStamp Static Operators**

Operator	Description
<a href="#">operator +</a>	Adds the supplied instance value to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded)
<a href="#">operator ==</a>	Determines if two OracleTimeStamp values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleTimeStamp values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleTimeStamp values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if the two OracleTimeStamp values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two OracleTimeStamp values is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two OracleTimeStamp values is less than or equal to the second
<a href="#">operator -</a>	Subtracts the supplied instance value from the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded)

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### operator +

operator+ adds the supplied object to the OracleTimeStamp and returns a new OracleTimeStamp structure.

### Overload List:

- [operator + \(OracleTimeStamp, OracleIntervalDS\)](#)  
This static operator adds the supplied OracleIntervalDS to the OracleTimeStamp and returns a new OracleTimeStamp structure.
- [operator + \(OracleTimeStamp, OracleIntervalYM\)](#)  
This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure.
- [operator + \(OracleTimeStamp, TimeSpan\)](#)  
This static operator adds the supplied TimeSpan to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator + (OracleTimeStamp, OracleIntervalDS)**

This static operator adds the supplied `OracleIntervalDS` to the `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static operator + (OracleTimeStamp value1, OracleIntervalDS value2);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.
- *value2*  
An `OracleIntervalDS`.

**Return Value**

An `OracleTimeStamp`.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator + (OracleTimeStamp, OracleIntervalYM)**

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static operator + (OracleTimeStamp value1, OracleIntervalYM value2);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.
- *value2*  
An `OracleIntervalYM`.

**Return Value**

An `OracleTimeStamp`.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator + (OracleTimeStamp, TimeSpan)**

This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static operator + (OracleTimeStamp value1, TimeSpan value2);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.
- *value2*  
A `TimeSpan`.

**Return Value**

An `OracleTimeStamp`.

**Remarks**

If the `OracleTimeStamp` instance has a null value, the returned `OracleTimeStamp` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator ==**

This static operator determines if two `OracleTimeStamp` values are equal.

**Declaration**

```
// C#  
public static bool operator == (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

**Return Value**

Returns `true` if they are the same; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator >**

This static operator determines if the first of two `OracleTimeStamp` values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

**Return Value**

Returns `true` if the first `OracleTimeStamp` value is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## operator >=

This static operator determines if the first of two `OracleTimeStamp` values is greater than or equal to the second.

### Declaration

```
// C#  
public static bool operator >= (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

### Parameters

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

### Return Value

Returns `true` if the first `OracleTimeStamp` is greater than or equal to the second; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## operator !=

This static operator determines if two `OracleTimeStamp` values are not equal.

### Declaration

```
// C#  
public static bool operator != (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

### Parameters

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

### Return Value

Returns `true` if two `OracleTimeStamp` values are not equal; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator <**

This static operator determines if the first of two `OracleTimeStamp` values is less than the second.

**Declaration**

```
// C#
public static bool operator < (OracleTimeStamp value1,
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStamp`.
- *value2*  
The second `OracleTimeStamp`.

**Return Value**

Returns `true` if the first `OracleTimeStamp` is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator <=**

This static operator determines if the first of two `OracleTimeStamp` values is less than or equal to the second.

**Declaration**

```
// C#
public static bool operator <= (OracleTimeStamp value1,
    OracleTimeStamp value2);
```

**Parameters**

- *value1*  
The first OracleTimeStamp.
- *value2*  
The second OracleTimeStamp.

**Return Value**

Returns true if the first OracleTimeStamp is less than or equal to the second; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator -**

operator- subtracts the supplied value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.

**Overload List:**

- [operator - \(OracleTimeStamp, OracleIntervalDS\)](#)  
This static operator subtracts the supplied OracleIntervalDS value, from the supplied OracleTimeStamp value, and return a new OracleTimeStamp structure.
- [operator - \(OracleTimeStamp, OracleIntervalYM\)](#)  
This static operator subtracts the supplied OracleIntervalYM value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.
- [operator - \(OracleTimeStamp, TimeSpan\)](#)  
This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator - (OracleTimeStamp, OracleIntervalDS)**

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStamp` value, and return a new `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static operator - (OracleTimeStamp value1, OracleIntervalDS value2);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.
- *value2*  
An `OracleIntervalDS` instance.

**Return Value**

An `OracleTimeStamp` structure.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator - (OracleTimeStamp, OracleIntervalYM)**

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static operator - (OracleTimeStamp value1, OracleIntervalYM value2);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.
- *value2*  
An `OracleIntervalYM` instance.

**Return Value**

An `OracleTimeStamp` structure.



**Remarks**

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**operator - (OracleTimeStamp, TimeSpan)**

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static operator - (OracleTimeStamp value1, TimeSpan value2);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.
- *value2*  
A `TimeSpan` instance.

**Return Value**

An `OracleTimeStamp` structure.

**Remarks**

If the `OracleTimeStamp` instance has a null value, the returned `OracleTimeStamp` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## OracleTimeStamp Static Type Conversions

The `OracleTimeStamp` static type conversions are listed in [Table 14–97](#).

**Table 14–97 OracleTimeStamp Static Type Conversions**

Operator	Description
<a href="#">explicit operator OracleTimeStamp</a>	Converts an instance value to an <code>OracleTimeStamp</code> structure (Overloaded)
<a href="#">implicit operator OracleTimeStamp</a>	Converts an instance value to an <code>OracleTimeStamp</code> structure (Overloaded)
<a href="#">explicit operator DateTime</a>	Converts an <code>OracleTimeStamp</code> value to a <code>DateTime</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### explicit operator OracleTimeStamp

`explicit operator OracleTimeStamp` converts the supplied value to an `OracleTimeStamp` structure

**Overload List:**

- [explicit operator OracleTimeStamp\(OracleTimeStampLTZ\)](#)  
This static type conversion operator converts an `OracleTimeStampLTZ` value to an `OracleTimeStamp` structure.
- [explicit operator OracleTimeStamp\(OracleTimeStampTZ\)](#)  
This static type conversion operator converts an `OracleTimeStampTZ` value to an `OracleTimeStamp` structure.
- [explicit operator OracleTimeStamp\(string\)](#)  
This static type conversion operator converts the supplied string to an `OracleTimeStamp` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### explicit operator OracleTimeStamp(OracleTimeStampLTZ)

This static type conversion operator converts an `OracleTimeStampLTZ` value to an `OracleTimeStamp` structure.

**Declaration**

```
// C#
public static explicit operator OracleTimeStamp(OracleTimeStampLTZ value1);
```

**Parameters**

- *value1*  
An OracleTimeStampLTZ instance.

**Return Value**

The returned OracleTimeStamp contains the date and time of the OracleTimeStampLTZ structure.

**Remarks**

If the OracleTimeStampLTZ structure has a null value, the returned OracleTimeStamp structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**explicit operator OracleTimeStamp(OracleTimeStampTZ)**

This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStamp structure.

**Declaration**

```
// C#
public static explicit operator OracleTimeStamp(OracleTimeStampTZ value1);
```

**Parameters**

- *value1*  
An OracleTimeStampTZ instance.

**Return Value**

The returned OracleTimeStamp contains the date and time information from *value1*, but the time zone information from *value1* is truncated.

**Remarks**

If the OracleTimeStampTZ structure has a null value, the returned OracleTimeStamp structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**explicit operator OracleTimeStamp(string)**

This static type conversion operator converts the supplied string to an OracleTimeStamp structure.

**Declaration**

```
// C#
```

```
public static explicit operator OracleTimeStamp(string tsStr);
```

### Parameters

- *tsStr*

A string representation of an Oracle TIMESTAMP.

### Return Value

An OracleTimeStamp.

### Exceptions

*ArgumentException* - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP or the *tsStr* is not in the timestamp format specified by the thread's OracleGlobalization.TimeStampFormat property, which represents the Oracle NLS\_TIMESTAMP\_FORMAT parameter.

### Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the explicit
        // operator OracleTimeStamp(string)
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110
- *Oracle Database SQL Reference* for further information on datetime format elements

**implicit operator OracleTimeStamp**

This static type conversion operator converts a value to an `OracleTimeStamp` structure.

**Overload List:**

- [implicit operator OracleTimeStamp\(OracleDate\)](#)

This static type conversion operator converts an `OracleDate` value to an `OracleTimeStamp` structure.

- [implicit operator OracleTimeStamp\(DateTime\)](#)

This static type conversion operator converts a `DateTime` value to an `OracleTimeStamp` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**implicit operator OracleTimeStamp(OracleDate)**

This static type conversion operator converts an `OracleDate` value to an `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static implicit operator OracleTimeStamp (OracleDate value1);
```

**Parameters**

- *value1*  
An `OracleDate` instance.

**Return Value**

An `OracleTimeStamp` structure that contains the date and time of the `OracleDate` structure, *value1*.

**Remarks**

If the `OracleDate` structure has a null value, the returned `OracleTimeStamp` structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**implicit operator OracleTimeStamp(DateTime)**

This static type conversion operator converts a `DateTime` value to an `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public static implicit operator OracleTimeStamp(DateTime value);
```

**Parameters**

- *value*  
A `DateTime` instance.

**Return Value**

An `OracleTimeStamp` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**explicit operator DateTime**

This static type conversion operator converts an `OracleTimeStamp` value to a `DateTime` structure.

**Declaration**

```
// C#  
public static explicit operator DateTime(OracleTimeStamp value1);
```

**Parameters**

- *value1*  
An `OracleTimeStamp` instance.

**Return Value**

A `DateTime` containing the date and time in the current instance.

**Exceptions**

`OracleNullValueException` - The `OracleTimeStamp` structure has a null value.

**Remarks**

The precision of the `OracleTimeStamp` can be lost during the conversion.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## OracleTimeStamp Properties

The `OracleTimeStamp` properties are listed in [Table 14-98](#).

**Table 14-98 OracleTimeStamp Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents an Oracle <code>TIMESTAMP</code> in Oracle internal format
<a href="#">Day</a>	Specifies the day component of an <code>OracleTimeStamp</code>
<a href="#">IsNull</a>	Indicates whether or not the <code>OracleTimeStamp</code> instance has a null value
<a href="#">Hour</a>	Specifies the hour component of an <code>OracleTimeStamp</code>
<a href="#">Millisecond</a>	Specifies the millisecond component of an <code>OracleTimeStamp</code>
<a href="#">Minute</a>	Specifies the minute component of an <code>OracleTimeStamp</code>
<a href="#">Month</a>	Specifies the month component of an <code>OracleTimeStamp</code>
<a href="#">Nanosecond</a>	Specifies the nanosecond component of an <code>OracleTimeStamp</code>
<a href="#">Second</a>	Specifies the second component of an <code>OracleTimeStamp</code>
<a href="#">Value</a>	Specifies the date and time that is stored in the <code>OracleTimeStamp</code> structure
<a href="#">Year</a>	Specifies the year component of an <code>OracleTimeStamp</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP` in Oracle internal format.

**Declaration**

```
// C#
public byte[] BinData {get;}
```

**Property Value**

A byte array that represents an Oracle `TIMESTAMP` in an internal format.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)



## Day

This property specifies the day component of an `OracleTimeStamp`.

### Declaration

```
// C#  
public int Day{get;}
```

### Property Value

A number that represents the day. Range of `Day` is (1 to 31).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## IsNull

This property indicates whether or not the current instance has a null value.

### Declaration

```
// C#  
public bool IsNull{get;}
```

### Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Hour

This property specifies the hour component of an `OracleTimeStamp`.

### Declaration

```
// C#  
public int Hour{get;}
```

### Property Value

A number that represents the hour. Range of `hour` is (0 to 23).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Millisecond

This property gets the millisecond component of an `OracleTimeStamp`.

**Declaration**

```
// C#  
public double Millisecond{get;}
```

**Property Value**

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Minute

This property gets the minute component of an `OracleTimeStamp`.

**Declaration**

```
// C#  
public int Minute{get;}
```

**Property Value**

A number that represent a minute. Range of `Minute` is (0 to 59).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Month

This property gets the month component of an `OracleTimeStamp`.

**Declaration**

```
// C#  
public int Month{get;}
```

**Property Value**

A number that represents a month. Range of `Month` is (1 to 12).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**Nanosecond**

This property gets the nanosecond component of an `OracleTimeStamp`.

**Declaration**

```
// C#  
public int Nanosecond{get;}
```

**Property Value**

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**Second**

This property gets the second component of an `OracleTimeStamp`.

**Declaration**

```
// C#  
public int Second{get;}
```

**Property Value**

A number that represents a second. Range of `Second` is (0 to 59).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Value

This property specifies the date and time that is stored in the `OracleTimeStamp` structure.

### Declaration

```
// C#  
public DateTime Value{get;}
```

### Property Value

A `DateTime`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Year

This property gets the year component of an `OracleTimeStamp`.

### Declaration

```
// C#  
public int Year{get;}
```

### Property Value

A number that represents a year. The range of `Year` is (-4712 to 9999).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## OracleTimeStamp Methods

The `OracleTimeStamp` methods are listed in [Table 14–99](#).

**Table 14–99 OracleTimeStamp Methods**

Methods	Description
<a href="#">AddDays</a>	Adds the supplied number of days to the current instance
<a href="#">AddHours</a>	Adds the supplied number of hours to the current instance
<a href="#">AddMilliseconds</a>	Adds the supplied number of milliseconds to the current instance
<a href="#">AddMinutes</a>	Adds the supplied number of minutes to the current instance
<a href="#">AddMonths</a>	Adds the supplied number of months to the current instance
<a href="#">AddNanoseconds</a>	Adds the supplied number of nanoseconds to the current instance
<a href="#">AddSeconds</a>	Adds the supplied number of seconds to the current instance
<a href="#">AddYears</a>	Adds the supplied number of years to the current instance
<a href="#">CompareTo</a>	Compares the current <code>OracleTimeStamp</code> instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleTimeStamp</code> instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleTimeStamp</code> instance
<a href="#">GetDaysBetween</a>	Subtracts an <code>OracleTimeStamp</code> value from the current instance and returns an <code>OracleIntervalDS</code> that represents the time difference between the supplied <code>OracleTimeStamp</code> and the current instance
<a href="#">GetYearsBetween</a>	Subtracts <code>value1</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the difference between <code>value1</code> and the current instance using <code>OracleIntervalYM</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToOracleDate</a>	Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleDate</code> structure
<a href="#">ToOracleTimeStampLTZ</a>	Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleTimeStampLTZ</code> structure
<a href="#">ToOracleTimeStampTZ</a>	Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleTimeStampTZ</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleTimeStamp</code> structure to a string

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

### AddDays

This method adds the supplied number of days to the current instance.

**Declaration**

```
// C#  
public OracleTimeStamp AddDays(double days);
```

**Parameters**

- *days*

The supplied number of days. Range is  $(-1,000,000,000 < days < 1,000,000,000)$

**Return Value**

An `OracleTimeStamp`.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**AddHours**

This method adds the supplied number of hours to the current instance.

**Declaration**

```
// C#  
public OracleTimeStamp AddHours(double hours);
```

**Parameters**

- *hours*

The supplied number of hours. Range is  $(-24,000,000,000 < hours < 24,000,000,000)$ .

**Return Value**

An `OracleTimeStamp`.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

### Declaration

```
// C#  
public OracleTimeStamp AddMilliseconds(double milliseconds);
```

### Parameters

- *milliseconds*

The supplied number of milliseconds. Range is  $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$ .

### Return Value

An `OracleTimeStamp`.

### Exceptions

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## AddMinutes

This method adds the supplied number of minutes to the current instance.

### Declaration

```
// C#  
public OracleTimeStamp AddMinutes(double minutes);
```

### Parameters

- *minutes*

The supplied number of minutes. Range is  $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$ .

### Return Value

An `OracleTimeStamp`.

### Exceptions

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## AddMonths

This method adds the supplied number of months to the current instance.

**Declaration**

```
// C#  
public OracleTimeStamp AddMonths(long months);
```

**Parameters**

- *months*

The supplied number of months. Range is  $(-12,000,000,000 < months < 12,000,000,000)$ .

**Return Value**

An `OracleTimeStamp`.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

**Declaration**

```
// C#  
public OracleTimeStamp AddNanoseconds(long nanoseconds);
```

**Parameters**

- *nanoseconds*

The supplied number of nanoseconds.

**Return Value**

An `OracleTimeStamp`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## AddSeconds

This method adds the supplied number of seconds to the current instance.

**Declaration**

```
// C#  
public OracleTimeStamp AddSeconds(double seconds);
```

**Parameters**

- *seconds*

The supplied number of seconds. Range is  $(-8.64 * 10^{13} < seconds < 8.64 * 10^{13})$ .

**Return Value**

An OracleTimeStamp.

**Exceptions**

*ArgumentOutOfRangeException* - The argument value is out of the specified range.

*OracleNullValueException* - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## AddYears

This method adds the supplied number of years to the current instance.

**Declaration**

```
// C#  
public OracleTimeStamp AddYears(int years);
```

**Parameters**

- *years*

The supplied number of years. Range is  $(-999,999,999 \leq years \leq 999,999,999)$

**Return Value**

An OracleTimeStamp.

**Exceptions**

*ArgumentOutOfRangeException* - The argument value is out of the specified range.

*OracleNullValueException* - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**CompareTo**

This method compares the current `OracleTimeStamp` instance to an object, and returns an integer that represents their relative values.

**Declaration**

```
// C#  
public int CompareTo(object obj);
```

**Parameters**

- *obj*

The object being compared to the current `OracleTimeStamp` instance.

**Return Value**

The method returns a number that is:

Less than zero: if the current `OracleTimeStamp` instance value is less than that of *obj*.

Zero: if the current `OracleTimeStamp` instance and *obj* values are equal.

Greater than zero: if the current `OracleTimeStamp` instance value is greater than that of *obj*.

**Implements**

`IComparable`

**Exceptions**

`ArgumentException` - The *obj* parameter is not of type `OracleTimeStamp`.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStamps`. For example, comparing an `OracleTimeStamp` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStamp` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## Equals

Overrides Object

This method determines whether or not an object has the same date and time as the current `OracleTimeStamp` instance.

### Declaration

```
// C#  
public override bool Equals(object obj);
```

### Parameters

- *obj*

The object being compared to the current `OracleTimeStamp` instance.

### Return Value

Returns `true` if the *obj* is of type `OracleTimeStamp` and represents the same date and time; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## GetHashCode

Overrides Object

This method returns a hash code for the `OracleTimeStamp` instance.

### Declaration

```
// C#  
public override int GetHashCode();
```

### Return Value

A number that represents the hash code.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## GetDaysBetween

This method subtracts an `OracleTimeStamp` value from the current instance and returns an `OracleIntervalDS` that represents the time difference between the supplied `OracleTimeStamp` structure and the current instance.

### Declaration

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStamp value1);
```

### Parameters

- *value1*  
The `OracleTimeStamp` value being subtracted.

### Return Value

An `OracleIntervalDS` that represents the interval between two `OracleTimeStamp` values.

### Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## GetYearsBetween

This method subtracts an `OracleTimeStamp` value from the current instance and returns an `OracleIntervalYM` that represents the time difference between the `OracleTimeStamp` value and the current instance.

### Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStamp value1);
```

### Parameters

- *value1*  
The `OracleTimeStamp` value being subtracted.

### Return Value

An `OracleIntervalYM` that represents the interval between two `OracleTimeStamp` values.

### Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalYM` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**ToOracleDate**

This method converts the current `OracleTimeStamp` structure to an `OracleDate` structure.

**Declaration**

```
// C#  
public OracleDate ToOracleDate();
```

**Return Value**

The returned `OracleDate` contains the date and time in the current instance.

**Remarks**

The precision of the `OracleTimeStamp` value can be lost during the conversion. If the value of the `OracleTimeStamp` has a null value, the value of the returned `OracleDate` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

**ToOracleTimeStampLTZ**

This method converts the current `OracleTimeStamp` structure to an `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public OracleTimeStampLTZ ToOracleTimeStampLTZ();
```

**Return Value**

The returned `OracleTimeStampLTZ` contains date and time in the current instance.

**Remarks**

If the value of the current instance has a null value, the value of the returned `OracleTimeStampLTZ` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

## ToOracleTimeStampTZ

This method converts the current `OracleTimeStamp` structure to an `OracleTimeStampTZ` structure.

### Declaration

```
// C#  
public OracleTimeStampTZ ToOracleTimeStampTZ();
```

### Return Value

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStamp` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

### Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## ToString

Overrides `Object`

This method converts the current `OracleTimeStamp` structure to a string.

### Declaration

```
// C#  
public override string ToString();
```

### Return Value

A string that represents the same date and time as the current `OracleTimeStamp` structure.

### Remarks

The returned value is a string representation of an `OracleTimeStamp` in the format specified by the `OracleGlobalization.TimeStampFormat` property of the thread.

The names and abbreviations used for months and days are in the language specified by the `OracleGlobalization's DateLanguage` and `Calendar` properties of the thread. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;
```

```
using Oracle.DataAccess.Client;

class ToStringSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStamp(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

---

## OracleTimeStampLTZ Structure

The `OracleTimeStampLTZ` structure represents the Oracle `TIMESTAMP WITH LOCAL TIME ZONE` data type to be stored in or retrieved from a database. Each `OracleTimeStampLTZ` stores the following information: year, month, day, hour, minute, second, and nanosecond.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStampLTZ`

### Declaration

```
// ADO.NET 2.0: C#  
public struct OracleTimeStampLTZ : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class OracleTimeStampLTZSample  
{  
    static void Main()  
    {  
        // Illustrates usage of OracleTimeStampLTZ  
        // Display Local Time Zone Name  
        Console.WriteLine("Local Time Zone Name = " +  
            OracleTimeStampLTZ.GetLocalTimeZoneName());  
        OracleTimeStampLTZ tsLocal1 = OracleTimeStampLTZ.GetSysDate();  
        OracleTimeStampLTZ tsLocal2 = DateTime.Now;  
  
        // Calculate the difference between tsLocal1 and tsLocal2  
        OracleIntervalDS idsDiff = tsLocal2.GetDaysBetween(tsLocal1);  
  
        // Calculate the difference using AddNanoseconds()  
        int nanoDiff = 0;  
        while (tsLocal2 > tsLocal1)  
        {  
            nanoDiff += 10;  
            tsLocal1 = tsLocal1.AddNanoseconds(10);  
        }  
        Console.WriteLine("idsDiff.Nanoseconds = " + idsDiff.Nanoseconds);  
        Console.WriteLine("nanoDiff = " + nanoDiff);  
    }  
}
```



**Requirements**

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Members](#)
- [OracleTimeStampLTZ Constructors](#)
- [OracleTimeStampLTZ Static Fields](#)
- [OracleTimeStampLTZ Static Methods](#)
- [OracleTimeStampLTZ Static Operators](#)
- [OracleTimeStampLTZ Static Type Conversions](#)
- [OracleTimeStampLTZ Properties](#)
- [OracleTimeStampLTZ Methods](#)

## OracleTimeStampLTZ Members

OracleTimeStampLTZ members are listed in the following tables:

### OracleTimeStampLTZ Constructors

OracleTimeStampLTZ constructors are listed in [Table 14-100](#)

**Table 14-100 OracleTimeStampLTZConstructors**

Constructor	Description
<a href="#">OracleTimeStampLTZ Constructors</a>	Instantiates a new instance of OracleTimeStampLTZ structure (Overloaded)

### OracleTimeStampLTZ Static Fields

The OracleTimeStampLTZ static fields are listed in [Table 14-101](#).

**Table 14-101 OracleTimeStampLTZ Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleTimeStampLTZ structure

### OracleTimeStampLTZ Static Methods

The OracleTimeStampLTZ static methods are listed in [Table 14-102](#).

**Table 14-102 OracleTimeStampLTZ Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleTimeStampLTZ values are equal (Overloaded)
<a href="#">GetLocalTimeZoneName</a>	Gets the client's local time zone name
<a href="#">GetLocalTimeZoneOffset</a>	Gets the client's local time zone offset relative to UTC
<a href="#">GetSysDate</a>	Gets an OracleTimeStampLTZ structure that represents the current date and time
<a href="#">GreaterThan</a>	Determines if the first of two OracleTimeStampLTZ values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleTimeStampLTZ values is less than the second

**Table 14–102 (Cont.) OracleTimeStampLTZ Static Methods**

Methods	Description
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleTimeStampLTZ values are not equal
<a href="#">Parse</a>	Gets an OracleTimeStampLTZ structure and sets its value for date and time using the supplied string
<a href="#">SetPrecision</a>	Returns a new instance of an OracleTimeStampLTZ with the specified fractional second precision

### OracleTimeStampLTZ Static Operators

The OracleTimeStampLTZ static operators are listed in [Table 14–103](#).

**Table 14–103 OracleTimeStampLTZ Static Operators**

Operator	Description
<a href="#">operator+</a>	Adds the supplied instance value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)
<a href="#">operator ==</a>	Determines if two OracleTimeStampLTZ values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleTimeStampLTZ values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if two OracleTimeStampLTZ values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two OracleTimeStampLTZ values is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
<a href="#">operator -</a>	Subtracts the supplied instance value from the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)

### OracleTimeStampLTZ Static Type Conversions

The OracleTimeStampLTZ static type conversions are listed in [Table 14–104](#).

**Table 14–104 OracleTimeStampLTZ Static Type Conversions**

Operator	Description
<a href="#">explicit operator OracleTimeStampLTZ</a>	Converts an instance value to an OracleTimeStampLTZ structure (Overloaded)

**Table 14–104 (Cont.) OracleTimeStampLTZ Static Type Conversions**

Operator	Description
<a href="#">implicit operator OracleTimeStampLTZ</a>	Converts an instance value to an OracleTimeStampLTZ structure (Overloaded)
<a href="#">explicit operator DateTime</a>	Converts an OracleTimeStampLTZ value to a DateTime structure

### OracleTimeStampLTZ Properties

The OracleTimeStampLTZ properties are listed in [Table 14–105](#).

**Table 14–105 OracleTimeStampLTZ Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents an Oracle TIMESTAMP WITH LOCAL TIME ZONE in Oracle internal format
<a href="#">Day</a>	Specifies the day component of an OracleTimeStampLTZ
<a href="#">IsNull</a>	Indicates whether or not the OracleTimeStampLTZ instance has a null value
<a href="#">Hour</a>	Specifies the hour component of an OracleTimeStampLTZ
<a href="#">Millisecond</a>	Specifies the millisecond component of an OracleTimeStampLTZ
<a href="#">Minute</a>	Specifies the minute component of an OracleTimeStampLTZ
<a href="#">Month</a>	Specifies the month component of an OracleTimeStampLTZ
<a href="#">Nanosecond</a>	Specifies the nanosecond component of an OracleTimeStampLTZ
<a href="#">Second</a>	Specifies the second component of an OracleTimeStampLTZ
<a href="#">Value</a>	Specifies the date and time that is stored in the OracleTimeStampLTZ structure
<a href="#">Year</a>	Specifies the year component of an OracleTimeStampLTZ

### OracleTimeStampLTZ Methods

The OracleTimeStampLTZ methods are listed in [Table 14–106](#).

**Table 14–106 OracleTimeStampLTZ Methods**

Methods	Description
<a href="#">AddDays</a>	Adds the supplied number of days to the current instance
<a href="#">AddHours</a>	Adds the supplied number of hours to the current instance
<a href="#">AddMilliseconds</a>	Adds the supplied number of milliseconds to the current instance

**Table 14–106 (Cont.) OracleTimeStampLTZ Methods**

Methods	Description
<a href="#">AddMinutes</a>	Adds the supplied number of minutes to the current instance
<a href="#">AddMonths</a>	Adds the supplied number of months to the current instance
<a href="#">AddNanoseconds</a>	Adds the supplied number of nanoseconds to the current instance
<a href="#">AddSeconds</a>	Adds the supplied number of seconds to the current instance
<a href="#">AddYears</a>	Adds the supplied number of years to the current instance
<a href="#">CompareTo</a>	Compares the current <code>OracleTimeStampLTZ</code> instance to an object and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleTimeStampLTZ</code> instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleTimeStampLTZ</code> instance
<a href="#">GetDaysBetween</a>	Subtracts an <code>OracleTimeStampLTZ</code> from the current instance and returns an <code>OracleIntervalDS</code> that represents the difference
<a href="#">GetYearsBetween</a>	Subtracts an <code>OracleTimeStampLTZ</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the difference
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToOracleDate</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleDate</code> structure
<a href="#">ToOracleTimeStamp</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleTimeStamp</code> structure
<a href="#">ToOracleTimeStampTZ</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleTimeStampTZ</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to a string
<a href="#">ToUniversalTime</a>	Converts the current local time to Coordinated Universal Time (UTC)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)

## OracleTimeStampLTZ Constructors

The `OracleTimeStampLTZ` constructors create new instances of the `OracleTimeStampLTZ` structure.

### Overload List:

- [OracleTimeStampLTZ\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStampLTZ\(string\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied string.
- [OracleTimeStampLTZ\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date using year, month, and day.
- [OracleTimeStampLTZ\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStampLTZ\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStampLTZ\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStampLTZ\(byte \[ \]\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value to the provided byte array, which is in the internal `Oracle TIMESTAMP WITH LOCAL TIME ZONE` format.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### OracleTimeStampLTZ(DateTime)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied `DateTime` value.

### Declaration

```
// C#  
public OracleTimeStampLTZ (DateTime dt);
```

**Parameters**

- *dt*  
The supplied `DateTime` value.

**Exceptions**

`ArgumentException` - The *dt* parameter cannot be used to construct a valid `OracleTimeStampLTZ`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**OracleTimeStampLTZ(string)**

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied string.

**Declaration**

```
// C#
public OracleTimeStampLTZ(string tsStr);
```

**Parameters**

- *tsStr*  
A string that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

**Exceptions**

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the supplied *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimestampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The *tsStr* value is null.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
    }
}
```

```
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStampLTZ from a string using the format
// specified.
OracleTimeStampLTZ ts =
    new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110
- *Oracle Database SQL Reference* for further information on date format elements

**OracleTimeStampLTZ(int, int, int)**

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date using year, month, and day.

**Declaration**

```
// C#
public OracleTimeStampLTZ(int year, int month, int day);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**OracleTimeStampLTZ(int, int, int, int, int, int)**

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.

**Declaration**

```
// C#
public OracleTimeStampLTZ (int year, int month, int day, int hour,
    int minute, int second);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**OracleTimeStampLTZ(int, int, int, int, int, int, double)**

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

**Declaration**

```
// C#  
public OracleTimeStampLTZ(int year, int month, int day, int hour, int minute, int  
second, double millisecond);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *milliSeconds*  
The milliseconds provided. Range of *millisecond* is (0 to 999.999999).

**Exceptions**

*ArgumentOutOfRangeException* - The argument value for one or more of the parameters is out of the specified range.

*ArgumentException* - The argument values of the parameters cannot be used to construct a valid *OracleTimeStampLTZ* (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**OracleTimeStampLTZ(int, int, int, int, int, int, int)**

This constructor creates a new instance of the *OracleTimeStampLTZ* structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

**Declaration**

```
// C#  
public OracleTimeStampLTZ (int year, int month, int day, int hour,  
int minute, int second, int nanosecond);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *nanosecond*  
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

**Exceptions**

*ArgumentOutOfRangeException* - The argument value for one or more of the parameters is out of the specified range.

*ArgumentException* - The argument values of the parameters cannot be used to construct a valid *OracleTimeStampLTZ* (that is, the day is out of range for the month).

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**OracleTimeStampLTZ(byte [ ])**

This constructor creates a new instance of the *OracleTimeStampLTZ* structure and sets its value to the provided byte array, which is in the internal Oracle *TIMESTAMP WITH LOCAL TIME ZONE* format.

**Declaration**

```
// C#
public OracleTimeStampLTZ (byte[] bytes);
```

**Parameters**

- *bytes*  
A byte array that represents an Oracle *TIMESTAMP WITH LOCAL TIME ZONE* in Oracle internal format.

### Exceptions

`ArgumentException` - *bytes* is not in an internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format or *bytes* is not a valid Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

`ArgumentNullException` - *bytes* is null.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## OracleTimeStampLTZ Static Fields

The OracleTimeStampLTZ static fields are listed in [Table 14–107](#).

**Table 14–107 OracleTimeStampLTZ Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleTimeStampLTZ structure

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### MaxValue

This static field represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999.

### Declaration

```
// C#
public static readonly OracleTimeStampLTZ MaxValue;
```

### Remarks

This value is the maximum date and time in the client time zone.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### MinValue

This static field represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0.

### Declaration

```
// C#
public static readonly OracleTimeStampLTZ MinValue;
```

### Remarks

This value is the minimum date and time in the client time zone.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public static readonly OracleTimeStampLTZ Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## OracleTimeStampLTZ Static Methods

The OracleTimeStampLTZ static methods are listed in [Table 14–108](#).

**Table 14–108 OracleTimeStampLTZ Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleTimeStampLTZ values are equal (Overloaded)
<a href="#">GetLocalTimeZoneName</a>	Gets the client's local time zone name
<a href="#">GetLocalTimeZoneOffset</a>	Gets the client's local time zone offset relative to UTC
<a href="#">GetSysDate</a>	Gets an OracleTimeStampLTZ structure that represents the current date and time
<a href="#">GreaterThan</a>	Determines if the first of two OracleTimeStampLTZ values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleTimeStampLTZ values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleTimeStampLTZ values are not equal
<a href="#">Parse</a>	Gets an OracleTimeStampLTZ structure and sets its value for date and time using the supplied string
<a href="#">SetPrecision</a>	Returns a new instance of an OracleTimeStampLTZ with the specified fractional second precision

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Equals

This static method determines if two OracleTimeStampLTZ values are equal.

### Declaration

```
// C#
public static bool Equals(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

### Parameters

- *value1*  
The first OracleTimeStampLTZ.
- *value2*  
The second OracleTimeStampLTZ.

**Return Value**

Returns `true` if two `OracleTimeStampLTZ` values are equal. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**GetLocalTimeZoneName**

This static method gets the client's local time zone name.

**Declaration**

```
// C#  
public static string GetLocalTimeZoneName();
```

**Return Value**

A string containing the local time zone.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**GetLocalTimeZoneOffset**

This static method gets the client's local time zone offset relative to Coordinated Universal Time (UTC).

**Declaration**

```
// C#  
public static TimeSpan GetLocalTimeZoneOffset( );
```

**Return Value**

A `TimeSpan` structure containing the local time zone hours and time zone minutes.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)



## GetSysDate

This static method gets an `OracleTimeStampLTZ` structure that represents the current date and time.

### Declaration

```
// C#  
public static OracleTimeStampLTZ GetSysDate();
```

### Return Value

An `OracleTimeStampLTZ` structure that represents the current date and time.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## GreaterThan

This static method determines if the first of two `OracleTimeStampLTZ` values is greater than the second.

### Declaration

```
// C#  
public static bool GreaterThan(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

### Parameters

- *value1*  
The first `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

### Return Value

Returns `true` if the first of two `OracleTimeStampLTZ` values is greater than the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## GreaterThanOrEqualTo

This static method determines if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second.

### Declaration

```
// C#
public static bool GreaterThanOrEqualTo(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

### Parameters

- *value1*  
The first `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

### Return Value

Returns `true` if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## LessThan

This static method determines if the first of two `OracleTimeStampLTZ` values is less than the second.

### Declaration

```
// C#
public static bool LessThan(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

### Parameters

- *value1*  
The first `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

**Return Value**

Returns `true` if the first of two `OracleTimeStampLTZ` values is less than the second. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZs` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**LessThanOrEqual**

This static method determines if the first of two `OracleTimeStampLTZ` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool LessThanOrEqual(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

**Return Value**

Returns `true` if the first of two `OracleTimeStampLTZ` values is less than or equal to the second. Returns `false` otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZs` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## NotEquals

This static method determines if two `OracleTimeStampLTZ` values are not equal.

### Declaration

```
// C#
public static bool NotEquals(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

### Parameters

- *value1*  
The first `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

### Return Value

Returns `true` if two `OracleTimeStampLTZ` values are not equal. Returns `false` otherwise.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Parse

This static method creates an `OracleTimeStampLTZ` structure and sets its value using the supplied string.

### Declaration

```
// C#
public static OracleTimeStampLTZ Parse(string tsStr);
```

### Parameters

- *tsStr*  
A string that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

### Return Value

An `OracleTimeStampLTZ` structure.

### Exceptions

`ArgumentException` - The *tsStr* parameter is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the *tsStr* is not in the timestamp

format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The `tsStr` value is null.

### Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format specified.
        OracleTimeStampLTZ ts =
            OracleTimeStampLTZ.Parse("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## SetPrecision

This static method returns a new instance of an `OracleTimeStampLTZ` with the specified fractional second precision.

### Declaration

```
// C#
public static OracleTimeStampLTZ SetPrecision(OracleTimeStampLTZ value1,
```

```
int fracSecPrecision);
```

**Parameters**

- *value1*

The provided OracleTimeStampLTZ object.

- *fracSecPrecision*

The fractional second precision provided. Range of fractional second precision is (0 to 9).

**Return Value**

An OracleTimeStampLTZ structure with the specified fractional second precision

**Exceptions**

ArgumentOutOfRangeException - *fracSecPrecision* is out of the specified range.

**Remarks**

The value specified in the supplied *fracSecPrecision* parameter is used to perform a rounding off operation on the supplied OracleTimeStampLTZ value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by ToString().

**Example**

The OracleTimeStampLTZ with a value of "December 31, 9999 23:59:59.99" results in the string "December 31, 9999 23:59:59.99000" when SetPrecision() is called with the fractional second precision set to 5.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## OracleTimeStampLTZ Static Operators

The OracleTimeStampLTZ static operators are listed in [Table 14–109](#).

**Table 14–109 OracleTimeStampLTZ Static Operators**

Operator	Description
<a href="#">operator+</a>	Adds the supplied instance value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)
<a href="#">operator ==</a>	Determines if two OracleTimeStampLTZ values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleTimeStampLTZ values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if two OracleTimeStampLTZ values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two OracleTimeStampLTZ values is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
<a href="#">operator -</a>	Subtracts the supplied instance value from the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### operator+

operator+ adds the supplied value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.

### Overload List:

- [operator + \(OracleTimeStampLTZ, OracleIntervalDS\)](#)  
This static operator adds the supplied OracleIntervalDS to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.
- [operator + \(OracleTimeStampLTZ, OracleIntervalYM\)](#)  
This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.
- [operator + \(OracleTimeStampLTZ, TimeSpan\)](#)  
This static operator adds the supplied TimeSpan to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator + (OracleTimeStampLTZ, OracleIntervalDS)**

This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public static operator +(OracleTimeStampLTZ value1,  
    OracleIntervalDS value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampLTZ`.
- *value2*  
An `OracleIntervalDS`.

**Return Value**

An `OracleTimeStampLTZ`.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator + (OracleTimeStampLTZ, OracleIntervalYM)**

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public static operator +(OracleTimeStampLTZ value1,  
    OracleIntervalYM value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampLTZ`.
- *value2*  
An `OracleIntervalYM`.



**Return Value**

An OracleTimeStampLTZ.

**Remarks**

If either parameter has a null value, the returned OracleTimeStampLTZ has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator + (OracleTimeStampLTZ, TimeSpan)**

This static operator adds the supplied TimeSpan to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.

**Declaration**

```
// C#  
public static operator +(OracleTimeStampLTZ value1, TimeSpan value2);
```

**Parameters**

- *value1*  
An OracleTimeStampLTZ.
- *value2*  
A TimeSpan.

**Return Value**

An OracleTimeStampLTZ.

**Remarks**

If the OracleTimeStampLTZ instance has a null value, the returned OracleTimeStampLTZ has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator ==**

This static operator determines if two OracleTimeStampLTZ values are equal.

**Declaration**

```
// C#  
public static bool operator ==(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
The first OracleTimeStampLTZ.
- *value2*  
The second OracleTimeStampLTZ.

**Return Value**

Returns `true` if they are the same; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator >**

This static operator determines if the first of two OracleTimeStampLTZ values is greater than the second.

**Declaration**

```
// C#  
public static bool operator > (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
The first OracleTimeStampLTZ.
- *value2*  
The second OracleTimeStampLTZ.

**Return Value**

Returns `true` if the first OracleTimeStampLTZ value is greater than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator >=**

This static operator determines if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second.

**Declaration**

```
// C#  
public static bool operator >= (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

**Return Value**

Returns `true` if the first `OracleTimeStampLTZ` is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator !=**

This static operator determines if two `OracleTimeStampLTZ` values are not equal.

**Declaration**

```
// C#  
public static bool operator != (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampLTZ`.

- *value2*  
The second OracleTimeStampLTZ.

**Return Value**

Returns `true` if two OracleTimeStampLTZ values are not equal; otherwise returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator <**

This static operator determines if the first of two OracleTimeStampLTZ values is less than the second.

**Declaration**

```
// C#  
public static bool operator < (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
The first OracleTimeStampLTZ.
- *value2*  
The second OracleTimeStampLTZ.

**Return Value**

Returns `true` if the first OracleTimeStampLTZ is less than the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator <=**

This static operator determines if the first of two `OracleTimeStampLTZ` values is less than or equal to the second.

**Declaration**

```
// C#
public static bool operator <= (OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampLTZ`.
- *value2*  
The second `OracleTimeStampLTZ`.

**Return Value**

Returns `true` if the first `OracleTimeStampLTZ` is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**operator -**

`operator-` subtracts the supplied value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

**Overload List:**

- [operator - \(OracleTimeStampLTZ, OracleIntervalDS\)](#)  
This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampLTZ` value, and return a new `OracleTimeStampLTZ` structure.
- [operator - \(OracleTimeStampLTZ, OracleIntervalYM\)](#)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

- [operator - \(OracleTimeStampLTZ, TimeSpan\)](#)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### **operator - (OracleTimeStampLTZ, OracleIntervalDS)**

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampLTZ` value, and return a new `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public static operator - (OracleTimeStampLTZ value1,  
    OracleIntervalDS value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampLTZ`.
- *value2*  
An `OracleIntervalDS` instance.

**Return Value**

An `OracleTimeStampLTZ` structure.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### **operator - (OracleTimeStampLTZ, OracleIntervalYM)**

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#
```

```
public static operator - (OracleTimeStampLTZ value1,
    OracleIntervalYM value2);
```

### Parameters

- *value1*  
An OracleTimeStampLTZ.
- *value2*  
An OracleIntervalYM.

### Return Value

An OracleTimeStampLTZ structure.

### Remarks

If either parameter has a null value, the returned OracleTimeStampLTZ has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## operator - (OracleTimeStampLTZ, TimeSpan)

This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStampLTZ value, and returns a new OracleTimeStampLTZ structure.

### Declaration

```
// C#
public static operator -(OracleTimeStampLTZ value1, TimeSpan value2);
```

### Parameters

- *value1*  
An OracleTimeStampLTZ.
- *value2*  
A TimeSpan.

### Return Value

An OracleTimeStampLTZ structure.

### Remarks

If the OracleTimeStampLTZ instance has a null value, the returned OracleTimeStampLTZ structure has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## OracleTimeStampLTZ Static Type Conversions

The `OracleTimeStampLTZ` static type conversions are listed in [Table 14–110](#).

**Table 14–110 OracleTimeStampLTZ Static Type Conversions**

Operator	Description
<a href="#">explicit operator OracleTimeStampLTZ</a>	Converts an instance value to an <code>OracleTimeStampLTZ</code> structure (Overloaded)
<a href="#">implicit operator OracleTimeStampLTZ</a>	Converts an instance value to an <code>OracleTimeStampLTZ</code> structure (Overloaded)
<a href="#">explicit operator DateTime</a>	Converts an <code>OracleTimeStampLTZ</code> value to a <code>DateTime</code> structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### explicit operator OracleTimeStampLTZ

`explicit operator OracleTimeStampLTZ` converts the supplied value to an `OracleTimeStampLTZ` structure.

**Overload List:**

- [explicit operator OracleTimeStampLTZ\(OracleTimeStamp\)](#)  
This static type conversion operator converts an `OracleTimeStamp` value to an `OracleTimeStampLTZ` structure.
- [explicit operator OracleTimeStampLTZ\(OracleTimeStampTZ\)](#)  
This static type conversion operator converts an `OracleTimeStampTZ` value to an `OracleTimeStampLTZ` structure.
- [explicit operator OracleTimeStampLTZ\(string\)](#)  
This static type conversion operator converts the supplied string to an `OracleTimeStampLTZ` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### explicit operator OracleTimeStampLTZ(OracleTimeStamp)

This static type conversion operator converts an `OracleTimeStamp` value to an `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#
public static explicit operator OracleTimeStampLTZ (OracleTimeStamp value1);
```



**Parameters**

- *value1*  
An OracleTimeStamp.

**Return Value**

The OracleTimeStampLTZ structure contains the date and time of the OracleTimeStampTZ structure.

**Remarks**

If the OracleTimeStamp structure has a null value, the returned OracleTimeStampLTZ structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**explicit operator OracleTimeStampLTZ(OracleTimeStampTZ)**

This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStampLTZ structure.

**Declaration**

```
// C#
public static explicit operator OracleTimeStampLTZ
    (OracleTimeStampTZ value1);
```

**Parameters**

- *value1*  
An OracleTimeStampTZ instance.

**Return Value**

The OracleTimeStampLTZ structure contains the date and time in the OracleTimeStampTZ structure (which is normalized to the client local time zone).

**Remarks**

If the OracleTimeStampTZ structure has a null value, the returned OracleTimeStampLTZ structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**explicit operator OracleTimeStampLTZ(string)**

This static type conversion operator converts the supplied string to an OracleTimeStampLTZ structure.

**Declaration**

```
// C#
public static explicit operator OracleTimeStampLTZ (string tsStr);
```

**Parameters**

- *tsStr*

A string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

**Return Value**

A `OracleTimeStampLTZ`.

**Exceptions**

`ArgumentException` - The *tsStr* parameter is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the *tsStr* is not in the timestamp format specified by the thread's `OracleGlobalization.TimeStampFormat` property, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format specified.
        OracleTimeStampLTZ ts =
            new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110
- *Oracle Database SQL Reference* for further information on datetime format elements

**implicit operator OracleTimeStampLTZ**

implicit operator OracleTimeStampLTZ converts the supplied structure to an OracleTimeStampLTZ structure.

**Overload List:**

- [implicit operator OracleTimeStampLTZ\(OracleDate\)](#)  
This static type conversion operator converts an OracleDate value to an OracleTimeStampLTZ structure.
- [implicit operator OracleTimeStampLTZ\(DateTime\)](#)  
This static type conversion operator converts a DateTime structure to an OracleTimeStampLTZ structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**implicit operator OracleTimeStampLTZ(OracleDate)**

This static type conversion operator converts an OracleDate value to an OracleTimeStampLTZ structure.

**Declaration**

```
// C#
public static implicit operator OracleTimeStampLTZ(OracleDate value1);
```

**Parameters**

- *value1*  
An OracleDate.

**Return Value**

The returned OracleTimeStampLTZ structure contains the date and time in the OracleDate structure.

**Remarks**

If the OracleDate structure has a null value, the returned OracleTimeStampLTZ structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**implicit operator OracleTimeStampLTZ(DateTime)**

This static type conversion operator converts a `DateTime` structure to an `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public static implicit operator OracleTimeStampLTZ(DateTime value1);
```

**Parameters**

- *value1*  
A `DateTime` structure.

**Return Value**

An `OracleTimeStampLTZ` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**explicit operator DateTime**

This static type conversion operator converts an `OracleTimeStampLTZ` value to a `DateTime` structure.

**Declaration**

```
// C#  
public static explicit operator DateTime(OracleTimeStampLTZ value1);
```

**Parameters**

- *value1*  
An `OracleTimeStampLTZ` instance.

**Return Value**

A `DateTime` that contains the date and time in the current instance.

**Exceptions**

`OracleNullValueException` - The `OracleTimeStampLTZ` structure has a null value.

**Remarks**

The precision of the `OracleTimeStampLTZ` value can be lost during the conversion.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## OracleTimeStampLTZ Properties

The OracleTimeStampLTZ properties are listed in [Table 14–111](#).

**Table 14–111 OracleTimeStampLTZ Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> in Oracle internal format
<a href="#">Day</a>	Specifies the day component of an OracleTimeStampLTZ
<a href="#">IsNull</a>	Indicates whether or not the OracleTimeStampLTZ instance has a null value
<a href="#">Hour</a>	Specifies the hour component of an OracleTimeStampLTZ
<a href="#">Millisecond</a>	Specifies the millisecond component of an OracleTimeStampLTZ
<a href="#">Minute</a>	Specifies the minute component of an OracleTimeStampLTZ
<a href="#">Month</a>	Specifies the month component of an OracleTimeStampLTZ
<a href="#">Nanosecond</a>	Specifies the nanosecond component of an OracleTimeStampLTZ
<a href="#">Second</a>	Specifies the second component of an OracleTimeStampLTZ
<a href="#">Value</a>	Specifies the date and time that is stored in the OracleTimeStampLTZ structure
<a href="#">Year</a>	Specifies the year component of an OracleTimeStampLTZ

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

### BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` in Oracle internal format.

**Declaration**

```
// C#
public byte[] BinData {get;}
```

**Property Value**

A byte array that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` internal format.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Day

This property specifies the day component of an `OracleTimeStampLTZ`.

### Declaration

```
// C#  
public int Day{get;}
```

### Property Value

A number that represents the day. Range of `Day` is (1 to 31).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## IsNull

This property indicates whether or not the current instance has a null value.

### Declaration

```
// C#  
public bool IsNull{get;}
```

### Property Value

Returns `true` if the current instance contains a null value; otherwise, returns `false`.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Hour

This property specifies the hour component of an `OracleTimeStampLTZ`.

### Declaration

```
// C#  
public int Hour{get;}
```

### Property Value

A number that represents the hour. Range of `Hour` is (0 to 23).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Millisecond

This property gets the millisecond component of an `OracleTimeStampLTZ`.

**Declaration**

```
// C#  
public double Millisecond{get;}
```

**Property Value**

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999)

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Minute

This property gets the minute component of an `OracleTimeStampLTZ`.

**Declaration**

```
// C#  
public int Minute{get;}
```

**Property Value**

A number that represent a minute. Range of `Minute` is (0 to 59).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Month

This property gets the month component of an `OracleTimeStampLTZ`.

**Declaration**

```
// C#  
public int Month{get;}
```



**Property Value**

A number that represents a month. Range of `Month` is (1 to 12).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**Nanosecond**

This property gets the nanosecond component of an `OracleTimeStampLTZ`.

**Declaration**

```
// C#  
public int Nanosecond{get;}
```

**Property Value**

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**Second**

This property gets the second component of an `OracleTimeStampLTZ`.

**Declaration**

```
// C#  
public int Second{get;}
```

**Property Value**

A number that represents a second. Range of `Second` is (0 to 59).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Value

This property specifies the date and time that is stored in the `OracleTimeStampLTZ` structure.

### Declaration

```
// C#  
public DateTime Value{get;}
```

### Property Value

A `DateTime`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Year

This property gets the year component of an `OracleTimeStampLTZ`.

### Declaration

```
// C#  
public int Year{get;}
```

### Property Value

A number that represents a year. The range of `Year` is (-4712 to 9999).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## OracleTimeStampLTZ Methods

The `OracleTimeStampLTZ` methods are listed in [Table 14–112](#).

**Table 14–112 OracleTimeStampLTZ Methods**

Methods	Description
<a href="#">AddDays</a>	Adds the supplied number of days to the current instance
<a href="#">AddHours</a>	Adds the supplied number of hours to the current instance
<a href="#">AddMilliseconds</a>	Adds the supplied number of milliseconds to the current instance
<a href="#">AddMinutes</a>	Adds the supplied number of minutes to the current instance
<a href="#">AddMonths</a>	Adds the supplied number of months to the current instance
<a href="#">AddNanoseconds</a>	Adds the supplied number of nanoseconds to the current instance
<a href="#">AddSeconds</a>	Adds the supplied number of seconds to the current instance
<a href="#">AddYears</a>	Adds the supplied number of years to the current instance
<a href="#">CompareTo</a>	Compares the current <code>OracleTimeStampLTZ</code> instance to an object and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleTimeStampLTZ</code> instance (Overloaded)
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleTimeStampLTZ</code> instance
<a href="#">GetDaysBetween</a>	Subtracts an <code>OracleTimeStampLTZ</code> from the current instance and returns an <code>OracleIntervalDS</code> that represents the difference
<a href="#">GetYearsBetween</a>	Subtracts an <code>OracleTimeStampLTZ</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the difference
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToOracleDate</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleDate</code> structure
<a href="#">ToOracleTimeStamp</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleTimeStamp</code> structure
<a href="#">ToOracleTimeStampTZ</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleTimeStampTZ</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleTimeStampLTZ</code> structure to a string
<a href="#">ToUniversalTime</a>	Converts the current local time to Coordinated Universal Time (UTC)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## AddDays

This method adds the supplied number of days to the current instance.

### Declaration

```
// C#  
public OracleTimeStampLTZ AddDays(double days);
```

### Parameters

- *days*  
The supplied number of days. Range is  $(-1,000,000,000 < days < 1,000,000,000)$

### Return Value

An `OracleTimeStampLTZ`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## AddHours

This method adds the supplied number of hours to the current instance.

### Declaration

```
// C#  
public OracleTimeStampLTZ AddHours(double hours);
```

### Parameters

- *hours*  
The supplied number of hours. Range is  $(-24,000,000,000 < hours < 24,000,000,000)$ .

### Return Value

An `OracleTimeStampLTZ`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**AddMilliseconds**

This method adds the supplied number of milliseconds to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampLTZ AddMilliseconds(double milliseconds);
```

**Parameters**

- *milliseconds*

The supplied number of milliseconds. Range is  $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$ .

**Return Value**

An OracleTimeStampLTZ.

**Exceptions**

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**AddMinutes**

This method adds the supplied number of minutes to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampLTZ AddMinutes(double minutes);
```

**Parameters**

- *minutes*

The supplied number of minutes. Range is  $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$ .

**Return Value**

An OracleTimeStampLTZ.

**Exceptions**

OracleNullValueException - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## AddMonths

This method adds the supplied number of months to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampLTZ AddMonths(long months);
```

**Parameters**

- *months*

The supplied number of months. Range is  $(-12,000,000,000 < months < 12,000,000,000)$ .

**Return Value**

An `OracleTimeStampLTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampLTZ AddNanoseconds(long nanoseconds);
```

**Parameters**

- *nanoseconds*

The supplied number of nanoseconds.

**Return Value**

An `OracleTimeStampLTZ`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## AddSeconds

This method adds the supplied number of seconds to the current instance.

### Declaration

```
// C#  
public OracleTimeStampLTZ AddSeconds(double seconds);
```

### Parameters

- *seconds*

The supplied number of seconds. Range is  $(-8.64 * 10^{13} < seconds < 8.64 * 10^{13})$ .

### Return Value

An `OracleTimeStampLTZ`.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## AddYears

This method adds the supplied number of years to the current instance

### Declaration

```
// C#  
public OracleTimeStampLTZ AddYears(int years);
```

### Parameters

- *years*

The supplied number of years. Range is  $(-999,999,999 \leq years \leq 999,999,999)$

### Return Value

An `OracleTimeStampLTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**CompareTo**

This method compares the current `OracleTimeStampLTZ` instance to an object, and returns an integer that represents their relative values.

**Declaration**

```
// C#  
public int CompareTo(object obj);
```

**Parameters**

- *obj*

The object being compared to the current `OracleTimeStampLTZ` instance.

**Return Value**

The method returns a number that is:

- Less than zero: if the current `OracleTimeStampLTZ` instance value is less than that of *obj*.
- Zero: if the current `OracleTimeStampLTZ` instance and *obj* values are equal.
- Greater than zero: if the current `OracleTimeStampLTZ` instance value is greater than that of *obj*.

**Implements**

`IComparable`

**Exceptions**

`ArgumentException` - The *obj* parameter is not of type `OracleTimeStampLTZ`.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStampLTZ`s. For example, comparing an `OracleTimeStampLTZ` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStampLTZ` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.



**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## Equals

Overrides Object

This method determines whether or not an object has the same date and time as the current OracleTimeStampLTZ instance.

**Declaration**

```
// C#  
public override bool Equals(object obj);
```

**Parameters**

- *obj*

The object being compared to the current OracleTimeStampLTZ instance.

**Return Value**

Returns true if the *obj* is of type OracleTimeStampLTZ and represents the same date and time; otherwise, returns false.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

## GetHashCode

Overrides Object

This method returns a hash code for the OracleTimeStampLTZ instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

A number that represents the hash code.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**GetDaysBetween**

This method subtracts an `OracleTimeStampLTZ` value from the current instance and returns an `OracleIntervalDS` that represents the difference.

**Declaration**

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStampLTZ value1);
```

**Parameters**

- *value1*

The `OracleTimeStampLTZ` value being subtracted.

**Return Value**

An `OracleIntervalDS` that represents the interval between two `OracleTimeStampLTZ` values.

**Remarks**

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**GetYearsBetween**

This method subtracts an `OracleTimeStampLTZ` value from the current instance and returns an `OracleIntervalYM` that represents the time interval.

**Declaration**

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStampLTZ value1);
```

**Parameters**

- *value1*

The `OracleTimeStampLTZ` value being subtracted.

**Return Value**

An `OracleIntervalYM` that represents the interval between two `OracleTimeStampLTZ` values.

**Remarks**

If either the current instance or the parameter has a null value, the returned `OracleIntervalYM` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**ToOracleDate**

This method converts the current `OracleTimeStampLTZ` structure to an `OracleDate` structure.

**Declaration**

```
// C#  
public OracleDate ToOracleDate();
```

**Return Value**

The returned `OracleDate` structure contains the date and time in the current instance.

**Remarks**

The precision of the `OracleTimeStampLTZ` value can be lost during the conversion.

If the current instance has a null value, the value of the returned `OracleDate` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**ToOracleTimeStamp**

This method converts the current `OracleTimeStampLTZ` structure to an `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

**Return Value**

The returned `OracleTimeStamp` contains the date and time in the current instance.

**Remarks**

If the current instance has a null value, the value of the returned `OracleTimeStamp` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

**ToOracleTimeStampTZ**

This method converts the current `OracleTimeStampLTZ` structure to an `OracleTimeStampTZ` structure.

**Declaration**

```
// C#  
public OracleTimeStampTZ ToOracleTimeStampTZ();
```

**Return Value**

The returned `OracleTimeStampTZ` contains the date and time of the current instance, with the time zone set to the `OracleGlobalization.TimeZone` from the thread.

**Remarks**

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**ToString**

Overrides `Object`

This method converts the current `OracleTimeStampLTZ` structure to a string.

**Declaration**

```
// C#  
public override string ToString();
```

**Return Value**

A string that represents the same date and time as the current `OracleTimeStampLTZ` structure.

**Remarks**

The returned value is a string representation of the `OracleTimeStampLTZ` in the format specified by the `OracleGlobalization.TimeStampFormat` property of the thread.

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's

OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ToStringSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format
        // specified.
        OracleTimeStampLTZ ts =
            new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimestampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## ToUniversalTime

This method converts the current local time to Coordinated Universal Time (UTC).

### Declaration

```
// C#
public OracleTimeStampTZ ToUniversalTime();
```

### Return Value

An OracleTimeStampTZ structure.

### Remarks

If the current instance has a null value, the value of the returned OracleTimeStampTZ structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

---

## OracleTimeStampTZ Structure

The `OracleTimeStampTZ` structure represents the Oracle `TIMESTAMP WITH TIME ZONE` data type to be stored in or retrieved from a database. Each `OracleTimeStampTZ` stores the following information: year, month, day, hour, minute, second, nanosecond, and time zone.

### Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStampTZ`

### Declaration

```
// ADO.NET 2.0: C#
public struct OracleTimeStampTZ : IComparable, INullable, IXmlSerializable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampTZSample
{
    static void Main()
    {
        // Set the nls parameters for the current thread
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeZone = "US/Eastern";
        info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        info.TimestampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Create an OracleTimeStampTZ in US/Pacific time zone
        OracleTimeStampTZ tstz1=new OracleTimeStampTZ("11-NOV-1999 "+"
            "11:02:33.444 AM US/Pacific");

        // Note that ToOracleTimeStampTZ uses the thread's time zone region,
        // "US/Eastern"
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");
        OracleTimeStampTZ tstz2 = ts.ToOracleTimeStampTZ();

        // Calculate the difference between tstz1 and tstz2
        OracleIntervalDS idsDiff = tstz1.GetDaysBetween(tstz2);

        // Display information
        Console.WriteLine("tstz1.TimeZone = " + tstz1.TimeZone);

        // Prints "US/Pacific"
```

```
Console.WriteLine("tstz2.TimeZone = " + tstz2.TimeZone);

// Prints "US/Eastern"
Console.WriteLine("idsDiff.Hours = " + idsDiff.Hours); // Prints 3
Console.WriteLine("idsDiff.Minutes = " + idsDiff.Minutes); // Prints 0
}
}
```

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Members](#)
- [OracleTimeStampTZ Constructors](#)
- [OracleTimeStampTZ Static Fields](#)
- [OracleTimeStampTZ Static Methods](#)
- [OracleTimeStampTZ Static Operators](#)
- [OracleTimeStampTZ Static Type Conversions](#)
- [OracleTimeStampTZ Properties](#)
- [OracleTimeStampTZ Methods](#)



## OracleTimeStampTZ Members

OracleTimeStampTZ members are listed in the following tables:

### OracleTimeStampTZ Constructors

OracleTimeStampTZ constructors are listed in [Table 14–113](#)

**Table 14–113 OracleTimeStampTZ Constructors**

Constructor	Description
<a href="#">OracleTimeStampTZ Constructors</a>	Instantiates a new instance of OracleTimeStampTZ structure (Overloaded)

### OracleTimeStampTZ Static Fields

The OracleTimeStampTZ static fields are listed in [Table 14–114](#).

**Table 14–114 OracleTimeStampTZ Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleTimeStampTZ structure

### OracleTimeStampTZ Static Methods

The OracleTimeStampTZ static methods are listed in [Table 14–115](#).

**Table 14–115 OracleTimeStampTZ Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleTimeStampTZ values are equal (Overloaded)
<a href="#">GetSysDate</a>	Gets an OracleTimeStampTZ structure that represents the current date and time
<a href="#">GreaterThan</a>	Determines if the first of two OracleTimeStampTZ values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleTimeStampTZ values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleTimeStampTZ values are not equal

**Table 14–115 (Cont.) OracleTimeStampTZ Static Methods**

Methods	Description
<a href="#">Parse</a>	Gets an OracleTimeStampTZ structure and sets its value for date and time using the supplied string
<a href="#">SetPrecision</a>	Returns a new instance of an OracleTimeStampTZ with the specified fractional second precision

### OracleTimeStampTZ Static Operators

The OracleTimeStampTZ static operators are listed in [Table 14–116](#).

**Table 14–116 OracleTimeStampTZ Static Operators**

Operator	Description
<a href="#">operator +</a>	Adds the supplied instance value to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded)
<a href="#">operator ==</a>	Determines if two OracleTimeStampTZ values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleTimeStampTZ values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if two OracleTimeStampTZ values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two OracleTimeStampTZ values is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
<a href="#">operator -</a>	Subtracts the supplied instance value from the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded)

### OracleTimeStampTZ Static Type Conversions

The OracleTimeStampTZ static type conversions are listed in [Table 14–117](#).

**Table 14–117 OracleTimeStampTZ Static Type Conversions**

Operator	Description
<a href="#">explicit operator OracleTimeStampTZ</a>	Converts an instance value to an OracleTimeStampTZ structure (Overloaded)
<a href="#">implicit operator OracleTimeStampTZ</a>	Converts an instance value to an OracleTimeStampTZ structure (Overloaded)
<a href="#">explicit operator DateTime</a>	Converts an OracleTimeStampTZ value to a DateTime structure

## OracleTimeStampTZ Properties

The OracleTimeStampTZ properties are listed in [Table 14–118](#).

**Table 14–118 OracleTimeStampTZ Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents an Oracle TIMESTAMP WITH TIME ZONE in Oracle internal format
<a href="#">Day</a>	Specifies the day component of an OracleTimeStampTZ in the current time zone
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Hour</a>	Specifies the hour component of an OracleTimeStampTZ in the current time zone
<a href="#">Millisecond</a>	Specifies the millisecond component of an OracleTimeStampTZ in the current time zone
<a href="#">Minute</a>	Specifies the minute component of an OracleTimeStampTZ in the current time zone
<a href="#">Month</a>	Specifies the month component of an OracleTimeStampTZ in the current time zone
<a href="#">Nanosecond</a>	Specifies the nanosecond component of an OracleTimeStampTZ in the current time zone
<a href="#">Second</a>	Specifies the second component of an OracleTimeStampTZ in the current time zone
<a href="#">TimeZone</a>	Returns the time zone of the OracleTimeStampTZ instance
<a href="#">Value</a>	Returns the date and time that is stored in the OracleTimeStampTZ structure in the current time zone
<a href="#">Year</a>	Specifies the year component of an OracleTimeStampTZ

## OracleTimeStampTZ Methods

The OracleTimeStampTZ methods are listed in [Table 14–119](#).

**Table 14–119 OracleTimeStampTZ Methods**

Methods	Description
<a href="#">AddDays</a>	Adds the supplied number of days to the current instance
<a href="#">AddHours</a>	Adds the supplied number of hours to the current instance
<a href="#">AddMilliseconds</a>	Adds the supplied number of milliseconds to the current instance
<a href="#">AddMinutes</a>	Adds the supplied number of minutes to the current instance
<a href="#">AddMonths</a>	Adds the supplied number of months to the current instance
<a href="#">AddNanoseconds</a>	Adds the supplied number of nanoseconds to the current instance

**Table 14–119 (Cont.) OracleTimeStampTZ Methods**

<b>Methods</b>	<b>Description</b>
<a href="#">AddSeconds</a>	Adds the supplied number of seconds to the current instance
<a href="#">AddYears</a>	Adds the supplied number of years to the current instance
<a href="#">CompareTo</a>	Compares the current <code>OracleTimeStampTZ</code> instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current <code>OracleTimeStampTZ</code> instance
<a href="#">GetDaysBetween</a>	Subtracts an <code>OracleTimeStampTZ</code> from the current instance and returns an <code>OracleIntervalDS</code> that represents the time interval
<a href="#">GetHashCode</a>	Returns a hash code for the <code>OracleTimeStampTZ</code> instance
<a href="#">GetTimeZoneOffset</a>	Gets the time zone information in hours and minutes of the current <code>OracleTimeStampTZ</code>
<a href="#">GetYearsBetween</a>	Subtracts an <code>OracleTimeStampTZ</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the time interval
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">ToLocalTime</a>	Converts the current <code>OracleTimeStampTZ</code> instance to local time
<a href="#">ToOracleDate</a>	Converts the current <code>OracleTimeStampTZ</code> structure to an <code>OracleDate</code> structure
<a href="#">ToOracleTimeStampLTZ</a>	Converts the current <code>OracleTimeStampTZ</code> structure to an <code>OracleTimeStampLTZ</code> structure
<a href="#">ToOracleTimeStamp</a>	Converts the current <code>OracleTimeStampTZ</code> structure to an <code>OracleTimeStamp</code> structure
<a href="#">ToString</a>	Converts the current <code>OracleTimeStampTZ</code> structure to a string
<a href="#">ToUniversalTime</a>	Converts the current datetime to Coordinated Universal Time (UTC)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)

## OracleTimeStampTZ Constructors

The `OracleTimeStampTZ` constructors create new instances of the `OracleTimeStampTZ` structure.

### Overload List:

- [OracleTimeStampTZ\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStampTZ\(DateTime, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value and the supplied time zone data.
- [OracleTimeStampTZ\(string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.
- [OracleTimeStampTZ\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, and day.
- [OracleTimeStampTZ\(int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStampTZ\(int, int, int, int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStampTZ\(int, int, int, int, int, int, double, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, millisecond, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStampTZ\(int, int, int, int, int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, nanosecond, and time zone data.

- [OracleTimeStampTZ\(byte \[ \]\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value to the provided byte array, that represents the internal Oracle `TIMESTAMP WITH TIME ZONE` format.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### OracleTimeStampTZ(DateTime)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value.

**Declaration**

```
// C#  
public OracleTimeStampTZ (DateTime dt);
```

**Parameters**

- *dt*

The supplied `DateTime` value.

**Remarks**

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

**Exceptions**

`ArgumentException` - The *dt* parameter cannot be used to construct a valid `OracleTimeStampTZ`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### OracleTimeStampTZ(DateTime, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure with the supplied `DateTime` value and the time zone data.

**Declaration**

```
// C#  
public OracleTimeStampTZ (DateTime value1, string timeZone);
```

**Parameters**

- *value1*

The supplied `DateTime` value.

- *timeZone*

The time zone data provided.

### Exceptions

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ`.

### Remarks

*timeZone* can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

---

**Note:** PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

---

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ(string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.

### Declaration

```
// C#
public OracleTimeStampTZ (string tsStr);
```

### Parameters

- *tsStr*

A string that represents an Oracle `TIMESTAMP WITH TIME ZONE`.

### Exceptions

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH TIME ZONE` or the *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread.

`ArgumentNullException` - The *tsStr* value is null.

### Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

### Example

```
// C#
```

```
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampTZSample
{
    static void Main()
    {
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampTZ from a string using the format specified.
        OracleTimeStampTZ tstz = new OracleTimeStampTZ("11-NOV-1999" +
            "11:02:33.444 AM US/Pacific");

        // Set the nls_timestamp_tz_format for the ToString() method
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM US/Pacific"
        Console.WriteLine(tstz.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class" on page 10-2](#)
- ["Globalization Support" on page 3-110](#)
- *Oracle Database SQL Reference* for further information on date format elements

**OracleTimeStampTZ(int, int, int)**

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, and day.

**Declaration**

```
// C#
public OracleTimeStampTZ(int year, int month, int day);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).



**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

**Remarks**

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**OracleTimeStampTZ(int, int, int, string)**

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, and time zone data.

**Declaration**

```
// C#
public OracleTimeStampTZ(int year, int month, int day,
    string timeZone);
```

**Parameters**

- *year*

The year provided. Range of *year* is (-4712 to 9999).
- *month*

The month provided. Range of *month* is (1 to 12).
- *day*

The day provided. Range of *day* is (1 to 31).
- *timeZone*

The time zone data provided.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

**Remarks**

*timeZone* can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

---

---

**Note:** PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

---

---

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.

### Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second);
```

### Parameters

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).

### Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

### Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**OracleTimeStampTZ(int, int, int, int, int, int, string)**

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and time zone data.

**Declaration**

```
// C#
public OracleTimeStampTZ (int year, int month, int day, int hour,
    int minute, int second, string timeZone);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *timeZone*  
The time zone data provided.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range of the month or the time zone is invalid).

**Remarks**

*timeZone* can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

---

---

**Note:** PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

---

---

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ(int, int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

### Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, double millisecond);
```

### Parameters

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *millisecond*  
The millisecond provided. Range of *millisecond* is (0 to 999.999999).

### Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

### Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**OracleTimeStampTZ(int, int, int, int, int, int, double, string)**

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, millisecond, and time zone data.

**Declaration**

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, double millisecond, string timeZone);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *millisecond*  
The millisecond provided. Range of *millisecond* is (0 to 999.999999).
- *timeZone*  
The time zone data provided.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

**Remarks**

*timeZone* can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

---

**Note:** PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

---

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### OracleTimeStampTZ(int, int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

#### Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, int nanosecond);
```

#### Parameters

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *nanosecond*  
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

#### Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

#### Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**OracleTimeStampTZ(int, int, int, int, int, int, int, string)**

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, nanosecond, and time zone data.

**Declaration**

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, int nanosecond, string timeZone);
```

**Parameters**

- *year*  
The year provided. Range of *year* is (-4712 to 9999).
- *month*  
The month provided. Range of *month* is (1 to 12).
- *day*  
The day provided. Range of *day* is (1 to 31).
- *hour*  
The hour provided. Range of *hour* is (0 to 23).
- *minute*  
The minute provided. Range of *minute* is (0 to 59).
- *second*  
The second provided. Range of *second* is (0 to 59).
- *nanosecond*  
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).
- *timeZone*  
The time zone data provided.

**Exceptions**

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

**Remarks**

*timeZone* can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

---

**Note:** PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

---

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ(byte [ ])

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value to the provided byte array, that represents the internal Oracle `TIMESTAMP WITH TIME ZONE` format.

### Declaration

```
// C#  
public OracleTimeStampLTZ (byte[] bytes);
```

### Parameters

- *bytes*

The provided byte array that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

### Exceptions

`ArgumentException` - *bytes* is not in internal Oracle `TIMESTAMP WITH TIME ZONE` format or *bytes* is not a valid Oracle `TIMESTAMP WITH TIME ZONE`.

`ArgumentNullException` - *bytes* is null.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)



## OracleTimeStampTZ Static Fields

The OracleTimeStampTZ static fields are listed in [Table 14–120](#).

**Table 14–120 OracleTimeStampTZ Static Fields**

Field	Description
<a href="#">MaxValue</a>	Represents the maximum valid date for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999
<a href="#">MinValue</a>	Represents the minimum valid date for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0
<a href="#">Null</a>	Represents a null value that can be assigned to an instance of the OracleTimeStampTZ structure

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### MaxValue

This static field represents the maximum valid datetime time for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999.

**Declaration**

```
// C#
public static readonly OracleTimeStampTZ MaxValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### MinValue

This static field represents the minimum valid datetime for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0.

**Declaration**

```
// C#
public static readonly OracleTimeStampTZ MinValue;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStampTZ` structure.

### Declaration

```
// C#  
public static readonly OracleTimeStampTZ Null;
```

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ Static Methods

The OracleTimeStampTZ static methods are listed in [Table 14–121](#).

**Table 14–121 OracleTimeStampTZ Static Methods**

Methods	Description
<a href="#">Equals</a>	Determines if two OracleTimeStampTZ values are equal (Overloaded)
<a href="#">GetSysDate</a>	Gets an OracleTimeStampTZ structure that represents the current date and time
<a href="#">GreaterThan</a>	Determines if the first of two OracleTimeStampTZ values is greater than the second
<a href="#">GreaterThanOrEqual</a>	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
<a href="#">LessThan</a>	Determines if the first of two OracleTimeStampTZ values is less than the second
<a href="#">LessThanOrEqual</a>	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
<a href="#">NotEquals</a>	Determines if two OracleTimeStampTZ values are not equal
<a href="#">Parse</a>	Gets an OracleTimeStampTZ structure and sets its value for date and time using the supplied string
<a href="#">SetPrecision</a>	Returns a new instance of an OracleTimeStampTZ with the specified fractional second precision

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Equals

This static method determines if two OracleTimeStampTZ values are equal.

### Declaration

```
// C#
public static bool Equals(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

### Parameters

- *value1*  
The first OracleTimeStampTZ.
- *value2*  
The second OracleTimeStampTZ.

### Return Value

Returns true if two OracleTimeStampTZ values are equal. Returns false otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**GetSysDate**

This static method gets an `OracleTimeStampTZ` structure that represents the current date and time.

**Declaration**

```
// C#  
public static OracleTimeStampTZ GetSysDate();
```

**Return Value**

An `OracleTimeStampTZ` structure that represents the current date and time.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**GreaterThan**

This static method determines if the first of two `OracleTimeStampTZ` values is greater than the second.

**Declaration**

```
// C#  
public static bool GreaterThan(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampTZ`.
- *value2*  
The second `OracleTimeStampTZ`.

**Return Value**

Returns `true` if the first of two `OracleTimeStampTZ` values is greater than the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## GreaterThanOrEqualTo

This static method determines if the first of two `OracleTimeStampTZ` values is greater than or equal to the second.

### Declaration

```
// C#  
public static bool GreaterThanOrEqualTo(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

### Parameters

- *value1*  
The first `OracleTimeStampTZ`.
- *value2*  
The second `OracleTimeStampTZ`.

### Return Value

Returns `true` if the first of two `OracleTimeStampTZ` values is greater than or equal to the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## LessThan

This static method determines if the first of two `OracleTimeStampTZ` values is less than the second.

**Declaration**

```
// C#  
public static bool LessThan(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*  
The first OracleTimeStampTZ.
- *value2*  
The second OracleTimeStampTZ.

**Return Value**

Returns true if the first of two OracleTimeStampTZ values is less than the second. Returns false otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**LessThanOrEqual**

This static method determines if the first of two OracleTimeStampTZ values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool LessThanOrEqual(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*  
The first OracleTimeStampTZ.
- *value2*  
The second OracleTimeStampTZ.

**Return Value**

Returns true if the first of two OracleTimeStampTZ values is less than or equal to the second. Returns false otherwise.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## NotEquals

This static method determines if two `OracleTimeStampTZ` values are not equal.

### Declaration

```
// C#
public static bool NotEquals(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

### Parameters

- *value1*  
The first `OracleTimeStampTZ`.
- *value2*  
The second `OracleTimeStampTZ`.

### Return Value

Returns `true` if two `OracleTimeStampTZ` values are not equal. Returns `false` otherwise.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Parse

This static method returns an `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.

### Declaration

```
// C#
public static OracleTimeStampTZ Parse(string tsStr);
```

**Parameters**

- *tsStr*

A string that represents an Oracle `TIMESTAMP WITH TIME ZONE`.

**Return Value**

An `OracleTimeStampTZ` structure.

**Exceptions**

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH TIME ZONE` or the *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_TZ_FORMAT` parameter.

`ArgumentNullException` - The *tsStr* value is null.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_tz_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampTZ from a string using the format specified.
        OracleTimeStampTZ tstz = OracleTimeStampTZ.Parse("11-NOV-1999 " +
            "11:02:33.444 AM US/Pacific");

        // Set the nls_timestamp_tz_format for the ToString() method
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM US/Pacific"
        Console.WriteLine(tstz.ToString());
    }
}
```



**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## SetPrecision

This static method returns a new instance of an `OracleTimeStampTZ` with the specified fractional second precision.

**Declaration**

```
// C#  
public static OracleTimeStampTZ SetPrecision(OracleTimeStampTZ value1,  
    int fracSecPrecision);
```

**Parameters**

- *value1*  
The provided `OracleTimeStampTZ` object.
- *fracSecPrecision*  
The fractional second precision provided. Range of fractional second precision is (0 to 9).

**Return Value**

An `OracleTimeStampTZ` structure with the specified fractional second precision

**Exceptions**

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

**Remarks**

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleTimeStampTZ` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

**Example**

The `OracleTimeStampTZ` with a value of "December 31, 9999 23:59:59.99 US/Pacific" results in the string "December 31, 9999 23:59:59.99000 US/Pacific" when `SetPrecision()` is called with the fractional second precision set to 5.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ Static Operators

The OracleTimeStampTZ static operators are listed in [Table 14–122](#).

**Table 14–122 OracleTimeStampTZ Static Operators**

Operator	Description
<a href="#">operator +</a>	Adds the supplied instance value to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded)
<a href="#">operator ==</a>	Determines if two OracleTimeStampTZ values are equal
<a href="#">operator &gt;</a>	Determines if the first of two OracleTimeStampTZ values is greater than the second
<a href="#">operator &gt;=</a>	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
<a href="#">operator !=</a>	Determines if two OracleTimeStampTZ values are not equal
<a href="#">operator &lt;</a>	Determines if the first of two OracleTimeStampTZ values is less than the second
<a href="#">operator &lt;=</a>	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
<a href="#">operator -</a>	Subtracts the supplied instance value from the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded)

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### operator +

`operator+` adds the supplied structure to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

#### Overload List:

- [operator +\(OracleTimeStampTZ, OracleIntervalDS\)](#)  
This static operator adds the supplied OracleIntervalDS to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.
- [operator +\(OracleTimeStampTZ, OracleIntervalYM\)](#)  
This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.
- [operator +\(OracleTimeStampTZ, TimeSpan\)](#)  
This static operator adds the supplied TimeSpan to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator +(OracleTimeStampTZ, OracleIntervalDS)**

This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

**Declaration**

```
// C#
public static operator +(OracleTimeStampTZ value1,
    OracleIntervalDS value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampTZ`.
- *value2*  
An `OracleIntervalDS`.

**Return Value**

An `OracleTimeStampTZ`.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStampTZ` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator +(OracleTimeStampTZ, OracleIntervalYM)**

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

**Declaration**

```
// C#
public static operator +(OracleTimeStampTZ value1,
    OracleIntervalYM value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampTZ`.
- *value2*  
An `OracleIntervalYM`.

**Return Value**

An OracleTimeStampTZ.

**Remarks**

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator +(OracleTimeStampTZ, TimeSpan)**

This static operator adds the supplied TimeSpan to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

**Declaration**

```
// C#  
public static operator +(OracleTimeStampTZ value1, TimeSpan value2);
```

**Parameters**

- *value1*  
An OracleTimeStampTZ.
- *value2*  
A TimeSpan.

**Return Value**

An OracleTimeStampTZ.

**Remarks**

If the OracleTimeStampTZ instance has a null value, the returned OracleTimeStampTZ has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator ==**

This static operator determines if two OracleTimeStampTZ values are equal.

**Declaration**

```
// C#  
public static bool operator ==(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*

The first `OracleTimeStampTZ`.

- `value2`

The second `OracleTimeStampTZ`.

### Return Value

Returns `true` if they are equal; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## operator >

This static operator determines if the first of two `OracleTimeStampTZ` values is greater than the second.

### Declaration

```
// C#
public static bool operator > (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

### Parameters

- `value1`

The first `OracleTimeStampTZ`.

- `value2`

The second `OracleTimeStampTZ`.

### Return Value

Returns `true` if the first `OracleTimeStampTZ` value is greater than the second; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator >=**

This static operator determines if the first of two `OracleTimeStampTZ` values is greater than or equal to the second.

**Declaration**

```
// C#
public static bool operator >= (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampTZ`.
- *value2*  
The second `OracleTimeStampTZ`.

**Return Value**

Returns `true` if the first `OracleTimeStampTZ` is greater than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator !=**

This static operator determines if two `OracleTimeStampTZ` values are not equal.

**Declaration**

```
// C#
public static bool operator != (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampTZ`.

- *value2*  
The second OracleTimeStampTZ.

### Return Value

Returns `true` if two OracleTimeStampTZ values are not equal; otherwise, returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## operator <

This static operator determines if the first of two OracleTimeStampTZ values is less than the second.

### Declaration

```
// C#
public static bool operator < (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

### Parameters

- *value1*  
The first OracleTimeStampTZ.
- *value2*  
The second OracleTimeStampTZ.

### Return Value

Returns `true` if the first OracleTimeStampTZ is less than the second; otherwise returns `false`.

### Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator <=**

This static operator determines if the first of two `OracleTimeStampTZ` values is less than or equal to the second.

**Declaration**

```
// C#  
public static bool operator <= (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

**Parameters**

- *value1*  
The first `OracleTimeStampTZ`.
- *value2*  
The second `OracleTimeStampTZ`.

**Return Value**

Returns `true` if the first `OracleTimeStampTZ` is less than or equal to the second; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator -**

`operator-` subtracts the supplied value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

**Overload List:**

- [operator - \(OracleTimeStampTZ, OracleIntervalDS\)](#)  
This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampTZ` value, and return a new `OracleTimeStampTZ` structure.
- [operator - \(OracleTimeStampTZ, OracleIntervalYM\)](#)



This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

- [operator - \(OracleTimeStampTZ value1, TimeSpan value2\)](#)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### operator - (OracleTimeStampTZ, OracleIntervalDS)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampTZ` value, and return a new `OracleTimeStampTZ` structure.

**Declaration**

```
// C#
public static operator - (OracleTimeStampTZ value1,
    OracleIntervalDS value2);
```

**Parameters**

- *value1*  
An `OracleTimeStampTZ`.
- *value2*  
An `OracleIntervalDS`.

**Return Value**

An `OracleTimeStampTZ` structure.

**Remarks**

If either parameter has a null value, the returned `OracleTimeStampTZ` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### operator - (OracleTimeStampTZ, OracleIntervalYM)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

**Declaration**

```
// C#
public static operator - (OracleTimeStampTZ value1,
```

```
OracleIntervalYM value2);
```

**Parameters**

- *value1*  
An OracleTimeStampTZ.
- *value2*  
An OracleIntervalYM.

**Return Value**

An OracleTimeStampTZ structure.

**Remarks**

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**operator - (OracleTimeStampTZ value1, TimeSpan value2)**

This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStampTZ value, and returns a new OracleTimeStampTZ structure.

**Declaration**

```
// C#  
public static operator - (OracleTimeStampTZ value1, TimeSpan value2);
```

**Parameters**

- *value1*  
An OracleTimeStampTZ.
- *value2*  
A TimeSpan.

**Return Value**

An OracleTimeStampTZ structure.

**Remarks**

If the OracleTimeStampTZ instance has a null value, the returned OracleTimeStampTZ structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ Static Type Conversions

The OracleTimeStampTZ static type conversions are listed in [Table 14–123](#).

**Table 14–123 OracleTimeStampTZ Static Type Conversions**

Operator	Description
<a href="#">explicit operator OracleTimeStampTZ</a>	Converts an instance value to an OracleTimeStampTZ structure (Overloaded)
<a href="#">implicit operator OracleTimeStampTZ</a>	Converts an instance value to an OracleTimeStampTZ structure (Overloaded)
<a href="#">explicit operator DateTime</a>	Converts an OracleTimeStampTZ value to a DateTime structure in the current time zone

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

### explicit operator OracleTimeStampTZ

explicit operator OracleTimeStampTZ converts an instance value to an OracleTimeStampTZ structure.

**Overload List:**

- [explicit operator OracleTimeStampTZ\(OracleTimeStamp\)](#)  
This static type conversion operator converts an OracleTimeStamp value to an OracleTimeStampTZ structure.
- [explicit operator OracleTimeStampTZ\(OracleTimeStampLTZ\)](#)  
This static type conversion operator converts an OracleTimeStampLTZ value to an OracleTimeStampTZ structure.
- [explicit operator OracleTimeStampTZ\(string\)](#)  
This static type conversion operator converts the supplied string value to an OracleTimeStampTZ structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

### explicit operator OracleTimeStampTZ(OracleTimeStamp)

This static type conversion operator converts an OracleTimeStamp value to an OracleTimeStampTZ structure.

**Declaration**

```
// C#  
public static explicit operator OracleTimeStampTZ(OracleTimeStamp value1);
```

**Parameters**

- *value1*  
An `OracleTimeStamp`.

**Return Value**

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStamp` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

**Remarks**

The `OracleGlobalization.TimeZone` of the thread is used to convert from an `OracleTimeStamp` structure to an `OracleTimeStampTZ` structure.

If the `OracleTimeStamp` structure has a null value, the returned `OracleTimeStampTZ` structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**explicit operator OracleTimeStampTZ(OracleTimeStampLTZ)**

This static type conversion operator converts an `OracleTimeStampLTZ` value to an `OracleTimeStampTZ` structure.

**Declaration**

```
// C#  
public static explicit operator OracleTimeStampTZ(OracleTimeStampLTZ value1);
```

**Parameters**

- *value1*  
An `OracleTimeStampLTZ`.

**Return Value**

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStampLTZ` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

**Remarks**

If the `OracleTimeStampLTZ` structure has a null value, the returned `OracleTimeStampTZ` structure also has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**explicit operator OracleTimeStampTZ(string)**

This static type conversion operator converts the supplied string value to an OracleTimeStampTZ structure.

**Declaration**

```
// C#
public static explicit operator OracleTimeStampTZ(string tsStr);
```

**Parameters**

- *tsStr*
  - A string representation of an Oracle TIMESTAMP WITH TIME ZONE.

**Return Value**

An OracleTimeStampTZ value.

**Exceptions**

ArgumentException - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP WITH TIME ZONE. or the *tsStr* is not in the timestamp format specified by the thread's OracleGlobalization.TimeStampTZFormat property, which represents the Oracle NLS\_TIMESTAMP\_TZ\_FORMAT parameter.

**Remarks**

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_tz_format for the explicit operator
        // OracleTimeStampTZ(string)
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);
    }
}
```

```
// construct OracleTimeStampTZ from a string using the format specified.
OracleTimeStampTZ tstz = new OracleTimeStampTZ("11-NOV-1999" +
    "11:02:33.444 AM US/Pacific");

// Set the nls_timestamp_tz_format for the ToString() method
info.TimestampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
OracleGlobalization.SetThreadInfo(info);
Console.WriteLine(tstz.ToString());
    }
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**implicit operator OracleTimeStampTZ**

implicit operator OracleTimeStampTZ converts a DateTime structure to an OracleTimeStampTZ structure.

**Overload List:**

- [implicit operator OracleTimeStampTZ\(OracleDate\)](#)

This static type conversion operator converts an OracleDate value to an OracleTimeStampTZ structure.

- [implicit operator OracleTimeStampTZ\(DateTime\)](#)

This static type conversion operator converts a DateTime structure to an OracleTimeStampTZ structure.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**implicit operator OracleTimeStampTZ(OracleDate)**

This static type conversion operator converts an OracleDate value to an OracleTimeStampTZ structure.

**Declaration**

```
// C#
public static implicit operator OracleTimeStampTZ(OracleDate value1);
```

**Parameters**

- *value1*

An OracleDate.

### Return Value

The returned OracleTimeStampTZ contains the date and time from the OracleDate and the time zone from the OracleGlobalization.TimeZone of the thread.

### Remarks

The OracleGlobalization.TimeZone of the thread is used to convert from an OracleDate to an OracleTimeStampTZ structure. If the OracleDate structure has a null value, the returned OracleTimeStampTZ structure also has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## implicit operator OracleTimeStampTZ(DateTime)

This static type conversion operator converts a DateTime structure to an OracleTimeStampTZ structure.

### Declaration

```
// C#  
public static implicit operator OracleTimeStampTZ (DateTime value1);
```

### Parameters

- *value1*  
A DateTime structure.

### Return Value

The returned OracleTimeStampTZ contains the date and time from the DateTime and the time zone from the OracleGlobalization.TimeZone of the thread.

### Remarks

The OracleGlobalization.TimeZone of the thread is used to convert from a DateTime to an OracleTimeStampTZ structure.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## explicit operator DateTime

This static type conversion operator converts an `OracleTimeStampTZ` value to a `DateTime` structure and truncates the time zone information.

### Declaration

```
// C#  
public static explicit operator DateTime(OracleTimeStampTZ value1);
```

### Parameters

- *value1*  
An `OracleTimeStampTZ`.

### Return Value

A `DateTime` containing the date and time in the current instance, but with the time zone information in the current instance truncated.

### Exceptions

`OracleNullValueException` - The `OracleTimeStampTZ` structure has a null value.

### Remarks

The precision of the `OracleTimeStampTZ` value can be lost during the conversion, and the time zone information in the current instance is truncated

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)



## OracleTimeStampTZ Properties

The OracleTimeStampTZ properties are listed in [Table 14–124](#).

**Table 14–124 OracleTimeStampTZ Properties**

Properties	Description
<a href="#">BinData</a>	Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH TIME ZONE</code> in Oracle internal format
<a href="#">Day</a>	Specifies the day component of an OracleTimeStampTZ in the current time zone
<a href="#">IsNull</a>	Indicates whether or not the current instance has a null value
<a href="#">Hour</a>	Specifies the hour component of an OracleTimeStampTZ in the current time zone
<a href="#">Millisecond</a>	Specifies the millisecond component of an OracleTimeStampTZ in the current time zone
<a href="#">Minute</a>	Specifies the minute component of an OracleTimeStampTZ in the current time zone
<a href="#">Month</a>	Specifies the month component of an OracleTimeStampTZ in the current time zone
<a href="#">Nanosecond</a>	Specifies the nanosecond component of an OracleTimeStampTZ in the current time zone
<a href="#">Second</a>	Specifies the second component of an OracleTimeStampTZ in the current time zone
<a href="#">TimeZone</a>	Returns the time zone of the OracleTimeStampTZ instance
<a href="#">Value</a>	Returns the date and time that is stored in the OracleTimeStampTZ structure in the current time zone
<a href="#">Year</a>	Specifies the year component of an OracleTimeStampTZ

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

### Declaration

```
// C#
public byte[] BinData {get;}
```

### Property Value

The provided byte array that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

### Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**Day**

This property specifies the day component of an `OracleTimeStampTZ` in the current time zone.

**Declaration**

```
// C#  
public int Day{get;}
```

**Property Value**

A number that represents the day. Range of `Day` is (1 to 31).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**IsNull**

This property indicates whether or not the current instance has a null value.

**Declaration**

```
// C#  
public bool IsNull{get;}
```

**Property Value**

Returns `true` if the current instance has a null value. Otherwise, returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**Hour**

This property specifies the hour component of an `OracleTimeStampTZ` in the current time zone.

**Declaration**

```
// C#  
public int Hour{get;}
```

**Property Value**

A number that represents the hour. Range of Hour is (0 to 23).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**Millisecond**

This property gets the millisecond component of an `OracleTimeStampTZ` in the current time zone.

**Declaration**

```
// C#  
public double Millisecond{get;}
```

**Property Value**

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999)

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**Minute**

This property gets the minute component of an `OracleTimeStampTZ` in the current time zone.

**Declaration**

```
// C#  
public int Minute{get;}
```

**Property Value**

A number that represent a minute. Range of `Minute` is (0 to 59).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Month

This property gets the month component of an `OracleTimeStampTZ` in the current time zone.

### Declaration

```
// C#  
public int Month{get;}
```

### Property Value

A number that represents a month. Range of `Month` is (1 to 12).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Nanosecond

This property gets the nanosecond component of an `OracleTimeStampTZ` in the current time zone.

### Declaration

```
// C#  
public int Nanosecond{get;}
```

### Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Second

This property gets the second component of an `OracleTimeStampTZ` in the current time zone.

### Declaration

```
// C#  
public int Second{get;}
```

### Property Value

A number that represents a second. Range of `Second` is (0 to 59).

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**TimeZone**

This property returns the time zone of the `OracleTimeStampTZ` instance.

**Declaration**

```
// C#
public string TimeZone{get;}
```

**Property Value**

A string that represents the time zone.

**Remarks**

If no time zone is specified in the constructor, this property is set to the thread's `OracleGlobalization.TimeZone` by default

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

**Value**

This property returns the date and time that is stored in the `OracleTimeStampTZ` structure in the current time zone.

**Declaration**

```
// C#
public DateTime Value{get;}
```

**Property Value**

A `DateTime` in the current time zone.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Year

This property sets the year component of an `OracleTimeStampTZ` in the current time zone.

### Declaration

```
// C#  
public int Year{get;}
```

### Property Value

A number that represents a year. The range of `Year` is (-4712 to 9999).

### Exceptions

`OracleNullValueException` - The current instance has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## OracleTimeStampTZ Methods

The OracleTimeStampTZ methods are listed in [Table 14–125](#).

**Table 14–125 OracleTimeStampTZ Methods**

Methods	Description
<a href="#">AddDays</a>	Adds the supplied number of days to the current instance
<a href="#">AddHours</a>	Adds the supplied number of hours to the current instance
<a href="#">AddMilliseconds</a>	Adds the supplied number of milliseconds to the current instance
<a href="#">AddMinutes</a>	Adds the supplied number of minutes to the current instance
<a href="#">AddMonths</a>	Adds the supplied number of months to the current instance
<a href="#">AddNanoseconds</a>	Adds the supplied number of nanoseconds to the current instance
<a href="#">AddSeconds</a>	Adds the supplied number of seconds to the current instance
<a href="#">AddYears</a>	Adds the supplied number of years to the current instance
<a href="#">CompareTo</a>	Compares the current OracleTimeStampTZ instance to an object, and returns an integer that represents their relative values
<a href="#">Equals</a>	Determines whether or not an object has the same date and time as the current OracleTimeStampTZ instance (Overloaded)
<a href="#">GetDaysBetween</a>	Subtracts an OracleTimeStampTZ from the current instance and returns an OracleIntervalDS that represents the time interval
<a href="#">GetHashCode</a>	Returns a hash code for the OracleTimeStampTZ instance
<a href="#">GetTimeZoneOffset</a>	Gets the time zone information in hours and minutes of the current OracleTimeStampTZ
<a href="#">GetYearsBetween</a>	Subtracts an OracleTimeStampTZ from the current instance and returns an OracleIntervalYM that represents the time interval
<a href="#">GetType</a>	Inherited from System.Object
<a href="#">ToLocalTime</a>	Converts the current OracleTimeStampTZ instance to local time
<a href="#">ToOracleDate</a>	Converts the current OracleTimeStampTZ structure to an OracleDate structure
<a href="#">ToOracleTimeStampLTZ</a>	Converts the current OracleTimeStampTZ structure to an OracleTimeStampLTZ structure
<a href="#">ToOracleTimeStamp</a>	Converts the current OracleTimeStampTZ structure to an OracleTimeStamp structure
<a href="#">ToString</a>	Converts the current OracleTimeStampTZ structure to a string
<a href="#">ToUniversalTime</a>	Converts the current datetime to Coordinated Universal Time (UTC)

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## AddDays

This method adds the supplied number of days to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampTZ AddDays(double days);
```

**Parameters**

- *days*  
The supplied number of days. Range is  $(-1,000,000,000 < days < 1,000,000,000)$

**Return Value**

An OracleTimeStampTZ.

**Exceptions**

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## AddHours

This method adds the supplied number of hours to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampTZ AddHours(double hours);
```

**Parameters**

- *hours*  
The supplied number of hours. Range is  $(-24,000,000,000 < hours < 24,000,000,000)$ .

**Return Value**

An OracleTimeStampTZ.

**Exceptions**

OracleNullValueException - The current instance has a null value.



`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

**Declaration**

```
// C#
public OracleTimeStampTZ AddMilliseconds(double milliseconds);
```

**Parameters**

- *milliseconds*

The supplied number of milliseconds. Range is  $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$ .

**Return Value**

An `OracleTimeStampTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## AddMinutes

This method adds the supplied number of minutes to the current instance.

**Declaration**

```
// C#
public OracleTimeStampTZ AddMinutes(double minutes);
```

**Parameters**

- *minutes*

The supplied number of minutes. Range is  $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$ .

**Return Value**

An `OracleTimeStampTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**AddMonths**

This method adds the supplied number of months to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampTZ AddMonths(long months);
```

**Parameters**

- *months*  
The supplied number of months. Range is  $(-12,000,000,000 < months < 12,000,000,000)$ .

**Return Value**

An `OracleTimeStampTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**AddNanoseconds**

This method adds the supplied number of nanoseconds to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampTZ AddNanoseconds(long nanoseconds);
```

**Parameters**

- *nanoseconds*  
The supplied number of nanoseconds.

**Return Value**

An `OracleTimeStampTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**AddSeconds**

This method adds the supplied number of seconds to the current instance.

**Declaration**

```
// C#  
public OracleTimeStampTZ AddSeconds(double seconds);
```

**Parameters**

- *seconds*

The supplied number of seconds. Range is  $(-8.64 * 1013 < seconds < 8.64 * 1013)$ .

**Return Value**

An `OracleTimeStampTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**AddYears**

This method adds the supplied number of years to the current instance

**Declaration**

```
// C#  
public OracleTimeStampTZ AddYears(int years);
```

**Parameters**

- *years*

The supplied number of years. Range is  $(-999,999,999 \leq years \leq 999,999,999)$ .

**Return Value**

An `OracleTimeStampTZ`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**CompareTo**

This method compares the current `OracleTimeStampTZ` instance to an object, and returns an integer that represents their relative values.

**Declaration**

```
// C#  
public int CompareTo(object obj);
```

**Parameters**

- *obj*

The object being compared to the current `OracleTimeStampTZ` instance.

**Return Value**

The method returns a number that is:

Less than zero: if the current `OracleTimeStampTZ` instance value is less than that of *obj*.

Zero: if the current `OracleTimeStampTZ` instance and *obj* values are equal.

Greater than zero: if the current `OracleTimeStampTZ` instance value is greater than that of *obj*.

**Implements**

`IComparable`

**Exceptions**

`ArgumentException` - The *obj* is not of type `OracleTimeStampTZ`.

**Remarks**

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStampTZ`s. For example, comparing an `OracleTimeStampTZ` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStampTZ` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.

- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## Equals

Overrides `Object`

This method determines whether or not an object has the same date and time as the current `OracleTimeStampTZ` instance.

**Declaration**

```
// C#
public override bool Equals(object obj);
```

**Parameters**

- *obj*  
The object being compared to the current `OracleTimeStampTZ` instance.

**Return Value**

Returns `true` if the *obj* is of type `OracleTimeStampTZ` and represents the same date and time; otherwise, returns `false`.

**Remarks**

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## GetDaysBetween

This method subtracts an `OracleTimeStampTZ` value from the current instance and returns an `OracleIntervalDS` that represents the time interval.

**Declaration**

```
// C#
public OracleIntervalDS GetDaysBetween(OracleTimeStampTZ value1);
```

**Parameters**

- *value1*  
The `OracleTimeStampTZ` value being subtracted.

**Return Value**

An `OracleIntervalDS` that represents the interval between two `OracleTimeStampTZ` values.

**Remarks**

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**GetHashCode**

Overrides `Object`

This method returns a hash code for the `OracleTimeStampTZ` instance.

**Declaration**

```
// C#  
public override int GetHashCode();
```

**Return Value**

A number that represents the hash code.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**GetTimeZoneOffset**

This method gets the time zone portion in hours and minutes of the current `OracleTimeStampTZ`.

**Declaration**

```
// C#  
public TimeSpan GetTimeZoneOffset();
```

**Return Value**

A `TimeSpan`.

**Exceptions**

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## GetYearsBetween

This method subtracts an `OracleTimeStampTZ` value from the current instance and returns an `OracleIntervalYM` that represents the time interval.

### Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStampTZ val);
```

### Parameters

- *val*  
The `OracleTimeStampTZ` value being subtracted.

### Return Value

An `OracleIntervalYM` that represents the interval between two `OracleTimeStampTZ` values.

### Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalYM` has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## ToLocalTime

This method converts the current `OracleTimeStampTZ` instance to local time.

### Declaration

```
// C#  
public OracleTimeStampLTZ ToLocalTime();
```

### Return Value

An `OracleTimeStampLTZ` that contains the date and time, which is normalized to the client local time zone, in the current instance.

### Remarks

If the current instance has a null value, the returned `OracleTimeStampLTZ` has a null value.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## ToOracleDate

This method converts the current `OracleTimeStampTZ` structure to an `OracleDate` structure.

**Declaration**

```
// C#  
public OracleDate ToOracleDate();
```

**Return Value**

The returned `OracleDate` contains the date and time in the current instance, but the time zone information in the current instance is truncated

**Remarks**

The precision of the `OracleTimeStampTZ` value can be lost during the conversion, and the time zone information in the current instance is truncated.

If the current instance has a null value, the value of the returned `OracleDate` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**ToOracleTimeStampLTZ**

This method converts the current `OracleTimeStampTZ` structure to an `OracleTimeStampLTZ` structure.

**Declaration**

```
// C#  
public OracleTimeStampLTZ ToOracleTimeStampLTZ();
```

**Return Value**

The returned `OracleTimeStampLTZ` structure contains the date and time, which is normalized to the client local time zone, in the current instance.

**Remarks**

If the value of the current instance has a null value, the value of the returned `OracleTimeStampLTZ` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**ToOracleTimeStamp**

This method converts the current `OracleTimeStampTZ` structure to an `OracleTimeStamp` structure.

**Declaration**

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```



**Return Value**

The returned `OracleTimeStamp` contains the date and time in the current instance, but the time zone information is truncated.

**Remarks**

If the value of the current instance has a null value, the value of the returned `OracleTimeStamp` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

**ToString**

Overrides `Object`

This method converts the current `OracleTimeStampTZ` structure to a string.

**Declaration**

```
// C#
public override string ToString();
```

**Return Value**

A string that represents the same date and time as the current `OracleTimeStampTZ` structure.

**Remarks**

The returned value is a string representation of an `OracleTimeStampTZ` in the format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread. The names and abbreviations used for months and days are in the language specified by the `OracleGlobalization.DateLanguage` and the `OracleGlobalization.Calendar` properties of the thread. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

**Example**

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ToStringSample
{
    static void Main()
    {
        // Set the nls parameters for the current thread
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeZone = "US/Eastern";
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Create an OracleTimeStampTZ in US/Pacific time zone
```

```
OracleTimeStampTZ tstz1=new OracleTimeStampTZ("11-NOV-1999 "+
    "11:02:33.444 AM US/Pacific");

// Note that ToOracleTimeStampTZ uses the thread's time zone region,
// "US/Eastern"
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");
OracleTimeStampTZ tstz2 = ts.ToOracleTimeStampTZ();

// Calculate the difference between tstz1 and tstz2
OracleIntervalDS idsDiff = tstz1.GetDaysBetween(tstz2);

// Prints "US/Pacific"
Console.WriteLine("tstz1.TimeZone = " + tstz1.TimeZone);

// Prints "US/Eastern"
Console.WriteLine("tstz2.TimeZone = " + tstz2.TimeZone);

// Prints 3
Console.WriteLine("idsDiff.Hours = " + idsDiff.Hours);

// Prints 0
Console.WriteLine("idsDiff.Minutes = " + idsDiff.Minutes);
}
}
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-110

## ToUniversalTime

This method converts the current datetime to Coordinated Universal Time (UTC).

**Declaration**

```
// C#
public OracleTimeStampTZ ToUniversalTime();
```

**Return Value**

An `OracleTimeStampTZ` structure.

**Remarks**

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

## INullable Interface

The `INullable` interface is used to determine whether or not an ODP.NET type has a NULL value.

### Declaration

```
// C#  
public interface INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [INullable Interface Members](#)
- [INullable Interface Properties](#)

## INullable Interface Members

INullable members are listed in the following tables.

### INullable Interface Properties

INullable interface properties are listed in [Table 14–126](#).

**Table 14–126** *INullable Interface Properties*

Public Property	Description
<a href="#">IsNull</a>	Indicates whether or not the ODP.NET type has a NULL value

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [INullable Interface](#)

## INullable Interface Properties

INullable interface properties are listed in [Table 14–126](#).

**Table 14–127** *INullable Interface Properties*

Public Property	Description
<a href="#">IsNull</a>	Indicates whether or not the ODP.NET type has a NULL value

### IsNull

This property indicates whether or not the ODP.NET type has a NULL value.

#### Declaration

```
// C#  
bool IsNull {get;}
```

#### Property Value

Returns true if the ODP.NET type has a NULL value; otherwise, returns false.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [INullable Interface](#)
- [INullable Interface Members](#)



---

---

## Oracle Data Provider for .NET Types Exceptions

This section covers the ODP.NET Types exceptions.

This chapter contains these topics:

- [OracleTypeException Class](#)
- [OracleNullValueException Class](#)
- [OracleTruncateException Class](#)

## OracleTypeException Class

The `OracleTypeException` is the base exception class for handling exceptions that occur in the ODP.NET Types classes.

### Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`Oracle.DataAccess.Types.OracleTypeException`

### Declaration

```
// C#  
public class OracleTypeException : SystemException
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTypeException Members](#)
- [OracleTypeException Constructors](#)
- [OracleTypeException Static Methods](#)
- [OracleTypeException Properties](#)
- [OracleTypeException Methods](#)



## OracleTypeException Members

OracleTypeException members are listed in the following tables.

### OracleTypeException Constructors

The OracleTypeException constructors are listed in [Table 15-1](#).

**Table 15-1 OracleTypeException Constructor**

Constructor	Description
<a href="#">OracleTypeException Constructors</a>	Creates a new instance of the OracleTypeException class (Overloaded)

### OracleTypeException Static Methods

The OracleTypeException static methods are listed in [Table 15-2](#).

**Table 15-2 OracleTypeException Static Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)

### OracleTypeException Properties

The OracleTypeException properties are listed in [Table 15-3](#).

**Table 15-3 OracleTypeException Properties**

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
<a href="#">Message</a>	Specifies the error messages that occur in the exception
<a href="#">Source</a>	Specifies the name of the data provider that generates the error
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

### OracleTypeException Methods

The OracleTypeException methods are listed in [Table 15-4](#).

**Table 15-4 OracleTypeException Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object

**Table 15–4 (Cont.) OracleTypeException Methods**

Methods	Description
GetObjectData	Inherited from <code>System.SystemException.Exception</code>
GetType	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Returns the fully qualified name of this exception

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTypeException Class](#)

## OracleTypeException Constructors

The `OracleTypeException` constructors create new instances of the `OracleTypeException` class.

### Overload List:

- [OracleTypeException\(string\)](#)

This constructor creates a new instance of the `OracleTypeException` class with the specified error message, `errorMessage`.

- [OracleTypeException\(SerializationInfo, StreamingContext\)](#)

This constructor creates a new instance of the `OracleTypeException` class with the specified serialization information, `si`, and the specified streaming context, `sc`.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

### OracleTypeException(string)

This constructor creates a new instance of the `OracleTypeException` class with the specified error message, `errorMessage`.

### Declaration

```
// C#  
public OracleTypeException (string errorMessage);
```

### Parameters

- *errorMessage*

The specified error message.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

### OracleTypeException(SerializationInfo, StreamingContext)

This constructor creates a new instance of the `OracleTypeException` class with the specified serialization information, `si`, and the specified streaming context, `sc`.

### Declaration

```
// C#  
protected OracleTypeException (SerializationInfo si, StreamingContext sc);
```

### Parameters

- *si*

The specified serialization information.

- *sc*

The specified streaming context.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

## OracleTypeException Static Methods

The `OracleTypeException` static methods are listed in [Table 15-5](#).

**Table 15-5** *OracleTypeException Static Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

## OracleTypeException Properties

The `OracleTypeException` properties are listed in [Table 15–6](#).

**Table 15–6 OracleTypeException Properties**

Properties	Description
<code>HelpLink</code>	Inherited from <code>System.SystemException.Exception</code>
<code>InnerException</code>	Inherited from <code>System.SystemException.Exception</code>
<a href="#">Message</a>	Specifies the error messages that occur in the exception
<a href="#">Source</a>	Specifies the name of the data provider that generates the error
<code>StackTrace</code>	Inherited from <code>System.SystemException.Exception</code>
<code>TargetSite</code>	Inherited from <code>System.SystemException.Exception</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

### Message

Overrides `Exception`

This property specifies the error messages that occur in the exception.

**Declaration**

```
// C#
public override string Message {get;}
```

**Property Value**

An error message.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

### Source

Overrides `Exception`

This property specifies the name of the data provider that generates the error.

**Declaration**

```
// C#
public override string Source {get;}
```

**Property Value**

Oracle Data Provider for .NET.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

## OracleTypeException Methods

The `OracleTypeException` methods are listed in [Table 15-7](#).

**Table 15-7 OracleTypeException Methods**

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetBaseException</code>	Inherited from <code>System.SystemException.Exception</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetObjectData</code>	Inherited from <code>System.SystemException.Exception</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<a href="#">ToString</a>	Returns the fully qualified name of this exception

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

### ToString

Overrides `Exception`

This method returns the fully qualified name of this exception, the error message in the `Message` property, the `InnerException.ToString()` message, and the stack trace.

**Declaration**

```
// C#
public override string ToString();
```

**Return Value**

The fully qualified name of this exception.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)



---

## OracleNullValueException Class

The `OracleNullValueException` represents an exception that is thrown when trying to access an ODP.NET Types structure that has a null value.

### Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`System.OracleTypeException`

`Oracle.DataAccess.Types.OracleNullValueException`

### Declaration

```
// C#  
public sealed class OracleNullValueException : OracleTypeException
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleNullValueException Members](#)
- [OracleNullValueException Constructors](#)
- [OracleNullValueException Static Methods](#)
- [OracleNullValueException Properties](#)
- [OracleNullValueException Methods](#)

## OracleNullValueException Members

OracleNullValueException members are listed in the following tables.

### OracleNullValueException Constructors

The OracleNullValueException constructors are listed in [Table 15–8](#).

**Table 15–8 OracleNullValueException Constructors**

Constructor	Description
<a href="#">OracleNullValueException Constructors</a>	Creates a new instance of the OracleNullValueException class (Overloaded)

### OracleNullValueException Static Methods

The OracleNullValueException static methods are listed in [Table 15–9](#).

**Table 15–9 OracleNullValueException Static Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)

### OracleNullValueException Properties

The OracleNullValueException properties are listed in [Table 15–10](#).

**Table 15–10 OracleNullValueException Properties**

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

### OracleNullValueException Methods

The OracleNullValueException methods are listed in [Table 15–11](#).

**Table 15–11 OracleNullValueException Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object
GetObjectData	Inherited from System.SystemException.Exception

**Table 15–11 (Cont.) OracleNullValueException Methods**

Methods	Description
GetType	Inherited from <code>System.Object</code>
ToString	Inherited from <code>OracleTypeException</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleNullValueException Class](#)

## OracleNullValueException Constructors

The `OracleNullValueException` constructors create new instances of the `OracleNullValueException` class.

### Overload List:

- [OracleNullValueException\(\)](#)

This constructor creates a new instance of the `OracleNullValueException` class with its default properties.

- [OracleNullValueException\(string\)](#)

This constructor creates a new instance of the `OracleNullValueException` class with the specified error message, `errorMessage`.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

### OracleNullValueException()

This constructor creates a new instance of the `OracleNullValueException` class with its default properties.

### Declaration

```
// C#  
public OracleNullValueException();
```

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

### OracleNullValueException(string)

This constructor creates a new instance of the `OracleNullValueException` class with the specified error message, `errorMessage`.

### Declaration

```
// C#  
public OracleNullValueException (string errorMessage);
```

### Parameters

- *errorMessage*

The specified error message.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

## OracleNullValueException Static Methods

The `OracleNullValueException` static methods are listed in [Table 15-12](#).

**Table 15-12** *OracleNullValueException Static Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

## OracleNullValueException Properties

The `OracleNullValueException` properties are listed in [Table 15–13](#).

**Table 15–13 OracleNullValueException Properties**

Properties	Description
<code>HelpLink</code>	Inherited from <code>System.SystemException.Exception</code>
<code>InnerException</code>	Inherited from <code>System.SystemException.Exception</code>
<code>Message</code>	Inherited from <code>OracleTypeException</code>
<code>Source</code>	Inherited from <code>OracleTypeException</code>
<code>StackTrace</code>	Inherited from <code>System.SystemException.Exception</code>
<code>TargetSite</code>	Inherited from <code>System.SystemException.Exception</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

## OracleNullValueException Methods

The `OracleNullValueException` methods are listed in [Table 15–14](#).

**Table 15–14** *OracleNullValueException Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetBaseException</code>	Inherited from <code>System.SystemException.Exception</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetObjectData</code>	Inherited from <code>System.SystemException.Exception</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>OracleTypeException</code>



---

## OracleTruncateException Class

The `OracleTruncateException` class represents an exception that is thrown when truncation in a ODP.NET Types class occurs.

### Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`System.OracleTypeException`

`Oracle.DataAccess.Types.OracleTruncateException`

### Declaration

```
// C#  
public sealed class OracleTruncateException : OracleTypeException
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTruncateException Members](#)
- [OracleTruncateException Constructors](#)
- [OracleTruncateException Static Methods](#)
- [OracleTruncateException Properties](#)
- [OracleTruncateException Methods](#)

## OracleTruncateException Members

OracleTruncateException members are listed in the following tables.

### OracleTruncateException Constructors

The OracleTruncateException constructors are listed in [Table 15–15](#).

**Table 15–15 OracleTruncateException Constructors**

Constructor	Description
<a href="#">OracleTruncateException Constructors</a>	Creates a new instance of the OracleTruncateException class (Overloaded)

### OracleTruncateException Static Methods

The OracleTruncateException static methods are listed in [Table 15–16](#).

**Table 15–16 OracleTruncateException Static Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)

### OracleTruncateException Properties

The OracleTruncateException properties are listed in [Table 15–17](#).

**Table 15–17 OracleTruncateException Properties**

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

### OracleTruncateException Methods

The OracleTruncateException methods are listed in [Table 15–18](#).

**Table 15–18 OracleTruncateException Methods**

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object
GetObjectData	Inherited from System.SystemException.Exception

**Table 15–18 (Cont.) OracleTruncateException Methods**

Methods	Description
GetType	Inherited from <code>System.Object</code>
ToString	Inherited from <code>OracleTypeException</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTruncateException Class](#)

## OracleTruncateException Constructors

The `OracleTruncateException` constructors create new instances of the `OracleTruncateException` class

### Overload List:

- [OracleTruncateException\(\)](#)

This constructor creates a new instance of the `OracleTruncateException` class with its default properties.

- [OracleTruncateException\(string\)](#)

This constructor creates a new instance of the `OracleTruncateException` class with the specified error message, `errorMessage`.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

### OracleTruncateException()

This constructor creates a new instance of the `OracleTruncateException` class with its default properties.

### Declaration

```
// C#  
public OracleTruncateException();
```

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

### OracleTruncateException(string)

This constructor creates a new instance of the `OracleTruncateException` class with the specified error message, `errorMessage`.

### Declaration

```
// C#  
public OracleTruncateException (string errorMessage);
```

### Parameters

- *errorMessage*

The specified error message.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

## OracleTruncateException Static Methods

The `OracleTruncateException` static methods are listed in [Table 15–19](#).

**Table 15–19** *OracleTruncateException Static Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

## OracleTruncateException Properties

The OracleTruncateException properties are listed in [Table 15–20](#).

**Table 15–20 OracleTruncateException Properties**

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

## OracleTruncateException Methods

The `OracleTruncateException` methods are listed in [Table 15–21](#).

**Table 15–21** *OracleTruncateException Methods*

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetBaseException</code>	Inherited from <code>System.SystemException.Exception</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetObjectData</code>	Inherited from <code>System.SystemException.Exception</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>OracleTypeException</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)



---

---

## Oracle Data Provider for .NET UDT-Related Classes

This chapter describes the object-related classes and interfaces in the Oracle Data Provider for .NET that provide support for Oracle user-defined data types (UDT).

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples\UDT` directory.

- [OracleCustomTypeMappingAttribute Class](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleArrayMappingAttribute Class](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomTypeFactory Interface](#)
- [IOracleArrayTypeFactory Interface](#)
- [OracleUdt Class](#)
- [OracleRef Class](#)
- [OracleUdtFetchOption Enumeration](#)
- [OracleUdtStatus Enumeration](#)

---

## OracleCustomTypeMappingAttribute Class

The `OracleCustomTypeMappingAttribute` class is used to mark a custom type factory class or struct with information that is used by ODP.NET when a custom type is used to represent an Oracle UDT.

### Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleCustomTypeMappingAttribute`

### Declaration

```
// C#
[AttributeUsageAttribute(AttributeTargets.Class|AttributeTargets.Struct,
    AllowMultiple=false, Inherited=true)]
public sealed class OracleCustomTypeMappingAttribute : Attribute
```

### Remarks

The `OracleCustomTypeMapping` attribute must be specified on the custom type factory class to indicate the Oracle UDT that the corresponding custom type represents. The Oracle UDT may be specified in the form `schema_name.type_name`.

For each Oracle UDT that the application uses, there must be a unique custom type factory, as follows:

- Oracle Object Types  
The custom type factory must return a custom type that cannot be used to represent any other Oracle Object Type.
- Oracle Collection Types  
The custom type factory may return a custom type that can be used by other Oracle Collection Types. This is common when an array type is used to represent an Oracle Collection, that is, when an `int []` is used to represent a collection of NUMBERS.

If the `OracleCustomTypeMappingAttribute` is not specified, then custom type mappings must be specified through an XML configuration file, for example, `app.config` for Windows applications or the `web.config` for web applications, and the `machine.config`

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleCustomTypeMappingAttribute Members](#)
- [OracleCustomTypeMappingAttribute Constructors](#)
- [OracleCustomTypeMappingAttribute Static Methods](#)
- [OracleCustomTypeMappingAttribute Methods](#)

## OracleCustomTypeMappingAttribute Members

OracleCustomTypeMappingAttribute members are listed in the following tables.

### OracleCustomTypeMappingAttribute Constructors

OracleCustomTypeMappingAttribute constructors are listed in [Table 16-1](#).

**Table 16-1 OracleCustomTypeMappingAttribute Constructors**

Constructor	Description
<a href="#">OracleCustomTypeMappingAttribute Constructors</a>	Instantiates a new instance of OracleCustomTypeMappingAttribute class

### OracleCustomTypeMappingAttribute Static Methods

OracleCustomTypeMappingAttribute static methods are listed in [Table 16-2](#).

**Table 16-2 OracleCustomTypeMappingAttribute Static Methods**

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

### OracleCustomTypeMappingAttribute Properties

OracleCustomTypeMappingAttribute properties are listed in [Table 16-3](#).

**Table 16-3 OracleCustomTypeMappingAttribute Properties**

Property	Description
<a href="#">UdtTypeName</a>	Specifies the Oracle user-defined type name that the custom class maps to
TypeId	Inherited from System.Attribute

### OracleCustomTypeMappingAttribute Methods

OracleCustomTypeMappingAttribute methods are listed in [Table 16-4](#).

**Table 16-4 OracleCustomTypeMappingAttribute Methods**

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleCustomTypeMappingAttribute Class](#)

## OracleCustomTypeMappingAttribute Constructors

OracleCustomTypeMappingAttribute constructors create new instances of the OracleCustomTypeMappingAttribute class.

### Overload List:

- [OracleCustomTypeMappingAttribute\(string\)](#)

This constructor creates and initializes an OracleCustomTypeMappingAttribute using the specified Oracle user-defined type name.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Methods](#)

### OracleCustomTypeMappingAttribute(string)

This constructor creates and initializes an OracleCustomTypeMappingAttribute using the specified Oracle user-defined type name.

#### Declaration

```
// C#  
public OracleCustomTypeMappingAttribute(string udtTypeName)
```

#### Parameters

- *udtTypeName*

The Oracle user-defined type name that the custom class maps to.

#### Remarks

The *udtTypeName* parameter is case-sensitive. The *udtTypeName* is specified in the form of *schema\_name.type\_name*.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

## OracleCustomTypeMappingAttribute Static Methods

OracleCustomTypeMappingAttribute static methods are listed in [Table 16-5](#).

**Table 16-5 OracleCustomTypeMappingAttribute Static Methods**

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

## OracleCustomTypeMappingAttribute Properties

OracleCustomTypeMappingAttribute properties are listed in [Table 16–6](#).

**Table 16–6 OracleCustomTypeMappingAttribute Properties**

Property	Description
<a href="#">UdtTypeName</a>	Specifies the Oracle user-defined type name that the custom class maps to
TypeId	Inherited from <code>System.Attribute</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

### UdtTypeName

This property specifies the Oracle user-defined type name that the custom class maps to.

**Declaration**

```
// C#  
public string UdtTypeName {get; set;}
```

**Property Value**

A string that represents an Oracle user-defined type name.

**Remarks**

UdtTypeName is case-sensitive. It is specified in the form of *schema\_name.type\_name*.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)



## OracleCustomTypeMappingAttribute Methods

OracleCustomTypeMappingAttribute methods are listed in [Table 16–7](#).

**Table 16–7 OracleCustomTypeMappingAttribute Methods**

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

## OracleObjectMappingAttribute Class

The `OracleObjectMappingAttribute` class marks custom class fields or properties with information that ODP.NET uses when a custom type represents an Oracle Object type.

### Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleObjectMappingAttribute`

### Declaration

```
// C#  
[AttributeUsageAttribute(AttributeTargets.Field|AttributeTargets.Property,  
AllowMultiple=false, Inherited=true)]
```

```
public sealed class OracleObjectMappingAttribute : Attribute
```

### Remarks

The `OracleObjectMappingAttribute` is specified on members of a custom type that represent an Oracle object type. This attribute must specify the name or zero-based index of the attribute in the Oracle object that the custom class field or property maps to. This also allows the custom type to declare field or property names which differ from the Oracle Object type.

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Members](#)
- [OracleObjectMappingAttribute Constructors](#)
- [OracleObjectMappingAttribute Static Methods](#)
- [OracleObjectMappingAttribute Properties](#)
- [OracleObjectMappingAttribute Methods](#)

## OracleObjectMappingAttribute Members

OracleObjectMappingAttribute members are listed in the following tables.

### OracleObjectMappingAttribute Constructors

OracleObjectMappingAttribute constructors are listed in [Table 16–8](#).

**Table 16–8 OracleObjectMappingAttribute Constructors**

Constructor	Description
<a href="#">OracleObjectMappingAttribute Constructors</a>	Instantiates a new instance of OracleObjectMappingAttribute class (Overloaded)

### OracleObjectMappingAttribute Static Methods

OracleObjectMappingAttribute static methods are listed in [Table 16–9](#).

**Table 16–9 OracleObjectMappingAttribute Static Methods**

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

### OracleObjectMappingAttribute Properties

OracleObjectMappingAttribute properties are listed in [Table 16–10](#).

**Table 16–10 OracleObjectMappingAttribute Properties**

Property	Description
<a href="#">AttributeIndex</a>	Specifies the index of the Oracle Object attribute that must be retrieved
<a href="#">AttributeName</a>	Specifies the name of Oracle Object attribute that must be retrieved
TypeId	Inherited from System.Attribute

### OracleObjectMappingAttribute Methods

OracleObjectMappingAttribute methods are listed in [Table 16–11](#).

**Table 16–11 OracleObjectMappingAttribute Methods**

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute

**Table 16–11 (Cont.) OracleObjectMappingAttribute Methods**

Method	Description
ToString	Inherited from <code>System.Attribute</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleObjectMappingAttribute Class](#)

## OracleObjectMappingAttribute Constructors

OracleObjectMappingAttribute constructors create new instances of the OracleObjectMappingAttribute class.

### Overload List:

- [OracleObjectMappingAttribute\(string\)](#)

This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute name.

- [OracleObjectMappingAttribute\(int\)](#)

This constructor creates and initializes an OracleObjectMappingAttribute with the specified Oracle Object attribute index.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

### OracleObjectMappingAttribute(string)

This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute name.

### Declaration

```
// C#  
public OracleObjectMappingAttribute(string attrName);
```

### Parameters

- *attrName*

The name of the Oracle Object attribute to map to.

### Remarks

The *attrName* parameter is case-sensitive.

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

### OracleObjectMappingAttribute(int)

This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute index.

### Declaration

```
// C#  
public OracleObjectMappingAttribute(int attrIndex);
```

### Parameters

- *attrIndex*

The zero-based index of the Oracle Object attribute to map to.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

## OracleObjectMappingAttribute Static Methods

OracleObjectMappingAttribute static methods are listed in [Table 16–12](#).

**Table 16–12 OracleObjectMappingAttribute Static Method**

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

## OracleObjectMappingAttribute Properties

OracleObjectMappingAttribute properties are listed in [Table 16–13](#).

**Table 16–13 OracleObjectMappingAttribute Properties**

Property	Description
<a href="#">AttributeIndex</a>	Specifies the index of the Oracle Object attribute that must be retrieved
<a href="#">AttributeName</a>	Specifies the name of the Oracle Object attribute that must be retrieved
TypeId	Inherited from <code>System.Attribute</code>

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

### AttributeIndex

This property specifies the index of the Oracle Object attribute that must be retrieved.

**Declaration**

```
// C#
public int AttributeIndex {get;}
```

**Property Value**

The zero-based index of an Oracle Object type attribute.

**Remarks**

The `AttributeIndex` property specifies the index of the Oracle Object type attribute that the custom class field or property maps to. This allows the custom class to declare fields or property names that differ from the Oracle object.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

### AttributeName

This property specifies the name of the Oracle Object attribute that must be retrieved.

**Declaration**

```
// C#
public string AttributeName {get;}
```



**Property Value**

The name of an attribute of an Oracle Object type.

**Remarks**

The `AttributeName` property specifies name of the attribute in the Oracle Object type that the custom class field or property maps to. This allows the custom class to declare field or property names that differ from the Oracle object.

The specified attribute name is case-sensitive.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

## OracleObjectMappingAttribute Methods

OracleObjectMappingAttribute methods are listed in [Table 16–14](#).

**Table 16–14 OracleObjectMappingAttribute Methods**

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

---

## OracleArrayMappingAttribute Class

The `OracleArrayMappingAttribute` class is required to mark a custom class field or property with information that ODP.NET uses when a custom type represents an Oracle Collection type.

### Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleArrayMappingAttribute`

### Declaration

[AttributeUsageAttribute(AttributeTargets.Field | AttributeTargets.Property, AllowMultiple=false, Inherited=true)]

```
// C#
public sealed class OracleArrayMappingAttribute : Attribute
```

### Remarks

An `OracleArrayMappingAttribute` object must be specified when a custom type represents an Oracle Collection. This attribute is applied only to the custom class member that stores the collection elements.

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleArrayMappingAttribute Members](#)
- [OracleArrayMappingAttribute Constructors](#)
- [OracleArrayMappingAttribute Static Methods](#)
- [OracleArrayMappingAttribute Properties](#)
- [OracleArrayMappingAttribute Methods](#)

## OracleArrayMappingAttribute Members

OracleArrayMappingAttribute members are listed in the following tables.

### OracleArrayMappingAttribute Constructors

OracleArrayMappingAttribute constructors are listed in [Table 16-15](#).

**Table 16-15 OracleArrayMappingAttribute Constructors**

Constructor	Description
<a href="#">OracleArrayMappingAttribute Constructors</a>	Instantiates a new instance of OracleArrayMappingAttribute class (Overloaded)

### OracleArrayMappingAttribute Static Methods

OracleArrayMappingAttribute static methods are listed in [Table 16-16](#).

**Table 16-16 OracleArrayMappingAttribute Static Methods**

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

### OracleArrayMappingAttribute Properties

OracleArrayMappingAttribute properties are listed in [Table 16-17](#).

**Table 16-17 OracleArrayMappingAttribute Properties**

Property	Description
TypeId	Inherited from System.Attribute

### OracleArrayMappingAttribute Methods

OracleArrayMappingAttribute methods are listed in [Table 16-18](#).

**Table 16-18 OracleArrayMappingAttribute Methods**

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleArrayMappingAttribute Class](#)

## OracleArrayMappingAttribute Constructors

OracleArrayMappingAttribute constructors create new instances of the OracleArrayMappingAttribute class.

### Overload List:

- [OracleArrayMappingAttribute\(\)](#)

This constructor creates and initializes an OracleArrayMappingAttribute object.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

### OracleArrayMappingAttribute()

This constructor creates and initializes an OracleArrayMappingAttribute object.

#### Declaration

```
// C#  
public OracleArrayMappingAttribute();
```

#### Remarks

An OracleArrayMappingAttribute object must be applied when a custom class represents an Oracle Collection type, to specify the custom class field or property that stores the collection elements.

The OracleArrayMappingAttribute can be applied to only one field or property in the custom class.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

## OracleArrayMappingAttribute Static Methods

OracleArrayMappingAttribute static methods are listed in [Table 16–19](#).

**Table 16–19 OracleArrayMappingAttribute Static Methods**

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

## OracleArrayMappingAttribute Properties

OracleArrayMappingAttribute properties are listed in [Table 16–20](#).

**Table 16–20 OracleArrayMappingAttribute Properties**

Property	Description
TypeId	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)



## OracleArrayMappingAttribute Methods

OracleArrayMappingAttribute methods are listed in [Table 16–21](#).

**Table 16–21 OracleArrayMappingAttribute Methods**

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

## IOracleCustomType Interface

IOracleCustomType is an interface for converting between a Custom Type and an Oracle Object or Collection Type.

### Declaration

```
// C#  
public interface IOracleCustomType
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [IOracleCustomType Members](#)
- [IOracleCustomType Interface Methods](#)

## IOracleCustomType Members

IOracleCustomType members are listed in the following tables.

### IOracleCustomType Interface Methods

IOracleCustomType interface methods are listed in [Table 16-22](#).

**Table 16-22** *IOracleCustomType Interface Methods*

Interface Method	Description
<a href="#">FromCustomObject</a>	Returns the values that set the Oracle Object attributes
<a href="#">ToCustomObject</a>	Provides the Oracle Object with the attribute values to set on the custom type

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleCustomType Interface](#)

## IOracleCustomType Interface Methods

IOracleCustomType Interface methods are listed in [Table 16–23](#).

**Table 16–23 IOracleCustomType Interface Methods**

Interface Method	Description
<a href="#">FromCustomObject</a>	Returns the values that set the Oracle Object attributes
<a href="#">ToCustomObject</a>	Provides the Oracle Object with the attribute values to set on the custom type

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

### FromCustomObject

This interface method creates an Oracle Object or Collection by setting the attribute or element values respectively on the specified Oracle UDT.

**Declaration**

```
// C#
void FromCustomObject(OracleConnection con, IntPtr pUdt);
```

**Parameters**

- *con*  
An OracleConnection instance.
- *pUdt*  
An opaque pointer to the Oracle Object or Collection to be created.

**Remarks**

The FromCustomObject method is used to build an Oracle Object or Collection from a custom object by setting attribute or element values respectively through the OracleUdt.SetValue method.

The OracleUdt.SetValue method is invoked as follows:

- Oracle Object Type  
For a custom type that represents an Oracle Object Type, the OracleUdt.SetValue method must be invoked for each non-NULL attribute value that needs to be set.
- Oracle Collection Type  
For a custom type that represents an Oracle Collection Type, a single call to OracleUdt.SetValue method specifies the collection element values.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

**ToCustomObject**

This interface initializes a custom object using the specified Oracle UDT.

**Declaration**

```
// C#  
void ToCustomObject (OracleConnection con, IntPtr pUdt);
```

**Parameters**

- *con*  
An OracleConnection instance.
- *pUdt*  
An opaque pointer to the Oracle UDT.

**Remarks**

The ToCustomObject method is used to initialize a custom object from the specified Oracle Object or Collection by retrieving attribute or element values respectively through the OracleUdt.GetValue method.

The OracleUdt.GetValue method is invoked as follows:

- Oracle Object Type  
For a custom type that represents an Oracle Object Type, the OracleUdt.GetValue method must be invoked for each attribute value to be retrieved.
- For a custom type that represents an Oracle Collection Type, a single call to OracleUdt.GetValue method retrieves the collection element values.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

## IOracleCustomTypeFactory Interface

---

The `IOracleCustomTypeFactory` interface is used by ODP.NET to create custom objects that represent Oracle Objects or Collections.

### Declaration

```
// C#  
public interface IOracleCustomTypeFactory
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [IOracleCustomTypeFactory Members](#)
- [IOracleCustomTypeFactory Interface Methods](#)

## IOracleCustomTypeFactory Members

IOracleCustomTypeFactory members are listed in the following tables.

### IOracleCustomTypeFactory Interface Methods

IOracleCustomTypeFactory interface methods are listed in [Table 16-24](#).

**Table 16-24** *IOracleCustomTypeFactory Interface Methods*

Public Method	Description
<a href="#">CreateObject</a>	Returns a new custom object to represent an Oracle Object or Collection

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleCustomTypeFactory Interface](#)

## IOracleCustomTypeFactory Interface Methods

IOracleCustomTypeFactory Interface methods are listed in [Table 16–25](#).

**Table 16–25** *IOracleCustomTypeFactory Interface Methods*

Public Method	Description
<a href="#">CreateObject</a>	Returns a new custom object to represent an Oracle Object or Collection

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleCustomTypeFactory Interface](#)
- [IOracleCustomTypeFactory Members](#)

### CreateObject

This interface method returns a new custom object to represent an Oracle Object or Collection.

**Declaration**

```
// C#  
IOracleCustomType CreateObject();
```

**Return Value**

An IOracleCustomType object.

**Remarks**

The `CreateObject` method is used to create a new instance of a custom object to represent an Oracle Object or Collection.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleCustomTypeFactory Interface](#)
- [IOracleCustomTypeFactory Members](#)



## IOracleArrayTypeFactory Interface

The `IOracleArrayTypeFactory` interface is used by ODP.NET to create arrays that represent Oracle Collections.

### Declaration

```
// C#  
public interface IOracleArrayTypeFactory
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [IOracleArrayTypeFactory Members](#)
- [IOracleArrayTypeFactory Interface Methods](#)

## IOracleArrayTypeFactory Members

IOracleArrayTypeFactory members are listed in the following tables.

### IOracleArrayTypeFactory Interface Methods

IOracleArrayTypeFactory interface methods are listed in [Table 16-26](#).

**Table 16-26** *IOracleArrayTypeFactory Interface Methods*

Public Method	Description
<a href="#">CreateArray</a>	Returns a new array of the specified length to store Oracle Collection elements
<a href="#">CreateStatusArray</a>	Returns a newly allocated <code>OracleUdtStatus</code> array of the specified length that will be used to store the null status of the collection elements

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleArrayTypeFactory Interface](#)

## IOracleArrayTypeFactory Interface Methods

IOracleArrayTypeFactory Interface methods are listed in [Table 16–27](#).

**Table 16–27 IOracleArrayTypeFactory Interface Methods**

Public Method	Description
<a href="#">CreateArray</a>	Returns a new array of the specified length to store Oracle Collection elements
<a href="#">CreateStatusArray</a>	Returns a newly allocated <code>OracleUdtStatus</code> array of the specified length that will be used to store the null status of the collection elements

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)

### CreateArray

This interface method returns a new array of the specified length to store Oracle Collection elements.

#### Declaration

```
// C#
Array CreateArray(int numElems);
```

#### Parameters

- *numElems*  
The number of collection elements to be returned.

#### Return Value

A `System.Array` object.

#### Remarks

An Oracle Collection Type may be represented in either of the following ways:

- As an array of the appropriate type. The type must be able to represent a collection element.
- As a Custom Type that contains an array of the appropriate type.

In both cases, the `CreateArray` method creates an array of the specified length to store the collection elements.

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)

## CreateStatusArray

This method returns a newly allocated `OracleUdtStatus` array of the specified length that will be used to store the null status of the collection elements.

### Declaration

```
// C#  
Array CreateStatusArray(int numElems);
```

### Parameters

- `numElems`

The number of collection elements to be returned.

### Return Value

A multi-dimensional `OracleUdtStatus` array as a `System.Array`.

### Remarks

An Oracle Collection Type can be represented in the following ways:

- As an array of the appropriate type. The type must be able to represent a collection element.
- As a Custom Type that contains an array of the appropriate type.

In both cases, the `CreateStatusArray` method creates an `OracleUdtStatus` array of the specified length that stores the null status of the collection elements.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

---

## OracleUdt Class

The `OracleUdt` class defines static methods that are used when converting between Custom Types and Oracle UDTs and vice-versa.

### Class Inheritance

`System.Object`

`System.OracleUdt`

### Declaration

```
public sealed class OracleUdt
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleUdt Members](#)
- [OracleUDT Static Methods](#)

## OracleUdt Members

OracleUdt static methods are listed in [Table 16–28](#).

**Table 16–28 OracleUdt Static Methods**

Static Method	Description
Equals	Inherited from <code>System.Object</code>
<a href="#">GetValue</a>	Gets the attributes or elements from the specified Oracle UDT (Overloaded)
<a href="#">IsDBNull</a>	Indicates whether or not the specified attribute being retrieved is NULL (Overloaded)
<a href="#">SetValue</a>	Sets the attributes or elements on the specified Oracle UDT (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)

## OracleUDT Static Methods

OracleUDT methods are listed in [Table 16–29](#).

**Table 16–29 OracleUdt Static Methods**

Static Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
<a href="#">GetValue</a>	Gets the attributes or elements from the specified Oracle UDT (Overloaded)
<a href="#">IsDBNull</a>	Indicates whether or not the specified attribute being retrieved is NULL (Overloaded)
<a href="#">SetValue</a>	Sets the attributes or elements on the specified Oracle UDT (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)

### GetValue

`GetValue` methods get the attributes or elements from the specified Oracle UDT.

**Overload List:**

- [GetValue\(OracleConnection, IntPtr, string\)](#)  
This method gets the attributes or elements from the specified Oracle UDT, using the specified attribute name.
- [GetValue\(OracleConnection, IntPtr, int\)](#)  
This method gets the attribute or elements from the specified Oracle UDT, using the specified index.
- [GetValue\(OracleConnection, IntPtr, string, out object\)](#)  
This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.
- [GetValue\(OracleConnection, IntPtr, int, out object\)](#)  
This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

### GetValue(OracleConnection, IntPtr, string)

This method gets the attributes or elements from the specified Oracle UDT, using the specified attribute name.

**Declaration**

```
public static object GetValue(OracleConnection con, IntPtr pUdt, string attrName);
```

**Parameters**

- *con*  
An `OracleConnection` instance.
- *pUdt*  
A pointer to an Oracle UDT.
- *attrName*  
The case-sensitive name of the attribute to be retrieved. Null is specified for retrieving collection elements from a Custom Type that represents an Oracle Collection.

**Return Value**

An object representing the returned attribute or collection elements.

**Exceptions**

`ArgumentException` - The specified name is not a valid attribute name.

**Remarks**

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type  
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73



## GetValue(OracleConnection, IntPtr, int)

This method gets the attribute or elements from the specified Oracle UDT, using the specified index.

### Declaration

```
// C#  
public static object GetValue(OracleConnection con, IntPtr pUdt, int attrIndex,);
```

### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*  
A pointer to an Oracle UDT.
- *attrIndex*  
The zero-based index of the attribute to be retrieved. For retrieving collection elements from a Custom Type that represents an Oracle Collection, zero must be specified.

### Return Value

An object representing the returned attribute or collection elements.

### Exceptions

`ArgumentOutOfRangeException` - The specified index is not a valid attribute index.

### Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type  
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

**GetValue(OracleConnection, IntPtr, string, out object)**

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

**Declaration**

```
// C#
public static object GetValue(OracleConnection con, IntPtr pUdt, string attrName,
    out object statusArray);
```

**Parameters**

- *con*  
An `OracleConnection` instance.
- *pUdt*  
An opaque pointer to an Oracle UDT.
- *attrName*  
The case-sensitive name of the attribute to be retrieved. Null must be specified for retrieving collection elements from a Custom Type that represents an Oracle Collection.
- *statusArray* - The `OracleUdtStatus` array which returns the null status for the retrieved collection elements.

**Return Value**

An object representing the returned attribute or collection elements.

**Exceptions**

`ArgumentException` - The specified name is not a valid attribute name.

**Remarks**

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of `NULL` attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

If the collection being returned is not `NULL`, the output `statusArray` parameter is populated with the null status for each of the collection elements.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

### GetValue(OracleConnection, IntPtr, int, out object)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

#### Declaration

```
// C#
public static object GetValue(OracleConnection con, IntPtr pUdt, int attrIndex,
    out object statusArray);
```

#### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*  
An opaque pointer to an Oracle UDT.
- *attrIndex*  
The zero-based index of the attribute to be retrieved. For retrieving collection elements from a Custom Type that represents an Oracle Collection, 0 is specified.
- *statusArray*  
The `OracleUdtStatus` array which returns the null status for the retrieved collection elements.

#### Return Value

An object representing the returned attribute or collection elements.

#### Exceptions

`ArgumentOutOfRangeException` - The specified index is not a valid attribute index.

**Remarks**

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the `con` and `pUdt` parameters. The `OracleUdt.GetValue` method returns these types of object:

- **Oracle Object Type**  
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- **Oracle Collection Type**  
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of `NULL` attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

If the collection being returned is not `NULL`, the output `statusArray` parameter is populated with the null status for each of the collection elements.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

**IsDBNull**

`IsDBNull` methods indicate whether or not the specified attribute being retrieved is `NULL`.

**Overload List:**

- [IsDBNull\(OracleConnection, IntPtr, string\)](#)  
This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, pointer, and attribute name, is `NULL`.
- [IsDBNull\(OracleConnection, IntPtr, int\)](#)  
This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, pointer, and attribute index, is `NULL`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

## IsDBNull(OracleConnection, IntPtr, string)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, pointer, and attribute name, is NULL.

### Declaration

```
// C#  
public static bool IsDBNull(OracleConnection con, IntPtr pUdt, string attrName);
```

### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*  
A pointer to an Oracle UDT.
- *attrName*  
The case-sensitive name of the attribute.

### Return Value

True if the specified attribute is NULL; otherwise, false.

### Exceptions

`ArgumentException` - The specified name is not a valid attribute name.

### Remarks

This method is invoked from the `IOracleCustomType.ToCustomObject` method. The *con* and *pUdt* parameter is passed from the `IOracleCustomType.ToCustomObject` method to the `OracleUdt.IsDBNull` method. The *attrName* parameter is case-sensitive.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)

## IsDBNull(OracleConnection, IntPtr, int)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, pointer, and attribute index, is NULL.

### Declaration

```
// C#  
public static bool IsDBNull(OracleConnection con, IntPtr pUdt, int attrIndex);
```

### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*

An opaque pointer to an Oracle UDT.

- *attrIndex*

The zero-based index of the attribute.

### Return Value

True if the specified attribute is NULL; otherwise, false.

### Exceptions

*ArgumentOutOfRangeException* - The specified index is not a valid attribute index

### Remarks

This method is invoked from the *IOracleCustomType.ToCustomObject* method. The *con* and *pUdt* parameter is passed from the *IOracleCustomType.ToCustomObject* method to the *OracleUdt.IsDBNull* method.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)

## SetValue

*SetValue* methods set the attributes or elements on the specified Oracle UDT.

### Overload List:

- [SetValue\(OracleConnection, IntPtr, string, object\)](#)

This method sets the attribute or elements on the specified Oracle UDT, using the specified attribute name and value.

- [SetValue\(OracleConnection, IntPtr, int, object\)](#)

This method sets the attribute or elements on the specified Oracle UDT, using the specified index and value.

- [SetValue\(OracleConnection, IntPtr, string, object, object\)](#)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

- [SetValue\(OracleConnection, IntPtr, int, object, object\)](#)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- [OracleUdt Members](#)

## SetValue(OracleConnection, IntPtr, string, object)

This method sets the attribute or elements on the specified Oracle UDT, using the specified attribute name and value.

### Declaration

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, string attrName,  
    object value);
```

### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*  
An opaque pointer to an Oracle UDT.
- *attrName*  
The name of the attribute to be set. Specify null for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*  
The attribute or collection value to be set.

### Exceptions

`ArgumentException` - The specified value is not of the appropriate type.

### Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type  
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

## SetValue(OracleConnection, IntPtr, int, object)

This method sets the attribute or elements on the specified Oracle UDT, using the specified index and value.

**Declaration**

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, int attrIndex,  
object value);
```

**Parameters**

- *con*  
An `OracleConnection` instance.
- *pUdt*  
An opaque pointer to an Oracle UDT.
- *attrIndex*  
The index of the attribute to be set. Specify 0 for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*  
The attribute or collection value to be set.

**Exceptions**

`ArgumentException` - The specified value is not of the appropriate type.

**Remarks**

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type  
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

**SetValue(OracleConnection, IntPtr, string, object, object)**

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

**Declaration**

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, string attrName,
```



```
object value, object statusArray);
```

### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*  
An opaque pointer to an Oracle UDT.
- *attrName*  
The name of the attribute to be set. Specify null for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*  
The attribute or collection value to be set.
- *statusArray*  
The null status for the collection elements.

### Exceptions

`ArgumentException` - The specified value is not of the appropriate type.

### Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type  
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

### SetValue(OracleConnection, IntPtr, int, object, object)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

### Declaration

```
// C#
public static void SetValue(OracleConnection con, IntPtr pUdt, int attrIndex,
```

```
object value, object statusArray);
```

### Parameters

- *con*  
An `OracleConnection` instance.
- *pUdt*  
An opaque pointer to an Oracle UDT.
- *attrIndex*  
The index of the attribute to be set. Specify 0 for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*  
The attribute or collection value to be set.
- *statusArray*  
The null status for the collection elements.

### Exceptions

`ArgumentException` - The specified value is not of the appropriate type.

### Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type  
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type  
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

---

## OracleRef Class

An `OracleRef` instance represents an Oracle REF, which references a persistent, standalone, referenceable object that resides in the database. The `OracleRef` object provides methods to insert, update, and delete the Oracle REF.

### Class Inheritance

```
System.Object
    System.MarshalByRefObject
        Oracle.DataAccess.Types.OracleRef
```

### Declaration

```
// C#
public sealed class OracleRef : MarshalByRefObject, ICloneable, IDisposable,
    INullable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

If two or more `OracleRef` objects that refer to the same Oracle object in the database are retrieved through the same `OracleConnection`, then their operations on the referenced object must be synchronized.

### Requirements

Namespace: `Oracle.DataAccess.Types`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Members](#)
- [OracleRef Constructors](#)
- [OracleRef Static Methods](#)
- [OracleRef Instance Properties](#)
- [Oracle Ref Instance Methods](#)

## OracleRef Members

OracleRef members are listed in the following tables.

### OracleRef Constructors

OracleRef constructors are listed in [Table 16–30](#).

**Table 16–30 OracleRef Constructors**

Constructor	Description
<a href="#">OracleRef Constructors</a>	Instantiates a new instance of OracleRef class (Overloaded)

### OracleRef Static Fields

OracleRef static methods are listed in [Table 16–31](#)

**Table 16–31 OracleRef Static Fields**

Static Field	Description
<a href="#">Null</a>	Represents a null value that can be assigned to an OracleRef instance

### OracleRef Static Methods

OracleRef static methods are listed in [Table 16–32](#).

**Table 16–32 OracleRef Static Methods**

Method	Description
<a href="#">Equals</a>	Inherited from System.Object (Overloaded)

### OracleRef Instance Properties

OracleRef instance properties are listed in [Table 16–33](#).

**Table 16–33 OracleRef Instance Properties**

Property	Description
<a href="#">Connection</a>	References the connection used by the OracleRef
<a href="#">HasChanges</a>	References the connection used by the OracleRef
<a href="#">IsLocked</a>	Indicates whether or not the REF is locked
<a href="#">IsNull</a>	Indicates whether or not the Oracle REF is NULL
<a href="#">ObjectTableName</a>	Returns the fully qualified object table name that is associated with the REF
<a href="#">Value</a>	Returns a .NET representation of this Oracle REF

### OracleRef Instance Methods

OracleRef instance methods are listed in [Table 16–34](#).

**Table 16–34 OracleRef Instance Methods**

Method	Description
<a href="#">Clone</a>	Clones the REF

**Table 16–34 (Cont.) OracleRef Instance Methods**

Method	Description
<a href="#">Delete</a>	Deletes the referenced object from the database
<a href="#">Dispose</a>	Releases resources allocated for the <code>OracleRef</code> instance
<code>Equals</code>	Inherited from <code>System.Object</code>
<a href="#">Flush</a>	Flushes changes made on the REF object to the database
<a href="#">GetCustomObject</a>	Returns the object that the specified REF references as a custom type (Overloaded)
<a href="#">GetCustomObjectForUpdate</a>	Returns the object that the specified REF references as a custom type (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<a href="#">IsEqual</a>	Compares two <code>OracleREF</code> objects
<a href="#">Lock</a>	Locks the REF in the database
<code>ToString</code>	Inherited from <code>System.Object</code>
<a href="#">Update</a>	Updates the object referenced by the specified REF in the database using the specified custom object

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)

## OracleRef Constructors

OracleRef constructors instantiate new instances of OracleRef class.

### Overload List:

- [OracleRef\(OracleConnection, string\)](#)

This constructor creates an instance of the OracleRef class with a connection and a HEX string that represents an REF instance in the database.

- [OracleRef\(OracleConnection, string, string\)](#)

This constructor creates an instance of the OracleRef class using the specified OracleConnection object, user-defined type name, and an object table name

### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

### OracleRef(OracleConnection, string)

This constructor creates an instance of the OracleRef class with a connection and a HEX string that represents an REF instance in the database.

### Declaration

```
// C#  
public OracleRef(OracleConnection con, string hexStr);
```

### Parameters

- *con*  
An OracleConnection instance.
- *hexStr*  
A HEX string that represents an REF instance in the database.

### Exceptions

*ArgumentException* - The HEX string does not represent a valid REF in the database.

*ArgumentNullException* - The connection or HEX string is null.

*InvalidOperationException* - The OracleConnection object is not open.

### Remarks

When an OracleRef instance is created, it is referenced to a specific table in the database.

The connection must be opened explicitly by the application. OracleRef does not open the connection implicitly.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

**OracleRef(OracleConnection, string, string)**

This constructor creates an instance of the `OracleRef` class using the specified `OracleConnection` object, user-defined type name, and an object table name.

**Declaration**

```
// C#  
public OracleRef(OracleConnection con, string udtTypeName, string objTabName);
```

**Parameters**

- *con*  
An `OracleConnection` instance.
- *udtTypeName*  
A user-defined type name.
- *objTabName*  
An object table name.

**Exceptions**

`ArgumentException` - The object type name or the object table name is not valid.

`ArgumentNullException` - The object type name or the table name is null.

`InvalidOperationException` - The `OracleConnection` object is not open.

**Remarks**

When an `OracleRef` instance is created, this `OracleRef` instance is associated with the specific table in the database. In other words, it represents a persistent REF.

This constructor creates a reference to the object table. However, it does not cause any entries to be made in database tables until the object is flushed to the database, that is, until the `OracleRef.Flush` or the `OracleConnection.FlushCache` method is called on the `OracleRef` Connection. Therefore, any operation that attempts to operate on the database copy of the object before flushing the object, such as, lock the object or fetch the latest copy of the object from the database, results in an `OracleException`.

The connection must be opened explicitly by the application. `OracleRef` does not open the connection implicitly.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["FlushCache" on page 5-98](#)

## OracleRef Static Fields

OracleRef static fields are listed in [Table 16–35](#).

**Table 16–35 OracleRef Static Fields**

Static Field	Description
<a href="#">Null</a>	Represents a null value that can be assigned to an OracleRef instance

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

### Null

This static field represents a null value that can be assigned to an OracleRef instance.

**Declaration**

```
// C#  
public static readonly OracleRef Null;
```

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)



## OracleRef Static Methods

OracleRef static methods are listed in [Table 16–36](#).

**Table 16–36 OracleRef Static Methods**

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## OracleRef Instance Properties

OracleRef instance properties are listed in [Table 16-37](#).

**Table 16-37 OracleRef Instance Properties**

Property	Description
<a href="#">Connection</a>	References the connection used by the OracleRef
<a href="#">HasChanges</a>	References the connection used by the OracleRef
<a href="#">IsLocked</a>	Indicates whether or not the REF is locked
<a href="#">IsNull</a>	Indicates whether or not the Oracle REF is NULL
<a href="#">ObjectTableName</a>	Returns the fully qualified object table name that is associated with the REF
<a href="#">Value</a>	Returns a .NET representation of this Oracle REF

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

### Connection

This instance property references the connection used by the OracleRef.

**Declaration**

```
// C#
public OracleConnection Connection{get;}
```

**Property Value**

An OracleConnection object associated with the REF.

**Exceptions**

ObjectDisposedException - The object is already disposed.

**Remarks**

Once the Dispose method is invoked, this property is set to null.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

### HasChanges

This instance property indicates whether or not the object referenced by the Oracle REF in the object cache has any changes that can be flushed to the database.

### Declaration

```
// C#  
public bool HasChanges {get;}
```

### Property Value

Returns `true` if the object referenced by the Oracle REF in the object cache has any changes that can be flushed to the database; otherwise, returns `false`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

### Remarks

This property returns `true` if a copy of the referenced object in the object cache is updated or deleted.

If there is no copy of the referenced object in the object cache, the latest copy of the referenced object in the database is cached in the object cache and `false` is returned.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## IsLocked

This instance property indicates whether or not the REF is locked.

### Declaration

```
// C#  
public bool IsLocked {get;}
```

### Property Value

Returns `true` if the REF is locked; otherwise returns `false`.

### Exceptions

`ObjectDisposedException` - The object is already disposed.

#### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## IsNull

This instance property indicates whether or not the Oracle REF is NULL.

### Declaration

```
// C#  
public bool IsNull {get;}
```

**Property Value**

Returns true if the REF is NULL; otherwise, returns false.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

If the Oracle REF is NULL, this property returns true. Otherwise, it returns false.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

**ObjectTableName**

This instance property returns the fully-qualified object table name that is associated with the REF.

**Declaration**

```
// C#  
public string ObjectTableName{get;}
```

**Property Value**

A fully-qualified object table name that is associated with the REF.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

The object table name is in the form *schema\_Name.Table\_Name*.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

**Value**

This instance property returns a .NET representation of this Oracle REF.

**Declaration**

```
// C#  
public string Value{get;}
```

**Property Value**

A .NET representation of the Oracle REF.

**Exceptions**

`ObjectDisposedException` - The object is already disposed.

**Remarks**

This property returns a HEX string that represents the REF.

The returned string can be used to create a new `OracleRef` instance by using the `OracleRef(OracleConnection, string)` constructor.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleRef\(OracleConnection, string\)"](#) on page 16-54

## Oracle Ref Instance Methods

OracleRef instance methods are listed in [Table 16–38](#).

**Table 16–38 OracleRef Instance Methods**

Method	Description
<a href="#">Clone</a>	Clones the REF
<a href="#">Delete</a>	Deletes the referenced object from the database
<a href="#">Dispose</a>	Releases resources allocated for the OracleRef instance
<a href="#">Equals</a>	Inherited from <code>System.Object</code>
<a href="#">Flush</a>	Flushes changes made on the REF object to the database
<a href="#">GetCustomObject</a>	Returns the object that the specified REF references as a custom type (Overloaded)
<a href="#">GetCustomObjectForUpdate</a>	Returns the object that the specified REF references as a custom type (Overloaded)
<a href="#">GetHashCode</a>	Inherited from <code>System.Object</code>
<a href="#">GetType</a>	Inherited from <code>System.Object</code>
<a href="#">IsEqual</a>	Compares two OracleREF objects
<a href="#">Lock</a>	Locks the REF in the database
<a href="#">ToString</a>	Inherited from <code>System.Object</code>
<a href="#">Update</a>	Updates the object referenced by the specified REF in the database using the specified custom object

### See Also:

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## Clone

This instance method clones the REF.

### Declaration

```
// C#
public OracleRef Clone();
```

### Return Value

A clone of the current instance.

### Implements

`ICloneable`

### Exceptions

`InvalidOperationException` - The associated connection is not open.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## Delete

This method deletes the referenced object from the database.

**Declaration**

```
// C#  
public void Delete(bool bFlush);
```

**Parameters**

- *bFlush*

A `bool` that specifies whether or not the REF is flushed immediately.

**Remarks**

This method marks the specified REF for deletion.

Depending on whether the value of *bFlush* is set to `true` or `false`, the following occurs:

- `True`

The object referenced by the specified REF is deleted immediately from the database.

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

- `False`

The object referenced by the REF is not deleted immediately from the database, but only when a subsequent `Flush` method is invoked for the specified REF or the `FlushCache` method is invoked on the `OracleRef` or the `FlushCache` method is invoked on the `OracleRef` connection.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)
- `OracleConnection` ["FlushCache"](#) on page 5-98

## Dispose

This instance method releases resources allocated for the `OracleRef` instance.

**Declaration**

```
// C#
```

```
public void Dispose();
```

**Implements**

IDisposable

**Remarks**

The object cannot be reused after it is disposed. Although some properties can still be accessed, their values may not be up-to-date.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

**Flush**

This instance method flushes changes made on the REF object to the database, such as updates or deletes.

**Declaration**

```
// C#  
public void Flush();
```

**Exceptions**

`InvalidOperationException` - The associated connection is not open.

**Remarks**

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

**GetCustomObject**

`GetCustomObject` methods return the object that the specified REF references as a custom type.

**Overload List**

- [GetCustomObject\(OracleUdtFetchOption\)](#)

This method returns the object that the specified REF references as a custom type using the specified fetch option.

- [GetCustomObject\(OracleUdtFetchOption, int\)](#)



This method returns the object that the specified REF references as a custom type using the specified fetch option and depth level.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

**GetCustomObject(OracleUdtFetchOption)**

This method returns the object that the specified REF references, as a custom type, using the specified fetch option.

**Declaration**

```
// C#  
public object GetCustomObject(OracleUdtFetchOption fetchOption);
```

**Parameters**

- *fetchOption*  
An `OracleUdtFetchOption` value.

**Return Value**

A custom object that represents the object that the specified REF references.

**Exceptions**

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for the type of the referenced object.

**Remarks**

This method returns a custom type determined by the UDT mappings on the specified connection.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned according to the specified option:

- `OracleUdtFetchOption.Cache` option  
If this option is specified, and there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
- `OracleUdtFetchOption.Server` option  
If this option is specified, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
- `OracleUdtFetchOption.TransactionCache` option  
If this option is specified, and a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a

copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the `OracleRef.HasChanges` property returns `true`, then the `Recent` option returns the cached copy of the referenced object. Outside of a transaction, the `Recent` option behaves like the `Any` option.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

### **GetCustomObject(OracleUdtFetchOption, int)**

This method returns the object that the specified REF references, as a custom type, using the specified fetch option and depth level.

**Declaration**

```
// C#  
public object GetCustomObject(OracleUdtFetchOption fetchOption, int depthLevel);
```

**Parameters**

- *fetchOption*  
An `OracleUdtFetchOption` value.
- *depthLevel*  
The number of levels to be fetched for nested REF attributes.

**Return Value**

A custom object that represents the object that the specified REF references.

**Exceptions**

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for the type of the referenced object.

**Remarks**

This method returns a custom type determined by the UDT mappings on the specified connection.

If the object that the REF references contains nested REF attributes, the *depthLevel* can be specified to optimize the subsequent object retrieval. The value of *depthLevel* determines the number of levels that are optimized.

For example, if the *depthLevel* is specified as two, the optimization is applied to all top-level nested REF attributes in the object being fetched and also to all nested REF attributes within the objects referenced by the top-level nested REF attributes.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned according to the specified option:

- `OracleUdtFetchOption.Cache` option  
If this option is specified, and there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
- `OracleUdtFetchOption.Server` option  
If this option is specified, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
- `OracleUdtFetchOption.TransactionCache` option  
If this option is specified, and a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the `OracleRef.HasChanges` property returns `true`, then the `Recent` option returns the cached copy of the referenced object. Outside of a transaction, the `Recent` option behaves like the `Any` option.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-73

## GetCustomObjectForUpdate

`GetCustomObjectForUpdate` methods return the object that the specified REF references as a custom type.

- `GetCustomObjectForUpdate(bool)`  
This method locks the specified REF in the database and returns the object that the specified REF references as a custom type using the specified wait option.
- `GetCustomObjectForUpdate(bool, int)`  
This method locks the specified REF in the database and returns the object that the specified REF references as a custom type using the specified wait option and depth level.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## GetCustomObjectForUpdate(bool)

This method locks the specified REF in the database and returns the object that the specified REF references, as a custom type, using the specified wait option.

### Declaration

```
// C#  
public object GetCustomObjectForUpdate(bool bWait);
```

### Parameters

- *bWait*

Specifies if the REF is to be locked with the no-wait option. If wait is set to `true`, this method invocation does not return until the REF is locked.

### Return Value

A custom object that represents the object that the specified REF references.

### Exceptions

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for type of the referenced object.

`OracleException` - *bWait* is set to `false`, and the lock cannot be acquired.

### Remarks

This method returns the latest copy of the referenced object, as a custom type, determined by the custom types registered on the `OracleRef` connection.

To be able to release the lock on the REF appropriately after flushing the REF using the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection`, the application must commit or rollback the transaction.

Therefore, it is required that, before invoking this method, a transaction is explicitly started by executing the `BeginTransaction` method on the `OracleConnection` object.

This method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the associated row object exclusively. Then a call to the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If `true` is passed, this method blocks until the lock can be acquired. If `false` is passed, this method immediately returns. If the lock cannot be acquired, an `OracleException` is thrown.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

#### See Also:

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

## GetCustomObjectForUpdate(bool, int)

This method locks the specified REF in the database and returns the object that the specified REF references, as a custom type, using the specified wait option and depth level

### Declaration

```
public object GetCustomObjectForUpdate(bool bWait, int depthLevel);
```

### Parameters

- *bWait*  
A boolean value that specifies if the REF is to be locked with the no-wait option. If wait is set to `true`, this method invocation does not return until the REF is locked.
- *depthLevel*  
The number of levels to be fetched for nested REF attributes.

### Return Value

A custom object that represents the object that the specified REF references.

### Exceptions

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for type of the referenced object.

`OracleException` - *bWait* is set to `false`, and the lock cannot be acquired.

### Remarks

This method returns the latest copy of the referenced object, as a custom type, determined by the custom types registered on the `OracleRef` connection.

To be able to release the lock on the REF appropriately after flushing the REF using the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection`, the application must commit or rollback the transaction. Therefore, it is required that, before invoking this method, a transaction is explicitly started by executing the `BeginTransaction` method on the `OracleConnection` object.

This method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the associated row object exclusively. Then a call to the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If `true` is passed, this method blocks until the lock can be acquired. If `false` is passed, this method immediately returns. If the lock cannot be acquired, an `OracleException` is thrown.

If the object that the REF references contains nested REF attributes, the *depthLevel* can be specified to optimize the subsequent object retrieval. The value of *depthLevel* determines the number of levels that are optimized.

For example, if the *depthLevel* is specified as 2, the optimization is applied to all top-level nested REF attributes in the object being fetched and also to all nested REF attributes within the objects referenced by the top-level nested REF attributes.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## IsEqual

This instance method compares two OracleREF objects.

**Declaration**

```
// C#  
public bool IsEqual(OracleRef oraRef);
```

**Parameters**

- *oraRef*

The provided OracleRef object.

**Return Value**

bool

**Remarks**

This instance method returns `true` if the OracleRef instance and the OracleRef parameter both reference the same object. Otherwise, it returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## Lock

This instance method locks the REF in the database.

**Declaration**

```
// C#  
public bool Lock(bool bWait);
```

**Parameters**

- *bWait*

Specifies if the lock is set to the no-wait option. If *bWait* is set to `true`, the method invocation does not return until the REF is locked.

**Return Value**

A boolean value that indicates whether or not the lock has been acquired.

**Exceptions**

`InvalidOperationException` - The associated connection is not open.

`ObjectDisposedException` - The object is already disposed.

**Remarks**

In order for the application to release the lock on the REF appropriately after the `Flush` invocation on the `OracleRef` or `FlushCache` methods, the application must commit or rollback the transaction. Therefore, it is required that, before invoking a lock on an `OracleRef` object, a transaction is explicitly started by executing the `BeginTransaction` method on the `OracleConnection` object.

This instance method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the attribute values of the associated row object exclusively. Then a call to the `Flush` instance method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If `true` is passed, this method blocks, that is, does not return, until the lock is acquired. Consequently, the return value is always `true`.

If `false` is passed, this method immediately returns. The return value indicates `true` if the lock is acquired, and `false` if it is not.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

**Update**

This method updates the object referenced by the specified REF in the database using the specified custom object.

**Declaration**

```
// C#
public void Update(object customObject, bool bFlush);
```

**Parameters**

- *customObject*  
The custom object used to update the referenced object.
- *bFlush*  
A boolean that specifies if the changes must be flushed immediately. If *bFlush* is set to true, this method invocation flushes the changes immediately.

**Exceptions**

`InvalidOperationException` - The specified connection is not open or the custom object does not map to the type of referenced object.

**Remarks**

This method marks the specified REF for update. Depending on whether the value of *bFlush* is set to true or false, the following occurs:

- True

The object referenced by the specified REF is updated immediately in the database.

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

- **False**

The object referenced by the REF is not updated immediately in the database, but only when a subsequent `Flush` method is invoked for the specified REF or the `FlushCache` method is invoked for the specified connection.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

**See Also:**

- ["Oracle.DataAccess.Types Namespace" on page 1-9](#)
- [OracleRef Class](#)
- [OracleRef Members](#)



## OracleUdtFetchOption Enumeration

OracleUdtFetchOption enumeration values specify how to retrieve a copy of the referenceable object.

Table 16–39 lists all the OracleUdtFetchOption enumeration values with a description of each enumerated value.

**Table 16–39 OracleUdtFetchOption Enumeration Values**

Member Name	Description
Cache	If there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
Server	The latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
TransactionCache	If a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.  Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the <code>OracleRef.HasChanges</code> property returns <code>true</code> , then the <code>Recent</code> option returns the cached copy of the referenced object. Outside of a transaction, the <code>Recent</code> option behaves like the <code>Any</code> option.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

## OracleUdtStatus Enumeration

OracleUdtStatus enumeration values specify the status of an object attribute or collection element. An object attribute or a collection element can be a valid value or a null value.

[Table 16–40](#) lists all the OracleUdtStatus enumeration values with a description of each enumerated value:

**Table 16–40** OracleUdtStatus Enumeration Values

Member Name	Description
Null	Indicates that an object attribute or collection element is NULL.
NotNull	Indicates that a non-NULL value exists for the object attribute or collection element.

**See Also:**

- ["Oracle.DataAccess.Types Namespace"](#) on page 1-9
- [OracleRef Class](#)
- [OracleRef Members](#)

---

---

## Oracle Data Provider for .NET Bulk Copy Classes

This chapter describes Oracle Data Provider for .NET support for Bulk Copy operations.

---

---

**Note:** Oracle Data Provider for .NET bulk copy operations do not support loading of UDT type columns.

---

---

This chapter includes the following topics:

- [OracleBulkCopy Class](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyOptions Enumeration](#)
- [OracleRowsCopiedEventHandler Delegate](#)
- [OracleRowsCopiedEventArgs Class](#)

## OracleBulkCopy Class

An `OracleBulkCopy` object efficiently bulk loads or copies data into an Oracle table from another data source.

### Class Inheritance

`System.Object`

`System.OracleBulkCopy`

### Declaration

```
// C#  
public sealed class OracleBulkCopy : IDisposable
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

The `OracleBulkCopy` class can be used to write data to Oracle database tables only. However, the data source is not limited to Oracle databases; any data source can be used, as long as the data can be loaded to a `DataTable` instance or read with an `IDataReader` instance.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopy Members](#)
- [OracleBulkCopy Constructors](#)
- [OracleBulkCopy Properties](#)
- [OracleBulkCopy Public Methods](#)
- [OracleBulkCopy Events](#)

## OracleBulkCopy Members

OracleBulkCopy members are listed in the following tables.

### OracleBulkCopy Constructors

OracleBulkCopy constructors are listed in [Table 17-1](#).

**Table 17-1 OracleBulkCopy Constructors**

Constructor	Description
<a href="#">OracleBulkCopy Constructors</a>	OracleBulkCopy constructors create new instances of the OracleBulkCopy class

### OracleBulkCopy Properties

OracleBulkCopy properties are listed in [Table 17-2](#).

**Table 17-2 OracleBulkCopy Properties**

Property	Description
<a href="#">BatchSize</a>	Specifies the number of rows to be sent as a batch to the database
<a href="#">BulkCopyOptions</a>	Specifies the OracleBulkCopyOptions enumeration value that determines the behavior of the bulk copy operation
<a href="#">BulkCopyTimeout</a>	Specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted
<a href="#">ColumnMappings</a>	Specifies the column mappings between the data source and destination table
<a href="#">Connection</a>	Specifies the OracleConnection object that the Oracle database uses to perform the bulk copy operation
<a href="#">DestinationTableName</a>	Specifies the database table that the data is loaded in
<a href="#">NotifyAfter</a>	Defines the number of rows to be processed before a notification event is generated

### OracleBulkCopy Public Methods

OracleBulkCopy public methods are listed in [Table 17-3](#).

**Table 17-3 OracleBulkCopy Public Methods**

Method	Description
<a href="#">Close</a>	Closes the OracleBulkCopy instance
<a href="#">Dispose</a>	Releases any resources or memory allocated by the object
<a href="#">WriteToServer</a>	Copies rows to a destination table

### OracleBulkCopy Events

OracleBulkCopy events are listed in [Table 17-4](#).

**Table 17-4 OracleBulkCopy Events**

Event	Description
<a href="#">OracleRowsCopied</a>	Triggered every time the number of rows specified by the <code>OracleBulkCopy.NotifyAfter</code> property has been processed

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)

## OracleBulkCopy Constructors

OracleBulkCopy constructors create new instances of the OracleBulkCopy class.

### Overload List:

- [OracleBulkCopy\(OracleConnection\)](#)  
This constructor instantiates a new instance of OracleBulkCopy class using the specified connection and default value for OracleBulkCopyOptions.
- [OracleBulkCopy\(string\)](#)  
This constructor instantiates a new instance of OracleBulkCopy based on the supplied *connectionString* and default value for OracleBulkCopyOptions.
- [OracleBulkCopy\(OracleConnection, OracleBulkCopyOptions\)](#)  
This constructor instantiates a new instance of OracleBulkCopy using the specified connection object and OracleBulkCopyOptions value.
- [OracleBulkCopy\(string, OracleBulkCopyOptions\)](#)  
This constructor instantiates a new instance of OracleConnection based on the supplied *connectionString* and OracleBulkCopyOptions value.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

### OracleBulkCopy(OracleConnection)

This constructor instantiates a new instance of OracleBulkCopy class using the specified connection and default OracleBulkCopyOptions enumeration values.

### Declaration

```
// C#
public OracleBulkCopy(OracleConnection connection);
```

### Parameters

- *connection*

The open instance of OracleConnection that performs the bulk copy operation.

### Exceptions

ArgumentNullException - The connection parameter is null.

InvalidOperationException - The connection is not in the open state.

### Remarks

The connection object passed to this constructor must be open. It remains open after the OracleBulkCopy instance is closed.

This constructor uses the default enumeration value OracleBulkCopyOptions.Default.

The `Connection` property is set to the supplied connection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-42

## OracleBulkCopy(string)

This constructor instantiates a new instance of the `OracleBulkCopy` class by first creating an `OracleConnection` object based on the supplied `connectionString`, then initializing the new `OracleBulkCopy` object with the `OracleConnection` object and `OracleBulkCopyOptions` default value.

**Declaration**

```
// C#  
public OracleBulkCopy(string connectionString);
```

**Parameters**

- `connectionString`  
The connection information used to connect to the Oracle database and perform the bulk copy operation.

**Exception**

`ArgumentNullException` - The `connectionString` parameter is null.

`ArgumentException` - The `connectionString` parameter is empty.

**Remarks**

The `WriteToServer` method opens the connection, if it is not already opened. The connection is automatically closed when the `OracleBulkCopy` instance is closed.

This constructor uses the default enumeration value `OracleBulkCopyOptions.Default`.

The `Connection` property is set to the `OracleConnection` object initialized using the supplied `connectionString`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-42

## OracleBulkCopy(OracleConnection, OracleBulkCopyOptions)

This constructor instantiates a new instance of `OracleBulkCopy` using the specified connection object and `OracleBulkCopyOptions` value.



**Declaration**

```
// C#
public OracleBulkCopy(OracleConnection connection, OracleBulkCopyOptions
    copyOptions);
```

**Parameters**

- *connection*  
The open instance of an `OracleConnection` object that performs the bulk copy operation.
- *copyOptions*  
The combination of `OracleBulkCopyOptions` enumeration values that determine the behavior of the `OracleBulkCopy` object.

**Exceptions**

`ArgumentNullException` - The *connection* parameter is null.

`InvalidOperationException` - The connection is not in the open state.

**Remarks**

The connection passed to this constructor must be open. It remains open after the `OracleBulkCopy` instance is closed.

The `Connection` property is set to the supplied connection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-42

**OracleBulkCopy(string, OracleBulkCopyOptions)**

This constructor instantiates a new instance of the `OracleBulkCopy` class by first creating an `OracleConnection` object based on the supplied *connectionString*, then initializing the new `OracleBulkCopy` object with the `OracleConnection` object and the supplied `OracleBulkCopyOptions` enumeration values.

**Declaration**

```
// C#
public OracleBulkCopy(string connectionString, OracleBulkCopyOptions copyOptions);
```

**Parameters**

- *connectionString*  
The connection information used to connect to the Oracle database to perform the bulk copy operation.
- *copyOptions*  
The combination of `OracleBulkCopyOptions` enumeration values that determine the behavior of the bulk copy operation.

### Exceptions

`ArgumentNullException` - The *connectionString* is null.

`ArgumentException` - The *connectionString* parameter is empty.

### Remarks

The constructor uses the new instance of the `OracleConnection` class to initialize a new instance of the `OracleBulkCopy` class. The `OracleBulkCopy` instance behaves according to options supplied in the *copyOptions* parameter.

The connection is automatically closed when the `OracleBulkCopy` instance is closed.

The `Connection` property is set to an `OracleConnection` object initialized using the supplied *connectionString*.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-42

## OracleBulkCopy Properties

OracleBulkCopy properties are listed in [Table 17-5](#).

**Table 17-5 OracleBulkCopy Properties**

Property	Description
<a href="#">BatchSize</a>	Specifies the number of rows to be sent as a batch to the database
<a href="#">BulkCopyOptions</a>	Specifies the <code>OracleBulkCopyOptions</code> enumeration value that determines the behavior of the bulk copy operation
<a href="#">BulkCopyTimeout</a>	Specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted
<a href="#">ColumnMappings</a>	Specifies the column mappings between the data source and destination table
<a href="#">Connection</a>	Specifies the <code>OracleConnection</code> object that the Oracle database uses to perform the bulk copy operation
<a href="#">DestinationTableName</a>	Specifies the database table that the data is loaded in
<a href="#">NotifyAfter</a>	Defines the number of rows to be processed before a notification event is generated

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

## BatchSize

This property specifies the number of rows to be sent as a batch to the database.

### Declaration

```
// C#
public int BatchSize {get; set;}
```

### Property Value

An integer value for the number of rows to be sent to the database as a batch.

### Exceptions

`ArgumentOutOfRangeException` - The batch size is less than zero.

### Remarks

The default value is zero, indicating that the rows are not sent to the database in batches. The entire set of rows are sent in one single batch.

A batch is complete when `BatchSize` number of rows have been processed or there are no more rows to send to the database.

- If `BatchSize > 0` and the `UseInternalTransaction` bulk copy option is specified, each batch of the bulk copy operation occurs within a transaction. If the

connection used to perform the bulk copy operation is already part of a transaction, an `InvalidOperationException` exception is raised.

- If `BatchSize > 0` and the `UseInternalTransaction` option is not specified, rows are sent to the database in batches of size `BatchSize`, but no transaction-related action is taken.

The `BatchSize` property can be set at any time. If a bulk copy is already in progress, the current batch size is determined by the previous batch size. Subsequent batches use the new batch size.

If the `BatchSize` property is initially zero and changes while a `WriteToServer` operation is in progress, that operation loads the data as a single batch. Any subsequent `WriteToServer` operations on the same `OracleBulkCopy` instance use the new `BatchSize`.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-42

## BulkCopyOptions

This property specifies the `OracleBulkCopyOptions` enumeration value that determines the behavior of the bulk copy option.

**Declaration**

```
// C#  
public OracleBulkCopyOptions BulkCopyOptions {get; set;}
```

**Property Value**

The `OracleBulkCopyOptions` enumeration object that defines the behavior of the bulk copy operation.

**Exceptions**

`ArgumentNullException` - The bulk copy options set is null.

**Remarks**

The default value of this property is `OracleBulkCopyOptions.Default` value. This property can be used to change the bulk copy options between the batches of a bulk copy operation.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-42

## BulkCopyTimeout

This property specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted.

### Declaration

```
// C#  
public int BulkCopyTimeout {get; set;}
```

### Property Value

An integer value for the number of seconds after which the bulk copy operation times out.

### Exceptions

`ArgumentOutOfRangeException` - The timeout value is set to less than zero.

### Remarks

The default value is 30 seconds.

If `BatchSize>0`, rows that were sent to the database in the previous batches remain committed. The rows that are processed in the current batch are not sent to the database. If `BatchSize=0`, no rows are sent to the database.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

## ColumnMappings

This property specifies the column mappings between the data source and destination table.

### Declaration

```
// C#  
public OracleBulkCopyColumnMappingCollection ColumnMappings {get;}
```

### Property Value

The `OracleBulkCopyColumnMappingCollection` object that defines the column mapping between the source and destination table.

### Remarks

The `ColumnMappings` collection is unnecessary if the data source and the destination table have the same number of columns, and the ordinal position of each source column matches the ordinal position of the corresponding destination column. However, if the column counts differ, or the ordinal positions are not consistent, the `ColumnMappings` collection must be used to ensure that data is copied into the correct columns.

During the execution of a bulk copy operation, this collection can be accessed, but it cannot be changed.

By default, this property specifies an empty collection of column mappings.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**Connection**

This property specifies the `OracleConnection` object that the Oracle database uses to perform the bulk copy operation.

**Declaration**

```
// C#  
public OracleConnection Connection {get; }
```

**Property Value**

The `OracleConnection` object used for the bulk copy operations.

**Remarks**

This property gets the connection constructed by the `OracleBulkCopy`, if the `OracleBulkCopy` object is initialized using a connection string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**DestinationTableName**

This property specifies the database table that the data is loaded into.

**Declaration**

```
// C#  
public string DestinationTableName {get; set;}
```

**Property Value**

A string value that identifies the destination table name.

**Exceptions**

`ArgumentNullException` - The destination table name set is null.

`ArgumentException` - The destination table name is empty.

**Remarks**

If `DestinationTableName` is modified while a `WriteToServer` operation is running, the change does not affect the current operation. The new `DestinationTableName` value is used the next time a `WriteToServer` method is called.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**NotifyAfter**

This property defines the number of rows to be processed before a notification event is generated.

**Declaration**

```
// C#  
public int NotifyAfter {get; set;}
```

**Property Value**

An integer value that specifies the number of rows to be processed before the notification event is raised.

**Exceptions**

*ArgumentOutOfRangeException* - The property value is set to a number less than zero.

**Remarks**

The default value for this property is zero, to specify that no notifications events are to be generated.

This property can be retrieved in user interface components to display the progress of a bulk copy operation. The `NotifyAfter` property can be set at anytime, even during a bulk copy operation. The changes take effect for the next notification and any subsequent operations on the same instance.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

## OracleBulkCopy Public Methods

OracleBulkCopy methods are listed in [Table 17-6](#).

**Table 17-6 OracleBulkCopy Public Methods**

Method	Description
<a href="#">Close</a>	Closes the OracleBulkCopy instance
<a href="#">Dispose</a>	Releases any resources or memory allocated by the object
<a href="#">WriteToServer</a>	Copies rows to a destination table

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

### Close

This method closes the OracleBulkCopy instance.

**Declaration**

```
// C#  
public void Close();
```

**Exceptions**

InvalidOperationException - The Close method was called from a OracleRowsCopied event.

**Remarks**

After the Close method is called on a OracleBulkCopy object, no other operation can succeed. Calls to the WriteToServer method throw an InvalidOperationException. The Close method closes the connection if the connection was opened by the OracleBulkCopy object, that is, if the OracleBulkCopy object was created by a constructor that takes a connection string.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

### Dispose

This method releases any resources or memory allocated by the object.

**Declaration**

```
// C#  
public void Dispose();
```



**Implements**

IDisposable

**Remarks**

After the `Dispose` method is called on the `OracleBulkCopy` object, no other operation can succeed. The connection is closed if the connection was opened by the `OracleBulkCopy` object, that is, if a constructor that takes a connection string created the `OracleBulkCopy` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**WriteToServer**

`WriteToServer` copies rows to a destination table.

**Overload List:**

- [WriteToServer\(DataRow\[\]\)](#)

This method copies all rows from the supplied `DataRow` array to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(DataTable\)](#)

This method copies all rows in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(IDataReader\)](#)

This method copies all rows in the supplied `IDataReader` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(DataTable, DataRowState\)](#)

This method copies rows that match the supplied row state in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(OracleRefCursor\)](#)

This method copies all rows from the specified `OracleRefCursor` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

## WriteToServer(DataRow[])

This method copies all rows from the supplied `DataRow` array to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

### Declaration

```
// C#  
public void WriteToServer(DataRow[] rows);
```

### Parameters

- *rows*

An array of `DataRow` objects to be copied to the destination table.

### Exceptions

`ArgumentNullException` - The *rows* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

### Remarks

The `ColumnMappings` collection maps from the `DataRow` columns to the destination database table.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

## WriteToServer(DataTable)

This method copies all rows in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

### Declaration

```
// C#  
public void WriteToServer(DataTable table);
```

### Parameters

- *table*

The source `DataTable` containing rows to be copied to the destination table.

### Exceptions

`ArgumentNullException` - The *table* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

### Remarks

All rows in the `DataTable` are copied to the destination table except those that have been deleted.

The `ColumnMappings` collection maps from the `DataTable` columns to the destination database table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**WriteToServer(IDataReader)**

This method copies all rows in the supplied `IDataReader` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

**Declaration**

```
// C#  
public void WriteToServer(IDataReader reader);
```

**Parameters**

- *reader*

A `IDataReader` instance containing rows to be copied to the destination table.

**Exceptions**

`ArgumentNullException` - The *reader* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

**Remarks**

The bulk copy operation starts with the next available row of the data reader. Typically, the *reader* returned by a call to the `ExecuteReader` method is passed to the `WriteToServer` method so that the next row becomes the first row. To copy multiple result sets, the application must call `NextResult` on the *reader* and then call the `WriteToServer` method again.

This `WriteToServer` method changes the state of the reader as it calls `reader.Read` internally to get the source rows. Thus, at the end of the `WriteToServer` operation, the *reader* is at the end of the result set.

The `ColumnMappings` collection maps from the data reader columns to the destination database table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**WriteToServer(DataTable, DataRowState)**

This method copies rows that match the supplied row state in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

**Declaration**

```
// C#  
public void WriteToServer(DataTable table, DataRowState rowState);
```

**Parameters**

- *table*  
A `DataTable` containing rows to be copied to the destination table.
- *rowState*  
The `DataRowState` enumeration value. Only rows matching the row state are copied to the destination.

**Exceptions**

`ArgumentNullException` - The *table* or *rowState* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

**Remarks**

Only rows in the `DataTable` that are in the state indicated in the *rowState* argument and have not been deleted are copied to the destination table.

The `ColumnMappings` collection maps from the `DataTable` columns to the destination database table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

**WriteToServer(OracleRefCursor)**

This method copies all rows from the specified `OracleRefCursor` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

**Declaration**

```
// C#  
public void WriteToServer(OracleRefCursor refCursor);
```

**Parameters**

- *refCursor*  
An `OracleRefCursor` object containing rows to be copied to the destination table.

**Exceptions**

`ArgumentNullException` - The *refCursor* parameter is null

`InvalidOperationException` - The connection is not in an open state.

**Remarks**

The `ColumnMappings` collection maps from the `OracleRefCursor` columns to the destination database table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

## OracleBulkCopy Events

OracleBulkCopy events are listed in [Table 17-7](#).

**Table 17-7 OracleBulkCopy Events**

Event	Description
<a href="#">OracleRowsCopied</a>	Triggered every time the number of rows specified by the <code>OracleBulkCopy.NotifyAfter</code> property has been processed

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

### OracleRowsCopied

This event is triggered every time the number of rows specified by the `OracleBulkCopy.NotifyAfter` property has been processed.

**Declaration**

```
// C#  
public event OracleRowsCopiedEventHandler OracleRowsCopied;
```

**Exceptions**

`InvalidOperationException` - The `Close` method is called inside this event.

**Remarks**

This event is raised when the number of rows specified by the `NotifyAfter` property has been processed. It does not imply that the rows have been sent to the database or committed.

To cancel the operation from this event, use the `Abort` property of `OracleRowsCopiedEventArgs` class.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["NotifyAfter"](#) on page 17-13

---

## OracleBulkCopyColumnMapping Class

The `OracleBulkCopyColumnMapping` class defines the mapping between a column in the data source and a column in the destination database table.

### Class Inheritance

`System.Object`

`System.OracleBulkCopyColumnMapping`

### Declaration

```
// C#  
public sealed class OracleBulkCopyColumnMapping
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

Column mappings define the mapping between data source and the target table.

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

---

---

**Note:** Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

---

---

### Example

```
// C#
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Members](#)
- [OracleBulkCopyColumnMapping Constructors](#)
- [OracleBulkCopyColumnMapping Properties](#)

## OracleBulkCopyColumnMapping Members

OracleBulkCopyColumnMapping members are listed in the following tables.

### OracleBulkCopyColumnMapping Constructors

The OracleBulkCopyColumnMapping constructors are listed in [Table 17-8](#).

**Table 17-8 OracleBulkCopyColumnMapping Constructors**

Constructor	Description
<a href="#">OracleBulkCopyColumnMapping Constructors</a>	Instantiates new instances of the OracleBulkCopyColumnMapping class

### OracleBulkCopyColumnMapping Properties

The OracleBulkCopyColumnMapping properties are listed in [Table 17-9](#).

**Table 17-9 OracleBulkCopyColumnMapping Properties**

Property	Description
<a href="#">DestinationColumn</a>	Specifies the column name of the destination table that is being mapped
<a href="#">DestinationOrdinal</a>	Specifies the column ordinal value of the destination table that is being mapped
<a href="#">SourceColumn</a>	Specifies the column name of the data source that is being mapped
<a href="#">SourceOrdinal</a>	Specifies the column ordinal value of the data source that is being mapped

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMapping Class](#)



## OracleBulkCopyColumnMapping Constructors

OracleBulkCopyColumnMapping constructors instantiates new instances of the OracleBulkCopyColumnMapping class.

### Overload List:

- [OracleBulkCopyColumnMapping\(\)](#)  
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class
- [OracleBulkCopyColumnMapping\(int, int\)](#)  
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column ordinal and destination column ordinal.
- [OracleBulkCopyColumnMapping\(int, string\)](#)  
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column ordinal and destination column name.
- [OracleBulkCopyColumnMapping\(string, int\)](#)  
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column name and destination column ordinal.
- [OracleBulkCopyColumnMapping\(string, string\)](#)  
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column name and destination column name.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

### OracleBulkCopyColumnMapping()

This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class.

### Declaration

```
// C#
public OracleBulkCopyColumnMapping();
```

### Remarks

Applications that use this constructor must define the source for the mapping using the SourceColumn or SourceOrdinal property, and must define the destination for the mapping using the DestinationColumn or DestinationOrdinal property.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

**OracleBulkCopyColumnMapping(int, int)**

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source and destination column ordinal positions.

**Declaration**

```
// C#  
public OracleBulkCopyColumnMapping(int sourceColumnOrdinal,  
    int destinationOrdinal);
```

**Parameters**

- *sourceColumnOrdinal*  
The ordinal position of the source column within the data source.
- *destinationOrdinal*  
The ordinal position of the destination column within the destination table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

**OracleBulkCopyColumnMapping(int, string)**

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column ordinal and destination column name.

**Declaration**

```
// C#  
public OracleBulkCopyColumnMapping(int sourceColumnOrdinal,  
    string destinationColumn);
```

**Parameters**

- *sourceColumnOrdinal*  
The ordinal position of the source column within the data source.
- *destinationColumn*  
The name of the destination column within the destination table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

**OracleBulkCopyColumnMapping(string, int)**

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column name and destination column ordinal.

**Declaration**

```
// C#
public OracleBulkCopyColumnMapping(string sourceColumn, int destinationOrdinal);
```

**Parameters**

- *sourceColumn*  
The name of the source column within the data source.
- *destinationOrdinal*  
The ordinal position of the destination column within the destination table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

**OracleBulkCopyColumnMapping(string, string)**

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source and destination column names.

**Declaration**

```
// C#
public OracleBulkCopyColumnMapping(string sourceColumn, string destinationColumn);
```

**Parameters**

- *sourceColumn*  
The name of the source column within the data source.
- *destinationColumn*  
The name of the destination column within the destination table.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

## OracleBulkCopyColumnMapping Properties

The `OracleBulkCopyColumnMapping` properties are listed in [Table 17-10](#).

**Table 17-10 OracleBulkCopyColumnMapping Properties**

Property	Description
<a href="#">DestinationColumn</a>	Specifies the column name of the destination table that is being mapped
<a href="#">DestinationOrdinal</a>	Specifies the column ordinal value of the destination table that is being mapped
<a href="#">SourceColumn</a>	Specifies the column name of the data source that is being mapped
<a href="#">SourceOrdinal</a>	Specifies the column ordinal value of the data source that is being mapped

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

### DestinationColumn

This property specifies the column name of the destination table that is being mapped.

**Declaration**

```
// C#
public string DestinationColumn {get; set;}
```

**Property Value**

A string value that represents the destination column name of the mapping.

**Remarks**

The `DestinationColumn` and `DestinationOrdinal` properties are mutually exclusive. The last value set takes precedence.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

### DestinationOrdinal

This property specifies the column ordinal value of the destination table that is being mapped.

**Declaration**

```
// C#
public int DestinationOrdinal {get; set;}
```

**Property Value**

An integer value that represents the destination column ordinal of the mapping.

**Exceptions**

`IndexOutOfRangeException` - The destination ordinal is invalid.

**Remarks**

The `DestinationOrdinal` and `DestinationColumn` properties are mutually exclusive. The last value set takes precedence.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

**SourceColumn**

This property specifies the column name of the data source that is being mapped.

**Declaration**

```
// C#  
public string SourceColumn {get; set;}
```

**Property Value**

A string value that represents the source column name of the mapping.

**Remarks**

The `SourceColumn` and `SourceOrdinal` properties are mutually exclusive. The last value set takes precedence.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

**SourceOrdinal**

This property specifies the column ordinal value of the data source that is being mapped.

**Declaration**

```
// C#  
public int SourceOrdinal {get; set;}
```

**Property Value**

An integer value that represents the source column ordinal of the mapping.

**Exceptions**

`IndexOutOfRangeException` - The source ordinal is invalid.

**Remarks**

The `SourceOrdinal` and `SourceColumn` properties are mutually exclusive. The last value set takes precedence.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

---

## OracleBulkCopyColumnMappingCollection Class

The `OracleBulkCopyColumnMappingCollection` class represents a collection of `OracleBulkCopyColumnMapping` objects that are used to map columns in the data source to columns in a destination table.

### Class Inheritance

`System.Object`

`System.CollectionBase`

`System.OracleBulkCopyColumnMappingCollection`

### Declaration

```
// C#  
public sealed class OracleBulkCopyColumnMappingCollection : CollectionBase
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

Column mappings define the mapping between data source and the target table.

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

---

---

**Note:** Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

---

---

### Example

```
// C#
```

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)
- [OracleBulkCopyColumnMappingCollection Properties](#)
- [OracleBulkCopyColumnMappingCollection Public Methods](#)



## OracleBulkCopyColumnMappingCollection Members

OracleBulkCopyColumnMappingCollection members are listed in the following tables.

### OracleBulkCopyColumnMappingCollection Properties

The OracleBulkCopyColumnMappingCollection properties are listed in [Table 17-11](#).

**Table 17-11 OracleBulkCopyColumnMappingCollection Properties**

Property	Description
<a href="#">Item[index]</a>	Gets or sets the OracleBulkCopyColumnMappingCollection object at the specified index

### OracleBulkCopyColumnMappingCollection Public Methods

The OracleBulkCopyColumnMappingCollection public methods are listed in [Table 17-12](#).

**Table 17-12 OracleBulkCopyColumnMappingCollection Public Methods**

Public Method	Description
<a href="#">Add</a>	Adds objects to the collection
<a href="#">Clear</a>	Clears the contents of the collection
<a href="#">Contains</a>	Returns a value indicating whether or not a specified OracleBulkCopyColumnMapping object exists in the collection
<a href="#">CopyTo</a>	Copies the elements of the OracleBulkCopyColumnMappingCollection to an array of OracleBulkCopyColumnMapping items, starting at a specified index
<a href="#">IndexOf</a>	Returns the index of the specified OracleBulkCopyColumnMapping object
<a href="#">Insert</a>	Inserts a new OracleBulkCopyColumnMapping object in the collection, at the index specified.
<a href="#">Remove</a>	Removes the specified OracleBulkCopyColumnMapping element from the OracleBulkCopyColumnMappingCollection.
<a href="#">RemoveAt</a>	Removes the mapping from the collection at the specified index.

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMappingCollection Class](#)

## OracleBulkCopyColumnMappingCollection Properties

The `OracleBulkCopyColumnMappingCollection` properties are listed in [Table 17–13](#).

**Table 17–13 OracleBulkCopyColumnMappingCollection Properties**

Property	Description
<a href="#">Item[index]</a>	Gets or sets the <code>OracleBulkCopyColumnMappingCollection</code> object at the specified index

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

### Item[index]

This property gets or sets the `OracleBulkCopyColumnMapping` object at the specified index.

**Declaration**

```
// C#
public OracleBulkCopyColumnMapping this[int index] {get;set;}
```

**Parameters**

- *index*

The zero-based index of the `OracleBulkCopyColumnMapping` being set or retrieved.

**Property Value**

An `OracleBulkCopyColumnMapping` object at the specified index.

**Exceptions**

`IndexOutOfRangeException` - The specified index does not exist.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## OracleBulkCopyColumnMappingCollection Public Methods

The `OracleBulkCopyColumnMappingCollection` public methods are listed in [Table 17–14](#).

**Table 17–14 OracleBulkCopyColumnMappingCollection Public Methods**

Public Method	Description
<a href="#">Add</a>	Adds objects to the collection
<a href="#">Clear</a>	Clears the contents of the collection
<a href="#">Contains</a>	Returns a value indicating whether or not a specified <code>OracleBulkCopyColumnMapping</code> object exists in the collection
<a href="#">CopyTo</a>	Copies the elements of the <code>OracleBulkCopyColumnMappingCollection</code> to an array of <code>OracleBulkCopyColumnMapping</code> items, starting at a specified index
<a href="#">IndexOf</a>	Returns the index of the specified <code>OracleBulkCopyColumnMapping</code> object
<a href="#">Insert</a>	Inserts a new <code>OracleBulkCopyColumnMapping</code> object in the collection, at the index specified.
<a href="#">Remove</a>	Removes the specified <code>OracleBulkCopyColumnMapping</code> element from the <code>OracleBulkCopyColumnMappingCollection</code> .
<a href="#">RemoveAt</a>	Removes the mapping from the collection at the specified index.

### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## Add

Add methods add objects to the collection.

### Overload List:

- [Add\(OracleBulkCopyColumnMapping\)](#)  
This method adds the supplied `OracleBulkCopyColumnMapping` object to the collection.
- [Add\(int, int\)](#)  
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column ordinal positions.
- [Add\(int, string\)](#)  
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column ordinal and destination column name.
- [Add\(string, int\)](#)  
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column name and destination column ordinal.

- [Add\(string, string\)](#)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column names.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## Add(OracleBulkCopyColumnMapping)

This method adds the supplied `OracleBulkCopyColumnMapping` object to the collection.

**Declaration**

```
// C#  
public OracleBulkCopyColumnMapping Add(OracleBulkCopyColumnMapping  
    bulkCopyColumnMapping);
```

**Parameters**

- *bulkCopyColumnMapping*

The `OracleBulkCopyColumnMapping` object that describes the mapping to be added to the collection.

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

**See Also:**

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## Add(int, int)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column ordinal positions.

**Declaration**

```
// C#  
public OracleBulkCopyColumnMapping Add(int sourceColumnIndex,  
    int destinationColumnIndex);
```

**Parameters**

- *sourceColumnIndex*

The ordinal position of the source column within the data source.

- *destinationColumnIndex*

The ordinal position of the destination column within the destination table.

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

**Return Value**

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

**Remarks**

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

---

**Note:** Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

---

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

**Add(int, string)**

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column ordinal and destination column name.

**Declaration**

```
// C#
public OracleBulkCopyColumnMapping Add(int sourceColumnIndex,
    string destinationColumn);
```

**Parameters**

- *sourceColumnIndex*  
The ordinal position of the source column within the data source.
- *destinationColumn*  
The name of the destination column within the destination table.

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

**Return Value**

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

**Remarks**

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

---

---

**Note:** Oracle Data Provider for .NET makes one or more round trips to the database to determine the column names if the mapping is specified by ordinal resulting in a performance overhead. Therefore, it is recommended to specify the mapping by column names.

---

---

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

**Add(string, int)**

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column name and destination column ordinal.

**Declaration**

```
// C#  
public OracleBulkCopyColumnMapping Add(string sourceColumn,  
    int destinationColumnIndex);
```

**Parameters**

- *sourceColumn*  
The name of the source column within the data source.
- *destinationColumnIndex*  
The ordinal position of the destination column within the destination table.

**Return Value**

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

**Remarks**

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

---

---

**Note:** Oracle Data Provider for .NET makes one or more round trips to the database to determine the column names if the mapping is specified by ordinal resulting in a performance overhead. Therefore, it is recommended to specify the mapping by column names.

---

---

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## Add(string, string)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column names.

### Declaration

```
// C#  
public OracleBulkCopyColumnMapping Add(string sourceColumn,  
    string destinationColumn);
```

### Parameters

- *sourceColumn*  
The name of the source column within the data source.
- *destinationColumn*  
The name of the destination column within the destination table.

### Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

### Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

### Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

---

---

**Note:** Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

---

---

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## Clear

This method clears the contents of the collection.

**Declaration**

```
// C#  
public void Clear();
```

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

**Remarks**

The `Clear` method is most commonly used when an application uses a single `OracleBulkCopy` instance to process more than one bulk copy operation. If column mappings are created for one bulk copy operation, the `OracleBulkCopyColumnMappingCollection` must be cleared after the `WriteToServer` method invocation and before the next bulk copy is processed.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## Contains

This method returns a value indicating whether or not a specified `OracleBulkCopyColumnMapping` object exists in the collection.

**Declaration**

```
// C#  
public bool Contains(OracleBulkCopyColumnMapping value);
```

**Parameters**

- *value*  
A valid `OracleBulkCopyColumnMapping` object.

**Return Value**

Returns `true` if the specified mapping exists in the collection; otherwise, returns `false`.



**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## CopyTo

This method copies the elements of the `OracleBulkCopyColumnMappingCollection` to an array of `OracleBulkCopyColumnMapping` items, starting at a specified index.

**Declaration**

```
// C#  
public void CopyTo(OracleBulkCopyColumnMapping[] array, int index);
```

**Parameters**

- *array*  
The one-dimensional `OracleBulkCopyColumnMapping` array that is the destination for the elements copied from the `OracleBulkCopyColumnMappingCollection` object. The array must have zero-based indexing.
- *index*  
The zero-based array index at which copying begins.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## IndexOf

This method returns the index of the specified `OracleBulkCopyColumnMapping` object.

**Declaration**

```
// C#  
public int IndexOf(OracleBulkCopyColumnMapping value);
```

**Parameters**

- *value*  
The `OracleBulkCopyColumnMapping` object that is being returned.

**Return Value**

The zero-based index of the column mapping or -1 if the column mapping is not found in the collection.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

**Insert**

This method inserts a new `OracleBulkCopyColumnMapping` object in the collection, at the index specified.

**Declaration**

```
// C#  
public void Insert(int index, OracleBulkCopyColumnMapping value);
```

**Parameters**

- *index*  
The integer value of the location within the `OracleBulkCopyColumnMappingCollection` at which the new `OracleBulkCopyColumnMapping` is inserted.
- *value*  
The `OracleBulkCopyColumnMapping` object to be inserted in the collection.

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

**See Also:**

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

**Remove**

This method removes the specified `OracleBulkCopyColumnMapping` element from the `OracleBulkCopyColumnMappingCollection`.

**Declaration**

```
// C#  
public void Remove(OracleBulkCopyColumnMapping value);
```

**Parameters**

- *value*  
The `OracleBulkCopyColumnMapping` object to be removed from the collection.

**Exceptions**

`InvalidOperationException` - The bulk copy operation is in progress.

### Remarks

The `Remove` method is most commonly used when a single `OracleBulkCopy` instance processes more than one bulk copy operation. If column mappings are created for one bulk copy operation, mappings that no longer apply must be removed after the `WriteToServer` method invocation and before mappings are defined for the next bulk copy. The `Clear` method can clear the entire collection, and the `Remove` and the `RemoveAt` methods can remove mappings individually.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

## RemoveAt

This method removes the mapping from the collection at the specified index.

### Declaration

```
// C#  
public void RemoveAt(int index);
```

### Parameters

- *index*

The zero-based index of the `OracleBulkCopyColumnMapping` object to be removed from the collection.

### Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

### Remarks

The `RemoveAt` method is most commonly used when a single `OracleBulkCopy` instance is used to process more than one bulk copy operation. If column mappings are created for one bulk copy operation, mappings that no longer apply must be removed after the `WriteToServer` method invocation and before the mappings for the next bulk copy are defined. The `Clear` method can clear the entire collection, and the `Remove` and the `RemoveAt` methods can remove mappings individually.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

---

## OracleBulkCopyOptions Enumeration

The `OracleBulkCopyOptions` enumeration specifies the values that can be combined with an instance of the `OracleBulkCopy` class and used as options to determine its behavior and the behavior of the `WriteToServer` methods for that instance.

[Table 17-15](#) lists all the `OracleBulkCopyOptions` enumeration values with a description of each enumerated value.

**Table 17-15** *OracleBulkCopyOptions Enumeration Members*

Member Name	Description
Default	Indicates that the default value for all options are to be used
UseInternalTransaction	Indicates that each batch of the bulk copy operation occurs within a transaction. If the connection used to perform the bulk copy operation is already part of a transaction, an <code>InvalidOperationException</code> exception is raised.  If this member is not specified, <code>BatchSize</code> number of rows are sent to the database, without any transaction-related activity.

---

---

**Note:** All bulk copy operations are agnostic of any local or distributed transaction created by the application.

---

---

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- `OracleBulkCopy` ["BulkCopyOptions"](#) on page 17-10

---

## OracleRowsCopiedEventHandler Delegate

The `OracleRowsCopiedEventHandler` delegate represents the method that handles the `OracleRowsCopied` event of an `OracleBulkCopy` object.

### Declaration

```
// C#  
public delegate void OracleRowsCopiedEventHandler (object sender,  
    OracleRowsCopiedEventArgs eventArgs);
```

### Parameters

- *sender*  
The source of the event.
- *eventArgs*  
The `OracleRowsCopiedEventArgs` object that contains the event data.

### Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified every time the number of rows specified by the `OracleBulkCopy.NotifyAfter` property has been processed.

If the event handler calls the `OracleBulkCopy.Close` method, an exception is generated, and the `OracleBulkCopy` object state does not change.

The event handler can also set the `OracleRowsCopiedEventArgs.Abort` property to `true` to indicate that the bulk copy operation must be aborted. If the bulk copy operation is part of an external transaction, an exception is generated and the transaction is not rolled back. The application is responsible for either committing or rolling back the external transaction.

If there is no external transaction, the internal transaction for the current batch of rows is automatically rolled back. However the previous batches of imported rows are unaffected, as their transactions have already been committed.

### Requirements

Namespace: `Oracle.DataAccess.Client`

Assembly: `Oracle.DataAccess.dll`

Microsoft .NET Framework Version: 2.0 or later

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- ["OracleRowsCopied"](#) on page 20
- ["NotifyAfter"](#) on page 17-13

## OracleRowsCopiedEventArgs Class

The `OracleRowsCopiedEventArgs` class represents the set of arguments passed as part of event data for the `OracleRowsCopied` event.

### Class Inheritance

`System.Object`

`System.EventArgs`

`System.OracleRowsCopiedEventArgs`

### Declaration

```
// C#  
public class OracleRowsCopiedEventArgs : EventArgs
```

### Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

### Remarks

Each time the number of rows represented by the `OracleBulkCopy.NotifyAfter` property is processed, the `OracleBulkCopy.OracleRowsCopied` event is raised, providing an `OracleRowsCopiedEventArgs` object that stores the event data.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowsCopiedEventArgs Members](#)
- [OracleRowsCopiedEventArgs Constructors](#)
- [OracleRowsCopiedEventArgs Properties](#)

## OracleRowsCopiedEventArgs Members

OracleRowsCopiedEventArgs members are listed in the following tables.

### OracleRowsCopiedEventArgs Constructors

OracleRowsCopiedEventArgs constructors are listed in [Table 17-16](#).

**Table 17-16 OracleRowsCopiedEventArgs Constructors**

Constructor	Description
<a href="#">OracleRowsCopiedEventArgs Constructors</a>	OracleRowsCopiedEventArgs creates new instances of the OracleRowsCopiedEventArgs class

### OracleRowsCopiedEventArgs Properties

OracleRowsCopiedEventArgs properties are listed in [Table 17-17](#).

**Table 17-17 OracleRowsCopiedEventArgs Properties**

Property	Description
<a href="#">Abort</a>	Retrieves or sets a value that indicates whether or not the bulk copy operation is aborted
<a href="#">RowsCopied</a>	Retrieves a value that represents the number of rows copied during the current bulk copy operation

#### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowsCopiedEventArgs Class](#)

## OracleRowsCopiedEventArgs Constructors

OracleRowsCopiedEventArgs creates new instances of the OracleRowsCopiedEventArgs class.

### Overload List:

- [OracleRowsCopiedEventArgs\(long\)](#)

This constructor creates a new instance of the OracleRowsCopiedEventArgs object.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

### OracleRowsCopiedEventArgs(long)

This constructor creates a new instance of the OracleRowsCopiedEventArgs object.

#### Declaration

```
// C#  
public OracleRowsCopiedEventArgs(long rowsCopied);
```

#### Parameters

- *rowsCopied*

An Int64 value that indicates the number of rows copied during the current bulk copy operation.

#### Remarks

The value in the *rowsCopied* parameter is reset by each call to a WriteToServer method.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)



## OracleRowsCopiedEventArgs Properties

OracleRowsCopiedEventArgs properties are listed in [Table 17–18](#).

**Table 17–18 OracleRowsCopiedEventArgs Properties**

Property	Description
<a href="#">Abort</a>	Retrieves or sets a value that indicates whether or not the bulk copy operation is aborted
<a href="#">RowsCopied</a>	Retrieves a value that represents the number of rows copied during the current bulk copy operation

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

### Abort

This property retrieves or sets a value that indicates whether or not the bulk copy operation is aborted.

#### Declaration

```
// C#
public bool Abort{get; set;}
```

#### Property Value

Returns `true` if the bulk copy operation is to be aborted; otherwise, returns `false`.

#### Remarks

Set the `Abort` property to `true` to cancel the bulk copy operation.

If the `Close` method is called from `OracleRowsCopied`, an exception is generated, and the `OracleBulkCopy` object state does not change.

If the application does not create a transaction, the internal transaction corresponding to the current batch is automatically rolled back. However, changes related to previous batches within the bulk copy operation are retained, because the transactions in those batches are committed. This case is applicable only when `UseInternalTransaction` bulk copy option is chosen.

### See Also:

- ["Oracle.DataAccess.Client Namespace"](#) on page 1-4
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

### RowsCopied

This property retrieves a value that represents the number of rows copied during the current bulk copy operation.

### Declaration

```
// C#  
public long RowsCopied {get;}
```

### Property Value

An `Int64` value that returns the number of rows copied.

### Remarks

The value in the `RowsCopied` property is reset by each call to a `WriteToServer` method.

#### See Also:

- ["Oracle.DataAccess.Client Namespace" on page 1-4](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

---



---

## Oracle Schema Collections

ODP.NET provides standard metadata collections as well as various Oracle database-specific metadata collections that can be retrieved through the `OracleConnection.GetSchema` API.

**See Also:**

- ["Support for Schema Discovery"](#) on page 3-21
- ["GetSchema"](#) on page 5-99

This appendix contains the following topics:

- [Common Schema Collections](#)
- [ODP.NET-Specific Schema Collection](#)

### Common Schema Collections

The common schema collections are available for all .NET Framework managed providers. ODP.NET supports the same common schema collections.

**See Also:** "Understanding the Common Schema Collections" in the MSDN Library

- [MetaDataCollections](#)
- [DataSourceInformation](#)
- [DataTypes](#)
- [Restrictions](#)
- [ReservedWords](#)

### MetaDataCollections

[Table A-1](#) is a list of metadata collections that is available from the data source, such as tables, columns, indexes, and stored procedures.

**Table A-1** *MetaDataCollections*

Column Name	Data Type	Description
CollectionName	string	The name of the collection passed to the <code>GetSchema</code> method for retrieval.

**Table A-1 (Cont.) MetaDataCollections**

Column Name	Data Type	Description
NumberOfRestrictions	int	Number of restrictions specified for the named collection.
NumberOfIdentifierParts	int	Number of parts in the composite identifier/database object name.

## DataSourceInformation

[Table A-2](#) lists `DataSourceInformation` information which may include these columns and possibly others.

**Table A-2 DataSourceInformation**

Columns	Data Type	Description
CompositeIdentifierSeparatorPattern	string	Separator for multipart names: @   \ .
DataSourceProductName	string	Database name: Oracle
DataSourceProductVersion	string	Database version. Note that this is the version of the database instance currently being accessed by <code>DbConnection</code> .
DataSourceProductVersionNormalized	string	A normalized <code>DataSource</code> version for easier comparison between different versions. For example: DataSource Version: 10.2.0.1.0 Normalized DataSource Version: 10.02.00.01.00
GroupByBehavior	GroupByBehavior	An enumeration that indicates the relationship between the columns in a <code>GROUP BY</code> clause and the non-aggregated columns in a select list.
IdentifierPattern	string	Format for a valid identifier.
IdentifierCase	IdentifierCase	An enumeration that specifies whether or not to treat non-quoted identifiers as case sensitive.
OrderByColumnsInSelect	bool	A boolean that indicates whether or not the select list must contain the columns in an <code>ORDER BY</code> clause.
ParameterMarkerFormat	string	A string indicating whether or not parameter markers begin with a special character.
ParameterMarkerPattern	string	The format of a parameter marker.
ParameterNameMaxLength	int	Maximum length of a parameter.
ParameterNamePattern	string	The format for a valid parameter name.
QuotedIdentifierPattern	string	The format of a quoted identifier.
QuotedIdentifierCase	IdentifierCase	An enumeration that specifies whether or not to treat quote identifiers as case sensitive.
StringLiteralPattern	string	The format for a string literal.
SupportedJoinOperators	SupportedJoinOperators	An enumeration indicating the types of SQL join statements supported by the data source.

## DataTypes

Table A-3 lists DataTypes Collection information which may include these columns and possibly others.

**Note:** As an example, the description column includes complete information for the `TIMESTAMP WITH LOCAL TIME ZONE` data type.

**Table A-3** *DataTypes*

ColumnName	Data Type	Description
TypeName	string	The provider-specific data type name. Example: <code>TIMESTAMP WITH LOCAL TIME ZONE</code>
ProviderDbType	int	The provider-specific type value. Example: 124
ColumnSize	long	The length of a non-numeric column or parameter. Example: 27
CreateFormat	string	A format string that indicates how to add this column to a DDL statement. Example: <code>TIMESTAMP ( {0} WITH LOCAL TIME ZONE)</code>
CreateParameters	string	The parameters specified to create a column of this data type. Example: 8
DataType	string	The .NET type for the data type. Example: <code>System.DateTime</code>
IsAutoIncrementable	bool	A boolean value that indicates whether or not this data type can be auto-incremented. Example: <code>false</code>
IsBestMatch	bool	A boolean value that indicates whether or not this data type is the best match to values in the <code>DataType</code> column. Example: <code>false</code>
IsCaseSensitive	bool	A boolean value that indicates whether or not this data type is case-sensitive. Example: <code>false</code>
IsFixedLength	bool	A boolean value that indicates whether or not this data type has a fixed length. Example: <code>true</code>
IsFixedPrecisionScale	bool	A boolean value that indicates whether or not this data type has a fixed precision and scale. Example: <code>false</code>
IsLong	bool	A boolean value that indicates whether or not this data type contains very long data. Example: <code>false</code>

**Table A-3 (Cont.) DataTypes**

ColumnName	Data Type	Description
IsNullable	bool	A boolean value that indicates whether or not this data type is nullable. Example: true
IsSearchable	bool	A boolean value that indicates whether or not the data type can be used in a WHERE clause with any operator, except the LIKE predicate. Example: true
IsSearchableWithLike	bool	A boolean value that indicates whether or not this data type can be used with the LIKE predicate. Example: false
IsUnsigned	bool	A boolean value that indicates whether or not the data type is unsigned.
MaximumScale	short	The maximum number of digits allowed to the right of the decimal point.
MinimumScale	short	The minimum number of digits allowed to the right of the decimal point.
IsConcurrencyType	bool	A boolean value that indicates whether or not the database updates the data type every time the row is changed and the value of the column differs from all previous values. Example: false
MinimumVersion	String	The earliest version of the database that can be used. Example: 09.00.00.00.00
IsLiteralSupported	bool	A boolean value that indicates whether or not the data type can be expressed as a literal. Example: true
LiteralPrefix	string	The prefix of a specified literal. Example: TO_TIMESTAMP_TZ ( '
LiteralSuffix	string	The suffix of a specified literal. Example: ' , ' YYYY-MM-DD HH24:MI:SS.FF ' )

## Restrictions

[Table A-4](#) lists Restrictions, including the following columns.

**Table A-4 Restrictions**

ColumnName	Data Type	Description
CollectionName	string	The collection that the restrictions apply to.
RestrictionName	string	The restriction name.
RestrictionNumber	int	A number that indicates the location of the restriction.

## ReservedWords

The `ReservedWords` collection exposes information about the words that are reserved by the database currently connected to ODP.NET.

[Table A-5](#) lists the `ReservedWords` Collection.

**Table A-5** *ReservedWords*

ColumnName	Data Type	Description
ReservedWord	string	Provider-specific reserved words

## ODP.NET-Specific Schema Collection

Oracle Data Provider for .NET supports both the common schema collections described previously and the following Oracle-specific schema collections:

- [Tables](#)
- [Columns](#)
- [Views](#)
- [XMLSchema](#)
- [Users](#)
- [Synonyms](#)
- [Sequences](#)
- [Functions](#)
- [Procedures](#)
- [ProcedureParameters](#)
- [Arguments](#)
- [Packages](#)
- [PackageBodies](#)
- [JavaClasses](#)
- [Indexes](#)
- [IndexColumns](#)
- [PrimaryKeys](#)
- [ForeignKeys](#)
- [ForeignKeyColumns](#)
- [UniqueKeys](#)

## Tables

[Table A-6](#) lists the column name, data type, and description of the `Tables` Schema Collection.

**Table A-6** *Tables*

Column Name	Data Type	Description
OWNER	String	Owner of the Table.

**Table A-6 (Cont.) Tables**

Column Name	Data Type	Description
TABLE_NAME	String	Name of the Table.
TYPE	String	Type of Table, for example, System or User.

## Columns

[Table A-7](#) lists the column name, data type, and description of the Columns Schema Collection .

**Table A-7 Columns**

ColumnName	Data Type	Description
OWNER	String	Owner of the table or view.
TABLE_NAME	String	Name of the table or view.
COLUMN_NAME	String	Name of the column.
ID	Decimal	Sequence number of the column as created.
DATATYPE	String	Data type of the column.
LENGTH	Decimal	Length of the column in bytes.
PRECISION	Decimal	Decimal precision for NUMBER data type; binary precision for FLOAT data type, null for all other data types.
Scale	Decimal	Digits to right of decimal point in a number.
NULLABLE	String	Specifies whether or not a column allows NULLS.
CHAR_USED	String	Indicates whether the column uses BYTE length semantics (B) or CHAR length semantics (C).
LengthInChars	Decimal	Length of the column in characters.  This value only applies to CHAR, VARCHAR2, NCHAR, and NVARCHAR2.

## Views

[Table A-8](#) lists the column name, data type, and description of the Views Schema Collection.

**Table A-8 Views**

Column Name	Data Type	Description
OWNER	String	Owner of the view.
VIEW_NAME	String	Name of the view.
TEXT_LENGTH	Decimal	Length of the view text.
TEXT	String	View text.
TYPE_TEXT_LENGTH	Decimal	Length of the type clause of the typed view.
TYPE_TEXT	String	Type clause of the typed view.
OID_TEXT_LENGTH	Decimal	Length of the WITH OID clause of the typed view.
OID_TEXT	String	WITH OID clause of the typed view.
VIEW_TYPE_OWNER	String	Owner of the view type if the view is a typed view.



**Table A-8 (Cont.) Views**

Column Name	Data Type	Description
VIEW_TYPE	String	Type of the view if the view is a typed view.
SUPERVIEW_NAME	String	Name of the superview. (Oracle9i or later)

## XMLSchema

[Table A-9](#) lists the column name, data type and description of the XMLSchema Schema Collection.

---

**Note:** This collection is only available with Oracle Database 10g and later.

---

**Table A-9 XMLSchema**

Column Name	Data Type	Description
OWNER	String	Owner of the XML schema.
SCHEMA_URL	String	Schema URL of the XML schema.
LOCAL	String	Indicates whether the XML schema is local (YES) or global (NO).
SCHEMA	String	XML schema document.
INT_OBJNAME	String	Internal database object name for the schema.
QUAL_SCHEMA_URL	String	Fully qualified schema URL.
HIER_TYPE	String	Hierarchy type for the schema.

## Users

[Table A-10](#) lists the column name, data type and description of the Users Schema Collection.

**Table A-10 Users**

Column Name	Data Type	Description
NAME	String	Name of the user.
ID	Decimal	ID number of the user.
CREATEDATE	DateTime	User creation date.

## Synonyms

[Table A-11](#) lists the column name, data type and description of the Synonyms Schema Collection.

**Table A-11 Synonyms**

Column Name	Data Type	Description
OWNER	String	Owner of the synonym.
SYNONYM_NAME	String	Name of the synonym.

**Table A–11 (Cont.) Synonyms**

Column Name	Data Type	Description
TABLE_OWNER	String	Owner of the object referenced by the synonym. Although the column is called TABLE_OWNER, the object owned is not necessarily a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
TABLE_NAME	String	Name of the object referenced by the synonym. Although the column is called TABLE_NAME, the object does not necessarily have to be a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
DB_LINK	String	Name of the database link referenced, if any.

## Sequences

Table A–12 lists the column name, data type, and description of the Sequences Schema Collection.

**Table A–12 Sequences**

Column Name	Data Type	Description
SEQUENCE_OWNER	String	Name of the owner of the sequence.
SEQUENCE_NAME	String	Sequence name.
MIN_VALUE	Decimal	Minimum value of the sequence.
MAX_VALUE	Decimal	Maximum value of the sequence.
INCREMENT_BY	Decimal	Value by which sequence is incremented.
CYCLE_FLAG	String	Indicates if sequence wraps around on reaching limit.
ORDER_FLAG	String	Indicates if sequence numbers are generated in order.
CACHE_SIZE	Decimal	Number of sequence numbers to cache.
LAST_NUMBER	Decimal	Last sequence number written to disk. If a sequence uses caching, the number written to disk is the last number placed in the sequence cache. This number is likely to be greater than the last sequence number that was used.

## Functions

Table A–13 lists the column name, data type, and description of the Functions Schema Collection.

**Table A–13 Functions**

Column Name	Data Type	Description
OWNER	String	Owner of the function.
OBJECT_NAME	String	Name of the function.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the function.

**Table A-13 (Cont.) Functions**

Column Name	Data Type	Description
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the function.
CREATED	DateTime	Timestamp for the creation of the function.
LAST_DDL_TIME	DateTime	Timestamp for the last modification of the function resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the function (character data).
STATUS	String	Status of the function (VALID, INVALID, or N/A).
TEMPORARY	String	Whether or not the function is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this function is system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y   N).

## Procedures

Table A-14 lists the column name, data type, and description of the Procedures Schema Collection.

**Table A-14 Procedures**

Column Name	Data Type	Description
OWNER	String	Owner of the procedure.
OBJECT_NAME	String	Name of the procedure.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the procedure.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the procedure.
CREATED	DateTime	Timestamp for the creation of the procedure.
LAST_DDL_TIME	Decimal	Timestamp for the last modification of the procedure resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the procedure (character data).
STATUS	String	Status of the procedure (VALID, INVALID, or N/A).
TEMPORARY	String	Whether or not the procedure is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this procedure is system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y   N).

## ProcedureParameters

[Table A–15](#) lists the column name, data type and description of the ProcedureParameters Schema Collection.

**Table A–15 ProcedureParameters**

Column Name	Data Type	Description
OWNER	String	Owner of the object.
OBJECT_NAME	String	Name of the procedure or function.
PACKAGE_NAME	String	Name of the package.
OBJECT_ID	Decimal	Object number of the object.
OVERLOAD	String	Indicates the <i>n</i> th overloading ordered by its appearance in the source; otherwise, it is NULL.
SUBPROGRAM_ID	Decimal	Subprogram id for the procedure or function
ARGUMENT_NAME	String	If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return value.
POSITION	Decimal	If DATA_LEVEL is zero, then this column holds the position of this item in the argument list, or zero for a function return value.
SEQUENCE	Decimal	Defines the sequential order of the argument. Argument sequence starts from 1.
DATA_LEVEL	Decimal	Nesting depth of the argument for composite types.
DATA_TYPE	String	Data type of the argument.
DEFAULT_VALUE	String	Default value for the argument.
DEFAULT_LENGTH	Decimal	Length of the default value for the argument.
IN_OUT	String	Direction of the argument: [IN] [OUT] [IN/OUT].
DATA_LENGTH	Decimal	Length of the column (in bytes).
DATA_PRECISION	Decimal	Length in decimal digits (NUMBER) or binary digits (FLOAT).
DATA_SCALE	Decimal	Digits to the right of the decimal point in a number.
RADIX	Decimal	Argument radix for a number.
CHARACTER_SET_NAME	String	Character set name for the argument.
TYPE_OWNER	String	Owner of the type of the argument.
TYPE_NAME	String	Name of the type of the argument. If the type is a package local type (that is, it is declared in a package specification), then this column displays the name of the package.
TYPE_SUBNAME	String	Displays the name of the type declared in the package identified in the TYPE_NAME column. Relevant only for package local types.
TYPE_LINK	String	Displays the database link that refers to the remote package.  Relevant only for package local types when the package identified in the TYPE_NAME column is a remote package.

**Table A–15 (Cont.) ProcedureParameters**

Column Name	Data Type	Description
PLS_TYPE	String	For numeric arguments, the name of the PL/SQL type of the argument. Otherwise, Null.
CHAR_LENGTH	Decimal	Character limit for string data types.
CHAR_USED	String	Indicates whether the byte limit (B) or character limit (C) is official for the string.

## Arguments

Table A–16 lists the column name, data type, and description of the Arguments Schema Collection.

**Table A–16 Arguments**

Column Name	Data Type	Description
OWNER	String	Owner of the object.
PACKAGE_NAME	String	Name of the package.
OBJECT_NAME	String	Name of the procedure or function.
ARGUMENT_NAME	String	If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return value.
POSITION	Decimal	If DATA_LEVEL is zero, then this column holds the position of this item in the argument list, or zero for a function return value.
SEQUENCE	Decimal	Defines the sequential order of the argument. Argument sequence starts from 1.
DEFAULT_VALUE	String	Default value for the argument.
DEFAULT_LENGTH	Decimal	Length of the default value for the argument.
IN_OUT	String	Direction of the argument: [IN] [OUT] [IN/OUT].
DATA_LENGTH	Decimal	Length of the column (in bytes).
DATA_PRECISION	Decimal	Length in decimal digits (NUMBER) or binary digits (FLOAT).
DATA_SCALE	Decimal	Digits to the right of the decimal point in a number.
DATA_TYPE	String	Data type of the argument.
CHAR_USED	String	Indicates whether the column uses BYTE length semantics (B) or CHAR length semantics (C).

## Packages

Table A–17 lists the column name, data type, and description of the Packages Schema Collection.

**Table A–17 Packages**

Column Name	Data Type	Description
OWNER	String	Owner of the package.
OBJECT_NAME	String	Name of the package.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).

**Table A–17 (Cont.) Packages**

Column Name	Data Type	Description
OBJECT_ID	Decimal	Dictionary object number of the package.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the package.
CREATED	DateTime	Timestamp for the creation of the package.
LAST_DDL_TIME	DateTime	Timestamp for the last modification of the package resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the package (character data).
STATUS	String	Status of the package (VALID, INVALID, or N/A).
TEMPORARY	String	Whether or not the package is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this package was system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y   N).

## PackageBodies

[Table A–18](#) lists the column name, data type, and description of the PackageBodies Schema Collection.

**Table A–18 PackageBodies**

Column Name	Data Type	Description
OWNER	String	Owner of the package body.
OBJECT_NAME	String	Name of the package body.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the package body.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the package body.
CREATED	DateTime	Timestamp for the creation of the package body.
LAST_DDL_TIME	DateTime	Timestamp for the last modification of the package body resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the package body (character data).
STATUS	String	Status of the package body (VALID, INVALID, or N/A).
TEMPORARY	String	Whether the package body is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this package body is system generated (Y) or not (N).

**Table A–18 (Cont.) PackageBodies**

Column Name	Data Type	Description
SECONDARY	String	Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y   N).

## JavaClasses

[Table A–19](#) lists the column name, data type, and description of the JavaClasses Schema Collection.

**Table A–19 JavaClasses**

Column Name	Data Type	Description
OWNER	String	Owner of the Java class.
NAME	String	Name of the Java class.
MAJOR	Decimal	Major version number of the Java class, as defined in the JVM specification.
MINOR	Decimal	Minor version number of the Java class, as defined in the JVM specification.
KIND	String	Indicates whether the stored object is a Java class (CLASS) or a Java interface (INTERFACE).
ACCESSIBILITY	String	Accessibility of the Java class.
IS_INNER	String	Indicates whether this Java class is an inner class (YES) or not (NO).
IS_ABSTRACT	String	Indicates whether this Java class is an abstract class (YES) or not (NO).
IS_FINAL	String	Indicates whether this Java class is a final class (YES) or not (NO).
IS_DEBUG	String	Indicates whether this Java class contains debug information (YES) or not (NO).
SOURCE	String	Source designation of the Java class.
SUPER	String	Super class of this Java class.
OUTER	String	Outer class of this Java class if this Java class is an inner class.

## Indexes

[Table A–20](#) lists the column name, data type, and description of the Indexes Schema Collection.

**Table A–20 Indexes**

Column Name	Data Type	Description
OWNER	String	Owner of the index.
INDEX_NAME	String	Name of the index.

**Table A–20 (Cont.) Indexes**

Column Name	Data Type	Description
INDEX_TYPE	String	Type of the index: <ul style="list-style-type: none"> <li>■ NORMAL</li> <li>■ BITMAP</li> <li>■ FUNCTION-BASED NORMAL</li> <li>■ FUNCTION-BASED BITMAP</li> <li>■ DOMAIN</li> </ul>
TABLE_OWNER	String	Owner of the indexed object.
TABLE_NAME	String	Name of the indexed object.
TABLE_TYPE	String	Type of the indexed object (for example, TABLE or CLUSTER).
UNIQUENESS	String	Indicates whether the index is UNIQUE or NONUNIQUE.
COMPRESSION	String	Indicates whether index compression is enabled (ENABLED) or not (DISABLED).
PREFIX_LENGTH	Decimal	Number of columns in the prefix of the compression key.
TABLESPACE_NAME	String	Name of the tablespace containing the index.
INI_TRANS	Decimal	Initial number of transactions.
MAX_TRANS	Decimal	Maximum number of transactions.
INITIAL_EXTENT	Decimal	Size of the initial extent.
NEXT_EXTENT	Decimal	Size of secondary extents.
MIN_EXTENTS	Decimal	Minimum number of extents allowed in the segment.
MAX_EXTENTS	Decimal	Maximum number of extents allowed in the segment.
PCT_INCREASE	Decimal	Percentage increase in extent size.
PCT_THRESHOLD	Decimal	Threshold percentage of block space allowed per index entry.
INCLUDE_COLUMN	Decimal	Column ID of the last column to be included in index-organized table primary key (non-overflow) index. This column maps to the COLUMN_ID column of the *_TAB_COLUMNS data dictionary views.
FREELISTS	Decimal	Number of process freelists allocated to this segment.
FREELIST_GROUPS	Decimal	Number of freelist groups allocated to this segment.
PCT_FREE	Decimal	Minimum percentage of free space in a block.
LOGGING	String	Logging information.
BLEVEL	Decimal	B*-Tree level: depth of the index from its root block to its leaf blocks. A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS	Decimal	Number of leaf blocks in the index.



**Table A-20 (Cont.) Indexes**

<b>Column Name</b>	<b>Data Type</b>	<b>Description</b>
DISTINCT_KEYS	Decimal	Number of distinct indexed values. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is the same as the number of rows in the table (USER_TABLES.NUM_ROWS).
AVG_LEAF_BLOCKS_ PER_KEY	Decimal	Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_ PER_KEY	Decimal	Average number of data blocks in the table that are pointed to by a distinct value in the index, rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.
CLUSTERING_ FACTOR	Decimal	Indicates the amount of order of the rows in the table based on the values of the index.
STATUS	String	Indicates whether a nonpartitioned index is VALID or UNUSABLE.
NUM_ROWS	Decimal	Number of rows in the index.
SAMPLE_SIZE	Decimal	Size of the sample used to analyze the index.
LAST_ANALYZED	Date	Date on which this index was most recently analyzed.
DEGREE	String	Number of threads per instance for scanning the index.
INSTANCES	String	Number of instances across which the indexes to be scanned.
PARTITIONED	String	Indicates whether the index is partitioned (YES) or not (NO).
TEMPORARY	String	Indicates whether or not the index is on a temporary table.
GENERATED	String	Indicates whether the name of the index is system generated (Y) or not (N).
SECONDARY	String	Indicates whether the index is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N).
BUFFER_POOL	String	Name of the default buffer pool to be used for the index blocks.
USER_STATS	String	Indicates whether statistics were entered directly by the user (YES) or not (NO).
DURATION	String	Indicates the duration of a temporary table.
PCT_DIRECT_ ACCESS	Decimal	For a secondary index on an index-organized table, the percentage of rows with VALID guess.
ITYP_OWNER	String	For a domain index, the owner of the index type.
ITYP_NAME	String	For a domain index, the name of the index type.
PARAMETERS	String	For a domain index, the parameter string.
GLOBAL_STATS	String	For partitioned indexes, indicates whether statistics are collected by analyzing the index as a whole (YES) or estimated from statistics on underlying index partitions and subpartitions (NO).

**Table A–20 (Cont.) Indexes**

Column Name	Data Type	Description
DOMIDX_STATUS	String	Status of the domain index: <ul style="list-style-type: none"> <li>■ NULL - Index is not a domain index.</li> <li>■ VALID - Index is a valid domain index.</li> <li>■ IDX_TYP_INVLD - Indextype of the domain index is invalid.</li> </ul>
DOMIDX_OPSTATUS	String	Status of the operation on the domain index: <ul style="list-style-type: none"> <li>■ NULL - Index is not a domain index.</li> <li>■ VALID - Operation performed without errors.</li> <li>■ FAILED - Operation failed with an error.</li> </ul>
FUNCIDX_STATUS	String	Status of a function-based index: <ul style="list-style-type: none"> <li>■ NULL - Index is not a function-based index.</li> <li>■ ENABLED - Function-based index is enabled.</li> <li>■ DISABLED - Function-based index is disabled.</li> </ul>
JOIN_INDEX	String	Indicates whether the index is a join index (YES) or not (NO).
IOT_REDUNDANT_PKEY_ELIM	String	Indicates whether redundant primary key columns are eliminated from secondary indexes on index-organized tables (YES) or not (NO).
DROPPED	String	Indicates whether the index has been dropped and is in the recycle bin (YES) or not (NO); null for partitioned tables.

## IndexColumns

[Table A–21](#) lists the column name, data type, and description of the IndexColumns Schema Collection.

**Table A–21 IndexColumns**

Column Name	Data Type	Description
INDEX_OWNER	String	Owner of the index.
INDEX_NAME	String	Name of the index.
TABLE_OWNER	String	Owner of the table or cluster.
TABLE_NAME	String	Name of the table or cluster.
COLUMN_NAME	String	Column name or attribute of object type column.
COLUMN_POSITION	Decimal	Position of column or attribute within the index.
COLUMN_LENGTH	Decimal	Indexed length of the column.
DESCEND	String	Whether the column is sorted in descending order (Y/N).
CHAR_LENGTH	Decimal	Maximum codepoint length of the column. (Oracle9i or later)

## PrimaryKeys

[Table A–22](#) lists the column name, data type, and description of the PrimaryKeys Schema Collection.

**Table A-22 PrimaryKeys**

Column Name	Data Type	Description
OWNER	String	Owner of the constraint definition.
CONSTRAINT_NAME	String	Name of the constraint definition.
TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
SEARCH_CONDITION	String	Text of search condition for a check constraint.
R_OWNER	String	Owner of table referred to in a referential constraint.
R_CONSTRAINT_NAME	String	Name of the unique constraint definition for referenced table.
DELETE_RULE	String	Delete rule for a referential constraint (CASCADE or NO ACTION).
STATUS	String	Enforcement status of constraint (ENABLED or DISABLED).
DEFERRABLE	String	Whether or not the constraint is deferrable.
VALIDATED	String	Whether all data obeys the constraint (VALIDATED or NOT VALIDATED).
GENERATED	String	Whether the name of the constraint is user or system generated.
BAD	String	Indicates that this constraint specifies a century in an ambiguous manner. (Yes   No)  To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year.
RELY	String	Whether an enabled constraint is enforced or unenforced.
LAST_CHANGE	DateTime	When the constraint was last enabled or disabled.
INDEX_OWNER	String	Name of the user owning the index. (Oracle9i or later)
INDEX_NAME	String	Name of the index (only shown for unique and primary-key constraints). (Oracle9i or later)

## ForeignKeys

Table A-23 lists the column name, data type, and description of the ForeignKeys Schema Collection.

**Table A-23 ForeignKeys**

Column Name	Data Type	Description
PRIMARY_KEY_CONSTRAINT_NAME	String	Name of the constraint definition.
PRIMARY_KEY_OWNER	String	Owner of the constraint definition.
PRIMARY_KEY_TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
FOREIGN_KEY_OWNER	String	Owner of the constraint definition.

**Table A-23 (Cont.) ForeignKeys**

Column Name	Data Type	Description
FOREIGN_KEY_ CONSTRAINT_NAME	String	Name of the constraint definition.
FOREIGN_KEY_ TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
SEARCH_CONDITION	String	Text of search condition for a check constraint
R_OWNER	String	Owner of table referred to, in a referential constraint.
R_CONSTRAINT_NAME	String	Name of the unique constraint definition for referenced table.
DELETE_RULE	String	Delete rule for a referential constraint (CASCADE or NO ACTION).
STATUS	String	Enforcement status of constraint (ENABLED or DISABLED).
VALIDATED	String	Whether or not all data obeys the constraint (VALIDATED or NOT VALIDATED).
GENERATED	String	Whether the name of the constraint is user or system generated.
RELY	String	Whether an enabled constraint is enforced or unenforced.
LAST_CHANGE	DateTime	When the constraint was last enabled or disabled.
INDEX_OWNER	String	Name of the user owning the index. (Oracle9i or later)
INDEX_NAME	String	Name of the index. (Oracle9i or later)

## ForeignKeyColumns

[Table A-24](#) lists the column name, data type, and description of the ForeignKeyColumns Schema Collection.

**Table A-24 ForeignKeyColumns**

Column Name	Data Type	Description
OWNER	String	Owner of the constraint definition.
CONSTRAINT_NAME	String	Name of the constraint definition.
TABLE_NAME	String	Name of the table with constraint definition.
COLUMN_NAME	String	Name of the column or attribute of the object type column specified in the constraint definition.
POSITION	String	Original position of column or attribute in the definition of the object.

## UniqueKeys

[Table A-25](#) lists the column name, data type, and description of the UniqueKeys Schema Collection.

**Table A-25 UniqueKeys**

Column Name	Data Type	Description
OWNER	String	Owner of the constraint definition.
CONSTRAINT_NAME	String	Name of the constraint definition.
TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
SEARCH_CONDITION	String	Text of search condition for a check constraint.
R_OWNER	String	Owner of table referred to in a referential constraint.
R_CONSTRAINT_NAME	String	Name of the unique constraint definition for referenced table.
DELETE_RULE	String	Delete rule for a referential constraint (CASCADE or NO ACTION).
STATUS	String	Enforcement status of constraint (ENABLED or DISABLED).
DEFERRABLE	String	Whether or not the constraint is deferrable.
VALIDATED	String	Whether all data obeys the constraint (VALIDATED or NOT VALIDATED).
GENERATED	String	Whether the name of the constraint is user or system generated.
BAD	String	Indicates that this constraint specifies a century in an ambiguous manner. (Yes   No)  To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year.
RELY	String	Whether an enabled constraint is enforced or not.
LAST_CHANGE	String	When the constraint was last enabled or disabled.
INDEX_OWNER	String	Name of the user owning the index. (Oracle9i or later)
INDEX_NAME	String	Name of the index (only shown for unique and primary-key constraints). (Oracle9i or later)



---

---

# Glossary

## **assembly**

Assembly is Microsoft's term for the module that is created when a DLL or .EXE is compiled by a .NET compiler.

## **BFILES**

External binary files that exist outside the database tablespaces residing in the operating system. BFILES are referenced from the database semantics, and are also known as external LOBs.

## **Binary Large Object (BLOB)**

A large object data type whose content consists of binary data. Additionally, this data is considered raw as its structure is not recognized by the database.

## **Character Large Object (CLOB)**

The LOB data type whose value is composed of character data corresponding to the database character set. A CLOB may be indexed and searched by the Oracle Text search engine.

## **data provider**

As the term is used with Oracle Data Provider for .NET, a data provider is the connected component in the ADO.NET model and transfers data between a data source and the DataSet.

## **DataSet**

A DataSet is an in-memory copy of database data. The DataSet exists in memory without an active connection to the database.

## **dirty writes**

Dirty writes means writing uncommitted or dirty data.

## **DDL**

DDL refers to data definition language, which includes statements defining or changing data structure.

## **DOM**

Document Object Model (DOM) is an application program interface (API) for HTML and XML documents. It defines the logical structure of documents and the way that a document is accessed and manipulated.

### **Extensible Stylesheet Language Transformation (XSLT)**

The XSL W3C standard specification that defines a transformation language to convert one XML document into another.

### **flush**

Flush or flushing refers to recording changes (that is, sending modified data) to the database.

### **Global Assembly Cache (GAC)**

A cache for .NET assemblies.

### **goodness**

The degree of load in the Oracle database. The lighter load is better and vice versa.

### **implicit database connection**

The connection that is implicitly available from the context of the .NET stored procedure execution.

### **instantiate**

A term used in object-based languages such as C# to refer to the creation of an object of a specific class.

### **invalidation message**

The content of a change notification which indicates that the cache is now invalid

### **Large Object (LOB)**

The class of SQL data type that is further divided into internal LOBs and external LOBs. Internal LOBs include BLOBs, CLOBs, and NCLOBs while external LOBs include BFILES.

### **Microsoft .NET Framework Class Library**

The Microsoft .NET Framework Class Library provides the classes for the .NET framework model.

### **namespace**

- .NET:  
A namespace is naming device for grouping related types. More than one namespace can be contained in an assembly.
- XML Documents:  
A namespace describes a set of related element names or attributes within an XML document.

### **National Character Large Object (NCLOB)**

The LOB data type whose value is composed of character data corresponding to the database national character set.

### **Oracle Net Services**

The Oracle client/server communication software that offers transparent operation to Oracle tools or databases over any type of network protocol and operating system.



**OracleDataReader**

An `OracleDataReader` is a read-only, forward-only result set.

**Oracle XML DB**

Oracle XML DB is the name for a distinct group of technologies related to high-performance XML storage and retrieval that are available within the Oracle database. Oracle XML DB is not a separate server.

Oracle XML DB is based on the W3C XML data model.

**PL/SQL**

The Oracle procedural language extension to SQL.

**primary key**

The column or set of columns included in the definition of a table's PRIMARY KEY constraint.

**reference semantics**

Reference semantics indicates that assignment is to a reference (an address such as a pointer) rather than to a value. See [value semantics](#).

**REF**

A data type that encapsulates references to row objects of a specified object type.

**result set**

The output of a SQL query, consisting of one or more rows of data.

**Safe Type Mapping**

Safe Type Mapping allows the `OracleDataAdapter` to populate a `DataSet` with .NET type representations of Oracle data without any data or precision loss.

**savepoint**

A point in the workspace to which operations can be rolled back.

**stored procedure**

A stored procedure is a PL/SQL block that Oracle stores in the database and can be executed from an application.

**Transparent Application Failover (TAF)**

Transparent Application Failover is a runtime failover for high-availability environments. It enables client applications to automatically reconnect to the database if the connection fails. This reconnect happens automatically from within the Oracle Call Interface (OCI) library.

**Unicode**

Unicode is a universal encoded character set that enables information from any language to be stored using a single character set.

**URL**

URL (Universal Resource Locator).

**value semantics**

Value semantics indicates that assignment copies the value, not the reference or address (such as a pointer). See [reference semantics](#).

**XPath**

XML Path Language (XPath), based on a W3C recommendation, is a language for addressing parts of an XML document. It is designed to be used by both XSLT and XPointer. It can be used as a searching or query language as well as in hypertext linking.

---

---

# Index

## A

---

- abstract data types, 3-77
- ADO, 1-3
- ADO.NET, 1-3, 3-90
- ADO.NET 1.x, 2-1
- ADO.NET 2.0, 2-2, 3-18
  - base or DbCommon classes, 3-19
  - classes and class members, 3-27
  - DbCommon classes, 3-18
- ADO.NET 2.x, 2-1
- ADTs, 3-77
- Advanced Queuing support, xxii
- app.config
  - sample, 3-122
  - setting performance counters, 3-8
- app.config file, 3-20
- AppDomain, 3-8
- application config, 3-114
- AQ support, xxii
- array bind
  - OracleParameter, 3-40
- array bind operations, 3-39
  - ArrayBindCount, 5-13
  - ArrayBindIndex, 5-219
  - ArrayBindSize, 5-264
  - ArrayBindStatus, 5-265
  - error handling, 3-40
- array binding, 3-39
- ArrayBindCount property, 5-13
- ArrayBindIndex property, 5-219
- ArrayBindSize property, 3-36, 3-40, 5-264
- ArrayBindStatus property, 3-36, 3-40, 5-265
- ASP.NET, 1-2
- assembly, 1-3
  - ODP.NET, 1-3

## B

---

- batch processing, 3-27
  - support, 3-18
- BatchUpdate
  - Microsoft Hotfix, 3-27
- behavior of ExecuteScalar method for REF CURSOR, 3-59
- BFILE, 3-61

- BINARY\_DOUBLE, 3-31
- BINARY\_FLOAT, 3-31
- binding, 3-31
  - PL/SQL Associative Array, 3-36
- BLOB, 3-61
- bulk copy constraints, 3-28
- bulk copy feature, 3-28
  - restrictions, 3-28

## C

---

- C#, Visual Basic .NET, C++ .NET, 1-1
- caching ODP.NET parameter contexts, xxv
- callback support, 3-16
- case-sensitivity
  - column name mapping, 3-75
- change notification
  - ODP.NET support, 3-100
- change notification, Database Change Notification, 9-1
- characters with special meaning
  - in column data, 3-74
  - in table or view, 3-75
- characters with special meaning in XML, 3-68
- client applications, 1-1
- client globalization settings, 3-111, 3-113
- client identifier, 3-16
- CLOB, 3-61
- close calls, 2-5
- CLR, 1-2
- collection types, 3-78
- CollectionType property, 3-36
- column data
  - special characters in, 3-74
- CommandBehavior.SequentialAccess, 3-51
- commit transactions
  - changes to XML data, 3-77
- CommittableTransaction, 3-22
- config files
  - samples, 3-122
- configuration settings
  - UDTs, 3-91
- connect descriptor, 3-4
- connection dependency, 3-66
- connection optimization, 3-9
- connection pool

- performance counters, 3-7
- connection pooling, 3-5
  - example, 3-5
  - for Oracle RAC database, 3-9
  - management, 3-7
- Connection property, 3-62
- connection string builder, 3-18
- ConnectionString attributes, 3-5
  - Connection Lifetime, 3-2, 3-5, 3-6
  - Connection Timeout, 3-2, 3-5, 3-6
  - Data Source, 3-2
  - DBA Privilege, 3-2
  - Decr Pool Size, 3-2, 3-5, 3-6
  - Enlist, 3-2
  - HA Events, 3-2, 3-5
  - Incr Pool Size, 3-2, 3-5, 3-6
  - Load Balancing, 3-2, 3-5
  - Max Pool Size, 3-2, 3-5, 3-6
  - Metadata Pooling, 3-2
  - Min Pool Size, 3-2, 3-5, 3-6
  - Password, 3-2
  - Persist Security Info, 3-2
  - Pooling, 3-2, 3-5, 3-6
  - Proxy Password, 3-2, 3-14
  - Proxy User Id, 3-2, 3-14
  - Statement Cache Purge, 3-2
  - Statement Cache Size, 3-2
  - User Id, 3-2
  - Validate Connection, 3-2, 3-5, 3-6
- ConnectionString property, 3-5, 3-6, 5-78
- Constraints property, 3-108
  - configuring, 3-109
- context connection, 4-2
- Continuous Query Notification, 3-97
- controlling query reexecution, 3-108
- custom classes, 3-78
- custom type factories, 3-78
- custom type factory, 3-81
- custom type implementations
  - optional, 3-80
- custom type mapping, 3-81
- custom type mappings
  - specifying, 3-81
  - specifying with custom type factories, 3-81
  - specifying with XML, 3-81
  - using, 3-83
- custom types
  - converting to Oracle UDTS, 3-83
  - requirements, 3-79
- custom UDT classes, 3-78

## D

---

- data loss, 3-104
- data manipulation
  - using XML, 3-73
- data source attribute, 3-4
- data source enumerator, 3-18
- data source enumerators, 3-20
- database

- changes to, 3-73
- Database Change Notification
  - best practices, 3-104
  - performance considerations, 3-104
- database change notification, 2-5, 3-97, 3-99
  - ODP.NET support, 3-100
- database notification
  - port to listen, 2-5
- database shutdown, xxiii
- database startup, xxiii
- DataSet, 3-63
  - populating, 3-59
  - populating from a REF CURSOR, 3-59
  - populating with generic and custom objects, 3-90
  - updating, 3-59
  - updating to database, 3-108
- DataSet Fill, xxii
- DataTable, 3-109
- Datatable properties, 3-108
- DbCommon classes, 3-18
- DBlinks, 4-2
- DbProviderFactories class, 2-2, 3-19
- DbType
  - inference, 3-33
- debug tracing, 3-114
- default mapping
  - improving, 3-77
- dependent unmanaged DLL mismatch, 2-4
- direct path load, 3-28
- dispose calls, 2-5
- distributed transactions, 3-22
- documentation
  - .NET, 1-1
- Dynamic Enlistment, 3-15
- dynamic help, 1-1, 2-2

## E

---

- Easy Connect naming method, 3-4
- end-to-end tracing, xxiv, 3-16
- EnlistDistributedTransaction method, 3-15
- enumeration type
  - OracleDbType, 3-32
- error handling, 3-40
- example
  - connection pooling, 3-5
- examples
  - documentation
    - readme file, 2-2
- ExecuteNonQuery method, 3-59
- ExecuteScalar method, 3-59
- explicit user connections, 4-1
- EZCONNECT, 3-4

## F

---

- failover, 3-16
  - registering an event handler, 3-16
- FailoverEvent Enumeration
  - description, 11-10

- FailoverReturnCode Enumeration
  - description, 11-11
- FailoverType Enumeration
  - description, 11-12
- FAN, 3-9
- Fast Application Notification (FAN), 3-9
- features, 3-1
  - new, xxi
- FetchSize property
  - fine-tuning, 3-56
  - setting at design time, 3-57
  - setting at run time, 3-57
  - using, 3-56
- file locations, 2-2

## G

---

- garbage collection, 2-5
- geographic data, 3-77
- Global Assembly Cache (GAC), 2-2
- globalization settings, 3-110
  - client, 3-111
  - session, 3-111
  - thread-based, 3-112
- globalization support, 3-110
- globalization-sensitive operations, 3-113
- Grid environment, 3-9
- grid-computing, xxviii, xxix
- grids, xxviii, xxix
- GUI access to ODP.NET, 1-1

## H

---

- HA Events, 3-2, 3-9, 3-10
- HA events, 2-5
- handling date and time format
  - manipulating data in XML, 3-73
  - retrieving queries in XML, 3-68

## I

---

- implicit database connection, 4-1, 4-2, 4-3, 5-84
- improving default mapping, 3-77
- inference from Value property, 3-34
- inference of DbType and OracleDbType from Value, 3-34
- inference of DbType from OracleDbType, 3-33
- inference of OracleDbType from DbType, 3-34
- inference of types, 3-33
- InitialLOBFetchSize property, 3-52
- InitialLONGFetchSize property, 3-51
- input binding
  - XMLType column, 3-67
- installation, 2-2
  - Oracle Data Provider for .NET, 2-2
  - XCopy class, 2-2
- integrated help, 2-2
- interference in OracleParameter class, 3-33
- introduction, overview, 1-3
- INullable Interface
  - interface description, 14-409

- interface members, 14-410
- interface properties, 14-411
- invalidation message, 3-99
  - ensuring persistency of, 3-100
- InvalidCastException, 3-48
- IOracleArrayTypeFactory Interface
  - interface description, 16-33
  - interface members, 16-34
  - interface methods, 16-35
- IOracleCustomType Interface
  - interface description, 16-26
  - interface members, 16-27
  - interface methods, 16-28
- IOracleCustomTypeFactory Interface
  - interface description, 16-30
  - interface members, 16-31
  - interface methods, 16-32

## L

---

- large binary datatypes, 3-61
- large character datatypes, 3-61
- limitations and restrictions, 4-2
- Load Balancing, 3-2, 3-9
- load balancing, 2-5
- LOB Connection property, 3-62
- LOB retrieval, xxv
- LOBs
  - temporary, 3-64
  - updating, 3-63
- LOBs updating, 3-63
- local transactions, 3-22
- location data, 3-77
- LONG and LONG RAW datatypes, 3-62

## M

---

- machine.config, 3-114
- machine.config file, 2-2
- metadata, 3-110
- method invocation
  - UDT, 3-91
- Microsoft ADO.NET 2.0, 3-18
- Microsoft Common Language Runtime (CLR), 1-2
- Microsoft Hotfix
  - BatchUpdate, 3-27
- Microsoft .NET Framework, 2-1
- Microsoft .NET Framework Class Library, 1-3
- Microsoft Transaction Server, 2-2
- MTS, 2-2
- multiple notification requests, 3-100
- Multiple Oracle Homes, xxix
- multiple tables
  - changes to, 3-77

## N

---

- namespace
  - Oracle.DataAccess.Types, 1-9
- native XML support, 3-64
- NCLOB, 3-61

- nested table types, 3-78
- .NET custom types, 3-77
- .NET Framework datatype, 3-46
- .NET languages, 1-1
- .NET products and documentation, 1-1
- .NET stored procedures and functions, 4-1
- .NET Stream class, 3-62
- .NET type accessors, 3-48
- .NET Types
  - inference, 3-33
- notification framework, 3-99
- notification information
  - retrieving, 3-100
- notification process
  - flow, 3-101
- notification registration, 3-100
  - requirements of, 3-101
- NULL values
  - retrieving from column, 3-73
- number of rows fetched in round-trip
  - controlling, 3-56

**O**

---

- object data type support, 3-77
- object types, 3-78
- object-relational data, 3-72
  - saving changes from XML data, 3-77
- obtaining a REF CURSOR, 3-58, 3-59
- obtaining an OracleRefCursor, 3-58
- obtaining data from an OracleDataReader, 3-47
- obtaining LOB data
  - InitialLOBFetchSize property, 3-52
- obtaining LONG and LONG RAW Data, 3-51
- OCI
  - statement caching, 3-42
- ODP.NET
  - installing, 2-2
- ODP.NET Configuration, 3-114
- ODP.NET LOB classes, 3-61
- ODP.NET Type accessors, 3-50
- ODP.NET Type classes, 3-46
- ODP.NET Type exceptions, 15-1
- ODP.NET Type structures, 3-46, 14-1
- ODP.NET Types, 3-46
  - overview, 3-46
- ODP.NET within a .NET stored procedure
  - limitations and restrictions, 4-2
  - transaction support, 4-3
  - unsupported SQL commands, 4-6
- ODP.NET XML Support, 3-64
- OnChangedEventArgs Class
  - instance properties, 9-34
  - members, 9-31
  - static fields, 9-32
  - static methods, 9-33
- OnChangeEventHandler Delegate
  - description, 9-40
- operating system authentication, 3-11
- Oracle Call Interface
  - statement caching, 3-42
- Oracle Data Guard
  - connecting, 3-9
- Oracle Data Provider for .NET
  - installing, 2-2
  - system requirements, 2-1
- Oracle Data Provider for .NET assembly, 1-3
- Oracle Database Extensions for .NET, 1-2, 4-1
- Oracle Developer Tools for Visual Studio, 1-1
- Oracle Label Security, 3-16
- Oracle native types, 3-46
  - supported by ODP.NET, 3-48
- Oracle Providers for ASP.NET, 1-2
- Oracle RAC
  - connecting, 3-9
- Oracle RAC database
  - pool size attributes, 3-11
- Oracle RAC environment, 3-9
- Oracle Services for Microsoft Transaction Server, 2-2
- Oracle UDT attribute mappings, 3-84
- Oracle Universal Installer (OUI), 2-2
- Oracle user-defined types, 3-77
- Oracle User-Defined Types (UDTs), 3-78
- Oracle Virtual Private Database (VPD), 3-16
- Oracle XML DB, 3-65
- Oracle8i Database, ADO.NET 2.0
  - interfaces, 3-18
- OracleAQAgent
  - constructors, 12-4
- OracleAQAgent Class
  - constructors, 12-4
  - description, 12-2
  - members, 12-3, 12-39
  - properties, 12-6, 12-12
- OracleAQDequeueMode Enumeration
  - description, 12-84
- OracleAQDequeueOptions Class
  - constructor, 12-11
  - description, 12-8
  - members, 12-9
  - properties, 12-12
  - public methods, 12-18
- OracleAQEnqueueOptions Class
  - constructor, 12-21
  - description, 12-19
  - members, 12-20
  - properties, 12-22
  - public methods, 12-24
- OracleAQMessage Class
  - constructors, 12-28
  - description, 12-25
  - members, 12-26
  - properties, 12-30
- OracleAQMessageAvailableEventArgs Class
  - description, 12-38
  - members, 12-39
  - properties, 12-40
- OracleAQMessageAvailableEventHandler Delegate
  - description, 12-47
- OracleAQMessageDeliveryMode Enumeration

- description, 12-85
- OracleAQMessageState Enumeration
  - description, 12-87
- OracleAQMessageType Enumeration
  - description, 12-88
- OracleAQNavigationMode Enumeration
  - description, 12-89
- OracleAQNotificationGroupingType Enumeration
  - description, 12-90
- OracleAQNotificationType Enumeration
  - description, 12-91
- OracleAQQueue Class
  - constructors, 12-51
  - description, 12-48
  - events, 12-79
  - members, 12-49
  - properties, 12-58
  - public methods, 12-64
  - static methods, 12-51
- OracleAQVisibilityMode Enumeration
  - description, 12-92
- OracleArrayMappingAttribute Class
  - constructors, 16-22
  - description, 16-19
  - members, 16-20
  - methods, 16-25
  - properties, 16-24
  - static methods, 16-23
- OracleBFile Class
  - class description, 13-2
  - constructors, 13-7
  - instance methods, 13-19
  - instance properties, 13-12
  - members, 13-4
  - static fields, 13-9
  - static methods, 13-11
- OracleBinary Structure
  - constructor, 14-7
  - description, 14-2
  - instance methods, 14-26
  - members, 14-4
  - properties, 14-23
  - static fields, 14-8
  - static methods, 14-9
  - static operators, 14-15
  - static type conversion operators, 14-21
- OracleBlob Class
  - class description, 13-38
  - constructors, 13-43
  - instance methods, 13-53
  - instance properties, 13-47
  - members, 13-40
  - static fields, 13-45
  - static methods, 13-46
- OracleBulkCopy Class
  - class description, 17-2
  - constructors, 17-5
  - events, 17-20
  - members, 17-3
  - properties, 17-9
  - public methods, 17-14
- OracleBulkCopyColumnMapping Class
  - class description, 17-21
  - constructors, 17-23
  - members, 17-22
  - properties, 17-26
- OracleBulkCopyColumnMappingCollection Class
  - class description, 17-29
  - members, 17-31
  - properties, 17-32
  - public methods, 17-33
- OracleBulkCopyOptions Enumeration
  - description, 17-42
- OracleClientFactory, 2-2
- OracleClientFactory Class
  - class description, 7-2
  - class members, 7-4
  - public methods, 7-6
  - public properties, 7-5
- OracleClientFactory class
  - instantiating, 3-19
- OracleClob Class
  - class description, 13-73
  - constructors, 13-78
  - instance methods, 13-88
  - instance properties, 13-82
  - members, 13-75
  - static fields, 13-80
  - static methods, 13-81
- OracleCollectionType Enumeration, 5-355
- OracleCommand
  - ArrayBindCount property, 3-39
  - constructors, 5-7
  - InitialLOBFetchSize property, 3-52
  - InitialLONGFetchSize property, 3-51
  - Transaction property, 3-30
- OracleCommand Class
  - ArrayBindCount, 5-13
  - class description, 5-2
  - ExecuteScalar method, 3-59
  - FetchSize property, 3-56
  - members, 5-4
  - properties, 5-10
  - public methods, 5-27, 12-18
  - RowSize property, 3-57
  - static methods, 5-9
- OracleCommand object, 3-30
- OracleCommand properties
  - ArrayBindCount, 3-39
- OracleCommand Transaction object, 3-30
- OracleCommandBuilder Class, 3-110
  - class description, 5-41
  - constructors, 5-47
  - events, 5-63
  - members, 5-44
  - properties, 5-53
  - public methods, 5-58
  - static methods, 5-49
  - updating dataset, 3-108
- OracleConnection

- ClearAllPools property, 3-7
- ClearPool property, 3-7
- ClientId property, 3-16
- events, 5-111
- OracleConnection Class
  - class description, 5-64
  - constructors, 5-69
  - members, 5-66
  - obtaining a reference, 3-66
  - properties, 5-76
  - public methods, 5-89
  - static methods, 5-73
- OracleConnection class
  - GetSchema methods, 3-21
- OracleConnectionStringBuilder Class
  - class description, 7-10
  - class members, 7-13
  - constructors, 7-16
  - public methods, 7-33
  - public properties, 7-18
- OracleConnectionStringBuilder class
  - using, 3-20
- OracleCustomTypeMappingAttribute Class
  - constructors, 16-6
  - description, 16-2
  - members, 16-4
  - methods, 16-9
  - properties, 16-8
  - static methods, 16-7
- Oracle.DataAccess.Client namespace, 1-3
- Oracle.DataAccess.dll, 1-3
- Oracle.DataAccess.Types namespace, 1-3, 1-9
- OracleDataAdapter, 3-104
  - constructors, 5-120
  - members, 5-117
  - SafeMapping Property, 3-106
  - SelectCommand property, 3-59
- OracleDataAdapter Class, 5-115
  - events, 5-135
  - FillSchema method, 3-110
  - properties, 5-124
  - public methods, 5-130
  - SelectCommand property, 3-110
  - static methods, 5-123
- OracleDataAdapter class
  - FillSchema method, 3-109
  - Requery property, 3-108
  - SelectCommand property, 3-109
- OracleDataAdapter Safe Type Mapping, 3-104
- OracleDatabase Class
  - class description, 5-139
  - constructor, 5-142
  - members, 5-141
  - properties, 5-143
  - public methods, 5-144
  - Shutdown method, 5-144
  - Startup method, 5-148
- OracleDataReader, 3-47, 3-51
  - members, 5-154
  - retrieving UDTs from, 3-86
  - typed accessors, 3-48
- OracleDataReader Class
  - class description, 5-151
  - FetchSize property, 3-56
  - populating, 3-58
  - properties, 5-159
  - public methods, 5-170
  - static methods, 5-158
- OracleDataReader Class SchemaTable, 5-205
- OracleDataSource Enumerator class
  - using, 3-20
- OracleDataSourceEnumerator Class
  - class description, 7-36
  - class members, 7-38
  - public methods, 7-39
- OracleDate Structure
  - constructors, 14-34
  - description, 14-29
  - members, 14-31
  - methods, 14-60
  - properties, 14-56
  - static fields, 14-39
  - static methods, 14-41
  - static operators, 14-47
  - static type conversions, 14-52
- OracleDBShutdownMode Enumeration
  - description, 5-356
- OracleDBStartupMode Enumeration
  - description, 5-357
- OracleDbType
  - inference, 3-33
- OracleDbType enumeration, 3-33
- OracleDbType enumeration type, 3-32, 5-358
- OracleDecimal Structure
  - constructors, 14-72
  - description, 14-65
  - instance methods, 14-133
  - members, 14-67
  - properties, 14-129
  - static comparison methods, 14-82
  - static comparison operators, 14-112
  - static logarithmic methods, 14-101
  - static manipulation methods, 14-87
  - static operators, .NET Type to
    - OracleDecimal, 14-120
  - static operators, OracleDecimal to .NET, 14-124
  - static trigonometric methods, 14-106
- OracleDependency Class
  - change notification, 3-99
  - class description, 9-2
  - constructors, 9-5
  - database change notification, 3-97
  - events, 9-21
  - instance methods, 9-18
  - instance properties, 9-12
  - members, 9-3
  - static fields, 9-9
  - static methods, 9-11
- OracleError Class
  - ArrayBindIndex, 5-219



- class description, 5-215
- members, 5-217
- methods, 5-222
- properties, 5-219
- static methods, 5-218
- OracleErrorCollection
  - members, 5-225
  - properties, 5-227
  - public methods, 5-228
  - static methods, 5-226
- OracleErrorCollection Class, 5-223
- OracleException
  - members, 5-231
  - methods, 5-237
  - properties, 5-234
  - static methods, 5-233
- OracleException Class, 5-229
- OracleFailoverEventArgs
  - members, 11-5
  - properties, 11-7
  - public methods, 11-8
- OracleFailoverEventHandler Delegate
  - description, 11-9
- OracleGlobalization Class
  - class description, 10-2
  - members, 10-4
  - properties, 10-12
  - public methods, 10-22
- OracleHAEventArgs Class
  - description, 8-2
  - members, 8-3
  - properties, 8-4
- OracleHAEventHandler Delegate
  - description, 8-8
- OracleHAEventSource Enumeration
  - description, 8-9
- OracleHAEventStatus Enumeration
  - description, 8-10
- OracleInfoMessageEventArgs
  - members, 5-241
  - properties, 5-243
  - public methods, 5-245
  - static methods, 5-242
- OracleInfoMessageEventHandler Delegate, 5-246
- OracleIntervalDS Structure
  - constructors, 14-144
  - description, 14-139
  - members, 14-141
  - methods, 14-174
  - properties, 14-169
  - static methods, 14-151
  - static operators, 14-158
  - type conversions, 14-166
- OracleIntervalYM Structure
  - constructors, 14-182
  - description, 14-177
  - members, 14-179
  - methods, 14-188, 14-207
  - properties, 14-204
  - static fields, 14-186
  - static operators, 14-194
  - type conversions, 14-201
- OracleNotificationEventArgs Class
  - change notification, 3-99
  - class description, 9-30
  - instance methods, 9-39
- OracleNotificationInfo Enumeration
  - description, 9-44
- OracleNotificationRequest Class
  - change notification, 3-99
  - class description, 9-22
  - database change notification, 3-97
  - instance methods, 9-29
  - instance properties, 9-25
  - members, 9-23
  - static methods, 9-24
- OracleNotificationSource Enumeration
  - description, 9-43
- OracleNotificationType Enumeration
  - description, 9-42
- OracleNullValueException Class
  - class description, 15-11
  - constructors, 15-14
  - members, 15-12
  - methods, 15-16, 15-18
  - properties, 15-17
- OracleObjectMappingAttribute Class
  - constructors, 16-13
  - description, 16-10
  - members, 16-11
  - methods, 16-18
  - properties, 16-16
  - static methods, 16-15
- OracleParameter
  - array bind properties, 3-40
  - ArrayBindSize property, 3-40, 5-264
  - ArrayBindStatus property, 3-40, 5-265
  - constructors, 5-251
  - inferences of types, 3-33
  - members, 5-249
  - properties, 5-262
  - public methods, 5-279
  - static methods, 5-262
- OracleParameter array bind feature, 3-39
- OracleParameter Class, 5-247
  - Value, 3-34
- OracleParameter object, 3-31
  - OracleDbType enumerated values, 3-32
- OracleParameter property
  - ArrayBindSize, 3-36
  - ArrayBindStatus, 3-36
  - CollectionType, 3-36
  - Size, 3-36
  - Value, 3-36
- OracleParameterCollection
  - members, 5-284
  - public methods, 5-290
  - static methods, 5-286
- OracleParameterCollection Class, 5-282
- OracleParameterStatus enumeration type, 3-42,

- 5-360
- OraclePermission Class
  - constructor, 5-311
  - members, 5-309
  - public methods, 5-314
  - public properties, 5-313
  - static methods, 5-312
- Oraclepermission Class
  - description, 5-308
- OraclePermissionAttribute Class
  - constructor, 5-320
  - description, 5-317
  - members, 5-318
  - public methods, 5-323
  - public properties, 5-322
  - static methods, 5-321
- OracleRef Class
  - class description, 16-51
  - class members, 16-52
  - constructors, 16-54
  - instance methods, 16-62
  - instance properties, 16-58
  - static fields, 16-56
  - static methods, 16-57
- OracleRefCursor, 3-58
- OracleRefCursor Class
  - class description, 13-113
  - instance methods, 13-121
  - members, 13-116
  - populating from a REF CURSOR, 3-59
  - properties, 13-118
  - static methods, 13-117
- OracleRowsCopiedEventArgs Class
  - class description, 17-44
  - constructors, 17-46
  - members, 17-45
  - properties, 17-47
- OracleRowsCopiedEventHandler Delegate
  - description, 17-43
- OracleRowUpdatedEventArgs
  - constructor, 5-327
  - members, 5-325
  - properties, 5-329
  - public methods, 5-330
  - static methods, 5-328
- OracleRowUpdatedEventArgs Class, 5-324
- OracleRowUpdatedEventHandler Delegate, 5-331
- OracleRowUpdatingEventArgs
  - constructor, 5-335
  - members, 5-333
  - properties, 5-337
  - public methods, 5-338
  - static methods, 5-336
- OracleRowUpdatingEventArgs Class, 5-332
- OracleRowUpdatingEventHandler Delegate, 5-339
- OracleString Structure
  - constructors, 14-215
  - description, 14-210
  - members, 14-212
  - methods, 14-236
  - properties, 14-233
  - static fields, 14-220
  - static methods, 14-221
  - static operators, 14-226
  - type conversions, 14-231
- OracleTimeStamp Structure
  - constructors, 14-247
  - description, 14-241
  - members, 14-243
  - methods, 14-283
  - properties, 14-278
  - static methods, 14-256
  - static operators, 14-263
  - static type conversions, 14-272
- OracleTimeStampLTZ Structure
  - constructors, 14-300
  - description, 14-294
  - members, 14-296
  - methods, 14-337
  - properties, 14-332
  - static fields, 14-307
  - static methods, 14-309
  - static operators, 14-317
  - static type conversions, 14-326
- OracleTimeStampTZ Structure
  - constructors, 14-355
  - description, 14-349
  - members, 14-351
  - methods, 14-397
  - properties, 14-391
  - static fields, 14-367
  - static methods, 14-369
  - static operators, 14-376
  - static type conversions, 14-385
- OracleTransaction
  - members, 5-343
  - properties, 5-345
  - public methods, 5-347
  - static methods, 5-344
- OracleTransaction Class
  - class description, 5-340
- OracleTruncateException Class
  - class description, 15-19
  - constructors, 15-22
  - members, 15-20
  - methods, 15-26
  - properties, 15-25
  - static methods, 15-24
- OracleTypeException Class
  - class description, 15-2
  - constructors, 15-5
  - members, 15-3
  - properties, 15-8
  - static methods, 15-7
- OracleUdt Class
  - description, 16-37
  - members, 16-38
  - static methods, 16-39
- OracleUdtFetchOption Enumeration
  - description, 16-73

- OracleUdtStatus Enumeration
  - description, 16-74
- OracleXmlCommandType Enumeration, 6-2
- OracleXmlQueryProperties Class
  - class description, 6-3
  - constructors, 6-8
  - members, 6-7
  - properties, 6-9
  - public methods, 6-12
- OracleXmlSaveProperties Class, 6-13
  - constructors, 6-17
  - members, 6-16
  - properties, 6-18
  - public methods, 6-22
- OracleXmlStream Class
  - class description, 6-23
  - constructors, 6-26
  - instance methods, 6-32
  - instance properties, 6-28
  - members, 6-24
  - static methods, 6-27
- OracleXmlType Class, 3-66
  - class description, 6-37
  - constructors, 6-40
  - instance methods, 6-49
  - instance properties, 6-44
  - members, 6-38
  - static methods, 6-43

## P

---

- parameter binding, 3-31
- parameter binding with OracleParameter, 3-88
- parameter context caching, xxv
- password expiration, 3-12
- passwords in code examples, xix
- performance, 3-42
  - array binding, 3-39
  - connection pooling, 3-5
  - fine-tuning FetchSize, 3-56
  - number of rows fetched, 3-56
  - Obtaining LOB Data, 3-52
- performance counters, 2-4
  - connection pool, 3-7
  - instance names of, 3-8
  - publishing, 3-7
  - using app.config entry, 3-8
- PL/SQL Associative Array binding, 3-36
- PL/SQL Index-By Tables, 3-36
- PL/SQL language, 3-58
- PL/SQL REF CURSOR, 3-58
- PL/SQL REF CURSOR and OracleRefCursor, 3-58
- PLSQLAssociativeArray, 5-355
- populating an OracleDataReader from a REF CURSOR, 3-58
- populating an OracleRefCursor from a REF CURSOR, 3-59
- populating the DataSet from a REF CURSOR, 3-59
- populating the DataSet with generic and custom objects, 3-90

- port
  - listen for database notifications, 2-5
- port number
  - defining listener, 3-100
- porting
  - client application to .NET stored procedure, 4-6
- preventing data loss, 3-104, 3-106
- PrimaryKey property, 3-108
  - configuring, 3-109
- privileged connections, 3-12
- promotable transactions, xxii, 3-22
- properties
  - ClientId property, 3-16
- provider factory classes, 3-18, 3-19
- provider independence, 3-18
- proxy authentication, 3-14

## Q

---

- query result set
  - retrieving as XML, 3-68

## R

---

- RAC database
  - pool size attributes, 3-11
- RAC environment, 3-9
- REF CURSOR
  - behavior of ExecuteScalar method, 3-59
  - obtaining, 3-58, 3-59
  - passing to stored procedure, 3-60
  - populating DataSet from, 3-59
  - populating from OracleDataReader, 3-58
- registry entries, 3-114
- release Oracle8i (8.1.7), 3-73
- release Oracle9i(9.0.x), 3-73
- Requery property, 3-108
- round-trip, 3-39
- RowSize property, 3-57
- Runtime Connection Load Balancing, 3-9

## S

---

- Safe Type Mapping, 3-104
- SafeMapping Property, 3-106
- Samples, 1-12
- samples, 2-2
  - UDT, 16-1
- saving change using an XML document, 3-75
- saving changes
  - using XML data, 3-73
- schema metadata
  - customizing metadata, 3-21
- SchemaTable, 5-205
- search order
  - unmanaged DLLs, 2-4
- SecureFiles, xxv, 3-61
- security enhancements, xxiii
- SelectCommand property, 3-59
- Self-Tuning, xxii
- session globalization parameters, 3-114

- session globalization settings, 3-111
- schema discovery
  - support, 3-18
- Shutdown method, 5-144
- shutdown, database, xxiii
- simple application, 1-11
- Size property, 3-36
- SQL commands
  - unsupported, 4-6
- Startup method, 5-148
- startup, database, xxiii
- Statement Caching
  - connection string attributes, 3-42
  - methods and properties, 3-43
  - Statement Cache Purge, 3-42
  - Statement Cache Size, 3-42
- StatementCacheWithUdts, 3-91
- stored procedures and functions, 3-60, 4-1
- Stream class, 3-62
- support comparison
  - client application versus .NET stored procedure, 4-6
- SYSDBA privileges, 3-12
- SYSOPER privileges, 3-12
- system requirements
  - Oracle Data Provider for .NET, 2-1
- System.Data.Common, 3-18
- System.Transactions support, 3-22

## T

---

- table or view
  - special characters in, 3-75
- TAF, 3-16
- TAF callback support, 3-16
- Temporary LOBs, 3-64
- thread globalization settings, 3-113
- Thread.Abort method, 2-5
- thread-based globalization settings, 3-112
- tips for ODP.NET, 2-5
- TNS alias, 3-4
- tracing
  - end-to-end, xxiv
- tracing attributes, 3-16
- Transaction object, 3-30
- Transaction property, 3-30
- transaction support, 4-3
- transactions
  - commit, 3-77
- TransactionScope, 3-22
- Transparent Application Failover (TAF), 3-16
- troubleshooting, 3-114
- typed OracleDataReader accessors, 3-48

## U

---

- UDT
  - method invocation, 3-91
- UDT metadata retrieval from
  - OracleDataReader, 3-87

- UdtCacheSize, 3-91
- UDTs, 3-77
  - collection types, 3-78
  - configuration settings, 3-91
  - object types, 3-78
  - parameter binding with OracleParameter, 3-88
  - retrieving from OracleDataReader, 3-86
  - samples, 16-1
- UDTs (Oracle User-Defined Types), 3-78
- UdtTypeName property, 3-88
- unique columns, 3-51, 3-52
- unique constraint, 3-51, 3-52
- unique index, 3-51, 3-52
- UniqueConstraint, 3-109
- uniqueness
  - in updating DataSet to database, 3-108
- uniqueness in DataRows, 3-109
- unmanaged DLLs
  - mismatch, 2-4
  - search order, 2-4
- unmanged DLLs
  - config support, 2-4
- unsupported SQL commands, 4-6
- updating
  - LOBs, 3-63
  - updating a DataSet obtained from a REF CURSOR, 3-59
  - updating LOBs using a DataSet, 3-63
  - updating LOBs using ODP.NET LOB objects, 3-63
  - updating LOBs using OracleCommand and OracleParameter, 3-63
  - updating without PrimaryKey and Constraints, 3-110
- user-defined types, 3-77
- using FetchSize property, 3-56

## V

---

- Value property, 3-36
- VARRAY types, 3-78
- Virtual Private Database(VPD), 3-16
- Visual Studio
  - documentation, 2-2

## W

---

- web.config, 3-114
- Windows registry, 2-3

## X

---

- XML
  - characters with special meaning, 3-68
  - data manipulation using, 3-73
- XML data
  - saving changes using, 3-73
  - updating in OracleXmlType, 3-68
- XML Database, 3-64
- XML DB, 3-64, 3-65
- XML element name
  - case-sensitivity in, 3-75

- XML Element Name to Column Name
  - Mapping, 3-75
- XML related classes, 6-1
- XML related enumerations, 6-1
- XML Support, 3-64
- XML to specify custom type mappings, 3-82
- XMLQuery, 3-65
- XMLTable, 3-65
- XMLType column
  - as a .NET String, 3-66
  - fetching into the DataSet, 3-66
  - updating with OracleCommand, 3-67
- XMLType columns
  - setting to NULL, 3-67
- XQUERY, 3-65
- XQuery
  - support, 3-65
- XQuery language, 3-65

